



API Reference

# Amazon Elastic Container Registry Public



**API Version 2020-10-30**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# Amazon Elastic Container Registry Public: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
BatchCheckLayerAvailability .....	3
Request Syntax .....	3
Request Parameters .....	3
Response Syntax .....	4
Response Elements .....	5
Errors .....	5
See Also .....	6
BatchDeleteImage .....	7
Request Syntax .....	7
Request Parameters .....	7
Response Syntax .....	8
Response Elements .....	9
Errors .....	9
See Also .....	10
CompleteLayerUpload .....	11
Request Syntax .....	11
Request Parameters .....	11
Response Syntax .....	12
Response Elements .....	13
Errors .....	13
See Also .....	15
CreateRepository .....	16
Request Syntax .....	16
Request Parameters .....	16
Response Syntax .....	17
Response Elements .....	18
Errors .....	18
See Also .....	19
DeleteRepository .....	21
Request Syntax .....	21
Request Parameters .....	21
Response Syntax .....	22

---

Response Elements .....	22
Errors .....	22
See Also .....	23
DeleteRepositoryPolicy .....	25
Request Syntax .....	25
Request Parameters .....	25
Response Syntax .....	25
Response Elements .....	26
Errors .....	26
See Also .....	27
DescribeImages .....	29
Request Syntax .....	29
Request Parameters .....	29
Response Syntax .....	31
Response Elements .....	31
Errors .....	32
See Also .....	32
DescribeImageTags .....	34
Request Syntax .....	34
Request Parameters .....	34
Response Syntax .....	35
Response Elements .....	36
Errors .....	36
See Also .....	37
DescribeRegistries .....	38
Request Syntax .....	38
Request Parameters .....	38
Response Syntax .....	39
Response Elements .....	39
Errors .....	40
See Also .....	40
DescribeRepositories .....	42
Request Syntax .....	42
Request Parameters .....	42
Response Syntax .....	43
Response Elements .....	44

---

Errors .....	44
See Also .....	45
GetAuthorizationToken .....	46
Response Syntax .....	46
Response Elements .....	46
Errors .....	46
See Also .....	47
GetRegistryCatalogData .....	48
Response Syntax .....	48
Response Elements .....	48
Errors .....	48
See Also .....	49
GetRepositoryCatalogData .....	50
Request Syntax .....	50
Request Parameters .....	50
Response Syntax .....	51
Response Elements .....	51
Errors .....	51
See Also .....	52
GetRepositoryPolicy .....	53
Request Syntax .....	53
Request Parameters .....	53
Response Syntax .....	53
Response Elements .....	54
Errors .....	54
See Also .....	55
InitiateLayerUpload .....	57
Request Syntax .....	57
Request Parameters .....	57
Response Syntax .....	58
Response Elements .....	58
Errors .....	58
See Also .....	59
ListTagsForResource .....	61
Request Syntax .....	61
Request Parameters .....	61

---

Response Syntax .....	61
Response Elements .....	61
Errors .....	62
See Also .....	62
PutImage .....	64
Request Syntax .....	64
Request Parameters .....	64
Response Syntax .....	66
Response Elements .....	66
Errors .....	66
See Also .....	68
PutRegistryCatalogData .....	69
Request Syntax .....	69
Request Parameters .....	69
Response Syntax .....	69
Response Elements .....	70
Errors .....	70
See Also .....	70
PutRepositoryCatalogData .....	72
Request Syntax .....	72
Request Parameters .....	72
Response Syntax .....	73
Response Elements .....	73
Errors .....	73
See Also .....	74
SetRepositoryPolicy .....	76
Request Syntax .....	76
Request Parameters .....	76
Response Syntax .....	77
Response Elements .....	77
Errors .....	78
See Also .....	79
TagResource .....	80
Request Syntax .....	80
Request Parameters .....	80
Response Elements .....	81

---

Errors .....	81
See Also .....	82
UntagResource .....	83
Request Syntax .....	83
Request Parameters .....	83
Response Elements .....	83
Errors .....	84
See Also .....	85
UploadLayerPart .....	86
Request Syntax .....	86
Request Parameters .....	86
Response Syntax .....	88
Response Elements .....	88
Errors .....	89
See Also .....	90
<b>Data Types .....</b>	<b>92</b>
AuthorizationData .....	93
Contents .....	93
See Also .....	93
Image .....	94
Contents .....	94
See Also .....	95
ImageDetail .....	96
Contents .....	96
See Also .....	98
ImageFailure .....	99
Contents .....	99
See Also .....	99
ImageIdentifier .....	101
Contents .....	101
See Also .....	101
ImageTagDetail .....	102
Contents .....	102
See Also .....	102
Layer .....	103
Contents .....	103

---

See Also .....	104
LayerFailure .....	105
Contents .....	105
See Also .....	105
ReferencedImageDetail .....	107
Contents .....	107
See Also .....	108
Registry .....	109
Contents .....	109
See Also .....	110
RegistryAlias .....	111
Contents .....	111
See Also .....	112
RegistryCatalogData .....	113
Contents .....	113
See Also .....	113
Repository .....	114
Contents .....	114
See Also .....	115
RepositoryCatalogData .....	116
Contents .....	116
See Also .....	118
RepositoryCatalogDataInput .....	119
Contents .....	119
See Also .....	121
Tag .....	122
Contents .....	122
See Also .....	122
<b>Common Parameters .....</b>	<b>123</b>
<b>Common Error Types .....</b>	<b>126</b>

# Welcome

Amazon Elastic Container Registry Public (Amazon ECR Public) is a managed container image registry service. Amazon ECR provides both public and private registries to host your container images. You can use the Docker CLI or your preferred client to push, pull, and manage images. Amazon ECR provides a secure, scalable, and reliable registry for your Docker or Open Container Initiative (OCI) images. Amazon ECR supports public repositories with this API. For information about the Amazon ECR API for private repositories, see [Amazon Elastic Container Registry API Reference](#).

This document was last published on April 18, 2026.

# Actions

The following actions are supported:

- [BatchCheckLayerAvailability](#)
- [BatchDeleteImage](#)
- [CompleteLayerUpload](#)
- [CreateRepository](#)
- [DeleteRepository](#)
- [DeleteRepositoryPolicy](#)
- [DescribeImages](#)
- [DescribeImageTags](#)
- [DescribeRegistries](#)
- [DescribeRepositories](#)
- [GetAuthorizationToken](#)
- [GetRegistryCatalogData](#)
- [GetRepositoryCatalogData](#)
- [GetRepositoryPolicy](#)
- [InitiateLayerUpload](#)
- [ListTagsForResource](#)
- [PutImage](#)
- [PutRegistryCatalogData](#)
- [PutRepositoryCatalogData](#)
- [SetRepositoryPolicy](#)
- [TagResource](#)
- [UntagResource](#)
- [UploadLayerPart](#)

# BatchCheckLayerAvailability

Checks the availability of one or more image layers that are within a repository in a public registry. When an image is pushed to a repository, each image layer is checked to verify if it has been uploaded before. If it has been uploaded, then the image layer is skipped.

## Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

## Request Syntax

```
{
  "layerDigests": [ "string" ],
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### layerDigests

The digests of the image layers to check.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

## registryId

The AWS account ID, or registry alias, associated with the public registry that contains the image layers to check. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

## repositoryName

The name of the repository that's associated with the image layers to check.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "layerDigest": "string"
    }
  ],
  "layers": [
    {
      "layerAvailability": "string",
      "layerDigest": "string",
      "layerSize": number,
      "mediaType": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### failures

Any failures associated with the call.

Type: Array of [LayerFailure](#) objects

### layers

A list of image layer objects that correspond to the image layer references in the request.

Type: Array of [Layer](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RegistryNotFoundException**

The registry doesn't exist.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchDeleteImage

Deletes a list of specified images that are within a repository in a public registry. Images are specified with either an `imageTag` or `imageDigest`.

You can remove a tag from an image by specifying the image's tag in your request. When you remove the last tag from an image, the image is deleted from your repository.

You can completely delete an image (and all of its tags) by specifying the digest of the image in your request.

## Request Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### imageIds

A list of image ID references that correspond to images to delete. The format of the `imageIds` reference is `imageTag=tag` or `imageDigest=digest`.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

## registryId

The AWS account ID, or registry alias, that's associated with the registry that contains the image to delete. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

## repositoryName

The repository in a public registry that contains the image to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "imageId": {
        "imageDigest": "string",
        "imageTag": "string"
      }
    }
  ],
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### failures

Any failures associated with the call.

Type: Array of [ImageFailure](#) objects

### imagelds

The image IDs of the deleted images.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CompleteLayerUpload

Notifies Amazon ECR that the image layer upload is complete for a specified public registry, repository name, and upload ID. You can optionally provide a sha256 digest of the image layer for data validation purposes.

When an image is pushed, the CompleteLayerUpload API is called once for each new image layer to verify that the upload is complete.

## Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

## Request Syntax

```
{
  "layerDigests": [ "string" ],
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### layerDigests

The sha256 digest of the image layer.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: Yes

### registryId

The AWS account ID, or registry alias, associated with the registry where layers are uploaded. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

### repositoryName

The name of the repository in a public registry to associate with the image layer.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

### uploadId

The upload ID from a previous [InitiateLayerUpload](#) operation to associate with the image layer.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

## Response Syntax

```
{
  "layerDigest": "string",
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### layerDigest

The sha256 digest of the image layer.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

### registryId

The public registry ID that's associated with the request.

Type: String

Pattern: `[0-9]{12}`

### repositoryName

The repository name that's associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

### uploadId

The upload ID that's associated with the layer.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

**EmptyUploadException**

The specified layer upload doesn't contain any layer parts.

HTTP Status Code: 400

**InvalidLayerException**

The layer digest calculation performed by Amazon ECR when the image layer doesn't match the digest specified.

HTTP Status Code: 400

**InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

**LayerAlreadyExistsException**

The image layer already exists in the associated repository.

HTTP Status Code: 400

**LayerPartTooSmallException**

Layer parts must be at least 5 MiB in size.

HTTP Status Code: 400

**RegistryNotFoundException**

The registry doesn't exist.

HTTP Status Code: 400

**RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

**ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

### **UploadNotFoundException**

The upload can't be found, or the specified upload ID isn't valid for this repository.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateRepository

Creates a repository in a public registry. For more information, see [Public repositories](#) in the *Amazon Elastic Container Registry Public User Guide*.

## Request Syntax

```
{
  "catalogData": {
    "aboutText": "string",
    "architectures": [ "string" ],
    "description": "string",
    "logoImageBlob": blob,
    "operatingSystems": [ "string" ],
    "usageText": "string"
  },
  "repositoryName": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### catalogData

The details about the repository that are publicly visible in the Amazon ECR Public Gallery.

Type: [RepositoryCatalogDataInput](#) object

Required: No

### repositoryName

The name to use for the repository. This appears publicly in the Amazon ECR Public Gallery. The repository name can be specified on its own (for example `nginx-web-app`) or prepended with

a namespace to group the repository into a category (for example `project-a/nginx-web-app`).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## tags

The metadata that you apply to each repository to help categorize and organize your repositories. Each tag consists of a key and an optional value. You define both of them. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
  "catalogData": {
    "aboutText": "string",
    "architectures": [ "string" ],
    "description": "string",
    "logoUrl": "string",
    "marketplaceCertified": boolean,
    "operatingSystems": [ "string" ],
    "usageText": "string"
  },
  "repository": {
    "createdAt": number,
    "registryId": "string",
    "repositoryArn": "string",
    "repositoryName": "string",
    "repositoryUri": "string"
  }
}
```

```
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### catalogData

The catalog data for a repository. This data is publicly visible in the Amazon ECR Public Gallery.

Type: [RepositoryCatalogData](#) object

### repository

The repository that was created.

Type: [Repository](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **InvalidTagParameterException**

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

### **LimitExceededException**

The operation didn't succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Public service quotas](#) in the Amazon Elastic Container Registry Public User Guide.

HTTP Status Code: 400

### **RepositoryAlreadyExistsException**

The specified repository already exists in the specified registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **TooManyTagsException**

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DeleteRepository

Deletes a repository in a public registry. If the repository contains images, you must either manually delete all images in the repository or use the `force` option. This option deletes all images on your behalf before deleting the repository.

## Request Syntax

```
{  
  "force": boolean,  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### force

The force option can be used to delete a repository that contains images. If the force option is not used, the repository must be empty prior to deletion.

Type: Boolean

Required: No

### registryId

The AWS account ID that's associated with the public registry that contains the repository to delete. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

### repositoryName

The name of the repository to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "repository": {
    "createdAt": number,
    "registryId": "string",
    "repositoryArn": "string",
    "repositoryName": "string",
    "repositoryUri": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### repository

The repository that was deleted.

Type: [Repository](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## RepositoryNotEmptyException

The specified repository contains images. To delete a repository that contains images, you must force the deletion with the `force` parameter.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DeleteRepositoryPolicy

Deletes the repository policy that's associated with the specified repository.

## Request Syntax

```
{
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### registryId

The AWS account ID that's associated with the public registry that contains the repository policy to delete. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

### repositoryName

The name of the repository that's associated with the repository policy to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

Required: Yes

## Response Syntax

```
{
```

```
"policyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### policyText

The JSON repository policy that was deleted from the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

### registryId

The registry ID that's associated with the request.

Type: String

Pattern: [0-9]{12}

### repositoryName

The repository name that's associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **RepositoryPolicyNotFoundException**

The specified repository and registry combination doesn't have an associated repository policy.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DescribeImages

Returns metadata that's related to the images in a repository in a public registry.

## Note

Beginning with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size. Therefore, it might return a larger image size than the image sizes that are returned by [DescribeImages](#).

## Request Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [imageIds](#)

The list of image IDs for the requested repository.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

### maxResults

The maximum number of repository results that's returned by `DescribeImages` in paginated output. When this parameter is used, `DescribeImages` only returns `maxResults` results in a single page along with a `nextToken` response element. You can see the remaining results of the initial request by sending another `DescribeImages` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter isn't used, then `DescribeImages` returns up to 100 results and a `nextToken` value, if applicable. If you specify images with `imageIds`, you can't use this option.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### nextToken

The `nextToken` value that's returned from a previous paginated `DescribeImages` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. If there are no more results to return, this value is `null`. If you specify images with `imageIds`, you can't use this option.

Type: String

Required: No

### registryId

The AWS account ID that's associated with the public registry that contains the repository where images are described. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

### repositoryName

The repository that contains the images to describe.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

Required: Yes

## Response Syntax

```
{
  "imageDetails": [
    {
      "artifactMediaType": "string",
      "imageDigest": "string",
      "imageManifestMediaType": "string",
      "imagePushedAt": number,
      "imageSizeInBytes": number,
      "imageTags": [ "string" ],
      "registryId": "string",
      "repositoryName": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### imageDetails

A list of [ImageDetail](#) objects that contain data about the image.

Type: Array of [ImageDetail](#) objects

### nextToken

The nextToken value to include in a future DescribeImages request. When the results of a DescribeImages request exceed maxResults, you can use this value to retrieve the next page of results. If there are no more results to return, this value is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ImageNotFoundException**

The image requested doesn't exist in the specified repository.

HTTP Status Code: 400

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeImageTags

Returns the image tag details for a repository in a public registry.

## Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of repository results that's returned by DescribeImageTags in paginated output. When this parameter is used, DescribeImageTags only returns maxResults results in a single page along with a nextToken response element. You can see the remaining results of the initial request by sending another DescribeImageTags request with the returned nextToken value. This value can be between 1 and 1000. If this parameter isn't used, then DescribeImageTags returns up to 100 results and a nextToken value, if applicable. If you specify images with imageIds, you can't use this option.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### nextToken

The nextToken value that's returned from a previous paginated DescribeImageTags request where maxResults was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the nextToken value. If there are

no more results to return, this value is `null`. If you specify images with `imageIds`, you can't use this option.

Type: String

Required: No

### registryId

The AWS account ID that's associated with the public registry that contains the repository where images are described. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

### repositoryName

The name of the repository that contains the image tag details to describe.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "imageTagDetails": [
    {
      "createdAt": number,
      "imageDetail": {
        "artifactMediaType": "string",
        "imageDigest": "string",
        "imageManifestMediaType": "string",
        "imagePushedAt": number,
        "imageSizeInBytes": number
      }
    },
  ],
}
```

```
    "imageTag": "string"  
  }  
],  
"nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### imageTagDetails

The image tag details for the images in the requested repository.

Type: Array of [ImageTagDetail](#) objects

### nextToken

The nextToken value to include in a future DescribeImageTags request. When the results of a DescribeImageTags request exceed maxResults, you can use this value to retrieve the next page of results. If there are no more results to return, this value is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeRegistries

Returns details for a public registry.

## Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of repository results that's returned by `DescribeRegistries` in paginated output. When this parameter is used, `DescribeRegistries` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `DescribeRegistries` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter isn't used, then `DescribeRegistries` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### nextToken

The `nextToken` value that's returned from a previous paginated `DescribeRegistries` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. If there are no more results to return, this value is `null`.

**Note**

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

## Response Syntax

```
{
  "nextToken": "string",
  "registries": [
    {
      "aliases": [
        {
          "defaultRegistryAlias": boolean,
          "name": "string",
          "primaryRegistryAlias": boolean,
          "status": "string"
        }
      ],
      "registryArn": "string",
      "registryId": "string",
      "registryUri": "string",
      "verified": boolean
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## nextToken

The `nextToken` value to include in a future `DescribeRepositories` request. If the results of a `DescribeRepositories` request exceed `maxResults`, you can use this value to retrieve the next page of results. If there are no more results, this value is `null`.

Type: String

## registries

An object that contains the details for a public registry.

Type: Array of [Registry](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeRepositories

Describes repositories that are in a public registry.

## Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryNames": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [maxResults](#)

The maximum number of repository results that's returned by `DescribeRepositories` in paginated output. When this parameter is used, `DescribeRepositories` only returns `maxResults` results in a single page along with a `nextToken` response element. You can see the remaining results of the initial request by sending another `DescribeRepositories` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter isn't used, then `DescribeRepositories` returns up to 100 results and a `nextToken` value, if applicable. If you specify repositories with `repositoryNames`, you can't use this option.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### [nextToken](#)

The `nextToken` value that's returned from a previous paginated `DescribeRepositories` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken`

value. If there are no more results to return, this value is `null`. If you specify repositories with `repositoryNames`, you can't use this option.

**Note**

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

**registryId**

The AWS account ID that's associated with the registry that contains the repositories to be described. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

**repositoryNames**

A list of repositories to describe. If this parameter is omitted, then all repositories in a registry are described.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

**Response Syntax**

```
{
```

```
"nextToken": "string",
"repositories": [
  {
    "createdAt": number,
    "registryId": "string",
    "repositoryArn": "string",
    "repositoryName": "string",
    "repositoryUri": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The `nextToken` value to include in a future `DescribeRepositories` request. When the results of a `DescribeRepositories` request exceed `maxResults`, this value can be used to retrieve the next page of results. If there are no more results to return, this value is `null`.

Type: String

### repositories

A list of repository objects corresponding to valid repositories.

Type: Array of [Repository](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAuthorizationToken

Retrieves an authorization token. An authorization token represents your IAM authentication credentials. You can use it to access any Amazon ECR registry that your IAM principal has access to. The authorization token is valid for 12 hours. This API requires the `ecr-public:GetAuthorizationToken` and `sts:GetServiceBearerToken` permissions.

## Response Syntax

```
{
  "authorizationData": {
    "authorizationToken": "string",
    "expiresAt": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### authorizationData

An authorization token data object that corresponds to a public registry.

Type: [AuthorizationData](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRegistryCatalogData

Retrieves catalog metadata for a public registry.

## Response Syntax

```
{
  "registryCatalogData": {
    "displayName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### registryCatalogData

The catalog metadata for the public registry.

Type: [RegistryCatalogData](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRepositoryCatalogData

Retrieve catalog metadata for a repository in a public registry. This metadata is displayed publicly in the Amazon ECR Public Gallery.

## Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### registryId

The AWS account ID that's associated with the registry that contains the repositories to be described. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

### repositoryName

The name of the repository to retrieve the catalog metadata for.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "catalogData": {
    "aboutText": "string",
    "architectures": [ "string" ],
    "description": "string",
    "logoUrl": "string",
    "marketplaceCertified": boolean,
    "operatingSystems": [ "string" ],
    "usageText": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### catalogData

The catalog metadata for the repository.

Type: [RepositoryCatalogData](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryCatalogDataNotFoundException**

The repository catalog data doesn't exist.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRepositoryPolicy

Retrieves the repository policy for the specified repository.

## Request Syntax

```
{
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### registryId

The AWS account ID that's associated with the public registry that contains the repository. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

### repositoryName

The name of the repository with the policy to retrieve.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

Required: Yes

## Response Syntax

```
{
```

```
"policyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### policyText

The repository policy text that's associated with the repository. The policy text will be in JSON format.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

### registryId

The registry ID that's associated with the request.

Type: String

Pattern: [0-9]{12}

### repositoryName

The repository name that's associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **RepositoryPolicyNotFoundException**

The specified repository and registry combination doesn't have an associated repository policy.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# InitiateLayerUpload

Notifies Amazon ECR that you intend to upload an image layer.

When an image is pushed, the `InitiateLayerUpload` API is called once for each image layer that hasn't already been uploaded. Whether an image layer uploads is determined by the `BatchCheckLayerAvailability` API action.

## Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

## Request Syntax

```
{
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### registryId

The AWS account ID, or registry alias, that's associated with the registry to which you intend to upload layers. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

### repositoryName

The name of the repository that you want to upload layers to.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "partSize": number,
  "uploadId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### partSize

The size, in bytes, that Amazon ECR expects future layer part uploads to be.

Type: Long

Valid Range: Minimum value of 0.

### uploadId

The upload ID for the layer upload. This parameter is passed to further [UploadLayerPart](#) and [CompleteLayerUpload](#) operations.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## RegistryNotFoundException

The registry doesn't exist.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

List the tags for an Amazon ECR Public resource.

## Request Syntax

```
{
  "resourceArn": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) that identifies the resource to list the tags for. Currently, the supported resource is an Amazon ECR Public repository.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

## Response Syntax

```
{
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## tags

The tags for the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutImage

Creates or updates the image manifest and tags that are associated with an image.

When an image is pushed and all new image layers have been uploaded, the PutImage API is called once to create or update the image manifest and the tags that are associated with the image.

## Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

## Request Syntax

```
{
  "imageDigest": "string",
  "imageManifest": "string",
  "imageManifestMediaType": "string",
  "imageTag": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### imageDigest

The image digest of the image manifest that corresponds to the image.

Type: String

Required: No

### imageManifest

The image manifest that corresponds to the image to be uploaded.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4194304.

Required: Yes

### imageManifestMediaType

The media type of the image manifest. If you push an image manifest that doesn't contain the `mediaType` field, you must specify the `imageManifestMediaType` in the request.

Type: String

Required: No

### imageTag

The tag to associate with the image. This parameter is optional.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

### registryId

The AWS account ID, or registry alias, that's associated with the public registry that contains the repository where the image is put. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

### repositoryName

The name of the repository where the image is put.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "image": {
    "imageId": {
      "imageDigest": "string",
      "imageTag": "string"
    },
    "imageManifest": "string",
    "imageManifestMediaType": "string",
    "registryId": "string",
    "repositoryName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### image

Details of the image uploaded.

Type: [Image](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ImageAlreadyExistsException**

The specified image has already been pushed, and there were no changes to the manifest or image tag after the last push.

HTTP Status Code: 400

## **ImageDigestDoesNotMatchException**

The specified image digest doesn't match the digest that Amazon ECR calculated for the image.

HTTP Status Code: 400

## **ImageTagAlreadyExistsException**

The specified image is tagged with a tag that already exists. The repository is configured for tag immutability.

HTTP Status Code: 400

## **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## **LayersNotFoundException**

The specified layers can't be found, or the specified layer isn't valid for this repository.

HTTP Status Code: 400

## **LimitExceededException**

The operation didn't succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Public service quotas](#) in the Amazon Elastic Container Registry Public User Guide.

HTTP Status Code: 400

## **ReferencedImagesNotFoundException**

The manifest list is referencing an image that doesn't exist.

HTTP Status Code: 400

## **RegistryNotFoundException**

The registry doesn't exist.

HTTP Status Code: 400

## **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutRegistryCatalogData

Create or update the catalog data for a public registry.

## Request Syntax

```
{  
  "displayName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### displayName

The display name for a public registry. The display name is shown as the repository author in the Amazon ECR Public Gallery.

#### Note

The registry display name is only publicly visible in the Amazon ECR Public Gallery for verified accounts.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

## Response Syntax

```
{  
  "registryCatalogData": {  
    "displayName": "string"  
  }  
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [registryCatalogData](#)

The catalog data for the public registry.

Type: [RegistryCatalogData](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutRepositoryCatalogData

Creates or updates the catalog data for a repository in a public registry.

## Request Syntax

```
{
  "catalogData": {
    "aboutText": "string",
    "architectures": [ "string" ],
    "description": "string",
    "logoImageBlob": blob,
    "operatingSystems": [ "string" ],
    "usageText": "string"
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### catalogData

An object containing the catalog data for a repository. This data is publicly visible in the Amazon ECR Public Gallery.

Type: [RepositoryCatalogDataInput](#) object

Required: Yes

### registryId

The AWS account ID that's associated with the public registry the repository is in. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

## repositoryName

The name of the repository to create or update the catalog data for.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

## Response Syntax

```
{
  "catalogData": {
    "aboutText": "string",
    "architectures": [ "string" ],
    "description": "string",
    "logoUrl": "string",
    "marketplaceCertified": boolean,
    "operatingSystems": [ "string" ],
    "usageText": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### catalogData

The catalog data for the repository.

Type: [RepositoryCatalogData](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# SetRepositoryPolicy

Applies a repository policy to the specified public repository to control access permissions. For more information, see [Amazon ECR repository policies](#) in the *Amazon Elastic Container Registry Public User Guide*.

## Request Syntax

```
{  
  "force": boolean,  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### force

If the policy that you want to set on a repository policy would prevent you from setting another policy in the future, you must force the [SetRepositoryPolicy](#) operation. This prevents accidental repository lockouts.

Type: Boolean

Required: No

### policyText

The JSON repository policy text to apply to the repository. For more information, see [Amazon ECR repository policies](#) in the *Amazon Elastic Container Registry Public User Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: Yes

## registryId

The AWS account ID that's associated with the registry that contains the repository. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

## repositoryName

The name of the repository to receive the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

Required: Yes

## Response Syntax

```
{
  "policyText": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### policyText

The JSON repository policy text that's applied to the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

### registryId

The registry ID that's associated with the request.

Type: String

Pattern: [0-9]{12}

### repositoryName

The repository name that's associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: (?:[a-z0-9]+(?:[.\_-][a-z0-9]+)\*/)\*[a-z0-9]+(?:[.\_-][a-z0-9]+)\*

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### **RepositoryNotFoundException**

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### **ServerException**

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### **UnsupportedCommandException**

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Associates the specified tags to a resource with the specified `resourceArn`. If existing tags on a resource aren't specified in the request parameters, they aren't changed. When a resource is deleted, the tags associated with that resource are also deleted.

## Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) of the resource to add tags to. Currently, the supported resource is an Amazon ECR Public repository.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

### tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### InvalidTagParameterException

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

### RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Deletes specified tags from a resource.

## Request Syntax

```
{
  "resourceArn": "string",
  "tagKeys": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) of the resource to delete tags from. Currently, the supported resource is an Amazon ECR Public repository.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

### tagKeys

The keys of the tags to be removed.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

### InvalidTagParameterException

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

### RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

### ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

### TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

### UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UploadLayerPart

Uploads an image layer part to Amazon ECR.

When an image is pushed, each new image layer is uploaded in parts. The maximum size of each image layer part can be 20971520 bytes (about 20MB). The UploadLayerPart API is called once for each new image layer part.

## Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

## Request Syntax

```
{
  "layerPartBlob": blob,
  "partFirstByte": number,
  "partLastByte": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### layerPartBlob

The base64-encoded layer part payload.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 20971520.

Required: Yes

### partFirstByte

The position of the first byte of the layer part within the overall image layer.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

### partLastByte

The position of the last byte of the layer part within the overall image layer.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

### registryId

The AWS account ID, or registry alias, that's associated with the registry that you're uploading layer parts to. If you do not specify a registry, the default public registry is assumed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

### repositoryName

The name of the repository that you're uploading layer parts to.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern:  $(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*$

Required: Yes

### uploadId

The upload ID from a previous [InitiateLayerUpload](#) operation to associate with the layer part upload.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

## Response Syntax

```
{
  "lastByteReceived": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### lastByteReceived

The integer value of the last byte that's received in the request.

Type: Long

Valid Range: Minimum value of 0.

### registryId

The registry ID that's associated with the request.

Type: String

Pattern: `[0-9]{12}`

### repositoryName

The repository name that's associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

### **uploadId**

The upload ID that's associated with the request.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

## **Errors**

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidLayerPartException**

The layer part size isn't valid, or the first byte specified isn't consecutive to the last byte of a previous layer part upload.

#### **lastValidByteReceived**

The position of the last byte of the layer part.

#### **registryId**

The AWS account ID that's associated with the layer part.

#### **repositoryName**

The name of the repository.

#### **uploadId**

The upload ID that's associated with the layer part.

HTTP Status Code: 400

### **InvalidParameterException**

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

## LimitExceededException

The operation didn't succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Public service quotas](#) in the Amazon Elastic Container Registry Public User Guide.

HTTP Status Code: 400

## RegistryNotFoundException

The registry doesn't exist.

HTTP Status Code: 400

## RepositoryNotFoundException

The specified repository can't be found. Check the spelling of the specified repository and ensure that you're performing operations on the correct registry.

HTTP Status Code: 400

## ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

## UnsupportedCommandException

The action isn't supported in this Region.

HTTP Status Code: 400

## UploadNotFoundException

The upload can't be found, or the specified upload ID isn't valid for this repository.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Amazon Elastic Container Registry Public API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AuthorizationData](#)
- [Image](#)
- [ImageDetail](#)
- [ImageFailure](#)
- [ImageIdentifier](#)
- [ImageTagDetail](#)
- [Layer](#)
- [LayerFailure](#)
- [ReferencedImageDetail](#)
- [Registry](#)
- [RegistryAlias](#)
- [RegistryCatalogData](#)
- [Repository](#)
- [RepositoryCatalogData](#)
- [RepositoryCatalogDataInput](#)
- [Tag](#)

# AuthorizationData

An authorization token data object that corresponds to a public registry.

## Contents

### authorizationToken

A base64-encoded string that contains authorization data for a public Amazon ECR registry. When the string is decoded, it's presented in the format `user:password` for public registry authentication using `docker login`.

Type: String

Pattern: `^\S+$`

Required: No

### expiresAt

The Unix time in seconds and milliseconds when the authorization token expires. Authorization tokens are valid for 12 hours.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Image

An object that represents an Amazon ECR image.

## Contents

### **imageId**

An object that contains the image tag and image digest associated with an image.

Type: [ImageIdentifier](#) object

Required: No

### **imageManifest**

The image manifest that's associated with the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4194304.

Required: No

### **imageManifestMediaType**

The manifest media type of the image.

Type: String

Required: No

### **registryId**

The AWS account ID that's associated with the registry containing the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Required: No

### **repositoryName**

The name of the repository that's associated with the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImageDetail

An object that describes an image that's returned by a [DescribeImages](#) operation.

## Contents

### **artifactMediaType**

The artifact media type of the image.

Type: String

Required: No

### **imageDigest**

The sha256 digest of the image manifest.

Type: String

Required: No

### **imageManifestMediaType**

The media type of the image manifest.

Type: String

Required: No

### **imagePushedAt**

The date and time, expressed in standard JavaScript date format, that the current image was pushed to the repository at.

Type: Timestamp

Required: No

### **imageSizeInBytes**

The size, in bytes, of the image in the repository.

If the image is a manifest list, this is the max size of all manifests in the list.

**Note**

Beginning with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size, so it might return a larger image size than the image sizes that are returned by [DescribeImages](#).

Type: Long

Required: No

**imageTags**

The list of tags that's associated with this image.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

**registryId**

The AWS account ID that's associated with the public registry where this image belongs.

Type: String

Pattern: `[0-9]{12}`

Required: No

**repositoryName**

The name of the repository where this image belongs.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImageFailure

An object that represents an Amazon ECR image failure.

## Contents

### failureCode

The code that's associated with the failure.

Type: String

Valid Values: `InvalidImageDigest` | `InvalidImageTag` | `ImageTagDoesNotMatchDigest` | `ImageNotFound` | `MissingDigestAndTag` | `ImageReferencedByManifestList` | `KmsError`

Required: No

### failureReason

The reason for the failure.

Type: String

Required: No

### imageId

The image ID that's associated with the failure.

Type: [ImageIdentifier](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ImageIdentifier

An object with identifying information for an Amazon ECR image.

## Contents

### imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

### imageTag

The tag that's used for the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImageTagDetail

An object that represents the image tag details for an image.

## Contents

### createdAt

The time stamp that indicates when the image tag was created.

Type: Timestamp

Required: No

### imageDetail

An object that describes the details of an image.

Type: [ReferencedImageDetail](#) object

Required: No

### imageTag

The tag that's associated with the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Layer

An object that represents an Amazon ECR image layer.

## Contents

### **layerAvailability**

The availability status of the image layer.

Type: String

Valid Values: AVAILABLE | UNAVAILABLE

Required: No

### **layerDigest**

The sha256 digest of the image layer.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: No

### **layerSize**

The size, in bytes, of the image layer.

Type: Long

Required: No

### **mediaType**

The media type of the layer, such as `application/vnd.docker.image.rootfs.diff.tar.gzip` or `application/vnd.oci.image.layer.v1.tar+gzip`.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LayerFailure

An object that represents an Amazon ECR image layer failure.

## Contents

### failureCode

The failure code that's associated with the failure.

Type: String

Valid Values: `InvalidLayerDigest` | `MissingLayerDigest`

Required: No

### failureReason

The reason for the failure.

Type: String

Required: No

### layerDigest

The layer digest that's associated with the failure.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ReferencedImageDetail

An object that describes the image tag details that are returned by a [DescribeImageTags](#) action.

## Contents

### **artifactMediaType**

The artifact media type of the image.

Type: String

Required: No

### **imageDigest**

The sha256 digest of the image manifest.

Type: String

Required: No

### **imageManifestMediaType**

The media type of the image manifest.

Type: String

Required: No

### **imagePushedAt**

The date and time, expressed in standard JavaScript date format, which the current image tag was pushed to the repository at.

Type: Timestamp

Required: No

### **imageSizeInBytes**

The size, in bytes, of the image in the repository.

If the image is a manifest list, this is the max size of all manifests in the list.

**Note**

Beginning with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size, so it might return a larger image size than the image sizes that are returned by [DescribeImages](#).

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Registry

The details of a public registry.

## Contents

### aliases

An array of objects that represents the aliases for a public registry.

Type: Array of [RegistryAlias](#) objects

Required: Yes

### registryArn

The Amazon Resource Name (ARN) of the public registry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

### registryId

The AWS account ID that's associated with the registry. If you do not specify a registry, the default public registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: Yes

### registryUri

The URI of a public registry. The URI contains a universal prefix and the registry alias.

Type: String

Required: Yes

### verified

Indicates whether the account is a verified AWS Marketplace vendor. If an account is verified, each public repository receives a verified account badge on the Amazon ECR Public Gallery.

Type: Boolean

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RegistryAlias

An object representing the aliases for a public registry. A public registry is given an alias when it's created. However, a custom alias can be set using the Amazon ECR console. For more information, see [Public registries](#) in the *Amazon Elastic Container Registry Public User Guide*.

## Contents

### defaultRegistryAlias

Indicates whether the registry alias is the default alias for the registry. When the first public repository is created, your public registry is assigned a default registry alias.

Type: Boolean

Required: Yes

### name

The name of the registry alias.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 50.

Pattern: `[a-z][a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

### primaryRegistryAlias

Indicates whether the registry alias is the primary alias for the registry. If true, the alias is the primary registry alias and is displayed in both the repository URL and the image URI used in the `docker pull` commands on the Amazon ECR Public Gallery.

#### Note

A registry alias that isn't the primary registry alias can be used in the repository URI in a `docker pull` command.

Type: Boolean

Required: Yes

### **status**

The status of the registry alias.

Type: String

Valid Values: ACTIVE | PENDING | REJECTED

Required: Yes

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RegistryCatalogData

The metadata for a public registry.

## Contents

### displayName

The display name for a public registry. This appears on the Amazon ECR Public Gallery.

#### Important

Only accounts that have the verified account badge can have a registry display name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Repository

An object representing a repository.

## Contents

### **createdAt**

The date and time, in JavaScript date format, when the repository was created.

Type: Timestamp

Required: No

### **registryId**

The AWS account ID that's associated with the public registry that contains the repository.

Type: String

Pattern: [0-9]{12}

Required: No

### **repositoryArn**

The Amazon Resource Name (ARN) that identifies the repository. The ARN contains the `arn:aws:ecr` namespace, followed by the region of the repository, AWS account ID of the repository owner, repository namespace, and repository name. For example, `arn:aws:ecr:region:012345678910:repository/test`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### **repositoryName**

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 205.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

### **repositoryUri**

The URI for the repository. You can use this URI for container image push and pull operations.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RepositoryCatalogData

The catalog data for a repository. This data is publicly visible in the Amazon ECR Public Gallery.

## Contents

### aboutText

The longform description of the contents of the repository. This text appears in the repository details on the Amazon ECR Public Gallery.

Type: String

Length Constraints: Maximum length of 25600.

Required: No

### architectures

The architecture tags that are associated with the repository.

#### Note

Only supported operating system tags appear publicly in the Amazon ECR Public Gallery. For more information, see [RepositoryCatalogDataInput](#).

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

### description

The short description of the repository.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

### **logoUrl**

The URL that contains the logo that's associated with the repository.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

### **marketplaceCertified**

Indicates whether the repository is certified by AWS Marketplace.

Type: Boolean

Required: No

### **operatingSystems**

The operating system tags that are associated with the repository.

#### **Note**

Only supported operating system tags appear publicly in the Amazon ECR Public Gallery. For more information, see [RepositoryCatalogDataInput](#).

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

### **usageText**

The longform usage details of the contents of the repository. The usage text provides context for users of the repository.

Type: String

Length Constraints: Maximum length of 25600.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RepositoryCatalogDataInput

An object that contains the catalog data for a repository. This data is publicly visible in the Amazon ECR Public Gallery.

## Contents

### aboutText

A detailed description of the contents of the repository. It's publicly visible in the Amazon ECR Public Gallery. The text must be in markdown format.

Type: String

Length Constraints: Maximum length of 25600.

Required: No

### architectures

The system architecture that the images in the repository are compatible with. On the Amazon ECR Public Gallery, the following supported architectures appear as badges on the repository and are used as search filters.

#### Note

If an unsupported tag is added to your repository catalog data, it's associated with the repository and can be retrieved using the API but isn't discoverable in the Amazon ECR Public Gallery.

- ARM
- ARM 64
- x86
- x86-64

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

## description

A short description of the contents of the repository. This text appears in both the image details and also when searching for repositories on the Amazon ECR Public Gallery.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

## logoImageBlob

The base64-encoded repository logo payload.

### Note

The repository logo is only publicly visible in the Amazon ECR Public Gallery for verified accounts.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 512000.

Required: No

## operatingSystems

The operating systems that the images in the repository are compatible with. On the Amazon ECR Public Gallery, the following supported operating systems appear as badges on the repository and are used as search filters.

### Note

If an unsupported tag is added to your repository catalog data, it's associated with the repository and can be retrieved using the API but isn't discoverable in the Amazon ECR Public Gallery.

- Linux

- Windows

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

### **usageText**

Detailed information about how to use the contents of the repository. It's publicly visible in the Amazon ECR Public Gallery. The usage text provides context, support information, and additional usage details for users of the repository. The text must be in markdown format.

Type: String

Length Constraints: Maximum length of 25600.

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Tag

The metadata that you apply to a resource to help you categorize and organize them. Each tag consists of a key and an optional value. You define both. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

## Contents

### Key

One part of a key-value pair that make up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### Value

The optional part of a key-value pair that make up a tag. A value acts as a descriptor within a tag category (key).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

## Required: Conditional

# Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

## **IncompleteSignature**

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

## **InternalFailure**

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

## **MalformedHttpRequestException**

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

**NotAuthorized**

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

**OptInRequired**

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

**RequestAbortedException**

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

**RequestEntityTooLargeException**

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

**RequestTimeoutException**

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

**ServiceUnavailable**

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

**ThrottlingException**

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

## **UnknownOperationException**

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

## **UnrecognizedClientException**

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

## **ValidationError**

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400