



API Reference Guide for Zonal Shift and Zonal Autoshift

Amazon Route 53 Application Recovery Controller



API Version 2022-10-30

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Route 53 Application Recovery Controller: API Reference Guide for Zonal Shift and Zonal Autoshift

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CancelPracticeRun	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	3
Response Elements	4
Errors	5
See Also	6
CancelZonalShift	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	8
Response Elements	9
Errors	11
See Also	12
CreatePracticeRunConfiguration	13
Request Syntax	13
URI Request Parameters	14
Request Body	14
Response Syntax	17
Response Elements	17
Errors	18
See Also	19
DeletePracticeRunConfiguration	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	22
Errors	22
See Also	23

GetAutoshiftObserverNotificationStatus	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	25
Response Elements	25
Errors	26
See Also	26
GetManagedResource	28
Request Syntax	28
URI Request Parameters	28
Request Body	28
Response Syntax	28
Response Elements	30
Errors	31
See Also	32
ListAutoshifts	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	34
Errors	34
See Also	35
ListManagedResources	36
Request Syntax	36
URI Request Parameters	36
Request Body	36
Response Syntax	36
Response Elements	37
Errors	38
See Also	38
ListZonalShifts	40
Request Syntax	40
URI Request Parameters	40
Request Body	41

Response Syntax	41
Response Elements	41
Errors	42
See Also	43
StartPracticeRun	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	45
Response Elements	45
Errors	47
See Also	48
StartZonalShift	49
Request Syntax	49
URI Request Parameters	49
Request Body	50
Response Syntax	51
Response Elements	52
Errors	54
See Also	55
UpdateAutoshiftObserverNotificationStatus	56
Request Syntax	56
URI Request Parameters	56
Request Body	56
Response Syntax	57
Response Elements	57
Errors	57
See Also	58
UpdatePracticeRunConfiguration	59
Request Syntax	59
URI Request Parameters	59
Request Body	60
Response Syntax	62
Response Elements	63
Errors	63
See Also	64

UpdateZonalAutoshiftConfiguration	66
Request Syntax	66
URI Request Parameters	66
Request Body	66
Response Syntax	67
Response Elements	67
Errors	68
See Also	69
UpdateZonalShift	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	71
Response Elements	72
Errors	74
See Also	75
Data Types	76
AutoshiftInResource	77
Contents	77
See Also	78
AutoshiftSummary	79
Contents	79
See Also	80
ControlCondition	81
Contents	81
See Also	81
ManagedResourceSummary	83
Contents	83
See Also	85
PracticeRunConfiguration	86
Contents	86
See Also	88
ZonalShiftInResource	89
Contents	89
See Also	92
ZonalShiftSummary	93

Contents	93
See Also	96
Common Parameters	97
Common Error Types	100

Welcome

Welcome to the API Reference Guide for zonal shift and zonal autoshift in Amazon Application Recovery Controller (ARC).

You can start a zonal shift to move traffic for a load balancer resource away from an Availability Zone to help your application recover quickly from an impairment in an Availability Zone. For example, you can recover your application from a developer's bad code deployment or from an AWS infrastructure failure in a single Availability Zone.

You can also configure zonal autoshift for supported load balancer resources. Zonal autoshift is a capability in ARC where you authorize AWS to shift away application resource traffic from an Availability Zone during events, on your behalf, to help reduce your time to recovery. AWS starts an autoshift when internal telemetry indicates that there is an Availability Zone impairment that could potentially impact customers.

For more information about using zonal shift and zonal autoshift, see the [Amazon Application Recovery Controller Developer Guide](#).

This document was last published on April 9, 2026.

Actions

The following actions are supported:

- [CancelPracticeRun](#)
- [CancelZonalShift](#)
- [CreatePracticeRunConfiguration](#)
- [DeletePracticeRunConfiguration](#)
- [GetAutoshiftObserverNotificationStatus](#)
- [GetManagedResource](#)
- [ListAutoshifts](#)
- [ListManagedResources](#)
- [ListZonalShifts](#)
- [StartPracticeRun](#)
- [StartZonalShift](#)
- [UpdateAutoshiftObserverNotificationStatus](#)
- [UpdatePracticeRunConfiguration](#)
- [UpdateZonalAutoshiftConfiguration](#)
- [UpdateZonalShift](#)

CancelPracticeRun

Cancel an in-progress practice run zonal shift in Amazon Application Recovery Controller.

Request Syntax

```
DELETE /practicерuns/zonalShiftId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

zonalShiftId

The identifier of a practice run zonal shift in Amazon Application Recovery Controller that you want to cancel.

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiryTime": number,
  "resourceIdentifier": "string",
  "startTime": number,
  "status": "string",
  "zonalShiftId": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

awayFrom

The Availability Zone (for example, use1-az1) that traffic was moved away from for a resource that you specified for the practice run.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

comment

The initial comment that you entered about the practice run. Be aware that this comment can be overwritten by AWS if the automatic check for balanced capacity fails. For more information, see [Capacity checks for practice runs](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

expiryTime

The expiry time (expiration time) for an on-demand practice run zonal shift is 30 minutes from the time when you start the practice run, unless you cancel it before that time. However, be aware that the `expiryTime` field for practice run zonal shifts always has a value of 1 minute.

Type: Timestamp

resourceIdentifier

The identifier for the resource that you canceled a practice run zonal shift for. The identifier is the Amazon Resource Name (ARN) for the resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

status

A status for the practice run that you canceled (expected status is **CANCELED**).

The Status for a practice run zonal shift can have one of the following values:

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

zonalShiftId

The identifier of the practice run zonal shift in Amazon Application Recovery Controller that was canceled.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelZonalShift

Cancel a zonal shift in Amazon Application Recovery Controller. To cancel the zonal shift, specify the zonal shift ID.

A zonal shift can be one that you've started for a resource in your AWS account in an AWS Region, or it can be a zonal shift started by a practice run with zonal autoshift.

Request Syntax

```
DELETE /zonalshifts/zonalShiftId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

zonalShiftId

The internally-generated identifier of a zonal shift.

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiryTime": number,
  "resourceIdentifier": "string",
```

```
"startTime": number,  
"status": "string",  
"zonalShiftId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

awayFrom

The Availability Zone (for example, use1-az1) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

comment

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. A new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

expiryTime

The expiry time (expiration time) for a customer-initiated zonal shift. A zonal shift is temporary and must be set to expire when you start the zonal shift. You can initially set a zonal shift to expire in a maximum of three days (72 hours). However, you can update a zonal shift to set a new expiration at any time.

When you start a zonal shift, you specify how long you want it to be active, which ARC converts to an expiry time (expiration time). You can cancel a zonal shift when you're ready to restore traffic to the Availability Zone, or just wait for it to expire. Or you can update the zonal shift to specify another length of time to expire in.

Type: Timestamp

resourceIdentifier

The identifier for the resource that AWS shifts traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

status

A status for a zonal shift.

The Status for a zonal shift can have one of the following values:

- **ACTIVE:** The zonal shift has been started and is active.
- **EXPIRED:** The zonal shift has expired (the expiry time was exceeded).
- **CANCELED:** The zonal shift was canceled.

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

zonalShiftId

The identifier of a zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePracticeRunConfiguration

A practice run configuration for zonal autoshift is required when you enable zonal autoshift. A practice run configuration includes specifications for blocked dates and blocked time windows, and for Amazon CloudWatch alarms that you create to use with practice runs. The alarms that you specify are an *outcome alarm*, to monitor application health during practice runs and, optionally, a *blocking alarm*, to block practice runs from starting.

When a resource has a practice run configuration, ARC starts zonal shifts for the resource weekly, to shift traffic for practice runs. Practice runs help you to ensure that shifting away traffic from an Availability Zone during an autoshift is safe for your application.

For more information, see [Considerations when you configure zonal autoshift](#) in the Amazon Application Recovery Controller Developer Guide.

Request Syntax

```
POST /configuration HTTP/1.1
Content-type: application/json

{
  "allowedWindows": [ "string" ],
  "blockedDates": [ "string" ],
  "blockedWindows": [ "string" ],
  "blockingAlarms": [
    {
      "alarmIdentifier": "string",
      "type": "string"
    }
  ],
  "outcomeAlarms": [
    {
      "alarmIdentifier": "string",
      "type": "string"
    }
  ],
  "resourceIdentifier": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

allowedWindows

Optionally, you can allow ARC to start practice runs for specific windows of days and times.

The format for allowed windows is: DAY:HH:SS-DAY:HH:SS. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Also, be aware of potential time adjustments that might be required for daylight saving time differences. Separate multiple allowed windows with spaces.

For example, say you want to allow practice runs only on Wednesdays and Fridays from noon to 5 p.m. For this scenario, you could set the following recurring days and times as allowed windows, for example: `Wed-12:00-Wed:17:00 Fri-12:00-Fri:17:00`.

Important

The allowedWindows have to start and end on the same day. Windows that span multiple days aren't supported.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: `(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}`

Required: No

blockedDates

Optionally, you can block ARC from starting practice runs for a resource on specific calendar dates.

The format for blocked dates is: YYYY-MM-DD. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Separate multiple blocked dates with spaces.

For example, if you have an application update scheduled to launch on May 1, 2024, and you don't want practice runs to shift traffic away at that time, you could set a blocked date for 2024-05-01.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 10.

Pattern: [0-9]{4}-[0-9]{2}-[0-9]{2}

Required: No

blockedWindows

Optionally, you can block ARC from starting practice runs for specific windows of days and times.

The format for blocked windows is: DAY:HH:SS-DAY:HH:SS. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Also, be aware of potential time adjustments that might be required for daylight saving time differences. Separate multiple blocked windows with spaces.

For example, say you run business report summaries three days a week. For this scenario, you could set the following recurring days and times as blocked windows, for example: Mon:00:00-Mon:10:00 Wed-20:30-Wed:21:30 Fri-20:30-Fri:21:30.

Important

The blockedWindows have to start and end on the same day. Windows that span multiple days aren't supported.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: (Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}

Required: No

blockingAlarms

Blocking alarms for practice runs are optional alarms that you can specify that block practice runs when one or more of the alarms is in an ALARM state.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

outcomeAlarms

Outcome alarms for practice runs are alarms that you specify that end a practice run when one or more of the alarms is in an ALARM state.

Configure one or more of these alarms to monitor the health of your application when traffic is shifted away from an Availability Zone during each practice run. You should configure these alarms to go into an ALARM state if you want to stop a zonal shift, to let traffic for the resource return to the original Availability Zone.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

resourceIdentifier

The identifier of the resource that AWS shifts traffic for with a practice run zonal shift. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)

- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "name": "string",
  "practiceRunConfiguration": {
    "allowedWindows": [ "string " ],
    "blockedDates": [ "string " ],
    "blockedWindows": [ "string " ],
    "blockingAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ],
    "outcomeAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ]
  },
  "zonalAutoshiftStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource that you configured the practice run for.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: `arn:.*`

name

The name of the resource that you configured the practice run for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

practiceRunConfiguration

A practice run configuration for a resource. Configurations include the outcome alarm that you specify for practice runs, and, optionally, a blocking alarm and blocking dates and windows.

Type: [PracticeRunConfiguration](#) object

zonalAutoshiftStatus

The status for zonal autoshift for a resource. When you specify ENABLED for the autoshift status, AWS shifts traffic away from shifts away application resource traffic from an Availability Zone, on your behalf, when internal telemetry indicates that there is an Availability Zone impairment that could potentially impact customers.

When you enable zonal autoshift, you must also configure practice runs for the resource.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePracticeRunConfiguration

Deletes the practice run configuration for a resource. Before you can delete a practice run configuration for a resource., you must disable zonal autoshift for the resource. Practice runs must be configured for zonal autoshift to be enabled.

Request Syntax

```
DELETE /configuration/resourceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The identifier for the resource that you want to delete the practice run configuration for. The identifier is the Amazon Resource Name (ARN) for the resource.

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "name": "string",
  "zonalAutoshiftStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource that you deleted the practice run for.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: `arn:.*`

name

The name of the resource that you deleted the practice run for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

zonalAutoshiftStatus

The status of zonal autoshift for the resource.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAutoshiftObserverNotificationStatus

Returns the status of the autoshift observer notification. Autoshift observer notifications notify you through Amazon EventBridge when there is an autoshift event for zonal autoshift. The status can be ENABLED or DISABLED. When ENABLED, a notification is sent when an autoshift is triggered. When DISABLED, notifications are not sent.

Request Syntax

```
GET /autoshift-observer-notification HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

The status of autoshift observer notification. If the status is ENABLED, ARC includes all autoshift events when you use the Amazon EventBridge pattern Autoshift In Progress. When the

status is DISABLED, ARC includes only autoshift events for autoshifts when one or more of your resources is included in the autoshift.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedResource

Get information about a resource that's been registered for zonal shifts with Amazon Application Recovery Controller in this AWS Region. Resources that are registered for zonal shifts are managed resources in ARC. You can start zonal shifts and configure zonal autoshift for managed resources.

Request Syntax

```
GET /managedresources/resourceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The identifier for the resource that AWS shifts traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "appliedWeights": {
    "string" : number
  },
  "arn": "string",
  "autoshifts": [
    {
      "appliedStatus": "string",
      "awayFrom": "string",
      "startTime": number
    }
  ],
  "name": "string",
  "practiceRunConfiguration": {
    "allowedWindows": [ "string" ],
    "blockedDates": [ "string" ],
    "blockedWindows": [ "string" ],
    "blockingAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ],
    "outcomeAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ]
  },
  "zonalAutoshiftStatus": "string",
  "zonalShifts": [
    {
      "appliedStatus": "string",
      "awayFrom": "string",
      "comment": "string",
      "expiryTime": number,
      "practiceRunOutcome": "string",
      "resourceIdentifier": "string",
      "shiftType": "string",
      "startTime": number,
      "zonalShiftId": "string"
    }
  ]
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

appliedWeights

A collection of key-value pairs that indicate whether resources are active in Availability Zones or not. The key name is the Availability Zone where the resource is deployed. The value is 1 or 0.

Type: String to float map

Key Length Constraints: Minimum length of 0. Maximum length of 20.

Valid Range: Minimum value of 0.0. Maximum value of 1.0.

arn

The Amazon Resource Name (ARN) for the resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: `arn:.*`

autoshifts

An array of the autoshifts that are active for the resource.

Type: Array of [AutoshiftInResource](#) objects

name

The name of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

practiceRunConfiguration

The practice run configuration for zonal autoshift that's associated with the resource.

Type: [PracticeRunConfiguration](#) object

[zonalAutoshiftStatus](#)

The status for zonal autoshift for a resource. When the autoshift status is ENABLED, AWS shifts traffic for a resource away from an Availability Zone, on your behalf, when AWS determines that there's an issue in the Availability Zone that could potentially affect customers.

Type: String

Valid Values: ENABLED | DISABLED

[zonalShifts](#)

The zonal shifts that are currently active for a resource.

Type: Array of [ZonalShiftInResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAutoshifts

Returns the autoshifts for an AWS Region. By default, the call returns only ACTIVE autoshifts. Optionally, you can specify the status parameter to return COMPLETED autoshifts.

Request Syntax

```
GET /autoshifts?maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The number of objects that you want to return with this call.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a nextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's nextToken response to request the next page of results.

status

The status of the autoshift.

Valid Values: ACTIVE | COMPLETED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "items": [
    {
      "awayFrom": "string",
      "endTime": number,
      "startTime": number,
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

The items in the response list.

Type: Array of [AutoshiftSummary](#) objects

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a nextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's nextToken response to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedResources

Lists all the resources in your AWS account in this AWS Region that are managed for zonal shifts in Amazon Application Recovery Controller, and information about them. The information includes the zonal autoshift status for the resource, as well as the Amazon Resource Name (ARN), the Availability Zones that each resource is deployed in, and the resource name.

Request Syntax

```
GET /managedresources?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The number of objects that you want to return with this call.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a `nextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `nextToken` response to request the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
```

```

    "appliedWeights": {
      "string" : number
    },
    "arn": "string",
    "autoshifts": [
      {
        "appliedStatus": "string",
        "awayFrom": "string",
        "startTime": number
      }
    ],
    "availabilityZones": [ "string" ],
    "name": "string",
    "practiceRunStatus": "string",
    "zonalAutoshiftStatus": "string",
    "zonalShifts": [
      {
        "appliedStatus": "string",
        "awayFrom": "string",
        "comment": "string",
        "expiryTime": number,
        "practiceRunOutcome": "string",
        "resourceIdentifier": "string",
        "shiftType": "string",
        "startTime": number,
        "zonalShiftId": "string"
      }
    ]
  },
  "nextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

The items in the response list.

Type: Array of [ManagedResourceSummary](#) objects

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a nextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's nextToken response to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListZonalShifts

By default, lists only active zonal shifts in Amazon Application Recovery Controller in your AWS account in this AWS Region. To list historical zonal shifts, specify `--status CANCELED` or `--status EXPIRED`. Most practice runs have a status of EXPIRED. `ListZonalShifts` returns customer-initiated zonal shifts, as well as practice run zonal shifts that ARC started on your behalf for zonal autoshift.

For more information about listing autoshifts, see [ListAutoshifts](#).

Request Syntax

```
GET /zonalshifts?
maxResults=maxResults&nextToken=nextToken&resourceIdentifier=resourceIdentifier&status=status
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The number of objects that you want to return with this call.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a `nextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `nextToken` response to request the next page of results.

[resourceIdentifier](#)

The identifier for the resource that you want to list zonal shifts for. The identifier is the Amazon Resource Name (ARN) for the resource.

Length Constraints: Minimum length of 8. Maximum length of 1024.

[status](#)

A status for a zonal shift.

The Status for a zonal shift can have one of the following values:

- **ACTIVE:** The zonal shift has been started and is active.
- **EXPIRED:** The zonal shift has expired (the expiry time was exceeded).
- **CANCELED:** The zonal shift was canceled.

Valid Values: ACTIVE | EXPIRED | CANCELED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "awayFrom": "string",
      "comment": "string",
      "expiryTime": number,
      "practiceRunOutcome": "string",
      "resourceIdentifier": "string",
      "shiftType": "string",
      "startTime": number,
      "status": "string",
      "zonalShiftId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

The items in the response list.

Type: Array of [ZonalShiftSummary](#) objects

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a nextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's nextToken response to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartPracticeRun

Start an on-demand practice run zonal shift in Amazon Application Recovery Controller. With zonal autoshift enabled, you can start an on-demand practice run to verify preparedness at any time. AWS also runs automated practice runs about weekly when you have enabled zonal autoshift.

For more information, see [Considerations when you configure zonal autoshift](#) in the Amazon Application Recovery Controller Developer Guide.

Request Syntax

```
POST /practiceruns HTTP/1.1
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "resourceIdentifier": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[awayFrom](#)

The Availability Zone (for example, use1-az1) that traffic is shifted away from for the resource that you specify for the practice run.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

[comment](#)

The initial comment that you enter about the practice run. Be aware that this comment can be overwritten by AWS if the automatic check for balanced capacity fails. For more information,

see [Capacity checks for practice runs](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: Yes

resourceIdentifier

The identifier for the resource that you want to start a practice run zonal shift for. The identifier is the Amazon Resource Name (ARN) for the resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiryTime": number,
  "resourceIdentifier": "string",
  "startTime": number,
  "status": "string",
  "zonalShiftId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

awayFrom

The Availability Zone (for example, use1-az1) that traffic is shifted away from for the resource that you specify for the practice run.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

comment

The initial comment that you enter about the practice run. Be aware that this comment can be overwritten by AWS if the automatic check for balanced capacity fails. For more information, see [Capacity checks for practice runs](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

expiryTime

The expiry time (expiration time) for an on-demand practice run zonal shift is 30 minutes from the time when you start the practice run, unless you cancel it before that time. However, be aware that the `expiryTime` field for practice run zonal shifts always has a value of 1 minute.

Type: Timestamp

resourceIdentifier

The identifier for the resource that you want to shift traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

status

A status for the practice run (expected status is **ACTIVE**).

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

zonalShiftId

The identifier of a practice run zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartZonalShift

You start a zonal shift to temporarily move load balancer traffic away from an Availability Zone in an AWS Region, to help your application recover immediately, for example, from a developer's bad code deployment or from an AWS infrastructure failure in a single Availability Zone. You can start a zonal shift in ARC only for managed resources in your AWS account in an AWS Region. Resources are automatically registered with ARC by AWS services.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

When you start a zonal shift, traffic for the resource is no longer routed to the Availability Zone. The zonal shift is created immediately in ARC. However, it can take a short time, typically up to a few minutes, for existing, in-progress connections in the Availability Zone to complete.

For more information, see [Zonal shift](#) in the Amazon Application Recovery Controller Developer Guide.

Request Syntax

```
POST /zonalshifts HTTP/1.1
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiresIn": "string",
  "resourceIdentifier": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

awayFrom

The Availability Zone (for example, use1-az1) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

comment

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. A new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: Yes

expiresIn

The length of time that you want a zonal shift to be active, which ARC converts to an expiry time (expiration time). Zonal shifts are temporary. You can set a zonal shift to be active initially for up to three days (72 hours).

If you want to still keep traffic away from an Availability Zone, you can update the zonal shift and set a new expiration. You can also cancel a zonal shift, before it expires, for example, if you're ready to restore traffic to the Availability Zone.

To set a length of time for a zonal shift to be active, specify a whole number, and then one of the following, with no space:

- **A lowercase letter m:** To specify that the value is in minutes.
- **A lowercase letter h:** To specify that the value is in hours.

For example: 20h means the zonal shift expires in 20 hours. 120m means the zonal shift expires in 120 minutes (2 hours).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Pattern: (`[1-9][0-9]*`)(m|h)

Required: Yes

resourceIdentifier

The identifier for the resource that AWS shifts traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiryTime": number,
  "resourceIdentifier": "string",
  "startTime": number,
```

```
"status": "string",  
"zonalShiftId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[awayFrom](#)

The Availability Zone (for example, use1-az1) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

[comment](#)

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. A new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

[expiryTime](#)

The expiry time (expiration time) for a customer-initiated zonal shift. A zonal shift is temporary and must be set to expire when you start the zonal shift. You can initially set a zonal shift to expire in a maximum of three days (72 hours). However, you can update a zonal shift to set a new expiration at any time.

When you start a zonal shift, you specify how long you want it to be active, which ARC converts to an expiry time (expiration time). You can cancel a zonal shift when you're ready to restore traffic to the Availability Zone, or just wait for it to expire. Or you can update the zonal shift to specify another length of time to expire in.

Type: Timestamp

resourceIdentifier

The identifier for the resource that AWS shifts traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

status

A status for a zonal shift.

The Status for a zonal shift can have one of the following values:

- **ACTIVE:** The zonal shift has been started and is active.
- **EXPIRED:** The zonal shift has expired (the expiry time was exceeded).
- **CANCELED:** The zonal shift was canceled.

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

zonalShiftId

The identifier of a zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAutoshiftObserverNotificationStatus

Update the status of autoshift observer notification. Autoshift observer notification enables you to be notified, through Amazon EventBridge, when there is an autoshift event for zonal autoshift.

If the status is `ENABLED`, ARC includes all autoshift events when you use the EventBridge pattern `Autoshift In Progress`. When the status is `DISABLED`, ARC includes only autoshift events for autoshifts when one or more of your resources is included in the autoshift.

For more information, see [Notifications for practice runs and autoshifts](#) in the Amazon Application Recovery Controller Developer Guide.

Request Syntax

```
PUT /autoshift-observer-notification HTTP/1.1
Content-type: application/json

{
  "status": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

status

The status to set for autoshift observer notification. If the status is `ENABLED`, ARC includes all autoshift events when you use the Amazon EventBridge pattern `Autoshift In Progress`. When the status is `DISABLED`, ARC includes only autoshift events for autoshifts when one or more of your resources is included in the autoshift.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

The status for autoshift observer notification.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePracticeRunConfiguration

Update a practice run configuration to change one or more of the following: add, change, or remove the blocking alarm; change the outcome alarm; or add, change, or remove blocking dates or time windows.

Request Syntax

```
PATCH /configuration/resourceIdentifier HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "allowedWindows": [ "string" ],
  "blockedDates": [ "string" ],
  "blockedWindows": [ "string" ],
  "blockingAlarms": [
    {
      "alarmIdentifier": "string",
      "type": "string"
    }
  ],
  "outcomeAlarms": [
    {
      "alarmIdentifier": "string",
      "type": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The identifier for the resource that you want to update the practice run configuration for. The identifier is the Amazon Resource Name (ARN) for the resource.

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Request Body

The request accepts the following data in JSON format.

allowedWindows

Add, change, or remove windows of days and times for when you can, optionally, allow ARC to start a practice run for a resource.

The format for allowed windows is: DAY:HH:SS-DAY:HH:SS. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Also, be aware of potential time adjustments that might be required for daylight saving time differences. Separate multiple allowed windows with spaces.

For example, say you want to allow practice runs only on Wednesdays and Fridays from noon to 5 p.m. For this scenario, you could set the following recurring days and times as allowed windows, for example: `Wed-12:00-Wed:17:00 Fri-12:00-Fri:17:00`.

Important

The allowedWindows have to start and end on the same day. Windows that span multiple days aren't supported.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: `(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}`

Required: No

blockedDates

Add, change, or remove blocked dates for a practice run in zonal autoshift.

Optionally, you can block practice runs for specific calendar dates. The format for blocked dates is: YYYY-MM-DD. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Separate multiple blocked dates with spaces.

For example, if you have an application update scheduled to launch on May 1, 2024, and you don't want practice runs to shift traffic away at that time, you could set a blocked date for 2024-05-01.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 10.

Pattern: `[0-9]{4}-[0-9]{2}-[0-9]{2}`

Required: No

blockedWindows

Add, change, or remove windows of days and times for when you can, optionally, block ARC from starting a practice run for a resource.

The format for blocked windows is: DAY:HH:SS-DAY:HH:SS. Keep in mind, when you specify dates, that dates and times for practice runs are in UTC. Also, be aware of potential time adjustments that might be required for daylight saving time differences. Separate multiple blocked windows with spaces.

For example, say you run business report summaries three days a week. For this scenario, you might set the following recurring days and times as blocked windows, for example: MON-20:30-21:30 WED-20:30-21:30 FRI-20:30-21:30.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: `(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}`

Required: No

blockingAlarms

Add, change, or remove the Amazon CloudWatch alarms that you optionally specify as the blocking alarms for practice runs.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

[outcomeAlarms](#)

Specify one or more Amazon CloudWatch alarms as the outcome alarms for practice runs.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "name": "string",
  "practiceRunConfiguration": {
    "allowedWindows": [ "string" ],
    "blockedDates": [ "string" ],
    "blockedWindows": [ "string" ],
    "blockingAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ],
    "outcomeAlarms": [
      {
        "alarmIdentifier": "string",
        "type": "string"
      }
    ]
  },
  "zonalAutoshiftStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource that you updated the practice run for.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: arn:.*

name

The name of the resource that you updated the practice run for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

practiceRunConfiguration

The practice run configuration that was updated.

Type: [PracticeRunConfiguration](#) object

zonalAutoshiftStatus

The zonal autoshift status for the resource that you updated the practice run for.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateZonalAutoshiftConfiguration

The zonal autoshift configuration for a resource includes the practice run configuration and the status for running autoshifts, zonal autoshift status. When a resource has a practice run configuration, ARC starts weekly zonal shifts for the resource, to shift traffic away from an Availability Zone. Weekly practice runs help you to make sure that your application can continue to operate normally with the loss of one Availability Zone.

You can update the zonal autoshift status to enable or disable zonal autoshift. When zonal autoshift is ENABLED, you authorize AWS to shift away resource traffic for an application from an Availability Zone during events, on your behalf, to help reduce time to recovery. Traffic is also shifted away for the required weekly practice runs.

Request Syntax

```
PUT /managedresources/resourceIdentifier HTTP/1.1
Content-type: application/json

{
  "zonalAutoshiftStatus": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The identifier for the resource that you want to update the zonal autoshift configuration for. The identifier is the Amazon Resource Name (ARN) for the resource.

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

Request Body

The request accepts the following data in JSON format.

zonalAutoshiftStatus

The zonal autoshift status for the resource that you want to update the zonal autoshift configuration for. Choose ENABLED to authorize AWS to shift away resource traffic for an application from an Availability Zone during events, on your behalf, to help reduce time to recovery.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "resourceIdentifier": "string",
  "zonalAutoshiftStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resourceIdentifier

The identifier for the resource that you updated the zonal autoshift configuration for. The identifier is the Amazon Resource Name (ARN) for the resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

zonalAutoshiftStatus

The updated zonal autoshift status for the resource.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerError

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateZonalShift

Update an active zonal shift in Amazon Application Recovery Controller in your AWS account. You can update a zonal shift to set a new expiration, or edit or replace the comment for the zonal shift.

Request Syntax

```
PATCH /zonalshifts/zonalShiftId HTTP/1.1  
Content-type: application/json
```

```
{  
  "comment": "string",  
  "expiresIn": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

zonalShiftId

The identifier of a zonal shift.

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

comment

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. A new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

expiresIn

The length of time that you want a zonal shift to be active, which ARC converts to an expiry time (expiration time). Zonal shifts are temporary. You can set a zonal shift to be active initially for up to three days (72 hours).

If you want to still keep traffic away from an Availability Zone, you can update the zonal shift and set a new expiration. You can also cancel a zonal shift, before it expires, for example, if you're ready to restore traffic to the Availability Zone.

To set a length of time for a zonal shift to be active, specify a whole number, and then one of the following, with no space:

- **A lowercase letter m:** To specify that the value is in minutes.
- **A lowercase letter h:** To specify that the value is in hours.

For example: 20h means the zonal shift expires in 20 hours. 120m means the zonal shift expires in 120 minutes (2 hours).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Pattern: ([1-9][0-9]*) (m|h)

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "awayFrom": "string",
  "comment": "string",
  "expiryTime": number,
  "resourceIdentifier": "string",
  "startTime": number,
```

```
"status": "string",  
"zonalShiftId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[awayFrom](#)

The Availability Zone (for example, use1-az1) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

[comment](#)

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. A new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

[expiryTime](#)

The expiry time (expiration time) for a customer-initiated zonal shift. A zonal shift is temporary and must be set to expire when you start the zonal shift. You can initially set a zonal shift to expire in a maximum of three days (72 hours). However, you can update a zonal shift to set a new expiration at any time.

When you start a zonal shift, you specify how long you want it to be active, which ARC converts to an expiry time (expiration time). You can cancel a zonal shift when you're ready to restore traffic to the Availability Zone, or just wait for it to expire. Or you can update the zonal shift to specify another length of time to expire in.

Type: Timestamp

resourceIdentifier

The identifier for the resource that AWS shifts traffic for. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

status

A status for a zonal shift.

The Status for a zonal shift can have one of the following values:

- **ACTIVE:** The zonal shift has been started and is active.
- **EXPIRED:** The zonal shift has expired (the expiry time was exceeded).
- **CANCELED:** The zonal shift was canceled.

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

zonalShiftId

The identifier of a zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be processed because of conflict in the current state of the resource.

reason

The reason for the conflict exception.

zonalShiftId

The zonal shift ID associated with the conflict exception.

HTTP Status Code: 409

InternalServerErrorException

There was an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The input requested a resource that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

reason

The reason for the validation exception.

HTTP Status Code: 400


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The ARC - Zonal Shift API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AutoshiftInResource](#)
- [AutoshiftSummary](#)
- [ControlCondition](#)
- [ManagedResourceSummary](#)
- [PracticeRunConfiguration](#)
- [ZonalShiftInResource](#)
- [ZonalShiftSummary](#)

AutoshiftInResource

A complex structure that lists an autoshift that is currently active for a managed resource and information about the autoshift.

For more information, see [How zonal autoshift and practice runs work](#) in the Amazon Application Recovery Controller Developer Guide.

Contents

appliedStatus

The `appliedStatus` field specifies which application traffic shift is in effect for a resource when there is more than one active traffic shift. There can be more than one application traffic shift in progress at the same time - that is, practice run zonal shifts, customer-initiated zonal shifts, or an autoshift. The `appliedStatus` field for a shift that is in progress for a resource can have one of two values: `APPLIED` or `NOT_APPLIED`. The zonal shift or autoshift that is currently in effect for the resource has an `appliedStatus` set to `APPLIED`.

The overall principle for precedence is that zonal shifts that you start as a customer take precedence autoshifts, which take precedence over practice runs. That is, customer-initiated zonal shifts > autoshifts > practice run zonal shifts.

For more information, see [How zonal autoshift and practice runs work](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Valid Values: `APPLIED` | `NOT_APPLIED`

Required: Yes

awayFrom

The Availability Zone (for example, `use1-az1`) that traffic is shifted away from for a resource, when AWS starts an autoshift. Until the autoshift ends, traffic for the resource is instead directed to other Availability Zones in the AWS Region. An autoshift can end for a resource, for example, when AWS ends the autoshift for the Availability Zone or when you disable zonal autoshift for the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

startTime

The time (UTC) when the autoshift started.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoshiftSummary

Information about an autoshift. AWS starts an autoshift to temporarily move traffic for a resource away from an Availability Zone in an AWS Region when AWS determines that there's an issue in the Availability Zone that could potentially affect customers. You can configure zonal autoshift in ARC for managed resources in your AWS account in a Region. Supported AWS resources are automatically registered with ARC.

Autoshifts are temporary. When the Availability Zone recovers, AWS ends the autoshift, and traffic for the resource is no longer directed to the other Availability Zones in the Region.

You can stop an autoshift for a resource by disabling zonal autoshift.

Contents

awayFrom

The Availability Zone (for example, use1-az1) that traffic is shifted away from for a resource when AWS starts an autoshift. Until the autoshift ends, traffic for the resource is instead directed to other Availability Zones in the AWS Region. An autoshift can end for a resource, for example, when AWS ends the autoshift for the Availability Zone or when you disable zonal autoshift for the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

startTime

The time (in UTC) when the autoshift started.

Type: Timestamp

Required: Yes

status

The status for an autoshift.

Type: String

Valid Values: ACTIVE | COMPLETED

Required: Yes

endTime

The time (in UTC) when the autoshift ended.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ControlCondition

A control condition is an alarm that you specify for a practice run. When you configure practice runs with zonal autoshift for a resource, you specify Amazon CloudWatch alarms, which you create in CloudWatch to use with the practice run. The alarms that you specify are an *outcome alarm*, to monitor application health during practice runs and, optionally, a *blocking alarm*, to block practice runs from starting or to interrupt a practice run in progress.

Control condition alarms do not apply for autoshifts.

For more information, see [Considerations when you configure zonal autoshift](#) in the Amazon Application Recovery Controller Developer Guide.

Contents

alarmIdentifier

The Amazon Resource Name (ARN) for an Amazon CloudWatch alarm that you specify as a control condition for a practice run.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: .*

Required: Yes

type

The type of alarm specified for a practice run. You can only specify Amazon CloudWatch alarms for practice runs, so the only valid value is CLOUDWATCH.

Type: String

Valid Values: CLOUDWATCH

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedResourceSummary

A complex structure for a managed resource in an AWS account with information about zonal shifts and autoshifts.

You can start a zonal shift in ARC for a managed resource to temporarily move traffic for the resource away from an Availability Zone in an AWS Region. You can also configure zonal autoshift for a managed resource.

Note

At this time, managed resources are Amazon EC2 Auto Scaling groups, Amazon Elastic Kubernetes Service, Network Load Balancers, and Application Load Balancer.

Contents

availabilityZones

The Availability Zones that a resource is deployed in.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

appliedWeights

A collection of key-value pairs that indicate whether resources are active in Availability Zones or not. The key name is the Availability Zone where the resource is deployed. The value is 1 or 0.

Type: String to float map

Key Length Constraints: Minimum length of 0. Maximum length of 20.

Valid Range: Minimum value of 0.0. Maximum value of 1.0.

Required: No

arn

The Amazon Resource Name (ARN) for the managed resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: arn:.*

Required: No

autoshifts

An array of the autoshifts that have been completed for a resource.

Type: Array of [AutoshiftInResource](#) objects

Required: No

name

The name of the managed resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

practiceRunStatus

This status tracks whether a practice run configuration exists for a resource. When you configure a practice run for a resource so that a practice run configuration exists, ARC sets this value to ENABLED. If you have not configured a practice run for the resource, or delete a practice run configuration, ARC sets the value to DISABLED.

ARC updates this status; you can't set a practice run status to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

zonalAutoshiftStatus

The status of autoshift for a resource. When you configure zonal autoshift for a resource, you can set the value of the status to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

zonalShifts

An array of the zonal shifts for a resource.

Type: Array of [ZonalShiftInResource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PracticeRunConfiguration

A practice run configuration for a resource includes the Amazon CloudWatch alarms that you've specified for a practice run, as well as any blocked dates or blocked windows for the practice run. When a resource has a practice run configuration, ARC shifts traffic for the resource weekly for practice runs.

Practice runs are required for zonal autoshift. The zonal shifts that ARC starts for practice runs help you to ensure that shifting away traffic from an Availability Zone during an autoshift is safe for your application.

You can update or delete a practice run configuration. Before you delete a practice run configuration, you must disable zonal autoshift for the resource. A practice run configuration is required when zonal autoshift is enabled.

Contents

outcomeAlarms

Outcome alarms for practice runs are alarms that you specify that end a practice run when one or more of the alarms is in an ALARM state.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

allowedWindows

An array of one or more windows of days and times that you can allow ARC to start practice runs for a resource.

For example, say you want to allow practice runs only on Wednesdays and Fridays from noon to 5 p.m. For this scenario, you could set the following recurring days and times as allowed windows, for example: `Wed-12:00-Wed:17:00 Fri-12:00-Fri:17:00`.

The `allowedWindows` have to start and end on the same day. Windows that span multiple days aren't supported.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: (Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}

Required: No

blockedDates

An array of one or more dates that you can specify when AWS does not start practice runs for a resource.

Specify blocked dates, in UTC, in the format YYYY-MM-DD, separated by spaces.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 10.

Pattern: [0-9]{4}-[0-9]{2}-[0-9]{2}

Required: No

blockedWindows

An array of one or more windows of days and times that you can block ARC from starting practice runs for a resource.

Specify the blocked windows in UTC, using the format DAY:HH:MM-DAY:HH:MM, separated by spaces. For example, MON:18:30-MON:19:30 TUE:18:30-TUE:19:30.

The `blockedWindows` have to start and end on the same day. Windows that span multiple days aren't supported.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 15 items.

Length Constraints: Fixed length of 19.

Pattern: (Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}-(Mon|Tue|Wed|Thu|Fri|Sat|Sun):[0-9]{2}:[0-9]{2}

Required: No

blockingAlarms

Blocking alarms for practice runs are optional alarms that you can specify that block practice runs when one or more of the alarms is in an ALARM state.

Type: Array of [ControlCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ZonalShiftInResource

A complex structure that lists the zonal shifts for a managed resource and their statuses for the resource.

Contents

appliedStatus

The `appliedStatus` field specifies which application traffic shift is in effect for a resource when there is more than one active traffic shift. There can be more than one application traffic shift in progress at the same time - that is, practice run zonal shifts, customer-initiated zonal shifts, or an autoshift. The `appliedStatus` field for a shift that is in progress for a resource can have one of two values: `APPLIED` or `NOT_APPLIED`. The zonal shift or autoshift that is currently in effect for the resource has an `appliedStatus` set to `APPLIED`.

The overall principle for precedence is that zonal shifts that you start as a customer take precedence autoshifts, which take precedence over practice runs. That is, customer-initiated zonal shifts > autoshifts > practice run zonal shifts.

For more information, see [How zonal autoshift and practice runs work](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Valid Values: `APPLIED` | `NOT_APPLIED`

Required: Yes

awayFrom

The Availability Zone (for example, `use1-az1`) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

comment

A comment that you enter for a customer-initiated zonal shift. Only the latest comment is retained; no comment history is maintained. That is, a new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: Yes

expiryTime

The expiry time (expiration time) for a customer-initiated zonal shift. A zonal shift is temporary and must be set to expire when you start the zonal shift. You can initially set a zonal shift to expire in a maximum of three days (72 hours). However, you can update a zonal shift to set a new expiration at any time.

When you start a zonal shift, you specify how long you want it to be active, which ARC converts to an expiry time (expiration time). You can cancel a zonal shift when you're ready to restore traffic to the Availability Zone, or just wait for it to expire. Or you can update the zonal shift to specify another length of time to expire in.

Type: Timestamp

Required: Yes

resourceIdentifier

The identifier for the resource to include in a zonal shift. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancer](#)
- [Network Load Balancer](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

Required: Yes

zonalShiftId

The identifier of a zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Required: Yes

practiceRunOutcome

The outcome, or end state, returned for a practice run. The following values can be returned:

- **PENDING:** Outcome value when a practice run is in progress.
- **SUCCEEDED:** Outcome value when the outcome alarm specified for the practice run configuration does not go into an ALARM state during the practice run, and the practice run was not interrupted before it completed the expected 30 minute zonal shift.
- **INTERRUPTED:** Outcome value when the practice run was stopped before the expected 30 minute zonal shift duration, or there was another problem with the practice run that created an inconclusive outcome.
- **FAILED:** Outcome value when the outcome alarm specified for the practice run configuration goes into an ALARM state during the practice run, and the practice run was not interrupted before it completed.
- **CAPACITY_CHECK_FAILED:** The check for balanced capacity across Availability Zones for your load balancing and Auto Scaling group resources failed.

For more information about practice run outcomes, see [Considerations when you configure zonal autoshift](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Valid Values: FAILED | INTERRUPTED | PENDING | SUCCEEDED |
CAPACITY_CHECK_FAILED

Required: No

shiftType

Defines the zonal shift type.

Type: String

Valid Values: ZONAL_SHIFT | PRACTICE_RUN | FIS_EXPERIMENT | ZONAL_AUTOSHIFT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ZonalShiftSummary

Lists information about zonal shifts in Amazon Application Recovery Controller, including zonal shifts that you start yourself and zonal shifts that ARC starts on your behalf for practice runs with zonal autoshift.

Zonal shifts are temporary, including customer-initiated zonal shifts and the zonal autoshift practice run zonal shifts that ARC starts weekly, on your behalf. A zonal shift that a customer starts can be active for up to three days (72 hours). A practice run zonal shift has a 30 minute duration.

Contents

awayFrom

The Availability Zone (for example, use1-az1) that traffic is moved away from for a resource when you start a zonal shift. Until the zonal shift expires or you cancel it, traffic for the resource is instead moved to other Availability Zones in the AWS Region.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: Yes

comment

A comment that you enter about the zonal shift. Only the latest comment is retained; no comment history is maintained. That is, a new comment overwrites any existing comment string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: Yes

expiryTime

The expiry time (expiration time) for a customer-initiated zonal shift. A zonal shift is temporary and must be set to expire when you start the zonal shift. You can initially set a zonal shift to expire in a maximum of three days (72 hours). However, you can update a zonal shift to set a new expiration at any time.

When you start a zonal shift, you specify how long you want it to be active, which ARC converts to an expiry time (expiration time). You can cancel a zonal shift when you're ready to restore traffic to the Availability Zone, or just wait for it to expire. Or you can update the zonal shift to specify another length of time to expire in.

Type: Timestamp

Required: Yes

resourceIdentifier

The identifier for the resource to include in a zonal shift. The identifier is the Amazon Resource Name (ARN) for the resource.

Amazon Application Recovery Controller currently supports enabling the following resources for zonal shift and zonal autoshift:

- [Amazon EC2 Auto Scaling groups](#)
- [Amazon Elastic Kubernetes Service](#)
- [Application Load Balancers](#)
- [Network Load Balancers](#)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: Yes

startTime

The time (UTC) when the zonal shift starts.

Type: Timestamp

Required: Yes

status

A status for a zonal shift.

The Status for a zonal shift can have one of the following values:

- **ACTIVE:** The zonal shift has been started and is active.
- **EXPIRED:** The zonal shift has expired (the expiry time was exceeded).

- **CANCELED:** The zonal shift was canceled.

Type: String

Valid Values: ACTIVE | EXPIRED | CANCELED

Required: Yes

zonalShiftId

The identifier of a zonal shift.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 36.

Pattern: [A-Za-z0-9-]+

Required: Yes

practiceRunOutcome

The outcome, or end state, of a practice run. The following values can be returned:

- **PENDING:** Outcome value when the practice run is in progress.
- **SUCCEEDED:** Outcome value when the outcome alarm specified for the practice run configuration does not go into an ALARM state during the practice run, and the practice run was not interrupted before it completed.
- **INTERRUPTED:** Outcome value when the practice run did not run for the expected 30 minutes or there was another problem with the practice run that created an inconclusive outcome.
- **FAILED:** Outcome value when the outcome alarm specified for the practice run configuration goes into an ALARM state during the practice run, and the practice run was not interrupted before it completed.
- **CAPACITY_CHECK_FAILED:** The check for balanced capacity across Availability Zones for your load balancing and Auto Scaling group resources failed.

For more information about practice run outcomes, see [Considerations when you configure zonal autoshift](#) in the Amazon Application Recovery Controller Developer Guide.

Type: String

Valid Values: FAILED | INTERRUPTED | PENDING | SUCCEEDED |
CAPACITY_CHECK_FAILED

Required: No

shiftType

Defines the zonal shift type.

Type: String

Valid Values: ZONAL_SHIFT | PRACTICE_RUN | FIS_EXPERIMENT | ZONAL_AUTOSHIFT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400