



API Reference

# AWS CodeDeploy



**API Version 2014-10-06**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS CodeDeploy: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>3</b>
AddTagsToOnPremisesInstances .....	5
Request Syntax .....	5
Request Parameters .....	5
Response Elements .....	6
Errors .....	6
Examples .....	7
See Also .....	8
BatchGetApplicationRevisions .....	9
Request Syntax .....	9
Request Parameters .....	9
Response Syntax .....	10
Response Elements .....	11
Errors .....	11
Examples .....	12
See Also .....	15
BatchGetApplications .....	16
Request Syntax .....	16
Request Parameters .....	16
Response Syntax .....	16
Response Elements .....	17
Errors .....	17
Examples .....	18
See Also .....	19
BatchGetDeploymentGroups .....	20
Request Syntax .....	20
Request Parameters .....	20
Response Syntax .....	20
Response Elements .....	24
Errors .....	25
Examples .....	26
See Also .....	28
BatchGetDeploymentInstances .....	30

---

Request Syntax .....	30
Request Parameters .....	30
Response Syntax .....	31
Response Elements .....	31
Errors .....	32
Examples .....	33
See Also .....	40
<b>BatchGetDeployments .....</b>	<b>41</b>
Request Syntax .....	41
Request Parameters .....	41
Response Syntax .....	41
Response Elements .....	45
Errors .....	45
Examples .....	46
See Also .....	49
<b>BatchGetDeploymentTargets .....</b>	<b>50</b>
Request Syntax .....	50
Request Parameters .....	50
Response Syntax .....	51
Response Elements .....	54
Errors .....	54
See Also .....	56
<b>BatchGetOnPremisesInstances .....</b>	<b>57</b>
Request Syntax .....	57
Request Parameters .....	57
Response Syntax .....	57
Response Elements .....	58
Errors .....	58
Examples .....	59
See Also .....	60
<b>ContinueDeployment .....</b>	<b>61</b>
Request Syntax .....	61
Request Parameters .....	61
Response Elements .....	62
Errors .....	62
Examples .....	63

---

See Also .....	63
CreateApplication .....	65
Request Syntax .....	65
Request Parameters .....	65
Response Syntax .....	66
Response Elements .....	66
Errors .....	66
Examples .....	67
See Also .....	68
CreateDeployment .....	69
Request Syntax .....	69
Request Parameters .....	70
Response Syntax .....	74
Response Elements .....	74
Errors .....	74
Examples .....	78
See Also .....	79
CreateDeploymentConfig .....	81
Request Syntax .....	81
Request Parameters .....	81
Response Syntax .....	83
Response Elements .....	83
Errors .....	83
Examples .....	84
See Also .....	85
CreateDeploymentGroup .....	87
Request Syntax .....	87
Request Parameters .....	90
Response Syntax .....	94
Response Elements .....	94
Errors .....	95
Examples .....	99
See Also .....	101
DeleteApplication .....	102
Request Syntax .....	102
Request Parameters .....	102

Response Elements .....	102
Errors .....	102
Examples .....	103
See Also .....	104
DeleteDeploymentConfig .....	105
Request Syntax .....	105
Request Parameters .....	105
Response Elements .....	105
Errors .....	105
Examples .....	106
See Also .....	107
DeleteDeploymentGroup .....	108
Request Syntax .....	108
Request Parameters .....	108
Response Syntax .....	108
Response Elements .....	109
Errors .....	109
Examples .....	110
See Also .....	111
DeleteGitHubAccountToken .....	112
Request Syntax .....	112
Request Parameters .....	112
Response Syntax .....	112
Response Elements .....	112
Errors .....	113
See Also .....	113
DeleteResourcesByExternalId .....	115
Request Syntax .....	115
Request Parameters .....	115
Response Elements .....	115
Errors .....	115
See Also .....	116
DeregisterOnPremisesInstance .....	117
Request Syntax .....	117
Request Parameters .....	117
Response Elements .....	117

---

Errors .....	117
Examples .....	118
See Also .....	118
GetApplication .....	120
Request Syntax .....	120
Request Parameters .....	120
Response Syntax .....	120
Response Elements .....	121
Errors .....	121
Examples .....	121
See Also .....	122
GetApplicationRevision .....	124
Request Syntax .....	124
Request Parameters .....	124
Response Syntax .....	125
Response Elements .....	126
Errors .....	126
Examples .....	127
See Also .....	128
GetDeployment .....	130
Request Syntax .....	130
Request Parameters .....	130
Response Syntax .....	130
Response Elements .....	134
Errors .....	134
Examples .....	135
See Also .....	136
GetDeploymentConfig .....	138
Request Syntax .....	138
Request Parameters .....	138
Response Syntax .....	138
Response Elements .....	139
Errors .....	139
Examples .....	140
See Also .....	141
GetDeploymentGroup .....	142

Request Syntax .....	142
Request Parameters .....	142
Response Syntax .....	142
Response Elements .....	146
Errors .....	146
Examples .....	147
See Also .....	149
<b>GetDeploymentInstance</b> .....	<b>150</b>
Request Syntax .....	150
Request Parameters .....	150
Response Syntax .....	150
Response Elements .....	151
Errors .....	151
Examples .....	152
See Also .....	155
<b>GetDeploymentTarget</b> .....	<b>157</b>
Request Syntax .....	157
Request Parameters .....	157
Response Syntax .....	157
Response Elements .....	160
Errors .....	160
See Also .....	161
<b>GetOnPremisesInstance</b> .....	<b>163</b>
Request Syntax .....	163
Request Parameters .....	163
Response Syntax .....	163
Response Elements .....	164
Errors .....	164
Examples .....	164
See Also .....	166
<b>ListApplicationRevisions</b> .....	<b>167</b>
Request Syntax .....	167
Request Parameters .....	167
Response Syntax .....	169
Response Elements .....	170
Errors .....	170

---

Examples .....	171
See Also .....	173
ListApplications .....	175
Request Syntax .....	175
Request Parameters .....	175
Response Syntax .....	175
Response Elements .....	175
Errors .....	176
Examples .....	176
See Also .....	177
ListDeploymentConfigs .....	178
Request Syntax .....	178
Request Parameters .....	178
Response Syntax .....	178
Response Elements .....	178
Errors .....	179
Examples .....	179
See Also .....	180
ListDeploymentGroups .....	182
Request Syntax .....	182
Request Parameters .....	182
Response Syntax .....	182
Response Elements .....	183
Errors .....	183
Examples .....	184
See Also .....	185
ListDeploymentInstances .....	186
Request Syntax .....	186
Request Parameters .....	186
Response Syntax .....	187
Response Elements .....	187
Errors .....	188
Examples .....	189
See Also .....	190
ListDeployments .....	192
Request Syntax .....	192

Request Parameters .....	192
Response Syntax .....	194
Response Elements .....	194
Errors .....	195
Examples .....	196
See Also .....	197
ListDeploymentTargets .....	198
Request Syntax .....	198
Request Parameters .....	198
Response Syntax .....	199
Response Elements .....	199
Errors .....	199
See Also .....	201
ListGitHubAccountTokenNames .....	202
Request Syntax .....	202
Request Parameters .....	202
Response Syntax .....	202
Response Elements .....	202
Errors .....	203
See Also .....	203
ListOnPremisesInstances .....	205
Request Syntax .....	205
Request Parameters .....	205
Response Syntax .....	206
Response Elements .....	206
Errors .....	207
Examples .....	207
See Also .....	208
ListTagsForResource .....	209
Request Syntax .....	209
Request Parameters .....	209
Response Syntax .....	209
Response Elements .....	210
Errors .....	210
See Also .....	211
PutLifecycleEventHookExecutionStatus .....	212

---

Request Syntax .....	212
Request Parameters .....	212
Response Syntax .....	213
Response Elements .....	213
Errors .....	213
See Also .....	214
<b>RegisterApplicationRevision .....</b>	<b>216</b>
Request Syntax .....	216
Request Parameters .....	216
Response Elements .....	217
Errors .....	217
Examples .....	218
See Also .....	219
<b>RegisterOnPremisesInstance .....</b>	<b>220</b>
Request Syntax .....	220
Request Parameters .....	220
Response Elements .....	221
Errors .....	221
Examples .....	222
See Also .....	223
<b>RemoveTagsFromOnPremisesInstances .....</b>	<b>224</b>
Request Syntax .....	224
Request Parameters .....	224
Response Elements .....	224
Errors .....	225
Examples .....	226
See Also .....	227
<b>SkipWaitTimeForInstanceTermination .....</b>	<b>228</b>
Request Syntax .....	228
Request Parameters .....	228
Response Elements .....	228
Errors .....	228
Examples .....	229
See Also .....	230
<b>StopDeployment .....</b>	<b>231</b>
Request Syntax .....	231

---

Request Parameters .....	231
Response Syntax .....	231
Response Elements .....	232
Errors .....	232
Examples .....	233
See Also .....	234
TagResource .....	235
Request Syntax .....	235
Request Parameters .....	235
Response Elements .....	236
Errors .....	236
See Also .....	237
UntagResource .....	238
Request Syntax .....	238
Request Parameters .....	238
Response Elements .....	238
Errors .....	239
See Also .....	240
UpdateApplication .....	241
Request Syntax .....	241
Request Parameters .....	241
Response Elements .....	241
Errors .....	242
Examples .....	242
See Also .....	243
UpdateDeploymentGroup .....	244
Request Syntax .....	244
Request Parameters .....	246
Response Syntax .....	251
Response Elements .....	251
Errors .....	251
Examples .....	256
See Also .....	257
<b>Data Types .....</b>	<b>259</b>
Alarm .....	262
Contents .....	262

See Also .....	262
AlarmConfiguration .....	263
Contents .....	263
See Also .....	263
ApplicationInfo .....	265
Contents .....	265
See Also .....	266
AppSpecContent .....	267
Contents .....	267
See Also .....	267
AutoRollbackConfiguration .....	269
Contents .....	269
See Also .....	269
AutoScalingGroup .....	270
Contents .....	270
See Also .....	270
BlueGreenDeploymentConfiguration .....	272
Contents .....	272
See Also .....	272
BlueInstanceTerminationOption .....	274
Contents .....	274
See Also .....	274
CloudFormationTarget .....	276
Contents .....	276
See Also .....	277
DeploymentConfigInfo .....	278
Contents .....	278
See Also .....	279
DeploymentGroupInfo .....	280
Contents .....	280
See Also .....	284
DeploymentInfo .....	286
Contents .....	286
See Also .....	292
DeploymentOverview .....	294
Contents .....	294

See Also .....	295
DeploymentReadyOption .....	296
Contents .....	296
See Also .....	296
DeploymentStyle .....	298
Contents .....	298
See Also .....	298
DeploymentTarget .....	299
Contents .....	299
See Also .....	300
Diagnostics .....	301
Contents .....	301
See Also .....	302
EC2TagFilter .....	303
Contents .....	303
See Also .....	303
EC2TagSet .....	305
Contents .....	305
See Also .....	305
ECSService .....	306
Contents .....	306
See Also .....	306
ECSTarget .....	307
Contents .....	307
See Also .....	308
ECSTaskSet .....	309
Contents .....	309
See Also .....	311
ELBInfo .....	312
Contents .....	312
See Also .....	312
ErrorInformation .....	313
Contents .....	313
See Also .....	314
GenericRevisionInfo .....	315
Contents .....	315

---

See Also .....	316
GitHubLocation .....	317
Contents .....	317
See Also .....	317
GreenFleetProvisioningOption .....	318
Contents .....	318
See Also .....	318
InstanceInfo .....	319
Contents .....	319
See Also .....	320
InstanceSummary .....	321
Contents .....	321
See Also .....	322
InstanceTarget .....	323
Contents .....	323
See Also .....	324
LambdaFunctionInfo .....	325
Contents .....	325
See Also .....	326
LambdaTarget .....	327
Contents .....	327
See Also .....	328
LastDeploymentInfo .....	329
Contents .....	329
See Also .....	330
LifecycleEvent .....	331
Contents .....	331
See Also .....	332
LoadBalancerInfo .....	333
Contents .....	333
See Also .....	334
MinimumHealthyHosts .....	335
Contents .....	335
See Also .....	336
MinimumHealthyHostsPerZone .....	337
Contents .....	337

See Also .....	337
OnPremisesTagSet .....	338
Contents .....	338
See Also .....	338
RawString .....	339
Contents .....	339
See Also .....	339
RelatedDeployments .....	340
Contents .....	340
See Also .....	340
RevisionInfo .....	341
Contents .....	341
See Also .....	341
RevisionLocation .....	342
Contents .....	342
See Also .....	343
RollbackInfo .....	344
Contents .....	344
See Also .....	344
S3Location .....	345
Contents .....	345
See Also .....	346
Tag .....	347
Contents .....	347
See Also .....	347
TagFilter .....	348
Contents .....	348
See Also .....	348
TargetGroupInfo .....	350
Contents .....	350
See Also .....	350
TargetGroupPairInfo .....	351
Contents .....	351
See Also .....	351
TargetInstances .....	353
Contents .....	353

---

See Also .....	353
TimeBasedCanary .....	355
Contents .....	355
See Also .....	355
TimeBasedLinear .....	356
Contents .....	356
See Also .....	356
TimeRange .....	357
Contents .....	357
See Also .....	357
TrafficRoute .....	359
Contents .....	359
See Also .....	359
TrafficRoutingConfig .....	360
Contents .....	360
See Also .....	361
TriggerConfig .....	362
Contents .....	362
See Also .....	362
ZonalConfig .....	364
Contents .....	364
See Also .....	365
<b>Common Parameters .....</b>	<b>366</b>
<b>Common Error Types .....</b>	<b>369</b>

# Welcome

AWS CodeDeploy is a deployment service that automates application deployments to Amazon EC2 instances, on-premises instances running in your own facility, serverless AWS Lambda functions, or applications in an Amazon ECS service.

You can deploy a nearly unlimited variety of application content, such as an updated Lambda function, updated applications in an Amazon ECS service, code, web and configuration files, executables, packages, scripts, multimedia files, and so on. AWS CodeDeploy can deploy application content stored in Amazon S3 buckets, GitHub repositories, or Bitbucket repositories. You do not need to make changes to your existing code before you can use AWS CodeDeploy.

AWS CodeDeploy makes it easier for you to rapidly release new features, helps you avoid downtime during application deployment, and handles the complexity of updating your applications, without many of the risks associated with error-prone manual deployments.

## AWS CodeDeploy Components

Use the information in this guide to help you work with the following AWS CodeDeploy components:

- **Application:** A name that uniquely identifies the application you want to deploy. AWS CodeDeploy uses this name, which functions as a container, to ensure the correct combination of revision, deployment configuration, and deployment group are referenced during a deployment.
- **Deployment group:** A set of individual instances, CodeDeploy Lambda deployment configuration settings, or an Amazon ECS service and network details. A Lambda deployment group specifies how to route traffic to a new version of a Lambda function. An Amazon ECS deployment group specifies the service created in Amazon ECS to deploy, a load balancer, and a listener to reroute production traffic to an updated containerized application. An Amazon EC2/On-premises deployment group contains individually tagged instances, Amazon EC2 instances in Amazon EC2 Auto Scaling groups, or both. All deployment groups can specify optional trigger, alarm, and rollback settings.
- **Deployment configuration:** A set of deployment rules and deployment success and failure conditions used by AWS CodeDeploy during a deployment.
- **Deployment:** The process and the components used when updating a Lambda function, a containerized application in an Amazon ECS service, or of installing content on one or more instances.

- **Application revisions:** For an AWS Lambda deployment, this is an AppSpec file that specifies the Lambda function to be updated and one or more functions to validate deployment lifecycle events. For an Amazon ECS deployment, this is an AppSpec file that specifies the Amazon ECS task definition, container, and port where production traffic is rerouted. For an EC2/On-premises deployment, this is an archive file that contains source content—source code, webpages, executable files, and deployment scripts—along with an AppSpec file. Revisions are stored in Amazon S3 buckets or GitHub repositories. For Amazon S3, a revision is uniquely identified by its Amazon S3 object key and its ETag, version, or both. For GitHub, a revision is uniquely identified by its commit ID.

This guide also contains information to help you get details about the instances in your deployments, to make on-premises instances available for AWS CodeDeploy deployments, to get details about a Lambda function deployment, and to get details about Amazon ECS service deployments.

### **AWS CodeDeploy Information Resources**

- [AWS CodeDeploy User Guide](#)
- [AWS CodeDeploy API Reference Guide](#)
- [AWS CLI Reference for AWS CodeDeploy](#)
- [AWS CodeDeploy Developer Forum](#)

This document was last published on April 10, 2026.

# Actions

The following actions are supported:

- [AddTagsToOnPremisesInstances](#)
- [BatchGetApplicationRevisions](#)
- [BatchGetApplications](#)
- [BatchGetDeploymentGroups](#)
- [BatchGetDeploymentInstances](#)
- [BatchGetDeployments](#)
- [BatchGetDeploymentTargets](#)
- [BatchGetOnPremisesInstances](#)
- [ContinueDeployment](#)
- [CreateApplication](#)
- [CreateDeployment](#)
- [CreateDeploymentConfig](#)
- [CreateDeploymentGroup](#)
- [DeleteApplication](#)
- [DeleteDeploymentConfig](#)
- [DeleteDeploymentGroup](#)
- [DeleteGitHubAccountToken](#)
- [DeleteResourcesByExternalId](#)
- [DeregisterOnPremisesInstance](#)
- [GetApplication](#)
- [GetApplicationRevision](#)
- [GetDeployment](#)
- [GetDeploymentConfig](#)
- [GetDeploymentGroup](#)
- [GetDeploymentInstance](#)
- [GetDeploymentTarget](#)
- [GetOnPremisesInstance](#)

- [ListApplicationRevisions](#)
- [ListApplications](#)
- [ListDeploymentConfigs](#)
- [ListDeploymentGroups](#)
- [ListDeploymentInstances](#)
- [ListDeployments](#)
- [ListDeploymentTargets](#)
- [ListGitHubAccountTokenNames](#)
- [ListOnPremisesInstances](#)
- [ListTagsForResource](#)
- [PutLifecycleEventHookExecutionStatus](#)
- [RegisterApplicationRevision](#)
- [RegisterOnPremisesInstance](#)
- [RemoveTagsFromOnPremisesInstances](#)
- [SkipWaitTimeForInstanceTermination](#)
- [StopDeployment](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateApplication](#)
- [UpdateDeploymentGroup](#)

# AddTagsToOnPremisesInstances

Adds tags to on-premises instances.

## Request Syntax

```
{
  "instanceNames": [ "string" ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### instanceNames

The names of the on-premises instances to which to add tags.

Type: Array of strings

Required: Yes

### tags

The tag key-value pairs to add to the on-premises instances.

Keys and values are both required. Keys cannot be null or empty strings. Value-only tags are not allowed.

Type: Array of [Tag](#) objects

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InstanceLimitExceededException**

The maximum number of allowed on-premises instances in a single call was exceeded.

HTTP Status Code: 400

### **InstanceNameRequiredException**

An on-premises instance name was not specified.

HTTP Status Code: 400

### **InstanceNotRegisteredException**

The specified on-premises instance is not registered.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

### **TagLimitExceededException**

The maximum allowed number of tags was exceeded.

HTTP Status Code: 400

### **TagRequiredException**

A tag was not specified.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `AddTagsToOnPremisesInstances`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 105
X-Amz-Target: CodeDeploy_20141006.AddTagsToOnPremisesInstances
X-Amz-Date: 20160707T225742Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceNames": [
    "grp-b-inst-2",
    "grp-b-inst-1"
  ],
  "tags": [
    {
      "Key": "Name",
      "Value": "Cost-Center-456"
    }
  ]
}
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetApplicationRevisions

Gets information about one or more application revisions. The maximum number of application revisions that can be returned is 25.

## Request Syntax

```
{
  "applicationName": "string",
  "revisions": [
    {
      "appSpecContent": {
        "content": "string",
        "sha256": "string"
      },
      "gitHubLocation": {
        "commitId": "string",
        "repository": "string"
      },
      "revisionType": "string",
      "s3Location": {
        "bucket": "string",
        "bundleType": "string",
        "eTag": "string",
        "key": "string",
        "version": "string"
      },
      "string": {
        "content": "string",
        "sha256": "string"
      }
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## applicationName

The name of an AWS CodeDeploy application about which to get revision information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## revisions

An array of RevisionLocation objects that specify information to get about the application revisions, including type and location. The maximum number of RevisionLocation objects you can specify is 25.

Type: Array of [RevisionLocation](#) objects

Required: Yes

## Response Syntax

```
{
  "applicationName": "string",
  "errorMessage": "string",
  "revisions": [
    {
      "genericRevisionInfo": {
        "deploymentGroups": [ "string" ],
        "description": "string",
        "firstUsedTime": number,
        "lastUsedTime": number,
        "registerTime": number
      },
      "revisionLocation": {
        "appSpecContent": {
          "content": "string",
          "sha256": "string"
        },
        "githubLocation": {
          "commitId": "string",
          "repository": "string"
        },
        "revisionType": "string",
```

```
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    },
    "string": {
      "content": "string",
      "sha256": "string"
    }
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationName

The name of the application that corresponds to the revisions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

### errorMessage

Information about errors that might have occurred during the API call.

Type: String

### revisions

Additional information about the revisions, including the type and location.

Type: Array of [RevisionInfo](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## ApplicationDoesNotExistException

The application does not exist with the user or AWS account.

HTTP Status Code: 400

## ApplicationNameRequiredException

The minimum number of required application names was not specified.

HTTP Status Code: 400

## BatchLimitExceededException

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

## InvalidApplicationNameException

The application name was specified in an invalid format.

HTTP Status Code: 400

## InvalidRevisionException

The revision was specified in an invalid format.

HTTP Status Code: 400

## RevisionRequiredException

The revision ID was not specified.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of BatchGetApplicationRevisions.

### Sample Request

```
POST / HTTP/1.1
```

```
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 284
X-Amz-Target: CodeDeploy_20141006.BatchGetApplicationRevisions
X-Amz-Date: 20160707T172627Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE
```

```
{
  "applicationName": "TestApp-us-east-1",
  "revisions": [
    {
      "revisionType": "S3",
      "s3Location": {
        "bundleType": "zip",
        "version": "4eQLXx7nw0iP22hxwt2_YXrUq972qkG6",
        "bucket": "project-123",
        "key": "North-App.zip",
        "eTag": "3fdd7b9196697a096d5af1d649e26a4a"
      }
    },
    {
      "revisionType": "S3",
      "s3Location": {
        "bundleType": "zip",
        "version": "BXrUq974e0iP22hxwt2_QLXx7nw3kjB9",
        "bucket": "project-123",
        "key": "North-App-2.zip",
        "eTag": "4hfhj7b911d649e26a4a45390a096d5af"
      }
    }
  ]
}
```

## Sample Response

```
{
  "applicationName": "TestApp-us-east-1",
  "errorMessage": "",
}
```

```
"revisions": [
  {
    "genericRevisionInfo": {
      "deploymentGroups": [
        "dep-group-def-456"
      ],
      "description": "Application revision registered by Deployment ID: d-
D1EGTDV3C",
      "firstUsedTime": 1446232255.734,
      "lastUsedTime": 1446232255.734,
      "registerTime": 1446232255.734
    },
    "revisionType": "S3",
    "s3Location": {
      "bucket": "project-1234",
      "bundleType": "zip",
      "eTag": "3fdd7b9196697a096d5af1d649e26a4a",
      "key": "North-App.zip",
      "version": "4eQLXx7nw0iP22hxwt2_YXrUq972qkG6"
    }
  },
  {
    "genericRevisionInfo": {
      "deploymentGroups": [
        "dep-group-def-456"
      ],
      "description": "Application revision registered by Deployment ID: d-
F8ROHSIK3K",
      "firstUsedTime": 1455988916.108,
      "lastUsedTime": 1455988916.288,
      "registerTime": 1455988912.217
    },
    "revisionType": "S3",
    "s3Location": {
      "bucket": "project-1234",
      "bundleType": "zip",
      "eTag": "4hfhj7b911d649e26a4a45390a096d5af",
      "key": "North-App-2.zip",
      "version": "BXrUq974e0iP22hxwt2_QLXx7nw3kjB9"
    }
  }
]
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetApplications

Gets information about one or more applications. The maximum number of applications that can be returned is 100.

## Request Syntax

```
{  
  "applicationNames": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationNames

A list of application names separated by spaces. The maximum number of application names you can specify is 100.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{  
  "applicationsInfo": [  
    {  
      "applicationId": "string",  
      "applicationName": "string",  
      "computePlatform": "string",  
      "createTime": number,  
      "gitHubAccountName": "string",  
      "linkedToGitHub": boolean  
    }  
  ]  
}
```

```
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [applicationsInfo](#)

Information about the applications.

Type: Array of [ApplicationInfo](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **BatchLimitExceededException**

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of BatchGetApplications.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 81
X-Amz-Target: CodeDeploy_20141006.BatchGetApplications
X-Amz-Date: 20160707T230945Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationNames": [
    "ProductionApp-us-east-1",
    "ProductionApp-us-west-2"
  ]
}
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 335

{
  "applicationsInfo": [
    {
      "applicationId": "d8347436-bc51-459e-9c44-f98abEXAMPLE",
      "applicationName": "ProductionApp-us-west-2",
      "createTime": 1446136767.311,
      "linkedToGitHub": false
    },
  ],
}
```

```
{
  "applicationId": "1ecfe802-63f1-4038-8f0d-06688EXAMPLE",
  "applicationName": "ProductionApp-us-east-1",
  "createTime": 1439488406.152,
  "linkedToGitHub": false
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetDeploymentGroups

Gets information about one or more deployment groups.

## Request Syntax

```
{
  "applicationName": "string",
  "deploymentGroupNames": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the applicable user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### deploymentGroupNames

The names of the deployment groups.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{
  "deploymentGroupsInfo": [
    {
```

```
"alarmConfiguration": {
  "alarms": [
    {
      "name": "string"
    }
  ],
  "enabled": boolean,
  "ignorePollAlarmFailure": boolean
},
"applicationName": "string",
"autoRollbackConfiguration": {
  "enabled": boolean,
  "events": [ "string" ]
},
"autoScalingGroups": [
  {
    "hook": "string",
    "name": "string",
    "terminationHook": "string"
  }
],
"blueGreenDeploymentConfiguration": {
  "deploymentReadyOption": {
    "actionOnTimeout": "string",
    "waitTimeInMinutes": number
  },
  "greenFleetProvisioningOption": {
    "action": "string"
  },
  "terminateBlueInstancesOnDeploymentSuccess": {
    "action": "string",
    "terminationWaitTimeInMinutes": number
  }
},
"computePlatform": "string",
"deploymentConfigName": "string",
"deploymentGroupId": "string",
"deploymentGroupName": "string",
"deploymentStyle": {
  "deploymentOption": "string",
  "deploymentType": "string"
},
"ec2TagFilters": [
  {
```

```
        "Key": "string",
        "Type": "string",
        "Value": "string"
    }
],
"ec2TagSet": {
    "ec2TagSetList": [
        [
            {
                "Key": "string",
                "Type": "string",
                "Value": "string"
            }
        ]
    ]
},
"ecsServices": [
    {
        "clusterName": "string",
        "serviceName": "string"
    }
],
"lastAttemptedDeployment": {
    "createTime": number,
    "deploymentId": "string",
    "endTime": number,
    "status": "string"
},
"lastSuccessfulDeployment": {
    "createTime": number,
    "deploymentId": "string",
    "endTime": number,
    "status": "string"
},
"loadBalancerInfo": {
    "elbInfoList": [
        [
            {
                "name": "string"
            }
        ]
    ],
    "targetGroupInfoList": [
        [
            {
                "name": "string"
            }
        ]
    ]
}
```

```
    ],
    "targetGroupPairInfoList": [
      {
        "prodTrafficRoute": {
          "listenerArns": [ "string" ]
        },
        "targetGroups": [
          {
            "name": "string"
          }
        ],
        "testTrafficRoute": {
          "listenerArns": [ "string" ]
        }
      }
    ]
  },
  "onPremisesInstanceTagFilters": [
    {
      "Key": "string",
      "Type": "string",
      "Value": "string"
    }
  ],
  "onPremisesTagSet": {
    "onPremisesTagSetList": [
      [
        {
          "Key": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    ]
  },
  "outdatedInstancesStrategy": "string",
  "serviceRoleArn": "string",
  "targetRevision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
```

```

        "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
        "bucket": "string",
        "bundleType": "string",
        "eTag": "string",
        "key": "string",
        "version": "string"
    },
    "string": {
        "content": "string",
        "sha256": "string"
    }
},
"terminationHookEnabled": boolean,
"triggerConfigurations": [
    {
        "triggerEvents": [ "string" ],
        "triggerName": "string",
        "triggerTargetArn": "string"
    }
]
},
"errorMessage": "string"
}

```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentGroupsInfo

Information about the deployment groups.

Type: Array of [DeploymentGroupInfo](#) objects

### errorMessage

Information about errors that might have occurred during the API call.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **BatchLimitExceededException**

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `BatchGetDeploymentGroups`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: CodeDeploy_20141006.BatchGetDeploymentGroups
X-Amz-Date: 20160317T175340Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160317/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1",
  "deploymentGroupNames": [
    "dep-group-def-456",
    "dep-group-jkl-234"
  ]
}
```

### Sample Response

```
{
  "deploymentGroupsInfo": [
    {
      "applicationName": "TestApp-us-east-1",
      "autoRollbackConfiguration": {
        "enabled": false
      },
      "autoScalingGroups": [],
      "deploymentConfigName": "CodeDeployDefault.OneAtATime",
      "deploymentGroupId": "d-DBF57CS3H",
      "deploymentGroupName": "dep-group-def-456",
      "deploymentStyle": {
```

```

        "deploymentOption": "WITHOUT_TRAFFIC_CONTROL",
        "deploymentType": "IN_PLACE"
    },
    "ec2TagFilters": [
        {
            "Key": "Name",
            "Type": "KEY_AND_VALUE",
            "Value": "Project-ABC"
        }
    ],
    "onPremisesInstanceTagFilters": [],
    "serviceRoleArn": "arn:aws:iam::444455556666:role/AnyCompany-service-role",
    "targetRevision": {
        "revisionType": "S3",
        "s3Location": {
            "bucket": "project-abc",
            "bundleType": "zip",
            "eTag": "ffe5402cff48b652bf903700453f7408",
            "key": "North-App-3.zip",
            "version": "4eQLXx7nw0iP22hxwt2_YXrUq972qkG6"
        }
    },
    "triggerConfigurations": [
        {
            "triggerEvents": [
                "DeploymentFailure"
            ],
            "triggerName": "Trigger-group-us-east-1-deploy-fail",
            "triggerTargetArn": "arn:aws:sns:us-east-1:80398EXAMPLE:us-east-
deploy-fail"
        }
    ],
    {
        "applicationName": "TestApp-us-east-1",
        "autoRollbackConfiguration": {
            "enabled": false
        },
        "autoScalingGroups": [],
        "deploymentConfigName": "CodeDeployDefault.OneAtATime",
        "deploymentGroupId": "d-DCS73HBF5",
        "deploymentGroupName": "dep-group-def-456",
        "deploymentStyle": {
            "deploymentOption": "WITHOUT_TRAFFIC_CONTROL",

```

```

        "deploymentType": "IN_PLACE"
    },
    "ec2TagFilters": [
        {
            "Key": "Name",
            "Type": "KEY_AND_VALUE",
            "Value": "Project-DEF"
        }
    ],
    "onPremisesInstanceTagFilters": [],
    "serviceRoleArn": "arn:aws:iam::444455556666:role/AnyCompany-service-role",
    "targetRevision": {
        "revisionType": "S3",
        "s3Location": {
            "bucket": "project-def",
            "bundleType": "zip",
            "eTag": "3fdd7b9196697a096d5af1d649e26a4a",
            "key": "North-App-3.zip",
            "version": "BXrUq974e0iP22hxwt2_QLXx7nw3kjB9"
        }
    },
    "triggerConfigurations": [
        {
            "triggerEvents": [
                "DeploymentSuccess"
            ],
            "triggerName": "Trigger-group-us-east-1-deploy-succeed",
            "triggerTargetArn": "arn:aws:sns:us-east-1:80398EXAMPLE:us-east-
deploy-succeed"
        }
    ]
},
    "errorMessage": ""
}

```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetDeploymentInstances

## Note

This method works, but is deprecated. Use `BatchGetDeploymentTargets` instead.

Returns an array of one or more instances associated with a deployment. This method works with EC2/On-premises and AWS Lambda compute platforms. The newer `BatchGetDeploymentTargets` works with all compute platforms. The maximum number of instances that can be returned is 25.

## Request Syntax

```
{
  "deploymentId": "string",
  "instanceIds": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

### instanceIds

The unique IDs of instances used in the deployment. The maximum number of instance IDs you can specify is 25.

Type: Array of strings

Required: Yes

## Response Syntax

```
{
  "errorMessage": "string",
  "instancesSummary": [
    {
      "deploymentId": "string",
      "instanceId": "string",
      "instanceType": "string",
      "lastUpdatedAt": number,
      "lifecycleEvents": [
        {
          "diagnostics": {
            "errorCode": "string",
            "logTail": "string",
            "message": "string",
            "scriptName": "string"
          },
          "endTime": number,
          "lifecycleEventName": "string",
          "startTime": number,
          "status": "string"
        }
      ],
      "status": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### errorMessage

Information about errors that might have occurred during the API call.

Type: String

### instancesSummary

Information about the instance.

Type: Array of [InstanceSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **BatchLimitExceededException**

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **InstanceIdRequiredException**

*This error has been deprecated.*

The instance ID was not specified.

HTTP Status Code: 400

### **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of BatchGetDeploymentInstances.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: CodeDeploy_20141006.BatchGetDeploymentInstances
X-Amz-Date: 20160707T175340Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentId": "d-DXT57CS2G",
  "instanceIds": [
    "i-2b4a36ad00EXAMPLE",
    "i-384a57d300EXAMPLE",
    "i-623g53b300EXAMPLE"
  ]
}
```

### Sample Response

```
{
  "errorMessage": "",
  "instancesSummary": [
    {
      "deploymentId": "d-DXT57CS2G",
      "instanceId": "arn:aws:ec2:us-east-1:803981987763:instance/
i-623g53b300EXAMPLE",
      "lastUpdatedAt": 1455988938.931,
```

```
"lifecycleEvents": [  
  {  
    "diagnostics": {  
      "errorCode": "Success",  
      "logTail": "",  
      "message": "Succeeded",  
      "scriptName": ""  
    },  
    "endTime": 1455988923.454,  
    "lifecycleEventName": "ApplicationStop",  
    "startTime": 1455988923.284,  
    "status": "Succeeded"  
  },  
  {  
    "diagnostics": {  
      "errorCode": "Success",  
      "logTail": "",  
      "message": "Succeeded",  
      "scriptName": ""  
    },  
    "endTime": 1455988925.903,  
    "lifecycleEventName": "DownloadBundle",  
    "startTime": 1455988925.574,  
    "status": "Succeeded"  
  },  
  {  
    "diagnostics": {  
      "errorCode": "Success",  
      "logTail": "",  
      "message": "Succeeded",  
      "scriptName": ""  
    },  
    "endTime": 1455988927.731,  
    "lifecycleEventName": "BeforeInstall",  
    "startTime": 1455988927.011,  
    "status": "Succeeded"  
  },  
  {  
    "diagnostics": {  
      "errorCode": "Success",  
      "logTail": "",  
      "message": "Succeeded",  
      "scriptName": ""  
    },  
    "endTime": 1455988929.958,  
    "lifecycleEventName": "ApplicationStart",  
    "startTime": 1455988929.788,  
    "status": "Succeeded"  
  }  
]
```

```
        "endTime": 1455988931.435,
        "lifecycleEventName": "Install",
        "startTime": 1455988931.272,
        "status": "Succeeded"
    },
    {
        "diagnostics": {
            "errorCode": "Success",
            "logTail": "",
            "message": "Succeeded",
            "scriptName": ""
        },
        "endTime": 1455988933.129,
        "lifecycleEventName": "AfterInstall",
        "startTime": 1455988932.951,
        "status": "Succeeded"
    },
    {
        "diagnostics": {
            "errorCode": "Success",
            "logTail": "",
            "message": "Succeeded",
            "scriptName": ""
        },
        "endTime": 1455988935.599,
        "lifecycleEventName": "ApplicationStart",
        "startTime": 1455988935.459,
        "status": "Succeeded"
    },
    {
        "diagnostics": {
            "errorCode": "Success",
            "logTail": "",
            "message": "Succeeded",
            "scriptName": ""
        },
        "endTime": 1455988937.286,
        "lifecycleEventName": "ValidateService",
        "startTime": 1455988937.166,
        "status": "Succeeded"
    }
],
"status": "Succeeded"
},
```

```
{
  "deploymentId": "d-DXT57CS2G",
  "instanceId": "arn:aws:ec2:us-east-1:803981987763:instance/
i-384a57d300EXAMPLE",
  "lastUpdatedAt": 1455988921.266,
  "lifecycleEvents": [
    {
      "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
      },
      "endTime": 1455988908.166,
      "lifecycleEventName": "ApplicationStop",
      "startTime": 1455988908.002,
      "status": "Succeeded"
    },
    {
      "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
      },
      "endTime": 1455988910.007,
      "lifecycleEventName": "DownloadBundle",
      "startTime": 1455988909.817,
      "status": "Succeeded"
    },
    {
      "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
      },
      "endTime": 1455988912.501,
      "lifecycleEventName": "BeforeInstall",
      "startTime": 1455988911.823,
      "status": "Succeeded"
    },
    {
      "diagnostics": {
```

```
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1455988914.18,
    "lifecycleEventName": "Install",
    "startTime": 1455988914.068,
    "status": "Succeeded"
},
{
    "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1455988916.288,
    "lifecycleEventName": "AfterInstall",
    "startTime": 1455988916.108,
    "status": "Succeeded"
},
{
    "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1455988917.63,
    "lifecycleEventName": "ApplicationStart",
    "startTime": 1455988917.513,
    "status": "Succeeded"
},
{
    "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1455988919.616,
    "lifecycleEventName": "ValidateService",
    "startTime": 1455988919.489,
```

```
        "status": "Succeeded"
      }
    ],
    "status": "Succeeded"
  },
  {
    "deploymentId": "d-DXT57CS2G",
    "instanceId": "arn:aws:ec2:us-east-1:803981987763:instance/
i-2b4a36ad00EXAMPLE",
    "lastUpdatedAt": 1455988905.795,
    "lifecycleEvents": [
      {
        "diagnostics": {
          "errorCode": "Success",
          "logTail": "",
          "message": "Succeeded",
          "scriptName": ""
        },
        "endTime": 1455988835.41,
        "lifecycleEventName": "ApplicationStop",
        "startTime": 1455988835.243,
        "status": "Succeeded"
      },
      {
        "diagnostics": {
          "errorCode": "Success",
          "logTail": "",
          "message": "Succeeded",
          "scriptName": ""
        },
        "endTime": 1455988843.137,
        "lifecycleEventName": "DownloadBundle",
        "startTime": 1455988842.349,
        "status": "Succeeded"
      },
      {
        "diagnostics": {
          "errorCode": "Success",
          "logTail": "",
          "message": "Succeeded",
          "scriptName": ""
        },
        "endTime": 1455988845.424,
        "lifecycleEventName": "BeforeInstall",
```

```
    "startTime": 1455988844.707,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1455988853.216,
    "lifecycleEventName": "Install",
    "startTime": 1455988853.096,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1455988858.017,
    "lifecycleEventName": "AfterInstall",
    "startTime": 1455988857.916,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1455988902.714,
    "lifecycleEventName": "ApplicationStart",
    "startTime": 1455988902.56,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
```

```
        "scriptName": ""
      },
      "endTime": 1455988904.577,
      "lifecycleEventName": "ValidateService",
      "startTime": 1455988904.38,
      "status": "Succeeded"
    }
  ],
  "status": "Succeeded"
}
]
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetDeployments

Gets information about one or more deployments. The maximum number of deployments that can be returned is 25.

## Request Syntax

```
{
  "deploymentIds": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentIds

A list of deployment IDs, separated by spaces. The maximum number of deployment IDs you can specify is 25.

Type: Array of strings

Required: Yes

## Response Syntax

```
{
  "deploymentsInfo": [
    {
      "additionalDeploymentStatusInfo": "string",
      "applicationName": "string",
      "autoRollbackConfiguration": {
        "enabled": boolean,
        "events": [ "string" ]
      },
      "blueGreenDeploymentConfiguration": {
        "deploymentReadyOption": {
          "actionOnTimeout": "string",
          "waitTimeInMinutes": number
        }
      }
    }
  ]
}
```

```

    },
    "greenFleetProvisioningOption": {
      "action": "string"
    },
    "terminateBlueInstancesOnDeploymentSuccess": {
      "action": "string",
      "terminationWaitTimeInMinutes": number
    }
  },
  "completeTime": number,
  "computePlatform": "string",
  "createTime": number,
  "creator": "string",
  "deploymentConfigName": "string",
  "deploymentGroupName": "string",
  "deploymentId": "string",
  "deploymentOverview": {
    "Failed": number,
    "InProgress": number,
    "Pending": number,
    "Ready": number,
    "Skipped": number,
    "Succeeded": number
  },
  "deploymentStatusMessages": [ "string" ],
  "deploymentStyle": {
    "deploymentOption": "string",
    "deploymentType": "string"
  },
  "description": "string",
  "errorInformation": {
    "code": "string",
    "message": "string"
  },
  "externalId": "string",
  "fileExistsBehavior": "string",
  "ignoreApplicationStopFailures": boolean,
  "instanceTerminationWaitTimeStarted": boolean,
  "loadBalancerInfo": {
    "elbInfoList": [
      {
        "name": "string"
      }
    ]
  },
],

```

```
    "targetGroupInfoList": [
      {
        "name": "string"
      }
    ],
    "targetGroupPairInfoList": [
      {
        "prodTrafficRoute": {
          "listenerArns": [ "string" ]
        },
        "targetGroups": [
          {
            "name": "string"
          }
        ],
        "testTrafficRoute": {
          "listenerArns": [ "string" ]
        }
      }
    ]
  },
  "overrideAlarmConfiguration": {
    "alarms": [
      {
        "name": "string"
      }
    ],
    "enabled": boolean,
    "ignorePollAlarmFailure": boolean
  },
  "previousRevision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
```

```
    "key": "string",
    "version": "string"
  },
  "string": {
    "content": "string",
    "sha256": "string"
  }
},
"relatedDeployments": {
  "autoUpdateOutdatedInstancesDeploymentIds": [ "string" ],
  "autoUpdateOutdatedInstancesRootDeploymentId": "string"
},
"revision": {
  "appSpecContent": {
    "content": "string",
    "sha256": "string"
  },
  "gitHubLocation": {
    "commitId": "string",
    "repository": "string"
  },
  "revisionType": "string",
  "s3Location": {
    "bucket": "string",
    "bundleType": "string",
    "eTag": "string",
    "key": "string",
    "version": "string"
  },
  "string": {
    "content": "string",
    "sha256": "string"
  }
},
"rollbackInfo": {
  "rollbackDeploymentId": "string",
  "rollbackMessage": "string",
  "rollbackTriggeringDeploymentId": "string"
},
"startTime": number,
"status": "string",
"targetInstances": {
  "autoScalingGroups": [ "string" ],
  "ec2TagSet": {
```

```
    "ec2TagSetList": [
      [
        {
          "Key": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    ],
    "tagFilters": [
      {
        "Key": "string",
        "Type": "string",
        "Value": "string"
      }
    ],
    "updateOutdatedInstancesOnly": boolean
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [deploymentsInfo](#)

Information about the deployments.

Type: Array of [DeploymentInfo](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **BatchLimitExceededException**

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

### DeploymentIdRequiredException

At least one deployment ID must be specified.

HTTP Status Code: 400

### InvalidDeploymentIdException

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of BatchGetDeployments.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 49
X-Amz-Target: CodeDeploy_20141006.BatchGetDeployments
X-Amz-Date: 20160707T232439Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentIds": [
    "d-5SJA0L04C",
    "d-75H25AT3C"
  ]
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 620484b7-88cb-11e5-b497-75c49EXAMPLE
Content-Type: application/x-amz-json-1.1
Content-Length: 1236

{
  "deploymentsInfo": [{
    "applicationName": "TestApp-us-east-1",
    "autoRollbackConfiguration": {
      "enabled": true
    },
    "completeTime": 1.446232681319E9,
    "createTime": 1.446232639487E9,
    "creator": "user",
    "deploymentConfigName": "CodeDeployDefault.OneAtATime",
    "deploymentGroupName": "dep-group-def-456",
    "deploymentId": "d-74D25AS7C",
    "deploymentOverview": {
      "Failed": 0,
      "InProgress": 0,
      "Pending": 0,
      "Skipped": 0,
      "Succeeded": 1
    },
    "deploymentStyle": {
      "deploymentOption": "WITHOUT_TRAFFIC_CONTROL",
      "deploymentType": "IN_PLACE"
    },
    "description": "Deployment for Project 5678",
    "ignoreApplicationStopFailures": false,
    "revision": {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "3fdd7b9196697a096d5af1d649e26a4a",
        "key": "North-App.zip"
      }
    },
    "startTime": 1.446246024315E9,
    "status": "Succeeded",
    "updateOutdatedInstancesOnly": false
  }
}
```

```
},
{
  "applicationName": "ProductionApp-eu-central-1",
  "autoRollbackConfiguration": {
    "enabled": false
  },
  "completeTime": 1.446246198207E9,
  "createTime": 1.446246024315E9,
  "creator": "user",
  "deploymentConfigName": "CodeDeployDefault.OneAtATime",
  "deploymentGroupName": "dep-group-jkl-234",
  "deploymentId": "d-5SJA0L04C",
  "deploymentOverview": {
    "Failed": 1,
    "InProgress": 0,
    "Pending": 0,
    "Skipped": 0,
    "Succeeded": 0
  },
  "deploymentStyle": {
    "deploymentOption": "WITHOUT_TRAFFIC_CONTROL",
    "deploymentType": "IN_PLACE"
  },
  "errorInformation": {
    "code": "HEALTH_CONSTRAINTS",
    "message": "The overall deployment failed because too many individual
instances failed deployment, too few healthy instances are available
for deployment, or some instances in your deployment group are
experiencing
problems."
  },
  "ignoreApplicationStopFailures": false,
  "revision": {
    "revisionType": "S3",
    "s3Location": {
      "bucket": "project-5678",
      "bundleType": "zip",
      "eTag": "9007397ea759a2f535bc9b6ef5414f04-1",
      "key": "Pipeline-123/AppBuild-1/CeGy55t"
    }
  },
  "startTime": 1.446246024315E9,
  "rollbackInfo": {},
  "status": "Failed",

```

```
"updateOutdatedInstancesOnly": false
}]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetDeploymentTargets

Returns an array of one or more targets associated with a deployment. This method works with all compute types and should be used instead of the deprecated `BatchGetDeploymentInstances`. The maximum number of targets that can be returned is 25.

The type of targets returned depends on the deployment's compute platform or deployment method:

- **EC2/On-premises:** Information about Amazon EC2 instance targets.
- **AWS Lambda :** Information about Lambda functions targets.
- **Amazon ECS:** Information about Amazon ECS service targets.
- **CloudFormation:** Information about targets of blue/green deployments initiated by a CloudFormation stack update.

## Request Syntax

```
{  
  "deploymentId": "string",  
  "targetIds": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

## targetIds

The unique IDs of the deployment targets. The compute platform of the deployment determines the type of the targets and their formats. The maximum number of deployment target IDs you can specify is 25.

- For deployments that use the EC2/On-premises compute platform, the target IDs are Amazon EC2 or on-premises instances IDs, and their target type is `instanceTarget`.
- For deployments that use the AWS Lambda compute platform, the target IDs are the names of Lambda functions, and their target type is `instanceTarget`.
- For deployments that use the Amazon ECS compute platform, the target IDs are pairs of Amazon ECS clusters and services specified using the format `<clustername>:<servicename>`. Their target type is `ecsTarget`.
- For deployments that are deployed with CloudFormation, the target IDs are CloudFormation stack IDs. Their target type is `ccloudFormationTarget`.

Type: Array of strings

Required: Yes

## Response Syntax

```
{
  "deploymentTargets": [
    {
      "cloudFormationTarget": {
        "deploymentId": "string",
        "lastUpdatedAt": number,
        "lifecycleEvents": [
          {
            "diagnostics": {
              "errorCode": "string",
              "logTail": "string",
              "message": "string",
              "scriptName": "string"
            },
            "endTime": number,
            "lifecycleEventName": "string",
            "startTime": number,
            "status": "string"
          }
        ]
      }
    }
  ]
}
```

```
    ],
    "resourceType": "string",
    "status": "string",
    "targetId": "string",
    "targetVersionWeight": number
  },
  "deploymentTargetType": "string",
  "ecsTarget": {
    "deploymentId": "string",
    "lastUpdatedAt": number,
    "lifecycleEvents": [
      {
        "diagnostics": {
          "errorCode": "string",
          "logTail": "string",
          "message": "string",
          "scriptName": "string"
        },
        "endTime": number,
        "lifecycleEventName": "string",
        "startTime": number,
        "status": "string"
      }
    ],
    "status": "string",
    "targetArn": "string",
    "targetId": "string",
    "taskSetsInfo": [
      {
        "desiredCount": number,
        "identifer": "string",
        "pendingCount": number,
        "runningCount": number,
        "status": "string",
        "targetGroup": {
          "name": "string"
        },
        "taskSetLabel": "string",
        "trafficWeight": number
      }
    ]
  },
  "instanceTarget": {
    "deploymentId": "string",
```

```
"instanceLabel": "string",
"lastUpdatedAt": number,
"lifecycleEvents": [
  {
    "diagnostics": {
      "errorCode": "string",
      "logTail": "string",
      "message": "string",
      "scriptName": "string"
    },
    "endTime": number,
    "lifecycleEventName": "string",
    "startTime": number,
    "status": "string"
  }
],
"status": "string",
"targetArn": "string",
"targetId": "string"
},
"lambdaTarget": {
  "deploymentId": "string",
  "lambdaFunctionInfo": {
    "currentVersion": "string",
    "functionAlias": "string",
    "functionName": "string",
    "targetVersion": "string",
    "targetVersionWeight": number
  }
},
"lastUpdatedAt": number,
"lifecycleEvents": [
  {
    "diagnostics": {
      "errorCode": "string",
      "logTail": "string",
      "message": "string",
      "scriptName": "string"
    },
    "endTime": number,
    "lifecycleEventName": "string",
    "startTime": number,
    "status": "string"
  }
],
```

```
        "status": "string",
        "targetArn": "string",
        "targetId": "string"
    }
}
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentTargets

A list of target objects for a deployment. Each target object contains details about the target, such as its status and lifecycle events. The type of the target objects depends on the deployment's compute platform.

- **EC2/On-premises:** Each target object is an Amazon EC2 or on-premises instance.
- **AWS Lambda :** The target object is a specific version of an AWS Lambda function.
- **Amazon ECS:** The target object is an Amazon ECS service.
- **CloudFormation:** The target object is an CloudFormation blue/green deployment.

Type: Array of [DeploymentTarget](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

## **DeploymentNotStartedException**

The specified deployment has not started.

HTTP Status Code: 400

## **DeploymentTargetDoesNotExistException**

The provided target ID does not belong to the attempted deployment.

HTTP Status Code: 400

## **DeploymentTargetIdRequiredException**

A deployment target ID was not provided.

HTTP Status Code: 400

## **DeploymentTargetListSizeExceededException**

The maximum number of targets that can be associated with an Amazon ECS or AWS Lambda deployment was exceeded. The target list of both types of deployments must have exactly one item. This exception does not apply to EC2/On-premises deployments.

HTTP Status Code: 400

## **InstanceDoesNotExistException**

*This error has been deprecated.*

The specified instance does not exist in the deployment group.

HTTP Status Code: 400

## **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## **InvalidDeploymentTargetIdException**

The target ID provided was not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetOnPremisesInstances

Gets information about one or more on-premises instances. The maximum number of on-premises instances that can be returned is 25.

## Request Syntax

```
{
  "instanceNames": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### instanceNames

The names of the on-premises instances about which to get information. The maximum number of instance names you can specify is 25.

Type: Array of strings

Required: Yes

## Response Syntax

```
{
  "instanceInfos": [
    {
      "deregisterTime": number,
      "iamSessionArn": "string",
      "iamUserArn": "string",
      "instanceArn": "string",
      "instanceName": "string",
      "registerTime": number,
      "tags": [
        {
```

```
    "Key": "string",  
    "Value": "string"  
  }  
]  
}  
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### instanceInfos

Information about the on-premises instances.

Type: Array of [InstanceInfo](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **BatchLimitExceededException**

The maximum number of names or IDs allowed for this request (100) was exceeded.

HTTP Status Code: 400

### **InstanceNameRequiredException**

An on-premises instance name was not specified.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `BatchGetOnPremisesInstances`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 63
X-Amz-Target: CodeDeploy_20141006.BatchGetOnPremisesInstances
X-Amz-Date: 20160707T232825Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceNames": [
    "grp-a-inst-1",
    "grp-a-inst-3"
  ]
}
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e895fb62-88cb-11e5-a908-6dc86959d072
Content-Type: application/x-amz-json-1.1
Content-Length: 303

{
  "instanceInfos": [
    {
      "iamUserArn": "arn:aws:iam::444455556666:user/janedoe",
      "instanceArn": "arn:aws:codedeploy:us-east-1:444455556666:instance/grp-a-
inst-1_rDH556dxUG",
      "instanceName": "grp-a-inst-1",
      "registerTime": 1428086184.401,
```

```
        "tags": [  
            {  
                "Key": "Name",  
                "Value": "Project-DEF"  
            }  
        ]  
    }  
]
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ContinueDeployment

For a blue/green deployment, starts the process of rerouting traffic from instances in the original environment to instances in the replacement environment without waiting for a specified wait time to elapse. (Traffic rerouting, which is achieved by registering instances in the replacement environment with the load balancer, can start as soon as all instances have a status of Ready.)

## Request Syntax

```
{
  "deploymentId": "string",
  "deploymentWaitType": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a blue/green deployment for which you want to start rerouting traffic to the replacement environment.

Type: String

Required: No

### deploymentWaitType

The status of the deployment's waiting period. READY\_WAIT indicates that the deployment is ready to start shifting traffic. TERMINATION\_WAIT indicates that the traffic is shifted, but the original target is not terminated.

Type: String

Valid Values: READY\_WAIT | TERMINATION\_WAIT

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentAlreadyCompletedException**

The deployment is already complete.

HTTP Status Code: 400

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **DeploymentIsNotInReadyStateException**

The deployment does not have a status of Ready and can't continue yet.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentStatusException**

The specified deployment status doesn't exist or cannot be determined.

HTTP Status Code: 400

### **InvalidDeploymentWaitTypeException**

The wait type is invalid.

HTTP Status Code: 400

## UnsupportedActionForDeploymentTypeException

A call was submitted that is not supported for the specified deployment type.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of ContinueDeployment.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.ContinueDeployment
X-Amz-Date: 20170412T195720Z
User-Agent: aws-cli/1.11.76 Python/2.7.9 Windows/8 botocore/1.5.39
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{"deploymentId": "d-7S8EXAMPL"}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateApplication

Creates an application.

## Request Syntax

```
{
  "applicationName": "string",
  "computePlatform": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [applicationName](#)

The name of the application. This name must be unique with the applicable user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### [computePlatform](#)

The destination platform type for the deployment (Lambda, Server, or ECS).

Type: String

Valid Values: Server | Lambda | ECS | Kubernetes

Required: No

## tags

The metadata that you apply to CodeDeploy applications to help you organize and categorize them. Each tag consists of a key and an optional value, both of which you define.

Type: Array of [Tag](#) objects

Required: No

## Response Syntax

```
{
  "applicationId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationId

A unique application ID.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationAlreadyExistsException**

An application with the specified name with the user or AWS account already exists.

HTTP Status Code: 400

### **ApplicationLimitExceededException**

More applications were attempted to be created than are allowed.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

### **InvalidTagsToAddException**

The specified tags are not valid.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of CreateApplication.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 37
X-Amz-Target: CodeDeploy_20141006.CreateApplication
X-Amz-Date: 20160707T233029Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
```

```
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,  
Signature=39c3b3042cd2aEXAMPLE  
  
{  
  "applicationName": "TestApp-ap-southeast-2"  
}
```

## Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 32431157-88cc-11e5-a908-6dc86959d022  
Content-Type: application/x-amz-json-1.1  
Content-Length: 56  
  
{  
  "applicationId": "767c40ba-2c8d-4ec1-8649-3gd18EXAMPLE"  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDeployment

Deploys an application revision through the specified deployment group.

## Request Syntax

```
{
  "applicationName": "string",
  "autoRollbackConfiguration": {
    "enabled": boolean,
    "events": [ "string" ]
  },
  "deploymentConfigName": "string",
  "deploymentGroupName": "string",
  "description": "string",
  "fileExistsBehavior": "string",
  "ignoreApplicationStopFailures": boolean,
  "overrideAlarmConfiguration": {
    "alarms": [
      {
        "name": "string"
      }
    ],
    "enabled": boolean,
    "ignorePollAlarmFailure": boolean
  },
  "revision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    }
  },
}
```

```
    "string": {
      "content": "string",
      "sha256": "string"
    }
  },
  "targetInstances": {
    "autoScalingGroups": [ "string" ],
    "ec2TagSet": {
      "ec2TagSetList": [
        [
          {
            "Key": "string",
            "Type": "string",
            "Value": "string"
          }
        ]
      ]
    },
    "tagFilters": [
      {
        "Key": "string",
        "Type": "string",
        "Value": "string"
      }
    ]
  },
  "updateOutdatedInstancesOnly": boolean
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [applicationName](#)

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## autoRollbackConfiguration

Configuration information for an automatic rollback that is added when a deployment is created.

Type: [AutoRollbackConfiguration](#) object

Required: No

## deploymentConfigName

The name of a deployment configuration associated with the user or AWS account.

If not specified, the value configured in the deployment group is used as the default. If the deployment group does not have a deployment configuration associated with it, `CodeDeployDefault.OneAtATime` is used by default.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## deploymentGroupName

The name of the deployment group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## description

A comment about the deployment.

Type: String

Required: No

## fileExistsBehavior

Information about how AWS CodeDeploy handles files that already exist in a deployment target location but weren't part of the previous successful deployment.

The `fileExistsBehavior` parameter takes any of the following values:

- **DISALLOW:** The deployment fails. This is also the default behavior if no option is specified.
- **OVERWRITE:** The version of the file from the application revision currently being deployed replaces the version already on the instance.
- **RETAIN:** The version of the file already on the instance is kept and used as part of the new deployment.

Type: String

Valid Values: DISALLOW | OVERWRITE | RETAIN

Required: No

### [ignoreApplicationStopFailures](#)

If true, then if an `ApplicationStop`, `BeforeBlockTraffic`, or `AfterBlockTraffic` deployment lifecycle event to an instance fails, then the deployment continues to the next deployment lifecycle event. For example, if `ApplicationStop` fails, the deployment continues with `DownloadBundle`. If `BeforeBlockTraffic` fails, the deployment continues with `BlockTraffic`. If `AfterBlockTraffic` fails, the deployment continues with `ApplicationStop`.

If false or not specified, then if a lifecycle event fails during a deployment to an instance, that deployment fails. If deployment to that instance is part of an overall deployment and the number of healthy hosts is not less than the minimum number of healthy hosts, then a deployment to the next instance is attempted.

During a deployment, the AWS CodeDeploy agent runs the scripts specified for `ApplicationStop`, `BeforeBlockTraffic`, and `AfterBlockTraffic` in the `AppSpec` file from the previous successful deployment. (All other scripts are run from the `AppSpec` file in the current deployment.) If one of these scripts contains an error and does not run successfully, the deployment can fail.

If the cause of the failure is a script from the last successful deployment that will never run successfully, create a new deployment and use `ignoreApplicationStopFailures` to specify that the `ApplicationStop`, `BeforeBlockTraffic`, and `AfterBlockTraffic` failures should be ignored.

Type: Boolean

Required: No

### overrideAlarmConfiguration

Allows you to specify information about alarms associated with a deployment. The alarm configuration that you specify here will override the alarm configuration at the deployment group level. Consider overriding the alarm configuration if you have set up alarms at the deployment group level that are causing deployment failures. In this case, you would call `CreateDeployment` to create a new deployment that uses a previous application revision that is known to work, and set its alarm configuration to turn off alarm polling. Turning off alarm polling ensures that the new deployment proceeds without being blocked by the alarm that was generated by the previous, failed, deployment.

#### Note

If you specify an `overrideAlarmConfiguration`, you need the `UpdateDeploymentGroup` IAM permission when calling `CreateDeployment`.

Type: [AlarmConfiguration](#) object

Required: No

### revision

The type and location of the revision to deploy.

Type: [RevisionLocation](#) object

Required: No

### targetInstances

Information about the instances that belong to the replacement environment in a blue/green deployment.

Type: [TargetInstances](#) object

Required: No

### updateOutdatedInstancesOnly

Indicates whether to deploy to all instances or only to instances that are not running the latest application revision.

Type: Boolean

Required: No

## Response Syntax

```
{  
  "deploymentId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentId

The unique ID of a deployment.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AlarmsLimitExceededException**

The maximum number of alarms for a deployment group (10) was exceeded.

HTTP Status Code: 400

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **DeploymentLimitExceededException**

The number of allowed deployments was exceeded.

HTTP Status Code: 400

### **DescriptionTooLongException**

The description is too long.

HTTP Status Code: 400

### **InvalidAlarmConfigException**

The format of the alarm configuration is invalid. Possible causes include:

- The alarm list is null.
- The alarm object is null.
- The alarm name is empty or null or exceeds the limit of 255 characters.
- Two alarms with the same name have been specified.
- The alarm configuration is enabled, but the alarm list is empty.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidAutoRollbackConfigException**

The automatic rollback configuration was specified in an invalid format. For example, automatic rollback is enabled, but an invalid triggering event type or no event types were listed.

HTTP Status Code: 400

### **InvalidAutoScalingGroupException**

The Auto Scaling group was specified in an invalid format or does not exist.

HTTP Status Code: 400

### **InvalidDeploymentConfigNameException**

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidFileExistsBehaviorException**

An invalid fileExistsBehavior option was specified to determine how AWS CodeDeploy handles files or directories that already exist in a deployment target location, but weren't part of the previous successful deployment. Valid values include "DISALLOW," "OVERWRITE," and "RETAIN."

HTTP Status Code: 400

### **InvalidGitHubAccountTokenException**

The GitHub token is not valid.

HTTP Status Code: 400

### **InvalidIgnoreApplicationStopFailuresValueException**

The IgnoreApplicationStopFailures value is invalid. For AWS Lambda deployments, false is expected. For EC2/On-premises deployments, true or false is expected.

HTTP Status Code: 400

## **InvalidLoadBalancerInfoException**

An invalid load balancer name, or no load balancer name, was specified.

HTTP Status Code: 400

## **InvalidRevisionException**

The revision was specified in an invalid format.

HTTP Status Code: 400

## **InvalidRoleException**

The service role ARN was specified in an invalid format. Or, if an Auto Scaling group was specified, the specified service role does not grant the appropriate permissions to Amazon EC2 Auto Scaling.

HTTP Status Code: 400

## **InvalidTargetInstancesException**

The target instance configuration is invalid. Possible causes include:

- Configuration data for target instances was entered for an in-place deployment.
- The limit of 10 tags for a tag type was exceeded.
- The combined length of the tag names exceeded the limit.
- A specified tag is not currently applied to any instances.

HTTP Status Code: 400

## **InvalidTrafficRoutingConfigurationException**

The configuration that specifies how traffic is routed during a deployment is invalid.

HTTP Status Code: 400

## **InvalidUpdateOutdatedInstancesOnlyValueException**

The UpdateOutdatedInstancesOnly value is invalid. For AWS Lambda deployments, `false` is expected. For EC2/On-premises deployments, `true` or `false` is expected.

HTTP Status Code: 400

## **RevisionDoesNotExistException**

The named revision does not exist with the user or AWS account.

HTTP Status Code: 400

### RevisionRequiredException

The revision ID was not specified.

HTTP Status Code: 400

### ThrottlingException

An API function was called too frequently.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of CreateDeployment.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 305
X-Amz-Target: CodeDeploy_20141006.CreateDeployment
X-Amz-Date: 20160707T235543Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-ap-southeast-2",
  "autoRollbackConfiguration": {
    "enabled": true,
    "events": [
      "DEPLOYMENT_FAILURE"
    ]
  },
  "deploymentGroupName": "dep-group-ghi-789",
```

```
"description": "Deployment for Project 1234",
"deploymentConfigName": "CodeDeployDefault.OneAtATime",
"ignoreApplicationStopFailures": true,
"revision": {
  "revisionType": "S3",
  "s3Location": {
    "bundleType": "zip",
    "bucket": "project-1234",
    "key": "East-App.zip"
  },
  "updateOutdatedInstancesOnly": true
}
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b8d39558-88cf-11f5-96e5-8bf4ee0ce84e
Content-Type: application/x-amz-json-1.1
Content-Length: 30

{
  "deploymentId": "d-IIMHK0NHC"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# CreateDeploymentConfig

Creates a deployment configuration.

## Request Syntax

```
{
  "computePlatform": "string",
  "deploymentConfigName": "string",
  "minimumHealthyHosts": {
    "type": "string",
    "value": number
  },
  "trafficRoutingConfig": {
    "timeBasedCanary": {
      "canaryInterval": number,
      "canaryPercentage": number
    },
    "timeBasedLinear": {
      "linearInterval": number,
      "linearPercentage": number
    },
    "type": "string"
  },
  "zonalConfig": {
    "firstZoneMonitorDurationInSeconds": number,
    "minimumHealthyHostsPerZone": {
      "type": "string",
      "value": number
    },
    "monitorDurationInSeconds": number
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### computePlatform

The destination platform type for the deployment (Lambda, Server, or ECS).

Type: String

Valid Values: `Server` | `Lambda` | `ECS` | `Kubernetes`

Required: No

### [deploymentConfigName](#)

The name of the deployment configuration to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### [minimumHealthyHosts](#)

The minimum number of healthy instances that should be available at any time during the deployment. There are two parameters expected in the input: type and value.

The type parameter takes either of the following values:

- `HOST_COUNT`: The value parameter represents the minimum number of healthy instances as an absolute value.
- `FLEET_PERCENT`: The value parameter represents the minimum number of healthy instances as a percentage of the total number of instances in the deployment. If you specify `FLEET_PERCENT`, at the start of the deployment, AWS CodeDeploy converts the percentage to the equivalent number of instances and rounds up fractional instances.

The value parameter takes an integer.

For example, to set a minimum of 95% healthy instance, specify a type of `FLEET_PERCENT` and a value of 95.

Type: [MinimumHealthyHosts](#) object

Required: No

### [trafficRoutingConfig](#)

The configuration that specifies how the deployment traffic is routed.

Type: [TrafficRoutingConfig](#) object

Required: No

## [zonalConfig](#)

Configure the `ZonalConfig` object if you want AWS CodeDeploy to deploy your application to one [Availability Zone](#) at a time, within an AWS Region.

For more information about the zonal configuration feature, see [zonal configuration](#) in the *CodeDeploy User Guide*.

Type: [ZonalConfig](#) object

Required: No

## Response Syntax

```
{
  "deploymentConfigId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [deploymentConfigId](#)

A unique deployment configuration ID.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentConfigAlreadyExistsException**

A deployment configuration with the specified name with the user or AWS account already exists.

HTTP Status Code: 400

## **DeploymentConfigLimitExceededException**

The deployment configurations limit was exceeded.

HTTP Status Code: 400

## **DeploymentConfigNameRequiredException**

The deployment configuration name was not specified.

HTTP Status Code: 400

## **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

## **InvalidDeploymentConfigNameException**

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

## **InvalidMinimumHealthyHostValueException**

The minimum healthy instance value was specified in an invalid format.

HTTP Status Code: 400

## **InvalidTrafficRoutingConfigurationException**

The configuration that specifies how traffic is routed during a deployment is invalid.

HTTP Status Code: 400

## **InvalidZonalDeploymentConfigurationException**

The ZonalConfig object is not valid.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of CreateDeploymentConfig.

## Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 103
X-Amz-Target: CodeDeploy_20141006.CreateDeploymentConfig
X-Amz-Date: 20160707T235925Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "minimumHealthyHosts": {
    "type": "HOST_COUNT",
    "value": 1
  },
  "deploymentConfigName": "CustomConfig.One"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3ea3b855-88d0-11e5-9958-cd5094947bf1
Content-Type: application/x-amz-json-1.1
Content-Length: 61

{
  "deploymentConfigId": "e0839cbd-af8a-4a6c-921g-9ad0245d3459"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDeploymentGroup

Creates a deployment group to which application revisions are deployed.

## Request Syntax

```
{
  "alarmConfiguration": {
    "alarms": [
      {
        "name": "string"
      }
    ],
    "enabled": boolean,
    "ignorePollAlarmFailure": boolean
  },
  "applicationName": "string",
  "autoRollbackConfiguration": {
    "enabled": boolean,
    "events": [ "string" ]
  },
  "autoScalingGroups": [ "string" ],
  "blueGreenDeploymentConfiguration": {
    "deploymentReadyOption": {
      "actionOnTimeout": "string",
      "waitTimeInMinutes": number
    },
    "greenFleetProvisioningOption": {
      "action": "string"
    },
    "terminateBlueInstancesOnDeploymentSuccess": {
      "action": "string",
      "terminationWaitTimeInMinutes": number
    }
  },
  "deploymentConfigName": "string",
  "deploymentGroupName": "string",
  "deploymentStyle": {
    "deploymentOption": "string",
    "deploymentType": "string"
  },
  "ec2TagFilters": [
    {
```

```
        "Key": "string",
        "Type": "string",
        "Value": "string"
    }
],
"ec2TagSet": {
    "ec2TagSetList": [
        [
            {
                "Key": "string",
                "Type": "string",
                "Value": "string"
            }
        ]
    ]
},
"ecsServices": [
    {
        "clusterName": "string",
        "serviceName": "string"
    }
],
"loadBalancerInfo": {
    "elbInfoList": [
        {
            "name": "string"
        }
    ],
    "targetGroupInfoList": [
        {
            "name": "string"
        }
    ],
    "targetGroupPairInfoList": [
        {
            "prodTrafficRoute": {
                "listenerArns": [ "string" ]
            },
            "targetGroups": [
                {
                    "name": "string"
                }
            ]
        },
        "testTrafficRoute": {
```

```
        "listenerArns": [ "string" ]
      }
    }
  ],
},
"onPremisesInstanceTagFilters": [
  {
    "Key": "string",
    "Type": "string",
    "Value": "string"
  }
],
"onPremisesTagSet": {
  "onPremisesTagSetList": [
    [
      {
        "Key": "string",
        "Type": "string",
        "Value": "string"
      }
    ]
  ]
},
"outdatedInstancesStrategy": "string",
"serviceRoleArn": "string",
"tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"terminationHookEnabled": boolean,
"triggerConfigurations": [
  {
    "triggerEvents": [ "string" ],
    "triggerName": "string",
    "triggerTargetArn": "string"
  }
]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [alarmConfiguration](#)

Information to add about Amazon CloudWatch alarms when the deployment group is created.

Type: [AlarmConfiguration](#) object

Required: No

### [applicationName](#)

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### [autoRollbackConfiguration](#)

Configuration information for an automatic rollback that is added when a deployment group is created.

Type: [AutoRollbackConfiguration](#) object

Required: No

### [autoScalingGroups](#)

A list of associated Amazon EC2 Auto Scaling groups.

Type: Array of strings

Required: No

### [blueGreenDeploymentConfiguration](#)

Information about blue/green deployment options for a deployment group.

Type: [BlueGreenDeploymentConfiguration](#) object

Required: No

### deploymentConfigName

If specified, the deployment configuration name can be either one of the predefined configurations provided with AWS CodeDeploy or a custom deployment configuration that you create by calling the create deployment configuration operation.

CodeDeployDefault.OneAtATime is the default deployment configuration. It is used if a configuration isn't specified for the deployment or deployment group.

For more information about the predefined deployment configurations in AWS CodeDeploy, see [Working with Deployment Configurations in CodeDeploy](#) in the *AWS CodeDeploy User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### deploymentGroupName

The name of a new deployment group for the specified application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### deploymentStyle

Information about the type of deployment, in-place or blue/green, that you want to run and whether to route deployment traffic behind a load balancer.

Type: [DeploymentStyle](#) object

Required: No

### ec2TagFilters

The Amazon EC2 tags on which to filter. The deployment group includes Amazon EC2 instances with any of the specified tags. Cannot be used in the same call as ec2TagSet.

Type: Array of [EC2TagFilter](#) objects

Required: No

### [ec2TagSet](#)

Information about groups of tags applied to Amazon EC2 instances. The deployment group includes only Amazon EC2 instances identified by all the tag groups. Cannot be used in the same call as `ec2TagFilters`.

Type: [EC2TagSet](#) object

Required: No

### [ecsServices](#)

The target Amazon ECS services in the deployment group. This applies only to deployment groups that use the Amazon ECS compute platform. A target Amazon ECS service is specified as an Amazon ECS cluster and service name pair using the format `<clustername>:<servicename>`.

Type: Array of [ECSService](#) objects

Required: No

### [loadBalancerInfo](#)

Information about the load balancer used in a deployment.

Type: [LoadBalancerInfo](#) object

Required: No

### [onPremisesInstanceTagFilters](#)

The on-premises instance tags on which to filter. The deployment group includes on-premises instances with any of the specified tags. Cannot be used in the same call as `OnPremisesTagSet`.

Type: Array of [TagFilter](#) objects

Required: No

### [onPremisesTagSet](#)

Information about groups of tags applied to on-premises instances. The deployment group includes only on-premises instances identified by all of the tag groups. Cannot be used in the same call as `onPremisesInstanceTagFilters`.

Type: [OnPremisesTagSet](#) object

Required: No

### [outdatedInstancesStrategy](#)

Indicates what happens when new Amazon EC2 instances are launched mid-deployment and do not receive the deployed application revision.

If this option is set to UPDATE or is unspecified, CodeDeploy initiates one or more 'auto-update outdated instances' deployments to apply the deployed application revision to the new Amazon EC2 instances.

If this option is set to IGNORE, CodeDeploy does not initiate a deployment to update the new Amazon EC2 instances. This may result in instances having different revisions.

Type: String

Valid Values: UPDATE | IGNORE

Required: No

### [serviceRoleArn](#)

A service role Amazon Resource Name (ARN) that allows AWS CodeDeploy to act on the user's behalf when interacting with AWS services.

Type: String

Required: Yes

### [tags](#)

The metadata that you apply to CodeDeploy deployment groups to help you organize and categorize them. Each tag consists of a key and an optional value, both of which you define.

Type: Array of [Tag](#) objects

Required: No

### [terminationHookEnabled](#)

This parameter only applies if you are using CodeDeploy with Amazon EC2 Auto Scaling. For more information, see [Integrating CodeDeploy with Amazon EC2 Auto Scaling](#) in the *AWS CodeDeploy User Guide*.

Set `terminationHookEnabled` to `true` to have CodeDeploy install a termination hook into your Auto Scaling group when you create a deployment group. When this hook is installed, CodeDeploy will perform termination deployments.

For information about termination deployments, see [Enabling termination deployments during Auto Scaling scale-in events](#) in the *AWS CodeDeploy User Guide*.

For more information about Auto Scaling scale-in events, see the [Scale in](#) topic in the *Amazon EC2 Auto Scaling User Guide*.

Type: Boolean

Required: No

### [triggerConfigurations](#)

Information about triggers to create when the deployment group is created. For examples, see [Create a Trigger for an AWS CodeDeploy Event](#) in the *AWS CodeDeploy User Guide*.

Type: Array of [TriggerConfig](#) objects

Required: No

## Response Syntax

```
{
  "deploymentGroupId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [deploymentGroupId](#)

A unique deployment group ID.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AlarmsLimitExceededException**

The maximum number of alarms for a deployment group (10) was exceeded.

HTTP Status Code: 400

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupAlreadyExistsException**

A deployment group with the specified name with the user or AWS account already exists.

HTTP Status Code: 400

### **DeploymentGroupLimitExceededException**

The deployment groups limit was exceeded.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **ECSServiceMappingLimitExceededException**

The Amazon ECS service is associated with more than one deployment groups. An Amazon ECS service can be associated with only one deployment group.

HTTP Status Code: 400

### **InvalidAlarmConfigException**

The format of the alarm configuration is invalid. Possible causes include:

- The alarm list is null.
- The alarm object is null.
- The alarm name is empty or null or exceeds the limit of 255 characters.
- Two alarms with the same name have been specified.
- The alarm configuration is enabled, but the alarm list is empty.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidAutoRollbackConfigException**

The automatic rollback configuration was specified in an invalid format. For example, automatic rollback is enabled, but an invalid triggering event type or no event types were listed.

HTTP Status Code: 400

### **InvalidAutoScalingGroupException**

The Auto Scaling group was specified in an invalid format or does not exist.

HTTP Status Code: 400

### **InvalidBlueGreenDeploymentConfigurationException**

The configuration for the blue/green deployment group was provided in an invalid format. For information about deployment configuration format, see [CreateDeploymentConfig](#).

HTTP Status Code: 400

### **InvalidDeploymentConfigNameException**

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

## **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

## **InvalidDeploymentStyleException**

An invalid deployment style was specified. Valid deployment types include "IN\_PLACE" and "BLUE\_GREEN." Valid deployment options include "WITH\_TRAFFIC\_CONTROL" and "WITHOUT\_TRAFFIC\_CONTROL."

HTTP Status Code: 400

## **InvalidEC2TagCombinationException**

A call was submitted that specified both `Ec2TagFilters` and `Ec2TagSet`, but only one of these data types can be used in a single call.

HTTP Status Code: 400

## **InvalidEC2TagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

## **InvalidECSServiceException**

The Amazon ECS service identifier is not valid.

HTTP Status Code: 400

## **InvalidInputException**

The input was specified in an invalid format.

HTTP Status Code: 400

## **InvalidLoadBalancerInfoException**

An invalid load balancer name, or no load balancer name, was specified.

HTTP Status Code: 400

## **InvalidOnPremisesTagCombinationException**

A call was submitted that specified both `OnPremisesTagFilters` and `OnPremisesTagSet`, but only one of these data types can be used in a single call.

HTTP Status Code: 400

### **InvalidRoleException**

The service role ARN was specified in an invalid format. Or, if an Auto Scaling group was specified, the specified service role does not grant the appropriate permissions to Amazon EC2 Auto Scaling.

HTTP Status Code: 400

### **InvalidTagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTagsToAddException**

The specified tags are not valid.

HTTP Status Code: 400

### **InvalidTargetGroupPairException**

A target group pair associated with this deployment is not valid.

HTTP Status Code: 400

### **InvalidTrafficRoutingConfigurationException**

The configuration that specifies how traffic is routed during a deployment is invalid.

HTTP Status Code: 400

### **InvalidTriggerConfigException**

The trigger was specified in an invalid format.

HTTP Status Code: 400

### **LifecycleHookLimitExceededException**

The limit for lifecycle hooks was exceeded.

HTTP Status Code: 400

### **RoleRequiredException**

The role ID was not specified.

HTTP Status Code: 400

### **TagSetListLimitExceededException**

The number of tag groups included in the tag set list exceeded the maximum allowed limit of 3.

HTTP Status Code: 400

### **ThrottlingException**

An API function was called too frequently.

HTTP Status Code: 400

### **TriggerTargetsLimitExceededException**

The maximum allowed number of triggers was exceeded.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of `CreateDeploymentGroup`.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 294
X-Amz-Target: CodeDeploy_20141006.CreateDeploymentGroup
X-Amz-Date: 20160707T000818Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "alarmConfiguration": {
    "alarms": [
      {
```

```
        "name": "project-abc-alarm"
      }
    ],
    "enabled": true,
    "ignorePollAlarmFailure": false
  },
  "applicationName": "TestApp-us-east-1",
  "autoRollbackConfiguration": {
    "enabled": true,
    "events": [
      "DEPLOYMENT_FAILURE"
    ]
  },
  "serviceRoleArn": "arn:aws:iam::444455556666:role/AnyCompany-service-role",
  "ec2TagFilters": [
    {
      "Type": "KEY_AND_VALUE",
      "Key": "Name",
      "Value": "Project-ABC"
    }
  ],
  "deploymentGroupName": "dep-group-ghi-789-2",
  "deploymentConfigName": "CodeDeployDefault.OneAtATime",
  "deploymentStyle": {
    "deploymentOption": "WITH_TRAFFIC_CONTROL",
    "deploymentType": "IN_PLACE"
  },
  "loadBalancerInfo": {
    "elbInfoList": [
      {
        "name": "USEastLoadBalancer"
      }
    ]
  },
  "triggerConfigurations": [
    {
      "triggerEvents": [
        "DeploymentFailure"
      ],
      "triggerName": "Trigger-group-us-east-1-deploy-fail",
      "triggerTargetArn": "arn:aws:sns:us-east-1:80398EXAMPLE:us-east-deploy-
fail"
    }
  ]
]
```

```
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 7aed4309-88d1-11e5-b0f5-a331fa97e4b5
Content-Type: application/x-amz-json-1.1
Content-Length: 60

{
  "deploymentGroupId": "e9be2617-8b71-46a1-944a-3c45c9138ee7"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteApplication

Deletes an application.

## Request Syntax

```
{  
  "applicationName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ApplicationNameRequiredException

The minimum number of required application names was not specified.

HTTP Status Code: 400

## InvalidApplicationNameException

The application name was specified in an invalid format.

HTTP Status Code: 400

## InvalidRoleException

The service role ARN was specified in an invalid format. Or, if an Auto Scaling group was specified, the specified service role does not grant the appropriate permissions to Amazon EC2 Auto Scaling.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DeleteApplication.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 37
X-Amz-Target: CodeDeploy_20141006.DeleteApplication
X-Amz-Date: 20160707T012940Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-ap-southeast-2"
}
```

### Sample Response

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDeploymentConfig

Deletes a deployment configuration.

## Note

A deployment configuration cannot be deleted if it is currently in use. Predefined configurations cannot be deleted.

## Request Syntax

```
{  
  "deploymentConfigName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentConfigName

The name of a deployment configuration associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## DeploymentConfigInUseException

The deployment configuration is still in use.

HTTP Status Code: 400

## DeploymentConfigNameRequiredException

The deployment configuration name was not specified.

HTTP Status Code: 400

## InvalidDeploymentConfigNameException

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

## InvalidOperationException

An invalid operation was detected.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DeleteDeploymentConfig.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 41
X-Amz-Target: CodeDeploy_20141006.DeleteDeploymentConfig
X-Amz-Date: 20160707T013153Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE
```

```
{
  "deploymentConfigName": "dep-group-ghi-789"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDeploymentGroup

Deletes a deployment group.

## Request Syntax

```
{
  "applicationName": "string",
  "deploymentGroupName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### deploymentGroupName

The name of a deployment group for the specified application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{
  "hooksNotCleanedUp": [
    {
```

```
    "hook": "string",  
    "name": "string",  
    "terminationHook": "string"  
  }  
]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### hooksNotCleanedUp

If the output contains no data, and the corresponding deployment group contained at least one Auto Scaling group, AWS CodeDeploy successfully removed all corresponding Auto Scaling lifecycle event hooks from the Amazon EC2 instances in the Auto Scaling group. If the output contains data, AWS CodeDeploy could not remove some Auto Scaling lifecycle event hooks from the Amazon EC2 instances in the Auto Scaling group.

Type: Array of [AutoScalingGroup](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

## InvalidDeploymentGroupNameException

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

## InvalidRoleException

The service role ARN was specified in an invalid format. Or, if an Auto Scaling group was specified, the specified service role does not grant the appropriate permissions to Amazon EC2 Auto Scaling.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DeleteDeploymentGroup.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 71
X-Amz-Target: CodeDeploy_20141006.DeleteDeploymentGroup
X-Amz-Date: 20160707T013700Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-eu-west-1",
  "deploymentGroupName": "dep-group-abc-123"
}
```

### Sample Response

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: dec21774-88dd-11e5-96e5-8bf4ee0ce84e
Content-Type: application/x-amz-json-1.1
Content-Length: 24

{
  "hooksNotCleanedUp": []
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteGitHubAccountToken

Deletes a GitHub account connection.

## Request Syntax

```
{
  "tokenName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### tokenName

The name of the GitHub account connection to delete.

Type: String

Required: No

## Response Syntax

```
{
  "tokenName": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### tokenName

The name of the GitHub account connection that was deleted.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **GitHubAccountTokenDoesNotExistException**

No GitHub account connection exists with the named specified in the call.

HTTP Status Code: 400

### **GitHubAccountTokenNameRequiredException**

The call is missing a required GitHub account connection name.

HTTP Status Code: 400

### **InvalidGitHubAccountTokenNameException**

The format of the specified GitHub account connection name is invalid.

HTTP Status Code: 400

### **OperationNotSupportedException**

The API used does not support the deployment.

HTTP Status Code: 400

### **ResourceValidationException**

The specified resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteResourcesByExternalId

Deletes resources linked to an external ID. This action only applies if you have configured blue/green deployments through CloudFormation.

## Note

It is not necessary to call this action directly. CloudFormation calls it on your behalf when it needs to delete stack resources. This action is offered publicly in case you need to delete resources to comply with General Data Protection Regulation (GDPR) requirements.

## Request Syntax

```
{
  "externalId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### externalId

The unique ID of an external resource (for example, a CloudFormation stack ID) that is linked to one or more CodeDeploy resources.

Type: String

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeregisterOnPremisesInstance

Deregisters an on-premises instance.

## Request Syntax

```
{  
  "instanceName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### instanceName

The name of the on-premises instance to deregister.

Type: String

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InstanceNameRequiredException**

An on-premises instance name was not specified.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `DeregisterOnPremisesInstance`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 43
X-Amz-Target: CodeDeploy_20141006.DeregisterOnPremisesInstance
X-Amz-Date: 20160707T182111Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceName": "grp-b-inst-3"
}
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApplication

Gets information about an application.

## Request Syntax

```
{
  "applicationName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{
  "application": {
    "applicationId": "string",
    "applicationName": "string",
    "computePlatform": "string",
    "createTime": number,
    "gitHubAccountName": "string",
    "linkedToGitHub": boolean
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### application

Information about the application.

Type: [ApplicationInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `GetApplication`.

### Sample Request

```
POST / HTTP/1.1
```

```
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 45
X-Amz-Target: CodeDeploy_20141006.GetApplication
X-Amz-Date: 20160707T014559Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2010bbbd-88df-11e5-9749-bba241db97da
Content-Type: application/x-amz-json-1.1
Content-Length: 168

{
  "application": {
    "applicationId": "d3be67e5-e716-457b-946b-7a457EXAMPLE",
    "applicationName": "TestApp-us-east-1",
    "createTime": 1446229001.211,
    "linkedToGitHub": false
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApplicationRevision

Gets information about an application revision.

## Request Syntax

```
{
  "applicationName": "string",
  "revision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    },
    "string": {
      "content": "string",
      "sha256": "string"
    }
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of the application that corresponds to the revision.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## revision

Information about the application revision to get, including type and location.

Type: [RevisionLocation](#) object

Required: Yes

## Response Syntax

```
{
  "applicationName": "string",
  "revision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    },
    "string": {
      "content": "string",
      "sha256": "string"
    }
  },
  "revisionInfo": {
    "deploymentGroups": [ "string" ],
    "description": "string",
    "firstUsedTime": number,
    "lastUsedTime": number,
  }
}
```

```
    "registerTime": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationName

The name of the application that corresponds to the revision.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

### revision

Additional information about the revision, including type and location.

Type: [RevisionLocation](#) object

### revisionInfo

General information about the revision.

Type: [GenericRevisionInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

## InvalidApplicationNameException

The application name was specified in an invalid format.

HTTP Status Code: 400

## InvalidRevisionException

The revision was specified in an invalid format.

HTTP Status Code: 400

## RevisionDoesNotExistException

The named revision does not exist with the user or AWS account.

HTTP Status Code: 400

## RevisionRequiredException

The revision ID was not specified.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `GetApplicationRevision`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 215
X-Amz-Target: CodeDeploy_20141006.GetApplicationRevision
X-Amz-Date: 20160707T015403Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
```

```
"applicationName": "TestApp-us-east-1",
"revision": {
  "revisionType": "S3",
  "s3Location": {
    "bundleType": "zip",
    "eTag": "fff9102ckv48b652bf903700453f7408",
    "bucket": "project-1234",
    "key": "North-App.zip"
  }
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 410338f8-88e0-11e5-bb59-fb8eade0dfc3
Content-Type: application/x-amz-json-1.1
Content-Length: 416

{
  "applicationName": "TestApp-us-east-1",
  "revision": {
    "revisionType": "S3",
    "s3Location": {
      "bucket": "project-1234",
      "bundleType": "zip",
      "eTag": "abc9102cff48b652bf903765453f7408",
      "key": "North-App.zip"
    }
  },
  "revisionInfo": {
    "deploymentGroups": [],
    "description": "Application revision registered by Deployment ID: d-D1EGTDV3C",
    "firstUsedTime": 1446232255.734,
    "lastUsedTime": 1446232255.734,
    "registerTime": 1446232255.734
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeployment

Gets information about a deployment.

## Note

The content property of the appSpecContent object in the returned revision is always null. Use GetApplicationRevision and the sha256 property of the returned appSpecContent object to get the content of the deployment's AppSpec file.

## Request Syntax

```
{  
  "deploymentId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment associated with the user or AWS account.

Type: String

Required: Yes

## Response Syntax

```
{  
  "deploymentInfo": {  
    "additionalDeploymentStatusInfo": "string",  
    "applicationName": "string",  
    "autoRollbackConfiguration": {  
      "enabled": boolean,  
      "events": [ "string" ]  
    }  
  }  
}
```

```
  },
  "blueGreenDeploymentConfiguration": {
    "deploymentReadyOption": {
      "actionOnTimeout": "string",
      "waitTimeInMinutes": number
    },
    "greenFleetProvisioningOption": {
      "action": "string"
    },
    "terminateBlueInstancesOnDeploymentSuccess": {
      "action": "string",
      "terminationWaitTimeInMinutes": number
    }
  },
  "completeTime": number,
  "computePlatform": "string",
  "createTime": number,
  "creator": "string",
  "deploymentConfigName": "string",
  "deploymentGroupName": "string",
  "deploymentId": "string",
  "deploymentOverview": {
    "Failed": number,
    "InProgress": number,
    "Pending": number,
    "Ready": number,
    "Skipped": number,
    "Succeeded": number
  },
  "deploymentStatusMessages": [ "string" ],
  "deploymentStyle": {
    "deploymentOption": "string",
    "deploymentType": "string"
  },
  "description": "string",
  "errorInformation": {
    "code": "string",
    "message": "string"
  },
  "externalId": "string",
  "fileExistsBehavior": "string",
  "ignoreApplicationStopFailures": boolean,
  "instanceTerminationWaitTimeStarted": boolean,
  "loadBalancerInfo": {
```

```
    "elbInfoList": [
      {
        "name": "string"
      }
    ],
    "targetGroupInfoList": [
      {
        "name": "string"
      }
    ],
    "targetGroupPairInfoList": [
      {
        "prodTrafficRoute": {
          "listenerArns": [ "string" ]
        },
        "targetGroups": [
          {
            "name": "string"
          }
        ],
        "testTrafficRoute": {
          "listenerArns": [ "string" ]
        }
      }
    ]
  },
  "overrideAlarmConfiguration": {
    "alarms": [
      {
        "name": "string"
      }
    ],
    "enabled": boolean,
    "ignorePollAlarmFailure": boolean
  },
  "previousRevision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    }
  },
}
```

```
"revisionType": "string",
"s3Location": {
  "bucket": "string",
  "bundleType": "string",
  "eTag": "string",
  "key": "string",
  "version": "string"
},
"string": {
  "content": "string",
  "sha256": "string"
}
},
"relatedDeployments": {
  "autoUpdateOutdatedInstancesDeploymentIds": [ "string" ],
  "autoUpdateOutdatedInstancesRootDeploymentId": "string"
},
"revision": {
  "appSpecContent": {
    "content": "string",
    "sha256": "string"
  },
  "gitHubLocation": {
    "commitId": "string",
    "repository": "string"
  },
  "revisionType": "string",
  "s3Location": {
    "bucket": "string",
    "bundleType": "string",
    "eTag": "string",
    "key": "string",
    "version": "string"
  },
  "string": {
    "content": "string",
    "sha256": "string"
  }
},
"rollbackInfo": {
  "rollbackDeploymentId": "string",
  "rollbackMessage": "string",
  "rollbackTriggeringDeploymentId": "string"
},
```

```
"startTime": number,
"status": "string",
"targetInstances": {
  "autoScalingGroups": [ "string" ],
  "ec2TagSet": {
    "ec2TagSetList": [
      [
        {
          "Key": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    ]
  },
  "tagFilters": [
    {
      "Key": "string",
      "Type": "string",
      "Value": "string"
    }
  ]
},
"updateOutdatedInstancesOnly": boolean
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentInfo

Information about the deployment.

Type: [DeploymentInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## DeploymentDoesNotExistException

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

## DeploymentIdRequiredException

At least one deployment ID must be specified.

HTTP Status Code: 400

## InvalidDeploymentIdException

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of GetDeployment.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.GetDeployment
X-Amz-Date: 20160707T015545Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentId": "d-74D24AS7X"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 7dca4dcf-88e0-11e5-96e5-5hj1ee0ce84e
Content-Type: application/x-amz-json-1.1
Content-Length: 622

{
  "deploymentInfo": {
    "applicationName": "TestApp-us-east-1",
    "completeTime": 1446232681.319,
    "createTime": 1446232639.487,
    "creator": "user",
    "deploymentConfigName": "CodeDeployDefault.OneAtATime",
    "deploymentGroupName": "dep-group-def-456",
    "deploymentId": "d-74D35AS7C",
    "deploymentOverview": {
      "Failed": 0,
      "InProgress": 0,
      "Pending": 0,
      "Skipped": 0,
      "Succeeded": 1
    },
    "description": "Deployment for project 8FHE43",
    "ignoreApplicationStopFailures": false,
    "revision": {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "3fdd7b968314a096d5af1d649e26a4a",
        "key": "North-App.zip"
      }
    },
    "startTime": 1446744188.711,
    "status": "Succeeded"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeploymentConfig

Gets information about a deployment configuration.

## Request Syntax

```
{  
  "deploymentConfigName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [deploymentConfigName](#)

The name of a deployment configuration associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{  
  "deploymentConfigInfo": {  
    "computePlatform": "string",  
    "createTime": number,  
    "deploymentConfigId": "string",  
    "deploymentConfigName": "string",  
    "minimumHealthyHosts": {  
      "type": "string",  
      "value": number  
    },  
    "trafficRoutingConfig": {  
      "timeBasedCanary": {  
        "canaryInterval": number,  
        "canaryPercentage": number  
      }  
    }  
  }  
}
```

```
    },
    "timeBasedLinear": {
      "linearInterval": number,
      "linearPercentage": number
    },
    "type": "string"
  },
  "zonalConfig": {
    "firstZoneMonitorDurationInSeconds": number,
    "minimumHealthyHostsPerZone": {
      "type": "string",
      "value": number
    },
    "monitorDurationInSeconds": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentConfigInfo

Information about the deployment configuration.

Type: [DeploymentConfigInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentConfigNameRequiredException**

The deployment configuration name was not specified.

HTTP Status Code: 400

### **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

### **InvalidDeploymentConfigNameException**

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of GetDeploymentConfig.

#### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 56
X-Amz-Target: CodeDeploy_20141006.GetDeploymentConfig
X-Amz-Date: 20160707T015738Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentConfigName": "CodeDeployDefault.OneAtATime"
}
```

#### **Sample Response**

```
HTTP/1.1 200 OK
x-amzn-RequestId: c177704f-88e0-11e5-b497-75c493756c4d
```

```
Content-Type: application/x-amz-json-1.1
```

```
Content-Length: 200
```

```
{
  "deploymentConfigInfo": {
    "createTime": 1446744188.711,
    "deploymentConfigId": "00000000-0000-0000-0000-000000000001",
    "deploymentConfigName": "CodeDeployDefault.OneAtATime",
    "minimumHealthyHosts": {
      "type": "MOST_CONCURRENCY",
      "value": 1
    }
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeploymentGroup

Gets information about a deployment group.

## Request Syntax

```
{
  "applicationName": "string",
  "deploymentGroupName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [applicationName](#)

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### [deploymentGroupName](#)

The name of a deployment group for the specified application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{
  "deploymentGroupInfo": {
    "alarmConfiguration": {
      "alarms": [
```

```
    {
      "name": "string"
    }
  ],
  "enabled": boolean,
  "ignorePollAlarmFailure": boolean
},
"applicationName": "string",
"autoRollbackConfiguration": {
  "enabled": boolean,
  "events": [ "string" ]
},
"autoScalingGroups": [
  {
    "hook": "string",
    "name": "string",
    "terminationHook": "string"
  }
],
"blueGreenDeploymentConfiguration": {
  "deploymentReadyOption": {
    "actionOnTimeout": "string",
    "waitTimeInMinutes": number
  },
  "greenFleetProvisioningOption": {
    "action": "string"
  },
  "terminateBlueInstancesOnDeploymentSuccess": {
    "action": "string",
    "terminationWaitTimeInMinutes": number
  }
},
"computePlatform": "string",
"deploymentConfigName": "string",
"deploymentGroupId": "string",
"deploymentGroupName": "string",
"deploymentStyle": {
  "deploymentOption": "string",
  "deploymentType": "string"
},
"ec2TagFilters": [
  {
    "Key": "string",
    "Type": "string",
```

```
    "Value": "string"
  }
],
"ec2TagSet": {
  "ec2TagSetList": [
    [
      {
        "Key": "string",
        "Type": "string",
        "Value": "string"
      }
    ]
  ]
},
"ecsServices": [
  {
    "clusterName": "string",
    "serviceName": "string"
  }
],
"lastAttemptedDeployment": {
  "createTime": number,
  "deploymentId": "string",
  "endTime": number,
  "status": "string"
},
"lastSuccessfulDeployment": {
  "createTime": number,
  "deploymentId": "string",
  "endTime": number,
  "status": "string"
},
"loadBalancerInfo": {
  "elbInfoList": [
    {
      "name": "string"
    }
  ],
  "targetGroupInfoList": [
    {
      "name": "string"
    }
  ],
  "targetGroupPairInfoList": [
```

```
    {
      "prodTrafficRoute": {
        "listenerArns": [ "string" ]
      },
      "targetGroups": [
        {
          "name": "string"
        }
      ],
      "testTrafficRoute": {
        "listenerArns": [ "string" ]
      }
    }
  ],
  "onPremisesInstanceTagFilters": [
    {
      "Key": "string",
      "Type": "string",
      "Value": "string"
    }
  ],
  "onPremisesTagSet": {
    "onPremisesTagSetList": [
      [
        {
          "Key": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    ]
  },
  "outdatedInstancesStrategy": "string",
  "serviceRoleArn": "string",
  "targetRevision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    }
  },
```

```

    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    },
    "string": {
      "content": "string",
      "sha256": "string"
    }
  },
  "terminationHookEnabled": boolean,
  "triggerConfigurations": [
    {
      "triggerEvents": [ "string" ],
      "triggerName": "string",
      "triggerTargetArn": "string"
    }
  ]
}

```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentGroupInfo

Information about the deployment group.

Type: [DeploymentGroupInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of `GetDeploymentGroup`.

## Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 99
X-Amz-Target: CodeDeploy_20141006.GetDeploymentGroup
X-Amz-Date: 20160707T020047Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1",
  "deploymentGroupName": "dep-group-def-456"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 31b0d6a4-88e1-11e5-bb59-fb8eade0dfc3
Content-Type: application/x-amz-json-1.1
Content-Length: 646

{
  "deploymentGroupInfo": {
    "applicationName": "TestApp-us-east-1",
    "autoScalingGroups": [],
    "deploymentConfigName": "CodeDeployDefault.OneAtATime",
    "deploymentGroupId": "c565c0f7-8927-45d5-ab11-c16c4b0540b6",
    "deploymentGroupName": "dep-group-def-456",
    "ec2TagFilters": [
      {
        "Key": "Name",
        "Type": "KEY_AND_VALUE",
        "Value": "grp-c-inst-1"
      }
    ],
    "onPremisesInstanceTagFilters": [],
    "serviceRoleArn": "arn:aws:iam::444455556666:role/AnyCompany-service-role",
```

```
    "targetRevision": {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "3fdd7b9193231a096d5af1d649e26a4a",
        "key": "North-App.zip"
      },
      "triggerConfigurations": [
        {
          "triggerEvents": [
            "DeploymentFailure"
          ],
          "triggerName": "Trigger-group-us-east-1-deploy-fail",
          "triggerTargetArn": "arn:aws:sns:us-east-1:80398EXAMPLE:us-east-
deploy-fail"
        }
      ]
    }
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeploymentInstance

Gets information about an instance as part of a deployment.

## Request Syntax

```
{  
  "deploymentId": "string",  
  "instanceId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

### instanceId

The unique ID of an instance in the deployment group.

Type: String

Required: Yes

## Response Syntax

```
{  
  "instanceSummary": {  
    "deploymentId": "string",  
    "instanceId": "string",  
    "instanceType": "string",  
  }  
}
```

```
"lastUpdatedAt": number,
"lifecycleEvents": [
  {
    "diagnostics": {
      "errorCode": "string",
      "logTail": "string",
      "message": "string",
      "scriptName": "string"
    },
    "endTime": number,
    "lifecycleEventName": "string",
    "startTime": number,
    "status": "string"
  }
],
"status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### instanceSummary

*This parameter has been deprecated.*

Information about the instance.

Type: [InstanceSummary](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### DeploymentDoesNotExistException

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

## **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

## **InstanceDoesNotExistException**

*This error has been deprecated.*

The specified instance does not exist in the deployment group.

HTTP Status Code: 400

## **InstanceIdRequiredException**

*This error has been deprecated.*

The instance ID was not specified.

HTTP Status Code: 400

## **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

## **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of `GetDeploymentInstance`.

## Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 59
X-Amz-Target: CodeDeploy_20141006.GetDeploymentInstance
X-Amz-Date: 20160707T020504Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceId": "i-496636f700EXAMPLE",
  "deploymentId": "d-7539MBT7C"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: caf06837-88e1-11e5-b0f5-a331fa97e4b5
Content-Type: application/x-amz-json-1.1
Content-Length: 1628

{
  "instanceSummary": {
    "deploymentId": "d-75I7MBT7C",
    "instanceId": "arn:aws:ec2:us-east-1:444455556666:instance/
i-496589f700EXAMPLE",
    "lastUpdatedAt": 1446744207.564,
    "lifecycleEvents": [
      {
        "diagnostics": {
          "errorCode": "Success",
          "logTail": "",
          "message": "Succeeded",
          "scriptName": ""
        },
        "endTime": 1446744188.711,
        "lifecycleEventName": "ApplicationStop",
```

```
    "startTime": 1446744188.595,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1446744190.402,
    "lifecycleEventName": "DownloadBundle",
    "startTime": 1446744189.827,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1446744196.971,
    "lifecycleEventName": "BeforeInstall",
    "startTime": 1446744192.922,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
      "scriptName": ""
    },
    "endTime": 1446744198.23,
    "lifecycleEventName": "Install",
    "startTime": 1446744198.084,
    "status": "Succeeded"
  },
  {
    "diagnostics": {
      "errorCode": "Success",
      "logTail": "",
      "message": "Succeeded",
```

```
        "scriptName": ""
    },
    "endTime": 1446744200.299,
    "lifecycleEventName": "AfterInstall",
    "startTime": 1446744200.185,
    "status": "Succeeded"
},
{
    "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1446744203.12,
    "lifecycleEventName": "ApplicationStart",
    "startTime": 1446744202.983,
    "status": "Succeeded"
},
{
    "diagnostics": {
        "errorCode": "Success",
        "logTail": "",
        "message": "Succeeded",
        "scriptName": ""
    },
    "endTime": 1446744204.558,
    "lifecycleEventName": "ValidateService",
    "startTime": 1446744204.438,
    "status": "Succeeded"
}
],
"status": "Succeeded"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeploymentTarget

Returns information about a deployment target.

## Request Syntax

```
{
  "deploymentId": "string",
  "targetId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

### targetId

The unique ID of a deployment target.

Type: String

Required: Yes

## Response Syntax

```
{
  "deploymentTarget": {
    "cloudFormationTarget": {
      "deploymentId": "string",
      "lastUpdatedAt": number,
      "lifecycleEvents": [
        {
          "diagnostics": {
```

```
        "errorCode": "string",
        "logTail": "string",
        "message": "string",
        "scriptName": "string"
    },
    "endTime": number,
    "lifecycleEventName": "string",
    "startTime": number,
    "status": "string"
}
],
"resourceType": "string",
"status": "string",
"targetId": "string",
"targetVersionWeight": number
},
"deploymentTargetType": "string",
"ecsTarget": {
    "deploymentId": "string",
    "lastUpdatedAt": number,
    "lifecycleEvents": [
        {
            "diagnostics": {
                "errorCode": "string",
                "logTail": "string",
                "message": "string",
                "scriptName": "string"
            },
            "endTime": number,
            "lifecycleEventName": "string",
            "startTime": number,
            "status": "string"
        }
    ],
    "status": "string",
    "targetArn": "string",
    "targetId": "string",
    "taskSetsInfo": [
        {
            "desiredCount": number,
            "identifer": "string",
            "pendingCount": number,
            "runningCount": number,
            "status": "string",
```

```
    "targetGroup": {
      "name": "string"
    },
    "taskSetLabel": "string",
    "trafficWeight": number
  }
]
},
"instanceTarget": {
  "deploymentId": "string",
  "instanceLabel": "string",
  "lastUpdatedAt": number,
  "lifecycleEvents": [
    {
      "diagnostics": {
        "errorCode": "string",
        "logTail": "string",
        "message": "string",
        "scriptName": "string"
      },
      "endTime": number,
      "lifecycleEventName": "string",
      "startTime": number,
      "status": "string"
    }
  ],
  "status": "string",
  "targetArn": "string",
  "targetId": "string"
},
"lambdaTarget": {
  "deploymentId": "string",
  "lambdaFunctionInfo": {
    "currentVersion": "string",
    "functionAlias": "string",
    "functionName": "string",
    "targetVersion": "string",
    "targetVersionWeight": number
  },
  "lastUpdatedAt": number,
  "lifecycleEvents": [
    {
      "diagnostics": {
        "errorCode": "string",
```

```
        "logTail": "string",
        "message": "string",
        "scriptName": "string"
    },
    "endTime": number,
    "lifecycleEventName": "string",
    "startTime": number,
    "status": "string"
}
],
"status": "string",
"targetArn": "string",
"targetId": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentTarget

A deployment target that contains information about a deployment such as its status, lifecycle events, and when it was last updated. It also contains metadata about the deployment target. The deployment target metadata depends on the deployment target's type (`instanceTarget`, `lambdaTarget`, or `ecsTarget`).

Type: [DeploymentTarget](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **DeploymentNotStartedException**

The specified deployment has not started.

HTTP Status Code: 400

### **DeploymentTargetDoesNotExistException**

The provided target ID does not belong to the attempted deployment.

HTTP Status Code: 400

### **DeploymentTargetIdRequiredException**

A deployment target ID was not provided.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentTargetIdException**

The target ID provided was not valid.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetOnPremisesInstance

Gets information about an on-premises instance.

## Request Syntax

```
{
  "instanceName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### instanceName

The name of the on-premises instance about which to get information.

Type: String

Required: Yes

## Response Syntax

```
{
  "instanceInfo": {
    "deregisterTime": number,
    "iamSessionArn": "string",
    "iamUserArn": "string",
    "instanceArn": "string",
    "instanceName": "string",
    "registerTime": number,
    "tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [instanceInfo](#)

Information about the on-premises instance.

Type: [InstanceInfo](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InstanceNameRequiredException**

An on-premises instance name was not specified.

HTTP Status Code: 400

### **InstanceNotRegisteredException**

The specified on-premises instance is not registered.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `GetOnPremisesInstance`.

## Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.GetOnPremisesInstance
X-Amz-Date: 20160707T020614Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceName": "grp-c-inst-2"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: caf06837-88e1-11e5-b0f5-a331fa97e4b5
Content-Type: application/x-amz-json-1.1
Content-Length: 386

{
  "InstanceInfo": {
    "deregisterTime": 1.446744190402E9,
    "iamUserArn": "arn:aws:iam::444455556666:user/janedoe",
    "instanceArn": "arn:aws:codedeploy:us-east-1:444455556666:instance/grp-e-
inst-3_EJFIFC3LrD",
    "instanceName": "grp-o-inst-7",
    "registerTime": 1.446744207564E9,
    "tags": [
      {
        "Key": "Name",
        "Value": "Cost-Center-765"
      }
    ]
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListApplicationRevisions

Lists information about revisions for an application.

## Request Syntax

```
{
  "applicationName": "string",
  "deployed": "string",
  "nextToken": "string",
  "s3Bucket": "string",
  "s3KeyPrefix": "string",
  "sortBy": "string",
  "sortOrder": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### deployed

Whether to list revisions based on whether the revision is the target revision of a deployment group:

- `include`: List revisions that are target revisions of a deployment group.
- `exclude`: Do not list revisions that are target revisions of a deployment group.
- `ignore`: List all revisions.

Type: String

Valid Values: `include` | `exclude` | `ignore`

Required: No

### nextToken

An identifier returned from the previous `ListApplicationRevisions` call. It can be used to return the next set of applications in the list.

Type: String

Required: No

### s3Bucket

An Amazon S3 bucket name to limit the search for revisions.

If set to null, all of the user's buckets are searched.

Type: String

Required: No

### s3KeyPrefix

A key prefix for the set of Amazon S3 objects to limit the search for revisions.

Type: String

Required: No

### sortBy

The column name to use to sort the list results:

- `registerTime`: Sort by the time the revisions were registered with AWS CodeDeploy.
- `firstUsedTime`: Sort by the time the revisions were first used in a deployment.
- `lastUsedTime`: Sort by the time the revisions were last used in a deployment.

If not specified or set to null, the results are returned in an arbitrary order.

Type: String

Valid Values: `registerTime` | `firstUsedTime` | `lastUsedTime`

Required: No

## sortOrder

The order in which to sort the list results:

- ascending: ascending order.
- descending: descending order.

If not specified, the results are sorted in ascending order.

If set to null, the results are sorted in an arbitrary order.

Type: String

Valid Values: ascending | descending

Required: No

## Response Syntax

```
{
  "nextToken": "string",
  "revisions": [
    {
      "appSpecContent": {
        "content": "string",
        "sha256": "string"
      },
      "gitHubLocation": {
        "commitId": "string",
        "repository": "string"
      },
      "revisionType": "string",
      "s3Location": {
        "bucket": "string",
        "bundleType": "string",
        "eTag": "string",
        "key": "string",
        "version": "string"
      },
      "string": {
        "content": "string",
        "sha256": "string"
      }
    }
  ]
}
```

```
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list application revisions call to return the next set of application revisions in the list.

Type: String

### revisions

A list of locations that contain the matching revisions.

Type: Array of [RevisionLocation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **BucketNameFilterRequiredException**

A bucket name is required, but was not provided.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidBucketNameFilterException**

The bucket name either doesn't exist or was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeployedStateFilterException**

The deployed state filter was specified in an invalid format.

HTTP Status Code: 400

### **InvalidKeyPrefixFilterException**

The specified key prefix filter was specified in an invalid format.

HTTP Status Code: 400

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

### **InvalidSortByException**

The column name to sort by is either not present or was specified in an invalid format.

HTTP Status Code: 400

### **InvalidSortOrderException**

The sort order was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of `ListApplicationRevisions`.

## Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 45
X-Amz-Target: CodeDeploy_20141006.ListApplicationRevisions
X-Amz-Date: 20160707T021008Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 8000a419-88e2-11e5-b497-75c493756c4d
Content-Type: application/x-amz-json-1.1
Content-Length: 611

{
  "revisions": [
    {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "3fdd7b3456697a096d5af1d649e26a4a",
        "key": "North-App.zip"
      }
    },
    {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "\"3fdd7b9142497a096d5af1d649e26a4a\"",

```

```
        "key": "North-App.zip"
      }
    },
    {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "ffe5402cff48b652bf903700453f7408",
        "key": "North-App.zip"
      }
    },
    {
      "revisionType": "S3",
      "s3Location": {
        "bucket": "project-1234",
        "bundleType": "zip",
        "eTag": "fff9102vdf48b652bf903700453f7408",
        "key": "North-App.zip"
      }
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListApplications

Lists the applications registered with the user or AWS account.

## Request Syntax

```
{
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [nextToken](#)

An identifier returned from the previous list applications call. It can be used to return the next set of applications in the list.

Type: String

Required: No

## Response Syntax

```
{
  "applications": [ "string" ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [applications](#)

A list of application names.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list applications call to return the next set of applications in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InvalidNextTokenException

The next token was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of ListApplications.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: CodeDeploy_20141006.ListApplications
X-Amz-Date: 20160707T021119Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: aa51ec1f-88e2-11e5-9958-cd5094947bf1
Content-Type: application/x-amz-json-1.1
Content-Length: 211

{
  "applications": [
    "TestApp-eu-west-1",
    "ProductionApp-us-west-2",
    "TestApp-us-east-1",
    "ProductionApp-us-east-1",
    "TestApp-ap-northeast-1",
    "ProductionApp-eu-central-1",
    "ProductionApp-us-west-2"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeploymentConfigs

Lists the deployment configurations with the user or AWS account.

## Request Syntax

```
{
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### nextToken

An identifier returned from the previous ListDeploymentConfigs call. It can be used to return the next set of deployment configurations in the list.

Type: String

Required: No

## Response Syntax

```
{
  "deploymentConfigsList": [ "string" ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## deploymentConfigsList

A list of deployment configurations, including built-in configurations such as `CodeDeployDefault.OneAtATime`.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

## nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list deployment configurations call to return the next set of deployment configurations in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `ListDeploymentConfigs`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: CodeDeploy_20141006.ListDeploymentConfigs
X-Amz-Date: 20160707T021208Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{

}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: c7c4ae40-88e2-11e5-9958-cd5094947bf1
Content-Type: application/x-amz-json-1.1
Content-Length: 223

{
  "deploymentConfigsList": [
    "CustomConfig.One",
    "ThreeQuartersHealthy",
    "MyCustomDeploymentConfig-OneAtATime",
    "Project-ABConfig",
    "CodeDeployDefault.OneAtATime",
    "CodeDeployDefault.AllAtOnce",
    "CodeDeployDefault.HalfAtATime"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeploymentGroups

Lists the deployment groups for an application registered with the AWS user or AWS account.

## Request Syntax

```
{  
  "applicationName": "string",  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### nextToken

An identifier returned from the previous list deployment groups call. It can be used to return the next set of deployment groups in the list.

Type: String

Required: No

## Response Syntax

```
{  
  "applicationName": "string",  
  "deploymentGroups": [ "string" ],  
  "nextToken": "string"  
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationName

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

### deploymentGroups

A list of deployment group names.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list deployment groups call to return the next set of deployment groups in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of ListDeploymentGroups.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 45
X-Amz-Target: CodeDeploy_20141006.ListDeploymentGroups
X-Amz-Date: 20160707T021406Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1"
}
```

### **Sample Response**

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0f5599cb-88e3-11e5-a087-ab26ee53e16e
```

```
Content-Type: application/x-amz-json-1.1
```

```
Content-Length: 95
```

```
{
  "applicationName": "TestApp-us-east-1",
  "deploymentGroups": [
    "dep-group-def-456"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeploymentInstances

## Note

The newer `BatchGetDeploymentTargets` should be used instead because it works with all compute types. `ListDeploymentInstances` throws an exception if it is used with a compute platform other than EC2/On-premises or AWS Lambda.

Lists the instance for a deployment associated with the user or AWS account.

## Request Syntax

```
{
  "deploymentId": "string",
  "instanceStatusFilter": [ "string" ],
  "instanceTypeFilter": [ "string" ],
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

### instanceStatusFilter

A subset of instances to list by status:

- `Pending`: Include those instances with pending deployments.
- `InProgress`: Include those instances where deployments are still in progress.
- `Succeeded`: Include those instances with successful deployments.

- **Failed:** Include those instances with failed deployments.
- **Skipped:** Include those instances with skipped deployments.
- **Unknown:** Include those instances with deployments in an unknown state.

Type: Array of strings

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

### instanceTypeFilter

The set of instances in a blue/green deployment, either those in the original environment ("BLUE") or those in the replacement environment ("GREEN"), for which you want to view instance information.

Type: Array of strings

Valid Values: Blue | Green

Required: No

### nextToken

An identifier returned from the previous list deployment instances call. It can be used to return the next set of deployment instances in the list.

Type: String

Required: No

## Response Syntax

```
{  
  "instancesList": [ "string" ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### instancesList

A list of instance IDs.

Type: Array of strings

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list deployment instances call to return the next set of deployment instances in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **DeploymentNotStartedException**

The specified deployment has not started.

HTTP Status Code: 400

### **InvalidComputePlatformException**

The computePlatform is invalid. The computePlatform should be Lambda, Server, or ECS.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentInstanceTypeException**

An instance type was specified for an in-place deployment. Instance types are supported for blue/green deployments only.

HTTP Status Code: 400

### **InvalidInstanceStatusException**

The specified instance status does not exist.

HTTP Status Code: 400

### **InvalidInstanceTypeException**

An invalid instance type was specified for instances in a blue/green deployment. Valid values include "Blue" for an original environment and "Green" for a replacement environment.

HTTP Status Code: 400

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTargetFilterNameException**

The target filter name is invalid.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of ListDeploymentInstances.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.ListDeploymentInstances
X-Amz-Date: 20160707T021610Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentId": "d-74D25NS7C"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 57a7b3d6-88e3-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 32

{
  "instancesList": [
    "i-b2f7jfd0d00EXAMPLE"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeployments

Lists the deployments in a deployment group for an application registered with the user or AWS account.

## Request Syntax

```
{
  "applicationName": "string",
  "createTimeRange": {
    "end": number,
    "start": number
  },
  "deploymentGroupName": "string",
  "externalId": "string",
  "includeOnlyStatuses": [ "string" ],
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The name of an AWS CodeDeploy application associated with the user or AWS account.

#### Note

If `applicationName` is specified, then `deploymentGroupName` must be specified. If it is not specified, then `deploymentGroupName` must not be specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## createTimeRange

A time range (start and end) for returning a subset of the list of deployments.

Type: [TimeRange](#) object

Required: No

## deploymentGroupName

The name of a deployment group for the specified application.

### Note

If `deploymentGroupName` is specified, then `applicationName` must be specified. If it is not specified, then `applicationName` must not be specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## externalId

The unique ID of an external resource for returning deployments linked to the external resource.

Type: String

Required: No

## includeOnlyStatuses

A subset of deployments to list by status:

- **Created:** Include created deployments in the resulting list.
- **Queued:** Include queued deployments in the resulting list.
- **In Progress:** Include in-progress deployments in the resulting list.
- **Succeeded:** Include successful deployments in the resulting list.
- **Failed:** Include failed deployments in the resulting list.
- **Stopped:** Include stopped deployments in the resulting list.

Type: Array of strings

Valid Values: Created | Queued | InProgress | Baking | Succeeded | Failed | Stopped | Ready

Required: No

### nextToken

An identifier returned from the previous list deployments call. It can be used to return the next set of deployments in the list.

Type: String

Required: No

## Response Syntax

```
{
  "deployments": [ "string" ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deployments

A list of deployment IDs.

Type: Array of strings

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list deployments call to return the next set of deployments in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentStatusException**

The specified deployment status doesn't exist or cannot be determined.

HTTP Status Code: 400

### **InvalidExternalIdException**

The external ID was specified in an invalid format.

HTTP Status Code: 400

### **InvalidInputException**

The input was specified in an invalid format.

HTTP Status Code: 400

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTimeRangeException**

The specified time range was specified in an invalid format.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of ListDeployments.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 99
X-Amz-Target: CodeDeploy_20141006.ListDeployments
X-Amz-Date: 20160707T021907Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1",
  "deploymentGroupName": "dep-group-def-456"
```

```
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: c15efe85-88e3-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 45

{
  "deployments": [
    "d-74D87AS7C",
    "d-D1EGTDV4C"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeploymentTargets

Returns an array of target IDs that are associated a deployment.

## Request Syntax

```
{
  "deploymentId": "string",
  "nextToken": "string",
  "targetFilters": {
    "string" : [ "string" ]
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

### nextToken

A token identifier returned from the previous ListDeploymentTargets call. It can be used to return the next set of deployment targets in the list.

Type: String

Required: No

### targetFilters

A key used to filter the returned targets. The two valid values are:

- **TargetStatus** - A TargetStatus filter string can be Failed, InProgress, Pending, Ready, Skipped, Succeeded, or Unknown.
- **ServerInstanceLabel** - A ServerInstanceLabel filter string can be Blue or Green.

Type: String to array of strings map

Valid Keys: TargetStatus | ServerInstanceLabel

Required: No

## Response Syntax

```
{  
  "nextToken": "string",  
  "targetIds": [ "string" ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

If a large amount of information is returned, a token identifier is also returned. It can be used in a subsequent `ListDeploymentTargets` call to return the next set of deployment targets in the list.

Type: String

### targetIds

The unique IDs of deployment targets.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **DeploymentNotStartedException**

The specified deployment has not started.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentInstanceTypeException**

An instance type was specified for an in-place deployment. Instance types are supported for blue/green deployments only.

HTTP Status Code: 400

### **InvalidInstanceStatusException**

The specified instance status does not exist.

HTTP Status Code: 400

### **InvalidInstanceTypeException**

An invalid instance type was specified for instances in a blue/green deployment. Valid values include "Blue" for an original environment and "Green" for a replacement environment.

HTTP Status Code: 400

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTargetFilterNameException**

The target filter name is invalid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGitHubAccountTokenNames

Lists the names of stored connections to GitHub accounts.

## Request Syntax

```
{  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### nextToken

An identifier returned from the previous ListGitHubAccountTokenNames call. It can be used to return the next set of names in the list.

Type: String

Required: No

## Response Syntax

```
{  
  "nextToken": "string",  
  "tokenNameList": [ "string" ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent `ListGitHubAccountTokenNames` call to return the next set of names in the list.

Type: String

## tokenNameList

A list of names of connections to GitHub accounts.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InvalidNextTokenException**

The next token was specified in an invalid format.

HTTP Status Code: 400

### **OperationNotSupportedException**

The API used does not support the deployment.

HTTP Status Code: 400

### **ResourceValidationException**

The specified resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListOnPremisesInstances

Gets a list of names for one or more on-premises instances.

Unless otherwise specified, both registered and deregistered on-premises instance names are listed. To list only registered or deregistered on-premises instance names, use the registration status parameter.

## Request Syntax

```
{
  "nextToken": "string",
  "registrationStatus": "string",
  "tagFilters": [
    {
      "Key": "string",
      "Type": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### nextToken

An identifier returned from the previous list on-premises instances call. It can be used to return the next set of on-premises instances in the list.

Type: String

Required: No

### registrationStatus

The registration status of the on-premises instances:

- **Deregistered:** Include deregistered on-premises instances in the resulting list.

- **Registered:** Include registered on-premises instances in the resulting list.

Type: String

Valid Values: Registered | Deregistered

Required: No

### tagFilters

The on-premises instance tags that are used to restrict the on-premises instance names returned.

Type: Array of [TagFilter](#) objects

Required: No

## Response Syntax

```
{
  "instanceNames": [ "string" ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### instanceNames

The list of matching on-premises instance names.

Type: Array of strings

### nextToken

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list on-premises instances call to return the next set of on-premises instances in the list.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InvalidNextTokenException

The next token was specified in an invalid format.

HTTP Status Code: 400

### InvalidRegistrationStatusException

The registration status was specified in an invalid format.

HTTP Status Code: 400

### InvalidTagFilterException

The tag filter was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of ListOnPremisesInstances.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: CodeDeploy_20141006.ListOnPremisesInstances
X-Amz-Date: 20160707T022010Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e69e5d14-88e3-11e5-bb59-fb8eade0dfc3
Content-Type: application/x-amz-json-1.1
Content-Length: 63

{
  "instanceNames": [
    "grp-a-inst-1",
    "grp-a-inst-2"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Returns a list of tags for the resource identified by a specified Amazon Resource Name (ARN). Tags are used to organize and categorize your CodeDeploy resources.

## Request Syntax

```
{  
  "NextToken": "string",  
  "ResourceArn": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

An identifier returned from the previous `ListTagsForResource` call. It can be used to return the next set of applications in the list.

Type: String

Required: No

### ResourceArn

The ARN of a CodeDeploy resource. `ListTagsForResource` returns all the tags associated with the resource that is identified by the `ResourceArn`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

## Response Syntax

```
{  
  "NextToken": "string",  
}
```

```
"Tags": [  
  {  
    "Key": "string",  
    "Value": "string"  
  }  
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

If a large amount of information is returned, an identifier is also returned. It can be used in a subsequent list application revisions call to return the next set of application revisions in the list.

Type: String

### [Tags](#)

A list of tags returned by `ListTagsForResource`. The tags are associated with the resource identified by the input `ResourceArn` parameter.

Type: Array of [Tag](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ArnNotSupportedException**

The specified ARN is not supported. For example, it might be an ARN for a resource that is not expected.

HTTP Status Code: 400

### **InvalidArnException**

The specified ARN is not in a valid format.

HTTP Status Code: 400

### **ResourceArnRequiredException**

The ARN of a resource is required, but was not found.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutLifecycleEventHookExecutionStatus

Sets the result of a Lambda validation function. The function validates lifecycle hooks during a deployment that uses the AWS Lambda or Amazon ECS compute platform. For AWS Lambda deployments, the available lifecycle hooks are `BeforeAllowTraffic` and `AfterAllowTraffic`. For Amazon ECS deployments, the available lifecycle hooks are `BeforeInstall`, `AfterInstall`, `AfterAllowTestTraffic`, `BeforeAllowTraffic`, and `AfterAllowTraffic`. Lambda validation functions return `Succeeded` or `Failed`. For more information, see [AppSpec 'hooks' Section for an AWS Lambda Deployment](#) and [AppSpec 'hooks' Section for an Amazon ECS Deployment](#).

## Request Syntax

```
{
  "deploymentId": "string",
  "lifecycleEventHookExecutionId": "string",
  "status": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a deployment. Pass this ID to a Lambda function that validates a deployment lifecycle event.

Type: String

Required: No

### lifecycleEventHookExecutionId

The execution ID of a deployment's lifecycle hook. A deployment lifecycle hook is specified in the `hooks` section of the AppSpec file.

Type: String

Required: No

### status

The result of a Lambda function that validates a deployment lifecycle event. The values listed in **Valid Values** are valid for lifecycle statuses in general; however, only Succeeded and Failed can be passed successfully in your API call.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown

Required: No

## Response Syntax

```
{
  "lifecycleEventHookExecutionId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### lifecycleEventHookExecutionId

The execution ID of the lifecycle event hook. A hook is specified in the hooks section of the deployment's AppSpec file.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentIdRequiredException**

At least one deployment ID must be specified.

HTTP Status Code: 400

### **InvalidDeploymentIdException**

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

### **InvalidLifecycleEventHookExecutionIdException**

A lifecycle event hook is invalid. Review the hooks section in your AppSpec file to ensure the lifecycle events and hooks functions are valid.

HTTP Status Code: 400

### **InvalidLifecycleEventHookExecutionStatusException**

The result of a Lambda validation function that verifies a lifecycle event is invalid. It should return `Succeeded` or `Failed`.

HTTP Status Code: 400

### **LifecycleEventAlreadyCompletedException**

An attempt to return the status of an already completed lifecycle event occurred.

HTTP Status Code: 400

### **UnsupportedActionForDeploymentTypeException**

A call was submitted that is not supported for the specified deployment type.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RegisterApplicationRevision

Registers with AWS CodeDeploy a revision for the specified application.

## Request Syntax

```
{
  "applicationName": "string",
  "description": "string",
  "revision": {
    "appSpecContent": {
      "content": "string",
      "sha256": "string"
    },
    "gitHubLocation": {
      "commitId": "string",
      "repository": "string"
    },
    "revisionType": "string",
    "s3Location": {
      "bucket": "string",
      "bundleType": "string",
      "eTag": "string",
      "key": "string",
      "version": "string"
    },
    "string": {
      "content": "string",
      "sha256": "string"
    }
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [applicationName](#)

The name of an AWS CodeDeploy application associated with the user or AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### description

A comment about the revision.

Type: String

Required: No

### revision

Information about the application revision to register, including type and location.

Type: [RevisionLocation](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DescriptionTooLongException**

The description is too long.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidRevisionException**

The revision was specified in an invalid format.

HTTP Status Code: 400

### **RevisionRequiredException**

The revision ID was not specified.

HTTP Status Code: 400

## **Examples**

### **Example**

This example illustrates one usage of RegisterApplicationRevision.

### **Sample Request**

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 257
X-Amz-Target: CodeDeploy_20141006.RegisterApplicationRevision
X-Amz-Date: 20160707T024712Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1",
  "description": "New application registration",
```

```
"revision": {
  "revisionType": "S3",
  "s3Location": {
    "bundleType": "zip",
    "eTag": "3fdd7b9196697a044d5af1d649e26a4a",
    "bucket": "project-1234",
    "key": "South-App.zip"
  }
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RegisterOnPremisesInstance

Registers an on-premises instance.

## Note

Only one IAM ARN (an IAM session ARN or IAM user ARN) is supported in the request. You cannot use both.

## Request Syntax

```
{
  "iamSessionArn": "string",
  "iamUserArn": "string",
  "instanceName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [iamSessionArn](#)

The ARN of the IAM session to associate with the on-premises instance.

Type: String

Required: No

### [iamUserArn](#)

The ARN of the user to associate with the on-premises instance.

Type: String

Required: No

### [instanceName](#)

The name of the on-premises instance to register.

Type: String

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **IamArnRequiredException**

No IAM ARN was included in the request. You must use an IAM session ARN or user ARN in the request.

HTTP Status Code: 400

### **IamSessionArnAlreadyRegisteredException**

The request included an IAM session ARN that has already been used to register a different instance.

HTTP Status Code: 400

### **IamUserArnAlreadyRegisteredException**

The specified user ARN is already registered with an on-premises instance.

HTTP Status Code: 400

### **IamUserArnRequiredException**

An user ARN was not specified.

HTTP Status Code: 400

### **InstanceNameAlreadyRegisteredException**

The specified on-premises instance name is already registered.

HTTP Status Code: 400

## InstanceNameRequiredException

An on-premises instance name was not specified.

HTTP Status Code: 400

## InvalidIamSessionArnException

The IAM session ARN was specified in an invalid format.

HTTP Status Code: 400

## InvalidIamUserArnException

The user ARN was specified in an invalid format.

HTTP Status Code: 400

## InvalidInstanceNameException

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

## MultipleIamArnsProvidedException

Both an user ARN and an IAM session ARN were included in the request. Use only one ARN type.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of RegisterOnPremisesInstance.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 257
X-Amz-Target: CodeDeploy_20141006.RegisterOnPremisesInstance
X-Amz-Date: 20160707T024712Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "IamUserArn": "arn:aws:iam::444455556666:user/janedoe",
  "instanceName": "grp-o-inst-5"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RemoveTagsFromOnPremisesInstances

Removes one or more tags from one or more on-premises instances.

## Request Syntax

```
{
  "instanceNames": [ "string" ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [instanceNames](#)

The names of the on-premises instances from which to remove tags.

Type: Array of strings

Required: Yes

### [tags](#)

The tag key-value pairs to remove from the on-premises instances.

Type: Array of [Tag](#) objects

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InstanceLimitExceededException**

The maximum number of allowed on-premises instances in a single call was exceeded.

HTTP Status Code: 400

### **InstanceNameRequiredException**

An on-premises instance name was not specified.

HTTP Status Code: 400

### **InstanceNotRegisteredException**

The specified on-premises instance is not registered.

HTTP Status Code: 400

### **InvalidInstanceNameException**

The on-premises instance name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidTagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

### **TagLimitExceededException**

The maximum allowed number of tags was exceeded.

HTTP Status Code: 400

### **TagRequiredException**

A tag was not specified.

HTTP Status Code: 400

# Examples

## Example

This example illustrates one usage of `RemoveTagsFromOnPremisesInstances`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.RemoveTagsFromOnPremisesInstances
X-Amz-Date: 20160707T025157Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "instanceNames": [
    "i-b2f7jfd00EXAMPLE",
    "i-u3d8xa3m00EXAMPLE"
  ],
  "tags": [
    {
      "Key": "Name",
      "Value": "Project-765"
    }
  ]
}
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SkipWaitTimeForInstanceTermination

In a blue/green deployment, overrides any specified wait time and starts terminating instances immediately after the traffic routing is complete.

## Request Syntax

```
{  
  "deploymentId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### deploymentId

The unique ID of a blue/green deployment for which you want to skip the instance termination wait time.

Type: String

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentAlreadyCompletedException**

The deployment is already complete.

HTTP Status Code: 400

## DeploymentDoesNotExistException

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

## DeploymentIdRequiredException

At least one deployment ID must be specified.

HTTP Status Code: 400

## DeploymentNotStartedException

The specified deployment has not started.

HTTP Status Code: 400

## InvalidDeploymentIdException

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## UnsupportedActionForDeploymentTypeException

A call was submitted that is not supported for the specified deployment type.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `SkipWaitTimeForInstanceTermination`.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.SkipWaitTimeForInstanceTermination
X-Amz-Date: 20170412T203610Z
User-Agent: aws-cli/1.11.76 Python/2.7.9 Windows/8 botocore/1.5.39
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE
```

```
{"deploymentId": "d-UBCT41FSL"}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StopDeployment

Attempts to stop an ongoing deployment.

## Request Syntax

```
{  
  "autoRollbackEnabled": boolean,  
  "deploymentId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### autoRollbackEnabled

Indicates, when a deployment is stopped, whether instances that have been updated should be rolled back to the previous version of the application revision.

Type: Boolean

Required: No

### deploymentId

The unique ID of a deployment.

Type: String

Required: Yes

## Response Syntax

```
{  
  "status": "string",  
  "statusMessage": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### status

The status of the stop deployment operation:

- Pending: The stop operation is pending.
- Succeeded: The stop operation was successful.

Type: String

Valid Values: Pending | Succeeded | Forced

### statusMessage

An accompanying status message.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **DeploymentAlreadyCompletedException**

The deployment is already complete.

HTTP Status Code: 400

### **DeploymentDoesNotExistException**

The deployment with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

## DeploymentIdRequiredException

At least one deployment ID must be specified.

HTTP Status Code: 400

## InvalidDeploymentIdException

At least one of the deployment IDs was specified in an invalid format.

HTTP Status Code: 400

## UnsupportedActionForDeploymentTypeException

A call was submitted that is not supported for the specified deployment type.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of StopDeployment.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: CodeDeploy_20141006.StopDeployment
X-Amz-Date: 20160707T025157Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "deploymentId": "d-LGUMS25CC"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 57a24279-88e8-11e5-a087-ab26ee53e16e
Content-Type: application/x-amz-json-1.1
Content-Length: 114

{
  "status": "Pending",
  "statusMessage": "Stopping Pending. Stopping to schedule commands in the deployment instances"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Associates the list of tags in the input `Tags` parameter with the resource identified by the `ResourceArn` input parameter.

## Request Syntax

```
{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [ResourceArn](#)

The ARN of a resource, such as a CodeDeploy application or deployment group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

### [Tags](#)

A list of tags that `TagResource` associates with a resource. The resource is identified by the `ResourceArn` input parameter.

Type: Array of [Tag](#) objects

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ArnNotSupportedException**

The specified ARN is not supported. For example, it might be an ARN for a resource that is not expected.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **InvalidArnException**

The specified ARN is not in a valid format.

HTTP Status Code: 400

### **InvalidTagsToAddException**

The specified tags are not valid.

HTTP Status Code: 400

### **ResourceArnRequiredException**

The ARN of a resource is required, but was not found.

HTTP Status Code: 400

### **TagRequiredException**

A tag was not specified.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Disassociates a resource from a list of tags. The resource is identified by the `ResourceArn` input parameter. The tags are identified by the list of keys in the `TagKeys` input parameter.

## Request Syntax

```
{
  "ResourceArn": "string",
  "TagKeys": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [ResourceArn](#)

The Amazon Resource Name (ARN) that specifies from which resource to disassociate the tags with the keys in the `TagKeys` input parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

### [TagKeys](#)

A list of keys of Tag objects. The Tag objects identified by the keys are disassociated from the resource specified by the `ResourceArn` input parameter.

Type: Array of strings

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ArnNotSupportedException**

The specified ARN is not supported. For example, it might be an ARN for a resource that is not expected.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **InvalidArnException**

The specified ARN is not in a valid format.

HTTP Status Code: 400

### **InvalidTagsToAddException**

The specified tags are not valid.

HTTP Status Code: 400

### **ResourceArnRequiredException**

The ARN of a resource is required, but was not found.

HTTP Status Code: 400

## TagRequiredException

A tag was not specified.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateApplication

Changes the name of an application.

## Request Syntax

```
{
  "applicationName": "string",
  "newApplicationName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### applicationName

The current name of the application you want to change.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### newApplicationName

The new name to give the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ApplicationAlreadyExistsException**

An application with the specified name with the user or AWS account already exists.

HTTP Status Code: 400

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of UpdateApplication.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 95
X-Amz-Target: CodeDeploy_20141006.UpdateApplication
X-Amz-Date: 20160707T025419Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "applicationName": "TestApp-us-east-1",
  "newApplicationName": "TestApp-us-west-2"
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4ccc9cf0-88c9-11e5-8ce3-2704437d0309
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDeploymentGroup

Changes information about a deployment group.

## Request Syntax

```
{
  "alarmConfiguration": {
    "alarms": [
      {
        "name": "string"
      }
    ],
    "enabled": boolean,
    "ignorePollAlarmFailure": boolean
  },
  "applicationName": "string",
  "autoRollbackConfiguration": {
    "enabled": boolean,
    "events": [ "string" ]
  },
  "autoScalingGroups": [ "string" ],
  "blueGreenDeploymentConfiguration": {
    "deploymentReadyOption": {
      "actionOnTimeout": "string",
      "waitTimeInMinutes": number
    },
    "greenFleetProvisioningOption": {
      "action": "string"
    },
    "terminateBlueInstancesOnDeploymentSuccess": {
      "action": "string",
      "terminationWaitTimeInMinutes": number
    }
  },
  "currentDeploymentGroupName": "string",
  "deploymentConfigName": "string",
  "deploymentStyle": {
    "deploymentOption": "string",
    "deploymentType": "string"
  },
  "ec2TagFilters": [
    {
```

```
    "Key": "string",
    "Type": "string",
    "Value": "string"
  }
],
"ec2TagSet": {
  "ec2TagSetList": [
    [
      {
        "Key": "string",
        "Type": "string",
        "Value": "string"
      }
    ]
  ]
},
"ecsServices": [
  {
    "clusterName": "string",
    "serviceName": "string"
  }
],
"loadBalancerInfo": {
  "elbInfoList": [
    {
      "name": "string"
    }
  ],
  "targetGroupInfoList": [
    {
      "name": "string"
    }
  ],
  "targetGroupPairInfoList": [
    {
      "prodTrafficRoute": {
        "listenerArns": [ "string" ]
      },
      "targetGroups": [
        {
          "name": "string"
        }
      ]
    },
    "testTrafficRoute": {
```

```
        "listenerArns": [ "string" ]
      }
    }
  ],
  "newDeploymentGroupName": "string",
  "onPremisesInstanceTagFilters": [
    {
      "Key": "string",
      "Type": "string",
      "Value": "string"
    }
  ],
  "onPremisesTagSet": {
    "onPremisesTagSetList": [
      [
        {
          "Key": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    ]
  },
  "outdatedInstancesStrategy": "string",
  "serviceRoleArn": "string",
  "terminationHookEnabled": boolean,
  "triggerConfigurations": [
    {
      "triggerEvents": [ "string" ],
      "triggerName": "string",
      "triggerTargetArn": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## alarmConfiguration

Information to add or change about Amazon CloudWatch alarms when the deployment group is updated.

Type: [AlarmConfiguration](#) object

Required: No

## applicationName

The application name that corresponds to the deployment group to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## autoRollbackConfiguration

Information for an automatic rollback configuration that is added or changed when a deployment group is updated.

Type: [AutoRollbackConfiguration](#) object

Required: No

## autoScalingGroups

The replacement list of Auto Scaling groups to be included in the deployment group, if you want to change them.

- To keep the Auto Scaling groups, enter their names or do not specify this parameter.
- To remove Auto Scaling groups, specify a non-null empty list of Auto Scaling group names to detach all CodeDeploy-managed Auto Scaling lifecycle hooks. For examples, see [Amazon EC2 instances in an Amazon EC2 Auto Scaling group fail to launch and receive the error "Heartbeat Timeout"](#) in the *AWS CodeDeploy User Guide*.

Type: Array of strings

Required: No

## blueGreenDeploymentConfiguration

Information about blue/green deployment options for a deployment group.

Type: [BlueGreenDeploymentConfiguration](#) object

Required: No

### [currentDeploymentGroupName](#)

The current name of the deployment group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### [deploymentConfigName](#)

The replacement deployment configuration name to use, if you want to change it.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### [deploymentStyle](#)

Information about the type of deployment, either in-place or blue/green, you want to run and whether to route deployment traffic behind a load balancer.

Type: [DeploymentStyle](#) object

Required: No

### [ec2TagFilters](#)

The replacement set of Amazon EC2 tags on which to filter, if you want to change them. To keep the existing tags, enter their names. To remove tags, do not enter any tag names.

Type: Array of [EC2TagFilter](#) objects

Required: No

### [ec2TagSet](#)

Information about groups of tags applied to on-premises instances. The deployment group includes only Amazon EC2 instances identified by all the tag groups.

Type: [EC2TagSet](#) object

Required: No

### [ecsServices](#)

The target Amazon ECS services in the deployment group. This applies only to deployment groups that use the Amazon ECS compute platform. A target Amazon ECS service is specified as an Amazon ECS cluster and service name pair using the format `<clustername>:<servicename>`.

Type: Array of [ECSService](#) objects

Required: No

### [loadBalancerInfo](#)

Information about the load balancer used in a deployment.

Type: [LoadBalancerInfo](#) object

Required: No

### [newDeploymentGroupName](#)

The new name of the deployment group, if you want to change it.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### [onPremisesInstanceTagFilters](#)

The replacement set of on-premises instance tags on which to filter, if you want to change them. To keep the existing tags, enter their names. To remove tags, do not enter any tag names.

Type: Array of [TagFilter](#) objects

Required: No

### [onPremisesTagSet](#)

Information about an on-premises instance tag set. The deployment group includes only on-premises instances identified by all the tag groups.

Type: [OnPremisesTagSet](#) object

Required: No

### outdatedInstancesStrategy

Indicates what happens when new Amazon EC2 instances are launched mid-deployment and do not receive the deployed application revision.

If this option is set to UPDATE or is unspecified, CodeDeploy initiates one or more 'auto-update outdated instances' deployments to apply the deployed application revision to the new Amazon EC2 instances.

If this option is set to IGNORE, CodeDeploy does not initiate a deployment to update the new Amazon EC2 instances. This may result in instances having different revisions.

Type: String

Valid Values: UPDATE | IGNORE

Required: No

### serviceRoleArn

A replacement ARN for the service role, if you want to change it.

Type: String

Required: No

### terminationHookEnabled

This parameter only applies if you are using CodeDeploy with Amazon EC2 Auto Scaling. For more information, see [Integrating CodeDeploy with Amazon EC2 Auto Scaling](#) in the *AWS CodeDeploy User Guide*.

Set `terminationHookEnabled` to `true` to have CodeDeploy install a termination hook into your Auto Scaling group when you update a deployment group. When this hook is installed, CodeDeploy will perform termination deployments.

For information about termination deployments, see [Enabling termination deployments during Auto Scaling scale-in events](#) in the *AWS CodeDeploy User Guide*.

For more information about Auto Scaling scale-in events, see the [Scale in](#) topic in the *Amazon EC2 Auto Scaling User Guide*.

Type: Boolean

Required: No

## [triggerConfigurations](#)

Information about triggers to change when the deployment group is updated. For examples, see [Edit a Trigger in a CodeDeploy Deployment Group](#) in the *AWS CodeDeploy User Guide*.

Type: Array of [TriggerConfig](#) objects

Required: No

## Response Syntax

```
{
  "hooksNotCleanedUp": [
    {
      "hook": "string",
      "name": "string",
      "terminationHook": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [hooksNotCleanedUp](#)

If the output contains no data, and the corresponding deployment group contained at least one Auto Scaling group, AWS CodeDeploy successfully removed all corresponding Auto Scaling lifecycle event hooks from the AWS account. If the output contains data, AWS CodeDeploy could not remove some Auto Scaling lifecycle event hooks from the AWS account.

Type: Array of [AutoScalingGroup](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AlarmsLimitExceededException**

The maximum number of alarms for a deployment group (10) was exceeded.

HTTP Status Code: 400

### **ApplicationDoesNotExistException**

The application does not exist with the user or AWS account.

HTTP Status Code: 400

### **ApplicationNameRequiredException**

The minimum number of required application names was not specified.

HTTP Status Code: 400

### **DeploymentConfigDoesNotExistException**

The deployment configuration does not exist with the user or AWS account.

HTTP Status Code: 400

### **DeploymentGroupAlreadyExistsException**

A deployment group with the specified name with the user or AWS account already exists.

HTTP Status Code: 400

### **DeploymentGroupDoesNotExistException**

The named deployment group with the user or AWS account does not exist.

HTTP Status Code: 400

### **DeploymentGroupNameRequiredException**

The deployment group name was not specified.

HTTP Status Code: 400

### **ECSServiceMappingLimitExceededException**

The Amazon ECS service is associated with more than one deployment groups. An Amazon ECS service can be associated with only one deployment group.

HTTP Status Code: 400

## **InvalidAlarmConfigException**

The format of the alarm configuration is invalid. Possible causes include:

- The alarm list is null.
- The alarm object is null.
- The alarm name is empty or null or exceeds the limit of 255 characters.
- Two alarms with the same name have been specified.
- The alarm configuration is enabled, but the alarm list is empty.

HTTP Status Code: 400

## **InvalidApplicationNameException**

The application name was specified in an invalid format.

HTTP Status Code: 400

## **InvalidAutoRollbackConfigException**

The automatic rollback configuration was specified in an invalid format. For example, automatic rollback is enabled, but an invalid triggering event type or no event types were listed.

HTTP Status Code: 400

## **InvalidAutoScalingGroupException**

The Auto Scaling group was specified in an invalid format or does not exist.

HTTP Status Code: 400

## **InvalidBlueGreenDeploymentConfigurationException**

The configuration for the blue/green deployment group was provided in an invalid format. For information about deployment configuration format, see [CreateDeploymentConfig](#).

HTTP Status Code: 400

## **InvalidDeploymentConfigNameException**

The deployment configuration name was specified in an invalid format.

HTTP Status Code: 400

## **InvalidDeploymentGroupNameException**

The deployment group name was specified in an invalid format.

HTTP Status Code: 400

### **InvalidDeploymentStyleException**

An invalid deployment style was specified. Valid deployment types include "IN\_PLACE" and "BLUE\_GREEN." Valid deployment options include "WITH\_TRAFFIC\_CONTROL" and "WITHOUT\_TRAFFIC\_CONTROL."

HTTP Status Code: 400

### **InvalidEC2TagCombinationException**

A call was submitted that specified both Ec2TagFilters and Ec2TagSet, but only one of these data types can be used in a single call.

HTTP Status Code: 400

### **InvalidEC2TagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

### **InvalidECSServiceException**

The Amazon ECS service identifier is not valid.

HTTP Status Code: 400

### **InvalidInputException**

The input was specified in an invalid format.

HTTP Status Code: 400

### **InvalidLoadBalancerInfoException**

An invalid load balancer name, or no load balancer name, was specified.

HTTP Status Code: 400

### **InvalidOnPremisesTagCombinationException**

A call was submitted that specified both OnPremisesTagFilters and OnPremisesTagSet, but only one of these data types can be used in a single call.

HTTP Status Code: 400

## **InvalidRoleException**

The service role ARN was specified in an invalid format. Or, if an Auto Scaling group was specified, the specified service role does not grant the appropriate permissions to Amazon EC2 Auto Scaling.

HTTP Status Code: 400

## **InvalidTagException**

The tag was specified in an invalid format.

HTTP Status Code: 400

## **InvalidTargetGroupPairException**

A target group pair associated with this deployment is not valid.

HTTP Status Code: 400

## **InvalidTrafficRoutingConfigurationException**

The configuration that specifies how traffic is routed during a deployment is invalid.

HTTP Status Code: 400

## **InvalidTriggerConfigException**

The trigger was specified in an invalid format.

HTTP Status Code: 400

## **LifecycleHookLimitExceededException**

The limit for lifecycle hooks was exceeded.

HTTP Status Code: 400

## **TagSetListLimitExceededException**

The number of tag groups included in the tag set list exceeded the maximum allowed limit of 3.

HTTP Status Code: 400

## **ThrottlingException**

An API function was called too frequently.

HTTP Status Code: 400

## TriggerTargetsLimitExceededException

The maximum allowed number of triggers was exceeded.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of UpdateDeploymentGroup.

### Sample Request

```
POST / HTTP/1.1
Host: codedeploy.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 167
X-Amz-Target: CodeDeploy_20141006.UpdateDeploymentGroup
X-Amz-Date: 20160707T025726Z
User-Agent: aws-cli/1.10.6 Python/2.7.9 Windows/7 botocore/1.3.28
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20160707/us-east-1/
codedeploy/aws4_request,
SignedHeaders=content-type;host;user-agent;x-amz-date;x-amz-target,
Signature=39c3b3042cd2aEXAMPLE

{
  "alarmConfiguration": {
    "alarms": [
      {
        "name": "project-def-alarm"
      }
    ],
    "enabled": true,
    "ignorePollAlarmFailure": false
  },
  "applicationName": "TestApp-us-east-1",
  "autoRollbackConfiguration": {
    "enabled": true,
    "events": [
```

```
        "DEPLOYMENT_FAILURE"
    ]
},
"newDeploymentGroupName": "dep-group-def-765",
"currentDeploymentGroupName": "dep-group-def-456",
"triggerConfigurations": [
    {
        "triggerEvents": [
            "DeploymentFailure"
        ],
        "triggerName": "Trigger-group-us-east-1-deploy-fail",
        "triggerTargetArn": "arn:aws:sns:us-east-1:80398EXAMPLE:us-east-deploy-
fail"
    }
]
}
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 1bd3a202-88e9-11e5-a087-ab26ee53e16e
Content-Type: application/x-amz-json-1.1
Content-Length: 24

{
  "hooksNotCleanedUp": []
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS CodeDeploy API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Alarm](#)
- [AlarmConfiguration](#)
- [ApplicationInfo](#)
- [AppSpecContent](#)
- [AutoRollbackConfiguration](#)
- [AutoScalingGroup](#)
- [BlueGreenDeploymentConfiguration](#)
- [BlueInstanceTerminationOption](#)
- [CloudFormationTarget](#)
- [DeploymentConfigInfo](#)
- [DeploymentGroupInfo](#)
- [DeploymentInfo](#)
- [DeploymentOverview](#)
- [DeploymentReadyOption](#)
- [DeploymentStyle](#)
- [DeploymentTarget](#)
- [Diagnostics](#)
- [EC2TagFilter](#)
- [EC2TagSet](#)
- [ECSService](#)

- [ECSTarget](#)
- [ECSTaskSet](#)
- [ELBInfo](#)
- [ErrorInformation](#)
- [GenericRevisionInfo](#)
- [GitHubLocation](#)
- [GreenFleetProvisioningOption](#)
- [InstanceInfo](#)
- [InstanceSummary](#)
- [InstanceTarget](#)
- [LambdaFunctionInfo](#)
- [LambdaTarget](#)
- [LastDeploymentInfo](#)
- [LifecycleEvent](#)
- [LoadBalancerInfo](#)
- [MinimumHealthyHosts](#)
- [MinimumHealthyHostsPerZone](#)
- [OnPremisesTagSet](#)
- [RawString](#)
- [RelatedDeployments](#)
- [RevisionInfo](#)
- [RevisionLocation](#)
- [RollbackInfo](#)
- [S3Location](#)
- [Tag](#)
- [TagFilter](#)
- [TargetGroupInfo](#)
- [TargetGroupPairInfo](#)
- [TargetInstances](#)
- [TimeBasedCanary](#)

- [TimeBasedLinear](#)
- [TimeRange](#)
- [TrafficRoute](#)
- [TrafficRoutingConfig](#)
- [TriggerConfig](#)
- [ZonalConfig](#)

# Alarm

Information about an alarm.

## Contents

### name

The name of the alarm. Maximum length is 255 characters. Each alarm name can be used only once in a list of alarms.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AlarmConfiguration

Information about alarms associated with a deployment or deployment group.

## Contents

### alarms

A list of alarms configured for the deployment or deployment group. A maximum of 10 alarms can be added.

Type: Array of [Alarm](#) objects

Required: No

### enabled

Indicates whether the alarm configuration is enabled.

Type: Boolean

Required: No

### ignorePollAlarmFailure

Indicates whether a deployment should continue if information about the current state of alarms cannot be retrieved from Amazon CloudWatch. The default value is false.

- `true`: The deployment proceeds even if alarm status information can't be retrieved from Amazon CloudWatch.
- `false`: The deployment stops if alarm status information can't be retrieved from Amazon CloudWatch.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ApplicationInfo

Information about an application.

## Contents

### **applicationId**

The application ID.

Type: String

Required: No

### **applicationName**

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **computePlatform**

The destination platform type for deployment of the application (Lambda or Server).

Type: String

Valid Values: Server | Lambda | ECS | Kubernetes

Required: No

### **createTime**

The time at which the application was created.

Type: Timestamp

Required: No

### **gitHubAccountName**

The name for a connection to a GitHub account.

Type: String

Required: No

### **linkedToGitHub**

True if the user has authenticated with GitHub for the specified application. Otherwise, false.

Type: Boolean

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AppSpecContent

A revision for an AWS Lambda or Amazon ECS deployment that is a YAML-formatted or JSON-formatted string. For AWS Lambda and Amazon ECS deployments, the revision is the same as the AppSpec file. This method replaces the deprecated `RawString` data type.

## Contents

### **content**

The YAML-formatted or JSON-formatted revision string.

For an AWS Lambda deployment, the content includes a Lambda function name, the alias for its original version, and the alias for its replacement version. The deployment shifts traffic from the original version of the Lambda function to the replacement version.

For an Amazon ECS deployment, the content includes the task name, information about the load balancer that serves traffic to the container, and more.

For both types of deployments, the content can specify Lambda functions that run at specified hooks, such as `BeforeInstall`, during a deployment.

Type: String

Required: No

### **sha256**

The SHA256 hash value of the revision content.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# AutoRollbackConfiguration

Information about a configuration for automatically rolling back to a previous version of an application revision when a deployment is not completed successfully.

## Contents

### enabled

Indicates whether a defined automatic rollback configuration is currently enabled.

Type: Boolean

Required: No

### events

The event type or types that trigger a rollback.

Type: Array of strings

Valid Values: DEPLOYMENT\_FAILURE | DEPLOYMENT\_STOP\_ON\_ALARM | DEPLOYMENT\_STOP\_ON\_REQUEST

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AutoScalingGroup

Information about an Auto Scaling group.

## Contents

### hook

The name of the launch hook that CodeDeploy installed into the Auto Scaling group.

For more information about the launch hook, see [How Amazon EC2 Auto Scaling works with CodeDeploy](#) in the *AWS CodeDeploy User Guide*.

Type: String

Required: No

### name

The Auto Scaling group name.

Type: String

Required: No

### terminationHook

The name of the termination hook that CodeDeploy installed into the Auto Scaling group.

For more information about the termination hook, see [Enabling termination deployments during Auto Scaling scale-in events](#) in the *AWS CodeDeploy User Guide*.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BlueGreenDeploymentConfiguration

Information about blue/green deployment options for a deployment group.

## Contents

### **deploymentReadyOption**

Information about the action to take when newly provisioned instances are ready to receive traffic in a blue/green deployment.

Type: [DeploymentReadyOption](#) object

Required: No

### **greenFleetProvisioningOption**

Information about how instances are provisioned for a replacement environment in a blue/green deployment.

Type: [GreenFleetProvisioningOption](#) object

Required: No

### **terminateBlueInstancesOnDeploymentSuccess**

Information about whether to terminate instances in the original fleet during a blue/green deployment.

Type: [BlueInstanceTerminationOption](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# BlueInstanceTerminationOption

Information about whether instances in the original environment are terminated when a blue/green deployment is successful. `BlueInstanceTerminationOption` does not apply to Lambda deployments.

## Contents

### action

The action to take on instances in the original environment after a successful blue/green deployment.

- `TERMINATE`: Instances are terminated after a specified wait time.
- `KEEP_ALIVE`: Instances are left running after they are deregistered from the load balancer and removed from the deployment group.

Type: String

Valid Values: `TERMINATE` | `KEEP_ALIVE`

Required: No

### terminationWaitTimeInMinutes

For an Amazon EC2 deployment, the number of minutes to wait after a successful blue/green deployment before terminating instances from the original environment.

For an Amazon ECS deployment, the number of minutes before deleting the original (blue) task set. During an Amazon ECS deployment, CodeDeploy shifts traffic from the original (blue) task set to a replacement (green) task set.

The maximum setting is 2880 minutes (2 days).

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CloudFormationTarget

Information about the target to be updated by an CloudFormation blue/green deployment. This target type is used for all deployments initiated by a CloudFormation stack update.

## Contents

### deploymentId

The unique ID of an CloudFormation blue/green deployment.

Type: String

Required: No

### lastUpdatedAt

The date and time when the target application was updated by an CloudFormation blue/green deployment.

Type: Timestamp

Required: No

### lifecycleEvents

The lifecycle events of the CloudFormation blue/green deployment to this target application.

Type: Array of [LifecycleEvent](#) objects

Required: No

### resourceType

The resource type for the CloudFormation blue/green deployment.

Type: String

Required: No

### status

The status of an CloudFormation blue/green deployment's target application.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

### **targetId**

The unique ID of a deployment target that has a type of CloudFormationTarget.

Type: String

Required: No

### **targetVersionWeight**

The percentage of production traffic that the target version of an CloudFormation blue/green deployment receives.

Type: Double

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentConfigInfo

Information about a deployment configuration.

## Contents

### **computePlatform**

The destination platform type for the deployment (Lambda, Server, or ECS).

Type: String

Valid Values: `Server` | `Lambda` | `ECS` | `Kubernetes`

Required: No

### **createTime**

The time at which the deployment configuration was created.

Type: Timestamp

Required: No

### **deploymentConfigId**

The deployment configuration ID.

Type: String

Required: No

### **deploymentConfigName**

The deployment configuration name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **minimumHealthyHosts**

Information about the number or percentage of minimum healthy instances.

Type: [MinimumHealthyHosts](#) object

Required: No

### **trafficRoutingConfig**

The configuration that specifies how the deployment traffic is routed. Used for deployments with a Lambda or Amazon ECS compute platform only.

Type: [TrafficRoutingConfig](#) object

Required: No

### **zonalConfig**

Information about a zonal configuration.

Type: [ZonalConfig](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentGroupInfo

Information about a deployment group.

## Contents

### **alarmConfiguration**

A list of alarms associated with the deployment group.

Type: [AlarmConfiguration](#) object

Required: No

### **applicationName**

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **autoRollbackConfiguration**

Information about the automatic rollback configuration associated with the deployment group.

Type: [AutoRollbackConfiguration](#) object

Required: No

### **autoScalingGroups**

A list of associated Auto Scaling groups.

Type: Array of [AutoScalingGroup](#) objects

Required: No

### **blueGreenDeploymentConfiguration**

Information about blue/green deployment options for a deployment group.

Type: [BlueGreenDeploymentConfiguration](#) object

Required: No

### **computePlatform**

The destination platform type for the deployment (Lambda, Server, or ECS).

Type: String

Valid Values: Server | Lambda | ECS | Kubernetes

Required: No

### **deploymentConfigName**

The deployment configuration name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **deploymentGroupId**

The deployment group ID.

Type: String

Required: No

### **deploymentGroupName**

The deployment group name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **deploymentStyle**

Information about the type of deployment, either in-place or blue/green, you want to run and whether to route deployment traffic behind a load balancer.

Type: [DeploymentStyle](#) object

Required: No

### **ec2TagFilters**

The Amazon EC2 tags on which to filter. The deployment group includes EC2 instances with any of the specified tags.

Type: Array of [EC2TagFilter](#) objects

Required: No

### **ec2TagSet**

Information about groups of tags applied to an Amazon EC2 instance. The deployment group includes only Amazon EC2 instances identified by all of the tag groups. Cannot be used in the same call as `ec2TagFilters`.

Type: [EC2TagSet](#) object

Required: No

### **ecsServices**

The target Amazon ECS services in the deployment group. This applies only to deployment groups that use the Amazon ECS compute platform. A target Amazon ECS service is specified as an Amazon ECS cluster and service name pair using the format `<clustername>:<servicename>`.

Type: Array of [ECSService](#) objects

Required: No

### **lastAttemptedDeployment**

Information about the most recent attempted deployment to the deployment group.

Type: [LastDeploymentInfo](#) object

Required: No

### **lastSuccessfulDeployment**

Information about the most recent successful deployment to the deployment group.

Type: [LastDeploymentInfo](#) object

Required: No

### **loadBalancerInfo**

Information about the load balancer to use in a deployment.

Type: [LoadBalancerInfo](#) object

Required: No

### **onPremisesInstanceTagFilters**

The on-premises instance tags on which to filter. The deployment group includes on-premises instances with any of the specified tags.

Type: Array of [TagFilter](#) objects

Required: No

### **onPremisesTagSet**

Information about groups of tags applied to an on-premises instance. The deployment group includes only on-premises instances identified by all the tag groups. Cannot be used in the same call as `onPremisesInstanceTagFilters`.

Type: [OnPremisesTagSet](#) object

Required: No

### **outdatedInstancesStrategy**

Indicates what happens when new Amazon EC2 instances are launched mid-deployment and do not receive the deployed application revision.

If this option is set to `UPDATE` or is unspecified, CodeDeploy initiates one or more 'auto-update outdated instances' deployments to apply the deployed application revision to the new Amazon EC2 instances.

If this option is set to `IGNORE`, CodeDeploy does not initiate a deployment to update the new Amazon EC2 instances. This may result in instances having different revisions.

Type: String

Valid Values: `UPDATE` | `IGNORE`

Required: No

### **serviceRoleArn**

A service role Amazon Resource Name (ARN) that grants CodeDeploy permission to make calls to AWS services on your behalf. For more information, see [Create a Service Role for AWS CodeDeploy](#) in the *AWS CodeDeploy User Guide*.

Type: String

Required: No

### **targetRevision**

Information about the deployment group's target revision, including type and location.

Type: [RevisionLocation](#) object

Required: No

### **terminationHookEnabled**

Indicates whether the deployment group was configured to have CodeDeploy install a termination hook into an Auto Scaling group.

For more information about the termination hook, see [How Amazon EC2 Auto Scaling works with CodeDeploy](#) in the *AWS CodeDeploy User Guide*.

Type: Boolean

Required: No

### **triggerConfigurations**

Information about triggers associated with the deployment group.

Type: Array of [TriggerConfig](#) objects

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentInfo

Information about a deployment.

## Contents

### **additionalDeploymentStatusInfo**

*This member has been deprecated.*

Provides information about the results of a deployment, such as whether instances in the original environment in a blue/green deployment were not terminated.

Type: String

Required: No

### **applicationName**

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **autoRollbackConfiguration**

Information about the automatic rollback configuration associated with the deployment.

Type: [AutoRollbackConfiguration](#) object

Required: No

### **blueGreenDeploymentConfiguration**

Information about blue/green deployment options for this deployment.

Type: [BlueGreenDeploymentConfiguration](#) object

Required: No

### **completeTime**

A timestamp that indicates when the deployment was complete.

Type: Timestamp

Required: No

### **computePlatform**

The destination platform type for the deployment (Lambda, Server, or ECS).

Type: String

Valid Values: `Server` | `Lambda` | `ECS` | `Kubernetes`

Required: No

### **createTime**

A timestamp that indicates when the deployment was created.

Type: Timestamp

Required: No

### **creator**

The means by which the deployment was created:

- `user`: A user created the deployment.
- `autoscaling`: Amazon EC2 Auto Scaling created the deployment.
- `codeDeployRollback`: A rollback process created the deployment.
- `CodeDeployAutoUpdate`: An auto-update process created the deployment when it detected outdated Amazon EC2 instances.

Type: String

Valid Values: `user` | `autoscaling` | `codeDeployRollback` | `CodeDeploy` | `CodeDeployAutoUpdate` | `CloudFormation` | `CloudFormationRollback` | `autoscalingTermination`

Required: No

### **deploymentConfigName**

The deployment configuration name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **deploymentGroupName**

The deployment group name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **deploymentId**

The unique ID of a deployment.

Type: String

Required: No

### **deploymentOverview**

A summary of the deployment status of the instances in the deployment.

Type: [DeploymentOverview](#) object

Required: No

### **deploymentStatusMessages**

Messages that contain information about the status of a deployment.

Type: Array of strings

Required: No

### **deploymentStyle**

Information about the type of deployment, either in-place or blue/green, you want to run and whether to route deployment traffic behind a load balancer.

Type: [DeploymentStyle](#) object

Required: No

## description

A comment about the deployment.

Type: String

Required: No

## errorInformation

Information about any error associated with this deployment.

Type: [ErrorInformation](#) object

Required: No

## externalId

The unique ID for an external resource (for example, a CloudFormation stack ID) that is linked to this deployment.

Type: String

Required: No

## fileExistsBehavior

Information about how AWS CodeDeploy handles files that already exist in a deployment target location but weren't part of the previous successful deployment.

- **DISALLOW**: The deployment fails. This is also the default behavior if no option is specified.
- **OVERWRITE**: The version of the file from the application revision currently being deployed replaces the version already on the instance.
- **RETAIN**: The version of the file already on the instance is kept and used as part of the new deployment.

Type: String

Valid Values: DISALLOW | OVERWRITE | RETAIN

Required: No

## ignoreApplicationStopFailures

If true, then if an `ApplicationStop`, `BeforeBlockTraffic`, or `AfterBlockTraffic` deployment lifecycle event to an instance fails, then the deployment continues to the

next deployment lifecycle event. For example, if `ApplicationStop` fails, the deployment continues with `DownloadBundle`. If `BeforeBlockTraffic` fails, the deployment continues with `BlockTraffic`. If `AfterBlockTraffic` fails, the deployment continues with `ApplicationStop`.

If `false` or not specified, then if a lifecycle event fails during a deployment to an instance, that deployment fails. If deployment to that instance is part of an overall deployment and the number of healthy hosts is not less than the minimum number of healthy hosts, then a deployment to the next instance is attempted.

During a deployment, the AWS CodeDeploy agent runs the scripts specified for `ApplicationStop`, `BeforeBlockTraffic`, and `AfterBlockTraffic` in the `AppSpec` file from the previous successful deployment. (All other scripts are run from the `AppSpec` file in the current deployment.) If one of these scripts contains an error and does not run successfully, the deployment can fail.

If the cause of the failure is a script from the last successful deployment that will never run successfully, create a new deployment and use `ignoreApplicationStopFailures` to specify that the `ApplicationStop`, `BeforeBlockTraffic`, and `AfterBlockTraffic` failures should be ignored.

Type: Boolean

Required: No

### **instanceTerminationWaitTimeStarted**

Indicates whether the wait period set for the termination of instances in the original environment has started. Status is `'false'` if the `KEEP_ALIVE` option is specified. Otherwise, `'true'` as soon as the termination wait period starts.

Type: Boolean

Required: No

### **loadBalancerInfo**

Information about the load balancer used in the deployment.

Type: [LoadBalancerInfo](#) object

Required: No

## **overrideAlarmConfiguration**

Information about alarms associated with a deployment or deployment group.

Type: [AlarmConfiguration](#) object

Required: No

## **previousRevision**

Information about the application revision that was deployed to the deployment group before the most recent successful deployment.

Type: [RevisionLocation](#) object

Required: No

## **relatedDeployments**

Information about deployments related to the specified deployment.

Type: [RelatedDeployments](#) object

Required: No

## **revision**

Information about the location of stored application artifacts and the service from which to retrieve them.

Type: [RevisionLocation](#) object

Required: No

## **rollbackInfo**

Information about a deployment rollback.

Type: [RollbackInfo](#) object

Required: No

## **startTime**

A timestamp that indicates when the deployment was deployed to the deployment group.

In some cases, the reported value of the start time might be later than the complete time. This is due to differences in the clock settings of backend servers that participate in the deployment process.

Type: Timestamp

Required: No

### **status**

The current state of the deployment as a whole.

Type: String

Valid Values: Created | Queued | InProgress | Baking | Succeeded | Failed | Stopped | Ready

Required: No

### **targetInstances**

Information about the instances that belong to the replacement environment in a blue/green deployment.

Type: [TargetInstances](#) object

Required: No

### **updateOutdatedInstancesOnly**

Indicates whether only instances that are not running the latest application revision are to be deployed to.

Type: Boolean

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentOverview

Information about the deployment status of the instances in the deployment.

## Contents

### Failed

The number of instances in the deployment in a failed state.

Type: Long

Required: No

### InProgress

The number of instances in which the deployment is in progress.

Type: Long

Required: No

### Pending

The number of instances in the deployment in a pending state.

Type: Long

Required: No

### Ready

The number of instances in a replacement environment ready to receive traffic in a blue/green deployment.

Type: Long

Required: No

### Skipped

The number of instances in the deployment in a skipped state.

Type: Long

Required: No

## Succeeded

The number of instances in the deployment to which revisions have been successfully deployed.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentReadyOption

Information about how traffic is rerouted to instances in a replacement environment in a blue/green deployment.

## Contents

### actionOnTimeout

Information about when to reroute traffic from an original environment to a replacement environment in a blue/green deployment.

- **CONTINUE\_DEPLOYMENT**: Register new instances with the load balancer immediately after the new application revision is installed on the instances in the replacement environment.
- **STOP\_DEPLOYMENT**: Do not register new instances with a load balancer unless traffic rerouting is started using [ContinueDeployment](#). If traffic rerouting is not started before the end of the specified wait period, the deployment status is changed to Stopped.

Type: String

Valid Values: CONTINUE\_DEPLOYMENT | STOP\_DEPLOYMENT

Required: No

### waitTimeInMinutes

The number of minutes to wait before the status of a blue/green deployment is changed to Stopped if rerouting is not started manually. Applies only to the STOP\_DEPLOYMENT option for actionOnTimeout.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# DeploymentStyle

Information about the type of deployment, either in-place or blue/green, you want to run and whether to route deployment traffic behind a load balancer.

## Contents

### deploymentOption

Indicates whether to route deployment traffic behind a load balancer.

Type: String

Valid Values: WITH\_TRAFFIC\_CONTROL | WITHOUT\_TRAFFIC\_CONTROL

Required: No

### deploymentType

Indicates whether to run an in-place deployment or a blue/green deployment.

Type: String

Valid Values: IN\_PLACE | BLUE\_GREEN

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeploymentTarget

Information about the deployment target.

## Contents

### cloudFormationTarget

Information about the target to be updated by an CloudFormation blue/green deployment. This target type is used for all deployments initiated by a CloudFormation stack update.

Type: [CloudFormationTarget](#) object

Required: No

### deploymentTargetType

The deployment type that is specific to the deployment's compute platform or deployments initiated by a CloudFormation stack update.

Type: String

Valid Values: InstanceTarget | LambdaTarget | ECSTarget | EKSTarget | CloudFormationTarget

Required: No

### ecsTarget

Information about the target for a deployment that uses the Amazon ECS compute platform.

Type: [ECSTarget](#) object

Required: No

### instanceTarget

Information about the target for a deployment that uses the EC2/On-premises compute platform.

Type: [InstanceTarget](#) object

Required: No

## lambdaTarget

Information about the target for a deployment that uses the AWS Lambda compute platform.

Type: [LambdaTarget](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Diagnostics

Diagnostic information about executable scripts that are part of a deployment.

## Contents

### **errorCode**

The associated error code:

- **Success**: The specified script ran.
- **ScriptMissing**: The specified script was not found in the specified location.
- **ScriptNotExecutable**: The specified script is not a recognized executable file type.
- **ScriptTimedOut**: The specified script did not finish running in the specified time period.
- **ScriptFailed**: The specified script failed to run as expected.
- **UnknownError**: The specified script did not run for an unknown reason.

Type: String

Valid Values: `Success` | `ScriptMissing` | `ScriptNotExecutable` | `ScriptTimedOut` | `ScriptFailed` | `UnknownError`

Required: No

### **logTail**

The last portion of the diagnostic log.

If available, AWS CodeDeploy returns up to the last 4 KB of the diagnostic log.

Type: String

Required: No

### **message**

The message associated with the error.

Type: String

Required: No

## scriptName

The name of the script.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EC2TagFilter

Information about an EC2 tag filter.

## Contents

### Key

The tag filter key.

Type: String

Required: No

### Type

The tag filter type:

- KEY\_ONLY: Key only.
- VALUE\_ONLY: Value only.
- KEY\_AND\_VALUE: Key and value.

Type: String

Valid Values: KEY\_ONLY | VALUE\_ONLY | KEY\_AND\_VALUE

Required: No

### Value

The tag filter value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EC2TagSet

Information about groups of Amazon EC2 instance tags.

## Contents

### ec2TagSetList

A list that contains other lists of Amazon EC2 instance tag groups. For an instance to be included in the deployment group, it must be identified by all of the tag groups in the list.

Type: Array of arrays of [EC2TagFilter](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ECSService

Contains the service and cluster names used to identify an Amazon ECS deployment's target.

## Contents

### clusterName

The name of the cluster that the Amazon ECS service is associated with.

Type: String

Required: No

### serviceName

The name of the target Amazon ECS service.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ECSTarget

Information about the target of an Amazon ECS deployment.

## Contents

### **deploymentId**

The unique ID of a deployment.

Type: String

Required: No

### **lastUpdatedAt**

The date and time when the target Amazon ECS application was updated by a deployment.

Type: Timestamp

Required: No

### **lifecycleEvents**

The lifecycle events of the deployment to this target Amazon ECS application.

Type: Array of [LifecycleEvent](#) objects

Required: No

### **status**

The status an Amazon ECS deployment's target ECS application.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

### **targetArn**

The Amazon Resource Name (ARN) of the target.

Type: String

Required: No

### **targetId**

The unique ID of a deployment target that has a type of `ecsTarget`.

Type: String

Required: No

### **taskSetsInfo**

The `ECSTaskSet` objects associated with the ECS target.

Type: Array of [ECSTaskSet](#) objects

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ECSTaskSet

Information about a set of Amazon ECS tasks in an AWS CodeDeploy deployment. An Amazon ECS task set includes details such as the desired number of tasks, how many tasks are running, and whether the task set serves production traffic. An AWS CodeDeploy application that uses the Amazon ECS compute platform deploys a containerized application in an Amazon ECS service as a task set.

## Contents

### **desiredCount**

The number of tasks in a task set. During a deployment that uses the Amazon ECS compute type, CodeDeploy instructs Amazon ECS to create a new task set and uses this value to determine how many tasks to create. After the updated task set is created, CodeDeploy shifts traffic to the new task set.

Type: Long

Required: No

### **identifer**

A unique ID of an ECSTaskSet.

Type: String

Required: No

### **pendingCount**

The number of tasks in the task set that are in the PENDING status during an Amazon ECS deployment. A task in the PENDING state is preparing to enter the RUNNING state. A task set enters the PENDING status when it launches for the first time, or when it is restarted after being in the STOPPED state.

Type: Long

Required: No

### **runningCount**

The number of tasks in the task set that are in the RUNNING status during an Amazon ECS deployment. A task in the RUNNING state is running and ready for use.

Type: Long

Required: No

### **status**

The status of the task set. There are three valid task set statuses:

- PRIMARY: Indicates the task set is serving production traffic.
- ACTIVE: Indicates the task set is not serving production traffic.
- DRAINING: Indicates the tasks in the task set are being stopped and their corresponding targets are being deregistered from their target group.

Type: String

Required: No

### **targetGroup**

The target group associated with the task set. The target group is used by AWS CodeDeploy to manage traffic to a task set.

Type: [TargetGroupInfo](#) object

Required: No

### **taskSetLabel**

A label that identifies whether the ECS task set is an original target (BLUE) or a replacement target (GREEN).

Type: String

Valid Values: Blue | Green

Required: No

### **trafficWeight**

The percentage of traffic served by this task set.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ELBInfo

Information about a Classic Load Balancer in Elastic Load Balancing to use in a deployment. Instances are registered directly with a load balancer, and traffic is routed to the load balancer.

## Contents

### name

For blue/green deployments, the name of the Classic Load Balancer that is used to route traffic from original instances to replacement instances in a blue/green deployment. For in-place deployments, the name of the Classic Load Balancer that instances are deregistered from so they are not serving traffic during a deployment, and then re-registered with after the deployment is complete.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ErrorInformation

Information about a deployment error.

## Contents

### code

For more information, see [Error Codes for AWS CodeDeploy](#) in the [AWS CodeDeploy User Guide](#).

The error code:

- **APPLICATION\_MISSING**: The application was missing. This error code is most likely raised if the application is deleted after the deployment is created, but before it is started.
- **DEPLOYMENT\_GROUP\_MISSING**: The deployment group was missing. This error code is most likely raised if the deployment group is deleted after the deployment is created, but before it is started.
- **HEALTH\_CONSTRAINTS**: The deployment failed on too many instances to be successfully deployed within the instance health constraints specified.
- **HEALTH\_CONSTRAINTS\_INVALID**: The revision cannot be successfully deployed within the instance health constraints specified.
- **IAM\_ROLE\_MISSING**: The service role cannot be accessed.
- **IAM\_ROLE\_PERMISSIONS**: The service role does not have the correct permissions.
- **INTERNAL\_ERROR**: There was an internal error.
- **NO\_EC2\_SUBSCRIPTION**: The calling account is not subscribed to Amazon EC2.
- **NO\_INSTANCES**: No instances were specified, or no instances can be found.
- **OVER\_MAX\_INSTANCES**: The maximum number of instances was exceeded.
- **THROTTLED**: The operation was throttled because the calling account exceeded the throttling limits of one or more AWS services.
- **TIMEOUT**: The deployment has timed out.
- **REVISION\_MISSING**: The revision ID was missing. This error code is most likely raised if the revision is deleted after the deployment is created, but before it is started.

Type: String

Valid Values: AGENT\_ISSUE | ALARM\_ACTIVE | APPLICATION\_MISSING | AUTOSCALING\_VALIDATION\_ERROR | AUTO\_SCALING\_CONFIGURATION |

AUTO\_SCALING\_IAM\_ROLE\_PERMISSIONS | CODEDEPLOY\_RESOURCE\_CANNOT\_BE\_FOUND  
| CUSTOMER\_APPLICATION\_UNHEALTHY | DEPLOYMENT\_GROUP\_MISSING  
| ECS\_UPDATE\_ERROR | ELASTIC\_LOAD\_BALANCING\_INVALID |  
ELB\_INVALID\_INSTANCE | HEALTH\_CONSTRAINTS | HEALTH\_CONSTRAINTS\_INVALID  
| HOOK\_EXECUTION\_FAILURE | IAM\_ROLE\_MISSING | IAM\_ROLE\_PERMISSIONS |  
INTERNAL\_ERROR | INVALID\_ECS\_SERVICE | INVALID\_LAMBDA\_CONFIGURATION  
| INVALID\_LAMBDA\_FUNCTION | INVALID\_REVISION | MANUAL\_STOP |  
MISSING\_BLUE\_GREEN\_DEPLOYMENT\_CONFIGURATION | MISSING\_ELB\_INFORMATION  
| MISSING\_GITHUB\_TOKEN | NO\_EC2\_SUBSCRIPTION | NO\_INSTANCES |  
OVER\_MAX\_INSTANCES | RESOURCE\_LIMIT\_EXCEEDED | REVISION\_MISSING |  
THROTTLED | TIMEOUT | CLOUDFORMATION\_STACK\_FAILURE | INVALID\_EKS\_CLUSTER  
| KUBERNETES\_UPDATE\_ERROR

Required: No

### message

An accompanying error message.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GenericRevisionInfo

Information about an application revision.

## Contents

### **deploymentGroups**

The deployment groups for which this is the current target revision.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### **description**

A comment about the revision.

Type: String

Required: No

### **firstUsedTime**

When the revision was first used by AWS CodeDeploy.

Type: Timestamp

Required: No

### **lastUsedTime**

When the revision was last used by AWS CodeDeploy.

Type: Timestamp

Required: No

### **registerTime**

When the revision was registered with AWS CodeDeploy.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GitHubLocation

Information about the location of application artifacts stored in GitHub.

## Contents

### **commitId**

The SHA1 commit ID of the GitHub commit that represents the bundled artifacts for the application revision.

Type: String

Required: No

### **repository**

The GitHub account and repository pair that stores a reference to the commit that represents the bundled artifacts for the application revision.

Specified as account/repository.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GreenFleetProvisioningOption

Information about the instances that belong to the replacement environment in a blue/green deployment.

## Contents

### action

The method used to add instances to a replacement environment.

- `DISCOVER_EXISTING`: Use instances that already exist or will be created manually.
- `COPY_AUTO_SCALING_GROUP`: Use settings from a specified Auto Scaling group to define and create instances in a new Auto Scaling group.

Type: String

Valid Values: `DISCOVER_EXISTING` | `COPY_AUTO_SCALING_GROUP`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InstanceInfo

Information about an on-premises instance.

## Contents

### deregisterTime

If the on-premises instance was deregistered, the time at which the on-premises instance was deregistered.

Type: Timestamp

Required: No

### iamSessionArn

The ARN of the IAM session associated with the on-premises instance.

Type: String

Required: No

### iamUserArn

The user ARN associated with the on-premises instance.

Type: String

Required: No

### instanceArn

The ARN of the on-premises instance.

Type: String

Required: No

### instanceName

The name of the on-premises instance.

Type: String

Required: No

## registerTime

The time at which the on-premises instance was registered.

Type: Timestamp

Required: No

## tags

The tags currently associated with the on-premises instance.

Type: Array of [Tag](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InstanceSummary

*This data type has been deprecated.*

Information about an instance in a deployment.

## Contents

### **deploymentId**

The unique ID of a deployment.

Type: String

Required: No

### **instanceId**

The instance ID.

Type: String

Required: No

### **instanceType**

Information about which environment an instance belongs to in a blue/green deployment.

- BLUE: The instance is part of the original environment.
- GREEN: The instance is part of the replacement environment.

Type: String

Valid Values: Blue | Green

Required: No

### **lastUpdatedAt**

A timestamp that indicates when the instance information was last updated.

Type: Timestamp

Required: No

## lifecycleEvents

A list of lifecycle events for this instance.

Type: Array of [LifecycleEvent](#) objects

Required: No

## status

*This member has been deprecated.*

The deployment status for this instance:

- **Pending:** The deployment is pending for this instance.
- **In Progress:** The deployment is in progress for this instance.
- **Succeeded:** The deployment has succeeded for this instance.
- **Failed:** The deployment has failed for this instance.
- **Skipped:** The deployment has been skipped for this instance.
- **Unknown:** The deployment status is unknown for this instance.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InstanceTarget

A target Amazon EC2 or on-premises instance during a deployment that uses the EC2/On-premises compute platform.

## Contents

### deploymentId

The unique ID of a deployment.

Type: String

Required: No

### instanceLabel

A label that identifies whether the instance is an original target (BLUE) or a replacement target (GREEN).

Type: String

Valid Values: Blue | Green

Required: No

### lastUpdatedAt

The date and time when the target instance was updated by a deployment.

Type: Timestamp

Required: No

### lifecycleEvents

The lifecycle events of the deployment to this target instance.

Type: Array of [LifecycleEvent](#) objects

Required: No

### status

The status an EC2/On-premises deployment's target instance.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

### **targetArn**

The Amazon Resource Name (ARN) of the target.

Type: String

Required: No

### **targetId**

The unique ID of a deployment target that has a type of `instanceTarget`.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaFunctionInfo

Information about a Lambda function specified in a deployment.

## Contents

### currentVersion

The version of a Lambda function that production traffic points to.

Type: String

Required: No

### functionAlias

The alias of a Lambda function. For more information, see [AWS Lambda Function Aliases](#) in the *AWS Lambda Developer Guide*.

Type: String

Required: No

### functionName

The name of a Lambda function.

Type: String

Required: No

### targetVersion

The version of a Lambda function that production traffic points to after the Lambda function is deployed.

Type: String

Required: No

### targetVersionWeight

The percentage of production traffic that the target version of a Lambda function receives.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaTarget

Information about the target AWS Lambda function during an AWS Lambda deployment.

## Contents

### deploymentId

The unique ID of a deployment.

Type: String

Required: No

### lambdaFunctionInfo

A `LambdaFunctionInfo` object that describes a target Lambda function.

Type: [LambdaFunctionInfo](#) object

Required: No

### lastUpdatedAt

The date and time when the target Lambda function was updated by a deployment.

Type: Timestamp

Required: No

### lifecycleEvents

The lifecycle events of the deployment to this target Lambda function.

Type: Array of [LifecycleEvent](#) objects

Required: No

### status

The status an AWS Lambda deployment's target Lambda function.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown  
| Ready

Required: No

### **targetArn**

The Amazon Resource Name (ARN) of the target.

Type: String

Required: No

### **targetId**

The unique ID of a deployment target that has a type of `LambdaTarget`.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LastDeploymentInfo

Information about the most recent attempted or successful deployment to a deployment group.

## Contents

### **createTime**

A timestamp that indicates when the most recent deployment to the deployment group started.

Type: Timestamp

Required: No

### **deploymentId**

The unique ID of a deployment.

Type: String

Required: No

### **endTime**

A timestamp that indicates when the most recent deployment to the deployment group was complete.

Type: Timestamp

Required: No

### **status**

The status of the most recent deployment.

Type: String

Valid Values: Created | Queued | InProgress | Baking | Succeeded | Failed | Stopped | Ready

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LifecycleEvent

Information about a deployment lifecycle event.

## Contents

### diagnostics

Diagnostic information about the deployment lifecycle event.

Type: [Diagnostics](#) object

Required: No

### endTime

A timestamp that indicates when the deployment lifecycle event ended.

Type: Timestamp

Required: No

### lifecycleEventName

The deployment lifecycle event name, such as `ApplicationStop`, `BeforeInstall`, `AfterInstall`, `ApplicationStart`, or `ValidateService`.

Type: String

Required: No

### startTime

A timestamp that indicates when the deployment lifecycle event started.

Type: Timestamp

Required: No

### status

The deployment lifecycle event status:

- `Pending`: The deployment lifecycle event is pending.
- `InProgress`: The deployment lifecycle event is in progress.

- **Succeeded:** The deployment lifecycle event ran successfully.
- **Failed:** The deployment lifecycle event has failed.
- **Skipped:** The deployment lifecycle event has been skipped.
- **Unknown:** The deployment lifecycle event is unknown.

Type: String

Valid Values: Pending | InProgress | Succeeded | Failed | Skipped | Unknown

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LoadBalancerInfo

Information about the Elastic Load Balancing load balancer or target group used in a deployment.

You can use load balancers and target groups in combination. For example, if you have two Classic Load Balancers, and five target groups tied to an Application Load Balancer, you can specify the two Classic Load Balancers in `elbInfoList`, and the five target groups in `targetGroupInfoList`.

## Contents

### `elbInfoList`

An array that contains information about the load balancers to use for load balancing in a deployment. If you're using Classic Load Balancers, specify those load balancers in this array.

#### **Note**

You can add up to 10 load balancers to the array.

#### **Note**

If you're using Application Load Balancers or Network Load Balancers, use the `targetGroupInfoList` array instead of this one.

Type: Array of [ELBInfo](#) objects

Required: No

### `targetGroupInfoList`

An array that contains information about the target groups to use for load balancing in a deployment. If you're using Application Load Balancers and Network Load Balancers, specify their associated target groups in this array.

#### **Note**

You can add up to 10 target groups to the array.

**Note**

If you're using Classic Load Balancers, use the `elbInfoList` array instead of this one.

Type: Array of [TargetGroupInfo](#) objects

Required: No

**targetGroupPairInfoList**

The target group pair information. This is an array of `TargeGroupPairInfo` objects with a maximum size of one.

Type: Array of [TargetGroupPairInfo](#) objects

Required: No

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MinimumHealthyHosts

Information about the minimum number of healthy instances.

## Contents

### type

The minimum healthy instance type:

- **HOST\_COUNT**: The minimum number of healthy instances as an absolute value.
- **FLEET\_PERCENT**: The minimum number of healthy instances as a percentage of the total number of instances in the deployment.

In an example of nine instances, if a **HOST\_COUNT** of six is specified, deploy to up to three instances at a time. The deployment is successful if six or more instances are deployed to successfully. Otherwise, the deployment fails. If a **FLEET\_PERCENT** of 40 is specified, deploy to up to five instances at a time. The deployment is successful if four or more instances are deployed to successfully. Otherwise, the deployment fails.

#### Note

In a call to the `GetDeploymentConfig`, `CodeDeployDefault.OneAtATime` returns a minimum healthy instance type of `MOST_CONCURRENCY` and a value of 1. This means a deployment to only one instance at a time. (You cannot set the type to `MOST_CONCURRENCY`, only to `HOST_COUNT` or `FLEET_PERCENT`.) In addition, with `CodeDeployDefault.OneAtATime`, AWS CodeDeploy attempts to ensure that all instances but one are kept in a healthy state during the deployment. Although this allows one instance at a time to be taken offline for a new deployment, it also means that if the deployment to the last instance fails, the overall deployment is still successful.

For more information, see [AWS CodeDeploy Instance Health](#) in the *AWS CodeDeploy User Guide*.

Type: String

Valid Values: `HOST_COUNT` | `FLEET_PERCENT`

Required: No

**value**

The minimum healthy instance value.

Type: Integer

Required: No

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MinimumHealthyHostsPerZone

Information about the minimum number of healthy instances per Availability Zone.

## Contents

### type

The type associated with the MinimumHealthyHostsPerZone option.

Type: String

Valid Values: HOST\_COUNT | FLEET\_PERCENT

Required: No

### value

The value associated with the MinimumHealthyHostsPerZone option.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OnPremisesTagSet

Information about groups of on-premises instance tags.

## Contents

### onPremisesTagSetList

A list that contains other lists of on-premises instance tag groups. For an instance to be included in the deployment group, it must be identified by all of the tag groups in the list.

Type: Array of arrays of [TagFilter](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RawString

*This data type has been deprecated.*

A revision for an AWS Lambda deployment that is a YAML-formatted or JSON-formatted string. For AWS Lambda deployments, the revision is the same as the AppSpec file.

## Contents

### content

The YAML-formatted or JSON-formatted revision string. It includes information about which Lambda function to update and optional Lambda functions that validate deployment lifecycle events.

Type: String

Required: No

### sha256

The SHA256 hash value of the revision content.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RelatedDeployments

Information about deployments related to the specified deployment.

## Contents

### **autoUpdateOutdatedInstancesDeploymentIds**

The deployment IDs of 'auto-update outdated instances' deployments triggered by this deployment.

Type: Array of strings

Required: No

### **autoUpdateOutdatedInstancesRootDeploymentId**

The deployment ID of the root deployment that triggered this deployment.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RevisionInfo

Information about an application revision.

## Contents

### **genericRevisionInfo**

Information about an application revision, including usage details and associated deployment groups.

Type: [GenericRevisionInfo](#) object

Required: No

### **revisionLocation**

Information about the location and type of an application revision.

Type: [RevisionLocation](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RevisionLocation

Information about the location of an application revision.

## Contents

### appSpecContent

The content of an AppSpec file for an AWS Lambda or Amazon ECS deployment. The content is formatted as JSON or YAML and stored as a RawString.

Type: [AppSpecContent](#) object

Required: No

### gitHubLocation

Information about the location of application artifacts stored in GitHub.

Type: [GitHubLocation](#) object

Required: No

### revisionType

The type of application revision:

- S3: An application revision stored in Amazon S3.
- GitHub: An application revision stored in GitHub (EC2/On-premises deployments only).
- String: A YAML-formatted or JSON-formatted string (AWS Lambda deployments only).
- AppSpecContent: An AppSpecContent object that contains the contents of an AppSpec file for an AWS Lambda or Amazon ECS deployment. The content is formatted as JSON or YAML stored as a RawString.

Type: String

Valid Values: S3 | GitHub | String | AppSpecContent | SystemsManagerPatchBaseline

Required: No

### s3Location

Information about the location of a revision stored in Amazon S3.

Type: [S3Location](#) object

Required: No

## string

*This member has been deprecated.*

Information about the location of an AWS Lambda deployment revision stored as a RawString.

Type: [RawString](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RollbackInfo

Information about a deployment rollback.

## Contents

### **rollbackDeploymentId**

The ID of the deployment rollback.

Type: String

Required: No

### **rollbackMessage**

Information that describes the status of a deployment rollback (for example, whether the deployment can't be rolled back, is in progress, failed, or succeeded).

Type: String

Required: No

### **rollbackTriggeringDeploymentId**

The deployment ID of the deployment that was underway and triggered a rollback deployment because it failed or was stopped.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# S3Location

Information about the location of application artifacts stored in Amazon S3.

## Contents

### bucket

The name of the Amazon S3 bucket where the application revision is stored.

Type: String

Required: No

### bundleType

The file type of the application revision. Must be one of the following:

- `tar`: A tar archive file.
- `tgz`: A compressed tar archive file.
- `zip`: A zip archive file.
- `YAML`: A YAML-formatted file.
- `JSON`: A JSON-formatted file.

Type: String

Valid Values: `tar` | `tgz` | `zip` | `YAML` | `JSON`

Required: No

### eTag

The ETag of the Amazon S3 object that represents the bundled artifacts for the application revision.

If the ETag is not specified as an input parameter, ETag validation of the object is skipped.

Type: String

Required: No

### key

The name of the Amazon S3 object that represents the bundled artifacts for the application revision.

Type: String

Required: No

### **version**

A specific version of the Amazon S3 object that represents the bundled artifacts for the application revision.

If the version is not specified, the system uses the most recent version by default.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Tag

Information about a tag.

## Contents

### Key

The tag's key.

Type: String

Required: No

### Value

The tag's value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TagFilter

Information about an on-premises instance tag filter.

## Contents

### Key

The on-premises instance tag filter key.

Type: String

Required: No

### Type

The on-premises instance tag filter type:

- `KEY_ONLY`: Key only.
- `VALUE_ONLY`: Value only.
- `KEY_AND_VALUE`: Key and value.

Type: String

Valid Values: `KEY_ONLY` | `VALUE_ONLY` | `KEY_AND_VALUE`

Required: No

### Value

The on-premises instance tag filter value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TargetGroupInfo

Information about a target group in Elastic Load Balancing to use in a deployment. Instances are registered as targets in a target group, and traffic is routed to the target group.

## Contents

### name

For blue/green deployments, the name of the target group that instances in the original environment are deregistered from, and instances in the replacement environment are registered with. For in-place deployments, the name of the target group that instances are deregistered from, so they are not serving traffic during a deployment, and then re-registered with after the deployment is complete.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TargetGroupPairInfo

Information about two target groups and how traffic is routed during an Amazon ECS deployment. An optional test traffic route can be specified.

## Contents

### prodTrafficRoute

The path used by a load balancer to route production traffic when an Amazon ECS deployment is complete.

Type: [TrafficRoute](#) object

Required: No

### targetGroups

One pair of target groups. One is associated with the original task set. The second is associated with the task set that serves traffic after the deployment is complete.

Type: Array of [TargetGroupInfo](#) objects

Required: No

### testTrafficRoute

An optional path used by a load balancer to route test traffic after an Amazon ECS deployment. Validation can occur while test traffic is served during a deployment.

Type: [TrafficRoute](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# TargetInstances

Information about the instances to be used in the replacement environment in a blue/green deployment.

## Contents

### autoScalingGroups

The names of one or more Auto Scaling groups to identify a replacement environment for a blue/green deployment.

Type: Array of strings

Required: No

### ec2TagSet

Information about the groups of Amazon EC2 instance tags that an instance must be identified by in order for it to be included in the replacement environment for a blue/green deployment. Cannot be used in the same call as `tagFilters`.

Type: [EC2TagSet](#) object

Required: No

### tagFilters

The tag filter key, type, and value used to identify Amazon EC2 instances in a replacement environment for a blue/green deployment. Cannot be used in the same call as `ec2TagSet`.

Type: Array of [EC2TagFilter](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# TimeBasedCanary

A configuration that shifts traffic from one version of a Lambda function or Amazon ECS task set to another in two increments. The original and target Lambda function versions or ECS task sets are specified in the deployment's AppSpec file.

## Contents

### canaryInterval

The number of minutes between the first and second traffic shifts of a TimeBasedCanary deployment.

Type: Integer

Required: No

### canaryPercentage

The percentage of traffic to shift in the first increment of a TimeBasedCanary deployment.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TimeBasedLinear

A configuration that shifts traffic from one version of a Lambda function or ECS task set to another in equal increments, with an equal number of minutes between each increment. The original and target Lambda function versions or ECS task sets are specified in the deployment's AppSpec file.

## Contents

### **linearInterval**

The number of minutes between each incremental traffic shift of a `TimeBasedLinear` deployment.

Type: Integer

Required: No

### **linearPercentage**

The percentage of traffic that is shifted at the start of each increment of a `TimeBasedLinear` deployment.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)


# TimeRange

Information about a time range.

## Contents

### end

The end time of the time range.

 **Note**


Specify null to leave the end time open-ended.

Type: Timestamp

Required: No

### start

The start time of the time range.

 **Note**

Specify null to leave the start time open-ended.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# TrafficRoute

Information about a listener. The listener contains the path used to route traffic that is received from the load balancer to a target group.

## Contents

### listenerArns

The Amazon Resource Name (ARN) of one listener. The listener identifies the route between a target group and a load balancer. This is an array of strings with a maximum size of one.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrafficRoutingConfig

The configuration that specifies how traffic is shifted from one version of a Lambda function to another version during an AWS Lambda deployment, or from one Amazon ECS task set to another during an Amazon ECS deployment.

## Contents

### timeBasedCanary

A configuration that shifts traffic from one version of a Lambda function or ECS task set to another in two increments. The original and target Lambda function versions or ECS task sets are specified in the deployment's AppSpec file.

Type: [TimeBasedCanary](#) object

Required: No

### timeBasedLinear

A configuration that shifts traffic from one version of a Lambda function or Amazon ECS task set to another in equal increments, with an equal number of minutes between each increment. The original and target Lambda function versions or Amazon ECS task sets are specified in the deployment's AppSpec file.

Type: [TimeBasedLinear](#) object

Required: No

### type

The type of traffic shifting (`TimeBasedCanary` or `TimeBasedLinear`) used by a deployment configuration.

Type: String

Valid Values: `TimeBasedCanary` | `TimeBasedLinear` | `TimeBasedFlexible` | `AllAtOnce`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TriggerConfig

Information about notification triggers for the deployment group.

## Contents

### triggerEvents

The event type or types for which notifications are triggered.

Type: Array of strings

Valid Values: DeploymentStart | DeploymentSuccess | DeploymentFailure | DeploymentStop | DeploymentRollback | DeploymentReady | InstanceStart | InstanceSuccess | InstanceFailure | InstanceReady

Required: No

### triggerName

The name of the notification trigger.

Type: String

Required: No

### triggerTargetArn

The Amazon Resource Name (ARN) of the Amazon Simple Notification Service topic through which notifications about deployment or instance events are sent.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ZonalConfig

Configure the `ZonalConfig` object if you want AWS CodeDeploy to deploy your application to one [Availability Zone](#) at a time, within an AWS Region. By deploying to one Availability Zone at a time, you can expose your deployment to a progressively larger audience as confidence in the deployment's performance and viability grows. If you don't configure the `ZonalConfig` object, CodeDeploy deploys your application to a random selection of hosts across a Region.

For more information about the zonal configuration feature, see [zonal configuration](#) in the *CodeDeploy User Guide*.

## Contents

### `firstZoneMonitorDurationInSeconds`

The period of time, in seconds, that CodeDeploy must wait after completing a deployment to the *first* Availability Zone. CodeDeploy will wait this amount of time before starting a deployment to the second Availability Zone. You might set this option if you want to allow extra bake time for the first Availability Zone. If you don't specify a value for `firstZoneMonitorDurationInSeconds`, then CodeDeploy uses the `monitorDurationInSeconds` value for the first Availability Zone.

For more information about the zonal configuration feature, see [zonal configuration](#) in the *CodeDeploy User Guide*.

Type: Long

Required: No

### `minimumHealthyHostsPerZone`

The number or percentage of instances that must remain available per Availability Zone during a deployment. This option works in conjunction with the `MinimumHealthyHosts` option. For more information, see [About the minimum number of healthy hosts per Availability Zone](#) in the *CodeDeploy User Guide*.

If you don't specify the `minimumHealthyHostsPerZone` option, then CodeDeploy uses a default value of 0 percent.

For more information about the zonal configuration feature, see [zonal configuration](#) in the *CodeDeploy User Guide*.

Type: [MinimumHealthyHostsPerZone](#) object

Required: No

### **monitorDurationInSeconds**

The period of time, in seconds, that CodeDeploy must wait after completing a deployment to an Availability Zone. CodeDeploy will wait this amount of time before starting a deployment to the next Availability Zone. Consider adding a monitor duration to give the deployment some time to prove itself (or 'bake') in one Availability Zone before it is released in the next zone. If you don't specify a `monitorDurationInSeconds`, CodeDeploy starts deploying to the next Availability Zone immediately.

For more information about the zonal configuration feature, see [zonal configuration](#) in the *CodeDeploy User Guide*.

Type: Long

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

## Required: Conditional

# Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

## **IncompleteSignature**

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

## **InternalFailure**

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

## **MalformedHttpRequestException**

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

**NotAuthorized**

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

**OptInRequired**

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

**RequestAbortedException**

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

**RequestEntityTooLargeException**

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

**RequestTimeoutException**

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

**ServiceUnavailable**

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

**ThrottlingException**

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

## **UnknownOperationException**

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

## **UnrecognizedClientException**

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

## **ValidationError**

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400