



Welcome

AWS CodeStar Notifications



API Version 2019-10-15

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS CodeStar Notifications: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	3
CreateNotificationRule	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	7
Response Elements	7
Errors	7
See Also	8
DeleteNotificationRule	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	10
Response Elements	11
Errors	11
See Also	11
DeleteTarget	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	14
Response Elements	14
Errors	14
See Also	14
DescribeNotificationRule	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	15
Response Elements	16
Errors	18
See Also	19

ListEventTypes	20
Request Syntax	20
URI Request Parameters	20
Request Body	20
Response Syntax	21
Response Elements	21
Errors	22
See Also	22
ListNotificationRules	24
Request Syntax	24
URI Request Parameters	24
Request Body	24
Response Syntax	25
Response Elements	25
Errors	26
See Also	26
ListTagsForResource	28
Request Syntax	28
URI Request Parameters	28
Request Body	28
Response Syntax	28
Response Elements	29
Errors	29
See Also	29
ListTargets	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	32
Response Elements	32
Errors	33
See Also	33
Subscribe	35
Request Syntax	35
URI Request Parameters	35
Request Body	35

Response Syntax	36
Response Elements	36
Errors	37
See Also	37
TagResource	38
Request Syntax	38
URI Request Parameters	38
Request Body	38
Response Syntax	39
Response Elements	39
Errors	39
See Also	40
Unsubscribe	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	43
Response Elements	43
Errors	43
See Also	44
UntagResource	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	45
Response Elements	46
Errors	46
See Also	46
UpdateNotificationRule	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	50
Response Elements	50
Errors	50
See Also	51

Data Types	52
EventTypeSummary	53
Contents	53
See Also	54
ListEventTypesFilter	55
Contents	55
See Also	55
ListNotificationRulesFilter	56
Contents	56
See Also	56
ListTargetsFilter	57
Contents	57
See Also	57
NotificationRuleSummary	58
Contents	58
See Also	58
Target	59
Contents	59
See Also	59
TargetSummary	61
Contents	61
See Also	62
Common Parameters	63
Common Error Types	66

Welcome

This AWS CodeStar Notifications API Reference provides descriptions and usage examples of the operations and data types for the AWS CodeStar Notifications API. You can use the AWS CodeStar Notifications API to work with the following objects:

Notification rules, by calling the following:

- [CreateNotificationRule](#), which creates a notification rule for a resource in your account.
- [DeleteNotificationRule](#), which deletes a notification rule.
- [DescribeNotificationRule](#), which provides information about a notification rule.
- [ListNotificationRules](#), which lists the notification rules associated with your account.
- [UpdateNotificationRule](#), which changes the name, events, or targets associated with a notification rule.
- [Subscribe](#), which subscribes a target to a notification rule.
- [Unsubscribe](#), which removes a target from a notification rule.

Targets, by calling the following:

- [DeleteTarget](#), which removes a notification rule target from a notification rule.
- [ListTargets](#), which lists the targets associated with a notification rule.

Events, by calling the following:

- [ListEventTypes](#), which lists the event types you can include in a notification rule.

Tags, by calling the following:

- [ListTagsForResource](#), which lists the tags already associated with a notification rule in your account.
- [TagResource](#), which associates a tag you provide with a notification rule in your account.
- [UntagResource](#), which removes a tag from a notification rule in your account.

For information about how to use AWS CodeStar Notifications, see the [AWS Developer Tools Console User Guide](#).

This document was last published on April 10, 2026.

Actions

The following actions are supported:

- [CreateNotificationRule](#)
- [DeleteNotificationRule](#)
- [DeleteTarget](#)
- [DescribeNotificationRule](#)
- [ListEventTypes](#)
- [ListNotificationRules](#)
- [ListTagsForResource](#)
- [ListTargets](#)
- [Subscribe](#)
- [TagResource](#)
- [Unsubscribe](#)
- [UntagResource](#)
- [UpdateNotificationRule](#)

CreateNotificationRule

Creates a notification rule for a resource. The rule specifies the events you want notifications about and the targets (such as Amazon Q Developer in chat applications topics or Amazon Q Developer in chat applications clients configured for Slack) where you want to receive them.

Request Syntax

```
POST /createNotificationRule HTTP/1.1
Content-type: application/json
```

```
{
  "ClientRequestToken": "string",
  "DetailType": "string",
  "EventTypeIds": [ "string" ],
  "Name": "string",
  "Resource": "string",
  "Status": "string",
  "Tags": {
    "string" : "string"
  },
  "Targets": [
    {
      "TargetAddress": "string",
      "TargetType": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientRequestToken

A unique, client-generated idempotency token that, when provided in a request, ensures the request cannot be repeated with a changed parameter. If a request with the same parameters is

received and a token is included, the request returns information about the initial request that used that token.

Note

The AWS SDKs prepopulate client request tokens. If you are using an AWS SDK, an idempotency token is created for you.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w:/-]+$`

Required: No

DetailType

The level of detail to include in the notifications for this resource. BASIC will include only the contents of the event as it would appear in Amazon CloudWatch. FULL will include any supplemental information provided by AWS CodeStar Notifications and/or the service for the resource for which the notification is created.

Type: String

Valid Values: BASIC | FULL

Required: Yes

EventTypesIds

A list of event types associated with this notification rule. For a list of allowed events, see [EventTypeSummary](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Name

The name for the notification rule. Notification rule names must be unique in your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9\-_]+$`

Required: Yes

Resource

The Amazon Resource Name (ARN) of the resource to associate with the notification rule. Supported resources include pipelines in AWS CodePipeline, repositories in AWS CodeCommit, and build projects in AWS CodeBuild.

Type: String

Pattern: `^arn:aws[^:\s]*:[^:\s]*:[^:\s]*:[0-9]{12}:[^:\s]+$`

Required: Yes

Status

The status of the notification rule. The default value is ENABLED. If the status is set to DISABLED, notifications aren't sent for the notification rule.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

Tags

A list of tags to apply to this notification rule. Key names cannot start with "aws".

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^([\p{L}\p{Z}\p{N}_ . :/=+\-@]*)$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}\p{N}_ . :/=+\-@]*)$`

Required: No

Targets

A list of Amazon Resource Names (ARNs) of Amazon Simple Notification Service topics and Amazon Q Developer in chat applications clients to associate with the notification rule.

Type: Array of [Target](#) objects

Array Members: Maximum number of 10 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

AWS CodeStar Notifications can't create the notification rule because you do not have sufficient permissions.

HTTP Status Code: 403

ConcurrentModificationException

AWS CodeStar Notifications can't complete the request because the resource is being modified by another process. Wait a few minutes and try again.

HTTP Status Code: 400

ConfigurationException

Some or all of the configuration is incomplete, missing, or not valid.

HTTP Status Code: 400

LimitExceededException

One of the AWS CodeStar Notifications limits has been exceeded. Limits apply to accounts, notification rules, notifications, resources, and targets. For more information, see [Limits](#).

HTTP Status Code: 400

ResourceAlreadyExistsException

A resource with the same name or ID already exists. Notification rule names must be unique in your AWS account.

HTTP Status Code: 409

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNotificationRule

Deletes a notification rule for a resource.

Request Syntax

```
POST /deleteNotificationRule HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[Arn](#)

The Amazon Resource Name (ARN) of the notification rule you want to delete.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the deleted notification rule.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConcurrentModificationException

AWS CodeStar Notifications can't complete the request because the resource is being modified by another process. Wait a few minutes and try again.

HTTP Status Code: 400

LimitExceededException

One of the AWS CodeStar Notifications limits has been exceeded. Limits apply to accounts, notification rules, notifications, resources, and targets. For more information, see [Limits](#).

HTTP Status Code: 400

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTarget

Deletes a specified target for notifications.

Request Syntax

```
POST /deleteTarget HTTP/1.1
Content-type: application/json

{
  "ForceUnsubscribeAll": boolean,
  "TargetAddress": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ForceUnsubscribeAll

A Boolean value that can be used to delete all associations with this Amazon Q Developer in chat applications topic. The default value is FALSE. If set to TRUE, all associations between that target and every notification rule in your AWS account are deleted.

Type: Boolean

Required: No

TargetAddress

The Amazon Resource Name (ARN) of the Amazon Q Developer in chat applications topic or Amazon Q Developer in chat applications client to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeNotificationRule

Returns information about a specified notification rule.

Request Syntax

```
POST /describeNotificationRule HTTP/1.1
Content-type: application/json

{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "CreatedBy": "string",
```

```
"CreatedTimestamp": number,
"DetailType": "string",
"EventTypes": [
  {
    "EventTypeId": "string",
    "EventTypeName": "string",
    "ResourceType": "string",
    "ServiceName": "string"
  }
],
"LastModifiedTimestamp": number,
"Name": "string",
"Resource": "string",
"Status": "string",
"Tags": {
  "string" : "string"
},
"Targets": [
  {
    "TargetAddress": "string",
    "TargetStatus": "string",
    "TargetType": "string"
  }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

CreatedBy

The name or email alias of the person who created the notification rule.

Type: String

Length Constraints: Minimum length of 1.

CreatedTimestamp

The date and time the notification rule was created, in timestamp format.

Type: Timestamp

DetailType

The level of detail included in the notifications for this resource. BASIC will include only the contents of the event as it would appear in Amazon CloudWatch. FULL will include any supplemental information provided by AWS CodeStar Notifications and/or the service for the resource for which the notification is created.

Type: String

Valid Values: BASIC | FULL

EventTypes

A list of the event types associated with the notification rule.

Type: Array of [EventTypeSummary](#) objects

LastModifiedTimestamp

The date and time the notification rule was most recently updated, in timestamp format.

Type: Timestamp

Name

The name of the notification rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9\-_]+\$

Resource

The Amazon Resource Name (ARN) of the resource associated with the notification rule.

Type: String

Pattern: `^arn:aws[^:\s]*:[^:\s]*:[^:\s]*:[0-9]{12}:[^\\s]+$`

Status

The status of the notification rule. Valid statuses are on (sending notifications) or off (not sending notifications).

Type: String

Valid Values: ENABLED | DISABLED

Tags

The tags associated with the notification rule.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^([\p{L}\p{Z}\p{N}_ :/=+\-@]*)$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}\p{N}_ :/=+\-@]*)$`

Targets

A list of the Amazon Q Developer in chat applications topics and Amazon Q Developer in chat applications clients associated with the notification rule.

Type: Array of [TargetSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventTypes

Returns information about the event types available for configuring notifications.

Request Syntax

```
POST /listEventTypes HTTP/1.1
Content-type: application/json

{
  "Filters": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

The filters to use to return information by service or resource type.

Type: Array of [ListEventTypesFilter](#) objects

Required: No

MaxResults

A non-negative integer used to limit the number of returned results. The default number is 50. The maximum number of results that can be returned is 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken](#)

An enumeration token that, when provided in a request, returns the next batch of the results.

Type: String

Pattern: `^[\\w/+=]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EventTypes": [
    {
      "EventTypeId": "string",
      "EventTypeName": "string",
      "ResourceType": "string",
      "ServiceName": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EventTypes](#)

Information about each event, including service name, resource type, event ID, and event name.

Type: Array of [EventTypeSummary](#) objects

NextToken

An enumeration token that can be used in a request to return the next batch of the results.

Type: String

Pattern: `^\w/+=]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The value for the enumeration token used in the request to return the next batch of the results is not valid.

HTTP Status Code: 400

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNotificationRules

Returns a list of the notification rules for an AWS account.

Request Syntax

```
POST /listNotificationRules HTTP/1.1
Content-type: application/json

{
  "Filters": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

The filters to use to return information by service or resource type. For valid values, see [ListNotificationRulesFilter](#).

Note

A filter with the same name can appear more than once when used with OR statements. Filters with different names should be applied with AND statements.

Type: Array of [ListNotificationRulesFilter](#) objects

Required: No

MaxResults

A non-negative integer used to limit the number of returned results. The maximum number of results that can be returned is 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

An enumeration token that, when provided in a request, returns the next batch of the results.

Type: String

Pattern: `^[\w/+=]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "NotificationRules": [
    {
      "Arn": "string",
      "Id": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

An enumeration token that can be used in a request to return the next batch of the results.

Type: String

Pattern: `^\w/+=]+$`

NotificationRules

The list of notification rules for the AWS account, by Amazon Resource Name (ARN) and ID.

Type: Array of [NotificationRuleSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The value for the enumeration token used in the request to return the next batch of the results is not valid.

HTTP Status Code: 400

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of the tags associated with a notification rule.

Request Syntax

```
POST /listTagsForResource HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) for the notification rule.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Tags": {
    "string" : "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The tags associated with the notification rule.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: $^([\p{L}\p{Z}\p{N}_ :/=+\-@]^*)\$$

Value Length Constraints: Maximum length of 256.

Value Pattern: $^([\p{L}\p{Z}\p{N}_ :/=+\-@]^*)\$$

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTargets

Returns a list of the notification rule targets for an AWS account.

Request Syntax

```
POST /listTargets HTTP/1.1
Content-type: application/json

{
  "Filters": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

The filters to use to return information by service or resource type. Valid filters include target type, target address, and target status.

Note

A filter with the same name can appear more than once when used with OR statements. Filters with different names should be applied with AND statements.

Type: Array of [ListTargetsFilter](#) objects

Required: No

MaxResults

A non-negative integer used to limit the number of returned results. The maximum number of results that can be returned is 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

An enumeration token that, when provided in a request, returns the next batch of the results.

Type: String

Pattern: `^[\\w/+=]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Targets": [
    {
      "TargetAddress": "string",
      "TargetStatus": "string",
      "TargetType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

An enumeration token that can be used in a request to return the next batch of results.

Type: String

Pattern: `^\[\w/+=\]+`

Targets

The list of notification rule targets.

Type: Array of [TargetSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The value for the enumeration token used in the request to return the next batch of the results is not valid.

HTTP Status Code: 400

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Subscribe

Creates an association between a notification rule and an Amazon Q Developer in chat applications topic or Amazon Q Developer in chat applications client so that the associated target can receive notifications when the events described in the rule are triggered.

Request Syntax

```
POST /subscribe HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "ClientRequestToken": "string",
  "Target": {
    "TargetAddress": "string",
    "TargetType": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the notification rule for which you want to create the association.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

ClientRequestToken

An enumeration token that, when provided in a request, returns the next batch of the results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w:/-]+$`

Required: No

Target

Information about the Amazon Q Developer in chat applications topics or Amazon Q Developer in chat applications clients associated with a notification rule.

Type: [Target](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the notification rule for which you have created associations.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConfigurationException

Some or all of the configuration is incomplete, missing, or not valid.

HTTP Status Code: 400

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates a set of provided tags with a notification rule.

Request Syntax

```
POST /tagResource HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the notification rule to tag.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

Tags

The list of tags to associate with the resource. Tag key names cannot start with "aws".

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=+\-@]^*)\$$

Value Length Constraints: Maximum length of 256.

Value Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=+\-@]^*)\$$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The list of tags associated with the resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=+\-@]^*)\$$

Value Length Constraints: Maximum length of 256.

Value Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=+\-@]^*)\$$

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConcurrentModificationException

AWS CodeStar Notifications can't complete the request because the resource is being modified by another process. Wait a few minutes and try again.

HTTP Status Code: 400

LimitExceededException

One of the AWS CodeStar Notifications limits has been exceeded. Limits apply to accounts, notification rules, notifications, resources, and targets. For more information, see [Limits](#).

HTTP Status Code: 400

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

Unsubscribe

Removes an association between a notification rule and an Amazon Q Developer in chat applications topic so that subscribers to that topic stop receiving notifications when the events described in the rule are triggered.

Request Syntax

```
POST /unsubscribe HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "TargetAddress": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

TargetAddress

The ARN of the Amazon Q Developer in chat applications topic to unsubscribe from the notification rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the the notification rule from which you have removed a subscription.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes the association between one or more provided tags and a notification rule.

Request Syntax

```
POST /untagResource/resourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the notification rule from which to remove the tags.

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

TagKeys

The key names of the tags to remove.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConcurrentModificationException

AWS CodeStar Notifications can't complete the request because the resource is being modified by another process. Wait a few minutes and try again.

HTTP Status Code: 400

LimitExceededException

One of the AWS CodeStar Notifications limits has been exceeded. Limits apply to accounts, notification rules, notifications, resources, and targets. For more information, see [Limits](#).

HTTP Status Code: 400

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNotificationRule

Updates a notification rule for a resource. You can change the events that trigger the notification rule, the status of the rule, and the targets that receive the notifications.

Note

To add or remove tags for a notification rule, you must use [TagResource](#) and [UntagResource](#).

Request Syntax

```
POST /updateNotificationRule HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "DetailType": "string",
  "EventTypeId": [ "string" ],
  "Name": "string",
  "Status": "string",
  "Targets": [
    {
      "TargetAddress": "string",
      "TargetType": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^:\s]*:codestar-notifications:[^:\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: Yes

DetailType

The level of detail to include in the notifications for this resource. BASIC will include only the contents of the event as it would appear in Amazon CloudWatch. FULL will include any supplemental information provided by AWS CodeStar Notifications and/or the service for the resource for which the notification is created.

Type: String

Valid Values: BASIC | FULL

Required: No

EventTypesIds

A list of event types associated with this notification rule. For a complete list of event types and IDs, see [Notification concepts](#) in the *Developer Tools Console User Guide*.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

Name

The name of the notification rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9\-_]+$`

Required: No

Status

The status of the notification rule. Valid statuses include enabled (sending notifications) or disabled (not sending notifications).

Type: String

Valid Values: ENABLED | DISABLED

Required: No

Targets

The address and type of the targets to receive notifications from this notification rule.

Type: Array of [Target](#) objects

Array Members: Maximum number of 10 items.

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConfigurationException

Some or all of the configuration is incomplete, missing, or not valid.

HTTP Status Code: 400

ResourceNotFoundException

AWS CodeStar Notifications can't find a resource that matches the provided ARN.

HTTP Status Code: 404

ValidationException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS CodeStar Notifications API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [EventTypeSummary](#)
- [ListEventTypesFilter](#)
- [ListNotificationRulesFilter](#)
- [ListTargetsFilter](#)
- [NotificationRuleSummary](#)
- [Target](#)
- [TargetSummary](#)

EventTypeSummary

Returns information about an event that has triggered a notification rule.

Contents

EventTypeId

The system-generated ID of the event. For a complete list of event types and IDs, see [Notification concepts](#) in the *Developer Tools Console User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

EventTypeName

The name of the event.

Type: String

Required: No

ResourceType

The resource type of the event.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `^[a-zA-Z0-9-]+$`

Required: No

ServiceName

The name of the service for which the event applies.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListEventTypesFilter

Information about a filter to apply to the list of returned event types. You can filter by resource type or service name.

Contents

Name

The system-generated name of the filter type you want to filter by.

Type: String

Valid Values: RESOURCE_TYPE | SERVICE_NAME

Required: Yes

Value

The name of the resource type (for example, pipeline) or service name (for example, CodePipeline) that you want to filter by.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListNotificationRulesFilter

Information about a filter to apply to the list of returned notification rules. You can filter by event type, owner, resource, or target.

Contents

Name

The name of the attribute you want to use to filter the returned notification rules.

Type: String

Valid Values: `EVENT_TYPE_ID` | `CREATED_BY` | `RESOURCE` | `TARGET_ADDRESS`

Required: Yes

Value

The value of the attribute you want to use to filter the returned notification rules. For example, if you specify filtering by *RESOURCE* in Name, you might specify the ARN of a pipeline in AWS CodePipeline for the value.

Type: String

Length Constraints: Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListTargetsFilter

Information about a filter to apply to the list of returned targets. You can filter by target type, address, or status. For example, to filter results to notification rules that have active Amazon Q Developer in chat applications topics as targets, you could specify a ListTargetsFilter Name as TargetType and a Value of SNS, and a Name of TARGET_STATUS and a Value of ACTIVE.

Contents

Name

The name of the attribute you want to use to filter the returned targets.

Type: String

Valid Values: TARGET_TYPE | TARGET_ADDRESS | TARGET_STATUS

Required: Yes

Value

The value of the attribute you want to use to filter the returned targets. For example, if you specify SNS for the Target type, you could specify an Amazon Resource Name (ARN) for a topic as the value.

Type: String

Length Constraints: Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotificationRuleSummary

Information about a specified notification rule.

Contents

Arn

The Amazon Resource Name (ARN) of the notification rule.

Type: String

Pattern: `^arn:aws[^\s]*:codestar-notifications:[^\s]+:\d{12}:notificationrule\/(.*\S)?$`

Required: No

Id

The unique ID of the notification rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 40.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Target

Information about the Amazon Q Developer in chat applications topics or Amazon Q Developer in chat applications clients associated with a notification rule.

Contents

TargetAddress

The Amazon Resource Name (ARN) of the Amazon Q Developer in chat applications topic or Amazon Q Developer in chat applications client.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Required: No

TargetType

The target type. Can be an Amazon Q Developer in chat applications topic or Amazon Q Developer in chat applications client.

- Amazon Q Developer in chat applications topics are specified as SNS.
- Amazon Q Developer in chat applications clients are specified as AWSChatbotSlack.
- Amazon Q Developer in chat applications clients for Microsoft Teams are specified as AWSChatbotMicrosoftTeams.

Type: String

Pattern: `^[A-Za-z]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

TargetSummary

Information about the targets specified for a notification rule.

Contents

TargetAddress

The Amazon Resource Name (ARN) of the Amazon Q Developer in chat applications topic or Amazon Q Developer in chat applications client.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Required: No

TargetStatus

The status of the target.

Type: String

Valid Values: PENDING | ACTIVE | UNREACHABLE | INACTIVE | DEACTIVATED

Required: No

TargetType

The type of the target (for example, SNS).

- Amazon Q Developer in chat applications topics are specified as SNS.
- Amazon Q Developer in chat applications clients for Slack are specified as `AWSChatbotSlack`.
- Amazon Q Developer in chat applications clients for Microsoft Teams are specified as `AWSChatbotMicrosoftTeams`.

Type: String

Pattern: `^[A-Za-z]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400