



API Reference

EBS direct APIs



API Version 2019-11-02

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

EBS direct APIs: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CompleteSnapshot	3
Request Syntax	3
URI Request Parameters	3
Request Body	4
Response Syntax	4
Response Elements	5
Errors	5
See Also	6
GetSnapshotBlock	8
Request Syntax	8
URI Request Parameters	8
Request Body	9
Response Syntax	9
Response Elements	9
Errors	10
See Also	11
ListChangedBlocks	13
Request Syntax	13
URI Request Parameters	13
Request Body	15
Response Syntax	15
Response Elements	15
Errors	16
See Also	17
ListSnapshotBlocks	19
Request Syntax	19
URI Request Parameters	19
Request Body	20
Response Syntax	20
Response Elements	21
Errors	21
See Also	23

PutSnapshotBlock	24
Request Syntax	24
URI Request Parameters	24
Request Body	26
Response Syntax	26
Response Elements	26
Errors	27
See Also	28
StartSnapshot	30
Request Syntax	30
URI Request Parameters	30
Request Body	31
Response Syntax	34
Response Elements	35
Errors	37
See Also	38
Data Types	40
Block	41
Contents	41
See Also	41
ChangedBlock	42
Contents	42
See Also	43
Tag	44
Contents	44
See Also	44
Common Parameters	45
Common Error Types	48

Welcome

You can use the Amazon Elastic Block Store (Amazon EBS) direct APIs to create Amazon EBS snapshots, write data directly to your snapshots, read data on your snapshots, and identify the differences or changes between two snapshots. If you're an independent software vendor (ISV) who offers backup services for Amazon EBS, the EBS direct APIs make it more efficient and cost-effective to track incremental changes on your Amazon EBS volumes through snapshots. This can be done without having to create new volumes from snapshots, and then use Amazon Elastic Compute Cloud (Amazon EC2) instances to compare the differences.

You can create incremental snapshots directly from data on-premises into volumes and the cloud to use for quick disaster recovery. With the ability to write and read snapshots, you can write your on-premises data to a snapshot during a disaster. Then after recovery, you can restore it back to AWS or on-premises from the snapshot. You no longer need to build and maintain complex mechanisms to copy data to and from Amazon EBS.

Note

Amazon EBS direct APIs does not support public snapshots and local snapshots on Outposts.

This API reference provides detailed information about the actions, data types, parameters, and errors of the EBS direct APIs. For more information about the elements that make up the EBS direct APIs, and examples of how to use them effectively, see [Accessing the Contents of an Amazon EBS Snapshot](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about the supported AWS Regions, endpoints, and service quotas for the EBS direct APIs, see [Amazon Elastic Block Store Endpoints and Quotas](#) in the *AWS General Reference*.

This document was last published on April 10, 2026.

Actions

The following actions are supported:

- [CompleteSnapshot](#)
- [GetSnapshotBlock](#)
- [ListChangedBlocks](#)
- [ListSnapshotBlocks](#)
- [PutSnapshotBlock](#)
- [StartSnapshot](#)

CompleteSnapshot

Seals and completes the snapshot after all of the required blocks of data have been written to it. Completing the snapshot changes the status to `completed`. You cannot write new blocks to a snapshot after it has been completed.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
POST /snapshots/completion/snapshotId HTTP/1.1
x-amz-ChangedBlocksCount: ChangedBlocksCount
x-amz-Checksum: Checksum
x-amz-Checksum-Algorithm: ChecksumAlgorithm
x-amz-Checksum-Aggregation-Method: ChecksumAggregationMethod
```

URI Request Parameters

The request uses the following URI parameters.

ChangedBlocksCount

The number of blocks that were written to the snapshot.

Valid Range: Minimum value of 0.

Required: Yes

Checksum

An aggregated Base-64 SHA256 checksum based on the checksums of each written block.

To generate the aggregated checksum using the linear aggregation method, arrange the checksums for each written block in ascending order of their block index, concatenate them to form a single string, and then generate the checksum on the entire string using the SHA256 algorithm.

Length Constraints: Maximum length of 64.

Pattern: `^[A-Za-z0-9+/=]+$`

ChecksumAggregationMethod

The aggregation method used to generate the checksum. Currently, the only supported aggregation method is LINEAR.

Length Constraints: Maximum length of 32.

Pattern: `^[A-Za-z0-9]+$`

Valid Values: LINEAR

ChecksumAlgorithm

The algorithm used to generate the checksum. Currently, the only supported algorithm is SHA256.

Length Constraints: Maximum length of 32.

Pattern: `^[A-Za-z0-9]+$`

Valid Values: SHA256

snapshotId

The ID of the snapshot.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json
```

```
{  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

Status

The status of the snapshot.

Type: String

Length Constraints: Maximum length of 32.

Valid Values: completed | pending | error

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

InternalServerError

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSnapshotBlock

Returns the data in a block in an Amazon Elastic Block Store snapshot.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
GET /snapshots/snapshotId/blocks/blockIndex?blockToken=BlockToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

blockIndex

The block index of the block in which to read the data. A block index is a logical index in units of 512 KiB blocks. To identify the block index, divide the logical offset of the data in the logical volume by the block size (logical offset of data/524288). The logical offset of the data must be 512 KiB aligned.

Valid Range: Minimum value of 0.

Required: Yes

BlockToken

The block token of the block from which to get data. You can obtain the `BlockToken` by running the `ListChangedBlocks` or `ListSnapshotBlocks` operations.

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

Required: Yes

snapshotId

The ID of the snapshot containing the block from which to get data.

Important

If the specified snapshot is encrypted, you must have permission to use the KMS key that was used to encrypt the snapshot. For more information, see [Using encryption](#) in the *Amazon Elastic Compute Cloud User Guide*.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^snap-[0-9a-f]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
x-amz-Data-Length: DataLength
x-amz-Checksum: Checksum
x-amz-Checksum-Algorithm: ChecksumAlgorithm
```

BlockData

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

Checksum

The checksum generated for the block, which is Base64 encoded.

Length Constraints: Maximum length of 64.

Pattern: `^[A-Za-z0-9+/=]+$`

ChecksumAlgorithm

The algorithm used to generate the checksum for the block, such as SHA256.

Length Constraints: Maximum length of 32.

Pattern: `^[A-Za-z0-9]+$`

Valid Values: SHA256

DataLength

The size of the data in the block.

The response returns the following as the HTTP body.

BlockData

The data content of the block.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

InternalServerError

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChangedBlocks

Returns information about the blocks that are different between two Amazon EBS snapshots of the same volume or between two snapshot copies of the same source snapshot.

If you specify snapshot copies, the API returns the difference only if the two snapshots are incremental copies. For more information, see [Incremental snapshot copying](#).

You must have permissions to access the specified snapshots.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
GET /snapshots/secondSnapshotId/changedblocks?  
firstSnapshotId=FirstSnapshotId&maxResults=MaxResults&pageToken=NextToken&startingBlockIndex=St  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[FirstSnapshotId](#)

The ID of the first snapshot to use for the comparison.

Important

The `FirstSnapshotID` parameter must be specified with a `SecondSnapshotId` parameter; otherwise, an error occurs.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

MaxResults

The maximum number of blocks to be returned by the request.

Even if additional blocks can be retrieved from the snapshot, the request can return less blocks than **MaxResults** or an empty array of blocks.

To retrieve the next set of blocks from the snapshot, make another request with the returned **NextToken** value. The value of **NextToken** is null when there are no more blocks to return.

Valid Range: Minimum value of 100. Maximum value of 10000.

NextToken

The token to request the next page of results.

If you specify **NextToken**, then **StartingBlockIndex** is ignored.

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

secondSnapshotId

The ID of the second snapshot to use for the comparison.

Important

The `SecondSnapshotId` parameter must be specified with a `FirstSnapshotID` parameter; otherwise, an error occurs.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

Required: Yes

StartingBlockIndex

The block index from which the comparison should start.

The list in the response will start from this block index or the next valid block index in the snapshots.

If you specify **NextToken**, then **StartingBlockIndex** is ignored.

Valid Range: Minimum value of 0.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BlockSize": number,
  "ChangedBlocks": [
    {
      "BlockIndex": number,
      "FirstBlockToken": "string",
      "SecondBlockToken": "string"
    }
  ],
  "ExpiryTime": number,
  "NextToken": "string",
  "VolumeSize": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BlockSize

The size of the blocks in the snapshot, in bytes.

Type: Integer

ChangedBlocks

An array of objects containing information about the changed blocks.

Type: Array of [ChangedBlock](#) objects

[ExpiryTime](#)

The time when the BlockToken expires.

Type: Timestamp

[NextToken](#)

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

[VolumeSize](#)

The size of the volume in GB.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSnapshotBlocks

Returns information about the blocks in an Amazon Elastic Block Store snapshot.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
GET /snapshots/snapshotId/blocks?  
maxResults=MaxResults&pageToken=NextToken&startingBlockIndex=StartingBlockIndex  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of blocks to be returned by the request.

Even if additional blocks can be retrieved from the snapshot, the request can return less blocks than **MaxResults** or an empty array of blocks.

To retrieve the next set of blocks from the snapshot, make another request with the returned **NextToken** value. The value of **NextToken** is `null` when there are no more blocks to return.

Valid Range: Minimum value of 100. Maximum value of 10000.

NextToken

The token to request the next page of results.

If you specify **NextToken**, then **StartingBlockIndex** is ignored.

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

snapshotId

The ID of the snapshot from which to get block indexes and block tokens.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

Required: Yes

StartingBlockIndex

The block index from which the list should start. The list in the response will start from this block index or the next valid block index in the snapshot.

If you specify **NextToken**, then **StartingBlockIndex** is ignored.

Valid Range: Minimum value of 0.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Blocks": [
    {
      "BlockIndex": number,
      "BlockToken": "string"
    }
  ],
  "BlockSize": number,
  "ExpiryTime": number,
  "NextToken": "string",
  "VolumeSize": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Blocks

An array of objects containing information about the blocks.

Type: Array of [Block](#) objects

BlockSize

The size of the blocks in the snapshot, in bytes.

Type: Integer

ExpiryTime

The time when the BlockToken expires.

Type: Timestamp

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

VolumeSize

The size of the volume in GB.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutSnapshotBlock

Writes a block of data to a snapshot. If the specified block contains data, the existing data is overwritten. The target snapshot must be in the pending state.

Data written to a snapshot must be aligned with 512-KiB sectors.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
PUT /snapshots/snapshotId/blocks/blockIndex HTTP/1.1
x-amz-Data-Length: DataLength
x-amz-Progress: Progress
x-amz-Checksum: Checksum
x-amz-Checksum-Algorithm: ChecksumAlgorithm
```

BlockData

URI Request Parameters

The request uses the following URI parameters.

blockIndex

The block index of the block in which to write the data. A block index is a logical index in units of 512 KiB blocks. To identify the block index, divide the logical offset of the data in the logical volume by the block size (logical offset of data/524288). The logical offset of the data must be 512 KiB aligned.

Valid Range: Minimum value of 0.

Required: Yes

Checksum

A Base64-encoded SHA256 checksum of the data. Only SHA256 checksums are supported.

Length Constraints: Maximum length of 64.

Pattern: `^[A-Za-z0-9+/=]+$`

Required: Yes

ChecksumAlgorithm

The algorithm used to generate the checksum. Currently, the only supported algorithm is SHA256.

Length Constraints: Maximum length of 32.

Pattern: `^[A-Za-z0-9]+$`

Valid Values: SHA256

Required: Yes

DataLength

The size of the data to write to the block, in bytes. Currently, the only supported size is 524288 bytes.

Valid values: 524288

Required: Yes

Progress

The progress of the write process, as a percentage.

Valid Range: Minimum value of 0. Maximum value of 100.

snapshotId

The ID of the snapshot.

Important

If the specified snapshot is encrypted, you must have permission to use the KMS key that was used to encrypt the snapshot. For more information, see [Using encryption](#) in the *Amazon Elastic Compute Cloud User Guide*..

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

Required: Yes

Request Body

The request accepts the following binary data.

BlockData

The data to write to the block.

The block data is not signed as part of the Signature Version 4 signing process. As a result, you must generate and provide a Base64-encoded SHA256 checksum for the block data using the **x-amz-Checksum** header. Also, you must specify the checksum algorithm using the **x-amz-Checksum-Algorithm** header. The checksum that you provide is part of the Signature Version 4 signing process. It is validated against a checksum generated by Amazon EBS to ensure the validity and authenticity of the data. If the checksums do not correspond, the request fails. For more information, see [Using checksums with the EBS direct APIs](#) in the *Amazon Elastic Compute Cloud User Guide*.

Required: Yes

Response Syntax

```
HTTP/1.1 201
x-amz-Checksum: Checksum
x-amz-Checksum-Algorithm: ChecksumAlgorithm
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The response returns the following HTTP headers.

Checksum

The SHA256 checksum generated for the block data by Amazon EBS.

Length Constraints: Maximum length of 64.

Pattern: `^[A-Za-z0-9+/=]+$`

ChecksumAlgorithm

The algorithm used by Amazon EBS to generate the checksum.

Length Constraints: Maximum length of 32.

Pattern: `^[A-Za-z0-9]+$`

Valid Values: SHA256

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

InternalServerError

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartSnapshot

Creates a new Amazon EBS snapshot. The new snapshot enters the pending state after the request completes.

After creating the snapshot, use [PutSnapshotBlock](#) to write blocks of data to the snapshot.

Note

You should always retry requests that receive server (5xx) error responses, and `ThrottlingException` and `RequestThrottledException` client error responses. For more information see [Error retries](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Syntax

```
POST /snapshots HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "Description": "string",
  "Encrypted": boolean,
  "KmsKeyArn": "string",
  "ParentSnapshotId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Timeout": number,
  "VolumeSize": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully. The subsequent retries with the same client token return the result from the original successful request and they have no additional effect.

If you do not specify a client token, one is automatically generated by the AWS SDK.

For more information, see [Idempotency for StartSnapshot API](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `^[\\S]+$`

Required: No

Description

A description for the snapshot.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `^[\\S\\s]+$`

Required: No

Encrypted

Indicates whether to encrypt the snapshot.

You can't specify **Encrypted** and **ParentSnapshotId** in the same request. If you specify both parameters, the request fails with `ValidationException`.

The encryption status of the snapshot depends on the values that you specify for **Encrypted**, **KmsKeyArn**, and **ParentSnapshotId**, and whether your AWS account is enabled for [encryption by default](#). For more information, see [Using encryption](#) in the *Amazon Elastic Compute Cloud User Guide*.

⚠ Important

To create an encrypted snapshot, you must have permission to use the KMS key. For more information, see [Permissions to use AWS Key Management Service keys](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: Boolean

Required: No

KmsKeyArn

The Amazon Resource Name (ARN) of the AWS Key Management Service (AWS KMS) key to be used to encrypt the snapshot.

The encryption status of the snapshot depends on the values that you specify for **Encrypted**, **KmsKeyArn**, and **ParentSnapshotId**, and whether your AWS account is enabled for [encryption by default](#). For more information, see [Using encryption](#) in the *Amazon Elastic Compute Cloud User Guide*.

⚠ Important

To create an encrypted snapshot, you must have permission to use the KMS key. For more information, see [Permissions to use AWS Key Management Service keys](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws[a-z\-*]:kms:.*:[0-9]{12}:key/.*`

Required: No

ParentSnapshotId

The ID of the parent snapshot. If there is no parent snapshot, or if you are creating the first snapshot for an on-premises volume, omit this parameter.

You can't specify **ParentSnapshotId** and **Encrypted** in the same request. If you specify both parameters, the request fails with `ValidationException`.

The encryption status of the snapshot depends on the values that you specify for **Encrypted**, **KmsKeyArn**, and **ParentSnapshotId**, and whether your AWS account is enabled for [encryption by default](#). For more information, see [Using encryption](#) in the *Amazon Elastic Compute Cloud User Guide*.

Important

If you specify an encrypted parent snapshot, you must have permission to use the KMS key that was used to encrypt the parent snapshot. For more information, see [Permissions to use AWS Key Management Service keys](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^snap-[0-9a-f]+$`

Required: No

Tags

The tags to apply to the snapshot.

Type: Array of [Tag](#) objects

Required: No

Timeout

The amount of time (in minutes) after which the snapshot is automatically cancelled if:

- No blocks are written to the snapshot.

- The snapshot is not completed after writing the last block of data.

If no value is specified, the timeout defaults to 60 minutes.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 4320.

Required: No

VolumeSize

The size of the volume, in GiB. The maximum size is 65536 GiB (64 TiB).

Type: Long

Valid Range: Minimum value of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "BlockSize": number,
  "Description": "string",
  "KmsKeyArn": "string",
  "OwnerId": "string",
  "ParentSnapshotId": "string",
  "SnapshotId": "string",
  "SseType": "string",
  "StartTime": number,
  "Status": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VolumeSize": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

BlockSize

The size of the blocks in the snapshot, in bytes.

Type: Integer

Description

The description of the snapshot.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `^[\S\s]+$`

KmsKeyArn

The Amazon Resource Name (ARN) of the AWS Key Management Service (AWS KMS) key used to encrypt the snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws[a-z\-*:kms:.*:[0-9]{12}:key/.*`

OwnerId

The AWS account ID of the snapshot owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `\S+`

ParentSnapshotId

The ID of the parent snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^snap-[0-9a-f]+\$

SnapshotId

The ID of the snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^snap-[0-9a-f]+\$

SseType

Reserved for future use.

Type: String

Valid Values: sse-ebc | sse-kms | none

StartTime

The timestamp when the snapshot was created.

Type: Timestamp

Status

The status of the snapshot.

Type: String

Length Constraints: Maximum length of 32.

Valid Values: completed | pending | error

Tags

The tags applied to the snapshot. You can specify up to 50 tags per snapshot. For more information, see [Tagging your Amazon EC2 resources](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: Array of [Tag](#) objects

VolumeSize

The size of the volume, in GiB.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 403

ConcurrentLimitExceededException

You have reached the limit for concurrent API requests. For more information, see [Optimizing performance of the EBS direct APIs](#) in the *Amazon Elastic Compute Cloud User Guide*.

HTTP Status Code: 400

ConflictException

The request uses the same client token as a previous, but non-identical request.

HTTP Status Code: 409

InternalServerError

An internal error has occurred. For more information see [Error retries](#).

HTTP Status Code: 500

RequestThrottledException

The number of API requests has exceeded the maximum allowed API request throttling limit for the snapshot. For more information see [Error retries](#).

Reason

The reason for the exception.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

Reason

The reason for the exception.

HTTP Status Code: 404

ServiceQuotaExceededException

Your current service quotas do not allow you to perform this action.

Reason

The reason for the exception.

HTTP Status Code: 402

ValidationException

The input fails to satisfy the constraints of the EBS direct APIs.

Reason

The reason for the validation exception.

HTTP Status Code: 400

See Also


For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The EBS direct APIs API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Block](#)
- [ChangedBlock](#)
- [Tag](#)

Block

A block of data in an Amazon Elastic Block Store snapshot.

Contents

BlockIndex

The block index.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

BlockToken

The block token for the block index.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChangedBlock

A block of data in an Amazon Elastic Block Store snapshot that is different from another snapshot of the same volume/snapshot lineage.

Contents

BlockIndex

The block index.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

FirstBlockToken

The block token for the block index of the `FirstSnapshotId` specified in the `ListChangedBlocks` operation. This value is absent if the first snapshot does not have the changed block that is on the second snapshot.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

Required: No

SecondBlockToken

The block token for the block index of the `SecondSnapshotId` specified in the `ListChangedBlocks` operation.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[A-Za-z0-9+/=]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Describes a tag.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Maximum length of 127.

Pattern: `^[\S\s]+$`

Required: No

Value

The value of the tag.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `^[\S\s]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400