



Welcome

# NeptuneAnalyticsAPI



**API Version 2023-11-29**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# NeptuneAnalyticsAPI: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
CancelExportTask .....	4
Request Syntax .....	4
URI Request Parameters .....	4
Request Body .....	4
Response Syntax .....	4
Response Elements .....	5
Errors .....	6
See Also .....	8
CancelImportTask .....	9
Request Syntax .....	9
URI Request Parameters .....	9
Request Body .....	9
Response Syntax .....	9
Response Elements .....	10
Errors .....	11
See Also .....	12
CancelQuery .....	14
Request Syntax .....	14
URI Request Parameters .....	14
Request Body .....	14
Response Syntax .....	14
Response Elements .....	14
Errors .....	15
See Also .....	16
CreateGraph .....	17
Request Syntax .....	17
URI Request Parameters .....	17
Request Body .....	17
Response Syntax .....	20
Response Elements .....	20
Errors .....	23
See Also .....	25

---

CreateGraphSnapshot .....	26
Request Syntax .....	26
URI Request Parameters .....	26
Request Body .....	26
Response Syntax .....	27
Response Elements .....	27
Errors .....	29
See Also .....	31
CreateGraphUsingImportTask .....	32
Request Syntax .....	32
URI Request Parameters .....	32
Request Body .....	33
Response Syntax .....	37
Response Elements .....	37
Errors .....	39
See Also .....	40
CreatePrivateGraphEndpoint .....	42
Request Syntax .....	42
URI Request Parameters .....	42
Request Body .....	42
Response Syntax .....	43
Response Elements .....	43
Errors .....	44
See Also .....	46
DeleteGraph .....	48
Request Syntax .....	48
URI Request Parameters .....	48
Request Body .....	48
Response Syntax .....	48
Response Elements .....	49
Errors .....	51
See Also .....	53
DeleteGraphSnapshot .....	54
Request Syntax .....	54
URI Request Parameters .....	54
Request Body .....	54

---

Response Syntax .....	54
Response Elements .....	55
Errors .....	56
See Also .....	57
DeletePrivateGraphEndpoint .....	59
Request Syntax .....	59
URI Request Parameters .....	59
Request Body .....	59
Response Syntax .....	59
Response Elements .....	60
Errors .....	60
See Also .....	62
ExecuteQuery .....	63
Request Syntax .....	63
URI Request Parameters .....	63
Request Body .....	64
Response Syntax .....	65
Response Elements .....	65
Errors .....	65
See Also .....	67
GetExportTask .....	68
Request Syntax .....	68
URI Request Parameters .....	68
Request Body .....	68
Response Syntax .....	68
Response Elements .....	69
Errors .....	71
See Also .....	72
GetGraph .....	74
Request Syntax .....	74
URI Request Parameters .....	74
Request Body .....	74
Response Syntax .....	74
Response Elements .....	75
Errors .....	77
See Also .....	78

---

GetGraphSnapshot .....	80
Request Syntax .....	80
URI Request Parameters .....	80
Request Body .....	80
Response Syntax .....	80
Response Elements .....	81
Errors .....	82
See Also .....	83
GetGraphSummary .....	84
Request Syntax .....	84
URI Request Parameters .....	84
Request Body .....	84
Response Syntax .....	84
Response Elements .....	85
Errors .....	86
See Also .....	87
GetImportTask .....	89
Request Syntax .....	89
URI Request Parameters .....	89
Request Body .....	89
Response Syntax .....	89
Response Elements .....	90
Errors .....	92
See Also .....	93
GetPrivateGraphEndpoint .....	95
Request Syntax .....	95
URI Request Parameters .....	95
Request Body .....	95
Response Syntax .....	95
Response Elements .....	96
Errors .....	96
See Also .....	97
GetQuery .....	99
Request Syntax .....	99
URI Request Parameters .....	99
Request Body .....	99

---

Response Syntax .....	99
Response Elements .....	100
Errors .....	101
See Also .....	102
ListExportTasks .....	103
Request Syntax .....	103
URI Request Parameters .....	103
Request Body .....	103
Response Syntax .....	103
Response Elements .....	104
Errors .....	104
See Also .....	105
ListGraphs .....	107
Request Syntax .....	107
URI Request Parameters .....	107
Request Body .....	107
Response Syntax .....	107
Response Elements .....	108
Errors .....	109
See Also .....	109
ListGraphSnapshots .....	111
Request Syntax .....	111
URI Request Parameters .....	111
Request Body .....	111
Response Syntax .....	112
Response Elements .....	112
Errors .....	113
See Also .....	114
ListImportTasks .....	115
Request Syntax .....	115
URI Request Parameters .....	115
Request Body .....	115
Response Syntax .....	115
Response Elements .....	116
Errors .....	116
See Also .....	117

---

ListPrivateGraphEndpoints .....	119
Request Syntax .....	119
URI Request Parameters .....	119
Request Body .....	120
Response Syntax .....	120
Response Elements .....	120
Errors .....	121
See Also .....	122
ListQueries .....	123
Request Syntax .....	123
URI Request Parameters .....	123
Request Body .....	123
Response Syntax .....	123
Response Elements .....	124
Errors .....	124
See Also .....	125
ListTagsForResource .....	127
Request Syntax .....	127
URI Request Parameters .....	127
Request Body .....	127
Response Syntax .....	127
Response Elements .....	127
Errors .....	128
See Also .....	129
ResetGraph .....	130
Request Syntax .....	130
URI Request Parameters .....	130
Request Body .....	130
Response Syntax .....	131
Response Elements .....	131
Errors .....	134
See Also .....	135
RestoreGraphFromSnapshot .....	136
Request Syntax .....	136
URI Request Parameters .....	136
Request Body .....	136

---

Response Syntax .....	138
Response Elements .....	139
Errors .....	141
See Also .....	143
StartExportTask .....	144
Request Syntax .....	144
URI Request Parameters .....	145
Request Body .....	145
Response Syntax .....	147
Response Elements .....	148
Errors .....	150
See Also .....	151
StartGraph .....	152
Request Syntax .....	152
URI Request Parameters .....	152
Request Body .....	152
Response Syntax .....	152
Response Elements .....	153
Errors .....	155
See Also .....	156
StartImportTask .....	158
Request Syntax .....	158
URI Request Parameters .....	158
Request Body .....	158
Response Syntax .....	160
Response Elements .....	160
Errors .....	162
See Also .....	163
StopGraph .....	165
Request Syntax .....	165
URI Request Parameters .....	165
Request Body .....	165
Response Syntax .....	165
Response Elements .....	166
Errors .....	168
See Also .....	169

---

TagResource .....	171
Request Syntax .....	171
URI Request Parameters .....	171
Request Body .....	171
Response Syntax .....	172
Response Elements .....	172
Errors .....	172
See Also .....	173
UntagResource .....	175
Request Syntax .....	175
URI Request Parameters .....	175
Request Body .....	175
Response Syntax .....	175
Response Elements .....	176
Errors .....	176
See Also .....	177
UpdateGraph .....	178
Request Syntax .....	178
URI Request Parameters .....	178
Request Body .....	178
Response Syntax .....	179
Response Elements .....	180
Errors .....	182
See Also .....	183
<b>Data Types .....</b>	<b>185</b>
EdgeStructure .....	186
Contents .....	186
See Also .....	186
ExportFilter .....	187
Contents .....	187
See Also .....	187
ExportFilterElement .....	188
Contents .....	188
See Also .....	188
ExportFilterPropertyAttributes .....	189
Contents .....	189

---

See Also .....	190
ExportTaskDetails .....	191
Contents .....	191
See Also .....	192
ExportTaskSummary .....	193
Contents .....	193
See Also .....	195
GraphDataSummary .....	196
Contents .....	196
See Also .....	198
GraphSnapshotSummary .....	199
Contents .....	199
See Also .....	200
GraphSummary .....	202
Contents .....	202
See Also .....	204
ImportOptions .....	205
Contents .....	205
See Also .....	205
ImportTaskDetails .....	206
Contents .....	206
See Also .....	207
ImportTaskSummary .....	208
Contents .....	208
See Also .....	209
NeptuneImportOptions .....	210
Contents .....	210
See Also .....	211
NodeStructure .....	212
Contents .....	212
See Also .....	212
PrivateGraphEndpointSummary .....	213
Contents .....	213
See Also .....	214
QuerySummary .....	215
Contents .....	215

---

See Also .....	216
VectorSearchConfiguration .....	217
Contents .....	217
See Also .....	217
<b>Common Parameters .....</b>	<b>218</b>
<b>Common Error Types .....</b>	<b>221</b>

# Welcome

Neptune Analytics is a new analytics database engine for Amazon Neptune that helps customers get to insights faster by quickly processing large amounts of graph data, invoking popular graph analytic algorithms in low-latency queries, and getting analytics results in seconds.

This document was last published on April 18, 2026.

# Actions

The following actions are supported:

- [CancelExportTask](#)
- [CancelImportTask](#)
- [CancelQuery](#)
- [CreateGraph](#)
- [CreateGraphSnapshot](#)
- [CreateGraphUsingImportTask](#)
- [CreatePrivateGraphEndpoint](#)
- [DeleteGraph](#)
- [DeleteGraphSnapshot](#)
- [DeletePrivateGraphEndpoint](#)
- [ExecuteQuery](#)
- [GetExportTask](#)
- [GetGraph](#)
- [GetGraphSnapshot](#)
- [GetGraphSummary](#)
- [GetImportTask](#)
- [GetPrivateGraphEndpoint](#)
- [GetQuery](#)
- [ListExportTasks](#)
- [ListGraphs](#)
- [ListGraphSnapshots](#)
- [ListImportTasks](#)
- [ListPrivateGraphEndpoints](#)
- [ListQueries](#)
- [ListTagsForResource](#)
- [ResetGraph](#)
- [RestoreGraphFromSnapshot](#)

- [StartExportTask](#)
- [StartGraph](#)
- [StartImportTask](#)
- [StopGraph](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateGraph](#)

# CancelExportTask

Cancel the specified export task.

## Request Syntax

```
DELETE /exporttasks/taskIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### taskIdentifier

The unique identifier of the export task.

Pattern: t-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "destination": "string",
  "format": "string",
  "graphId": "string",
  "kmsKeyIdentifier": "string",
  "parquetType": "string",
  "roleArn": "string",
  "status": "string",
  "statusReason": "string",
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### destination

The Amazon S3 URI of the cancelled export task where data will be exported to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

### format

The format of the cancelled export task.

Type: String

Valid Values: PARQUET | CSV

### graphId

The source graph identifier of the cancelled export task.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdentifier

The KMS key identifier of the cancelled export task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### parquetType

The parquet type of the cancelled export task.

Type: String

Valid Values: COLUMNAR

### roleArn

The ARN of the IAM role that will allow the exporting of data to the destination.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

### status

The current status of the export task. The status is CANCELLING when the export task is cancelled.

Type: String

Valid Values: INITIALIZING | EXPORTING | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

### statusReason

The reason that the export task has this status value.

Type: String

### taskId

The unique identifier of the export task.

Type: String

Pattern: `t-[a-z0-9]{10}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

**reason**

The reason for the conflict exception.

HTTP Status Code: 409

**InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelImportTask

Deletes the specified import task.

## Request Syntax

```
DELETE /importtasks/taskIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### taskIdentifier

The unique identifier of the import task.

Pattern: t-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "format": "string",
  "graphId": "string",
  "parquetType": "string",
  "roleArn": "string",
  "source": "string",
  "status": "string",
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### format

Specifies the format of S3 data to be imported. Valid values are CSV, which identifies the [Gremlin CSV format](#) or OPENCYPHER, which identifies the [openCypher load format](#).

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

### graphId

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

### parquetType

The parquet type of the cancelled import task.

Type: String

Valid Values: COLUMNAR

### roleArn

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: arn:aws[^:]\*:iam::\d{12}:(role|role/service-role)(/[\w+=, .@-]+)+

### source

A URL identifying to the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot.

Type: String

## status

Current status of the task. Status is CANCELLING when the import task is cancelled.

Type: String

Valid Values: INITIALIZING | EXPORTING | ANALYZING\_DATA | IMPORTING | REPROVISIONING | ROLLING\_BACK | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

## taskId

The unique identifier of the import task.

Type: String

Pattern: t-[a-z0-9]{10}

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelQuery

Cancels a specified query.

## Request Syntax

```
DELETE /queries/queryId HTTP/1.1  
graphIdentifier: graphIdentifier
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### queryId

The unique identifier of the query to cancel.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

Raised in case of an authentication or authorization failure.

#### message

A message describing the problem.

HTTP Status Code: 403

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

### ValidationException

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateGraph

Creates a new Neptune Analytics graph.

## Request Syntax

```
POST /graphs HTTP/1.1
Content-type: application/json

{
  "deletionProtection": boolean,
  "graphName": "string",
  "kmsKeyIdentifier": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
  "tags": {
    "string" : "string"
  },
  "vectorSearchConfiguration": {
    "dimension": number
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### deletionProtection

Indicates whether or not to enable deletion protection on the graph. The graph can't be deleted when deletion protection is enabled. (true or false).

Type: Boolean

Required: No

## graphName

A name for the new Neptune Analytics graph to be created.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

Required: Yes

## kmsKeyIdIdentifier

Specifies a KMS key to use to encrypt data in the new graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

Required: No

## provisionedMemory

The provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph. Min = 16

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: Yes

## publicConnectivity

Specifies whether or not the graph can be reachable over the internet. All access to graphs is IAM authenticated. (`true` to enable, or `false` to disable).

Type: Boolean

Required: No

### replicaCount

The number of replicas in other AZs. Min =0, Max = 2, Default = 1.

#### **Important**

Additional charges equivalent to the m-NCUs selected for the graph apply for each replica.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

Required: No

### tags

Adds metadata tags to the new graph. These tags can also be used with cost allocation reporting, or used in a Condition statement in an IAM policy.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-. \_:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings that will be loaded into the graph. The value is specified as `dimension=value`. Max = 65,535

Type: [VectorSearchConfiguration](#) object

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
  "sourceSnapshotId": "string",
  "status": "string",
  "statusReason": "string",
  "vectorSearchConfiguration": {
    "dimension": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### [arn](#)

The ARN of the graph.

Type: String

### [buildNumber](#)

The build number of the graph software.

Type: String

### createTime

The time when the graph was created.

Type: Timestamp

### deletionProtection

A value that indicates whether the graph has deletion protection enabled. The graph can't be deleted when deletion protection is enabled.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The ID of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdentifier

Specifies the KMS key used to encrypt data in the new graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The graph name. For example: my-graph-1.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### provisionedMemory

The provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph.

Min = 16

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

Specifies whether or not the graph can be reachable over the internet. All access to graphs is IAM authenticated.

#### Note

If enabling public connectivity for the first time, there will be a delay while it is enabled.

Type: Boolean

### replicaCount

The number of replicas in other AZs.

Default: If not specified, the default value is 1.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

### sourceSnapshotId

The ID of the source graph.

Type: String

Pattern: gs-[a-z0-9]{10}

### status

The current status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

### statusReason

The reason the status was given.

Type: String

### vectorSearchConfiguration

The vector-search configuration for the graph, which specifies the vector dimension to use in the vector index, if any.

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ConflictException**

Raised when a conflict is encountered.

#### **message**

A message describing the problem.

#### **reason**

The reason for the conflict exception.

HTTP Status Code: 409

### **InternalServerErrorException**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ServiceQuotaExceededException**

A service quota was exceeded.

**quotaCode**

Service quota code of the resource for which quota was exceeded.

**resourceId**

The identifier of the resource that exceeded quota.

**resourceType**

The type of the resource that exceeded quota. Ex: Graph, Snapshot

**serviceCode**

The service code that exceeded quota.

HTTP Status Code: 402

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateGraphSnapshot

Creates a snapshot of the specific graph.

## Request Syntax

```
POST /snapshots HTTP/1.1
Content-type: application/json

{
  "graphIdentifier": "string",
  "snapshotName": "string",
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

Required: Yes

### snapshotName

The snapshot name. For example: my-snapshot-1.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!gs-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

Required: Yes

## tags

Adds metadata tags to the new graph. These tags can also be used with cost allocation reporting, or used in a Condition statement in an IAM policy.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-.\_:/+]

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "snapshotCreateTime": number,
  "sourceGraphId": "string",
  "status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### arn

The ARN of the snapshot created.

Type: String

### id

The ID of the snapshot created.

Type: String

Pattern: gs-[a-z0-9]{10}

### kmsKeyIdentifier

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The name of the snapshot created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!gs-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### snapshotCreateTime

The snapshot creation time

Type: Timestamp

### sourceGraphId

The Id of the Neptune Analytics graph from which the snapshot is created.

Type: String

Pattern: g-[a-z0-9]{10}

### status

The current state of the snapshot.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### **ServiceQuotaExceededException**

A service quota was exceeded.

#### **quotaCode**

Service quota code of the resource for which quota was exceeded.

#### **resourceId**

The identifier of the resource that exceeded quota.

#### **resourceType**

The type of the resource that exceeded quota. Ex: Graph, Snapshot

#### **serviceCode**

The service code that exceeded quota.

HTTP Status Code: 402

### **ThrottlingException**

The exception was interrupted by throttling.

#### **message**

A message describing the problem.

HTTP Status Code: 429

### **ValidationException**

A resource could not be validated.

#### **message**

A message describing the problem.

#### **reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateGraphUsingImportTask

Creates a new Neptune Analytics graph and imports data into it, either from Amazon Simple Storage Service (S3) or from a Neptune database or a Neptune database snapshot.

The data can be loaded from files in S3 that in either the [Gremlin CSV format](#) or the [openCypher load format](#).

## Request Syntax

```
POST /importtasks HTTP/1.1
Content-type: application/json

{
  "blankNodeHandling": "string",
  "deletionProtection": boolean,
  "failOnError": boolean,
  "format": "string",
  "graphName": "string",
  "importOptions": { ... },
  "kmsKeyIdentifier": "string",
  "maxProvisionedMemory": number,
  "minProvisionedMemory": number,
  "parquetType": "string",
  "publicConnectivity": boolean,
  "replicaCount": number,
  "roleArn": "string",
  "source": "string",
  "tags": {
    "string" : "string"
  },
  "vectorSearchConfiguration": {
    "dimension": number
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### blankNodeHandling

The method to handle blank nodes in the dataset. Currently, only `convertToIri` is supported, meaning blank nodes are converted to unique IRIs at load time. Must be provided when format is `ntriples`. For more information, see [Handling RDF values](#).

Type: String

Valid Values: `convertToIri`

Required: No

### deletionProtection

Indicates whether or not to enable deletion protection on the graph. The graph can't be deleted when deletion protection is enabled. (`true` or `false`).

Type: Boolean

Required: No

### failOnError

If set to `true`, the task halts when an import error is encountered. If set to `false`, the task skips the data that caused the error and continues if possible.

Type: Boolean

Required: No

### format

Specifies the format of S3 data to be imported. Valid values are `CSV`, which identifies the [Gremlin CSV format](#), `OPEN_CYPHER`, which identifies the [openCypher load format](#), or `ntriples`, which identifies the [RDF n-triples](#) format.

Type: String

Valid Values: `CSV` | `OPEN_CYPHER` | `PARQUET` | `NTRIPLES`

Required: No

## graphName

A name for the new Neptune Analytics graph to be created.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `(?!g-)[a-z][a-z0-9]*(-[a-z0-9]+)*`

Required: Yes

## importOptions

Contains options for controlling the import process. For example, if the `failOnError` key is set to `false`, the import skips problem data and attempts to continue (whereas if set to `true`, the default, or if omitted, the import operation halts immediately when an error is encountered).

Type: [ImportOptions](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## kmsKeyIdentifier

Specifies a KMS key to use to encrypt data imported into the new graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

Required: No

## maxProvisionedMemory

The maximum provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph. Default: 1024, or the approved upper limit for your account.

If both the minimum and maximum values are specified, the final provisioned-memory will be chosen per the actual size of your imported data. If neither value is specified, 128 m-NCUs are used.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: No

### minProvisionedMemory

The minimum provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph. Default: 16

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: No

### parquetType

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

Required: No

### publicConnectivity

Specifies whether or not the graph can be reachable over the internet. All access to graphs is IAM authenticated. (`true` to enable, or `false` to disable).

Type: Boolean

Required: No

### replicaCount

The number of replicas in other AZs to provision on the new graph after import. Default = 0, Min = 0, Max = 2.

**⚠ Important**

Additional charges equivalent to the m-NCUs selected for the graph apply for each replica.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

Required: No

**roleArn**

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

Required: Yes

**source**

A URL identifying to the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot.

Type: String

Required: Yes

**tags**

Adds metadata tags to the new graph. These tags can also be used with cost allocation reporting, or used in a Condition statement in an IAM policy.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `(?!aws:)[a-zA-Z+-._:/+]`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings that will be loaded into the graph. The value is specified as `dimension=value`. Max = 65,535

Type: [VectorSearchConfiguration](#) object

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "format": "string",
  "graphId": "string",
  "importOptions": { ... },
  "parquetType": "string",
  "roleArn": "string",
  "source": "string",
  "status": "string",
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### format

Specifies the format of S3 data to be imported. Valid values are CSV, which identifies the [Gremlin CSV format](#), OPENCYPHER, which identifies the [openCypher load format](#), or ntriples, which identifies the [RDF n-triples](#) format.

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

## graphId

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

## importOptions

Contains options for controlling the import process. For example, if the `failOnError` key is set to `false`, the import skips problem data and attempts to continue (whereas if set to `true`, the default, or if omitted, the import operation halts immediately when an error is encountered).

Type: [ImportOptions](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

## parquetType

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

## roleArn

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: arn:aws[^:]\*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+

## source

A URL identifying to the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot.

Type: String

## status

The status of the import task.

Type: String

Valid Values: INITIALIZING | EXPORTING | ANALYZING\_DATA | IMPORTING | REPROVISIONING | ROLLING\_BACK | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

### taskId

The unique identifier of the import task.

Type: String

Pattern: t-[a-z0-9]{10}

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ServiceQuotaExceededException

A service quota was exceeded.

#### quotaCode

Service quota code of the resource for which quota was exceeded.

**resourceId**

The identifier of the resource that exceeded quota.

**resourceType**

The type of the resource that exceeded quota. Ex: Graph, Snapshot

**serviceCode**

The service code that exceeded quota.

HTTP Status Code: 402

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreatePrivateGraphEndpoint

Create a private graph endpoint to allow private access from to the graph from within a VPC. You can attach security groups to the private graph endpoint.

## Note

VPC endpoint charges apply.

## Request Syntax

```
POST /graphs/graphIdentifier/endpoints/ HTTP/1.1
Content-type: application/json
```

```
{
  "subnetIds": [ "string" ],
  "vpcId": "string",
  "vpcSecurityGroupIds": [ "string" ]
}
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### subnetIds

Subnets in which private graph endpoint ENIs are created.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Pattern: subnet-[a-z0-9]+

Required: No

### vpclId

The VPC in which the private graph endpoint needs to be created.

Type: String

Pattern: vpc-[a-z0-9]+

Required: No

### vpcSecurityGroupIds

Security groups to be attached to the private graph endpoint..

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: sg-[a-z0-9]+

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "status": "string",
  "subnetIds": [ "string" ],
  "vpcEndpointId": "string",
  "vpcId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### status

Status of the private graph endpoint.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

### subnetIds

Subnets in which the private graph endpoint ENIs are created.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Pattern: subnet-[a-z0-9]+

### vpcEndpointId

Endpoint ID of the private graph endpoint.

Type: String

Pattern: vpce-[0-9a-f]{17}

### vpcId

VPC in which the private graph endpoint is created.

Type: String

Pattern: vpc-[a-z0-9]+

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ConflictException**

Raised when a conflict is encountered.

**message**

A message describing the problem.

**reason**

The reason for the conflict exception.

HTTP Status Code: 409

**InternalServerErrorException**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ServiceQuotaExceededException**

A service quota was exceeded.

**quotaCode**

Service quota code of the resource for which quota was exceeded.

**resourceId**

The identifier of the resource that exceeded quota.

**resourceType**

The type of the resource that exceeded quota. Ex: Graph, Snapshot

**serviceCode**

The service code that exceeded quota.

HTTP Status Code: 402

### **ThrottlingException**

The exception was interrupted by throttling.

#### **message**

A message describing the problem.

HTTP Status Code: 429

### **ValidationException**

A resource could not be validated.

#### **message**

A message describing the problem.

#### **reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteGraph

Deletes the specified graph. Graphs cannot be deleted if delete-protection is enabled.

## Request Syntax

```
DELETE /graphs/graphIdentifier?skipSnapshot=skipSnapshot HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [graphIdentifier](#)

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### [skipSnapshot](#)

Determines whether a final graph snapshot is created before the graph is deleted. If `true` is specified, no graph snapshot is created. If `false` is specified, a graph snapshot is created before the graph is deleted.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
```

```
"deletionProtection": boolean,
"endpoint": "string",
"id": "string",
"kmsKeyIdentifier": "string",
"name": "string",
"provisionedMemory": number,
"publicConnectivity": boolean,
"replicaCount": number,
"sourceSnapshotId": "string",
"status": "string",
"statusReason": "string",
"vectorSearchConfiguration": {
  "dimension": number
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number associated with the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection was enabled for the graph.

Type: Boolean

## endpoint

The graph endpoint.

Type: String

## id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

## kmsKeyId

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

## name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

## provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

## publicConnectivity

If true, the graph has a public endpoint, otherwise not.

Type: Boolean

## replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

## sourceSnapshotId

The ID of the snapshot from which the graph was created, if the graph was recovered from a snapshot.

Type: String

Pattern: gs-[a-z0-9]{10}

## status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING | SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

## statusReason

The reason for the status of the graph.

Type: String

## vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

**message**

A message describing the problem.

**reason**

The reason for the conflict exception.

HTTP Status Code: 409

**InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteGraphSnapshot

Deletes the specified graph snapshot.

## Request Syntax

```
DELETE /snapshots/snapshotIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### snapshotIdentifier

ID of the graph snapshot to be deleted.

Pattern: gs-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "snapshotCreateTime": number,
  "sourceGraphId": "string",
  "status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN of the graph snapshot.

Type: String

### id

The unique identifier of the graph snapshot.

Type: String

Pattern: `gs-[a-z0-9]{10}`

### kmsKeyId

The ID of the KMS key used to encrypt and decrypt the snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

### name

The snapshot name. For example: `my-snapshot-1`.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `(?!gs-)[a-z][a-z0-9]*(-[a-z0-9]+)*`

## snapshotCreateTime

The time when the snapshot was created.

Type: Timestamp

## sourceGraphId

The graph identifier for the graph from which the snapshot was created.

Type: String

Pattern: g-[a-z0-9]{10}

## status

The status of the graph snapshot.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### **message**

A message describing the problem.

#### **reason**

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### **message**

A message describing the problem.

HTTP Status Code: 500

### **ResourceNotFoundException**

A specified resource could not be located.

#### **message**

A message describing the problem.

HTTP Status Code: 404

### **ThrottlingException**

The exception was interrupted by throttling.

#### **message**

A message describing the problem.

HTTP Status Code: 429

### **ValidationException**

A resource could not be validated.

#### **message**

A message describing the problem.

#### **reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeletePrivateGraphEndpoint

Deletes a private graph endpoint.

## Request Syntax

```
DELETE /graphs/graphIdentifier/endpoints/vpcId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### vpcId

The ID of the VPC where the private endpoint is located.

Pattern: vpc-[a-z0-9]+

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string",
  "subnetIds": [ "string" ],
  "vpcEndpointId": "string",
  "vpcId": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### status

The status of the delete operation.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

### subnetIds

The subnet IDs involved.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Pattern: subnet-[a-z0-9]+

### vpcEndpointId

The ID of the VPC endpoint that was deleted.

Type: String

Pattern: vpce-[0-9a-f]{17}

### vpcId

The ID of the VPC where the private endpoint was deleted.

Type: String

Pattern: vpc-[a-z0-9]+

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## **ConflictException**

Raised when a conflict is encountered.

### **message**

A message describing the problem.

### **reason**

The reason for the conflict exception.

HTTP Status Code: 409

## **InternalServerErrorException**

A failure occurred on the server.

### **message**

A message describing the problem.

HTTP Status Code: 500

## **ResourceNotFoundException**

A specified resource could not be located.

### **message**

A message describing the problem.

HTTP Status Code: 404

## **ThrottlingException**

The exception was interrupted by throttling.

### **message**

A message describing the problem.

HTTP Status Code: 429

## **ValidationException**

A resource could not be validated.

### **message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ExecuteQuery

Execute an openCypher query.

When invoking this operation in a Neptune Analytics cluster, the IAM user or role making the request must have a policy attached that allows one of the following IAM actions in that cluster, depending on the query:

- `neptune-graph:ReadDataViaQuery`
- `neptune-graph:WriteDataViaQuery`
- `neptune-graph>DeleteDataViaQuery`

## Request Syntax

```
POST /queries HTTP/1.1
graphIdentifier: graphIdentifier
Content-type: application/json

{
  "explain": "string",
  "language": "string",
  "parameters": {
    "string" : JSON value
  },
  "planCache": "string",
  "query": "string",
  "queryTimeoutMilliseconds": number
}
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: `g-[a-z0-9]{10}`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### explain

The explain mode parameter returns a query explain instead of the actual query results. A query explain can be used to gather insights about the query execution such as planning decisions, time spent on each operator, solutions flowing etc.

Type: String

Valid Values: STATIC | DETAILS

Required: No

### language

The query language the query is written in. Currently only openCypher is supported.

Type: String

Valid Values: OPEN\_CYPHER

Required: Yes

### parameters

The data parameters the query can use in JSON format. For example: {"name": "john", "age": 20}. (optional)

Type: String to JSON value map

Required: No

### planCache

Query plan cache is a feature that saves the query plan and reuses it on successive executions of the same query. This reduces query latency, and works for both READ and UPDATE queries. The plan cache is an LRU cache with a 5 minute TTL and a capacity of 1000.

Type: String

Valid Values: ENABLED | DISABLED | AUTO

Required: No

### query

The query string to be executed.

Type: String

Required: Yes

### queryTimeoutMilliseconds

Specifies the query timeout duration, in milliseconds. (optional)

Type: Integer

Required: No

## Response Syntax

```
HTTP/1.1 200
```

```
payload
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following as the HTTP body.

### payload

The query results.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

Raised in case of an authentication or authorization failure.

**message**

A message describing the problem.

HTTP Status Code: 403

**ConflictException**

Raised when a conflict is encountered.

**message**

A message describing the problem.

**reason**

The reason for the conflict exception.

HTTP Status Code: 409

**InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**UnprocessableException**

Request cannot be processed due to known reasons. Eg. partition full.

**reason**

The reason for the unprocessable exception.

HTTP Status Code: 422

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetExportTask

Retrieves a specified export task.

## Request Syntax

```
GET /exporttasks/taskIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### taskIdentifier

The unique identifier of the export task.

Pattern: t-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "destination": "string",
  "exportFilter": {
    "edgeFilter": {
      "string": {
        "properties": {
          "string": {
            "multiValueHandling": "string",
            "outputType": "string",
            "sourcePropertyName": "string"
          }
        }
      }
    }
  }
}
```

```

    }
  }
},
  "vertexFilter": {
    "string": {
      "properties": {
        "string": {
          "multiValueHandling": "string",
          "outputType": "string",
          "sourcePropertyName": "string"
        }
      }
    }
  }
},
  "exportTaskDetails": {
    "numEdgesWritten": number,
    "numVerticesWritten": number,
    "progressPercentage": number,
    "startTime": number,
    "timeElapsedSeconds": number
  },
  "format": "string",
  "graphId": "string",
  "kmsKeyIdentifier": "string",
  "parquetType": "string",
  "roleArn": "string",
  "status": "string",
  "statusReason": "string",
  "taskId": "string"
}

```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### destination

The Amazon S3 URI of the export task where data will be exported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

### exportFilter

The export filter of the export task.

Type: [ExportFilter](#) object

### exportTaskDetails

The details of the export task.

Type: [ExportTaskDetails](#) object

### format

The format of the export task.

Type: String

Valid Values: PARQUET | CSV

### graphId

The source graph identifier of the export task.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdIdentifier

The KMS key identifier of the export task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### parquetType

The parquet type of the export task.

Type: String

Valid Values: COLUMNAR

## roleArn

The ARN of the IAM role that will allow data to be exported to the destination.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

## status

The current status of the export task.

Type: String

Valid Values: INITIALIZING | EXPORTING | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

## statusReason

The reason that the export task has this status value.

Type: String

## taskId

The unique identifier of the export task.

Type: String

Pattern: `t-[a-z0-9]{10}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### **message**

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGraph

Gets information about a specified graph.

## Request Syntax

```
GET /graphs/graphIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
```

```
"sourceSnapshotId": "string",
"status": "string",
"statusReason": "string",
"vectorSearchConfiguration": {
  "dimension": number
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyId

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If `true`, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

## sourceSnapshotId

The ID of the snapshot from which the graph was created, if it was created from a snapshot.

Type: String

Pattern: gs-[a-z0-9]{10}

## status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

## statusReason

The reason that the graph has this status.

Type: String

## vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGraphSnapshot

Retrieves a specified graph snapshot.

## Request Syntax

```
GET /snapshots/snapshotIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### snapshotIdentifier

The ID of the snapshot to retrieve.

Pattern: `gs-[a-z0-9]{10}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "snapshotCreateTime": number,
  "sourceGraphId": "string",
  "status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN of the graph snapshot.

Type: String

### id

The unique identifier of the graph snapshot.

Type: String

Pattern: `gs-[a-z0-9]{10}`

### kmsKeyId

The ID of the KMS key used to encrypt and decrypt the snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

### name

The snapshot name. For example: `my-snapshot-1`.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `(?!gs-)[a-z][a-z0-9]*(-[a-z0-9]+)*`

## snapshotCreateTime

The time when the snapshot was created.

Type: Timestamp

## sourceGraphId

The graph identifier for the graph for which a snapshot is to be created.

Type: String

Pattern: g-[a-z0-9]{10}

## status

The status of the graph snapshot.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGraphSummary

Gets a graph summary for a property graph.

## Request Syntax

```
GET /summary?mode=mode HTTP/1.1
graphIdentifier: graphIdentifier
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### mode

The summary mode can take one of two values: `basic` (the default), and `detailed`.

Valid Values: BASIC | DETAILED

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "graphSummary": {
    "edgeLabels": [ "string" ],
    "edgeProperties": [
      {
        "string" : number
      }
    ]
  }
}
```

```
    }
  ],
  "edgeStructures": [
    {
      "count": number,
      "edgeProperties": [ "string" ]
    }
  ],
  "nodeLabels": [ "string" ],
  "nodeProperties": [
    {
      "string" : number
    }
  ],
  "nodeStructures": [
    {
      "count": number,
      "distinctOutgoingEdgeLabels": [ "string" ],
      "nodeProperties": [ "string" ]
    }
  ],
  "numEdgeLabels": number,
  "numEdgeProperties": number,
  "numEdges": number,
  "numNodeLabels": number,
  "numNodeProperties": number,
  "numNodes": number,
  "totalEdgePropertyValues": number,
  "totalNodePropertyValues": number
},
"lastStatisticsComputationTime": "string",
"version": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### graphSummary

The graph summary.

Type: [GraphDataSummary](#) object

### lastStatisticsComputationTime

The timestamp, in ISO 8601 format, of the time at which Neptune Analytics last computed statistics.

Type: Timestamp

### version

Display the version of this tool.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

Raised in case of an authentication or authorization failure.

#### **message**

A message describing the problem.

HTTP Status Code: 403

### **InternalServerError**

A failure occurred on the server.

#### **message**

A message describing the problem.

HTTP Status Code: 500

### **ResourceNotFoundException**

A specified resource could not be located.

#### **message**

A message describing the problem.

HTTP Status Code: 404

### **ThrottlingException**

The exception was interrupted by throttling.

#### **message**

A message describing the problem.

HTTP Status Code: 429

### **ValidationException**

A resource could not be validated.

#### **message**

A message describing the problem.

#### **reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# GetImportTask

Retrieves a specified import task.

## Request Syntax

```
GET /importtasks/taskIdentifier HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### taskIdentifier

The unique identifier of the import task.

Pattern: t-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "attemptNumber": number,
  "format": "string",
  "graphId": "string",
  "importOptions": { ... },
  "importTaskDetails": {
    "dictionaryEntryCount": number,
    "errorCount": number,
    "errorDetails": "string",
    "progressPercentage": number,
    "startTime": number,
    "statementCount": number,
  }
}
```

```
    "status": "string",
    "timeElapsedSeconds": number
  },
  "parquetType": "string",
  "roleArn": "string",
  "source": "string",
  "status": "string",
  "statusReason": "string",
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### attemptNumber

The number of the current attempts to execute the import task.

Type: Integer

### format

Specifies the format of S3 data to be imported. Valid values are CSV, which identifies the [Gremlin CSV format](#) or OPENCYPHER, which identifies the [openCypher load format](#).

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

### graphId

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

### importOptions

Contains options for controlling the import process. For example, if the `failOnError` key is set to `false`, the import skips problem data and attempts to continue (whereas if set to `true`, the default, or if omitted, the import operation halts immediately when an error is encountered).

Type: [ImportOptions](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### [importTaskDetails](#)

Contains details about the specified import task.

Type: [ImportTaskDetails](#) object

### [parquetType](#)

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

### [roleArn](#)

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

### [source](#)

A URL identifying to the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot

Type: String

### [status](#)

The status of the import task:

- **INITIALIZING** – The necessary resources needed to create the graph are being prepared.
- **ANALYZING\_DATA** – The data is being analyzed to determine the optimal infrastructure configuration for the new graph.
- **RE\_PROVISIONING** – The data did not fit into the provisioned graph, so it is being re-provisioned with more capacity.
- **IMPORTING** – The data is being loaded.
- **ERROR\_ENCOUNTERED** – An error has been encountered while trying to create the graph and import the data.

- **ERROR\_ENCOUNTERED\_ROLLING\_BACK** – Because of the error that was encountered, the graph is being rolled back and all its resources released.
- **SUCCEEDED** – Graph creation and data loading succeeded.
- **FAILED** – Graph creation or data loading failed. When the status is FAILED, you can use `get-graphs` to get more information about the state of the graph.
- **CANCELLING** – Because you cancelled the import task, cancellation is in progress.
- **CANCELLED** – You have successfully cancelled the import task.

Type: String

Valid Values: INITIALIZING | EXPORTING | ANALYZING\_DATA | IMPORTING | REPROVISIONING | ROLLING\_BACK | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

### statusReason

The reason that the import task has this status value.

Type: String

### taskId

The unique identifier of the import task.

Type: String

Pattern: `t-[a-z0-9]{10}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetPrivateGraphEndpoint

Retrieves information about a specified private endpoint.

## Request Syntax

```
GET /graphs/graphIdentifier/endpoints/vpcId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### vpcId

The ID of the VPC where the private endpoint is located.

Pattern: vpc-[a-z0-9]+

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string",
  "subnetIds": [ "string" ],
  "vpcEndpointId": "string",
  "vpcId": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### status

The current status of the private endpoint.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

### subnetIds

The subnet IDs involved.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Pattern: subnet-[a-z0-9]+

### vpcEndpointId

The ID of the private endpoint.

Type: String

Pattern: vpce-[0-9a-f]{17}

### vpcId

The ID of the VPC where the private endpoint is located.

Type: String

Pattern: vpc-[a-z0-9]+

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## InternalServerErrorException

A failure occurred on the server.

### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetQuery

Retrieves the status of a specified query.

## Note

When invoking this operation in a Neptune Analytics cluster, the IAM user or role making the request must have the `neptune-graph:GetQueryStatus` IAM action attached.

## Request Syntax

```
GET /queries/queryId HTTP/1.1  
graphIdentifier: graphIdentifier
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: `g-[a-z0-9]{10}`

Required: Yes

### queryId

The ID of the query in question.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "elapsed": number,
  "id": "string",
  "queryString": "string",
  "state": "string",
  "waited": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### elapsed

The number of milliseconds the query has been running.

Type: Integer

### id

The ID of the query in question.

Type: String

### queryString

The query in question.

Type: String

### state

State of the query.

Type: String

Valid Values: RUNNING | WAITING | CANCELLING

### waited

Indicates how long the query waited, in milliseconds.

Type: Integer

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

Raised in case of an authentication or authorization failure.

#### message

A message describing the problem.

HTTP Status Code: 403

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListExportTasks

Retrieves a list of export tasks.

## Request Syntax

```
GET /exporttasks?  
graphIdentifier=graphIdentifier&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

### maxResults

The maximum number of export tasks to return.

Valid Range: Minimum value of 1. Maximum value of 100.

### nextToken

Pagination token used to paginate input.

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{
```

```
"nextToken": "string",
"tasks": [
  {
    "destination": "string",
    "format": "string",
    "graphId": "string",
    "kmsKeyIdentifier": "string",
    "parquetType": "string",
    "roleArn": "string",
    "status": "string",
    "statusReason": "string",
    "taskId": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

Pagination token used to paginate output.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

### tasks

The requested list of export tasks.

Type: Array of [ExportTaskSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGraphs

Lists available Neptune Analytics graphs.

## Request Syntax

```
GET /graphs?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### maxResults

The total number of records to return in the command's output.

If the total number of records available is more than the value specified, `nextToken` is provided in the command's output. To resume pagination, provide the `nextToken` output value in the `nextToken` argument of a subsequent command. Do not use the `nextToken` response element directly outside of the Amazon CLI.

Valid Range: Minimum value of 1. Maximum value of 100.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "graphs": [
    {
      "arn": "string",
      "deletionProtection": boolean,
      "endpoint": "string",
      "id": "string",
      "kmsKeyIdentifier": "string",
      "name": "string",
      "provisionedMemory": number,
      "publicConnectivity": boolean,
      "replicaCount": number,
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### graphs

A list of the graphs.

Type: Array of [GraphSummary](#) objects

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGraphSnapshots

Lists available snapshots of a specified Neptune Analytics graph.

## Request Syntax

```
GET /snapshots?  
graphIdentifier=graphIdentifier&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

### maxResults

The total number of records to return in the command's output.

If the total number of records available is more than the value specified, `nextToken` is provided in the command's output. To resume pagination, provide the `nextToken` output value in the `nextToken` argument of a subsequent command. Do not use the `nextToken` response element directly outside of the Amazon CLI.

Valid Range: Minimum value of 1. Maximum value of 100.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "graphSnapshots": [
    {
      "arn": "string",
      "id": "string",
      "kmsKeyIdentifier": "string",
      "name": "string",
      "snapshotCreateTime": number,
      "sourceGraphId": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### graphSnapshots

The requested list of snapshots.

Type: Array of [GraphSnapshotSummary](#) objects

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

### ValidationException

A resource could not be validated.

#### message

A message describing the problem.

#### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListImportTasks

Lists import tasks.

## Request Syntax

```
GET /importtasks?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### maxResults

The total number of records to return in the command's output.

If the total number of records available is more than the value specified, `nextToken` is provided in the command's output. To resume pagination, provide the `nextToken` output value in the `nextToken` argument of a subsequent command. Do not use the `nextToken` response element directly outside of the Amazon CLI.

Valid Range: Minimum value of 1. Maximum value of 100.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "nextToken": "string",
  "tasks": [
    {
      "format": "string",
      "graphId": "string",
      "parquetType": "string",
      "roleArn": "string",
      "source": "string",
      "status": "string",
      "taskId": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

### tasks

The requested list of import tasks.

Type: Array of [ImportTaskSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## InternalServerErrorException

A failure occurred on the server.

### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListPrivateGraphEndpoints

Lists private endpoints for a specified Neptune Analytics graph.

## Request Syntax

```
GET /graphs/graphIdentifier/endpoints/?maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### maxResults

The total number of records to return in the command's output.

If the total number of records available is more than the value specified, `nextToken` is provided in the command's output. To resume pagination, provide the `nextToken` output value in the `nextToken` argument of a subsequent command. Do not use the `nextToken` response element directly outside of the Amazon CLI.

Valid Range: Minimum value of 1. Maximum value of 100.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 8192.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "privateGraphEndpoints": [
    {
      "status": "string",
      "subnetIds": [ "string" ],
      "vpcEndpointId": "string",
      "vpcId": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

Pagination token used to paginate output.

When this value is provided as input, the service returns results from where the previous response left off. When this value is present in output, it indicates that there are more results to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

### privateGraphEndpoints

A list of private endpoints for the specified Neptune Analytics graph.

Type: Array of [PrivateGraphEndpointSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

### ValidationException

A resource could not be validated.

#### message

A message describing the problem.

#### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListQueries

Lists active openCypher queries.

## Request Syntax

```
GET /queries?maxResults=maxResults&state=state HTTP/1.1  
graphIdentifier: graphIdentifier
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

### maxResults

The maximum number of results to be fetched by the API.

Required: Yes

### state

Filtered list of queries based on state.

Valid Values: ALL | RUNNING | WAITING | CANCELLING

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "queries": [
    {
      "elapsed": number,
      "id": "string",
      "queryString": "string",
      "state": "string",
      "waited": number
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### queries

A list of current openCypher queries.

Type: Array of [QuerySummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

Raised in case of an authentication or authorization failure.

#### **message**

A message describing the problem.

HTTP Status Code: 403

### **InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Lists tags associated with a specified resource.

## Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn: .+

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## tags

The list of metadata tags associated with the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+ -= . \_ : / ]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ResetGraph

Empties the data from a specified Neptune Analytics graph.

## Request Syntax

```
PUT /graphs/graphIdentifier HTTP/1.1
Content-type: application/json

{
  "skipSnapshot": boolean
}
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

ID of the graph to reset.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### skipSnapshot

Determines whether a final graph snapshot is created before the graph data is deleted. If set to `true`, no graph snapshot is created. If set to `false`, a graph snapshot is created before the data is deleted.

Type: Boolean

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
  "sourceSnapshotId": "string",
  "status": "string",
  "statusReason": "string",
  "vectorSearchConfiguration": {
    "dimension": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: `g-[a-z0-9]{10}`

### kmsKeyIdentifier

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `(?!g-)[a-z][a-z0-9]*(-[a-z0-9]+)*`

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If `true`, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

### sourceSnapshotId

The ID of the snapshot from which the graph was created, if any.

Type: String

Pattern: `gs-[a-z0-9]{10}`

### status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING | SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

### statusReason

The reason that the graph has this status.

Type: String

### vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RestoreGraphFromSnapshot

Restores a graph from a snapshot.

## Request Syntax

```
POST /snapshots/snapshotIdentifier/restore HTTP/1.1
Content-type: application/json
```

```
{
  "deletionProtection": boolean,
  "graphName": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### snapshotIdentifier

The ID of the snapshot in question.

Pattern: gs-[a-z0-9]{10}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### deletionProtection

A value that indicates whether the graph has deletion protection enabled. The graph can't be deleted when deletion protection is enabled.

Type: Boolean

Required: No

### graphName

A name for the new Neptune Analytics graph to be created from the snapshot.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

Required: Yes

### provisionedMemory

The provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph.

Min = 16

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: No

### publicConnectivity

Specifies whether or not the graph can be reachable over the internet. All access to graphs is IAM authenticated. (`true` to enable, or `false` to disable).

Type: Boolean

Required: No

### replicaCount

The number of replicas in other AZs. Min = 0, Max = 2, Default = 1

**⚠ Important**

Additional charges equivalent to the m-NCUs selected for the graph apply for each replica.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

Required: No

**tags**

Adds metadata tags to the snapshot. These tags can also be used with cost allocation reporting, or used in a Condition statement in an IAM policy.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+--=.\_:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

**Response Syntax**

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
```

```
"name": "string",
"provisionedMemory": number,
"publicConnectivity": boolean,
"replicaCount": number,
"sourceSnapshotId": "string",
"status": "string",
"statusReason": "string",
"vectorSearchConfiguration": {
  "dimension": number
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyId

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If true, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

### sourceSnapshotId

The ID of the snapshot from which the graph was created, if any.

Type: String

Pattern: gs-[a-z0-9]{10}

### status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

### statusReason

The reason that the graph has this status.

Type: String

### vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

**reason**

The reason for the conflict exception.

HTTP Status Code: 409

**InternalServerError**

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ServiceQuotaExceededException**

A service quota was exceeded.

**quotaCode**

Service quota code of the resource for which quota was exceeded.

**resourceId**

The identifier of the resource that exceeded quota.

**resourceType**

The type of the resource that exceeded quota. Ex: Graph, Snapshot

**serviceCode**

The service code that exceeded quota.

HTTP Status Code: 402

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartExportTask

Export data from an existing Neptune Analytics graph to Amazon S3. The graph state should be AVAILABLE.

## Request Syntax

```
POST /exporttasks HTTP/1.1
Content-type: application/json
```

```
{
  "destination": "string",
  "exportFilter": {
    "edgeFilter": {
      "string": {
        "properties": {
          "string": {
            "multiValueHandling": "string",
            "outputType": "string",
            "sourcePropertyName": "string"
          }
        }
      }
    },
    "vertexFilter": {
      "string": {
        "properties": {
          "string": {
            "multiValueHandling": "string",
            "outputType": "string",
            "sourcePropertyName": "string"
          }
        }
      }
    }
  },
  "format": "string",
  "graphIdentifier": "string",
  "kmsKeyIdentifier": "string",
  "parquetType": "string",
  "roleArn": "string",
  "tags": {
    "string": "string"
  }
}
```

```
}  
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### destination

The Amazon S3 URI where data will be exported to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

### exportFilter

The export filter of the export task.

Type: [ExportFilter](#) object

Required: No

### format

The format of the export task.

Type: String

Valid Values: PARQUET | CSV

Required: Yes

### graphIdentifier

The source graph identifier of the export task.

Type: String

Pattern: g-[a-z0-9]{10}

Required: Yes

### kmsKeyId

The KMS key identifier of the export task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

Required: Yes

### parquetType

The parquet type of the export task.

Type: String

Valid Values: COLUMNAR

Required: No

### roleArn

The ARN of the IAM role that will allow data to be exported to the destination.

Type: String

Pattern: arn:aws[^:]\*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+

Required: Yes

### tags

Tags to be applied to the export task.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+ -=.\_:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "destination": "string",
  "exportFilter": {
    "edgeFilter": {
      "string": {
        "properties": {
          "string": {
            "multiValueHandling": "string",
            "outputType": "string",
            "sourcePropertyName": "string"
          }
        }
      }
    },
    "vertexFilter": {
      "string": {
        "properties": {
          "string": {
            "multiValueHandling": "string",
            "outputType": "string",
            "sourcePropertyName": "string"
          }
        }
      }
    }
  },
  "format": "string",
  "graphId": "string",
  "kmsKeyIdentifier": "string",
  "parquetType": "string",
```

```
"roleArn": "string",  
"status": "string",  
"statusReason": "string",  
"taskId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### destination

The Amazon S3 URI of the export task where data will be exported to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

### exportFilter

The export filter of the export task.

Type: [ExportFilter](#) object

### format

The format of the export task.

Type: String

Valid Values: PARQUET | CSV

### graphId

The source graph identifier of the export task.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdentifier

The KMS key identifier of the export task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

### parquetType

The parquet type of the export task.

Type: String

Valid Values: COLUMNAR

### roleArn

The ARN of the IAM role that will allow data to be exported to the destination.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

### status

The current status of the export task.

Type: String

Valid Values: INITIALIZING | EXPORTING | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

### statusReason

The reason that the export task has this status value.

Type: String

### taskId

The unique identifier of the export task.

Type: String

Pattern: `t-[a-z0-9]{10}`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartGraph

Starts the specific graph.

## Request Syntax

```
POST /graphs/graphIdentifier/start HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
```

```
"sourceSnapshotId": "string",
"status": "string",
"statusReason": "string",
"vectorSearchConfiguration": {
  "dimension": number
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdentifier

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If `true`, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

## sourceSnapshotId

The ID of the snapshot from which the graph was created, if it was created from a snapshot.

Type: String

Pattern: gs-[a-z0-9]{10}

## status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

## statusReason

The reason that the graph has this status.

Type: String

## vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

## InternalServerErrorException

A failure occurred on the server.

### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartImportTask

Import data into existing Neptune Analytics graph from Amazon Simple Storage Service (S3). The graph needs to be empty and in the AVAILABLE state.

## Request Syntax

```
POST /graphs/graphIdentifier/importtasks HTTP/1.1
Content-type: application/json
```

```
{
  "blankNodeHandling": "string",
  "failOnError": boolean,
  "format": "string",
  "importOptions": { ... },
  "parquetType": "string",
  "roleArn": "string",
  "source": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### blankNodeHandling

The method to handle blank nodes in the dataset. Currently, only `convertToIri` is supported, meaning blank nodes are converted to unique IRIs at load time. Must be provided when `format` is `ntriples`. For more information, see [Handling RDF values](#).

Type: String

Valid Values: `convertToIri`

Required: No

### failOnError

If set to true, the task halts when an import error is encountered. If set to false, the task skips the data that caused the error and continues if possible.

Type: Boolean

Required: No

### format

Specifies the format of Amazon S3 data to be imported. Valid values are CSV, which identifies the Gremlin CSV format or OPENCYPHER, which identifies the openCypher load format.

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

Required: No

### importOptions

Options for how to perform an import.

Type: [ImportOptions](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

### parquetType

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

Required: No

### roleArn

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

Required: Yes

### [source](#)

A URL identifying the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "format": "string",
  "graphId": "string",
  "importOptions": { ... },
  "parquetType": "string",
  "roleArn": "string",
  "source": "string",
  "status": "string",
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### [format](#)

Specifies the format of Amazon S3 data to be imported. Valid values are CSV, which identifies the Gremlin CSV format or OPENCYPHER, which identifies the openCypher load format.

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

### graphId

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

### importOptions

Options for how to perform an import.

Type: [ImportOptions](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### parquetType

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

### roleArn

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: arn:aws[^:]\*:iam::\d{12}:(role|role/service-role)(/[\w+=, .@-]+)+

### source

A URL identifying the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot.

Type: String

### status

The status of the import task.

Type: String

Valid Values: INITIALIZING | EXPORTING | ANALYZING\_DATA | IMPORTING | REPROVISIONING | ROLLING\_BACK | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

### taskId

The unique identifier of the import task.

Type: String

Pattern: t-[a-z0-9]{10}

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### **message**

A message describing the problem.

#### **reason**

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

#### **message**

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### **message**

A message describing the problem.

HTTP Status Code: 404

### **ThrottlingException**

The exception was interrupted by throttling.

#### **message**

A message describing the problem.

HTTP Status Code: 429

### **ValidationException**

A resource could not be validated.

#### **message**

A message describing the problem.

#### **reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# StopGraph

Stops the specific graph.

## Request Syntax

```
POST /graphs/graphIdentifier/stop HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
```

```
"sourceSnapshotId": "string",
"status": "string",
"statusReason": "string",
"vectorSearchConfiguration": {
  "dimension": number
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

### kmsKeyIdentifier

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If true, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

## sourceSnapshotId

The ID of the snapshot from which the graph was created, if it was created from a snapshot.

Type: String

Pattern: gs-[a-z0-9]{10}

## status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

## statusReason

The reason that the graph has this status.

Type: String

## vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

## InternalServerErrorException

A failure occurred on the server.

### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Adds tags to the specified resource.

## Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

ARN of the resource for which tags need to be added.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn: .+

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### tags

The tags to be assigned to the Neptune Analytics resource.

The tags are metadata that are specified as a list of key-value pairs:

**Key (string)** – A key is the required name of the tag. The string value can be from 1 to 128 Unicode characters in length. It can't be prefixed with `aws :` and can only contain the set of

Unicode characters specified by this Java regular expression: "`^([\p{L}\p{Z}\p{N}_.:/=+\-]*)$`").

**Value** (string) – A value is the optional value of the tag. The string value can be from 1 to 256 Unicode characters in length. It can't be prefixed with `aws :` and can only contain the set of Unicode characters specified by this Java regular expression: "`^([\p{L}\p{Z}\p{N}_.:/=+\-]*)$`").

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `(?!aws:)[a-zA-Z+-._: / ]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

## ResourceNotFoundException

A specified resource could not be located.

### message

A message describing the problem.

HTTP Status Code: 404

## ThrottlingException

The exception was interrupted by throttling.

### message

A message describing the problem.

HTTP Status Code: 429

## ValidationException

A resource could not be validated.

### message

A message describing the problem.

### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Removes the specified tags from the specified resource.

## Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

ARN of the resource whose tag needs to be removed.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:.*+`

Required: Yes

### tagKeys

Tag keys for the tags to be removed.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(?!aws:)[a-zA-Z+-. _:/]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalServerErrorException

A failure occurred on the server.

#### message

A message describing the problem.

HTTP Status Code: 500

### ResourceNotFoundException

A specified resource could not be located.

#### message

A message describing the problem.

HTTP Status Code: 404

### ThrottlingException

The exception was interrupted by throttling.

#### message

A message describing the problem.

HTTP Status Code: 429

### ValidationException

A resource could not be validated.

#### message

A message describing the problem.

#### reason

The reason that the resource could not be validated.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateGraph

Updates the configuration of a specified Neptune Analytics graph

## Request Syntax

```
PATCH /graphs/graphIdentifier HTTP/1.1
Content-type: application/json

{
  "deletionProtection": boolean,
  "provisionedMemory": number,
  "publicConnectivity": boolean
}
```

## URI Request Parameters

The request uses the following URI parameters.

### graphIdentifier

The unique identifier of the Neptune Analytics graph.

Pattern: g-[a-z0-9]{10}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### deletionProtection

A value that indicates whether the graph has deletion protection enabled. The graph can't be deleted when deletion protection is enabled.

Type: Boolean

Required: No

## provisionedMemory

The provisioned memory-optimized Neptune Capacity Units (m-NCUs) to use for the graph.

Min = 16

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: No

## publicConnectivity

Specifies whether or not the graph can be reachable over the internet. All access to graphs is IAM authenticated. (true to enable, or false to disable.

Type: Boolean

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "buildNumber": "string",
  "createTime": number,
  "deletionProtection": boolean,
  "endpoint": "string",
  "id": "string",
  "kmsKeyIdentifier": "string",
  "name": "string",
  "provisionedMemory": number,
  "publicConnectivity": boolean,
  "replicaCount": number,
  "sourceSnapshotId": "string",
  "status": "string",
  "statusReason": "string",
  "vectorSearchConfiguration": {
    "dimension": number
```

```
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The ARN associated with the graph.

Type: String

### buildNumber

The build number of the graph.

Type: String

### createTime

The time at which the graph was created.

Type: Timestamp

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

### endpoint

The graph endpoint.

Type: String

### id

The unique identifier of the graph.

Type: String

Pattern: `g-[a-z0-9]{10}`

### kmsKeyId

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `(?!g-)[a-z][a-z0-9]*(-[a-z0-9]+)*`

### provisionedMemory

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

### publicConnectivity

If `true`, the graph has a public endpoint, otherwise not.

Type: Boolean

### replicaCount

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

### sourceSnapshotId

The ID of the snapshot from which the graph was created, if any.

Type: String

Pattern: gs-[a-z0-9]{10}

### status

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

### statusReason

The reason that the graph has this status.

Type: String

### vectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

Type: [VectorSearchConfiguration](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### ConflictException

Raised when a conflict is encountered.

#### message

A message describing the problem.

#### reason

The reason for the conflict exception.

HTTP Status Code: 409

### InternalServerError

A failure occurred on the server.

**message**

A message describing the problem.

HTTP Status Code: 500

**ResourceNotFoundException**

A specified resource could not be located.

**message**

A message describing the problem.

HTTP Status Code: 404

**ThrottlingException**

The exception was interrupted by throttling.

**message**

A message describing the problem.

HTTP Status Code: 429

**ValidationException**

A resource could not be validated.

**message**

A message describing the problem.

**reason**

The reason that the resource could not be validated.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Amazon Neptune Graph API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [EdgeStructure](#)
- [ExportFilter](#)
- [ExportFilterElement](#)
- [ExportFilterPropertyAttributes](#)
- [ExportTaskDetails](#)
- [ExportTaskSummary](#)
- [GraphDataSummary](#)
- [GraphSnapshotSummary](#)
- [GraphSummary](#)
- [ImportOptions](#)
- [ImportTaskDetails](#)
- [ImportTaskSummary](#)
- [NeptuneImportOptions](#)
- [NodeStructure](#)
- [PrivateGraphEndpointSummary](#)
- [QuerySummary](#)
- [VectorSearchConfiguration](#)

# EdgeStructure

Contains information about an edge in a Neptune Analytics graph.

## Contents

### count

The number of instances of the edge in the graph.

Type: Long

Required: No

### edgeProperties

A list of the properties associated with the edge.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportFilter

This is the top-level field for specifying vertex or edge filters. If the ExportFilter is not provided, then all properties for all labels will be exported. If the ExportFilter is provided but is an empty object, then no data will be exported.

## Contents

### edgeFilter

Used to specify filters on a per-label basis for edges. This allows you to control which edge labels and properties are included in the export.

Type: String to [ExportFilterElement](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### vertexFilter

Used to specify filters on a per-label basis for vertices. This allows you to control which vertex labels and properties are included in the export.

Type: String to [ExportFilterElement](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportFilterElement

Specifies which properties of that label should be included in the export.

## Contents

### properties

Each property is defined by a key-value pair, where the key is the desired output property name (e.g. "name"), and the value is an object.

Type: String to [ExportFilterPropertyAttributes](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: [a-zA-Z0-9\_]+

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportFilterPropertyAttributes

A structure representing a property's attributes. It is a map object of `outputType`, `sourcePropertyName` and `multiValueHandling`.

## Contents

### `multiValueHandling`

Specifies how to handle properties that have multiple values. Can be either `T0_LIST` to export all values as a list, or `PICK_FIRST` to export the first value encountered. If not specified, the default value is `PICK_FIRST`.

Type: String

Valid Values: `T0_LIST` | `PICK_FIRST`

Required: No

### `outputType`

Specifies the data type to use for the property in the exported data (e.g. "String", "Int", "Float"). If a type is not provided, the export process will determine the type. If a given property is present as multiple types (e.g. one vertex has "height" stored as a double, and another edge has it stored as a string), the type will be of Any type, otherwise, it will be the type of the property as present in vertices.

Type: String

Pattern: `(Any|Byte|Short|Int|Long|Float|Double|String|Bool|Boolean|Float|[\]|Double\[\\])`

Required: No

### `sourcePropertyName`

The name of the property as it exists in the original graph data. If not provided, it is assumed that the key matches the desired `sourcePropertyName`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportTaskDetails

Contains details about the specified export task.

## Contents

### **progressPercentage**

The number of progress percentage of the export task.

Type: Integer

Required: Yes

### **startTime**

The start time of the export task.

Type: Timestamp

Required: Yes

### **timeElapsedSeconds**

The time elapsed, in seconds, since the start time of the export task.

Type: Long

Required: Yes

### **numEdgesWritten**

The number of exported edges.

Type: Long

Required: No

### **numVerticesWritten**

The number of exported vertices.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportTaskSummary

Provides details about an export task.

## Contents

### destination

The Amazon S3 URI of the export task where data will be exported to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

### format

The format of the export task.

Type: String

Valid Values: PARQUET | CSV

Required: Yes

### graphId

The source graph identifier of the export task.

Type: String

Pattern: g-[a-z0-9]{10}

Required: Yes

### kmsKeyIdentifier

The KMS key identifier of the export task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]\*:[0-9]{12}:key/[a-zA-Z0-9-]{36}

Required: Yes

### **roleArn**

The ARN of the IAM role that will allow the data to be exported to the destination.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

Required: Yes

### **status**

The current status of the export task.

Type: String

Valid Values: INITIALIZING | EXPORTING | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

Required: Yes

### **taskId**

The unique identifier of the export task.

Type: String

Pattern: `t-[a-z0-9]{10}`

Required: Yes

### **parquetType**

The parquet type of the export task.

Type: String

Valid Values: COLUMNAR

Required: No

### **statusReason**

The reason that the export task has this status value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GraphDataSummary

Summary information about the graph.

## Contents

### edgeLabels

A list of the edge labels in the graph.

Type: Array of strings

Required: No

### edgeProperties

A list of the distinct edge properties in the graph, along with the count of edges where each property is used.

Type: Array of string to long maps

Required: No

### edgeStructures

This field is only present when the requested mode is DETAILED. It contains a list of edge structures.

Type: Array of [EdgeStructure](#) objects

Required: No

### nodeLabels

A list of distinct node labels in the graph.

Type: Array of strings

Required: No

### nodeProperties

A list of the distinct node properties in the graph, along with the count of nodes where each property is used.

Type: Array of string to long maps

Required: No

### **nodeStructures**

This field is only present when the requested mode is DETAILED. It contains a list of node structures.

Type: Array of [NodeStructure](#) objects

Required: No

### **numEdgeLabels**

The number of unique edge labels in the graph.

Type: Long

Required: No

### **numEdgeProperties**

The number of edge properties in the graph.

Type: Long

Required: No

### **numEdges**

The number of edges in the graph.

Type: Long

Required: No

### **numNodeLabels**

The number of distinct node labels in the graph.

Type: Long

Required: No

### **numNodeProperties**

The number of distinct node properties in the graph.

Type: Long

Required: No

### **numNodes**

The number of nodes in the graph.

Type: Long

Required: No

### **totalEdgePropertyValues**

The total number of usages of all edge properties.

Type: Long

Required: No

### **totalNodePropertyValues**

The total number of usages of all node properties.

Type: Long

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GraphSnapshotSummary

Details about a graph snapshot.

## Contents

### arn

The ARN of the graph snapshot.

Type: String

Required: Yes

### id

The unique identifier of the graph snapshot.

Type: String

Pattern: gs-[a-z0-9]{10}

Required: Yes

### name

The snapshot name. For example: my-snapshot-1.

The name must contain from 1 to 63 letters, numbers, or hyphens, and its first character must be a letter. It cannot end with a hyphen or contain two consecutive hyphens. Only lowercase letters are allowed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!gs-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

Required: Yes

### kmsKeyIdentifier

The ID of the KMS key used to encrypt and decrypt the snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:aws(|-cn|-us-gov):kms:[a-zA-Z0-9-]*:[0-9]{12}:key/[a-zA-Z0-9-]{36}`

Required: No

### **snapshotCreateTime**

The time when the snapshot was created.

Type: Timestamp

Required: No

### **sourceGraphId**

The graph identifier for the graph for which a snapshot is to be created.

Type: String

Pattern: `g-[a-z0-9]{10}`

Required: No

### **status**

The status of the graph snapshot.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# GraphSummary

Summary details about a graph.

## Contents

### arn

The ARN associated with the graph.

Type: String

Required: Yes

### id

The unique identifier of the graph.

Type: String

Pattern: g-[a-z0-9]{10}

Required: Yes

### name

The name of the graph.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: (?!g-)[a-z][a-z0-9]\*(-[a-z0-9]+)\*

Required: Yes

### deletionProtection

If `true`, deletion protection is enabled for the graph.

Type: Boolean

Required: No

**endpoint**

The graph endpoint.

Type: String

Required: No

**kmsKeyId**

The ID of the KMS key used to encrypt and decrypt graph data.

Type: String

Required: No

**provisionedMemory**

The number of memory-optimized Neptune Capacity Units (m-NCUs) allocated to the graph.

Type: Integer

Valid Range: Minimum value of 16. Maximum value of 24576.

Required: No

**publicConnectivity**

If `true`, the graph has a public endpoint, otherwise not.

Type: Boolean

Required: No

**replicaCount**

The number of replicas for the graph.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2.

Required: No

**status**

The status of the graph.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | RESETTING | UPDATING |  
SNAPSHOTTING | FAILED | IMPORTING | STARTING | STOPPING | STOPPED

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImportOptions

Options for how to perform an import.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## neptune

Options for importing data from a Neptune database.

Type: [NeptuneImportOptions](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImportTaskDetails

Contains details about an import task.

## Contents

### **dictionaryEntryCount**

The number of dictionary entries in the import task.

Type: Long

Required: Yes

### **errorCount**

The number of errors encountered so far.

Type: Integer

Required: Yes

### **progressPercentage**

The percentage progress so far.

Type: Integer

Required: Yes

### **startTime**

Time at which the import task started.

Type: Timestamp

Required: Yes

### **statementCount**

The number of statements in the import task.

Type: Long

Required: Yes

**status**

Status of the import task.

Type: String

Required: Yes

**timeElapsedSeconds**

Seconds elapsed since the import task started.

Type: Long

Required: Yes

**errorDetails**

Details about the errors that have been encountered.

Type: String

Required: No

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ImportTaskSummary

Details about an import task.

## Contents

### roleArn

The ARN of the IAM role that will allow access to the data that is to be imported.

Type: String

Pattern: `arn:aws[^:]*:iam::\d{12}:(role|role/service-role)(/[\w+=,.\@-]+)+`

Required: Yes

### source

A URL identifying to the location of the data to be imported. This can be an Amazon S3 path, or can point to a Neptune database endpoint or snapshot

Type: String

Required: Yes

### status

Status of the import task.

Type: String

Valid Values: INITIALIZING | EXPORTING | ANALYZING\_DATA | IMPORTING | REPROVISIONING | ROLLING\_BACK | SUCCEEDED | FAILED | CANCELLING | CANCELLED | DELETED

Required: Yes

### taskId

The unique identifier of the import task.

Type: String

Pattern: `t-[a-z0-9]{10}`

Required: Yes

### **format**

Specifies the format of S3 data to be imported. Valid values are CSV, which identifies the [Gremlin CSV format](#) or OPENCYPHER, which identifies the [openCypher load format](#).

Type: String

Valid Values: CSV | OPEN\_CYPHER | PARQUET | NTRIPLES

Required: No

### **graphId**

The unique identifier of the Neptune Analytics graph.

Type: String

Pattern: g-[a-z0-9]{10}

Required: No

### **parquetType**

The parquet type of the import task.

Type: String

Valid Values: COLUMNAR

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NeptuneImportOptions

Options for how to import Neptune data.

## Contents

### **s3ExportKmsKeyId**

The KMS key to use to encrypt data in the S3 bucket where the graph data is exported

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

### **s3ExportPath**

The path to an S3 bucket from which to import data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

### **preserveDefaultVertexLabels**

Neptune Analytics supports label-less vertices and no labels are assigned unless one is explicitly provided. Neptune assigns default labels when none is explicitly provided. When importing the data into Neptune Analytics, the default vertex labels can be omitted by setting *preserveDefaultVertexLabels* to false. Note that if the vertex only has default labels, and has no other properties or edges, then the vertex will effectively not get imported into Neptune Analytics when *preserveDefaultVertexLabels* is set to false.

Type: Boolean

Required: No

### **preserveEdgeIds**

Neptune Analytics currently does not support user defined edge ids. The edge ids are not imported by default. They are imported if *preserveEdgeIds* is set to true, and ids are stored as properties on the relationships with the property name *neptuneEdgeId*.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeStructure

Information about a node.

## Contents

### count

The number of instances of this node.

Type: Long

Required: No

### distinctOutgoingEdgeLabels

The outgoing edge labels associated with this node.

Type: Array of strings

Required: No

### nodeProperties

Properties associated with this node.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PrivateGraphEndpointSummary

Details about a private graph endpoint.

## Contents

### status

The status of the private graph endpoint.

Type: String

Valid Values: CREATING | AVAILABLE | DELETING | FAILED

Required: Yes

### subnetIds

The subnet IDs associated with the private graph endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Pattern: subnet-[a-z0-9]+

Required: Yes

### vpId

The ID of the VPC in which the private graph endpoint is located.

Type: String

Pattern: vpc-[a-z0-9]+

Required: Yes

### vpcEndpointId

The ID of the VPC endpoint.

Type: String

Pattern: vpce-[0-9a-f]{17}

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# QuerySummary

Details of the query listed.

## Contents

### elapsed

The running time of the query, in milliseconds.

Type: Integer

Required: No

### id

A string representation of the id of the query.

Type: String

Required: No

### queryString

The actual query text. The queryString may be truncated if the actual query string is too long.

Type: String

Required: No

### state

State of the query.

Type: String

Valid Values: RUNNING | WAITING | CANCELLING

Required: No

### waited

The amount of time, in milliseconds, the query has waited in the queue before being picked up by a worker thread.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VectorSearchConfiguration

Specifies the number of dimensions for vector embeddings loaded into the graph. Max = 65535

## Contents

### dimension

The number of dimensions.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65536.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

## Required: Conditional

# Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

## **IncompleteSignature**

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

## **InternalFailure**

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

## **MalformedHttpRequestException**

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

**NotAuthorized**

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

**OptInRequired**

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

**RequestAbortedException**

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

**RequestEntityTooLargeException**

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

**RequestTimeoutException**

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

**ServiceUnavailable**

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

**ThrottlingException**

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

### **UnknownOperationException**

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

### **UnrecognizedClientException**

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

### **ValidationError**

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400