



API Reference

AWS Outposts



API Version 2019-12-03

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Outposts: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CancelCapacityTask	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	4
Response Elements	5
Errors	5
See Also	6
CancelOrder	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	7
Response Elements	7
Errors	7
See Also	8
CreateOrder	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	11
Response Elements	12
Errors	12
See Also	13
CreateOutpost	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	17
Response Elements	18
Errors	18
See Also	19

CreateSite	21
Request Syntax	21
URI Request Parameters	22
Request Body	22
Response Syntax	24
Response Elements	25
Errors	25
See Also	26
DeleteOutpost	27
Request Syntax	27
URI Request Parameters	27
Request Body	27
Response Syntax	27
Response Elements	27
Errors	28
See Also	28
DeleteSite	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	30
Response Elements	30
Errors	31
See Also	31
GetCapacityTask	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	34
Errors	37
See Also	38
GetCatalogItem	39
Request Syntax	39
URI Request Parameters	39
Request Body	39

Response Syntax	39
Response Elements	40
Errors	40
See Also	41
GetConnection	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	42
Response Elements	43
Errors	43
See Also	44
GetOrder	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	45
Response Elements	46
Errors	46
See Also	47
GetOutpost	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	48
Response Elements	49
Errors	49
See Also	50
GetOutpostBillingInformation	51
Request Syntax	51
URI Request Parameters	51
Request Body	51
Response Syntax	52
Response Elements	52
Errors	53
Examples	53

See Also	54
GetOutpostInstanceTypes	56
Request Syntax	56
URI Request Parameters	56
Request Body	57
Response Syntax	57
Response Elements	57
Errors	58
See Also	59
GetOutpostSupportedInstanceTypes	60
Request Syntax	60
URI Request Parameters	60
Request Body	61
Response Syntax	61
Response Elements	61
Errors	62
See Also	62
GetSite	64
Request Syntax	64
URI Request Parameters	64
Request Body	64
Response Syntax	64
Response Elements	65
Errors	65
See Also	66
GetSiteAddress	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	68
Response Elements	68
Errors	69
See Also	69
ListAssetInstances	71
Request Syntax	71
URI Request Parameters	71

Request Body	72
Response Syntax	72
Response Elements	73
Errors	73
See Also	74
ListAssets	75
Request Syntax	75
URI Request Parameters	75
Request Body	76
Response Syntax	76
Response Elements	77
Errors	77
See Also	78
ListBlockingInstancesForCapacityTask	79
Request Syntax	79
URI Request Parameters	79
Request Body	80
Response Syntax	80
Response Elements	80
Errors	81
See Also	81
ListCapacityTasks	83
Request Syntax	83
URI Request Parameters	83
Request Body	84
Response Syntax	84
Response Elements	84
Errors	85
See Also	85
ListCatalogItems	87
Request Syntax	87
URI Request Parameters	87
Request Body	88
Response Syntax	88
Response Elements	88
Errors	89

See Also	90
ListOrders	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	92
Response Elements	92
Errors	93
See Also	93
ListOutposts	95
Request Syntax	95
URI Request Parameters	95
Request Body	96
Response Syntax	96
Response Elements	97
Errors	97
See Also	98
ListSites	99
Request Syntax	99
URI Request Parameters	99
Request Body	100
Response Syntax	100
Response Elements	101
Errors	101
See Also	102
ListTagsForResource	103
Request Syntax	103
URI Request Parameters	103
Request Body	103
Response Syntax	103
Response Elements	103
Errors	104
See Also	104
StartCapacityTask	106
Request Syntax	106
URI Request Parameters	106

Request Body	107
Response Syntax	108
Response Elements	109
Errors	111
See Also	112
StartConnection	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	115
Response Elements	116
Errors	116
See Also	117
StartOutpostDecommission	118
Request Syntax	118
URI Request Parameters	118
Request Body	118
Response Syntax	119
Response Elements	119
Errors	119
See Also	120
TagResource	122
Request Syntax	122
URI Request Parameters	122
Request Body	122
Response Syntax	123
Response Elements	123
Errors	123
See Also	124
UntagResource	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	125
Response Elements	126
Errors	126

See Also	126
UpdateOutpost	128
Request Syntax	128
URI Request Parameters	128
Request Body	128
Response Syntax	129
Response Elements	130
Errors	130
See Also	131
UpdateSite	132
Request Syntax	132
URI Request Parameters	132
Request Body	132
Response Syntax	133
Response Elements	134
Errors	134
See Also	135
UpdateSiteAddress	137
Request Syntax	137
URI Request Parameters	137
Request Body	138
Response Syntax	138
Response Elements	139
Errors	139
See Also	140
UpdateSiteRackPhysicalProperties	142
Request Syntax	142
URI Request Parameters	142
Request Body	143
Response Syntax	146
Response Elements	147
Errors	147
See Also	148
Data Types	149
Address	151
Contents	151

See Also	153
AssetInfo	155
Contents	155
See Also	156
AssetInstance	157
Contents	157
See Also	158
AssetInstanceTypeCapacity	159
Contents	159
See Also	159
AssetLocation	160
Contents	160
See Also	160
BlockingInstance	161
Contents	161
See Also	161
CapacityTaskFailure	163
Contents	163
See Also	163
CapacityTaskSummary	164
Contents	164
See Also	166
CatalogItem	167
Contents	167
See Also	168
ComputeAttributes	169
Contents	169
See Also	170
ConnectionDetails	171
Contents	171
See Also	172
EC2Capacity	173
Contents	173
See Also	173
InstancesToExclude	175
Contents	175

See Also	176
InstanceTypeCapacity	177
Contents	177
See Also	177
InstanceTypeItem	178
Contents	178
See Also	178
LineItem	179
Contents	179
See Also	180
LineItemAssetInformation	182
Contents	182
See Also	182
LineItemRequest	183
Contents	183
See Also	183
Order	184
Contents	184
See Also	186
OrderSummary	187
Contents	187
See Also	189
Outpost	190
Contents	190
See Also	193
RackPhysicalProperties	194
Contents	194
See Also	196
ShipmentInformation	197
Contents	197
See Also	197
Site	198
Contents	198
See Also	201
Subscription	202
Contents	202

See Also	204
Common Parameters	205
Common Error Types	208

Welcome

AWS Outposts is a fully managed service that extends AWS infrastructure, APIs, and tools to customer premises. By providing local access to AWS managed infrastructure, AWS Outposts enables customers to build and run applications on premises using the same programming interfaces as in AWS Regions, while using local compute and storage resources for lower latency and local data processing needs.

You can use certain Amazon EC2 API actions for AWS Outposts. For more information on these API actions, see [AWS Outposts actions](#) in the *Amazon EC2 API Reference*.

This document was last published on April 9, 2026.

Actions

The following actions are supported:

- [CancelCapacityTask](#)
- [CancelOrder](#)
- [CreateOrder](#)
- [CreateOutpost](#)
- [CreateSite](#)
- [DeleteOutpost](#)
- [DeleteSite](#)
- [GetCapacityTask](#)
- [GetCatalogItem](#)
- [GetConnection](#)
- [GetOrder](#)
- [GetOutpost](#)
- [GetOutpostBillingInformation](#)
- [GetOutpostInstanceTypes](#)
- [GetOutpostSupportedInstanceTypes](#)
- [GetSite](#)
- [GetSiteAddress](#)
- [ListAssetInstances](#)
- [ListAssets](#)
- [ListBlockingInstancesForCapacityTask](#)
- [ListCapacityTasks](#)
- [ListCatalogItems](#)
- [ListOrders](#)
- [ListOutposts](#)
- [ListSites](#)
- [ListTagsForResource](#)
- [StartCapacityTask](#)

- [StartConnection](#)
- [StartOutpostDecommission](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateOutpost](#)
- [UpdateSite](#)
- [UpdateSiteAddress](#)
- [UpdateSiteRackPhysicalProperties](#)

CancelCapacityTask

Cancels the capacity task.

Request Syntax

```
POST /outposts/OutpostId/capacity/CapacityTaskId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskId

ID of the capacity task that you want to cancel.

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: Yes

OutpostId

ID or ARN of the Outpost associated with the capacity task that you want to cancel.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelOrder

Cancels the specified order for an Outpost.

Request Syntax

```
POST /orders/OrderId/cancel HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OrderId

The ID of the order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOrder

Creates an order for an Outpost.

Request Syntax

```
POST /orders HTTP/1.1
Content-type: application/json

{
  "LineItems": [
    {
      "CatalogItemId": "string",
      "Quantity": number
    }
  ],
  "OutpostIdentifier": "string",
  "PaymentOption": "string",
  "PaymentTerm": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

LineItems

The line items that make up the order.

Type: Array of [LineItemRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

OutpostIdentifier

The ID or the Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

PaymentOption

The payment option.

Type: String

Valid Values: ALL_UPFRONT | NO_UPFRONT | PARTIAL_UPFRONT

Required: Yes

PaymentTerm

The payment terms.

Type: String

Valid Values: THREE_YEARS | ONE_YEAR | FIVE_YEARS

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Order": {
    "LineItems": [
      {
        "AssetInformationList": [
          {
            "AssetId": "string",
            "MacAddressList": [ "string" ]
          }
        ],

```

```
    "CatalogItemId": "string",
    "LineItemId": "string",
    "PreviousLineItemId": "string",
    "PreviousOrderId": "string",
    "Quantity": number,
    "ShipmentInformation": {
      "ShipmentCarrier": "string",
      "ShipmentTrackingNumber": "string"
    },
    "Status": "string"
  }
],
"OrderFulfilledDate": number,
"OrderId": "string",
"OrderSubmissionDate": number,
"OrderType": "string",
"OutpostId": "string",
"PaymentOption": "string",
"PaymentTerm": "string",
"Status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Order

Information about this order.

Type: [Order](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOutpost

Creates an Outpost.

You can specify either an Availability one or an AZ ID.

Request Syntax

```
POST /outposts HTTP/1.1
Content-type: application/json

{
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "Name": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AvailabilityZone

The Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^([a-zA-Z]+-){1,3}([a-zA-Z]+)?(\d+[a-zA-Z])?$`

Required: No

AvailabilityZoneId

The ID of the Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z]+\d-[a-zA-Z]+\d$`

Required: No

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^[\\S]*$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[\\S]+$`

Required: Yes

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

SupportedHardwareType

The type of hardware for this Outpost.

Type: String

Valid Values: RACK | SERVER

Required: No

Tags

The tags to apply to the Outpost.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._: /]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\S \n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Outpost": {
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "LifecycleStatus": "string",
  "Name": "string",
  "OutpostArn": "string",
  "OutpostId": "string",
  "OwnerId": "string",
  "SiteArn": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSite

Creates a site for an Outpost.

Request Syntax

```
POST /sites HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddress": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "ShippingAddress": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
```

```
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\\S]+$`

Required: Yes

Notes

Additional information that you provide about site access requirements, electrician scheduling, personal protective equipment, or regulation of equipment materials that could affect your installation process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^[\\S \\n]+$`

Required: No

OperatingAddress

The location to install and power on the hardware. This address might be different from the shipping address.

Type: [Address](#) object

Required: No

RackPhysicalProperties

Information about the physical and logistical details for the rack at this site. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

Type: [RackPhysicalProperties](#) object

Required: No

ShippingAddress

The location to ship the hardware. This address might be different from the operating address.

Type: [Address](#) object

Required: No

Tags

The tags to apply to a site.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Site": {
    "AccountId": "string",
    "Description": "string",
    "Name": "string",
    "Notes": "string",
    "OperatingAddressCity": "string",
    "OperatingAddressCountryCode": "string",
    "OperatingAddressStateOrRegion": "string",
    "RackPhysicalProperties": {
      "FiberOpticCableType": "string",
      "MaximumSupportedWeightLbs": "string",
      "OpticalStandard": "string",
      "PowerConnector": "string",
      "PowerDrawKva": "string",
      "PowerFeedDrop": "string",
      "PowerPhase": "string",
      "UplinkCount": "string",
      "UplinkGbps": "string"
    },
    "SiteArn": "string",
    "SiteId": "string",
    "Tags": {
      "string" : "string"
    }
  }
}
```

```
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Site](#)

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOutpost

Deletes the specified Outpost.

Request Syntax

```
DELETE /outposts/OutpostId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSite

Deletes the specified site.

Request Syntax

```
DELETE /sites/SiteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCapacityTask

Gets details of the specified capacity task.

Request Syntax

```
GET /outposts/OutpostId/capacity/CapacityTaskId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskId

ID of the capacity task.

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: Yes

OutpostId

ID or ARN of the Outpost associated with the specified capacity task.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "AssetId": "string",
  "CapacityTaskId": "string",
  "CapacityTaskStatus": "string",
  "CompletionDate": number,
  "CreationDate": number,
  "DryRun": boolean,
  "Failed": {
    "Reason": "string",
    "Type": "string"
  },
  "InstancesToExclude": {
    "AccountIds": [ "string" ],
    "Instances": [ "string" ],
    "Services": [ "string" ]
  },
  "LastModifiedDate": number,
  "OrderId": "string",
  "OutpostId": "string",
  "RequestedInstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ],
  "TaskActionOnBlockingInstances": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssetId

The ID of the Outpost asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\\w+)$`

CapacityTaskId

ID of the capacity task.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

CapacityTaskStatus

Status of the capacity task.

A capacity task can have one of the following statuses:

- **REQUESTED** - The capacity task was created and is awaiting the next step by AWS Outposts.
- **IN_PROGRESS** - The capacity task is running and cannot be cancelled.
- **FAILED** - The capacity task could not be completed.
- **COMPLETED** - The capacity task has completed successfully.
- **WAITING_FOR_EVACUATION** - The capacity task requires capacity to run. You must stop the recommended EC2 running instances to free up capacity for the task to run.
- **CANCELLATION_IN_PROGRESS** - The capacity task has been cancelled and is in the process of cleaning up resources.
- **CANCELLED** - The capacity task is cancelled.

Type: String

Valid Values: **REQUESTED** | **IN_PROGRESS** | **FAILED** | **COMPLETED** | **WAITING_FOR_EVACUATION** | **CANCELLATION_IN_PROGRESS** | **CANCELLED**

CompletionDate

The date the capacity task ran successfully.

Type: Timestamp

CreationDate

The date the capacity task was created.

Type: Timestamp

DryRun

Performs a dry run to determine if you are above or below instance capacity.

Type: Boolean

Failed

Reason why the capacity task failed.

Type: [CapacityTaskFailure](#) object

InstancesToExclude

Instances that the user specified they cannot stop in order to free up the capacity needed to run the capacity task.

Type: [InstancesToExclude](#) object

LastModifiedDate

The date the capacity task was last modified.

Type: Timestamp

OrderId

ID of the AWS Outposts order associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

OutpostId

ID of the Outpost associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: ^(arn:aws([a-z-]+)? :outposts :[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$

RequestedInstancePools

List of instance pools requested in the capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

TaskActionOnBlockingInstances

User-specified option in case an instance is blocking the capacity task from running. Shows one of the following options:

- `WAIT_FOR_EVACUATION` - Checks every 10 minutes over 48 hours to determine if instances have stopped and capacity is available to complete the task.
- `FAIL_TASK` - The capacity task fails.

Type: String

Valid Values: `WAIT_FOR_EVACUATION` | `FAIL_TASK`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCatalogItem

Gets information about the specified catalog item.

Request Syntax

```
GET /catalog/item/CatalogItemId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CatalogItemId

The ID of the catalog item.

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR-[A-Z0-9]{7}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CatalogItem": {
    "CatalogItemId": "string",
    "EC2Capacities": [
      {
        "Family": "string",
        "MaxSize": "string",
        "Quantity": "string"
      }
    ],
  },
}
```

```
"ItemStatus": "string",
"PowerKva": number,
"SupportedStorage": [ "string" ],
"SupportedUplinkGbps": [ number ],
"WeightLbs": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CatalogItem

Information about this catalog item.

Type: [CatalogItem](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnection

Note

AWS uses this action to install Outpost servers.

Gets information about the specified connection.

Use CloudTrail to monitor this action or AWS managed policy for AWS Outposts to secure it. For more information, see [AWS managed policies for AWS Outposts](#) and [Logging AWS Outposts API calls with AWS CloudTrail](#) in the *AWS Outposts User Guide*.

Request Syntax

```
GET /connections/ConnectionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectionId

The ID of the connection.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "ConnectionDetails": {
    "AllowedIps": [ "string" ],
    "ClientPublicKey": "string",
    "ClientTunnelAddress": "string",
    "ServerEndpoint": "string",
    "ServerPublicKey": "string",
    "ServerTunnelAddress": "string"
  },
  "ConnectionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectionDetails

Information about the connection.

Type: [ConnectionDetails](#) object

ConnectionId

The ID of the connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOrder

Gets information about the specified order.

Request Syntax

```
GET /orders/OrderId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OrderId

The ID of the order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Order": {
    "LineItems": [
      {
        "AssetInformationList": [
          {
            "AssetId": "string",
            "MacAddressList": [ "string" ]
          }
        ],
      },
    ],
  },
}
```

```
    "CatalogItemId": "string",
    "LineItemId": "string",
    "PreviousLineItemId": "string",
    "PreviousOrderId": "string",
    "Quantity": number,
    "ShipmentInformation": {
      "ShipmentCarrier": "string",
      "ShipmentTrackingNumber": "string"
    },
    "Status": "string"
  }
],
"OrderFulfilledDate": number,
"OrderId": "string",
"OrderSubmissionDate": number,
"OrderType": "string",
"OutpostId": "string",
"PaymentOption": "string",
"PaymentTerm": "string",
"Status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Order

Information about an order.

Type: [Order](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpost

Gets information about the specified Outpost.

Request Syntax

```
GET /outposts/OutpostId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Outpost": {
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "LifecycleStatus": "string",
  "Name": "string",
  "OutpostArn": "string",
  "OutpostId": "string",
  "OwnerId": "string",
  "SiteArn": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpostBillingInformation

Gets current and historical billing information about the specified Outpost.

Request Syntax

```
GET /outpost/OutpostIdentifier/billing-information?  
MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\#\#(\S+)\$$

OutpostIdentifier

The ID or ARN of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+\d{12}:outpost/)?op-[a-f0-9]{17}\$$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ContractEndDate": "string",
  "NextToken": "string",
  "Subscriptions": [
    {
      "BeginDate": number,
      "EndDate": number,
      "MonthlyRecurringPrice": number,
      "OrderIds": [ "string" ],
      "SubscriptionId": "string",
      "SubscriptionStatus": "string",
      "SubscriptionType": "string",
      "UpfrontPrice": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ContractEndDate

The date the current contract term ends for the specified Outpost. You must start the renewal or decommission process at least 5 business days before the current term for your AWS Outposts ends. Failing to complete these steps at least 5 business days before the current term ends might result in unanticipated charges.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: ^[\S \n]+\$

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^\d+##(\S+)$`

Subscriptions

The subscription details for the specified Outpost.

Type: Array of [Subscription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

Examples

Example

This example displays information about the subscription for the specified Outpost.

Sample Request

```
aws outposts get-outpost-billing-information --outpost-identifier op-1234567890example"
```

Sample Response

```
{
  "Subscriptions": [
    {
      "SubscriptionId": "1234567890",
      "SubscriptionType": "ORIGINAL",
      "SubscriptionStatus": "ACTIVE",
      "OrderIds": [
        "oo-000000000000000000"
      ],
      "BeginDate": "Tue Jul 18 16:09:01 UTC 2024",
      "EndDate": "Fri Jul 17 16:09:01 UTC 2026",
      "Currency": "USD",
      "MonthlyRecurringPrice": 100.12,
      "UpfrontPrice": 1000.10
    }
  ],
  "ContractEndDate": "Fri Jul 17 16:09:01 UTC 2026"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpostInstanceTypes

Gets the instance types for the specified Outpost.

Request Syntax

```
GET /outposts/OutpostId/instanceTypes?MaxResults=MaxResults&NextToken=NextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\#\#(\S+)\$$

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InstanceTypes": [
    {
      "InstanceType": "string",
      "VCPU": number
    }
  ],
  "NextToken": "string",
  "OutpostArn": "string",
  "OutpostId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceTypes

Information about the instance types.

Type: Array of [InstanceTypeItem](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostArn

The Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\\d-]+:\\d{12}:outpost/op-[a-f0-9]{17}$`

OutpostId

The ID of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\\d-]+:\\d{12}:outpost/)?op-[a-f0-9]{17}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpostSupportedInstanceTypes

Gets the instance types that an Outpost can support in InstanceTypeCapacity. This will generally include instance types that are not currently configured and therefore cannot be launched with the current Outpost capacity configuration.

Request Syntax

```
GET /outposts/OutpostId/supportedInstanceTypes?  
AssetId=AssetId&MaxResults=MaxResults&NextToken=NextToken&OrderId=OrderId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AssetId

The ID of the Outpost asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Length Constraints: Fixed length of 10.

Pattern: `\d{10}`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OrderId

The ID for the AWS Outposts order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `oo-[a-f0-9]{17}$`

OutpostId

The ID or ARN of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InstanceTypes": [
    {
      "InstanceType": "string",
      "VCPUs": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceTypes

Information about the instance types.

Type: Array of [InstanceTypeItem](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSite

Gets information about the specified Outpost site.

Request Syntax

```
GET /sites/SiteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Site": {
  "AccountId": "string",
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddressCity": "string",
  "OperatingAddressCountryCode": "string",
  "OperatingAddressStateOrRegion": "string",
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "SiteArn": "string",
  "SiteId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSiteAddress

Gets the site address of the specified site.

Request Syntax

```
GET /sites/SiteId/address?AddressType=AddressType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AddressType

The type of the address you request.

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Required: Yes

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Address": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "AddressType": "string",
  "SiteId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

Information about the address.

Type: [Address](#) object

AddressType

The type of the address you receive.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :d{12}:site/)?(os-[a-f0-9]{17})$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssetInstances

A list of Amazon EC2 instances, belonging to all accounts, running on the specified Outpost. Does not include Amazon EBS or Amazon S3 instances.

Request Syntax

```
GET /outposts/OutpostId/assetInstances?  
AccountIdFilter=AccountIdFilter&AssetIdFilter=AssetIdFilter&AwsServiceFilter=AwsServiceFilter&I  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountIdFilter

Filters the results by account ID.

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

AssetIdFilter

Filters the results by asset ID.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\w+)$`

AwsServiceFilter

Filters the results by AWS service.

Valid Values: `AWS | EC2 | ELASTICACHE | ELB | RDS | ROUTE53`

InstanceTypeFilter

Filters the results by instance ID.

Length Constraints: Minimum length of 3. Maximum length of 30.

Pattern: `[a-z0-9\-\.\.]+`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostId

The ID of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\\d-]+:\\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AssetInstances": [
    {
      "AccountId": "string",
      "AssetId": "string",
      "AwsServiceName": "string",
      "InstanceId": "string",
      "InstanceType": "string"
    }
  ]
}
```

```
] ,
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssetInstances

List of instances owned by all accounts on the Outpost. Does not include Amazon EBS or Amazon S3 instances.

Type: Array of [AssetInstance](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssets

Lists the hardware assets for the specified Outpost.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /outposts/OutpostId/assets?  
HostIdFilter=HostIdFilter&MaxResults=MaxResults&NextToken=NextToken&StatusFilter=StatusFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

HostIdFilter

Filters the results by the host ID of a Dedicated Host.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[A-Za-z0-9-]*$`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostId

The ID or the Amazon Resource Name (ARN) of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

StatusFilter

Filters the results by state.

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Valid Values: ACTIVE | RETIRING | ISOLATED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Assets": [
    {
      "AssetId": "string",
      "AssetLocation": {
        "RackElevation": number
      },
      "AssetType": "string",
      "ComputeAttributes": {
        "HostId": "string",
        "InstanceFamilies": [ "string" ],
        "InstanceTypeCapacities": [
          {
            "Count": number,
            "InstanceType": "string"
          }
        ],
        "MaxVcpus": number,
        "State": "string"
      }
    }
  ]
}
```

```
    },  
    "RackId": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Assets

Information about the hardware assets.

Type: Array of [AssetInfo](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListBlockingInstancesForCapacityTask

A list of Amazon EC2 instances running on the Outpost and belonging to the account that initiated the capacity task. Use this list to specify the instances you cannot stop to free up capacity to run the capacity task.

Request Syntax

```
GET /outposts/OutpostId/capacity/CapacityTaskId/blockingInstances?  
MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskId

The ID of the capacity task.

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: Yes

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostId

The ID or ARN of the Outpost associated with the specified capacity task.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BlockingInstances": [
    {
      "AccountId": "string",
      "AwsServiceName": "string",
      "InstanceId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BlockingInstances

A list of all running Amazon EC2 instances on the Outpost. Stopping one or more of these instances can free up the capacity needed to run the capacity task.

Type: Array of [BlockingInstance](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^\d+##\S+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCapacityTasks

Lists the capacity tasks for your AWS account.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /capacity/tasks?  
CapacityTaskStatusFilter=CapacityTaskStatusFilter&MaxResults=MaxResults&NextToken=NextToken&Out  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskStatusFilter

A list of statuses. For example, REQUESTED or WAITING_FOR_EVACUATION.

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED |
WAITING_FOR_EVACUATION | CANCELLATION_IN_PROGRESS | CANCELLED

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\##(\S+)\$$

OutpostIdentifierFilter

Filters the results by an Outpost ID or an Outpost ARN.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CapacityTasks": [
    {
      "AssetId": "string",
      "CapacityTaskId": "string",
      "CapacityTaskStatus": "string",
      "CompletionDate": number,
      "CreationDate": number,
      "LastModifiedDate": number,
      "OrderId": "string",
      "OutpostId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityTasks

Lists all the capacity tasks.

Type: Array of [CapacityTaskSummary](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCatalogItems

Lists the items in the catalog.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /catalog/items?  
EC2FamilyFilter=EC2FamilyFilter&ItemClassFilter=ItemClassFilter&MaxResults=MaxResults&NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[EC2FamilyFilter](#)

Filters the results by EC2 family (for example, M5).

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: [a-z0-9]+

[ItemClassFilter](#)

Filters the results by item class.

Valid Values: RACK | SERVER

[MaxResults](#)

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

[NextToken](#)

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\d+)##(\S+)$`

SupportedStorageFilter

Filters the results by storage option.

Valid Values: EBS | S3

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CatalogItems": [
    {
      "CatalogItemId": "string",
      "EC2Capacities": [
        {
          "Family": "string",
          "MaxSize": "string",
          "Quantity": "string"
        }
      ],
      "ItemStatus": "string",
      "PowerKva": number,
      "SupportedStorage": [ "string" ],
      "SupportedUplinkGbps": [ number ],
      "WeightLbs": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CatalogItems

Information about the catalog items.

Type: Array of [CatalogItem](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrders

Lists the Outpost orders for your AWS account.

Request Syntax

```
GET /list-orders?  
MaxResults=MaxResults&NextToken=NextToken&OutpostIdentifierFilter=OutpostIdentifierFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\backslash d+)##(\backslash S+)$$

OutpostIdentifierFilter

The ID or the Amazon Resource Name (ARN) of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Orders": [
    {
      "LineItemCountsByStatus": {
        "string" : number
      },
      "OrderFulfilledDate": number,
      "OrderId": "string",
      "OrderSubmissionDate": number,
      "OrderType": "string",
      "OutpostId": "string",
      "Status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\##(\S+)\$$

Orders

Information about the orders.

Type: Array of [OrderSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOutposts

Lists the Outposts for your AWS account.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /outposts?  
AvailabilityZoneFilter=AvailabilityZoneFilter&AvailabilityZoneIdFilter=AvailabilityZoneIdFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[AvailabilityZoneFilter](#)

Filters the results by Availability Zone (for example, us-east-1a).

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: $^([a-zA-Z]+-){1,3}([a-zA-Z]+)?(\d+[a-zA-Z])?$$

[AvailabilityZoneIdFilter](#)

Filters the results by AZ ID (for example, use1-az1).

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: $^[a-zA-Z]+\d-[a-zA-Z]+\d$$

[LifeCycleStatusFilter](#)

Filters the results by the lifecycle status.

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[A-Za-z]+$`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Outposts": [
    {
      "AvailabilityZone": "string",
      "AvailabilityZoneId": "string",
      "Description": "string",
      "LifecycleStatus": "string",
      "Name": "string",
      "OutpostArn": "string",
      "OutpostId": "string",
      "OwnerId": "string",
      "SiteArn": "string",
      "SiteId": "string",
      "SupportedHardwareType": "string",
      "Tags": {
```

```
        "string" : "string"  
      }  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Outposts

Information about the Outposts.

Type: Array of [Outpost](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSites

Lists the Outpost sites for your AWS account. Use filters to return specific results.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /sites?
MaxResults=MaxResults&NextToken=NextToken&OperatingAddressCityFilter=OperatingAddressCityFilter
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OperatingAddressCityFilter

Filters the results by city.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\\S[\\S]*$`

OperatingAddressCountryCodeFilter

Filters the results by country code.

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

OperatingAddressStateOrRegionFilter

Filters the results by state or region.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Sites": [
    {
      "AccountId": "string",
      "Description": "string",
      "Name": "string",
      "Notes": "string",
      "OperatingAddressCity": "string",
      "OperatingAddressCountryCode": "string",
      "OperatingAddressStateOrRegion": "string",
      "RackPhysicalProperties": {
        "FiberOpticCableType": "string",
        "MaximumSupportedWeightLbs": "string",
        "OpticalStandard": "string",
        "PowerConnector": "string",
        "PowerDrawKva": "string",
        "PowerFeedDrop": "string",
        "PowerPhase": "string",
        "UplinkCount": "string",
        "UplinkGbps": "string"
      }
    },
  ],
}
```

```
    "SiteArn": "string",
    "SiteId": "string",
    "Tags": {
      "string" : "string"
    }
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\#\#(\S+)\$$

Sites

Information about the sites.

Type: Array of [Site](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for the specified resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+\:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartCapacityTask

Starts the specified capacity task. You can have one active capacity task for each order and each Outpost.

Request Syntax

```
POST /outposts/OutpostId/capacity HTTP/1.1
Content-type: application/json

{
  "AssetId": "string",
  "DryRun": boolean,
  "InstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ],
  "InstancesToExclude": {
    "AccountIds": [ "string" ],
    "Instances": [ "string" ],
    "Services": [ "string" ]
  },
  "OrderId": "string",
  "TaskActionOnBlockingInstances": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outposts associated with the specified capacity task.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$$

Required: Yes

Request Body

The request accepts the following data in JSON format.

AssetId

The ID of the Outpost asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Fixed length of 10.

Pattern: `\d{10}`

Required: No

DryRun

You can request a dry run to determine if the instance type and instance size changes is above or below available instance capacity. Requesting a dry run does not make any changes to your plan.

Type: Boolean

Required: No

InstancePools

The instance pools specified in the capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

Required: Yes

InstancesToExclude

List of user-specified running instances that must not be stopped in order to free up the capacity needed to run the capacity task.

Type: [InstancesToExclude](#) object

Required: No

OrderId

The ID of the AWS Outposts order associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

TaskActionOnBlockingInstances

Specify one of the following options in case an instance is blocking the capacity task from running.

- `WAIT_FOR_EVACUATION` - Checks every 10 minutes over 48 hours to determine if instances have stopped and capacity is available to complete the task.
- `FAIL_TASK` - The capacity task fails.

Type: String

Valid Values: `WAIT_FOR_EVACUATION` | `FAIL_TASK`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AssetId": "string",
  "CapacityTaskId": "string",
  "CapacityTaskStatus": "string",
  "CompletionDate": number,
  "CreationDate": number,
  "DryRun": boolean,
  "Failed": {
    "Reason": "string",
    "Type": "string"
  },
  "InstancesToExclude": {
    "AccountIds": [ "string" ],
    "Instances": [ "string" ],
    "Services": [ "string" ]
  }
}
```

```
},
  "LastModifiedDate": number,
  "OrderId": "string",
  "OutpostId": "string",
  "RequestedInstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ],
  "TaskActionOnBlockingInstances": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssetId

The ID of the asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^(\backslash w+)$$

CapacityTaskId

ID of the capacity task that you want to start.

Type: String

Length Constraints: Fixed length of 21.

Pattern: $^cap-[a-f0-9]{17}$$

CapacityTaskStatus

Status of the specified capacity task.

Type: String

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED |
WAITING_FOR_EVACUATION | CANCELLATION_IN_PROGRESS | CANCELLED

CompletionDate

Date that the specified capacity task ran successfully.

Type: Timestamp

CreationDate

Date that the specified capacity task was created.

Type: Timestamp

DryRun

Results of the dry run showing if the specified capacity task is above or below the available instance capacity.

Type: Boolean

Failed

Reason that the specified capacity task failed.

Type: [CapacityTaskFailure](#) object

InstancesToExclude

User-specified instances that must not be stopped in order to free up the capacity needed to run the capacity task.

Type: [InstancesToExclude](#) object

LastModifiedDate

Date that the specified capacity task was last modified.

Type: Timestamp

OrderId

ID of the AWS Outposts order of the host associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `oo-[a-f0-9]{17}$`

OutpostId

ID of the Outpost associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

RequestedInstancePools

List of the instance pools requested in the specified capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

TaskActionOnBlockingInstances

User-specified option in case an instance is blocking the capacity task from running.

- `WAIT_FOR_EVACUATION` - Checks every 10 minutes over 48 hours to determine if instances have stopped and capacity is available to complete the task.
- `FAIL_TASK` - The capacity task fails.

Type: String

Valid Values: `WAIT_FOR_EVACUATION` | `FAIL_TASK`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartConnection

Note

AWS uses this action to install Outpost servers.

Starts the connection required for Outpost server installation.

Use CloudTrail to monitor this action or AWS managed policy for AWS Outposts to secure it. For more information, see [AWS managed policies for AWS Outposts](#) and [Logging AWS Outposts API calls with AWS CloudTrail](#) in the *AWS Outposts User Guide*.

Request Syntax

```
POST /connections HTTP/1.1
Content-type: application/json

{
  "AssetId": "string",
  "ClientPublicKey": "string",
  "DeviceSerialNumber": "string",
  "NetworkInterfaceDeviceIndex": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AssetId

The ID of the Outpost server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^(\backslashw+)\$$

Required: Yes

ClientPublicKey

The public key of the client.

Type: String

Length Constraints: Fixed length of 44.

Pattern: $^[a-zA-Z0-9/+]{43}=\$$

Required: Yes

DeviceSerialNumber

The serial number of the dongle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^(\backslashw+)\$$

Required: No

NetworkInterfaceDeviceIndex

The device index of the network interface on the Outpost server.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"ConnectionId": "string",  
"UnderlayIpAddress": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectionId](#)

The ID of the connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

[UnderlayIpAddress](#)

The underlay IP address.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 15.

Pattern: `^([\d]{1,3}\.){3}[\d]{1,3}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartOutpostDecommission

Starts the decommission process to return the Outposts racks or servers.

Request Syntax

```
POST /outposts/OutpostId/decommission HTTP/1.1
Content-type: application/json

{
  "ValidateOnly": boolean
}
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost that you want to decommission.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ValidateOnly

Validates the request without starting the decommission process.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BlockingResourceTypes": [ "string" ],
  "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[BlockingResourceTypes](#)

The resources still associated with the Outpost that you are decommissioning.

Type: Array of strings

Valid Values: EC2_INSTANCE | OUTPOST_RAM_SHARE | LGW_ROUTING_DOMAIN
| LGW_ROUTE_TABLE | LGW_VIRTUAL_INTERFACE_GROUP |
OUTPOST_ORDER_CANCELLABLE | OUTPOST_ORDER_INTERVENTION_REQUIRED

[Status](#)

The status of the decommission request.

Type: String

Valid Values: SKIPPED | BLOCKED | REQUESTED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds tags to the specified resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to add to the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from the specified resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

TagKeys

The tag keys.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UpdateOutpost

Updates an Outpost.

Request Syntax

```
PATCH /outposts/OutpostId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "SupportedHardwareType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is OutpostId for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^\[\\S]*$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\[\\S]+$`

Required: No

SupportedHardwareType

The type of hardware for this Outpost.

Type: String

Valid Values: RACK | SERVER

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Outpost": {
    "AvailabilityZone": "string",
    "AvailabilityZoneId": "string",
    "Description": "string",
```

```
"LifecycleStatus": "string",
"Name": "string",
"OutpostArn": "string",
"OutpostId": "string",
"OwnerId": "string",
"SiteArn": "string",
"SiteId": "string",
"SupportedHardwareType": "string",
"Tags": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSite

Updates the specified site.

Request Syntax

```
PATCH /sites/SiteId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "Notes": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+):outposts:[a-z\d-]+\:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\\S]+$`

Required: No

Notes

Notes about a site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^[\\S \\n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Site": {
  "AccountId": "string",
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddressCity": "string",
  "OperatingAddressCountryCode": "string",
  "OperatingAddressStateOrRegion": "string",
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "SiteArn": "string",
  "SiteId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSiteAddress

Updates the address of the specified site.

You can't update a site address if there is an order in progress. You must wait for the order to complete or cancel the order.

You can update the operating address before you place an order at the site, or after all Outposts that belong to the site have been deactivated.

Request Syntax

```
PUT /sites/SiteId/address HTTP/1.1
Content-type: application/json

{
  "Address": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "AddressType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Address

The address for the site.

Type: [Address](#) object

Required: Yes

AddressType

The type of the address.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Address": {
  "AddressLine1": "string",
  "AddressLine2": "string",
  "AddressLine3": "string",
  "City": "string",
  "ContactName": "string",
  "ContactPhoneNumber": "string",
  "CountryCode": "string",
  "DistrictOrCounty": "string",
  "Municipality": "string",
  "PostalCode": "string",
  "StateOrRegion": "string"
},
"AddressType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

Information about an address.

Type: [Address](#) object

AddressType

The type of the address.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSiteRackPhysicalProperties

Update the physical and logistical details for a rack at a site. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

To update a rack at a site with an order of IN_PROGRESS, you must wait for the order to complete or cancel the order.

Request Syntax

```
PATCH /sites/SiteId/rackPhysicalProperties HTTP/1.1
Content-type: application/json
```

```
{
  "FiberOpticCableType": "string",
  "MaximumSupportedWeightLbs": "string",
  "OpticalStandard": "string",
  "PowerConnector": "string",
  "PowerDrawKva": "string",
  "PowerFeedDrop": "string",
  "PowerPhase": "string",
  "UplinkCount": "string",
  "UplinkGbps": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12}:site/)?(os-[a-f0-9]{17}))$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

FiberOpticCableType

The type of fiber that you will use to attach the Outpost to your network.

Type: String

Valid Values: SINGLE_MODE | MULTI_MODE

Required: No

MaximumSupportedWeightLbs

The maximum rack weight that this site can support. NO_LIMIT is over 2000lbs.

Type: String

Valid Values: NO_LIMIT | MAX_1400_LBS | MAX_1600_LBS | MAX_1800_LBS | MAX_2000_LBS

Required: No

OpticalStandard

The type of optical standard that you will use to attach the Outpost to your network. This field is dependent on uplink speed, fiber type, and distance to the upstream device. For more information about networking requirements for racks, see [Network](#) in the AWS Outposts User Guide.

- OPTIC_10GBASE_SR: 10GBASE-SR
- OPTIC_10GBASE_IR: 10GBASE-IR
- OPTIC_10GBASE_LR: 10GBASE-LR
- OPTIC_40GBASE_SR: 40GBASE-SR

- OPTIC_40GBASE_ESR: 40GBASE-ESR
- OPTIC_40GBASE_IR4_LR4L: 40GBASE-IR (LR4L)
- OPTIC_40GBASE_LR4: 40GBASE-LR4
- OPTIC_100GBASE_SR4: 100GBASE-SR4
- OPTIC_100GBASE_CWDM4: 100GBASE-CWDM4
- OPTIC_100GBASE_LR4: 100GBASE-LR4
- OPTIC_100G_PSM4_MSA: 100G PSM4 MSA
- OPTIC_1000BASE_LX: 1000Base-LX
- OPTIC_1000BASE_SX : 1000Base-SX

Type: String

Valid Values: OPTIC_10GBASE_SR | OPTIC_10GBASE_IR | OPTIC_10GBASE_LR
| OPTIC_40GBASE_SR | OPTIC_40GBASE_ESR | OPTIC_40GBASE_IR4_LR4L
| OPTIC_40GBASE_LR4 | OPTIC_100GBASE_SR4 | OPTIC_100GBASE_CWDM4
| OPTIC_100GBASE_LR4 | OPTIC_100G_PSM4_MSA | OPTIC_1000BASE_LX |
OPTIC_1000BASE_SX

Required: No

PowerConnector

The power connector that AWS should plan to provide for connections to the hardware. Note the correlation between `PowerPhase` and `PowerConnector`.

- Single-phase AC feed
 - **L6-30P** – (common in US); 30A; single phase
 - **IEC309 (blue)** – P+N+E, 6hr; 32 A; single phase
- Three-phase AC feed
 - **AH530P7W (red)** – 3P+N+E, 7hr; 30A; three phase
 - **AH532P6W (red)** – 3P+N+E, 6hr; 32A; three phase
 - **CS8365C** – (common in US); 3P+E, 50A; three phase

Type: String

Valid Values: L6_30P | IEC309 | AH530P7W | AH532P6W | CS8365C

Required: No

PowerDrawKva

The power draw, in kVA, available at the hardware placement position for the rack.

Type: String

Valid Values: POWER_5_KVA | POWER_10_KVA | POWER_15_KVA | POWER_30_KVA

Required: No

PowerFeedDrop

Indicates whether the power feed comes above or below the rack.

Type: String

Valid Values: ABOVE_RACK | BELOW_RACK

Required: No

PowerPhase

The power option that you can provide for hardware.

- Single-phase AC feed: 200 V to 277 V, 50 Hz or 60 Hz
- Three-phase AC feed: 346 V to 480 V, 50 Hz or 60 Hz

Type: String

Valid Values: SINGLE_PHASE | THREE_PHASE

Required: No

UplinkCount

Racks come with two Outpost network devices. Depending on the supported uplink speed at the site, the Outpost network devices provide a variable number of uplinks. Specify the number of uplinks for each Outpost network device that you intend to use to connect the rack to your network. Note the correlation between UplinkGbps and UplinkCount.

- 1Gbps - Uplinks available: 1, 2, 4, 6, 8
- 10Gbps - Uplinks available: 1, 2, 4, 8, 12, 16
- 40 and 100 Gbps- Uplinks available: 1, 2, 4

Type: String

Valid Values: UPLINK_COUNT_1 | UPLINK_COUNT_2 | UPLINK_COUNT_3 | UPLINK_COUNT_4 | UPLINK_COUNT_5 | UPLINK_COUNT_6 | UPLINK_COUNT_7 | UPLINK_COUNT_8 | UPLINK_COUNT_12 | UPLINK_COUNT_16

Required: No

UplinkGbps

The uplink speed the rack should support for the connection to the Region.

Type: String

Valid Values: UPLINK_1G | UPLINK_10G | UPLINK_40G | UPLINK_100G

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Site": {
    "AccountId": "string",
    "Description": "string",
    "Name": "string",
    "Notes": "string",
    "OperatingAddressCity": "string",
    "OperatingAddressCountryCode": "string",
    "OperatingAddressStateOrRegion": "string",
    "RackPhysicalProperties": {
      "FiberOpticCableType": "string",
      "MaximumSupportedWeightLbs": "string",
      "OpticalStandard": "string",
      "PowerConnector": "string",
      "PowerDrawKva": "string",
      "PowerFeedDrop": "string",
      "PowerPhase": "string",
      "UplinkCount": "string",
      "UplinkGbps": "string"
    },
    "SiteArn": "string",
    "SiteId": "string",
```

```
    "Tags": {  
      "string" : "string"  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

ResourceId

The ID of the resource causing the conflict.

ResourceType

The type of the resource causing the conflict.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Outposts API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Address](#)
- [AssetInfo](#)
- [AssetInstance](#)
- [AssetInstanceTypeCapacity](#)
- [AssetLocation](#)
- [BlockingInstance](#)
- [CapacityTaskFailure](#)
- [CapacityTaskSummary](#)
- [CatalogItem](#)
- [ComputeAttributes](#)
- [ConnectionDetails](#)
- [EC2Capacity](#)
- [InstancesToExclude](#)
- [InstanceTypeCapacity](#)
- [InstanceTypeItem](#)
- [LineItem](#)
- [LineItemAssetInformation](#)
- [LineItemRequest](#)
- [Order](#)
- [OrderSummary](#)

- [Outpost](#)
- [RackPhysicalProperties](#)
- [ShipmentInformation](#)
- [Site](#)
- [Subscription](#)

Address

Information about an address.

Contents

AddressLine1

The first line of the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^\S[\S]*$`

Required: Yes

City

The city for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: Yes

ContactName

The name of the contact.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\S[\S]*$`

Required: Yes

ContactPhoneNumber

The phone number of the contact.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^\S]+$`

Required: Yes

CountryCode

The ISO-3166 two-letter country code for the address.

Type: String

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

Required: Yes

PostalCode

The postal code for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[a-zA-Z0-9 -]+$`

Required: Yes

StateOrRegion

The state for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: Yes

AddressLine2

The second line of the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 60.

Pattern: `^\S[\S]*$`

Required: No

AddressLine3

The third line of the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 60.

Pattern: `^\S[\S]*$`

Required: No

DistrictOrCounty

The district or county for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 60.

Pattern: `^\S[\S]*`

Required: No

Municipality

The municipality for the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 180.

Pattern: `^\S[\S]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetInfo

Information about hardware assets.

Contents

AssetId

The ID of the asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^\w+$`

Required: No

AssetLocation

The position of an asset in a rack.

Type: [AssetLocation](#) object

Required: No

AssetType

The type of the asset.

Type: String

Valid Values: COMPUTE

Required: No

ComputeAttributes

Information about compute hardware assets.

Type: [ComputeAttributes](#) object

Required: No

RackId

The rack ID of the asset.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 20.

Pattern: `^[\\S \\n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetInstance

An Amazon EC2 instance.

Contents

AccountId

The ID of the AWS account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

AssetId

The ID of the asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\\w+)$`

Required: No

AwsServiceName

The AWS service name of the instance.

Type: String

Valid Values: `AWS | EC2 | ELASTICACHE | ELB | RDS | ROUTE53`

Required: No

InstanceId

The ID of the instance.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 32.

Pattern: `^i-[0-9a-z]+$`

Required: No

InstanceType

The type of instance.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 30.

Pattern: `[a-z0-9\-\.\.]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetInstanceTypeCapacity

The capacity for each instance type.

Contents

Count

The number of each instance type.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 9999.

Required: Yes

InstanceType

The type of instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-z0-9\-\.\]+[a-z0-9\-\.\]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetLocation

Information about the position of the asset in a rack.

Contents

RackElevation

The position of an asset in a rack measured in rack units.

Type: Float

Valid Range: Minimum value of 0. Maximum value of 99.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BlockingInstance

A running Amazon EC2 instance that can be stopped to free up capacity needed to run the capacity task.

Contents

AccountId

The ID of the AWS account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

AwsServiceName

The AWS service name that owns the specified blocking instance.

Type: String

Valid Values: `AWS` | `EC2` | `ELASTICACHE` | `ELB` | `RDS` | `ROUTE53`

Required: No

InstanceId

The ID of the blocking instance.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 32.

Pattern: `^i-[0-9a-z]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityTaskFailure

The capacity tasks that failed.

Contents

Reason

The reason that the specified capacity task failed.

Type: String

Length Constraints: Maximum length of 128.

Required: Yes

Type

The type of failure.

Type: String

Valid Values: UNSUPPORTED_CAPACITY_CONFIGURATION | UNEXPECTED_ASSET_STATE
| BLOCKING_INSTANCES_NOT_EVACUATED | INTERNAL_SERVER_ERROR |
RESOURCE_NOT_FOUND

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityTaskSummary

The summary of the capacity task.

Contents

AssetId

The ID of the asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\\w+)$`

Required: No

CapacityTaskId

The ID of the specified capacity task.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: No

CapacityTaskStatus

The status of the capacity task.

Type: String

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED | WAITING_FOR_EVACUATION | CANCELLATION_IN_PROGRESS | CANCELLED

Required: No

CompletionDate

The date that the specified capacity task successfully ran.

Type: Timestamp

Required: No

CreationDate

The date that the specified capacity task was created.

Type: Timestamp

Required: No

LastModifiedDate

The date that the specified capacity was last modified.

Type: Timestamp

Required: No

OrderId

The ID of the AWS Outposts order of the host associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OutpostId

The ID of the Outpost associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: ^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CatalogItem

Information about a catalog item.

Contents

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `OR-[A-Z0-9]{7}`

Required: No

EC2Capacities

Information about the EC2 capacity of an item.

Type: Array of [EC2Capacity](#) objects

Required: No

ItemStatus

The status of a catalog item.

Type: String

Valid Values: AVAILABLE | DISCONTINUED

Required: No

PowerKva

Information about the power draw of an item.

Type: Float

Required: No

SupportedStorage

The supported storage options for the catalog item.

Type: Array of strings

Valid Values: EBS | S3

Required: No

SupportedUplinkGbps

The uplink speed this catalog item requires for the connection to the Region.

Type: Array of integers

Required: No

WeightLbs

The weight of the item in pounds.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeAttributes

Information about compute hardware assets.

Contents

HostId

The host ID of the Dedicated Host on the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[A-Za-z0-9-]*$`

Required: No

InstanceFamilies

A list of the names of instance families that are currently associated with a given asset.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(?:.{1,200}/)?(?:[a-z0-9-_A-Z])+$`

Required: No

InstanceTypeCapacities

The instance type capacities configured for this asset. This can be changed through a capacity task.

Type: Array of [AssetInstanceTypeCapacity](#) objects

Required: No

MaxVcpus

The maximum number of vCPUs possible for the specified asset.

Type: Integer

Required: No

State

The state.

- **ACTIVE** - The asset is available and can provide capacity for new compute resources.
- **ISOLATED** - The asset is undergoing maintenance and can't provide capacity for new compute resources. Existing compute resources on the asset are not affected.
- **RETIRING** - The underlying hardware for the asset is degraded. Capacity for new compute resources is reduced. AWS sends notifications for resources that must be stopped before the asset can be replaced.

Type: String

Valid Values: ACTIVE | ISOLATED | RETIRING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectionDetails

Information about a connection.

Contents

AllowedIps

The allowed IP addresses.

Type: Array of strings

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: $^([\d-]{1,3}\.){3}[\d-]{1,3}/[\d-]{1,2}\$$

Required: No

ClientPublicKey

The public key of the client.

Type: String

Length Constraints: Fixed length of 44.

Pattern: $^[a-zA-Z\d-9/+]{44}=\$$

Required: No

ClientTunnelAddress

The client tunnel address.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: $^([\d-]{1,3}\.){3}[\d-]{1,3}/[\d-]{1,2}\$$

Required: No

ServerEndpoint

The endpoint for the server.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 21.

Pattern: `^([\0-9]{1,3}\.){3}[\0-9]{1,3}:[\0-9]{1,5}$`

Required: No

ServerPublicKey

The public key of the server.

Type: String

Length Constraints: Fixed length of 44.

Pattern: `^[a-zA-Z0-9/+] {43}=$`

Required: No

ServerTunnelAddress

The server tunnel address.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: `^([\0-9]{1,3}\.){3}[\0-9]{1,3}/[\0-9]{1,2}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EC2Capacity

Information about EC2 capacity.

Contents

Family

The family of the EC2 capacity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: [a-z0-9]+

Required: No

MaxSize

The maximum size of the EC2 capacity.

Type: String

Required: No

Quantity

The quantity of the EC2 capacity.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstancesToExclude

User-specified instances that must not be stopped. These instances will not appear in the list of instances that AWS recommends to stop in order to free up capacity.

Contents

AccountIds

IDs of the accounts that own each instance that must not be stopped.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

Instances

List of user-specified instances that must not be stopped.

Type: Array of strings

Length Constraints: Minimum length of 11. Maximum length of 32.

Pattern: `^i-[0-9a-z]+$`

Required: No

Services

Names of the services that own each instance that must not be stopped in order to free up the capacity needed to run the capacity task.

Type: Array of strings

Valid Values: `AWS | EC2 | ELASTICACHE | ELB | RDS | ROUTE53`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceTypeCapacity

The instance type that you specify determines the combination of CPU, memory, storage, and networking capacity.

Contents

Count

The number of instances for the specified instance type.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 9999.

Required: Yes

InstanceType

The instance type of the hosts.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-z0-9\-\.\.][a-z0-9\-\.\.]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceTypeItem

Information about an instance type.

Contents

InstanceType

The instance type.

Type: String

Required: No

VCPUs

The number of default VCPUs in an instance type.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItem

Information about a line item.

Contents

AssetInformationList

Information about assets.

Type: Array of [LineItemAssetInformation](#) objects

Required: No

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR- [A-Z0-9]{7}

Required: No

LineItemId

The ID of the line item.

Type: String

Pattern: ooi- [a-f0-9]{17}

Required: No

PreviousLineItemId

The ID of the previous line item.

Type: String

Pattern: ooi- [a-f0-9]{17}

Required: No

PreviousOrderId

The ID of the previous order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

Quantity

The quantity of the line item.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

ShipmentInformation

Information about a line item shipment.

Type: [ShipmentInformation](#) object

Required: No

Status

The status of the line item.

Type: String

Valid Values: PREPARING | BUILDING | SHIPPED | DELIVERED | INSTALLING |
INSTALLED | ERROR | CANCELLED | REPLACED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItemAssetInformation

Information about a line item asset.

Contents

AssetId

The ID of the asset. An Outpost asset can be a single server within an Outposts rack or an Outposts server configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\w+)$`

Required: No

MacAddressList

The MAC addresses of the asset.

Type: Array of strings

Length Constraints: Fixed length of 17.

Pattern: `^([\0-9A-Fa-f]{2}[:-]){5}([\0-9A-Fa-f]{2})$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItemRequest

Information about a line item request.

Contents

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR-[A-Z0-9]{7}

Required: No

Quantity

The quantity of a line item request.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Order

Information about an order.

Contents

LineItems

The line items for the order

Type: Array of [LineItem](#) objects

Required: No

OrderFulfilledDate

The fulfillment date of the order.

Type: Timestamp

Required: No

OrderId

The ID of the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OrderSubmissionDate

The submission date for the order.

Type: Timestamp

Required: No

OrderType

The type of order.

Type: String

Valid Values: OUTPOST | REPLACEMENT

Required: No

OutpostId

The ID of the Outpost in the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^op-[a-f0-9]{17}$`

Required: No

PaymentOption

The payment option for the order.

Type: String

Valid Values: ALL_UPFRONT | NO_UPFRONT | PARTIAL_UPFRONT

Required: No

PaymentTerm

The payment term.

Type: String

Valid Values: THREE_YEARS | ONE_YEAR | FIVE_YEARS


Required: No

Status

The status of the order.

- PREPARING - Order is received and being prepared.
- IN_PROGRESS - Order is either being built or shipped. To get more details, see the line item status.
- DELIVERED - Order was delivered to the Outpost site.

- COMPLETED - Order is complete.
- CANCELLED - Order is cancelled.
- ERROR - Customer should contact support.

 **Note**

The following status are deprecated: RECEIVED, PENDING, PROCESSING, INSTALLING, and FULFILLED.

Type: String

Valid Values: RECEIVED | PENDING | PROCESSING | INSTALLING | FULFILLED | CANCELLED | PREPARING | IN_PROGRESS | DELIVERED | COMPLETED | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrderSummary

A summary of line items in your order.

Contents

LineItemCountsByStatus

The status of all line items in the order.

Type: String to integer map

Valid Keys: PREPARING | BUILDING | SHIPPED | DELIVERED | INSTALLING |
INSTALLED | ERROR | CANCELLED | REPLACED

Valid Range: Minimum value of 1.

Required: No

OrderFulfilledDate

The fulfilment date for the order.

Type: Timestamp

Required: No

OrderId

The ID of the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OrderSubmissionDate

The submission date for the order.

Type: Timestamp

Required: No

OrderType

The type of order.

Type: String

Valid Values: OUTPOST | REPLACEMENT

Required: No

OutpostId

The ID of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^op-[a-f0-9]{17}$`

Required: No

Status

The status of the order.

- PREPARING - Order is received and is being prepared.
- IN_PROGRESS - Order is either being built, shipped, or installed. For more information, see the `LineItem` status.
- COMPLETED - Order is complete.
- CANCELLED - Order is cancelled.
- ERROR - Customer should contact support.

Note

The following statuses are deprecated: RECEIVED, PENDING, PROCESSING, INSTALLING, and FULFILLED.

Type: String

Valid Values: RECEIVED | PENDING | PROCESSING | INSTALLING | FULFILLED | CANCELLED | PREPARING | IN_PROGRESS | DELIVERED | COMPLETED | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Outpost

Information about an Outpost.

Contents

AvailabilityZone

The Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^([a-zA-Z]+-){1,3}([a-zA-Z]+)?(\d+[a-zA-Z])?$`

Required: No

AvailabilityZoneId

The ID of the Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z]+\d-[a-zA-Z]+\d$`

Required: No

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^[\\S]*$`

Required: No

LifeCycleStatus

The life cycle status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[A-Za-z]+$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[\S]+$`

Required: No

OutpostArn

The Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/op-[a-f0-9]{17}$`

Required: No

OutpostId

The ID of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: No

OwnerId

The AWS account ID of the Outpost owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

SiteArn

The Amazon Resource Name (ARN) of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/(os-[a-f0-9]{17})$`

Required: No

SiteId

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: No

SupportedHardwareType

The hardware type.

Type: String

Valid Values: RACK | SERVER

Required: No

Tags

The Outpost tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._: /]+`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\S \n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RackPhysicalProperties

Information about the physical and logistical details for racks at sites. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

Contents

FiberOpticCableType

The type of fiber used to attach the Outpost to the network.

Type: String

Valid Values: SINGLE_MODE | MULTI_MODE

Required: No

MaximumSupportedWeightLbs

The maximum rack weight that this site can support. NO_LIMIT is over 2000 lbs (907 kg).

Type: String

Valid Values: NO_LIMIT | MAX_1400_LBS | MAX_1600_LBS | MAX_1800_LBS | MAX_2000_LBS

Required: No

OpticalStandard

The type of optical standard used to attach the Outpost to the network. This field is dependent on uplink speed, fiber type, and distance to the upstream device. For more information about networking requirements for racks, see [Network](#) in the AWS Outposts User Guide.

Type: String

Valid Values: OPTIC_10GBASE_SR | OPTIC_10GBASE_IR | OPTIC_10GBASE_LR | OPTIC_40GBASE_SR | OPTIC_40GBASE_ESR | OPTIC_40GBASE_IR4_LR4L | OPTIC_40GBASE_LR4 | OPTIC_100GBASE_SR4 | OPTIC_100GBASE_CWDM4 | OPTIC_100GBASE_LR4 | OPTIC_100G_PSM4_MSA | OPTIC_1000BASE_LX | OPTIC_1000BASE_SX

Required: No

PowerConnector

The power connector for the hardware.

Type: String

Valid Values: L6_30P | IEC309 | AH530P7W | AH532P6W | CS8365C

Required: No

PowerDrawKva

The power draw available at the hardware placement position for the rack.

Type: String

Valid Values: POWER_5_KVA | POWER_10_KVA | POWER_15_KVA | POWER_30_KVA

Required: No

PowerFeedDrop

The position of the power feed.

Type: String

Valid Values: ABOVE_RACK | BELOW_RACK

Required: No

PowerPhase

The power option that you can provide for hardware.

Type: String

Valid Values: SINGLE_PHASE | THREE_PHASE

Required: No

UplinkCount

The number of uplinks each Outpost network device.

Type: String

Valid Values: UPLINK_COUNT_1 | UPLINK_COUNT_2 | UPLINK_COUNT_3 |
UPLINK_COUNT_4 | UPLINK_COUNT_5 | UPLINK_COUNT_6 | UPLINK_COUNT_7 |
UPLINK_COUNT_8 | UPLINK_COUNT_12 | UPLINK_COUNT_16

Required: No

UplinkGbps

The uplink speed the rack supports for the connection to the Region.

Type: String

Valid Values: UPLINK_1G | UPLINK_10G | UPLINK_40G | UPLINK_100G

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ShipmentInformation

Information about a line item shipment.

Contents

ShipmentCarrier

The carrier of the shipment.

Type: String

Valid Values: DHL | DBS | FEDEX | UPS | EXPEDITORS

Required: No

ShipmentTrackingNumber

The tracking number of the shipment.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 42.

Pattern: `^[a-zA-Z0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Site

Information about a site.

Contents

AccountId

The ID of the AWS account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\S]+$`

Required: No

Notes

Notes about a site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^\S \n]+$`

Required: No

OperatingAddressCity

City where the hardware is installed and powered on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: No

OperatingAddressCountryCode

The ISO-3166 two-letter country code where the hardware is installed and powered on.

Type: String

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

Required: No

OperatingAddressStateOrRegion

State or region where the hardware is installed and powered on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: No

RackPhysicalProperties

Information about the physical and logistical details for a rack at the site.

Type: [RackPhysicalProperties](#) object

Required: No

SiteArn

The Amazon Resource Name (ARN) of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/(os-[a-f0-9]{17})$`

Required: No

SiteId

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: No

Tags

The site tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._:/$]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Subscription

Provides information about your AWS Outposts subscriptions.

Contents

BeginDate

The date your subscription starts.

Type: Timestamp

Required: No

EndDate

The date your subscription ends.

Type: Timestamp

Required: No

MonthlyRecurringPrice

The amount you are billed each month in the subscription period.

Type: Double

Required: No

OrderIds

The order ID for your subscription.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\\S \\n]+$`

Required: No

SubscriptionId

The ID of the subscription that appears on the AWS Billing Center console.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^\[S \n]+\$`

Required: No

SubscriptionStatus

The status of subscription which can be one of the following:

- **INACTIVE** - Subscription requests that are inactive.
- **ACTIVE** - Subscription requests that are in progress and have an end date in the future.
- **CANCELLED** - Subscription requests that are cancelled.

Type: String

Valid Values: ACTIVE | INACTIVE | CANCELLED

Required: No

SubscriptionType

The type of subscription which can be one of the following:

- **ORIGINAL** - The first order on the AWS Outposts.
- **RENEWAL** - Renewal requests, both month to month and longer term.
- **CAPACITY_INCREASE** - Capacity scaling orders.

Type: String

Valid Values: ORIGINAL | RENEWAL | CAPACITY_INCREASE

Required: No

UpfrontPrice

The amount billed when the subscription is created. This is a one-time charge.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400