



Welcome

# AWS Private CA Connector for SCEP



**API Version 2018-05-10**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS Private CA Connector for SCEP: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
CreateChallenge .....	3
Request Syntax .....	3
URI Request Parameters .....	3
Request Body .....	3
Response Syntax .....	4
Response Elements .....	5
Errors .....	5
See Also .....	7
CreateConnector .....	8
Request Syntax .....	8
URI Request Parameters .....	8
Request Body .....	8
Response Syntax .....	10
Response Elements .....	10
Errors .....	11
See Also .....	12
DeleteChallenge .....	14
Request Syntax .....	14
URI Request Parameters .....	14
Request Body .....	14
Response Syntax .....	14
Response Elements .....	14
Errors .....	14
See Also .....	16
DeleteConnector .....	17
Request Syntax .....	17
URI Request Parameters .....	17
Request Body .....	17
Response Syntax .....	17
Response Elements .....	17
Errors .....	17
See Also .....	19

---

GetChallengeMetadata .....	20
Request Syntax .....	20
URI Request Parameters .....	20
Request Body .....	20
Response Syntax .....	20
Response Elements .....	21
Errors .....	21
See Also .....	22
GetChallengePassword .....	24
Request Syntax .....	24
URI Request Parameters .....	24
Request Body .....	24
Response Syntax .....	24
Response Elements .....	24
Errors .....	25
See Also .....	26
GetConnector .....	27
Request Syntax .....	27
URI Request Parameters .....	27
Request Body .....	27
Response Syntax .....	27
Response Elements .....	28
Errors .....	28
See Also .....	29
ListChallengeMetadata .....	31
Request Syntax .....	31
URI Request Parameters .....	31
Request Body .....	32
Response Syntax .....	32
Response Elements .....	32
Errors .....	33
See Also .....	34
ListConnectors .....	35
Request Syntax .....	35
URI Request Parameters .....	35
Request Body .....	35

---

Response Syntax .....	35
Response Elements .....	36
Errors .....	37
See Also .....	37
ListTagsForResource .....	39
Request Syntax .....	39
URI Request Parameters .....	39
Request Body .....	39
Response Syntax .....	39
Response Elements .....	39
Errors .....	40
See Also .....	41
TagResource .....	42
Request Syntax .....	42
URI Request Parameters .....	42
Request Body .....	42
Response Syntax .....	42
Response Elements .....	43
Errors .....	43
See Also .....	44
UntagResource .....	45
Request Syntax .....	45
URI Request Parameters .....	45
Request Body .....	45
Response Syntax .....	45
Response Elements .....	45
Errors .....	45
See Also .....	47
<b>Data Types .....</b>	<b>48</b>
Challenge .....	49
Contents .....	49
See Also .....	50
ChallengeMetadata .....	51
Contents .....	51
See Also .....	52
ChallengeMetadataSummary .....	53

---

Contents .....	53
See Also .....	54
Connector .....	55
Contents .....	55
See Also .....	57
ConnectorSummary .....	58
Contents .....	58
See Also .....	60
IntuneConfiguration .....	61
Contents .....	61
See Also .....	61
MobileDeviceManagement .....	63
Contents .....	63
See Also .....	63
OpenIdConfiguration .....	64
Contents .....	64
See Also .....	64
<b>Common Parameters .....</b>	<b>65</b>
<b>Common Error Types .....</b>	<b>68</b>

# Welcome

Connector for SCEP creates a connector between AWS Private CA and your SCEP-enabled clients and devices. For more information, see [Connector for SCEP](#) in the *AWS Private CA User Guide*.

This document was last published on April 18, 2026.

# Actions

The following actions are supported:

- [CreateChallenge](#)
- [CreateConnector](#)
- [DeleteChallenge](#)
- [DeleteConnector](#)
- [GetChallengeMetadata](#)
- [GetChallengePassword](#)
- [GetConnector](#)
- [ListChallengeMetadata](#)
- [ListConnectors](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)

# CreateChallenge

For general-purpose connectors. Creates a *challenge password* for the specified connector. The SCEP protocol uses a challenge password to authenticate a request before issuing a certificate from a certificate authority (CA). Your SCEP clients include the challenge password as part of their certificate request to Connector for SCEP. To retrieve the connector Amazon Resource Names (ARNs) for the connectors in your account, call [ListConnectors](#).

To create additional challenge passwords for the connector, call `CreateChallenge` again. We recommend frequently rotating your challenge passwords.

## Request Syntax

```
POST /challenges HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "ConnectorArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### ClientToken

Custom string that can be used to distinguish between calls to the [CreateChallenge](#) action. Client tokens for `CreateChallenge` time out after five minutes. Therefore, if you call `CreateChallenge` multiple times with the same client token within five minutes, Connector for SCEP recognizes that you are requesting only one challenge and will only respond with one. If you change the client token for each call, Connector for SCEP recognizes that you are requesting multiple challenge passwords.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [!-~]+

Required: No

### ConnectorArn

The Amazon Resource Name (ARN) of the connector that you want to create a challenge for.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: arn:aws(-[a-z]+)\*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d\*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}

Required: Yes

### Tags

The key-value pairs to associate with the resource.

Type: String to string map

Required: No

## Response Syntax

```
HTTP/1.1 202
Content-type: application/json
```

```
{
  "Challenge": {
    "Arn": "string",
    "ConnectorArn": "string",
    "CreatedAt": number,
    "Password": "string",
    "UpdatedAt": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

### Challenge

Returns the challenge details for the specified connector.

Type: [Challenge](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### **BadRequestException**

The request is malformed or contains an error such as an invalid parameter value or a missing required parameter.

HTTP Status Code: 400

### **ConflictException**

This request can't be completed for one of the following reasons because the requested resource was being concurrently modified by another request.

#### **ResourceId**

The identifier of the AWS resource.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 409

### **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### **ResourceId**

The identifier of the AWS resource.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### **ServiceQuotaExceededException**

The request would cause a service quota to be exceeded.

#### **QuotaCode**

The quota identifier.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

#### **ServiceCode**

Identifies the originating service.

HTTP Status Code: 402

### **ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateConnector

Creates a SCEP connector. A SCEP connector links AWS Private Certificate Authority to your SCEP-compatible devices and mobile device management (MDM) systems. Before you create a connector, you must complete a set of prerequisites, including creation of a private certificate authority (CA) to use with this connector. For more information, see [Connector for SCEP prerequisites](#).

## Request Syntax

```
POST /connectors HTTP/1.1
Content-type: application/json

{
  "CertificateAuthorityArn": "string",
  "ClientToken": "string",
  "MobileDeviceManagement": { ... },
  "Tags": {
    "string" : "string"
  },
  "VpcEndpointId": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### CertificateAuthorityArn

The Amazon Resource Name (ARN) of the AWS Private Certificate Authority certificate authority to use with this connector. Due to security vulnerabilities present in the SCEP protocol, we recommend using a private CA that's dedicated for use with the connector.

To retrieve the private CAs associated with your account, you can call [ListCertificateAuthorities](#) using the AWS Private CA API.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:acm-pca:[a-z]+(-[a-z]+)-[1-9]\d*:\d{12}:certificate-authority\/[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## ClientToken

Custom string that can be used to distinguish between calls to the [CreateChallenge](#) action. Client tokens for CreateChallenge time out after five minutes. Therefore, if you call CreateChallenge multiple times with the same client token within five minutes, Connector for SCEP recognizes that you are requesting only one challenge and will only respond with one. If you change the client token for each call, Connector for SCEP recognizes that you are requesting multiple challenge passwords.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[!-~]+`

Required: No

## MobileDeviceManagement

If you don't supply a value, by default Connector for SCEP creates a connector for general-purpose use. A general-purpose connector is designed to work with clients or endpoints that support the SCEP protocol, except Connector for SCEP for Microsoft Intune. With connectors for general-purpose use, you manage SCEP challenge passwords using Connector for SCEP. For information about considerations and limitations with using Connector for SCEP, see [Considerations and Limitations](#).

If you provide an `IntuneConfiguration`, Connector for SCEP creates a connector for use with Microsoft Intune, and you manage the challenge passwords using Microsoft Intune. For more information, see [Using Connector for SCEP for Microsoft Intune](#).

Type: [MobileDeviceManagement](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## Tags

The key-value pairs to associate with the resource.

Type: String to string map

Required: No

## VpcEndpointId

If you don't supply a value, by default Connector for SCEP creates a connector accessible over the public internet. If you provide a VPC endpoint ID, creates a connector accessible only through that specific VPC endpoint.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 22.

Pattern: `vpce-[0-9a-f]{8}([0-9a-f]{9})?`

Required: No

## Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "ConnectorArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

### ConnectorArn

Returns the Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: arn:aws(-[a-z]+)\*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d\*:\d{12}:connector\/[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### ConflictException

This request can't be completed for one of the following reasons because the requested resource was being concurrently modified by another request.

#### ResourceId

The identifier of the AWS resource.

#### ResourceType

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 409

### InternalServerError

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### ResourceNotFoundException

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### ResourceId

The identifier of the AWS resource.

**ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

**ServiceQuotaExceededException**

The request would cause a service quota to be exceeded.

**QuotaCode**

The quota identifier.

**ResourceType**

The resource type, which can be either Connector or Challenge.

**ServiceCode**

Identifies the originating service.

HTTP Status Code: 402

**ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

**ValidationException**

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

**Reason**

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteChallenge

Deletes the specified [Challenge](#).

## Request Syntax

```
DELETE /challenges/ChallengeArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### ChallengeArn

The Amazon Resource Name (ARN) of the challenge password to delete.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 202
```

## Response Elements

If the action is successful, the service sends back an HTTP 202 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

## **ConflictException**

This request can't be completed for one of the following reasons because the requested resource was being concurrently modified by another request.

### **ResourceId**

The identifier of the AWS resource.

### **ResourceType**

The resource type, which can be either `Connector` or `Challenge`.

HTTP Status Code: 409

## **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

## **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than `ACTIVE`.

### **ResourceId**

The identifier of the AWS resource.

### **ResourceType**

The resource type, which can be either `Connector` or `Challenge`.

HTTP Status Code: 404

## ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteConnector

Deletes the specified [Connector](#). This operation also deletes any challenges associated with the connector.

## Request Syntax

```
DELETE /connectors/ConnectorArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### ConnectorArn

The Amazon Resource Name (ARN) of the connector to delete.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 202
```

## Response Elements

If the action is successful, the service sends back an HTTP 202 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

## **ConflictException**

This request can't be completed for one of the following reasons because the requested resource was being concurrently modified by another request.

### **ResourceId**

The identifier of the AWS resource.

### **ResourceType**

The resource type, which can be either `Connector` or `Challenge`.

HTTP Status Code: 409

## **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

## **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than `ACTIVE`.

### **ResourceId**

The identifier of the AWS resource.

### **ResourceType**

The resource type, which can be either `Connector` or `Challenge`.

HTTP Status Code: 404

## ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetChallengeMetadata

Retrieves the metadata for the specified [Challenge](#).

## Request Syntax

```
GET /challengeMetadata/ChallengeArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [ChallengeArn](#)

The Amazon Resource Name (ARN) of the challenge.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "ChallengeMetadata": {
    "Arn": "string",
    "ConnectorArn": "string",
    "CreatedAt": number,
    "UpdatedAt": number
  }
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### ChallengeMetadata

The metadata for the challenge.

Type: [ChallengeMetadata](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### **ResourceId**

The identifier of the AWS resource.

## ResourceType

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

## ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# GetChallengePassword

Retrieves the challenge password for the specified [Challenge](#).

## Request Syntax

```
GET /challengePasswords/ChallengeArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [ChallengeArn](#)

The Amazon Resource Name (ARN) of the challenge.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Password": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Password

The SCEP challenge password.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### **ResourceId**

The identifier of the AWS resource.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### **ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetConnector

Retrieves details about the specified [Connector](#). Calling this action returns important details about the connector, such as the public SCEP URL where your clients can request certificates.

## Request Syntax

```
GET /connectors/ConnectorArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [ConnectorArn](#)

The Amazon Resource Name (ARN) of the connector.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f\]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Connector": {
    "Arn": "string",
    "CertificateAuthorityArn": "string",
    "CreatedAt": number,
    "Endpoint": "string",
```

```
"MobileDeviceManagement": { ... },
"OpenIdConfiguration": {
  "Audience": "string",
  "Issuer": "string",
  "Subject": "string"
},
"Status": "string",
"StatusReason": "string",
"Type": "string",
"UpdatedAt": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Connector

The properties of the connector.

Type: [Connector](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### **ResourceId**

The identifier of the AWS resource.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### **ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

### **ValidationException**

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

#### **Reason**

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListChallengeMetadata

Retrieves the challenge metadata for the specified ARN.

## Request Syntax

```
GET /challengeMetadata?  
ConnectorArn=ConnectorArn&MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### ConnectorArn

The Amazon Resource Name (ARN) of the connector.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: Yes

### MaxResults

The maximum number of objects that you want Connector for SCEP to return for this request. If more objects are available, in the response, Connector for SCEP provides a `NextToken` value that you can use in a subsequent call to get the next batch of objects.

Valid Range: Minimum value of 1. Maximum value of 1000.

### NextToken

When you request a list of objects with a `MaxResults` setting, if the number of objects that are still available for retrieval exceeds the maximum you requested, Connector for SCEP returns a `NextToken` value in the response. To retrieve the next batch of objects, use the token returned from the prior request in your next request.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `(?:[A-Za-z0-9_-]{4})*(?:[A-Za-z0-9_-]{2}==|[A-Za-z0-9_-]{3}=)?`

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Challenges": [
    {
      "Arn": "string",
      "ConnectorArn": "string",
      "CreatedAt": number,
      "UpdatedAt": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Challenges

The challenge metadata for the challenges belonging to your AWS account.

Type: Array of [ChallengeMetadataSummary](#) objects

### NextToken

When you request a list of objects with a `MaxResults` setting, if the number of objects that are still available for retrieval exceeds the maximum you requested, Connector for SCEP returns a `NextToken` value in the response. To retrieve the next batch of objects, use the token returned from the prior request in your next request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: (?:[A-Za-z0-9\_-]{4})\*(?:[A-Za-z0-9\_-]{2}=?|[A-Za-z0-9\_-]{3}=)?

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### InternalServerError

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### ResourceNotFoundException

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### ResourceId

The identifier of the AWS resource.

#### ResourceType

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListConnectors

Lists the connectors belonging to your AWS account.

## Request Syntax

```
GET /connectors?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MaxResults

The maximum number of objects that you want Connector for SCEP to return for this request. If more objects are available, in the response, Connector for SCEP provides a `NextToken` value that you can use in a subsequent call to get the next batch of objects.

Valid Range: Minimum value of 1. Maximum value of 1000.

### NextToken

When you request a list of objects with a `MaxResults` setting, if the number of objects that are still available for retrieval exceeds the maximum you requested, Connector for SCEP returns a `NextToken` value in the response. To retrieve the next batch of objects, use the token returned from the prior request in your next request.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `(?:[A-Za-z0-9_-]{4})*(?:[A-Za-z0-9_-]{2}=|[A-Za-z0-9_-]{3}=)?`

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "Connectors": [
    {
      "Arn": "string",
      "CertificateAuthorityArn": "string",
      "CreatedAt": number,
      "Endpoint": "string",
      "MobileDeviceManagement": { ... },
      "OpenIdConfiguration": {
        "Audience": "string",
        "Issuer": "string",
        "Subject": "string"
      },
      "Status": "string",
      "StatusReason": "string",
      "Type": "string",
      "UpdatedAt": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Connectors

The connectors belonging to your AWS account.

Type: Array of [ConnectorSummary](#) objects

### NextToken

When you request a list of objects with a `MaxResults` setting, if the number of objects that are still available for retrieval exceeds the maximum you requested, Connector for SCEP returns a `NextToken` value in the response. To retrieve the next batch of objects, use the token returned from the prior request in your next request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: (? : [A-Za-z0-9\_-]{4})\* (? : [A-Za-z0-9\_-]{2}== | [A-Za-z0-9\_-]{3}=) ?

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### InternalServerError

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

### ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

#### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Retrieves the tags associated with the specified resource. Tags are key-value pairs that you can use to categorize and manage your resources, for purposes like billing. For example, you might set the tag key to "customer" and the value to the customer name or ID. You can specify one or more tags to add to each AWS resource, up to 50 tags for a resource.

## Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [ResourceArn](#)

The Amazon Resource Name (ARN) of the resource.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## Tags

The key-value pairs to associate with the resource.

Type: String to string map

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### **ResourceId**

The identifier of the AWS resource.

#### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### **ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Adds one or more tags to your resource.

## Request Syntax

```
POST /tags/ResourceArn HTTP/1.1  
Content-type: application/json
```

```
{  
  "Tags": {  
    "string" : "string"  
  }  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### Tags

The key-value pairs to associate with the resource.

Type: String to string map

Required: Yes

## Response Syntax

```
HTTP/1.1 204
```

## Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### AccessDeniedException

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

### InternalServerError

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

### ResourceNotFoundException

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

#### ResourceId

The identifier of the AWS resource.

#### ResourceType

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

### ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## ValidationException

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### Reason

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Removes one or more tags from your resource.

## Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Required: Yes

### TagKeys

Specifies a list of tag keys that you want to remove from the specified resources.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 204
```

## Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## **AccessDeniedException**

You can receive this error if you attempt to perform an operation and you don't have the required permissions. This can be caused by insufficient permissions in policies attached to your AWS Identity and Access Management (IAM) principal. It can also happen because of restrictions in place from an AWS Organizations service control policy (SCP) that affects your AWS account.

HTTP Status Code: 403

## **InternalServerError**

The request processing has failed because of an unknown error, exception or failure with an internal server.

HTTP Status Code: 500

## **ResourceNotFoundException**

The operation tried to access a nonexistent resource. The resource might be incorrectly specified, or it might have a status other than ACTIVE.

### **ResourceId**

The identifier of the AWS resource.

### **ResourceType**

The resource type, which can be either Connector or Challenge.

HTTP Status Code: 404

## **ThrottlingException**

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

## **ValidationException**

An input validation error occurred. For example, invalid characters in a name tag, or an invalid pagination token.

### **Reason**

The reason for the validation error, if available. The service doesn't return a reason for every validation exception.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Private CA Connector for SCEP API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Challenge](#)
- [ChallengeMetadata](#)
- [ChallengeMetadataSummary](#)
- [Connector](#)
- [ConnectorSummary](#)
- [IntuneConfiguration](#)
- [MobileDeviceManagement](#)
- [OpenIdConfiguration](#)

# Challenge

For Connector for SCEP for general-purpose. An object containing information about the specified connector's SCEP challenge passwords.

## Contents

### Arn

The Amazon Resource Name (ARN) of the challenge.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### ConnectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CreatedAt

The date and time that the challenge was created.

Type: Timestamp

Required: No

### Password

The SCEP challenge password, in UUID format.

Type: String

Required: No

### **UpdatedAt**

The date and time that the challenge was updated.

Type: Timestamp

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ChallengeMetadata

Contains details about the connector's challenge.

## Contents

### Arn

The Amazon Resource Name (ARN) of the challenge.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### ConnectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CreatedAt

The date and time that the connector was created.

Type: Timestamp

Required: No

### UpdatedAt

The date and time that the connector was updated.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ChallengeMetadataSummary

Details about the specified challenge, returned by the [GetChallengeMetadata](#) action.

## Contents

### Arn

The Amazon Resource Name (ARN) of the challenge.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}\challenge\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### ConnectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CreatedAt

The date and time that the challenge was created.

Type: Timestamp

Required: No

### UpdatedAt

The date and time that the challenge was updated.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Connector

Connector for SCEP is a service that links AWS Private Certificate Authority to your SCEP-enabled devices. The connector brokers the exchange of certificates from AWS Private CA to your SCEP-enabled devices and mobile device management systems. The connector is a complex type that contains the connector's configuration settings.

## Contents

### Arn

The Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CertificateAuthorityArn

The Amazon Resource Name (ARN) of the certificate authority associated with the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:acm-pca:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:certificate-authority\[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CreatedAt

The date and time that the connector was created.

Type: Timestamp

Required: No

## Endpoint

The connector's HTTPS public SCEP URL.

Type: String

Required: No

## MobileDeviceManagement

Contains settings relevant to the mobile device management system that you chose for the connector. If you didn't configure `MobileDeviceManagement`, then the connector is for general-purpose use and this object is empty.

Type: [MobileDeviceManagement](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## OpenIdConfiguration

Contains OpenID Connect (OIDC) parameters for use with Connector for SCEP for Microsoft Intune. For more information about using Connector for SCEP for Microsoft Intune, see [Using Connector for SCEP for Microsoft Intune](#).

Type: [OpenIdConfiguration](#) object

Required: No

## Status

The connector's status.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | FAILED

Required: No

## StatusReason

Information about why connector creation failed, if status is FAILED.

Type: String

Valid Values: INTERNAL\_FAILURE | PRIVATECA\_ACCESS\_DENIED | PRIVATECA\_INVALID\_STATE | PRIVATECA\_RESOURCE\_NOT\_FOUND | VPC\_ENDPOINT\_RESOURCE\_NOT\_FOUND | VPC\_ENDPOINT\_DNS\_ENTRIES\_NOT\_FOUND

Required: No

## Type

The connector type.

Type: String

Valid Values: GENERAL\_PURPOSE | INTUNE

Required: No

## UpdatedAt

The date and time that the connector was updated.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ConnectorSummary

Lists the AWS Private CA SCEP connectors belonging to your AWS account.

## Contents

### Arn

The Amazon Resource Name (ARN) of the connector.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:pca-connector-scep:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:connector\/[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CertificateAuthorityArn

The Amazon Resource Name (ARN) of the connector's associated certificate authority.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `arn:aws(-[a-z]+)*:acm-pca:[a-z]+(-[a-z]+)+-[1-9]\d*:\d{12}:certificate-authority\/[0-9a-f]{8}(-[0-9a-f]{4}){3}-[0-9a-f]{12}`

Required: No

### CreatedAt

The date and time that the challenge was created.

Type: Timestamp

Required: No

### Endpoint

The connector's HTTPS public SCEP URL.

Type: String

Required: No

## MobileDeviceManagement

Contains settings relevant to the mobile device management system that you chose for the connector. If you didn't configure MobileDeviceManagement, then the connector is for general-purpose use and this object is empty.

Type: [MobileDeviceManagement](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## OpenIdConfiguration

Contains OpenID Connect (OIDC) parameters for use with Microsoft Intune.

Type: [OpenIdConfiguration](#) object

Required: No

## Status

The connector's status. Status can be creating, active, deleting, or failed.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | FAILED

Required: No

## StatusReason

Information about why connector creation failed, if status is FAILED.

Type: String

Valid Values: INTERNAL\_FAILURE | PRIVATECA\_ACCESS\_DENIED | PRIVATECA\_INVALID\_STATE | PRIVATECA\_RESOURCE\_NOT\_FOUND | VPC\_ENDPOINT\_RESOURCE\_NOT\_FOUND | VPC\_ENDPOINT\_DNS\_ENTRIES\_NOT\_FOUND

Required: No

## Type

The connector type.

Type: String

Valid Values: GENERAL\_PURPOSE | INTUNE

Required: No

### **UpdatedAt**

The date and time that the challenge was updated.

Type: Timestamp

Required: No

### **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IntuneConfiguration

Contains configuration details for use with Microsoft Intune. For information about using Connector for SCEP for Microsoft Intune, see [Using Connector for SCEP for Microsoft Intune](#).

When you use Connector for SCEP for Microsoft Intune, certain functionalities are enabled by accessing Microsoft Intune through the Microsoft API. Your use of the Connector for SCEP and accompanying AWS services doesn't remove your need to have a valid license for your use of the Microsoft Intune service. You should also review the [Microsoft Intune® App Protection Policies](#).

## Contents

### AzureApplicationId

The directory (tenant) ID from your Microsoft Entra ID app registration.

Type: String

Length Constraints: Minimum length of 15. Maximum length of 100.

Pattern: `[a-zA-Z0-9]{2,15}-[a-zA-Z0-9]{2,15}-[a-zA-Z0-9]{2,15}-[a-zA-Z0-9]{2,15}-[a-zA-Z0-9]{2,15}`

Required: Yes

### Domain

The primary domain from your Microsoft Entra ID app registration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MobileDeviceManagement

If you don't supply a value, by default Connector for SCEP creates a connector for general-purpose use. A general-purpose connector is designed to work with clients or endpoints that support the SCEP protocol, except Connector for SCEP for Microsoft Intune. For information about considerations and limitations with using Connector for SCEP, see [Considerations and Limitations](#).

If you provide an `IntuneConfiguration`, Connector for SCEP creates a connector for use with Microsoft Intune, and you manage the challenge passwords using Microsoft Intune. For more information, see [Using Connector for SCEP for Microsoft Intune](#).

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Intune

Configuration settings for use with Microsoft Intune. For information about using Connector for SCEP for Microsoft Intune, see [Using Connector for SCEP for Microsoft Intune](#).

Type: [IntuneConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OpenIdConfiguration

Contains OpenID Connect (OIDC) parameters for use with Microsoft Intune. For more information about using Connector for SCEP for Microsoft Intune, see [Using Connector for SCEP for Microsoft Intune](#).

## Contents

### Audience

The audience value to copy into your Microsoft Entra app registration's OIDC.

Type: String

Required: No

### Issuer

The issuer value to copy into your Microsoft Entra app registration's OIDC.

Type: String

Required: No

### Subject

The subject value to copy into your Microsoft Entra app registration's OIDC.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

## Required: Conditional

# Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

## **IncompleteSignature**

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

## **InternalFailure**

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

## **MalformedHttpRequestException**

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

**NotAuthorized**

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

**OptInRequired**

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

**RequestAbortedException**

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

**RequestEntityTooLargeException**

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

**RequestTimeoutException**

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

**ServiceUnavailable**

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

**ThrottlingException**

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

**UnknownOperationException**

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

**UnrecognizedClientException**

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

**ValidationError**

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400