



Designing for HA and resiliency in Amazon EKS applications

AWS Prescriptive Guidance



AWS Prescriptive Guidance: Designing for HA and resiliency in Amazon EKS applications

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Introduction	1
HA and resilience design	2
Spread workloads	2
Use pod topology spread constraints	3
Pod affinity and anti-affinity	7
Pod disruption budget	9
Probes and health checks	9
Startup probe	10
Liveness probe	10
Readiness probe	10
Ingress resource and load balancer health checks	11
Container lifecycle hooks	11
Understand pod eviction during zonal disruptions	13
Implementing Amazon EKS zonal shift for improved resilience	14
Understanding the zonal shift mechanism	14
Zonal shift activation methods	15
Prerequisites for effective zonal shift	15
Recommendations for zonal disruption resilience	16
Shift completion and recovery	16
Conclusion	17
Resources	18
Document history	19
Glossary	20
#	20
A	21
B	24
C	26
D	29
E	33
F	35
G	37
H	38
I	39
L	41

M	43
O	47
P	49
Q	52
R	52
S	55
T	59
U	60
V	61
W	61
Z	62

Designing for high availability and resiliency in Amazon EKS applications

Haofei Feng, Frank Fan, and Rus Kalakutskiy, Amazon Web Services (AWS)

October 2025 ([document history](#))

Ensuring high availability (HA) and resiliency in application design is crucial for achieving near-zero recovery point objective (RPO) and recovery time objective (RTO). As organizations increasingly migrate and modernize their applications to Kubernetes environments, the demand for robust and scalable solutions continues to increase. Amazon Elastic Kubernetes Service (Amazon EKS) helps you to efficiently manage containerized applications at scale.

This guide delves into a set of widely recognized recommendations and best practices for designing and managing Amazon EKS microservice applications. Based on extensive experience and real-world deployments, these insights offer valuable guidance for architects and developers. Implement these recommendations for high performance, reliability, and scalability of your Kubernetes-based applications to achieve robust operations.

High availability and resilience design considerations

The shared responsibility model becomes more complex with Kubernetes. Amazon EKS control plane availability and resilience are managed by Amazon Web Services (AWS). Your organization manages the data plane, which can significantly affect the performance and availability of your microservices applications.

When designing a highly available and resilient application on Amazon EKS, consider the following components:

- The microservices application: its pods and containers
- The workload data plane: Ingress Controller, pod, system components such as the [Amazon Virtual Private Cloud \(Amazon VPC\) Container Network Interface \(CNI\)](#), service mesh sidecars, and kube-proxy
- The workload-mangement layer: controllers, admission controllers, network policy engines, and persistent data storage for these components
- The Kubernetes control plane
- Infrastructure: nodes, network, and network appliances

For the first three considerations, which refer to components that run within a Kubernetes cluster, this guide covers the following topics:

- [Spreading workloads across nodes and Availability Zones](#)
- [Protecting critical workloads with a PDB](#)
- [Configuring probes and health checks](#)
- [Configuring container lifecycle hooks](#)
- [Understanding pod eviction during zonal disruptions](#)

Spread workloads across nodes and Availability Zones

Distributing a workload across [failure domains](#) such as Availability Zones and nodes improves component availability and decreases the chances of failure for horizontally scalable applications. The following sections introduce ways to spread workloads across nodes and Availability Zones.

Use pod topology spread constraints

[Kubernetes pod topology spread constraints](#) instruct the Kubernetes scheduler to distribute pods that are managed by ReplicaSet or StatefulSet across different failure domains (Availability Zones, nodes, and types of hardware). When you use pod topology spread constraints, you can do the following:

- Distribute or concentrate pods across different failure domains depending on application requirements. For example, you can distribute pods for resilience, and you can concentrate pods for network performance.
- Combine different conditions, such as distributing across Availability Zones and distributing across nodes.
- Specify the preferred action if conditions can't be met:
 - Use `whenUnsatisfiable: DoNotSchedule` with a combination of `maxSkew` and `minDomains` to create hard requirements for the scheduler.
 - Use `whenUnsatisfiable: ScheduleAnyway` to reduce `maxSkew`.

If a failure zone becomes unavailable, the pods in that zone become unhealthy. Kubernetes reschedules the pods while adhering to the spread constraint if possible.

The following code shows an example of using pod topology spread constraints across Availability Zones or across nodes:

```
...
spec:
  selector:
    matchLabels:
      app: <your-app-label>
  replicas: 3
  template:
    metadata:
      labels: <your-app-label>
    spec:
      serviceAccountName: <ServiceAccountName>
...
  topologySpreadConstraints:
  - labelSelector:
      matchLabels:
        app: <your-app-label>
```

```
    maxSkew: 1
    topologyKey: topology.kubernetes.io/zone # <---spread those pods evenly over
all availability zones
    whenUnsatisfiable: ScheduleAnyway
  - labelSelector:
    matchLabels:
      app: <your-app-label>
    maxSkew: 1
    topologyKey: kubernetes.io/hostname # <---spread those pods evenly over all
nodes
    whenUnsatisfiable: ScheduleAnyway
```

Default cluster-wide topology spread constraints

By default, Kubernetes provides a [set of topology spread constraints](#) for distributing pods across nodes and Availability Zones:

```
defaultConstraints:
  - maxSkew: 3
    topologyKey: "kubernetes.io/hostname"
    whenUnsatisfiable: ScheduleAnyway
  - maxSkew: 5
    topologyKey: "topology.kubernetes.io/zone"
    whenUnsatisfiable: ScheduleAnyway
```

Note

Applications that need different types of topology constraints can override the cluster-level policy.

The default constraints set a high `maxSkew`, which isn't useful for deployments that have a small number of pods. As of now, `KubeSchedulerConfiguration` [can't be changed](#) in Amazon EKS. If you need to enforce other sets of topology spread constraints, consider using mutating admission controller like in the section below. You can also control default topology spread constraints if you run an alternative scheduler. However, managing custom schedulers adds complexity and can have implications on cluster resilience and HA. For these reasons, we don't recommend using an alternative scheduler for topology spread constraints only.

The Gatekeeper policy for topology spread constraints

Another option for enforcing topology spread constraints is to use a policy from the [Gatekeeper](#) project. Gatekeeper policies are defined at the application level.

The following code examples show the use of a Gatekeeper OPA policy for deployment. You can modify the policy for your needs. For example, apply the policy only to deployments that have the label `HA=true`, or write a similar policy using a different policy controller.

This first example shows `ConstraintTemplate` used with `k8stopologyspreadrequired_template.yml`:

```
apiVersion: templates.gatekeeper.sh/v1
kind: ConstraintTemplate
metadata:
  name: k8stopologyspreadrequired
spec:
  crd:
    spec:
      names:
        kind: K8sTopologySpreadRequired
      validation:
        openAPIV3Schema:
          type: object
          properties:
            message:
              type: string
  targets:
    - target: admission.k8s.gatekeeper.sh
      rego: |
        package k8stopologyspreadrequired

        get_message(parameters, _default) =3D msg {
          not parameters.message
          msg :=_default
        }

        get_message(parameters, _default) =3D msg {
          msg := parameters.message
        }

        violation[{"msg": msg}] {
```

```
input.review.kind.kind = "Deployment"
not input.review.object.spec.template.spec.topologySpreadConstraint
def_msg : "Pod Topology Spread Constraints are required for Deployments"
msg : get_message(input.parameters, def_msg)

}
```

The following code shows the constraints YAML manifest `k8stopologyspreadrequired_constraint.yml`:

```
apiVersion: constraints.gatekeeper.sh/v1beta1
kind: K8sTopologySpreadRequired
metadata:
  name: require-topologyspread-for-deployments
spec:
  match:
    kinds:
      - apiGroups: ["apps"]
        kinds: ["Deployment"]
    namespaces: ## Without theses two lines will apply to the whole cluster
      - "example"
```

When to use topology spread constraints

Consider using topology spread constraints for the following scenarios:

- Any horizontally scalable application (for example, stateless web services)
- Applications with active-active or active-passive replicas (for example, NoSQL databases or caches)
- Applications with stand-by replicas (for example, controllers)

System components that can be used for the horizontally scalable scenario, for example, include the following:

- [Cluster Autoscaler](#) and [Karpenter](#) (with `replicaCount > 1` and `leader-elect = true`)
- [AWS Load Balancer Controller](#)
- [CoreDNS](#)

Pod affinity and anti-affinity

In some cases, it's beneficial to ensure that no more than one pod of a specific type is running on a node. For example, to avoid scheduling multiple network-heavy pods on the same node, you can use the anti-affinity rule with the label `Ingress` or `Network-heavy`. When you use anti-affinity, you can also use a combination of the following:

- Taints on network-optimized nodes
- Corresponding tolerations on network-heavy pods
- Node affinity or node selector to ensure that network-heavy pods use network-optimized instances

Network-heavy pods are used as an example. You might have different requirements, such as GPU, memory, or local storage. For other usage examples and configuration options, see the [Kubernetes documentation](#).

Rebalance pods

This section discusses two approaches to rebalancing pods in a Kubernetes cluster. The first uses the Descheduler for Kubernetes. The Descheduler helps to maintain pod distribution by enforcing strategies to remove pods that violate topology spread constraints or anti-affinity rules. The second approach uses the Karpenter consolidation and bin-packing feature. Consolidation continuously evaluates and optimizes resource usage by consolidating workloads onto fewer, more efficiently packed nodes.

We recommend using Descheduler if you aren't using Karpenter. If you're using Karpenter and Cluster Autoscaler together, you can use Descheduler with Cluster Autoscaler for node groups.

Descheduler for groupless nodes

There's no guarantee that the topology constraints remain satisfied when pods are removed. For example, scaling down a deployment might result in imbalanced pod distribution. However, because Kubernetes uses pod topology spread constraints only at the scheduling stage, pods are left unbalanced across the failure domain.

To maintain a balanced pod distribution in such scenarios, you can use [Descheduler for Kubernetes](#). Descheduler is a useful tool for multiple purposes, such as to enforce the maximum pod age or time to live (TTL), or to improve the use of infrastructure. In the context of resilience and high availability (HA), consider the following Descheduler strategies:

- [RemovePodsViolatingTopologySpreadConstraint](#)
- [RemovePodsViolatingInterPodAntiAffinity](#)
- [RemoveDuplicates](#)

Karpenter consolidation and bin-packing feature

For workloads that use Karpenter, you can use the consolidation and bin-packing functionality to optimize resource utilization and reduce costs in Kubernetes clusters. Karpenter continuously evaluates pod placements and node utilization, and it attempts to consolidate workloads onto fewer, more efficiently packed nodes when possible. This process involves analyzing resource requirements, considering constraints such as pod affinity rules, and potentially moving pods between nodes to improve overall cluster efficiency. The following code provides an example:

```
apiVersion: karpenter.sh/v1beta1
kind: NodePool
metadata:
  name: default
spec:
  disruption:
    consolidationPolicy: WhenUnderutilized
    expireAfter: 720h
```

For `consolidationPolicy`, you can use `WhenUnderutilized` or `WhenEmpty`:

- When `consolidationPolicy` is set to `WhenUnderutilized`, Karpenter considers all nodes for consolidation. When Karpenter discovers a node that's empty or underused, Karpenter attempts to remove or replace the node to reduce cost.
- When `consolidationPolicy` is set to `WhenEmpty`, Karpenter considers for consolidation only nodes that contain no workload pods.

The Karpenter consolidation decisions are not based solely on CPU or memory utilization percentages that you might see in monitoring tools. Instead, Karpenter uses a more complex algorithm based on pod resource requests and potential cost optimizations. For more information, see the [Karpenter documentation](#).

Protect critical workloads with a PDB

A pod disruption budget (PDB) is an essential feature for maintaining the high availability of applications in a cluster. The PDB specifies a target size, which is the minimum availability for a particular type of pod. This means that a minimum number of replicas of a particular pod type must be running at any given time. If the number of running replicas falls below the target size, Kubernetes prevents further disruptions to the remaining replicas until the target size is met. PDBs help to ensure that workloads are not affected by these events and can continue to run uninterrupted. When a disruption occurs, Kubernetes attempts to gracefully evict pods from the affected nodes while maintaining the number of replicas specified in the PDB.

You can use a PDB to declare the `minAvailable` and `maxUnavailable` number of replicas. For example, if you want at least three copies of your app to be available, create a PDB that is similar to the following example:

```
apiVersion: policy/v1beta1
kind: PodDisruptionBudget
metadata:
  name: my-svc-pdb
spec:
  minAvailable: 3
  selector:
    matchLabels:
      app: my-svc
```

Setting up PDBs correctly for your applications helps to minimize the disruption during planned or unplanned events. You can use the anti-affinity rule to schedule a deployment's pods on different nodes and avoid PDB delays during node upgrades.

Configure probes and load balancer health checks

Kubernetes provides several ways to perform application health checks in addition to load balancer health checks. You can run the following Kubernetes built-in probes together with the load balancer health check as a command in the pod's context or as an HTTP/TCP probe to kubelet or the host IP address.

Liveness probes and readiness probes should be different and independent (or at least with different timeout values). If an application has a temporary issue, the readiness probe will mark the

pod as unready until the issue is resolved. If the liveness probe settings aren't correct, the liveness probe might terminate the pod.

Startup probe

Use startup probes to protect applications that have long initialization cycles. Until the startup probe succeeds, the other probes are disabled.

You can define a maximum time that Kubernetes should wait for application startup. If, after the maximum configured time, the pod still fails the startup probes, the application is terminated, and a new pod is created.

Use startup probes when the startup time of an application is unpredictable. If you know that your application needs 10 seconds to start, use a liveness probe or a readiness probe with `initialDelaySeconds` instead.

Liveness probe

Use liveness probes to detect application issues or whether the process is running without issues. A liveness probe can detect deadlock conditions where the process continues to run but the application becomes unresponsive. When using a liveness probe, do the following:

- Use `initialDelaySeconds` to delay the first probe.
- Don't set the same specification for liveness and readiness probes.
- Don't configure a liveness probe to depend on a factor that is external to your pod (for example, a database).
- Set the liveness probe for a specific `terminationGracePeriodSeconds`. For more information, see the [Kubernetes documentation](#).

Readiness probe

Use a readiness probe to detect the following:

- Whether the application is ready to accept traffic
- Partial availability, where the application might be temporarily unavailable but is expected to be healthy again after a certain operation completes

Readiness probes help to ensure that the application configuration and dependencies are running without issues or errors, so that the application can serve traffic. However, a poorly configured readiness probe can cause an outage instead of preventing it. Readiness probes that depend on external factors, such as connectivity to a database, can cause all pods to fail the probe. Such failures can result in an outage, and they can lead to a cascading failure from a backend service to other services that used the failed pods.

Ingress resource and load balancer health checks

Application Load Balancer and Kubernetes `ingress` provide health-check features. For the Application Load Balancer health checks, specify the target ports and path.

Note

For the Kubernetes `ingress`, there will be a deregistration latency. The default for Application Load Balancer is 300 seconds. Consider setting up your ingress resource or load balancer health check by using the same values that you used for your readiness probe.

NGINX also provides a health check. For more information, see the [NGINX documentation](#).

Istio ingress and egress gateways don't have a health check mechanism that's comparable to the HTTP health check from NGINX. However, you can achieve similar functionality by using the [Istio circuit breaker](#) or `DestinationRule` outlier detection.

For more information, see [Availability and Pod Lifecycle](#) in the *Amazon EKS Best Practices Guide*.

Configure container lifecycle hooks

During a graceful container shutdown, your application should respond to a `SIGTERM` signal by starting its shutdown so that clients don't experience any downtime. Your application should run cleanup procedures such as the following:

- Saving data
- Closing file descriptors
- Closing database connections
- Completing in-flight requests gracefully
- Exiting in a timely manner to fulfill the pod termination request

Set a grace period that is long enough for cleanup to finish. To learn how to respond to the SIGTERM signal, see the documentation for the programming language that you use for your application.

[Container lifecycle hooks](#) enable containers to be aware of events in their management lifecycle. Containers can run code implemented in a handler when the corresponding lifecycle hook is executed. Container lifecycle hooks provide a workaround for the asynchronous nature of Kubernetes and the cloud. This approach can prevent the loss of connections that are forwarded to the terminating pod before the ingress resource and iptables are updated to not send new traffic to the pod.

Container lifecycle, Endpoint, and EndpointSlice are part of different APIs. It's important to orchestrate these APIs. However, when a pod is being terminated, the Kubernetes API simultaneously notifies both the kubelet (for container lifecycle) and the EndpointSlice controller. For more information, including a diagram, see [Gracefully handle the client requests](#) in the *Amazon EKS Best Practices Guide*.

When kubelet sends SIGTERM to the pod, the EndpointSlice controller is terminating the EndpointSlice object. That termination notifies the Kubernetes API servers to notify the kube-proxy of each node to update iptables. Although these actions occur at the same time, there are no dependencies or sequences between them. There is a high chance that the container receives the SIGKILL signal much earlier than the kube-proxy on each node updates the local iptables rules. In that case, possible scenarios include the following:

- If your application immediately and bluntly drops the in-flight requests and connections upon receipt of SIGTERM, the clients see 500 errors.
- If your application ensures that all in-flight requests and connections are processed completely upon receipt of SIGTERM, during the grace period, new client requests would still be sent to the application container because iptables rules might not be updated yet. Until the cleanup procedure closes the server socket on the container, those new requests will result in new connections. When the grace period ends, the new connections that were established after the SIGTERM was sent are dropped unconditionally.

To address the previous scenarios, you can implement in-app integration or the PreStop lifecycle hook. For more information, including a diagram, see [Gracefully shutdown applications](#) in the *Amazon EKS Best Practices Guide*.

Note

Regardless of whether the application shuts down gracefully, or the result of the `preStop` hook, the application containers are eventually terminated at the end of the grace period through SIGKILL.

Use the `preStop` hook with a `sleep` command to delay sending SIGTERM. This will help to continue accepting the new connections while the ingress object routes them to the pod. Test the time value of the `sleep` command to ensure that any latency of Kubernetes and other application dependencies are taken into account, as shown in the following example:

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: nginx
spec:
  containers:
    - name: nginx
      lifecycle:
        # This "sleep" preStop hook delays the Pod shutdown until
        # after the Ingress Controller removes the matching Endpoint or EndpointSlice
        preStop:
          exec:
            command:
              - /bin/sleep
              - "20"
            # This period should be turned to Ingress/Service Mesh update latency
```

For more information, see [Container hooks](#) in the Kubernetes documentation and [Gracefully shutdown applications](#) in the *Amazon EKS Best Practices Guide*.

Understand pod eviction during zonal disruptions

When a full Availability Zone disruption occurs—that is, when all nodes in that Availability Zone lose connectivity to the Kubernetes control plane—the [node lifecycle controller](#) in Kubernetes detects the situation and evicts pods from the impacted zone. Pods on unreachable nodes are marked as `Terminating` and new pods are scheduled on healthy nodes in available Availability Zones. During this period, affected nodes display a `NotReady` status, the scheduler prevents new

Pods from being placed on those nodes, and the EndpointSlice controller removes endpoints that are associated with the impaired Availability Zone from service routing until connectivity is restored.

For scenarios that involve partial node failures within a zone—where only a subset of nodes becomes unreachable—the node lifecycle controller applies different eviction behavior. If the disruption persists beyond the configured toleration period (by default, five minutes), pods on disconnected nodes are marked as `Terminating` and new pods are scheduled on healthy nodes in available Availability Zones.

Implementing Amazon EKS zonal shift for improved resilience

[Amazon EKS zonal shift](#), which integrates with Amazon Application Recovery Controller (ARC), provides a mechanism to proactively manage traffic during Availability Zone impairments. This capability allows temporary redirection of network traffic away from an unhealthy Availability Zone toward healthy zones within the same AWS Region to minimize service disruption.

Understanding the zonal shift mechanism

Amazon EKS zonal shift addresses east-west traffic (inter-pod communication within the cluster). When zonal shift is configured with Application Load Balancers or Network Load Balancers, it also supports ingress traffic routing. The mechanism operates by coordinating multiple Kubernetes and AWS control plane components to safely redirect traffic without disrupting running workloads. During an active zonal shift, Amazon EKS automatically performs the following coordinated actions:

- **Node cordoning:** All nodes in the impaired Availability Zone are cordoned. This prevents the Kubernetes scheduler from placing new pods on the nodes while it maintains existing workloads.
- **Availability Zone rebalancing suspension:** For managed node groups, Availability Zone rebalancing operations are suspended, and Auto Scaling groups are updated to launch new data plane nodes exclusively in healthy Availability Zones. This ensures that new capacity isn't provisioned in the impaired zone.
- **Endpoint removal:** The EndpointSlice controller removes pod endpoints in the impaired Availability Zone from all relevant EndpointSlices. This ensures that service discovery and load balancing mechanisms route traffic only to pods that are running in healthy Availability Zones.
- **Workload preservation:** Amazon EKS refrains from terminating nodes or evicting pods in the affected Availability Zone. It maintains full capacity in the impaired zone so that when the

zonal shift expires or is canceled, traffic can safely return without requiring additional scaling operations.

Zonal shift activation methods

You can choose from two approaches to initiate zonal shifts, depending on your operational model:

- [Manual zonal shift](#) provides operator-driven control when specific Availability Zone issues are detected through monitoring, alerts, or customer reports. This method requires explicit action through the ARC console, AWS Command Line Interface (AWS CLI), or zonal shift APIs, where operators specify the impaired Availability Zone and define an expiration time for the shift. Manual shifts are appropriate when teams have dedicated monitoring and on-call capabilities and prefer to maintain direct control over traffic management decisions.
- [Zonal autoshift](#) authorizes AWS to automatically initiate shifts when ARC detects potential Availability Zone failures or impairments based on internal telemetry and health signals across multiple AWS services, including network metrics, Amazon Elastic Compute Cloud (Amazon EC2), and Elastic Load Balancing. AWS automatically ends an autoshift when indicators show that the issue has been resolved. If you want the highest availability posture with minimal manual intervention, we recommend this approach, because it enables sub-minute response to detected Availability Zone impairments.

Prerequisites for effective zonal shift

For zonal shift to successfully protect applications during Availability Zone impairments, you must architect your clusters for Multi-AZ resiliency before you enable the zonal shift feature:

- **Multi-AZ node distribution:** Provision worker nodes across at least three Availability Zones to ensure sufficient redundancy when one zone becomes unavailable.
- **Capacity planning:** Pre-provision enough compute capacity across healthy Availability Zones to accommodate the full workload when one Availability Zone is removed from service, because scaling operations during an active disruption might encounter insufficient capacity.
- **Pod distribution and pre-scaling:** Deploy multiple replicas of each application across all Availability Zones and pre-scale critical system components such as [CoreDNS](#) in every zone. This helps ensure that sufficient capacity remains after a zone is shifted away.

Recommendations for zonal disruption resilience

- **Enable zonal shift at cluster creation:** For new EKS clusters, enable zonal shift integration with ARC during initial provisioning through the Amazon EKS console, AWS CLI, or infrastructure as code (IaC) tools such as AWS CloudFormation. [EKS Auto Mode clusters](#) that are created with quick configuration have zonal shift enabled by default.
- **Select the appropriate activation method:** Choose zonal autoshift for production environments that require maximum availability with automated response, particularly for customer-facing applications where minutes of downtime during an Availability Zone impairment can carry significant business impact. Use manual zonal shift for environments where operations teams prefer to provide explicit approval before traffic shifts, or where application testing and validation are still in progress.
- **Test resilience before production deployment:** Validate cluster behavior under Single-AZ loss by manually initiating test zonal shifts or enabling zonal autoshift practice runs to verify that applications maintain availability, performance remains acceptable, and capacity is sufficient when operating with reduced Availability Zone count. We strongly recommend this testing so you can identify configuration gaps before actual Availability Zone impairments occur.
- **Coordinate with load balancer configuration:** For applications that receive external traffic, enable ARC zonal shift on associated Application Load Balancers and Network Load Balancers to ensure that both ingress traffic and in-cluster east-west traffic shift together during Availability Zone impairments. This coordination prevents scenarios where external requests reach healthy pods but those pods cannot communicate with dependencies in the shifted-away zone.
- **Monitor shift operations:** After you enable zonal shift, configure monitoring and alerting for shift events, including autoshift activations, manual shift initiations, and shift expirations, to maintain operational visibility into traffic management actions and their impact on application behavior.

Shift completion and recovery

When a zonal shift expires based on its configured duration or is manually canceled after the Availability Zone impairment resolves, the EndpointSlice controller automatically updates all EndpointSlices to reincorporate endpoints in the restored Availability Zone. Traffic gradually returns to the previously impacted zone as clients refresh endpoint information and establish new connections. This enables full cluster capacity utilization without requiring manual intervention or pod rescheduling.

Conclusion

When you design your architecture for high application availability and resiliency, consider the following components:

- The microservices application (its pods and containers)
- The workload data plane (Ingress Controller, pod, system components such as the [Amazon VPC CNI](#), service mesh sidecars, and kube-proxy)
- The workload-management layer (controllers, admission controllers, network policy engines, and persistent data storage for these components)
- The Kubernetes control plane
- Infrastructure (nodes, network, and network appliances)

To address those component considerations, use the following key strategies:

- To help ensure high availability and fault tolerance, spread workloads across nodes and Availability Zones.
- To protect critical workloads, maintain application stability during disruptions by using pod disruption budgets (PDBs).
- To help ensure that pods are running and serving traffic correctly, configure startup probes, liveness probes, readiness probes, and load balancer health checks.
- To manage container state transitions efficiently, configure container lifecycle hooks.
- To provide control over the eviction process during node failures or maintenance, configure the pod eviction time.

By implementing these practices, you can significantly enhance the reliability and resilience of applications running on Amazon EKS, ensuring robust performance and high availability.

Resources

- [Kubernetes Pod Topology Spread Constraints](#) (Kubernetes documentation)
- [Karpenter FAQs](#) (Karpenter documentation)
- [Descheduler for Kubernetes](#) (GitHub repository)
- [Availability and Pod Lifecycle](#) *Amazon EKS Best Practices Guide*
- [Gracefully shutdown applications](#) *Amazon EKS Best Practices Guide*
- [\[EKS\] \[request\]: Ability to configure pod-eviction-timeout and workarounds](#) (Containers Roadmap repository)

Document history

The following table describes significant changes to this guide. If you want to be notified about future updates, you can subscribe to an [RSS feed](#).

Change	Description	Date
Update	Revised the section about pod evictions during zonal disruptions .	October 29, 2025
Update	Revised the Use pod topology spread constraints section.	January 27, 2025
Initial publication	—	October 23, 2024

AWS Prescriptive Guidance glossary

The following are commonly used terms in strategies, guides, and patterns provided by AWS Prescriptive Guidance. To suggest entries, please use the **Provide feedback** link at the end of the glossary.

Numbers

7 Rs

Seven common migration strategies for moving applications to the cloud. These strategies build upon the 5 Rs that Gartner identified in 2011 and consist of the following:

- Refactor/re-architect – Move an application and modify its architecture by taking full advantage of cloud-native features to improve agility, performance, and scalability. This typically involves porting the operating system and database. Example: Migrate your on-premises Oracle database to the Amazon Aurora PostgreSQL-Compatible Edition.
- Replatform (lift and reshape) – Move an application to the cloud, and introduce some level of optimization to take advantage of cloud capabilities. Example: Migrate your on-premises Oracle database to Amazon Relational Database Service (Amazon RDS) for Oracle in the AWS Cloud.
- Repurchase (drop and shop) – Switch to a different product, typically by moving from a traditional license to a SaaS model. Example: Migrate your customer relationship management (CRM) system to Salesforce.com.
- Rehost (lift and shift) – Move an application to the cloud without making any changes to take advantage of cloud capabilities. Example: Migrate your on-premises Oracle database to Oracle on an EC2 instance in the AWS Cloud.
- Relocate (hypervisor-level lift and shift) – Move infrastructure to the cloud without purchasing new hardware, rewriting applications, or modifying your existing operations. You migrate servers from an on-premises platform to a cloud service for the same platform. Example: Migrate a Microsoft Hyper-V application to AWS.
- Retain (revisit) – Keep applications in your source environment. These might include applications that require major refactoring, and you want to postpone that work until a later time, and legacy applications that you want to retain, because there's no business justification for migrating them.

- Retire – Decommission or remove applications that are no longer needed in your source environment.

A

ABAC

See [attribute-based access control](#).

abstracted services

See [managed services](#).

ACID

See [atomicity, consistency, isolation, durability](#).

active-active migration

A database migration method in which the source and target databases are kept in sync (by using a bidirectional replication tool or dual write operations), and both databases handle transactions from connecting applications during migration. This method supports migration in small, controlled batches instead of requiring a one-time cutover. It's more flexible but requires more work than [active-passive migration](#).

active-passive migration

A database migration method in which the source and target databases are kept in sync, but only the source database handles transactions from connecting applications while data is replicated to the target database. The target database doesn't accept any transactions during migration.

aggregate function

A SQL function that operates on a group of rows and calculates a single return value for the group. Examples of aggregate functions include SUM and MAX.

AI

See [artificial intelligence](#).

AIOps

See [artificial intelligence operations](#).

anonymization

The process of permanently deleting personal information in a dataset. Anonymization can help protect personal privacy. Anonymized data is no longer considered to be personal data.

anti-pattern

A frequently used solution for a recurring issue where the solution is counter-productive, ineffective, or less effective than an alternative.

application control

A security approach that allows the use of only approved applications in order to help protect a system from malware.

application portfolio

A collection of detailed information about each application used by an organization, including the cost to build and maintain the application, and its business value. This information is key to [the portfolio discovery and analysis process](#) and helps identify and prioritize the applications to be migrated, modernized, and optimized.

artificial intelligence (AI)

The field of computer science that is dedicated to using computing technologies to perform cognitive functions that are typically associated with humans, such as learning, solving problems, and recognizing patterns. For more information, see [What is Artificial Intelligence?](#)

artificial intelligence operations (AIOps)

The process of using machine learning techniques to solve operational problems, reduce operational incidents and human intervention, and increase service quality. For more information about how AIOps is used in the AWS migration strategy, see the [operations integration guide](#).

asymmetric encryption

An encryption algorithm that uses a pair of keys, a public key for encryption and a private key for decryption. You can share the public key because it isn't used for decryption, but access to the private key should be highly restricted.

atomicity, consistency, isolation, durability (ACID)

A set of software properties that guarantee the data validity and operational reliability of a database, even in the case of errors, power failures, or other problems.

attribute-based access control (ABAC)

The practice of creating fine-grained permissions based on user attributes, such as department, job role, and team name. For more information, see [ABAC for AWS](#) in the AWS Identity and Access Management (IAM) documentation.

authoritative data source

A location where you store the primary version of data, which is considered to be the most reliable source of information. You can copy data from the authoritative data source to other locations for the purposes of processing or modifying the data, such as anonymizing, redacting, or pseudonymizing it.

Availability Zone

A distinct location within an AWS Region that is insulated from failures in other Availability Zones and provides inexpensive, low-latency network connectivity to other Availability Zones in the same Region.

AWS Cloud Adoption Framework (AWS CAF)

A framework of guidelines and best practices from AWS to help organizations develop an efficient and effective plan to move successfully to the cloud. AWS CAF organizes guidance into six focus areas called perspectives: business, people, governance, platform, security, and operations. The business, people, and governance perspectives focus on business skills and processes; the platform, security, and operations perspectives focus on technical skills and processes. For example, the people perspective targets stakeholders who handle human resources (HR), staffing functions, and people management. For this perspective, AWS CAF provides guidance for people development, training, and communications to help ready the organization for successful cloud adoption. For more information, see the [AWS CAF website](#) and the [AWS CAF whitepaper](#).

AWS Workload Qualification Framework (AWS WQF)

A tool that evaluates database migration workloads, recommends migration strategies, and provides work estimates. AWS WQF is included with AWS Schema Conversion Tool (AWS SCT). It analyzes database schemas and code objects, application code, dependencies, and performance characteristics, and provides assessment reports.

B

bad bot

A [bot](#) that is intended to disrupt or cause harm to individuals or organizations.

BCP

See [business continuity planning](#).

behavior graph

A unified, interactive view of resource behavior and interactions over time. You can use a behavior graph with Amazon Detective to examine failed logon attempts, suspicious API calls, and similar actions. For more information, see [Data in a behavior graph](#) in the Detective documentation.

big-endian system

A system that stores the most significant byte first. See also [endianness](#).

binary classification

A process that predicts a binary outcome (one of two possible classes). For example, your ML model might need to predict problems such as "Is this email spam or not spam?" or "Is this product a book or a car?"

bloom filter

A probabilistic, memory-efficient data structure that is used to test whether an element is a member of a set.

blue/green deployment

A deployment strategy where you create two separate but identical environments. You run the current application version in one environment (blue) and the new application version in the other environment (green). This strategy helps you quickly roll back with minimal impact.

bot

A software application that runs automated tasks over the internet and simulates human activity or interaction. Some bots are useful or beneficial, such as web crawlers that index information on the internet. Some other bots, known as *bad bots*, are intended to disrupt or cause harm to individuals or organizations.

botnet

Networks of [bots](#) that are infected by [malware](#) and are under the control of a single party, known as a *bot herder* or *bot operator*. Botnets are the best-known mechanism to scale bots and their impact.

branch

A contained area of a code repository. The first branch created in a repository is the *main branch*. You can create a new branch from an existing branch, and you can then develop features or fix bugs in the new branch. A branch you create to build a feature is commonly referred to as a *feature branch*. When the feature is ready for release, you merge the feature branch back into the main branch. For more information, see [About branches](#) (GitHub documentation).

break-glass access

In exceptional circumstances and through an approved process, a quick means for a user to gain access to an AWS account that they don't typically have permissions to access. For more information, see the [Implement break-glass procedures](#) indicator in the AWS Well-Architected guidance.

brownfield strategy

The existing infrastructure in your environment. When adopting a brownfield strategy for a system architecture, you design the architecture around the constraints of the current systems and infrastructure. If you are expanding the existing infrastructure, you might blend brownfield and [greenfield](#) strategies.

buffer cache

The memory area where the most frequently accessed data is stored.

business capability

What a business does to generate value (for example, sales, customer service, or marketing). Microservices architectures and development decisions can be driven by business capabilities. For more information, see the [Organized around business capabilities](#) section of the [Running containerized microservices on AWS](#) whitepaper.

business continuity planning (BCP)

A plan that addresses the potential impact of a disruptive event, such as a large-scale migration, on operations and enables a business to resume operations quickly.

C

CAF

See [AWS Cloud Adoption Framework](#).

canary deployment

The slow and incremental release of a version to end users. When you are confident, you deploy the new version and replace the current version in its entirety.

CCoE

See [Cloud Center of Excellence](#).

CDC

See [change data capture](#).

change data capture (CDC)

The process of tracking changes to a data source, such as a database table, and recording metadata about the change. You can use CDC for various purposes, such as auditing or replicating changes in a target system to maintain synchronization.

chaos engineering

Intentionally introducing failures or disruptive events to test a system's resilience. You can use [AWS Fault Injection Service \(AWS FIS\)](#) to perform experiments that stress your AWS workloads and evaluate their response.

CI/CD

See [continuous integration and continuous delivery](#).

classification

A categorization process that helps generate predictions. ML models for classification problems predict a discrete value. Discrete values are always distinct from one another. For example, a model might need to evaluate whether or not there is a car in an image.

client-side encryption

Encryption of data locally, before the target AWS service receives it.

Cloud Center of Excellence (CCoE)

A multi-disciplinary team that drives cloud adoption efforts across an organization, including developing cloud best practices, mobilizing resources, establishing migration timelines, and leading the organization through large-scale transformations. For more information, see the [CCoE posts](#) on the AWS Cloud Enterprise Strategy Blog.

cloud computing

The cloud technology that is typically used for remote data storage and IoT device management. Cloud computing is commonly connected to [edge computing](#) technology.

cloud operating model

In an IT organization, the operating model that is used to build, mature, and optimize one or more cloud environments. For more information, see [Building your Cloud Operating Model](#).

cloud stages of adoption

The four phases that organizations typically go through when they migrate to the AWS Cloud:

- Project – Running a few cloud-related projects for proof of concept and learning purposes
- Foundation – Making foundational investments to scale your cloud adoption (e.g., creating a landing zone, defining a CCoE, establishing an operations model)
- Migration – Migrating individual applications
- Re-invention – Optimizing products and services, and innovating in the cloud

These stages were defined by Stephen Orban in the blog post [The Journey Toward Cloud-First & the Stages of Adoption](#) on the AWS Cloud Enterprise Strategy blog. For information about how they relate to the AWS migration strategy, see the [migration readiness guide](#).

CMDB

See [configuration management database](#).

code repository

A location where source code and other assets, such as documentation, samples, and scripts, are stored and updated through version control processes. Common cloud repositories include GitHub or Bitbucket Cloud. Each version of the code is called a *branch*. In a microservice structure, each repository is devoted to a single piece of functionality. A single CI/CD pipeline can use multiple repositories.

cold cache

A buffer cache that is empty, not well populated, or contains stale or irrelevant data. This affects performance because the database instance must read from the main memory or disk, which is slower than reading from the buffer cache.

cold data

Data that is rarely accessed and is typically historical. When querying this kind of data, slow queries are typically acceptable. Moving this data to lower-performing and less expensive storage tiers or classes can reduce costs.

computer vision (CV)

A field of [AI](#) that uses machine learning to analyze and extract information from visual formats such as digital images and videos. For example, Amazon SageMaker AI provides image processing algorithms for CV.

configuration drift

For a workload, a configuration change from the expected state. It might cause the workload to become noncompliant, and it's typically gradual and unintentional.

configuration management database (CMDB)

A repository that stores and manages information about a database and its IT environment, including both hardware and software components and their configurations. You typically use data from a CMDB in the portfolio discovery and analysis stage of migration.

conformance pack

A collection of AWS Config rules and remediation actions that you can assemble to customize your compliance and security checks. You can deploy a conformance pack as a single entity in an AWS account and Region, or across an organization, by using a YAML template. For more information, see [Conformance packs](#) in the AWS Config documentation.

continuous integration and continuous delivery (CI/CD)

The process of automating the source, build, test, staging, and production stages of the software release process. CI/CD is commonly described as a pipeline. CI/CD can help you automate processes, improve productivity, improve code quality, and deliver faster. For more information, see [Benefits of continuous delivery](#). CD can also stand for *continuous deployment*. For more information, see [Continuous Delivery vs. Continuous Deployment](#).

CV

See [computer vision](#).

D

data at rest

Data that is stationary in your network, such as data that is in storage.

data classification

A process for identifying and categorizing the data in your network based on its criticality and sensitivity. It is a critical component of any cybersecurity risk management strategy because it helps you determine the appropriate protection and retention controls for the data. Data classification is a component of the security pillar in the AWS Well-Architected Framework. For more information, see [Data classification](#).

data drift

A meaningful variation between the production data and the data that was used to train an ML model, or a meaningful change in the input data over time. Data drift can reduce the overall quality, accuracy, and fairness in ML model predictions.

data in transit

Data that is actively moving through your network, such as between network resources.

data mesh

An architectural framework that provides distributed, decentralized data ownership with centralized management and governance.

data minimization

The principle of collecting and processing only the data that is strictly necessary. Practicing data minimization in the AWS Cloud can reduce privacy risks, costs, and your analytics carbon footprint.

data perimeter

A set of preventive guardrails in your AWS environment that help make sure that only trusted identities are accessing trusted resources from expected networks. For more information, see [Building a data perimeter on AWS](#).

data preprocessing

To transform raw data into a format that is easily parsed by your ML model. Preprocessing data can mean removing certain columns or rows and addressing missing, inconsistent, or duplicate values.

data provenance

The process of tracking the origin and history of data throughout its lifecycle, such as how the data was generated, transmitted, and stored.

data subject

An individual whose data is being collected and processed.

data warehouse

A data management system that supports business intelligence, such as analytics. Data warehouses commonly contain large amounts of historical data, and they are typically used for queries and analysis.

database definition language (DDL)

Statements or commands for creating or modifying the structure of tables and objects in a database.

database manipulation language (DML)

Statements or commands for modifying (inserting, updating, and deleting) information in a database.

DDL

See [database definition language](#).

deep ensemble

To combine multiple deep learning models for prediction. You can use deep ensembles to obtain a more accurate prediction or for estimating uncertainty in predictions.

deep learning

An ML subfield that uses multiple layers of artificial neural networks to identify mapping between input data and target variables of interest.

defense-in-depth

An information security approach in which a series of security mechanisms and controls are thoughtfully layered throughout a computer network to protect the confidentiality, integrity, and availability of the network and the data within. When you adopt this strategy on AWS, you add multiple controls at different layers of the AWS Organizations structure to help secure resources. For example, a defense-in-depth approach might combine multi-factor authentication, network segmentation, and encryption.

delegated administrator

In AWS Organizations, a compatible service can register an AWS member account to administer the organization's accounts and manage permissions for that service. This account is called the *delegated administrator* for that service. For more information and a list of compatible services, see [Services that work with AWS Organizations](#) in the AWS Organizations documentation.

deployment

The process of making an application, new features, or code fixes available in the target environment. Deployment involves implementing changes in a code base and then building and running that code base in the application's environments.

development environment

See [environment](#).

detective control

A security control that is designed to detect, log, and alert after an event has occurred. These controls are a second line of defense, alerting you to security events that bypassed the preventative controls in place. For more information, see [Detective controls](#) in *Implementing security controls on AWS*.

development value stream mapping (DVSM)

A process used to identify and prioritize constraints that adversely affect speed and quality in a software development lifecycle. DVSM extends the value stream mapping process originally designed for lean manufacturing practices. It focuses on the steps and teams required to create and move value through the software development process.

digital twin

A virtual representation of a real-world system, such as a building, factory, industrial equipment, or production line. Digital twins support predictive maintenance, remote monitoring, and production optimization.

dimension table

In a [star schema](#), a smaller table that contains data attributes about quantitative data in a fact table. Dimension table attributes are typically text fields or discrete numbers that behave like text. These attributes are commonly used for query constraining, filtering, and result set labeling.

disaster

An event that prevents a workload or system from fulfilling its business objectives in its primary deployed location. These events can be natural disasters, technical failures, or the result of human actions, such as unintentional misconfiguration or a malware attack.

disaster recovery (DR)

The strategy and process you use to minimize downtime and data loss caused by a [disaster](#). For more information, see [Disaster Recovery of Workloads on AWS: Recovery in the Cloud](#) in the AWS Well-Architected Framework.

DML

See [database manipulation language](#).

domain-driven design

An approach to developing a complex software system by connecting its components to evolving domains, or core business goals, that each component serves. This concept was introduced by Eric Evans in his book, *Domain-Driven Design: Tackling Complexity in the Heart of Software* (Boston: Addison-Wesley Professional, 2003). For information about how you can use domain-driven design with the strangler fig pattern, see [Modernizing legacy Microsoft ASP.NET \(ASMX\) web services incrementally by using containers and Amazon API Gateway](#).

DR

See [disaster recovery](#).

drift detection

Tracking deviations from a baselined configuration. For example, you can use AWS CloudFormation to [detect drift in system resources](#), or you can use AWS Control Tower to [detect changes in your landing zone](#) that might affect compliance with governance requirements.

DVSM

See [development value stream mapping](#).

E

EDA

See [exploratory data analysis](#).

EDI

See [electronic data interchange](#).

edge computing

The technology that increases the computing power for smart devices at the edges of an IoT network. When compared with [cloud computing](#), edge computing can reduce communication latency and improve response time.

electronic data interchange (EDI)

The automated exchange of business documents between organizations. For more information, see [What is Electronic Data Interchange](#).

encryption

A computing process that transforms plaintext data, which is human-readable, into ciphertext.

encryption key

A cryptographic string of randomized bits that is generated by an encryption algorithm. Keys can vary in length, and each key is designed to be unpredictable and unique.

endianness

The order in which bytes are stored in computer memory. Big-endian systems store the most significant byte first. Little-endian systems store the least significant byte first.

endpoint

See [service endpoint](#).

endpoint service

A service that you can host in a virtual private cloud (VPC) to share with other users. You can create an endpoint service with AWS PrivateLink and grant permissions to other AWS accounts or to AWS Identity and Access Management (IAM) principals. These accounts or principals can connect to your endpoint service privately by creating interface VPC endpoints. For more

information, see [Create an endpoint service](#) in the Amazon Virtual Private Cloud (Amazon VPC) documentation.

enterprise resource planning (ERP)

A system that automates and manages key business processes (such as accounting, [MES](#), and project management) for an enterprise.

envelope encryption

The process of encrypting an encryption key with another encryption key. For more information, see [Envelope encryption](#) in the AWS Key Management Service (AWS KMS) documentation.

environment

An instance of a running application. The following are common types of environments in cloud computing:

- development environment – An instance of a running application that is available only to the core team responsible for maintaining the application. Development environments are used to test changes before promoting them to upper environments. This type of environment is sometimes referred to as a *test environment*.
- lower environments – All development environments for an application, such as those used for initial builds and tests.
- production environment – An instance of a running application that end users can access. In a CI/CD pipeline, the production environment is the last deployment environment.
- upper environments – All environments that can be accessed by users other than the core development team. This can include a production environment, preproduction environments, and environments for user acceptance testing.

epic

In agile methodologies, functional categories that help organize and prioritize your work. Epics provide a high-level description of requirements and implementation tasks. For example, AWS CAF security epics include identity and access management, detective controls, infrastructure security, data protection, and incident response. For more information about epics in the AWS migration strategy, see the [program implementation guide](#).

ERP

See [enterprise resource planning](#).

exploratory data analysis (EDA)

The process of analyzing a dataset to understand its main characteristics. You collect or aggregate data and then perform initial investigations to find patterns, detect anomalies, and check assumptions. EDA is performed by calculating summary statistics and creating data visualizations.

F

fact table

The central table in a [star schema](#). It stores quantitative data about business operations. Typically, a fact table contains two types of columns: those that contain measures and those that contain a foreign key to a dimension table.

fail fast

A philosophy that uses frequent and incremental testing to reduce the development lifecycle. It is a critical part of an agile approach.

fault isolation boundary

In the AWS Cloud, a boundary such as an Availability Zone, AWS Region, control plane, or data plane that limits the effect of a failure and helps improve the resilience of workloads. For more information, see [AWS Fault Isolation Boundaries](#).

feature branch

See [branch](#).

features

The input data that you use to make a prediction. For example, in a manufacturing context, features could be images that are periodically captured from the manufacturing line.

feature importance

How significant a feature is for a model's predictions. This is usually expressed as a numerical score that can be calculated through various techniques, such as Shapley Additive Explanations (SHAP) and integrated gradients. For more information, see [Machine learning model interpretability with AWS](#).

feature transformation

To optimize data for the ML process, including enriching data with additional sources, scaling values, or extracting multiple sets of information from a single data field. This enables the ML model to benefit from the data. For example, if you break down the “2021-05-27 00:15:37” date into “2021”, “May”, “Thu”, and “15”, you can help the learning algorithm learn nuanced patterns associated with different data components.

few-shot prompting

Providing an [LLM](#) with a small number of examples that demonstrate the task and desired output before asking it to perform a similar task. This technique is an application of in-context learning, where models learn from examples (*shots*) that are embedded in prompts. Few-shot prompting can be effective for tasks that require specific formatting, reasoning, or domain knowledge. See also [zero-shot prompting](#).

FGAC

See [fine-grained access control](#).

fine-grained access control (FGAC)

The use of multiple conditions to allow or deny an access request.

flash-cut migration

A database migration method that uses continuous data replication through [change data capture](#) to migrate data in the shortest time possible, instead of using a phased approach. The objective is to keep downtime to a minimum.

FM

See [foundation model](#).

foundation model (FM)

A large deep-learning neural network that has been training on massive datasets of generalized and unlabeled data. FMs are capable of performing a wide variety of general tasks, such as understanding language, generating text and images, and conversing in natural language. For more information, see [What are Foundation Models](#).

G

generative AI

A subset of [AI](#) models that have been trained on large amounts of data and that can use a simple text prompt to create new content and artifacts, such as images, videos, text, and audio. For more information, see [What is Generative AI](#).

geo blocking

See [geographic restrictions](#).

geographic restrictions (geo blocking)

In Amazon CloudFront, an option to prevent users in specific countries from accessing content distributions. You can use an allow list or block list to specify approved and banned countries. For more information, see [Restricting the geographic distribution of your content](#) in the CloudFront documentation.

Gitflow workflow

An approach in which lower and upper environments use different branches in a source code repository. The Gitflow workflow is considered legacy, and the [trunk-based workflow](#) is the modern, preferred approach.

golden image

A snapshot of a system or software that is used as a template to deploy new instances of that system or software. For example, in manufacturing, a golden image can be used to provision software on multiple devices and helps improve speed, scalability, and productivity in device manufacturing operations.

greenfield strategy

The absence of existing infrastructure in a new environment. When adopting a greenfield strategy for a system architecture, you can select all new technologies without the restriction of compatibility with existing infrastructure, also known as [brownfield](#). If you are expanding the existing infrastructure, you might blend brownfield and greenfield strategies.

guardrail

A high-level rule that helps govern resources, policies, and compliance across organizational units (OUs). *Preventive guardrails* enforce policies to ensure alignment to compliance standards. They are implemented by using service control policies and IAM permissions boundaries.

Detective guardrails detect policy violations and compliance issues, and generate alerts for remediation. They are implemented by using AWS Config, AWS Security Hub CSPM, Amazon GuardDuty, AWS Trusted Advisor, Amazon Inspector, and custom AWS Lambda checks.

H

HA

See [high availability](#).

heterogeneous database migration

Migrating your source database to a target database that uses a different database engine (for example, Oracle to Amazon Aurora). Heterogeneous migration is typically part of a re-architecting effort, and converting the schema can be a complex task. [AWS provides AWS SCT](#) that helps with schema conversions.

high availability (HA)

The ability of a workload to operate continuously, without intervention, in the event of challenges or disasters. HA systems are designed to automatically fail over, consistently deliver high-quality performance, and handle different loads and failures with minimal performance impact.

historian modernization

An approach used to modernize and upgrade operational technology (OT) systems to better serve the needs of the manufacturing industry. A *historian* is a type of database that is used to collect and store data from various sources in a factory.

holdout data

A portion of historical, labeled data that is withheld from a dataset that is used to train a [machine learning](#) model. You can use holdout data to evaluate the model performance by comparing the model predictions against the holdout data.

homogeneous database migration

Migrating your source database to a target database that shares the same database engine (for example, Microsoft SQL Server to Amazon RDS for SQL Server). Homogeneous migration is typically part of a rehosting or replatforming effort. You can use native database utilities to migrate the schema.

hot data

Data that is frequently accessed, such as real-time data or recent translational data. This data typically requires a high-performance storage tier or class to provide fast query responses.

hotfix

An urgent fix for a critical issue in a production environment. Due to its urgency, a hotfix is usually made outside of the typical DevOps release workflow.

hypercare period

Immediately following cutover, the period of time when a migration team manages and monitors the migrated applications in the cloud in order to address any issues. Typically, this period is 1–4 days in length. At the end of the hypercare period, the migration team typically transfers responsibility for the applications to the cloud operations team.

I

laC

See [infrastructure as code](#).

identity-based policy

A policy attached to one or more IAM principals that defines their permissions within the AWS Cloud environment.

idle application

An application that has an average CPU and memory usage between 5 and 20 percent over a period of 90 days. In a migration project, it is common to retire these applications or retain them on premises.

IIoT

See [Industrial Internet of Things](#).

immutable infrastructure

A model that deploys new infrastructure for production workloads instead of updating, patching, or modifying the existing infrastructure. Immutable infrastructures are inherently more consistent, reliable, and predictable than [mutable infrastructure](#). For more information, see the [Deploy using immutable infrastructure](#) best practice in the AWS Well-Architected Framework.

inbound (ingress) VPC

In an AWS multi-account architecture, a VPC that accepts, inspects, and routes network connections from outside an application. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

incremental migration

A cutover strategy in which you migrate your application in small parts instead of performing a single, full cutover. For example, you might move only a few microservices or users to the new system initially. After you verify that everything is working properly, you can incrementally move additional microservices or users until you can decommission your legacy system. This strategy reduces the risks associated with large migrations.

Industry 4.0

A term that was introduced by [Klaus Schwab](#) in 2016 to refer to the modernization of manufacturing processes through advances in connectivity, real-time data, automation, analytics, and AI/ML.

infrastructure

All of the resources and assets contained within an application's environment.

infrastructure as code (IaC)

The process of provisioning and managing an application's infrastructure through a set of configuration files. IaC is designed to help you centralize infrastructure management, standardize resources, and scale quickly so that new environments are repeatable, reliable, and consistent.

industrial Internet of Things (IIoT)

The use of internet-connected sensors and devices in the industrial sectors, such as manufacturing, energy, automotive, healthcare, life sciences, and agriculture. For more information, see [Building an industrial Internet of Things \(IIoT\) digital transformation strategy](#).

inspection VPC

In an AWS multi-account architecture, a centralized VPC that manages inspections of network traffic between VPCs (in the same or different AWS Regions), the internet, and on-premises networks. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

Internet of Things (IoT)

The network of connected physical objects with embedded sensors or processors that communicate with other devices and systems through the internet or over a local communication network. For more information, see [What is IoT?](#)

interpretability

A characteristic of a machine learning model that describes the degree to which a human can understand how the model's predictions depend on its inputs. For more information, see [Machine learning model interpretability with AWS.](#)

IoT

See [Internet of Things.](#)

IT information library (ITIL)

A set of best practices for delivering IT services and aligning these services with business requirements. ITIL provides the foundation for ITSM.

IT service management (ITSM)

Activities associated with designing, implementing, managing, and supporting IT services for an organization. For information about integrating cloud operations with ITSM tools, see the [operations integration guide.](#)

ITIL

See [IT information library.](#)

ITSM

See [IT service management.](#)

L

label-based access control (LBAC)

An implementation of mandatory access control (MAC) where the users and the data itself are each explicitly assigned a security label value. The intersection between the user security label and data security label determines which rows and columns can be seen by the user.

landing zone

A landing zone is a well-architected, multi-account AWS environment that is scalable and secure. This is a starting point from which your organizations can quickly launch and deploy workloads and applications with confidence in their security and infrastructure environment. For more information about landing zones, see [Setting up a secure and scalable multi-account AWS environment](#).

large language model (LLM)

A deep learning [AI](#) model that is pretrained on a vast amount of data. An LLM can perform multiple tasks, such as answering questions, summarizing documents, translating text into other languages, and completing sentences. For more information, see [What are LLMs](#).

large migration

A migration of 300 or more servers.

LBAC

See [label-based access control](#).

least privilege

The security best practice of granting the minimum permissions required to perform a task. For more information, see [Apply least-privilege permissions](#) in the IAM documentation.

lift and shift

See [7 Rs](#).

little-endian system

A system that stores the least significant byte first. See also [endianness](#).

LLM

See [large language model](#).

lower environments

See [environment](#).

M

machine learning (ML)

A type of artificial intelligence that uses algorithms and techniques for pattern recognition and learning. ML analyzes and learns from recorded data, such as Internet of Things (IoT) data, to generate a statistical model based on patterns. For more information, see [Machine Learning](#).

main branch

See [branch](#).

malware

Software that is designed to compromise computer security or privacy. Malware might disrupt computer systems, leak sensitive information, or gain unauthorized access. Examples of malware include viruses, worms, ransomware, Trojan horses, spyware, and keyloggers.

managed services

AWS services for which AWS operates the infrastructure layer, the operating system, and platforms, and you access the endpoints to store and retrieve data. Amazon Simple Storage Service (Amazon S3) and Amazon DynamoDB are examples of managed services. These are also known as *abstracted services*.

manufacturing execution system (MES)

A software system for tracking, monitoring, documenting, and controlling production processes that convert raw materials to finished products on the shop floor.

MAP

See [Migration Acceleration Program](#).

mechanism

A complete process in which you create a tool, drive adoption of the tool, and then inspect the results in order to make adjustments. A mechanism is a cycle that reinforces and improves itself as it operates. For more information, see [Building mechanisms](#) in the AWS Well-Architected Framework.

member account

All AWS accounts other than the management account that are part of an organization in AWS Organizations. An account can be a member of only one organization at a time.

MES

See [manufacturing execution system](#).

Message Queuing Telemetry Transport (MQTT)

A lightweight, machine-to-machine (M2M) communication protocol, based on the [publish/subscribe](#) pattern, for resource-constrained [IoT](#) devices.

microservice

A small, independent service that communicates over well-defined APIs and is typically owned by small, self-contained teams. For example, an insurance system might include microservices that map to business capabilities, such as sales or marketing, or subdomains, such as purchasing, claims, or analytics. The benefits of microservices include agility, flexible scaling, easy deployment, reusable code, and resilience. For more information, see [Integrating microservices by using AWS serverless services](#).

microservices architecture

An approach to building an application with independent components that run each application process as a microservice. These microservices communicate through a well-defined interface by using lightweight APIs. Each microservice in this architecture can be updated, deployed, and scaled to meet demand for specific functions of an application. For more information, see [Implementing microservices on AWS](#).

Migration Acceleration Program (MAP)

An AWS program that provides consulting support, training, and services to help organizations build a strong operational foundation for moving to the cloud, and to help offset the initial cost of migrations. MAP includes a migration methodology for executing legacy migrations in a methodical way and a set of tools to automate and accelerate common migration scenarios.

migration at scale

The process of moving the majority of the application portfolio to the cloud in waves, with more applications moved at a faster rate in each wave. This phase uses the best practices and lessons learned from the earlier phases to implement a *migration factory* of teams, tools, and processes to streamline the migration of workloads through automation and agile delivery. This is the third phase of the [AWS migration strategy](#).

migration factory

Cross-functional teams that streamline the migration of workloads through automated, agile approaches. Migration factory teams typically include operations, business analysts and owners,

migration engineers, developers, and DevOps professionals working in sprints. Between 20 and 50 percent of an enterprise application portfolio consists of repeated patterns that can be optimized by a factory approach. For more information, see the [discussion of migration factories](#) and the [Cloud Migration Factory guide](#) in this content set.

migration metadata

The information about the application and server that is needed to complete the migration. Each migration pattern requires a different set of migration metadata. Examples of migration metadata include the target subnet, security group, and AWS account.

migration pattern

A repeatable migration task that details the migration strategy, the migration destination, and the migration application or service used. Example: Rehost migration to Amazon EC2 with AWS Application Migration Service.

Migration Portfolio Assessment (MPA)

An online tool that provides information for validating the business case for migrating to the AWS Cloud. MPA provides detailed portfolio assessment (server right-sizing, pricing, TCO comparisons, migration cost analysis) as well as migration planning (application data analysis and data collection, application grouping, migration prioritization, and wave planning). The [MPA tool](#) (requires login) is available free of charge to all AWS consultants and APN Partner consultants.

Migration Readiness Assessment (MRA)

The process of gaining insights about an organization's cloud readiness status, identifying strengths and weaknesses, and building an action plan to close identified gaps, using the AWS CAF. For more information, see the [migration readiness guide](#). MRA is the first phase of the [AWS migration strategy](#).

migration strategy

The approach used to migrate a workload to the AWS Cloud. For more information, see the [7 Rs](#) entry in this glossary and see [Mobilize your organization to accelerate large-scale migrations](#).

ML

See [machine learning](#).

modernization

Transforming an outdated (legacy or monolithic) application and its infrastructure into an agile, elastic, and highly available system in the cloud to reduce costs, gain efficiencies, and take advantage of innovations. For more information, see [Strategy for modernizing applications in the AWS Cloud](#).

modernization readiness assessment

An evaluation that helps determine the modernization readiness of an organization's applications; identifies benefits, risks, and dependencies; and determines how well the organization can support the future state of those applications. The outcome of the assessment is a blueprint of the target architecture, a roadmap that details development phases and milestones for the modernization process, and an action plan for addressing identified gaps. For more information, see [Evaluating modernization readiness for applications in the AWS Cloud](#).

monolithic applications (monoliths)

Applications that run as a single service with tightly coupled processes. Monolithic applications have several drawbacks. If one application feature experiences a spike in demand, the entire architecture must be scaled. Adding or improving a monolithic application's features also becomes more complex when the code base grows. To address these issues, you can use a microservices architecture. For more information, see [Decomposing monoliths into microservices](#).

MPA

See [Migration Portfolio Assessment](#).

MQTT

See [Message Queuing Telemetry Transport](#).

multiclass classification

A process that helps generate predictions for multiple classes (predicting one of more than two outcomes). For example, an ML model might ask "Is this product a book, car, or phone?" or "Which product category is most interesting to this customer?"

mutable infrastructure

A model that updates and modifies the existing infrastructure for production workloads. For improved consistency, reliability, and predictability, the AWS Well-Architected Framework recommends the use of [immutable infrastructure](#) as a best practice.

O

OAC

See [origin access control](#).

OAI

See [origin access identity](#).

OCM

See [organizational change management](#).

offline migration

A migration method in which the source workload is taken down during the migration process. This method involves extended downtime and is typically used for small, non-critical workloads.

OI

See [operations integration](#).

OLA

See [operational-level agreement](#).

online migration

A migration method in which the source workload is copied to the target system without being taken offline. Applications that are connected to the workload can continue to function during the migration. This method involves zero to minimal downtime and is typically used for critical production workloads.

OPC-UA

See [Open Process Communications - Unified Architecture](#).

Open Process Communications - Unified Architecture (OPC-UA)

A machine-to-machine (M2M) communication protocol for industrial automation. OPC-UA provides an interoperability standard with data encryption, authentication, and authorization schemes.

operational-level agreement (OLA)

An agreement that clarifies what functional IT groups promise to deliver to each other, to support a service-level agreement (SLA).

operational readiness review (ORR)

A checklist of questions and associated best practices that help you understand, evaluate, prevent, or reduce the scope of incidents and possible failures. For more information, see [Operational Readiness Reviews \(ORR\)](#) in the AWS Well-Architected Framework.

operational technology (OT)

Hardware and software systems that work with the physical environment to control industrial operations, equipment, and infrastructure. In manufacturing, the integration of OT and information technology (IT) systems is a key focus for [Industry 4.0](#) transformations.

operations integration (OI)

The process of modernizing operations in the cloud, which involves readiness planning, automation, and integration. For more information, see the [operations integration guide](#).

organization trail

A trail that's created by AWS CloudTrail that logs all events for all AWS accounts in an organization in AWS Organizations. This trail is created in each AWS account that's part of the organization and tracks the activity in each account. For more information, see [Creating a trail for an organization](#) in the CloudTrail documentation.

organizational change management (OCM)

A framework for managing major, disruptive business transformations from a people, culture, and leadership perspective. OCM helps organizations prepare for, and transition to, new systems and strategies by accelerating change adoption, addressing transitional issues, and driving cultural and organizational changes. In the AWS migration strategy, this framework is called *people acceleration*, because of the speed of change required in cloud adoption projects. For more information, see the [OCM guide](#).

origin access control (OAC)

In CloudFront, an enhanced option for restricting access to secure your Amazon Simple Storage Service (Amazon S3) content. OAC supports all S3 buckets in all AWS Regions, server-side encryption with AWS KMS (SSE-KMS), and dynamic PUT and DELETE requests to the S3 bucket.

origin access identity (OAI)

In CloudFront, an option for restricting access to secure your Amazon S3 content. When you use OAI, CloudFront creates a principal that Amazon S3 can authenticate with. Authenticated principals can access content in an S3 bucket only through a specific CloudFront distribution. See also [OAC](#), which provides more granular and enhanced access control.

ORR

See [operational readiness review](#).

OT

See [operational technology](#).

outbound (egress) VPC

In an AWS multi-account architecture, a VPC that handles network connections that are initiated from within an application. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

P

permissions boundary

An IAM management policy that is attached to IAM principals to set the maximum permissions that the user or role can have. For more information, see [Permissions boundaries](#) in the IAM documentation.

personally identifiable information (PII)

Information that, when viewed directly or paired with other related data, can be used to reasonably infer the identity of an individual. Examples of PII include names, addresses, and contact information.

PII

See [personally identifiable information](#).

playbook

A set of predefined steps that capture the work associated with migrations, such as delivering core operations functions in the cloud. A playbook can take the form of scripts, automated runbooks, or a summary of processes or steps required to operate your modernized environment.

PLC

See [programmable logic controller](#).

PLM

See [product lifecycle management](#).

policy

An object that can define permissions (see [identity-based policy](#)), specify access conditions (see [resource-based policy](#)), or define the maximum permissions for all accounts in an organization in AWS Organizations (see [service control policy](#)).

polyglot persistence

Independently choosing a microservice's data storage technology based on data access patterns and other requirements. If your microservices have the same data storage technology, they can encounter implementation challenges or experience poor performance. Microservices are more easily implemented and achieve better performance and scalability if they use the data store best adapted to their requirements.

portfolio assessment

A process of discovering, analyzing, and prioritizing the application portfolio in order to plan the migration. For more information, see [Evaluating migration readiness](#).

predicate

A query condition that returns true or false, commonly located in a WHERE clause.

predicate pushdown

A database query optimization technique that filters the data in the query before transfer. This reduces the amount of data that must be retrieved and processed from the relational database, and it improves query performance.

preventative control

A security control that is designed to prevent an event from occurring. These controls are a first line of defense to help prevent unauthorized access or unwanted changes to your network. For more information, see [Preventative controls](#) in *Implementing security controls on AWS*.

principal

An entity in AWS that can perform actions and access resources. This entity is typically a root user for an AWS account, an IAM role, or a user. For more information, see *Principal* in [Roles terms and concepts](#) in the IAM documentation.

privacy by design

A system engineering approach that takes privacy into account through the whole development process.

private hosted zones

A container that holds information about how you want Amazon Route 53 to respond to DNS queries for a domain and its subdomains within one or more VPCs. For more information, see [Working with private hosted zones](#) in the Route 53 documentation.

proactive control

A [security control](#) designed to prevent the deployment of noncompliant resources. These controls scan resources before they are provisioned. If the resource is not compliant with the control, then it isn't provisioned. For more information, see the [Controls reference guide](#) in the AWS Control Tower documentation and see [Proactive controls](#) in *Implementing security controls on AWS*.

product lifecycle management (PLM)

The management of data and processes for a product throughout its entire lifecycle, from design, development, and launch, through growth and maturity, to decline and removal.

production environment

See [environment](#).

programmable logic controller (PLC)

In manufacturing, a highly reliable, adaptable computer that monitors machines and automates manufacturing processes.

prompt chaining

Using the output of one [LLM](#) prompt as the input for the next prompt to generate better responses. This technique is used to break down a complex task into subtasks, or to iteratively refine or expand a preliminary response. It helps improve the accuracy and relevance of a model's responses and allows for more granular, personalized results.

pseudonymization

The process of replacing personal identifiers in a dataset with placeholder values. Pseudonymization can help protect personal privacy. Pseudonymized data is still considered to be personal data.

publish/subscribe (pub/sub)

A pattern that enables asynchronous communications among microservices to improve scalability and responsiveness. For example, in a microservices-based [MES](#), a microservice can publish event messages to a channel that other microservices can subscribe to. The system can add new microservices without changing the publishing service.

Q

query plan

A series of steps, like instructions, that are used to access the data in a SQL relational database system.

query plan regression

When a database service optimizer chooses a less optimal plan than it did before a given change to the database environment. This can be caused by changes to statistics, constraints, environment settings, query parameter bindings, and updates to the database engine.

R

RACI matrix

See [responsible, accountable, consulted, informed \(RACI\)](#).

RAG

See [Retrieval Augmented Generation](#).

ransomware

A malicious software that is designed to block access to a computer system or data until a payment is made.

RASCI matrix

See [responsible, accountable, consulted, informed \(RACI\)](#).

RCAC

See [row and column access control](#).

read replica

A copy of a database that's used for read-only purposes. You can route queries to the read replica to reduce the load on your primary database.

re-architect

See [7 Rs](#).

recovery point objective (RPO)

The maximum acceptable amount of time since the last data recovery point. This determines what is considered an acceptable loss of data between the last recovery point and the interruption of service.

recovery time objective (RTO)

The maximum acceptable delay between the interruption of service and restoration of service.

refactor

See [7 Rs](#).

Region

A collection of AWS resources in a geographic area. Each AWS Region is isolated and independent of the others to provide fault tolerance, stability, and resilience. For more information, see [Specify which AWS Regions your account can use](#).

regression

An ML technique that predicts a numeric value. For example, to solve the problem of "What price will this house sell for?" an ML model could use a linear regression model to predict a house's sale price based on known facts about the house (for example, the square footage).

rehost

See [7 Rs](#).

release

In a deployment process, the act of promoting changes to a production environment.

relocate

See [7 Rs](#).

replatform

See [7 Rs](#).

repurchase

See [7 Rs](#).

resiliency

An application's ability to resist or recover from disruptions. [High availability](#) and [disaster recovery](#) are common considerations when planning for resiliency in the AWS Cloud. For more information, see [AWS Cloud Resilience](#).

resource-based policy

A policy attached to a resource, such as an Amazon S3 bucket, an endpoint, or an encryption key. This type of policy specifies which principals are allowed access, supported actions, and any other conditions that must be met.

responsible, accountable, consulted, informed (RACI) matrix

A matrix that defines the roles and responsibilities for all parties involved in migration activities and cloud operations. The matrix name is derived from the responsibility types defined in the matrix: responsible (R), accountable (A), consulted (C), and informed (I). The support (S) type is optional. If you include support, the matrix is called a *RASCI matrix*, and if you exclude it, it's called a *RACI matrix*.

responsive control

A security control that is designed to drive remediation of adverse events or deviations from your security baseline. For more information, see [Responsive controls](#) in *Implementing security controls on AWS*.

retain

See [7 Rs](#).

retire

See [7 Rs](#).

Retrieval Augmented Generation (RAG)

A [generative AI](#) technology in which an [LLM](#) references an authoritative data source that is outside of its training data sources before generating a response. For example, a RAG model might perform a semantic search of an organization's knowledge base or custom data. For more information, see [What is RAG](#).

rotation

The process of periodically updating a [secret](#) to make it more difficult for an attacker to access the credentials.

row and column access control (RCAC)

The use of basic, flexible SQL expressions that have defined access rules. RCAC consists of row permissions and column masks.

RPO

See [recovery point objective](#).

RTO

See [recovery time objective](#).

runbook

A set of manual or automated procedures required to perform a specific task. These are typically built to streamline repetitive operations or procedures with high error rates.

S

SAML 2.0

An open standard that many identity providers (IdPs) use. This feature enables federated single sign-on (SSO), so users can log into the AWS Management Console or call the AWS API operations without you having to create user in IAM for everyone in your organization. For more information about SAML 2.0-based federation, see [About SAML 2.0-based federation](#) in the IAM documentation.

SCADA

See [supervisory control and data acquisition](#).

SCP

See [service control policy](#).

secret

In AWS Secrets Manager, confidential or restricted information, such as a password or user credentials, that you store in encrypted form. It consists of the secret value and its metadata.

The secret value can be binary, a single string, or multiple strings. For more information, see [What's in a Secrets Manager secret?](#) in the Secrets Manager documentation.

security by design

A system engineering approach that takes security into account through the whole development process.

security control

A technical or administrative guardrail that prevents, detects, or reduces the ability of a threat actor to exploit a security vulnerability. There are four primary types of security controls: [preventative](#), [detective](#), [responsive](#), and [proactive](#).

security hardening

The process of reducing the attack surface to make it more resistant to attacks. This can include actions such as removing resources that are no longer needed, implementing the security best practice of granting least privilege, or deactivating unnecessary features in configuration files.

security information and event management (SIEM) system

Tools and services that combine security information management (SIM) and security event management (SEM) systems. A SIEM system collects, monitors, and analyzes data from servers, networks, devices, and other sources to detect threats and security breaches, and to generate alerts.

security response automation

A predefined and programmed action that is designed to automatically respond to or remediate a security event. These automations serve as [detective](#) or [responsive](#) security controls that help you implement AWS security best practices. Examples of automated response actions include modifying a VPC security group, patching an Amazon EC2 instance, or rotating credentials.

server-side encryption

Encryption of data at its destination, by the AWS service that receives it.

service control policy (SCP)

A policy that provides centralized control over permissions for all accounts in an organization in AWS Organizations. SCPs define guardrails or set limits on actions that an administrator can delegate to users or roles. You can use SCPs as allow lists or deny lists, to specify which services or actions are permitted or prohibited. For more information, see [Service control policies](#) in the AWS Organizations documentation.

service endpoint

The URL of the entry point for an AWS service. You can use the endpoint to connect programmatically to the target service. For more information, see [AWS service endpoints](#) in *AWS General Reference*.

service-level agreement (SLA)

An agreement that clarifies what an IT team promises to deliver to their customers, such as service uptime and performance.

service-level indicator (SLI)

A measurement of a performance aspect of a service, such as its error rate, availability, or throughput.

service-level objective (SLO)

A target metric that represents the health of a service, as measured by a [service-level indicator](#).

shared responsibility model

A model describing the responsibility you share with AWS for cloud security and compliance. AWS is responsible for security *of* the cloud, whereas you are responsible for security *in* the cloud. For more information, see [Shared responsibility model](#).

SIEM

See [security information and event management system](#).

single point of failure (SPOF)

A failure in a single, critical component of an application that can disrupt the system.

SLA

See [service-level agreement](#).

SLI

See [service-level indicator](#).

SLO

See [service-level objective](#).

split-and-seed model

A pattern for scaling and accelerating modernization projects. As new features and product releases are defined, the core team splits up to create new product teams. This helps scale your

organization's capabilities and services, improves developer productivity, and supports rapid innovation. For more information, see [Phased approach to modernizing applications in the AWS Cloud](#).

SPOF

See [single point of failure](#).

star schema

A database organizational structure that uses one large fact table to store transactional or measured data and uses one or more smaller dimensional tables to store data attributes. This structure is designed for use in a [data warehouse](#) or for business intelligence purposes.

strangler fig pattern

An approach to modernizing monolithic systems by incrementally rewriting and replacing system functionality until the legacy system can be decommissioned. This pattern uses the analogy of a fig vine that grows into an established tree and eventually overcomes and replaces its host. The pattern was [introduced by Martin Fowler](#) as a way to manage risk when rewriting monolithic systems. For an example of how to apply this pattern, see [Modernizing legacy Microsoft ASP.NET \(ASMX\) web services incrementally by using containers and Amazon API Gateway](#).

subnet

A range of IP addresses in your VPC. A subnet must reside in a single Availability Zone.

supervisory control and data acquisition (SCADA)

In manufacturing, a system that uses hardware and software to monitor physical assets and production operations.

symmetric encryption

An encryption algorithm that uses the same key to encrypt and decrypt the data.

synthetic testing

Testing a system in a way that simulates user interactions to detect potential issues or to monitor performance. You can use [Amazon CloudWatch Synthetics](#) to create these tests.

system prompt

A technique for providing context, instructions, or guidelines to an [LLM](#) to direct its behavior. System prompts help set context and establish rules for interactions with users.

T

tags

Key-value pairs that act as metadata for organizing your AWS resources. Tags can help you manage, identify, organize, search for, and filter resources. For more information, see [Tagging your AWS resources](#).

target variable

The value that you are trying to predict in supervised ML. This is also referred to as an *outcome variable*. For example, in a manufacturing setting the target variable could be a product defect.

task list

A tool that is used to track progress through a runbook. A task list contains an overview of the runbook and a list of general tasks to be completed. For each general task, it includes the estimated amount of time required, the owner, and the progress.

test environment

See [environment](#).

training

To provide data for your ML model to learn from. The training data must contain the correct answer. The learning algorithm finds patterns in the training data that map the input data attributes to the target (the answer that you want to predict). It outputs an ML model that captures these patterns. You can then use the ML model to make predictions on new data for which you don't know the target.

transit gateway

A network transit hub that you can use to interconnect your VPCs and on-premises networks. For more information, see [What is a transit gateway](#) in the AWS Transit Gateway documentation.

trunk-based workflow

An approach in which developers build and test features locally in a feature branch and then merge those changes into the main branch. The main branch is then built to the development, preproduction, and production environments, sequentially.

trusted access

Granting permissions to a service that you specify to perform tasks in your organization in AWS Organizations and in its accounts on your behalf. The trusted service creates a service-linked role in each account, when that role is needed, to perform management tasks for you. For more information, see [Using AWS Organizations with other AWS services](#) in the AWS Organizations documentation.

tuning

To change aspects of your training process to improve the ML model's accuracy. For example, you can train the ML model by generating a labeling set, adding labels, and then repeating these steps several times under different settings to optimize the model.

two-pizza team

A small DevOps team that you can feed with two pizzas. A two-pizza team size ensures the best possible opportunity for collaboration in software development.

U

uncertainty

A concept that refers to imprecise, incomplete, or unknown information that can undermine the reliability of predictive ML models. There are two types of uncertainty: *Epistemic uncertainty* is caused by limited, incomplete data, whereas *aleatoric uncertainty* is caused by the noise and randomness inherent in the data. For more information, see the [Quantifying uncertainty in deep learning systems](#) guide.

undifferentiated tasks

Also known as *heavy lifting*, work that is necessary to create and operate an application but that doesn't provide direct value to the end user or provide competitive advantage. Examples of undifferentiated tasks include procurement, maintenance, and capacity planning.

upper environments

See [environment](#).

V

vacuuming

A database maintenance operation that involves cleaning up after incremental updates to reclaim storage and improve performance.

version control

Processes and tools that track changes, such as changes to source code in a repository.

VPC peering

A connection between two VPCs that allows you to route traffic by using private IP addresses. For more information, see [What is VPC peering](#) in the Amazon VPC documentation.

vulnerability

A software or hardware flaw that compromises the security of the system.

W

warm cache

A buffer cache that contains current, relevant data that is frequently accessed. The database instance can read from the buffer cache, which is faster than reading from the main memory or disk.

warm data

Data that is infrequently accessed. When querying this kind of data, moderately slow queries are typically acceptable.

window function

A SQL function that performs a calculation on a group of rows that relate in some way to the current record. Window functions are useful for processing tasks, such as calculating a moving average or accessing the value of rows based on the relative position of the current row.

workload

A collection of resources and code that delivers business value, such as a customer-facing application or backend process.

workstream

Functional groups in a migration project that are responsible for a specific set of tasks. Each workstream is independent but supports the other workstreams in the project. For example, the portfolio workstream is responsible for prioritizing applications, wave planning, and collecting migration metadata. The portfolio workstream delivers these assets to the migration workstream, which then migrates the servers and applications.

WORM

See [write once, read many](#).

WQF

See [AWS Workload Qualification Framework](#).

write once, read many (WORM)

A storage model that writes data a single time and prevents the data from being deleted or modified. Authorized users can read the data as many times as needed, but they cannot change it. This data storage infrastructure is considered [immutable](#).

Z

zero-day exploit

An attack, typically malware, that takes advantage of a [zero-day vulnerability](#).

zero-day vulnerability

An unmitigated flaw or vulnerability in a production system. Threat actors can use this type of vulnerability to attack the system. Developers frequently become aware of the vulnerability as a result of the attack.

zero-shot prompting

Providing an [LLM](#) with instructions for performing a task but no examples (*shots*) that can help guide it. The LLM must use its pre-trained knowledge to handle the task. The effectiveness of zero-shot prompting depends on the complexity of the task and the quality of the prompt. See also [few-shot prompting](#).

zombie application

An application that has an average CPU and memory usage below 5 percent. In a migration project, it is common to retire these applications.