



Recovery Control Configuration API Reference Guide

# Amazon Route 53 Application Recovery Controller



# Amazon Route 53 Application Recovery Controller: Recovery Control Configuration API Reference Guide

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

# Table of Contents

<b>What is recovery control configuration in Amazon Application Recovery Controller (ARC)? .....</b>	<b>1</b>
<b>Resources .....</b>	<b>3</b>
CreateControlPanel, UpdateControlPanel .....	3
URI .....	3
HTTP methods .....	3
Schemas .....	6
Properties .....	8
See also .....	15
CreateRoutingControl, UpdateRoutingControl .....	16
URI .....	16
HTTP methods .....	16
Schemas .....	19
Properties .....	21
See also .....	27
CreateSafetyRule, UpdateSafetyRule .....	28
URI .....	28
HTTP methods .....	28
Schemas .....	30
Properties .....	34
See also .....	49
DescribeCluster, DeleteCluster .....	50
URI .....	50
HTTP methods .....	50
Schemas .....	53
Properties .....	55
See also .....	59
DescribeControlPanel, DeleteControlPanel .....	60
URI .....	60
HTTP methods .....	60
Schemas .....	64
Properties .....	65
See also .....	69
DescribeRoutingControl, DeleteRoutingControl .....	70
URI .....	70

HTTP methods .....	70
Schemas .....	74
Properties .....	75
See also .....	79
DescribeSafetyRule, DeleteSafetyRule .....	80
URI .....	80
HTTP methods .....	80
Schemas .....	82
Properties .....	84
See also .....	92
GetResourcePolicy .....	93
URI .....	93
HTTP methods .....	93
Schemas .....	94
Properties .....	95
See also .....	96
ListAssociatedRoute53HealthChecks .....	96
URI .....	96
HTTP methods .....	97
Schemas .....	99
Properties .....	99
See also .....	101
ListClusters, CreateCluster, UpdateCluster .....	101
URI .....	101
HTTP methods .....	101
Schemas .....	106
Properties .....	109
See also .....	116
ListControlPanels .....	117
URI .....	117
HTTP methods .....	117
Schemas .....	119
Properties .....	120
See also .....	124
ListRoutingControls .....	125
URI .....	125

HTTP methods .....	125
Schemas .....	127
Properties .....	129
See also .....	132
ListSafetyRules .....	133
URI .....	133
HTTP methods .....	133
Schemas .....	135
Properties .....	137
See also .....	146
ListTagsForResource, TagResource, UntagResource .....	147
URI .....	147
HTTP methods .....	147
Schemas .....	151
Properties .....	152
See also .....	154
<b>CLI examples .....</b>	<b>156</b>
Create a cluster .....	157
List clusters .....	157
Describe a cluster .....	158
Update a cluster .....	159
Delete a cluster .....	159
Create a control panel .....	160
List control panels .....	160
Describe a control panel .....	161
Delete a control panel .....	162
Create a routing control .....	162
List routing controls .....	163
Describe a routing control .....	164
Delete a routing control .....	164
Create safety rules .....	165
List safety rules .....	167
Describe a safety rule .....	168
Delete a safety rule .....	168
Get routing control state .....	169
Update state for one routing control .....	169

---

Update state for two routing controls at the same time, in a batch .....	170
<b>Document history .....</b>	<b>171</b>
<b>AWS Glossary .....</b>	<b>172</b>

# What is recovery control configuration in Amazon Application Recovery Controller (ARC)?

Welcome to the Recovery Control Configuration API Reference Guide for Amazon Application Recovery Controller (ARC).

With recovery control configuration in ARC, you can use extremely reliable routing control to enable you to recover applications by rerouting traffic, for example, across Availability Zones or Regions. Routing controls are simple on/off switches hosted on a ARC cluster. You integrate your routing controls with Amazon Route 53 health checks that are configured with DNS records. Then, to implement failover, you turn one routing control on and another one off to reroute traffic from one Availability Zone or AWS Region to another.

When you create routing controls, you add them to a control panel. All routing controls are grouped on control panels. You can use the default control panel that is created for each cluster, or create your own custom control panels. You must create a cluster before you can create a routing control or control panel.

After you create routing controls, you can create safety rules to put safeguards in place when you reroute traffic. Safety rules can help you avoid unintentional consequences, like turning two routing controls off at once and stopping all traffic flow.

## Important

ARC is a global service that supports endpoints in multiple AWS Regions but you must specify the US West (Oregon) Region when you work with readiness and recovery control configuration resources, for example, to create readiness checks or routing controls. In addition, you must specify regional endpoints when you work with API cluster operations to update routing control states to reroute traffic for failover.

For more information about ARC, see the following:

- Learn about the components in recovery control configuration, including clusters, routing controls, and control panels. For more information, see [Recovery control components](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

- You can set up readiness checks with ARC to ensure that your applications are scaled to handle failover traffic and configured so you can easily route around failures. For more information about the related API actions, see [Recovery Readiness API Reference Guide for Amazon Route 53 Application Recovery Controller](#).
- You can work with routing control states to reroute traffic for fail over. For more information about the related API actions, see [Routing Control API Reference Guide for Amazon Route 53 Application Recovery Controller](#).
- For more information about creating resilient applications and preparing for recovery readiness with ARC, see the [Amazon Route 53 Application Recovery Controller Developer Guide](#).

# Resources

The Amazon Route 53 Application Recovery Controller REST API includes the following resources.

## Topics

- [CreateControlPanel, UpdateControlPanel](#)
- [CreateRoutingControl, UpdateRoutingControl](#)
- [CreateSafetyRule, UpdateSafetyRule](#)
- [DescribeCluster, DeleteCluster](#)
- [DescribeControlPanel, DeleteControlPanel](#)
- [DescribeRoutingControl, DeleteRoutingControl](#)
- [DescribeSafetyRule, DeleteSafetyRule](#)
- [GetResourcePolicy](#)
- [ListAssociatedRoute53HealthChecks](#)
- [ListClusters, CreateCluster, UpdateCluster](#)
- [ListControlPanels](#)
- [ListRoutingControls](#)
- [ListSafetyRules](#)
- [ListTagsForResource, TagResource, UntagResource](#)

## CreateControlPanel, UpdateControlPanel

### URI

/controlpanel

### HTTP methods

#### POST

**Operation ID:** CreateControlPanel

Creates a new control panel. A control panel represents a group of routing controls that can be changed together in a single transaction. You can use a control panel to centrally view the

operational status of applications across your organization, and trigger multi-app failovers in a single transaction, for example, to fail over an Availability Zone or AWS Region.

## Responses

Status code	Response model	Description
200	<a href="#">CreateControlPanelResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
402	<a href="#">ServiceQuotaExceededException</a>	402 response
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.

Status code	Response model	Description
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## PUT

### Operation ID: UpdateControlPanel

Updates a control panel. The only update that you can make to a control panel is to change its name.

Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

### Responses

Status code	Response model	Description
200	<a href="#">UpdateControlPanelResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - MalformedQueryString. The query string

Status code	Response model	Description
409	<a href="#">ConflictException</a>	contains a syntax error or resource not found. 409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Request bodies

#### POST schema

```
{
  "ClusterArn": "string",
  "ClientToken": "string",
  "ControlPanelName": "string",
  "Tags": {
  }
}
```

## PUT schema

```
{
  "ControlPanelArn": "string",
  "ControlPanelName": "string"
}
```

## Response bodies

### CreateControlPanelResponse schema

```
{
  "ControlPanel": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "ControlPanelArn": "string",
    "DefaultControlPanel": boolean,
    "RoutingControlCount": integer,
    "Name": "string"
  }
}
```

### UpdateControlPanelResponse schema

```
{
  "ControlPanel": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "ControlPanelArn": "string",
    "DefaultControlPanel": boolean,
    "RoutingControlCount": integer,
    "Name": "string"
  }
}
```

### ValidationException schema

```
{
  "message": "string"
}
```

## ServiceQuotaExceededException schema

```
{  
  "message": "string"  
}
```

## AccessDeniedException schema

```
{  
  "message": "string"  
}
```

## ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

## ConflictException schema

```
{  
  "message": "string"  
}
```

## ThrottlingException schema

```
{  
  "message": "string"  
}
```

## InternalServerErrorException schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

## message

**Type:** string

**Required:** True

## ConflictException

409 response - ConflictException. You might be using a predefined variable.

## message

**Type:** string

**Required:** True

## ControlPanel

A control panel represents a group of routing controls that can be changed together in a single transaction.

## ClusterArn

The Amazon Resource Name (ARN) of the cluster that includes the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Status

The deployment status of the control panel. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

## Owner

The AWS account ID of the control panel owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## DefaultControlPanel

A flag that Amazon Route 53 Application Recovery Controller sets to true to designate the default control panel for a cluster. When you create a cluster, Amazon Route 53 Application Recovery Controller creates a control panel, and sets this flag for that control panel. If you create a control panel yourself, this flag is set to false.

**Type:** boolean

**Required:** False

## RoutingControlCount

The number of routing controls in the control panel.

**Type:** integer

**Required:** False

**Format:** int32

## Name

The name of the control panel. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+`

**MinLength:** 1

**MaxLength:** 64

## CreateControlPanelRequest

A request to create a control panel.

### ClusterArn

The Amazon Resource Name (ARN) of the cluster for the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*`

**MinLength:** 1

**MaxLength:** 256

### ClientToken

A unique, case-sensitive string of up to 64 ASCII characters. To make an idempotent API request with an action, specify a client token in the request.

**Type:** string

**Required:** False

**Pattern:** `^[-a-zA-z0-9 ]+`

**MinLength:** 1

**MaxLength:** 64

## ControlPanelName

The name of the control panel. Note that only ASCII characters are supported for control panel names.

**Type:** string

**Required:** True

**Pattern:** ^((?![;'\s<>&"'])[\u0021-\u007E])+

**MinLength:** 1

**MaxLength:** 64

## Tags

The tags associated with the control panel.

**Type:** object

**Required:** False

## CreateControlPanelResponse

The result of a successful `CreateControlPanel` request.

## ControlPanel

Information about a control panel, including a list of the routing controls included in it.

**Type:** [ControlPanel](#)

**Required:** True

## InternalServerError

500 response - `InternalServerError`. Temporary service error. Retry the request.

## message

**Type:** string

**Required:** True

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## ServiceQuotaExceededException

402 response - You attempted to create more resources than the service allows based on service quotas.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

PENDING: Amazon Route 53 Application Recovery Controller is creating the resource.

DEPLOYED: The resource is deployed and ready to use.

PENDING\_DELETION: Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## UpdateControlPanelRequest

Updates an existing control panel.

### ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### ControlPanelName

The name of the control panel. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## UpdateControlPanelResponse

The result of a successful `UpdateControlPanel` request.

### ControlPanel

The control panel to update.

**Type:** [ControlPanel](#)

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### CreateControlPanel

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

### UpdateControlPanel

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## CreateRoutingControl, UpdateRoutingControl

### URI

/routingcontrol

### HTTP methods

#### POST

**Operation ID:** CreateRoutingControl

Creates a new routing control.

A routing control has one of two states: ON and OFF. You configure routing controls so they update Amazon Route 53 health checks, which reroute traffic for your application.

Note that a routing control name must be unique within a control panel.

To get or update the routing control state, see the [GetRoutingControlState](#) API in the Routing Control (Recovery Cluster) API Reference Guide for Amazon Route 53 Application Recovery Controller.

### Responses

Status code	Response model	Description
200	<a href="#">CreateRoutingControlResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input

Status code	Response model	Description
402	<a href="#">ServiceQuotaExceededException</a>	parameter might be out of range, or you used parameters together incorrectly. 402 response
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - MalformedQueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## PUT

### Operation ID: UpdateRoutingControl

Updates a routing control. You can only update the name of the routing control. The name must be unique within a control panel. To get or update the routing control state, see the [GetRoutingControlState](#) API in the Routing Control (Recovery Cluster) API Reference Guide for Amazon Route 53 Application Recovery Controller.

## Responses

Status code	Response model	Description
200	<a href="#">UpdateRoutingControlResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Request bodies

#### POST schema

```
{
  "ClusterArn": "string",
  "RoutingControlName": "string",
  "ControlPanelArn": "string",
  "ClientToken": "string"
}
```

#### PUT schema

```
{
  "RoutingControlName": "string",
  "RoutingControlArn": "string"
}
```

### Response bodies

#### CreateRoutingControlResponse schema

```
{
  "RoutingControl": {
    "Status": enum,
    "Owner": "string",
    "RoutingControlArn": "string",
    "ControlPanelArn": "string",
    "Name": "string"
  }
}
```

```
}
```

## UpdateRoutingControlResponse schema

```
{
  "RoutingControl": {
    "Status": enum,
    "Owner": "string",
    "RoutingControlArn": "string",
    "ControlPanelArn": "string",
    "Name": "string"
  }
}
```

## ValidationException schema

```
{
  "message": "string"
}
```

## ServiceQuotaExceededException schema

```
{
  "message": "string"
}
```

## AccessDeniedException schema

```
{
  "message": "string"
}
```

## ResourceNotFoundException schema

```
{
  "message": "string"
}
```

## ConflictException schema

```
{
```

```
"message": "string"  
}
```

### ThrottlingException schema

```
{  
  "message": "string"  
}
```

### InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### ConflictException

409 response - ConflictException. You might be using a predefined variable.

#### message

**Type:** string

**Required:** True

### CreateRoutingControlRequest

A request to create a routing control. If you don't specify `ControlPanelArn`, Amazon Route 53 Application Recovery Controller creates the routing control in `DefaultControlPanel`.

## ClusterArn

The Amazon Resource Name (ARN) of the cluster that includes the routing control.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RoutingControlName

The name of the routing control. Note that only ASCII characters are supported for routing control names.

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel that includes the routing control.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## ClientToken

A unique, case-sensitive string of up to 64 ASCII characters. To make an idempotent API request with an action, specify a client token in the request.

**Type:** string

**Required:** False

**Pattern:** ^[-a-zA-z0-9 ]+\$

**MinLength:** 1

**MaxLength:** 64

## CreateRoutingControlResponse

The result of a successful `CreateRoutingControl` request.

### RoutingControl

The routing control that is created.

**Type:** [RoutingControl](#)

**Required:** False

## InternalServerError

500 response - `InternalServerError`. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ResourceNotFoundException

404 response - `MalformedQueryString`. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## RoutingControl

A routing control has one of two states: ON and OFF. You configure routing controls so they update Amazon Route 53 health checks, which reroute traffic for your application.

## Status

The deployment status of a routing control. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

## Owner

The AWS account ID of the routing control owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## RoutingControlArn

The Amazon Resource Name (ARN) of the routing control.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel that includes the routing control.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Name

The name of the routing control. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** False

**Pattern:** ^((?![;'\s<>&"])[\u0021-\u007E])+\$

**MinLength:** 1

**MaxLength:** 64

## ServiceQuotaExceededException

402 response - You attempted to create more resources than the service allows based on service quotas.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

PENDING: Amazon Route 53 Application Recovery Controller is creating the resource.

DEPLOYED: The resource is deployed and ready to use.

PENDING\_DELETION: Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

## message

**Type:** string

**Required:** True

## UpdateRoutingControlRequest

A request to update a routing control.

### RoutingControlName

The name of the routing control. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+`

**MinLength:** 1

**MaxLength:** 64

### RoutingControlArn

The Amazon Resource Name (ARN) of the routing control.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*`

**MinLength:** 1

**MaxLength:** 256

## UpdateRoutingControlResponse

The result of a successful `UpdateRoutingControl` request.

### RoutingControl

The routing control that was updated.

**Type:** [RoutingControl](#)

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### CreateRoutingControl

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

### UpdateRoutingControl

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## CreateSafetyRule, UpdateSafetyRule

### URI

/safetyrule

### HTTP methods

#### POST

##### **Operation ID:** CreateSafetyRule

Creates a safety rule in a control panel. Safety rules let you add safeguards around changing routing control states, and for enabling and disabling routing controls, to help prevent unexpected outcomes.

There are two types of safety rules: assertion rules and gating rules.

**Assertion rule:** An assertion rule enforces that, when you change a routing control state, that a certain criteria is met. For example, the criteria might be that at least one routing control state is On after the transaction so that traffic continues to flow to at least one cell for the application. This ensures that you avoid a fail-open scenario.

**Gating rule:** A gating rule lets you configure a gating routing control as an overall "on/off" switch for a group of routing controls. Or, you can configure more complex gating scenarios, for example by configuring multiple gating routing controls.

Note that the name of a safety rule must be unique within a control panel.

For more information, see [Safety rules](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

## Responses

Status code	Response model	Description
200	<a href="#">CreateSafetyRuleResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## PUT

### Operation ID: UpdateSafetyRule

Update a safety rule (an assertion rule or gating rule). You can only update the name and the waiting period for a safety rule. To make other updates, delete the safety rule and create a new one.

## Responses

Status code	Response model	Description
200	<a href="#">UpdateSafetyRuleResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	range, or you used parameter s together incorrectly. 404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Request bodies

#### POST schema

```
{
  "AssertionRule": {
    "ControlPanelArn": "string",
    "AssertedControls": [
      "string"
    ],
    "RuleConfig": {
      "Type": enum,
      "Inverted": boolean,
      "Threshold": integer
    },
    "WaitPeriodMs": integer,
  }
}
```

```

  "Name": "string"
},
"ClientToken": "string",
"GatingRule": {
  "TargetControls": [
    "string"
  ],
  "ControlPanelArn": "string",
  "GatingControls": [
    "string"
  ],
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
},
"Tags": {
}
}

```

## PUT schema

```

{
  "GatingRuleUpdate": {
    "SafetyRuleArn": "string",
    "WaitPeriodMs": integer,
    "Name": "string"
  },
  "AssertionRuleUpdate": {
    "SafetyRuleArn": "string",
    "WaitPeriodMs": integer,
    "Name": "string"
  }
}

```

## Response bodies

### CreateSafetyRuleResponse schema

```

{

```

```
"AssertionRule": {
  "Status": enum,
  "Owner": "string",
  "ControlPanelArn": "string",
  "AssertedControls": [
    "string"
  ],
  "SafetyRuleArn": "string",
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
},
"GatingRule": {
  "Status": enum,
  "TargetControls": [
    "string"
  ],
  "Owner": "string",
  "ControlPanelArn": "string",
  "GatingControls": [
    "string"
  ],
  "SafetyRuleArn": "string",
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
}
}
```

## UpdateSafetyRuleResponse schema

```
{
  "AssertionRule": {
    "Status": enum,
    "Owner": "string",
```

```
"ControlPanelArn": "string",
"AssertedControls": [
  "string"
],
"SafetyRuleArn": "string",
"RuleConfig": {
  "Type": enum,
  "Inverted": boolean,
  "Threshold": integer
},
"WaitPeriodMs": integer,
"Name": "string"
},
"GatingRule": {
  "Status": enum,
  "TargetControls": [
    "string"
  ],
  "Owner": "string",
  "ControlPanelArn": "string",
  "GatingControls": [
    "string"
  ],
  "SafetyRuleArn": "string",
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
}
}
```

### ValidationException schema

```
{
  "message": "string"
}
```

### ResourceNotFoundException schema

```
{
```

```
"message": "string"
}
```

## InternalServerError schema

```
{
  "message": "string"
}
```

## Properties

### AssertionRule

An assertion rule enforces that, when you change a routing control state, that the criteria that you set in the rule configuration is met. Otherwise, the change to the routing control is not accepted. For example, the criteria might be that at least one routing control state is On after the transaction so that traffic continues to flow to at least one cell for the application. This ensures that you avoid a fail-open scenario.

### Status

The deployment status of an assertion rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

### Owner

The AWS account ID of the assertion rule owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

### ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### AssertedControls

The routing controls that are part of transactions that are evaluated to determine if a request to change a routing control state is allowed. For example, you might include three routing controls, one for each of three AWS Regions.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### SafetyRuleArn

The Amazon Resource Name (ARN) of the assertion rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### RuleConfig

The criteria that you set for specific assertion routing controls (AssertedControls) that designate how many routing control states must be ON as the result of a transaction. For example, if you have three assertion routing controls, you might specify `atLeast 2` for your rule configuration. This means that at least two assertion routing control states must be ON, so that at least two AWS Regions have traffic flowing to them.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

Name of the assertion rule. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** ^((?![;'\s<>&"])[\u0021-\u007E])+\$

**MinLength:** 1

**MaxLength:** 64

## AssertionRuleUpdate

An update to an assertion rule. You can update the name or the evaluation period (wait period). If you don't specify one of the items to update, the item is unchanged.

## SafetyRuleArn

The Amazon Resource Name (ARN) of the assertion rule.

**Type:** string

**Required:** True

**Pattern:** ^[A-Za-z0-9:\/\_-]\*\$

**MinLength:** 1

**MaxLength:** 256

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer  
**Required:** True  
**Format:** int32

## Name

The name of the assertion rule. The name must be unique within a control panel. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string  
**Required:** True  
**Pattern:** ^((?![;'\s<>&"])[\u0021-\u007E])+  
**MinLength:** 1  
**MaxLength:** 64

## CreateSafetyRuleRequest

Request to create a safety rule. You can create either an assertion rule or a gating rule with a `CreateSafetyRuleRequest` call. To learn more, [Safety rules](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

## AssertionRule

The assertion rule requested.

**Type:** [NewAssertionRule](#)  
**Required:** False

## ClientToken

A unique, case-sensitive string of up to 64 ASCII characters. To make an idempotent API request with an action, specify a client token in the request.

**Type:** string

**Required:** False

**Pattern:** ^[-a-z-A-z0-9 ]+\$

**MinLength:** 1

**MaxLength:** 64

## GatingRule

The gating rule requested.

**Type:** [NewGatingRule](#)

**Required:** False

## Tags

The tags associated with the safety rule.

**Type:** object

**Required:** False

## CreateSafetyRuleResponse

The result of a successful CreateSafetyRule request.

## AssertionRule

The assertion rule created.

**Type:** [AssertionRule](#)

**Required:** False

## GatingRule

The gating rule created.

**Type:** [GatingRule](#)

**Required:** False

## GatingRule

A gating rule verifies that a gating routing control or set of gating routing controls, evaluates as true, based on a rule configuration that you specify, which allows a set of routing control state changes to complete.

For example, if you specify one gating routing control and you set the Type in the rule configuration to OR, that indicates that you must set the gating routing control to On for the rule to evaluate as true; that is, for the gating control "switch" to be "On". When you do that, then you can update the routing control states for the target routing controls that you specify in the gating rule.

### Status

The deployment status of a gating rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

### TargetControls

An array of target routing control Amazon Resource Names (ARNs) for which the states can only be updated if the rule configuration that you specify evaluates to true for the gating routing control. As a simple example, if you have a single gating control, it acts as an overall "on/off" switch for a set of target routing controls. You can use this to manually override automated failover, for example.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### Owner

The AWS account ID of the gating rule owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

### ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### GatingControls

An array of gating routing control Amazon Resource Names (ARNs). For a simple "on/off" switch, specify the ARN for one routing control. The gating routing controls are evaluated by the rule configuration that you specify to determine if the target routing control states can be changed.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### SafetyRuleArn

The Amazon Resource Name (ARN) of the gating rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for gating routing controls that designate how many of the routing control states must be ON to allow you to update target routing control states.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

The name of the gating rule. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** ^((?![;'\s<>&"])[\u0021-\u007E])+\$

**MinLength:** 1

**MaxLength:** 64

## GatingRuleUpdate

Update to a gating rule. You can update the name or the evaluation period (wait period). If you don't specify one of the items to update, the item is unchanged.

## SafetyRuleArn

The Amazon Resource Name (ARN) of the gating rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

The name of the gating rule. The name must be unique within a control panel. Note that only ASCII characters are supported for gating rule names.

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## NewAssertionRule

A new assertion rule for a control panel.

## ControlPanelArn

The Amazon Resource Name (ARN) for the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## AssertedControls

The routing controls that are part of transactions that are evaluated to determine if a request to change a routing control state is allowed. For example, you might include three routing controls, one for each of three AWS Regions.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for specific assertion controls (routing controls) that designate how many control states must be ON as the result of a transaction. For example, if you have three assertion controls, you might specify `ATLEAST 2` for your rule configuration. This means that at least two assertion controls must be ON, so that at least two AWS Regions have traffic flowing to them.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer  
**Required:** True  
**Format:** int32

## Name

The name of the assertion rule. The name must be unique within a control panel. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string  
**Required:** True  
**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+`  
**MinLength:** 1  
**MaxLength:** 64

## NewGatingRule

A new gating rule for a control panel. To learn more, [Safety rules](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

## TargetControls

Routing controls that can only be set or unset if the specified `RuleConfig` evaluates to true for the specified `GatingControls`. For example, say you have three gating controls, one for each of three AWS Regions. Now you specify `ATLEAST 2` as your `RuleConfig`. With these settings, you can only change (set or unset) the routing controls that you have specified as `TargetControls` if that rule evaluates to true.

In other words, your ability to change the routing controls that you have specified as `TargetControls` is gated by the rule that you set for the routing controls in `GatingControls`.

**Type:** Array of type string  
**Required:** True  
**Pattern:** `^[A-Za-z0-9:\/_-]*`  
**MinLength:** 1  
**MaxLength:** 256

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## GatingControls

The gating controls for the new gating rule. That is, routing controls that are evaluated by the rule configuration that you specify. To learn more, [Safety rules](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for specific gating controls (routing controls) that designate how many control states must be ON to allow you to change (set or unset) the target control states.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

The name for the new gating rule.

**Type:** string

**Required:** True

**Pattern:** ^((?![;'\s<>&"'])[\u0021-\u007E])+\$

**MinLength:** 1

**MaxLength:** 64

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## RuleConfig

The rule configuration for an assertion rule. That is, the criteria that you set for specific assertion controls (routing controls) that specify how many control states must be ON after a transaction completes.

### Type

A rule can be one of the following: ATLEAST, AND, or OR.

**Type:** [RuleType](#)

**Required:** True

### Inverted

Logical negation of the rule. If the rule would usually evaluate true, it's evaluated as false, and vice versa.

**Type:** boolean

**Required:** True

## Threshold

The value of N, when you specify an ATLEAST rule type. That is, Threshold is the number of controls that must be set when you specify an ATLEAST type.

**Type:** integer

**Required:** True

**Format:** int32

## RuleType

An enumerated type that determines how the evaluated rules are processed. RuleType can be one of the following:

**ATLEAST** - At least N routing controls must be set. You specify N as the Threshold in the rule configuration.

**AND** - All routing controls must be set. This is a shortcut for "At least N," where N is the total number of controls in the rule.

**OR** - Any control must be set. This is a shortcut for "At least N," where N is 1.

ATLEAST

AND

OR

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## UpdateSafetyRuleRequest

Request to update a safety rule. A safety rule can be an assertion rule or a gating rule.

### GatingRuleUpdate

The gating rule to update.

**Type:** [GatingRuleUpdate](#)

**Required:** False

### AssertionRuleUpdate

The assertion rule to update.

**Type:** [AssertionRuleUpdate](#)

**Required:** False

## UpdateSafetyRuleResponse

The result of a successful UpdateSafetyRule request.

### AssertionRule

The assertion rule updated.

**Type:** [AssertionRule](#)

**Required:** False

### GatingRule

The gating rule updated.

**Type:** [GatingRule](#)

**Required:** False

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

## message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### CreateSafetyRule

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

### UpdateSafetyRule

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

## DescribeCluster, DeleteCluster

### URI

/cluster/*ClusterArn*

### HTTP methods

#### GET

**Operation ID:** DescribeCluster

Display the details about a cluster. The response includes the cluster name, endpoints, status, and Amazon Resource Name (ARN).

#### Path parameters

Name	Type	Required	Description
<i>ClusterArn</i>	String	True	The Amazon Resource Name (ARN) of the cluster.

#### Responses

Status code	Response model	Description
200	<a href="#">DescribeClusterResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameter s together incorrectly.

Status code	Response model	Description
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - MalformedQueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## DELETE

**Operation ID:** DeleteCluster

Delete a cluster.

### Path parameters

Name	Type	Required	Description
<i>ClusterArn</i>	String	True	The Amazon Resource Name (ARN) of the cluster that you're deleting.

## Responses

Status code	Response model	Description
200	<a href="#">DeleteClusterResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ClusterArn</i>	String	True	The Amazon Resource Name (ARN) of a cluster.

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### DescribeClusterResponse schema

```
{
  "Cluster": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "NetworkType": enum,
    "ClusterEndpoints": [
      {
        "Endpoint": "string",
        "Region": "string"
      }
    ],
    "Name": "string"
  }
}
```

## DeleteClusterResponse schema

```
{  
}
```

## ValidationException schema

```
{  
  "message": "string"  
}
```

## AccessDeniedException schema

```
{  
  "message": "string"  
}
```

## ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

## ConflictException schema

```
{  
  "message": "string"  
}
```

## ThrottlingException schema

```
{  
  "message": "string"  
}
```

## InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### Cluster

A set of five redundant Regional endpoints against which you can execute API calls to update or get the state of routing controls. You can host multiple control panels and routing controls on one cluster.

#### ClusterArn

The Amazon Resource Name (ARN) of the cluster.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### Status

Deployment status of a resource. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

### Owner

The AWS account ID of the cluster owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## NetworkType

The network-type can either be IPV4 or DUALSTACK.

**Type:** [NetworkType](#)

**Required:** False

## ClusterEndpoints

Endpoints for a cluster. Specify one of these endpoints when you want to set or retrieve a routing control state in the cluster. To learn more, see [Best practices](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

To learn more about getting or updating a routing control state, see [Routing control](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

**Type:** Array of type [ClusterEndpoint](#)

**Required:** False

## Name

The name of the cluster. Note that only ASCII characters are supported for cluster names.

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## ClusterEndpoint

A cluster endpoint. Specify an endpoint when you want to set or retrieve a routing control state in the cluster.

## Endpoint

A cluster endpoint. Specify an endpoint and AWS Region when you want to set or retrieve a routing control state in the cluster.

To get or update the routing control state, see the Amazon Route 53 Application Recovery Controller Routing Control Actions.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:.\|/_-]*$`

**MinLength:** 1

**MaxLength:** 128

## Region

The AWS Region for a cluster endpoint.

**Type:** string

**Required:** False

**Pattern:** `^\S+$`

**MinLength:** 1

**MaxLength:** 32

## ConflictException

409 response - ConflictException. You might be using a predefined variable.

### message

**Type:** string

**Required:** True

## DeleteClusterResponse

A successful DeleteCluster request returns no response.

## DescribeClusterResponse

The result of a successful DescribeCluster request.

## Cluster

The cluster for the DescribeCluster request.

**Type:** [Cluster](#)

**Required:** True

## InternalServerError

500 response - InternalServerError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## NetworkType

The network-type of a cluster can either be IPV4 or DUALSTACK.

IPV4

DUALSTACK

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

PENDING: Amazon Route 53 Application Recovery Controller is creating the resource.

DEPLOYED: The resource is deployed and ready to use.

PENDING\_DELETION: Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## DescribeCluster

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteCluster

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DescribeControlPanel, DeleteControlPanel

### URI

/controlpanel/*ControlPanelArn*

### HTTP methods

#### GET

**Operation ID:** DescribeControlPanel

Displays details about a control panel.

## Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of the control panel.

## Responses

Status code	Response model	Description
200	<a href="#">DescribeControlPanelResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.

Status code	Response model	Description
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## DELETE

**Operation ID:** DeleteControlPanel

Deletes a control panel.

### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of the control panel.

### Responses

Status code	Response model	Description
200	<a href="#">DeleteControlPanelResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.

Status code	Response model	Description
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - MalformedQueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of a control panel.

## Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### DescribeControlPanelResponse schema

```
{
  "ControlPanel": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "ControlPanelArn": "string",
    "DefaultControlPanel": boolean,
    "RoutingControlCount": integer,
    "Name": "string"
  }
}
```

#### DeleteControlPanelResponse schema

```
{
}
```

#### ValidationException schema

```
{
  "message": "string"
}
```

#### AccessDeniedException schema

```
{
  "message": "string"
}
```

```
}
```

### ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

### ConflictException schema

```
{  
  "message": "string"  
}
```

### ThrottlingException schema

```
{  
  "message": "string"  
}
```

### InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### ConflictException

409 response - ConflictException. You might be using a predefined variable.

## message

**Type:** string

**Required:** True

## ControlPanel

A control panel represents a group of routing controls that can be changed together in a single transaction.

## ClusterArn

The Amazon Resource Name (ARN) of the cluster that includes the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Status

The deployment status of the control panel. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

## Owner

The AWS account ID of the control panel owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## DefaultControlPanel

A flag that Amazon Route 53 Application Recovery Controller sets to true to designate the default control panel for a cluster. When you create a cluster, Amazon Route 53 Application Recovery Controller creates a control panel, and sets this flag for that control panel. If you create a control panel yourself, this flag is set to false.

**Type:** boolean

**Required:** False

## RoutingControlCount

The number of routing controls in the control panel.

**Type:** integer

**Required:** False

**Format:** int32

## Name

The name of the control panel. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## DeleteControlPanelResponse

A successful DeleteControlPanel request returns no response.

## DescribeControlPanelResponse

The result of a successful DescribeControlPanel request.

### ControlPanel

Information about the control panel, including a list of the routing controls that it includes.

**Type:** [ControlPanel](#)

**Required:** True

## InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

PENDING: Amazon Route 53 Application Recovery Controller is creating the resource.

DEPLOYED: The resource is deployed and ready to use.

PENDING\_DELETION: Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## DescribeControlPanel

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteControlPanel

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DescribeRoutingControl, DeleteRoutingControl

### URI

/routingcontrol/*RoutingControlArn*

### HTTP methods

#### GET

**Operation ID:** DescribeRoutingControl

Displays details about a routing control. A routing control has one of two states: ON or OFF. When you change routing control states, Route 53 ARC updates Amazon Route 53 health checks, which reroute traffic for your application.

To get or update the routing control state, see the [GetRoutingControlState](#) API in the Routing Control (Recovery Cluster) API Reference Guide for Amazon Route 53 Application Recovery Controller.

### Path parameters

Name	Type	Required	Description
<i>RoutingControlArn</i>	String	True	The Amazon Resource Name (ARN) of the routing control.

### Responses

Status code	Response model	Description
200	<a href="#">DescribeRoutingControlResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameter s together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.

Status code	Response model	Description
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## DELETE

**Operation ID:** DeleteRoutingControl

Deletes a routing control.

### Path parameters

Name	Type	Required	Description
<i>RoutingControlArn</i>	String	True	The Amazon Resource Name (ARN) of the routing control that you're deleting.

### Responses

Status code	Response model	Description
200	<a href="#">DeleteRoutingControlResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed

Status code	Response model	Description
403	<a href="#">AccessDeniedException</a>	query string and input parameter might be out of range, or you used parameters together incorrectly. 403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>RoutingControlArn</i>	String	True	The Amazon Resource Name (ARN) of a routing control.

## Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### DescribeRoutingControlResponse schema

```
{
  "RoutingControl": {
    "Status": enum,
    "Owner": "string",
    "RoutingControlArn": "string",
    "ControlPanelArn": "string",
    "Name": "string"
  }
}
```

#### DeleteRoutingControlResponse schema

```
{
}
```

#### ValidationException schema

```
{
  "message": "string"
}
```

#### AccessDeniedException schema

```
{
  "message": "string"
}
```

## ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

## ConflictException schema

```
{  
  "message": "string"  
}
```

## ThrottlingException schema

```
{  
  "message": "string"  
}
```

## InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### ConflictException

409 response - ConflictException. You might be using a predefined variable.

**message****Type:** string**Required:** True**DeleteRoutingControlResponse**

A successful `DeleteRoutingControl` request returns no response.

**DescribeRoutingControlResponse**

The result of a successful `DescribeRoutingControl` request.

**RoutingControl**

Information about the routing control.

**Type:** [RoutingControl](#)**Required:** True**InternalServerError**

500 response - `InternalServerError`. Temporary service error. Retry the request.

**message****Type:** string**Required:** True**ResourceNotFoundException**

404 response - `MalformedQueryString`. The query string contains a syntax error or resource not found.

**message****Type:** string**Required:** True

## RoutingControl

A routing control has one of two states: ON and OFF. You configure routing controls so they update Amazon Route 53 health checks, which reroute traffic for your application.

### Status

The deployment status of a routing control. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

### Owner

The AWS account ID of the routing control owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

### RoutingControlArn

The Amazon Resource Name (ARN) of the routing control.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### ControlPanelArn

The Amazon Resource Name (ARN) of the control panel that includes the routing control.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Name

The name of the routing control. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&" ])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## DescribeRoutingControl

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteRoutingControl

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DescribeSafetyRule, DeleteSafetyRule

### URI

/safetyrule/*SafetyRuleArn*

### HTTP methods

#### GET

**Operation ID:** DescribeSafetyRule

Returns information about a safety rule.

#### Path parameters

Name	Type	Required	Description
<i>SafetyRuleArn</i>	String	True	The ARN of the safety rule.

#### Responses

Status code	Response model	Description
200	<a href="#">DescribeSafetyRuleResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	parameter might be out of range, or you used parameters together incorrectly.  404 response - Malformed QueryString. The query string contains a syntax error or resource not found.

## DELETE

**Operation ID:** DeleteSafetyRule

Deletes a safety rule.

### Path parameters

Name	Type	Required	Description
<i>SafetyRuleArn</i>	String	True	The ARN of the safety rule.

### Responses

Status code	Response model	Description
200	<a href="#">DeleteSafetyRuleResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>SafetyRuleArn</i>	String	True	The ARN of the safety rule.

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### DescribeSafetyRuleResponse schema

```
{
  "AssertionRule": {
    "Status": enum,
    "Owner": "string",
    "ControlPanelArn": "string",
    "AssertedControls": [
```

```
    "string"
  ],
  "SafetyRuleArn": "string",
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
},
"GatingRule": {
  "Status": enum,
  "TargetControls": [
    "string"
  ],
  "Owner": "string",
  "ControlPanelArn": "string",
  "GatingControls": [
    "string"
  ],
  "SafetyRuleArn": "string",
  "RuleConfig": {
    "Type": enum,
    "Inverted": boolean,
    "Threshold": integer
  },
  "WaitPeriodMs": integer,
  "Name": "string"
}
}
```

### DeleteSafetyRuleResponse schema

```
{
}
```

### ValidationException schema

```
{
  "message": "string"
}
```

## ResourceNotFoundException schema

```
{
  "message": "string"
}
```

## InternalServerError schema

```
{
  "message": "string"
}
```

## Properties

### AssertionRule

An assertion rule enforces that, when you change a routing control state, that the criteria that you set in the rule configuration is met. Otherwise, the change to the routing control is not accepted. For example, the criteria might be that at least one routing control state is On after the transaction so that traffic continues to flow to at least one cell for the application. This ensures that you avoid a fail-open scenario.

### Status

The deployment status of an assertion rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

### Owner

The AWS account ID of the assertion rule owner.

**Type:** string

**Required:** False

**Pattern:**  $^\backslash d\{12\}\$$

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## AssertedControls

The routing controls that are part of transactions that are evaluated to determine if a request to change a routing control state is allowed. For example, you might include three routing controls, one for each of three AWS Regions.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## SafetyRuleArn

The Amazon Resource Name (ARN) of the assertion rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for specific assertion routing controls (AssertedControls) that designate how many routing control states must be ON as the result of a transaction. For example, if you have three assertion routing controls, you might specify at least 2 for your rule configuration.

This means that at least two assertion routing control states must be ON, so that at least two AWS Regions have traffic flowing to them.

**Type:** [RuleConfig](#)

**Required:** True

### WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

### Name

Name of the assertion rule. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"])[\u0021-\u007E])+`

**MinLength:** 1

**MaxLength:** 64

### DeleteSafetyRuleResponse

There is an empty response when you delete a safety rule.

### DescribeSafetyRuleResponse

The response when you send a DescribeSafetyRuleResponse request.

### AssertionRule

The assertion rule in the response.

**Type:** [AssertionRule](#)

**Required:** False

## GatingRule

The gating rule in the response.

**Type:** [GatingRule](#)

**Required:** False

## GatingRule

A gating rule verifies that a gating routing control or set of gating routing controls, evaluates as true, based on a rule configuration that you specify, which allows a set of routing control state changes to complete.

For example, if you specify one gating routing control and you set the Type in the rule configuration to OR, that indicates that you must set the gating routing control to On for the rule to evaluate as true; that is, for the gating control "switch" to be "On". When you do that, then you can update the routing control states for the target routing controls that you specify in the gating rule.

## Status

The deployment status of a gating rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

## TargetControls

An array of target routing control Amazon Resource Names (ARNs) for which the states can only be updated if the rule configuration that you specify evaluates to true for the gating routing control. As a simple example, if you have a single gating control, it acts as an overall "on/off" switch for a set of target routing controls. You can use this to manually override automated failover, for example.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Owner

The AWS account ID of the gating rule owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## GatingControls

An array of gating routing control Amazon Resource Names (ARNs). For a simple "on/off" switch, specify the ARN for one routing control. The gating routing controls are evaluated by the rule configuration that you specify to determine if the target routing control states can be changed.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## SafetyRuleArn

The Amazon Resource Name (ARN) of the gating rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for gating routing controls that designate how many of the routing control states must be ON to allow you to update target routing control states.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

The name of the gating rule. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## InternalServerErrorException

500 response - InternalServiceError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## RuleConfig

The rule configuration for an assertion rule. That is, the criteria that you set for specific assertion controls (routing controls) that specify how many control states must be ON after a transaction completes.

### Type

A rule can be one of the following: ATLEAST, AND, or OR.

**Type:** [RuleType](#)

**Required:** True

### Inverted

Logical negation of the rule. If the rule would usually evaluate true, it's evaluated as false, and vice versa.

**Type:** boolean

**Required:** True

## Threshold

The value of N, when you specify an ATLEAST rule type. That is, Threshold is the number of controls that must be set when you specify an ATLEAST type.

**Type:** integer

**Required:** True

**Format:** int32

## RuleType

An enumerated type that determines how the evaluated rules are processed. RuleType can be one of the following:

**ATLEAST** - At least N routing controls must be set. You specify N as the Threshold in the rule configuration.

**AND** - All routing controls must be set. This is a shortcut for "At least N," where N is the total number of controls in the rule.

**OR** - Any control must be set. This is a shortcut for "At least N," where N is 1.

ATLEAST

AND

OR

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### DescribeSafetyRule

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

### DeleteSafetyRule

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetResourcePolicy

Returns the current resource policy for a cluster. You can use this information, for example, to verify that permissions in AWS RAM are set up correctly.

### URI

/resourcePolicy/*ResourceArn*

### HTTP methods

#### GET

**Operation ID:** GetResourcePolicy

Get information about the resource policy for a cluster.

#### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

#### Responses

Status code	Response model	Description
200	<a href="#">GetResourcePolicyResponse</a>	200 response - Success.

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

### Responses

Status code	Response model	Description
200	None	Default response for CORS method.

## Schemas

### Response bodies

#### GetResourcePolicyResponse schema

```
{
  "Policy": "string"
}
```

## ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

## InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### GetResourcePolicyResponse

Returns the current Amazon Resource Access Manager resource policy for a cluster.

#### Policy

The resource policy.

**Type:** string

**Required:** True

**Pattern:** `[\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]+`

**MinLength:** 2

**MaxLength:** 10240

### InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

#### message

**Type:** string

**Required:** True

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### GetResourcePolicy

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListAssociatedRoute53HealthChecks

### URI

/routingcontrol/*RoutingControlArn*/associatedRoute53HealthChecks

## HTTP methods

### GET

**Operation ID:** ListAssociatedRoute53HealthChecks

Returns an array of all Amazon Route 53 health checks associated with a specific routing control.

#### Path parameters

Name	Type	Required	Description
<i>RoutingControlArn</i>	String	True	The Amazon Resource Name (ARN) of the routing control.

#### Query parameters

Name	Type	Required	Description
MaxResults	String	False	The number of objects that you want to return with this call.
NextToken	String	False	The token that identifies which batch of results you want to see.

#### Responses

Status code	Response model	Description
200	<a href="#">ListAssociatedRoute53HealthChecksResponse</a>	200 response - Success.

Status code	Response model	Description
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>RoutingControlArn</i>	String	True	The Amazon Resource Name (ARN) of a routing control.

### Responses

Status code	Response model	Description
200	None	200 response - Success.

# Schemas

## Response bodies

### ListAssociatedRoute53HealthChecksResponse schema

```
{
  "NextToken": "string",
  "HealthCheckIds": [
    "string"
  ]
}
```

### ValidationException schema

```
{
  "message": "string"
}
```

### ResourceNotFoundException schema

```
{
  "message": "string"
}
```

### InternalServerError schema

```
{
  "message": "string"
}
```

## Properties

### InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

#### message

**Type:** string

**Required:** True

## ListAssociatedRoute53HealthChecksResponse

The result of a successful `ListAssociatedRoute53HealthChecks` request.

### NextToken

Next token for listing health checks.

**Type:** string

**Required:** False

**Pattern:** `[\S]*`

**MinLength:** 1

**MaxLength:** 8096

### HealthCheckIds

Identifiers for the health checks.

**Type:** Array of type string

**Required:** True

**Pattern:** `^\S+$`

**MaxLength:** 36

## ResourceNotFoundException

404 response - `MalformedQueryString`. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

## message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### ListAssociatedRoute53HealthChecks

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListClusters, CreateCluster, UpdateCluster

### URI

/cluster

### HTTP methods

### GET

**Operation ID:** ListClusters

Returns an array of all the clusters in an account.

### Query parameters

Name	Type	Required	Description
MaxResults	String	False	The number of objects that you want to return with this call.
NextToken	String	False	The token that identifies which batch of results you want to see.

### Responses

Status code	Response model	Description
200	<a href="#">ListClustersResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.

Status code	Response model	Description
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## POST

### Operation ID: CreateCluster

Create a new cluster. A cluster is a set of redundant Regional endpoints against which you can run API calls to update or get the state of one or more routing controls. Each cluster has a name, status, Amazon Resource Name (ARN), and an array of the five cluster endpoints (one for each supported AWS Region) that you can use with API calls to the cluster data plane.

### Responses

Status code	Response model	Description
200	<a href="#">CreateClusterResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
402	<a href="#">ServiceQuotaExceededException</a>	402 response
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have

Status code	Response model	Description
		sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## PUT

**Operation ID:** UpdateCluster

### Responses

Status code	Response model	Description
200	<a href="#">UpdateClusterResponse</a>	200 response
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of

Status code	Response model	Description
403	<a href="#">AccessDeniedException</a>	range, or you used parameter s together incorrectly. 403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
409	<a href="#">ConflictException</a>	409 response - ConflictException. You might be using a predefined variable.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Responses

Status code	Response model	Description
200	None	200 response - Success.

# Schemas

## Request bodies

### POST schema

```
{
  "UseRoute53GammaHealthChecks": boolean,
  "NetworkType": enum,
  "ClusterName": "string",
  "ClientToken": "string",
  "Tags": {
  }
}
```

### PUT schema

```
{
  "ClusterArn": "string",
  "NetworkType": enum
}
```

## Response bodies

### ListClustersResponse schema

```
{
  "NextToken": "string",
  "Clusters": [
    {
      "ClusterArn": "string",
      "Status": enum,
      "Owner": "string",
      "NetworkType": enum,
      "ClusterEndpoints": [
        {
          "Endpoint": "string",
          "Region": "string"
        }
      ],
      "Name": "string"
    }
  ]
}
```

```
]
}
```

## CreateClusterResponse schema

```
{
  "Cluster": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "NetworkType": enum,
    "ClusterEndpoints": [
      {
        "Endpoint": "string",
        "Region": "string"
      }
    ],
    "Name": "string"
  }
}
```

## UpdateClusterResponse schema

```
{
  "Cluster": {
    "ClusterArn": "string",
    "Status": enum,
    "Owner": "string",
    "NetworkType": enum,
    "ClusterEndpoints": [
      {
        "Endpoint": "string",
        "Region": "string"
      }
    ],
    "Name": "string"
  }
}
```

## ValidationException schema

```
{
```

```
"message": "string"  
}
```

### ServiceQuotaExceededException schema

```
{  
  "message": "string"  
}
```

### AccessDeniedException schema

```
{  
  "message": "string"  
}
```

### ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

### ConflictException schema

```
{  
  "message": "string"  
}
```

### ThrottlingException schema

```
{  
  "message": "string"  
}
```

### InternalServerErrorException schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### Cluster

A set of five redundant Regional endpoints against which you can execute API calls to update or get the state of routing controls. You can host multiple control panels and routing controls on one cluster.

#### ClusterArn

The Amazon Resource Name (ARN) of the cluster.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### Status

Deployment status of a resource. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

### Owner

The AWS account ID of the cluster owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## NetworkType

The network-type can either be IPV4 or DUALSTACK.

**Type:** [NetworkType](#)

**Required:** False

## ClusterEndpoints

Endpoints for a cluster. Specify one of these endpoints when you want to set or retrieve a routing control state in the cluster. To learn more, see [Best practices](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

To learn more about getting or updating a routing control state, see [Routing control](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

**Type:** Array of type [ClusterEndpoint](#)

**Required:** False

## Name

The name of the cluster. Note that only ASCII characters are supported for cluster names.

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## ClusterEndpoint

A cluster endpoint. Specify an endpoint when you want to set or retrieve a routing control state in the cluster.

## Endpoint

A cluster endpoint. Specify an endpoint and AWS Region when you want to set or retrieve a routing control state in the cluster.

To get or update the routing control state, see the Amazon Route 53 Application Recovery Controller Routing Control Actions.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:.\|/_-]*$`

**MinLength:** 1

**MaxLength:** 128

## Region

The AWS Region for a cluster endpoint.

**Type:** string

**Required:** False

**Pattern:** `^\S+$`

**MinLength:** 1

**MaxLength:** 32

## ConflictException

409 response - ConflictException. You might be using a predefined variable.

### message

**Type:** string

**Required:** True

## CreateClusterRequest

The properties of a request to create a cluster.

### UseRoute53GammaHealthChecks

**Type:** boolean

**Required:** False

## NetworkType

The network-type is optional, and can either be IPV4 or DUALSTACK. The default is IPV4.

**Type:** [NetworkType](#)

**Required:** False

## ClusterName

The name of the cluster. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&" ])[\u0021-\u007E])+`

**MinLength:** 1

**MaxLength:** 64

## ClientToken

A unique, case-sensitive string of up to 64 ASCII characters. To make an idempotent API request with an action, specify a client token in the request.

**Type:** string

**Required:** False

**Pattern:** `^[-a-z-A-z0-9 ]+$`

**MinLength:** 1

**MaxLength:** 64

## Tags

The tags associated with the cluster.

**Type:** object

**Required:** False

## CreateClusterResponse

The result of a successful `CreateCluster` request.

### Cluster

The cluster that was created.

**Type:** [Cluster](#)

**Required:** True

## InternalServerErrorException

500 response - `InternalServerError`. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ListClustersResponse

The result of a successful `ListClusters` request.

### NextToken

The token that identifies which batch of results you want to see.

**Type:** string

**Required:** False

**Pattern:** `[\S]*`

**MinLength:** 1

**MaxLength:** 8096

### Clusters

An array of the clusters in an account.

**Type:** Array of type [Cluster](#)

**Required:** False

## NetworkType

The network-type of a cluster can either be IPV4 or DUALSTACK.

IPV4

DUALSTACK

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## ServiceQuotaExceededException

402 response - You attempted to create more resources than the service allows based on service quotas.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING  
DEPLOYED  
PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string  
**Required:** True

## UpdateClusterRequest

Updates an existing cluster.

### ClusterArn

**Type:** string  
**Required:** True  
**Pattern:** `^[A-Za-z0-9:\_\-]*$`  
**MinLength:** 1  
**MaxLength:** 256

### NetworkType

The network-type is required, and can either be IPV4 or DUALSTACK.

**Type:** [NetworkType](#)  
**Required:** True

## UpdateClusterResponse

### Cluster

The result of a successful UpdateCluster request.

**Type:** [Cluster](#)

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ListClusters

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## CreateCluster

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## UpdateCluster

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListControlPanels

### URI

/controlpanels

### HTTP methods

### GET

**Operation ID:** ListControlPanels

Returns an array of control panels in an account or in a cluster.

### Query parameters

Name	Type	Required	Description
ClusterArn	String	False	The Amazon Resource Name (ARN) of a cluster.
MaxResults	String	False	The number of objects that you want to return with this call.
NextToken	String	False	The token that identifies which batch of results you want to see.

### Responses

Status code	Response model	Description
200	<a href="#">ListControlPanelsResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### ListControlPanelsResponse schema

```
{
  "ControlPanels": [
    {
      "ClusterArn": "string",
      "Status": enum,
      "Owner": "string",
      "ControlPanelArn": "string",
      "DefaultControlPanel": boolean,
      "RoutingControlCount": integer,
      "Name": "string"
    }
  ]
}
```

```
    }  
  ],  
  "NextToken": "string"  
}
```

### ValidationException schema

```
{  
  "message": "string"  
}
```

### AccessDeniedException schema

```
{  
  "message": "string"  
}
```

### ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

### ThrottlingException schema

```
{  
  "message": "string"  
}
```

### InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

## message

**Type:** string

**Required:** True

## ControlPanel

A control panel represents a group of routing controls that can be changed together in a single transaction.

## ClusterArn

The Amazon Resource Name (ARN) of the cluster that includes the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## Status

The deployment status of the control panel. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

## Owner

The AWS account ID of the control panel owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** False

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## DefaultControlPanel

A flag that Amazon Route 53 Application Recovery Controller sets to true to designate the default control panel for a cluster. When you create a cluster, Amazon Route 53 Application Recovery Controller creates a control panel, and sets this flag for that control panel. If you create a control panel yourself, this flag is set to false.

**Type:** boolean

**Required:** False

## RoutingControlCount

The number of routing controls in the control panel.

**Type:** integer

**Required:** False

**Format:** int32

## Name

The name of the control panel. Note that only ASCII characters are supported for control panel names, and each name must be unique within a control panel.

**Type:** string

**Required:** False

**Pattern:** `^((?![;'\s<>&"'])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## InternalServerErrorException

500 response - InternalServiceError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ListControlPanelsResponse

The result of a successful ListControlPanel request.

### ControlPanels

The result of a successful ListControlPanel request.

**Type:** Array of type [ControlPanel](#)

**Required:** False

### NextToken

The token that identifies which batch of results you want to see.

**Type:** string

**Required:** False

**Pattern:** `[\S]*`

**MinLength:** 1

**MaxLength:** 8096

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - `LimitExceededException` or `TooManyRequestsException`.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ListControlPanels

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListRoutingControls

### URI

/controlpanel/*ControlPanelArn*/routingcontrols

### HTTP methods

#### GET

**Operation ID:** ListRoutingControls

Returns an array of routing controls for a control panel. A routing control is an Amazon Route 53 Application Recovery Controller construct that has one of two states: ON and OFF. You configure routing controls so they update Amazon Route 53 health checks, which reroute traffic for your application.

### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of the control panel.

## Query parameters

Name	Type	Required	Description
MaxResults	String	False	The number of objects that you want to return with this call.
NextToken	String	False	The token that identifies which batch of results you want to see.

## Responses

Status code	Response model	Description
200	<a href="#">ListRoutingControlsResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameter s together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.

Status code	Response model	Description
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of a control panel.

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### ListRoutingControlsResponse schema

```
{
  "NextToken": "string",
  "RoutingControls": [
    {
      "Status": enum,
```

```
    "Owner": "string",
    "RoutingControlArn": "string",
    "ControlPanelArn": "string",
    "Name": "string"
  }
]
```

### ValidationException schema

```
{
  "message": "string"
}
```

### AccessDeniedException schema

```
{
  "message": "string"
}
```

### ResourceNotFoundException schema

```
{
  "message": "string"
}
```

### ThrottlingException schema

```
{
  "message": "string"
}
```

### InternalServerError schema

```
{
  "message": "string"
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

#### message

**Type:** string

**Required:** True

### ListRoutingControlsResponse

The result of a successful `ListRoutingControl` request.

#### NextToken

The token that identifies which batch of results you want to see.

**Type:** string

**Required:** False

**Pattern:** `[\S]*`

**MinLength:** 1

**MaxLength:** 8096

### RoutingControls

An array of routing controls.

**Type:** Array of type [RoutingControl](#)

**Required:** False

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## RoutingControl

A routing control has one of two states: ON and OFF. You configure routing controls so they update Amazon Route 53 health checks, which reroute traffic for your application.

### Status

The deployment status of a routing control. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** False

### Owner

The AWS account ID of the routing control owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## RoutingControlArn

The Amazon Resource Name (ARN) of the routing control.

**Type:** string  
**Required:** False  
**Pattern:** `^[A-Za-z0-9:\/_-]*$`  
**MinLength:** 1  
**MaxLength:** 256

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel that includes the routing control.

**Type:** string  
**Required:** False  
**Pattern:** `^[A-Za-z0-9:\/_-]*$`  
**MinLength:** 1  
**MaxLength:** 256

## Name

The name of the routing control. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string  
**Required:** False  
**Pattern:** `^((?![;'\s<>&"])[\u0021-\u007E])+$`  
**MinLength:** 1  
**MaxLength:** 64

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

**DEPLOYED:** The resource is deployed and ready to use.

**PENDING\_DELETION:** Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING  
DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ListRoutingControls

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

## ListSafetyRules

### URI

/controlpanel/*ControlPanelArn*/safetyrules

### HTTP methods

#### GET

**Operation ID:** ListSafetyRules

List the safety rules (the assertion rules and gating rules) that you've defined for the routing controls in a control panel.

#### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of the control panel.

#### Query parameters

Name	Type	Required	Description
MaxResults	String	False	The number of objects that you want to return with this call.
NextToken	String	False	The token that identifies which batch of results you want to see.

## Responses

Status code	Response model	Description
200	<a href="#">ListSafetyRulesResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
403	<a href="#">AccessDeniedException</a>	403 response - AccessDeniedException. You do not have sufficient access to perform this action.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
429	<a href="#">ThrottlingException</a>	429 response - LimitExceededException or TooManyRequestsException.
500	<a href="#">InternalServerError</a>	500 response - InternalServerError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ControlPanelArn</i>	String	True	The Amazon Resource Name (ARN) of a control panel.

### Responses

Status code	Response model	Description
200	None	200 response - Success.

## Schemas

### Response bodies

#### ListSafetyRulesResponse schema

```
{
  "NextToken": "string",
  "SafetyRules": [
    {
      "ASSERTION": {
        "Status": enum,
        "Owner": "string",
        "ControlPanelArn": "string",
        "AssertedControls": [
          "string"
        ],
        "SafetyRuleArn": "string",
        "RuleConfig": {
          "Type": enum,
          "Inverted": boolean,
          "Threshold": integer
        },
        "WaitPeriodMs": integer,

```

```

    "Name": "string"
  },
  "GATING": {
    "Status": enum,
    "TargetControls": [
      "string"
    ],
    "Owner": "string",
    "ControlPanelArn": "string",
    "GatingControls": [
      "string"
    ],
    "SafetyRuleArn": "string",
    "RuleConfig": {
      "Type": enum,
      "Inverted": boolean,
      "Threshold": integer
    },
    "WaitPeriodMs": integer,
    "Name": "string"
  }
}
]
}

```

### ValidationException schema

```

{
  "message": "string"
}

```

### AccessDeniedException schema

```

{
  "message": "string"
}

```

### ResourceNotFoundException schema

```

{
  "message": "string"
}

```

## ThrottlingException schema

```
{  
  "message": "string"  
}
```

## InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### AccessDeniedException

403 response - You do not have sufficient access to perform this action.

#### message

**Type:** string

**Required:** True

### AssertionRule

An assertion rule enforces that, when you change a routing control state, that the criteria that you set in the rule configuration is met. Otherwise, the change to the routing control is not accepted. For example, the criteria might be that at least one routing control state is On after the transaction so that traffic continues to flow to at least one cell for the application. This ensures that you avoid a fail-open scenario.

#### Status

The deployment status of an assertion rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

## Owner

The AWS account ID of the assertion rule owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## AssertedControls

The routing controls that are part of transactions that are evaluated to determine if a request to change a routing control state is allowed. For example, you might include three routing controls, one for each of three AWS Regions.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## SafetyRuleArn

The Amazon Resource Name (ARN) of the assertion rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for specific assertion routing controls (AssertedControls) that designate how many routing control states must be ON as the result of a transaction. For example, if you have three assertion routing controls, you might specify `atLeast 2` for your rule configuration. This means that at least two assertion routing control states must be ON, so that at least two AWS Regions have traffic flowing to them.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

Name of the assertion rule. You can use any non-white space character in the name except the following: `&` `>` `<` `'` (single quote) `"` (double quote) `;` (semicolon)

**Type:** string

**Required:** True

**Pattern:** `^((?![;'\s<>&"])[\u0021-\u007E])+$`

**MinLength:** 1

**MaxLength:** 64

## GatingRule

A gating rule verifies that a gating routing control or set of gating routing controls, evaluates as true, based on a rule configuration that you specify, which allows a set of routing control state changes to complete.

For example, if you specify one gating routing control and you set the Type in the rule configuration to OR, that indicates that you must set the gating routing control to On for the rule to evaluate as true; that is, for the gating control "switch" to be "On". When you do that, then you can update the routing control states for the target routing controls that you specify in the gating rule.

### Status

The deployment status of a gating rule. Status can be one of the following: PENDING, DEPLOYED, PENDING\_DELETION.

**Type:** [Status](#)

**Required:** True

### TargetControls

An array of target routing control Amazon Resource Names (ARNs) for which the states can only be updated if the rule configuration that you specify evaluates to true for the gating routing control. As a simple example, if you have a single gating control, it acts as an overall "on/off" switch for a set of target routing controls. You can use this to manually override automated failover, for example.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

### Owner

The AWS account ID of the gating rule owner.

**Type:** string

**Required:** False

**Pattern:** `^\d{12}$`

**MinLength:** 12

**MaxLength:** 12

## ControlPanelArn

The Amazon Resource Name (ARN) of the control panel.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## GatingControls

An array of gating routing control Amazon Resource Names (ARNs). For a simple "on/off" switch, specify the ARN for one routing control. The gating routing controls are evaluated by the rule configuration that you specify to determine if the target routing control states can be changed.

**Type:** Array of type string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## SafetyRuleArn

The Amazon Resource Name (ARN) of the gating rule.

**Type:** string

**Required:** True

**Pattern:** `^[A-Za-z0-9:\/_-]*$`

**MinLength:** 1

**MaxLength:** 256

## RuleConfig

The criteria that you set for gating routing controls that designate how many of the routing control states must be ON to allow you to update target routing control states.

**Type:** [RuleConfig](#)

**Required:** True

## WaitPeriodMs

An evaluation period, in milliseconds (ms), during which any request against the target routing controls will fail. This helps prevent "flapping" of state. The wait period is 5000 ms by default, but you can choose a custom value.

**Type:** integer

**Required:** True

**Format:** int32

## Name

The name of the gating rule. You can use any non-white space character in the name except the following: & > < ' (single quote) " (double quote) ; (semicolon)

**Type:** string

**Required:** True

**Pattern:** ^((?![ ; '\s<>&"])[\u0021-\u007E])+\$

**MinLength:** 1

**MaxLength:** 64

## InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

### message

**Type:** string

**Required:** True

## ListSafetyRulesResponse

The response to a ListSafetyRulesRequest.

### NextToken

The token that identifies which batch of results you want to see.

**Type:** string

**Required:** False

**Pattern:** [\S]\*

**MinLength:** 1

**MaxLength:** 8096

### SafetyRules

The list of safety rules in a control panel.

**Type:** Array of type [Rule](#)

**Required:** False

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## Rule

A safety rule. A safety rule can be an assertion rule or a gating rule. To learn more, see [Safety rules](#) in the Amazon Route 53 Application Recovery Controller Developer Guide.

## ASSERTION

An assertion rule enforces that, when a routing control state is changed, the criteria set by the rule configuration is met. Otherwise, the change to the routing control state is not accepted. For example, the criteria might be that at least one routing control state is On after the transaction so that traffic continues to flow to at least one cell for the application. This ensures that you avoid a fail-open scenario.

**Type:** [AssertionRule](#)

**Required:** False

## GATING

A gating rule verifies that a gating routing control or set of gating routing controls, evaluates as true, based on a rule configuration that you specify, which allows a set of routing control state changes to complete.

For example, if you specify one gating routing control and you set the Type in the rule configuration to OR, that indicates that you must set the gating routing control to On for the rule to evaluate as true; that is, for the gating control "switch" to be "On". When you do that, then you can update the routing control states for the target routing controls that you specify in the gating rule.

**Type:** [GatingRule](#)

**Required:** False

## RuleConfig

The rule configuration for an assertion rule. That is, the criteria that you set for specific assertion controls (routing controls) that specify how many control states must be ON after a transaction completes.

### Type

A rule can be one of the following: ATLEAST, AND, or OR.

**Type:** [RuleType](#)

**Required:** True

## Inverted

Logical negation of the rule. If the rule would usually evaluate true, it's evaluated as false, and vice versa.

**Type:** boolean

**Required:** True

## Threshold

The value of N, when you specify an ATLEAST rule type. That is, Threshold is the number of controls that must be set when you specify an ATLEAST type.

**Type:** integer

**Required:** True

**Format:** int32

## RuleType

An enumerated type that determines how the evaluated rules are processed. RuleType can be one of the following:

**ATLEAST** - At least N routing controls must be set. You specify N as the Threshold in the rule configuration.

**AND** - All routing controls must be set. This is a shortcut for "At least N," where N is the total number of controls in the rule.

**OR** - Any control must be set. This is a shortcut for "At least N," where N is 1.

ATLEAST

AND

OR

## Status

The deployment status of a resource. Status can be one of the following:

**PENDING:** Amazon Route 53 Application Recovery Controller is creating the resource.

DEPLOYED: The resource is deployed and ready to use.

PENDING\_DELETION: Amazon Route 53 Application Recovery Controller is deleting the resource.

PENDING

DEPLOYED

PENDING\_DELETION

## ThrottlingException

429 response - LimitExceededException or TooManyRequestsException.

### message

**Type:** string

**Required:** True

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### ListSafetyRules

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListTagsForResource, TagResource, UntagResource

### URI

/tags/*ResourceArn*

### HTTP methods

#### GET

**Operation ID:** ListTagsForResource

Lists the tags for a resource.

#### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

#### Responses

Status code	Response model	Description
200	<a href="#">ListTagsForResourceResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.  404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## POST

**Operation ID:** TagResource

Adds a tag to a resource.

### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

### Responses

Status code	Response model	Description
200	<a href="#">TagResourceResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you

Status code	Response model	Description
404	<a href="#">ResourceNotFoundException</a>	might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.  404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## DELETE

**Operation ID:** UntagResource

Removes a tag from a resource.

### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

### Query parameters

Name	Type	Required	Description
TagKeys	String	True	Keys for the tags to be removed.

## Responses

Status code	Response model	Description
200	<a href="#">UntagResourceResponse</a>	200 response - Success.
400	<a href="#">ValidationException</a>	400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you used parameters together incorrectly.
404	<a href="#">ResourceNotFoundException</a>	404 response - Malformed QueryString. The query string contains a syntax error or resource not found.
500	<a href="#">InternalServerError</a>	500 response - InternalServiceError. Temporary service error. Retry the request.

## OPTIONS

### Path parameters

Name	Type	Required	Description
<i>ResourceArn</i>	String	True	The Amazon Resource Name (ARN) for the resource.

## Responses

Status code	Response model	Description
200	None	Default response for CORS method.

## Schemas

### Request bodies

#### POST schema

```
{  
  "Tags": {  
  }  
}
```

### Response bodies

#### ListTagsForResourceResponse schema

```
{  
  "Tags": {  
  }  
}
```

#### TagResourceResponse schema

```
{  
}
```

#### UntagResourceResponse schema

```
{  
}
```

#### ValidationException schema

```
{
```

```
"message": "string"  
}
```

### ResourceNotFoundException schema

```
{  
  "message": "string"  
}
```

### InternalServerError schema

```
{  
  "message": "string"  
}
```

## Properties

### InternalServerError

500 response - InternalServiceError. Temporary service error. Retry the request.

#### message

**Type:** string

**Required:** True

### ListTagsForResourceResponse

The result of a successful `ListTagsForResource` request.

#### Tags

The tags associated with the resource.

**Type:** object

**Required:** False

## ResourceNotFoundException

404 response - MalformedQueryString. The query string contains a syntax error or resource not found.

### message

**Type:** string

**Required:** True

## TagResourceRequest

Request to tag a resource.

### Tags

The tags associated with the resource.

**Type:** object

**Required:** True

## TagResourceResponse

The result of a successful TagResource request.

## UntagResourceResponse

The result of a successful UntagResource request.

## ValidationException

400 response - Multiple causes. For example, you might have a malformed query string and input parameter might be out of range, or you might have used parameters together incorrectly.

### message

**Type:** string

**Required:** True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### ListTagsForResource

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

### TagResource

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## UntagResource

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CLI Examples for the Recovery Control Configuration API

This section includes CLI examples for working with the APIs for Recovery Control Configuration with Amazon Application Recovery Controller (ARC).

ARC is a global service that supports endpoints in multiple AWS Regions but you must specify the US West (Oregon) Region (that is, specify the parameter `--region us-west-2`) in most ARC CLI commands. For example, to create resources such as routing controls or clusters.

When you create a cluster, ARC provides you with a set of Regional endpoints. To get or update routing control states, you must specify the Regional endpoint (the AWS Region and the endpoint URL) in your CLI command.

## Topics

- [Create a cluster](#)
- [List clusters](#)
- [Describe a cluster](#)
- [Update a cluster](#)
- [Delete a cluster](#)
- [Create a control panel](#)
- [List control panels](#)
- [Describe a control panel](#)
- [Delete a control panel](#)
- [Create a routing control](#)
- [List routing controls](#)
- [Describe a routing control](#)
- [Delete a routing control](#)
- [Create safety rules](#)
- [List safety rules](#)
- [Describe a safety rule](#)
- [Delete a safety rule](#)
- [Get routing control state](#)
- [Update state for one routing control](#)

- [Update state for two routing controls at the same time, in a batch](#)

## Create a cluster

The following is an example of a request to create a cluster, and the response.

```
aws route53-recovery-control-config create-cluster --cluster-name test --network-type DUALSTACK
```

```
"Cluster": {
  "ClusterArn": "arn:aws:route53-recovery-
control::123456789123:cluster/12341234-1234-1234-1234-123412341234",
  "Name": "test",
  "Status": "PENDING",
  "Owner": "123456789123",
  "NetworkType": "DUALSTACK"
}
```

## List clusters

The following is an example of a request to list the clusters in an account, and the response.

```
aws route53-recovery-control-config --region us-west-2 list-clusters
```

```
"Clusters": [
  {
    "ClusterArn": "arn:aws:route53-recovery-
control::012345678:cluster/1234abcd-abcd-1234-abcd-1234abcdefgh",
    "ClusterEndpoints": [
      {"Endpoint": "https://host-aaaaaa.us-east-1.example.com/v1",
"Region": "us-east-1"},
      {"Endpoint": "https://host-bbbbbbb.ap-southeast-2.example.com/v1",
"Region": "ap-southeast-2"},
      {"Endpoint": "https://host-ccccc.eu-west-1.example.com/v1",
"Region": "eu-west-1"},
      {"Endpoint": "https://host-ddddd.us-west-2.example.com/v1",
"Region": "us-west-2"},
      {"Endpoint": "https://host-eeeeee.ap-northeast-1.example.com/v1",
"Region": "ap-northeast-1"}
    ]
  }
]
```

```

    ],
    "Name": "AnotherCluster",
    "Status": "DEPLOYED"
    "Owner": "012345678",
    "NetworkType": "IPV4"
  },
  {
    "ClusterArn": "arn:aws:route53-recovery-
control::012345678:cluster/5678abcd-abcd-5678-abcd-5678abcdefgh",
    "ClusterEndpoints": [
      {"Endpoint": "https://host-ffffff.us-east-1.example.com/v1",
"Region":"us-east-1"},
      {"Endpoint": "https://host-gggggg.ap-southeast-2.example.com/v1",
"Region":"ap-southeast-2"},
      {"Endpoint": "https://host-hhhhhh.eu-west-1.example.com/v1",
"Region":"eu-west-1"},
      {"Endpoint": "https://host-iiiiii.us-west-2.example.com/v1",
"Region":"us-west-2"},
      {"Endpoint": "https://host-jjjjjj.ap-northeast-1.example.com/v1",
"Region":"ap-northeast-1"}
    ],
    "Name": "NewCluster",
    "Status": "DEPLOYED",
    "Owner": "012345678",
    "NetworkType": "DUALSTACK"
  }
]

```

## Describe a cluster

The following is an example of a request to describe a cluster, and the response.

```

aws route53-recovery-control-config --region us-west-2 describe-cluster \
  --cluster-arn arn:aws:route53-recovery-control::012345678901:cluster/abc123456-aa11-
bb22-cc33-abc123456

```

```

"Cluster":{
  "ClusterArn": "arn:aws:route53-recovery-control::012345678:cluster/5678abcd-
abcd-5678-abcd-5678abcdefgh",
  "ClusterEndpoints":[
    {"Endpoint": "https://host-aaaaaa.us-east-1.example.com", "Region":"us-
east-1"},

```

```

        {"Endpoint": "https://host-bbbbbbb.ap-southeast-2.example.com",
"Region": "ap-southeast-2"},
        {"Endpoint": "https://host-cccccc.eu-west-1.example.com", "Region": "eu-
west-1"},
        {"Endpoint": "https://host-dddddd.us-west-2.example.com", "Region": "us-
west-2"},
        {"Endpoint": "https://host-eeeeee.ap-northeast-1.example.com",
"Region": "ap-northeast-1"}
    ]
    "Name": "NewCluster",
    "Status": "DEPLOYED",
    "Owner": "012345678",
    "NetworkType": "IPV4"
}

```

## Update a cluster

The following is an example of a request to update a cluster, and the response.

```

aws route53-recovery-control-config update-cluster \
--cluster-arn arn:aws:route53-recovery-
control::123456789123:cluster/12341234-1234-1234-1234-123412341234 \
--network-type DUALSTACK

```

```

"Cluster": {
    "ClusterArn": "arn:aws:route53-recovery-
control::123456789123:cluster/12341234-1234-1234-1234-123412341234",
    "Name": "test",
    "Status": "PENDING",
    "Owner": "123456789123",
    "NetworkType": "DUALSTACK"
}

```

## Delete a cluster

The following is an example of a request to delete a cluster. Deleting a cluster doesn't return a response.

```

aws route53-recovery-control-config --region us-west-2 delete-cluster \

```

```
--cluster-arn arn:aws:route53-recovery-control::012345678901:cluster/abc123456-aa11-bb22-cc33-abc123456
```

## Create a control panel

A control panel is a logical grouping for organizing your Amazon Route 53 Application Recovery Controller routing controls. When you create a cluster, Amazon Route 53 Application Recovery Controller automatically provides a control panel for you called `DefaultControlPanel`. You can use this control panel right away.

Optionally, create your own control panel by calling `create-control-panel`. A control panel can only exist in one cluster. If you want to move a control panel to another cluster, you must delete it and then create it in the second cluster.

The following is an example of a request to create a control panel in a cluster, and the response.

```
aws route53-recovery-control-config --region us-west-2 create-control-panel \
  --control-panel-name NewControlPanel2 \
  --cluster-arn arn:aws:route53-recovery-control::012345678901:cluster/abc123456-aa11-bb22-cc33-abc123456
```

```
{
  "ControlPanel": {
    "ControlPanelArn": "arn:aws:route53-recovery-control::012345678901:controlpanel/d22190fdbfca4845804e3f76457d57c9",
    "ClusterArn": "arn:aws:route53-recovery-control::012345678901:cluster/abc123456-aa11-bb22-cc33-abc123456",
    "DefaultControlPanel": false,
    "Name": "NewControlPanel2",
    "RoutingControlCount": 0,
    "Status": "PENDING"
  }
}
```

## List control panels

A control panel is a logical grouping for organizing your Amazon Route 53 Application Recovery Controller routing controls. When you create a cluster, Amazon Route 53 Application Recovery

Controller automatically provides a control panel for you called `DefaultControlPanel`. You can use this control panel right away.

You can see all of the control panels in your account by calling `list-control-panels`. To see just the control panels in a specific cluster, add the `--cluster-arn` field.

The following is an example of a request to list the control panels in your account, and the response.

```
aws route53-recovery-control-config --region us-west-2 list-control-panels \
  --cluster-arn arn:aws:route53-recovery-control::012345678901:cluster/abc123456-aa11-
bb22-cc33-abc123456
```

```
{
  "ControlPanels": [
    {
      "ControlPanelArn": "arn:aws:route53-recovery-
control::012345678901:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx789",
      "ClusterArn": "arn:aws:route53-recovery-control::012345678901:cluster/
abc123456-aa11-bb22-cc33-abc123456",
      "DefaultControlPanel": true,
      "Name": "DefaultControlPanel",
      "RoutingControlCount": 0,
      "Status": "PENDING"
    },
    {
      "ControlPanelArn": "arn:aws:route53-recovery-
control::012345678901:controlpanel/aaa123bbb456ccc789aaa123bbb456ccc789",
      "ClusterArn": "arn:aws:route53-recovery-control::012345678901:cluster/
abc123456-aa11-bb22-cc33-abc123456",
      "DefaultControlPanel": false,
      "Name": "SecondControlPanel",
      "RoutingControlCount": 0,
      "Status": "PENDING"
    }
  ]
}
```

## Describe a control panel

The following is an example of a request to describe a control panel, and the response.

```
aws route53-recovery-control-config --region us-west-2 describe-control-panel \  
  --control-panel-arn arn:aws:route53-recovery-control::012345678901:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/5362908c4c734c2b
```

```
{  
  "ControlPanel": {  
    "ControlPanelArn": "arn:aws:route53-recovery-  
control::012345678901:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",  
    "ClusterArn": "arn:aws:route53-recovery-control::012345678901:cluster/a2002f8b-  
e664-4671-bf4d-42e185241731",  
    "DefaultControlPanel": true,  
    "Name": "DefaultControlPanel",  
    "RoutingControlCount": 3,  
    "Status": "DEPLOYED"  
  }  
}
```

## Delete a control panel

The following is an example of a request to delete a control panel. Deleting a control panel doesn't return a response.

```
aws route53-recovery-control-config --region us-west-2 delete-control-panel \  
  --control-panel-arn arn:aws:route53-recovery-control::012345678901:controlpanel/  
  aaa123bbb456ccc789aaa123bbb456ccc789
```

## Create a routing control

When you create a routing control, at a minimum you must specify the Amazon Resource Name (ARN) of the cluster that you want the routing control to be in. You can also specify the ARN of a control panel for the routing control. You'll also need to specify the cluster where the control panel is located.

If you don't specify a control panel, your routing control is added to the automatically created control panel, `DefaultControlPanel`.

The following is an example of a request to create a routing control in a control panel, and the response.

```
aws route53-recovery-control-config --region us-west-2 create-routing-control \
  --routing-control-name NewRc1 \
  --cluster-arn arn:aws:route53-recovery-control::888888888888:cluster/5678abcd-
abcd-5678-abcd-5678abcdefgh
```

```
{
  "RoutingControl": {
    "ControlPanelArn": " arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456",
    "Name": "NewRc1",
    "RoutingControlArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456/routingcontrol/
abcdefg1234567",
    "Status": "PENDING"
  }
}
```

## List routing controls

The following is an example of a request to list the routing controls in a control panel, and the response.

```
aws route53-recovery-control-config --region us-west-2 list-routing-controls \
  --control-panel-arn arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456
```

```
{
  "RoutingControls": [
    {
      "ControlPanelArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456",
      "Name": "Rc1",
      "RoutingControlArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456/routingcontrol/
abcdefg1234567",
      "Status": "DEPLOYED"
    },
    {
      "ControlPanelArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbbb0123456",
```

```
        "Name": "Rc2",
        "RoutingControlArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbb0123456/routingcontrol/
hijklmnop987654321",
        "Status": "DEPLOYED"
    }
]
}
```

## Describe a routing control

The following is an example of a request to describe a routing control, and the response.

```
aws route53-recovery-control-config --region us-west-2 describe-routing-control \
--routing-control-arn arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def
```

```
{
  "RoutingControl": {
    "ControlPanelArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",
    "Name": "NewRc1",
    "RoutingControlArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/
def123def123def",
    "Status": "DEPLOYED"
  }
}
```

## Delete a routing control

The following is an example of a request to delete a routing control. Deleting a routing control doesn't return a response.

```
aws route53-recovery-control-config --region us-west-2 delete-routing-control \
--routing-control-arn arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/abc123abc123abc
```

## Create safety rules

The following are examples of requests to create the two types of safety rules, assertion rules and gating rules, and the responses.

The following call provides an example of creating an assertion rule that makes sure that at least one of your routing controls is enabled at any given time.

```
aws route53-recovery-control-config --region us-west-2 create-safety-rule \
  --assertion-rule '{"Name": "TestAssertionRule",
    "ControlPanelArn": "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx",
    "WaitPeriodMs": 5000,
    "AssertedControls":
    ["arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def",
    "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/ghi456ghi456ghi"]',
    "RuleConfig": {"Threshold": 1, "Type": "ATLEAST", "Inverted": false}}'
```

```
{
  "Rule": {
    "ASSERTION": {
      "Arn": "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/333333444444",
      "AssertedControls": [
        "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def",
        "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/ghi456ghi456ghi"],
      "ControlPanelArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",
      "Name": "TestAssertionRule",
      "RuleConfig": {
        "Inverted": false,
        "Threshold": 1,
        "Type": "ATLEAST"
      },
      "Status": "PENDING",
      "WaitPeriodMs": 5000
    }
  }
}
```

```
}

```

The following call provides an example of creating a gating rule that acts as an overall "on/off" switch for a set of target routing controls in a control panel, to enable or disable the target routing controls from being turned on or off.

```
aws route53-recovery-control-config --region us-west-2 create-safety-rule \
  --gating-rule '{"Name": "TestGatingRule",
    "ControlPanelArn": "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx",
    "WaitPeriodMs": 5000,
    "GatingControls": ["arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def"],
    "TargetControls": ["arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/ghi456ghi456ghi",
    "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/lmn789lmn789lmn"],
    "RuleConfig": {"Threshold": 0, "Type": "OR", "Inverted": false}}'
```

```
{
  "Rule": {
    "GATING": {
      "Arn": "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/4444444444444",
      "GatingControls": [
        "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def"
      ],
      "TargetControls": [
        "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/ghi456ghi456ghi",
        "arn:aws:route53-recovery-control::888888888888:controlpanel/
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/lmn789lmn789lmn"
      ],
      "ControlPanelArn": "arn:aws:route53-recovery-
control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",
      "Name": "TestGatingRule",
      "RuleConfig": {
        "Inverted": false,
        "Threshold": 0,
        "Type": "OR"
      }
    },
  }
```

```

        "Status": "PENDING",
        "WaitPeriodMs": 5000
    }
}

```

## List safety rules

The following is an example of a request to list the safety rules in a control panel, and the response.

```

aws route53-recovery-control-config --region us-west-2 list-safety-rules \
  --control-panel-arn arn:aws:route53-recovery-control::888888888888:controlpanel/
  zzz123yyy456xxx789zzz123yyy456xxx

```

```

{
  "SafetyRules": [
    {
      "ASSERTION": {
        "Arn": "arn:aws:route53-recovery-control::888888888888:controlpanel/
        zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/333333444444",
        "AssertedControls": [
          "arn:aws:route53-recovery-control::888888888888:controlpanel/
          zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/def123def123def"
        ],
        "ControlPanelArn": "arn:aws:route53-recovery-
        control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",
        "Name": "TestSafetyRule",
        "RuleConfig": {
          "Inverted": false,
          "Threshold": 1,
          "Type": "ATLEAST"
        },
        "Status": "DEPLOYED",
        "WaitPeriodMs": 5000
      }
    }
  ]
}

```

## Describe a safety rule

The following is an example of a request to describe a type of safety rule, and the response. This safety rule is an assertion rule.

```
aws route53-recovery-control-config --region us-west-2 describe-safety-rule \  
  --safety-rule-arn arn:aws:route53-recovery-control::888888888888:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/333333444444
```

```
{  
  "SafetyRule": {  
    "ASSERTION": {  
      "Arn": "arn:aws:route53-recovery-control::888888888888:controlpanel/  
zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/333333444444",  
      "AssertedControls": [  
        "arn:aws:route53-recovery-control::888888888888:controlpanel/  
zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/abcdefg1234567"  
      ],  
      "ControlPanelArn": "arn:aws:route53-recovery-  
control::888888888888:controlpanel/zzz123yyy456xxx789zzz123yyy456xxx",  
      "Name": "TestSafetyRule",  
      "RuleConfig": {  
        "Inverted": false,  
        "Threshold": 1,  
        "Type": "ATLEAST"  
      },  
      "Status": "DEPLOYED",  
      "WaitPeriodMs": 5000  
    }  
  }  
}
```

## Delete a safety rule

The following is an example of a request to delete a safety rule. Deleting a safety rule doesn't return a response.

```
aws route53-recovery-control-config --region us-west-2 delete-safety-rule \  
  --safety-rule-arn arn:aws:route53-recovery-control::888888888888:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/safetyrule/333333444444
```

## Get routing control state

The following is an example of a request to get a routing control state, and the response.

For more information, see [GetRoutingControlState](#) in the Recovery Control Configuration API Reference Guide for Amazon Route 53 Application Recovery Controller.

```
aws route53-recovery-cluster get-routing-control-state \  
  --routing-control-arn arn:aws:route53-recovery-control::888888888888:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/abcdefg1234567 \  
  --region us-west-2 \  
  --endpoint-url https://host-dddddd.us-west-2.example.com/v1
```

```
{  
  "RoutingControlArn": "arn:aws:route53-recovery-control::888888888888:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/abcdefg1234567",  
  "RoutingControlState": "On"  
}
```

## Update state for one routing control

The following is an example of a request to update a routing control state to be ON. Updating a routing control state doesn't return a response.

For more information, see [UpdateRoutingControlState](#) in the Recovery Control Configuration API Reference Guide for Amazon Route 53 Application Recovery Controller.

```
aws route53-recovery-cluster update-routing-control-state \  
  --routing-control-arn arn:aws:route53-recovery-control::888888888888:controlpanel/  
  zzz123yyy456xxx789zzz123yyy456xxx/routingcontrol/abcdefg1234567 \  
  --routing-control-state On \  
  --region us-west-2 \  
  --endpoint-url https://host-dddddd.us-west-2.example.com/v1
```

## Update state for two routing controls at the same time, in a batch

The following is an example of a request to update two routing control states at the same time. It sets one to the state OFF and the other to the state ON. Updating routing control states with this command doesn't return a response.

For more information, see [UpdateRoutingControlStates](#) in the Recovery Control Configuration API Reference Guide for Amazon Route 53 Application Recovery Controller.

```
aws route53-recovery-cluster update-routing-control-states \  
  --update-routing-control-state-entries \  
  '[{"RoutingControlArn": "arn:aws:route53-recovery-  
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbb0123456/routingcontrol/  
abcdefg1234567",  
  "RoutingControlState": "Off"}, \  
 {"RoutingControlArn": "arn:aws:route53-recovery-  
control::888888888888:controlpanel/0123456bbbbbbb0123456bbbbbb0123456/routingcontrol/  
hijklmnop987654321",  
  "RoutingControlState": "On"}]' \  
  --region us-west-2 \  
  --endpoint-url https://host-dddddd.us-west-2.example.com/v1
```

# Document history for the Recovery Control Configuration API Reference Guide for Amazon Application Recovery Controller (ARC)

The following table describes the documentation for this release of the Recovery Control Configuration API Reference Guide for Amazon Application Recovery Controller (ARC).

- **API version: latest**
- **Latest documentation update: July 27 2021**

Change	Description	Date
--------	-------------	------

# AWS Glossary

For the latest AWS terminology, see the [AWS glossary](#) in the *AWS Glossary Reference*.