



API Reference

AWS Snowball Edge



AWS Snowball Edge: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Job Management API	1
API Endpoint	2
API Version	2
API Permission Policy Reference	3
Creating an IAM Role for Snowball Edge and Snowball Edge	6
Actions	10
AWS Snowball Edge	11
CancelCluster	13
CancelJob	16
CreateAddress	19
CreateCluster	22
CreateJob	32
CreateLongTermPricing	43
CreateReturnShippingLabel	46
DescribeAddress	50
DescribeAddresses	53
DescribeCluster	57
DescribeJob	61
DescribeReturnShippingLabel	69
GetJobManifest	73
GetJobUnlockCode	76
GetSnowballUsage	79
GetSoftwareUpdates	81
ListClusterJobs	84
ListClusters	88
ListCompatibleImages	91
ListJobs	95
ListLongTermPricing	99
ListPickupLocations	103
ListServiceVersions	107
UpdateCluster	112
UpdateJob	118
UpdateJobShipmentState	125
UpdateLongTermPricing	128

AWS Snowball Edge Device Management	130
CancelTask	131
CreateTask	134
DescribeDevice	138
DescribeDeviceEc2Instances	143
DescribeExecution	147
DescribeTask	151
ListDeviceResources	155
ListDevices	159
ListExecutions	162
ListTagsForResource	166
ListTasks	169
TagResource	172
UntagResource	175
Data Types	177
AWS Snowball Edge	178
Address	181
ClusterListEntry	186
ClusterMetadata	188
CompatibleImage	193
DataTransfer	195
DependentService	197
DeviceConfiguration	199
Ec2AmiResource	200
EKSONDeviceServiceConfiguration	202
EventTriggerDefinition	204
INDTaxDocuments	205
JobListEntry	206
JobLogs	209
JobMetadata	211
JobResource	218
KeyRange	220
LambdaResource	222
LongTermPricingListEntry	224
NFSOnDeviceServiceConfiguration	227
Notification	229

OnDeviceServiceConfiguration	231
PickupDetails	233
S3OnDeviceServiceConfiguration	236
S3Resource	238
ServiceVersion	240
Shipment	241
ShippingDetails	243
SnowconeDeviceConfiguration	245
TargetOnDeviceService	246
TaxDocuments	248
TGWOnDeviceServiceConfiguration	250
WirelessConnection	252
AWS Snowball Edge Device Management	252
Capacity	254
Command	256
CpuOptions	257
DeviceSummary	258
EbsInstanceBlockDevice	260
ExecutionSummary	262
Instance	264
InstanceBlockDeviceMapping	267
InstanceState	268
InstanceSummary	270
PhysicalNetworkInterface	271
Reboot	273
ResourceSummary	274
SecurityGroupIdentifier	275
SoftwareInformation	276
TaskSummary	277
Unlock	279
Common Parameters	280
Common Error Types	283

Job Management API Reference

The job management API for AWS Snowball Edge is a network protocol based on HTTP (RFC 2616). For more information on this RFC, see [HTTP \(RFC 2616\)](#) on the IETF website. For each call to the job management API, you make an HTTP request to the region-specific job management API endpoint for the AWS Region where you want to manage jobs. The API uses JSON (RFC 4627) documents for HTTP request/response bodies.

Note

API calls made within the US regions for listing jobs or describing addresses return all jobs or addresses within the US for that account.

The job management API for Snowball Edge is an RPC model. In this model, there is a fixed set of operations and the syntax for each operation is known to clients without any previous interaction. Following, you can find a description of each API operation using an abstract RPC notation, with an operation name that does not appear on the wire. For each operation, the topic specifies the mapping to HTTP request elements.

The specific job management operation to which a given request maps is determined by a combination of the request's method (GET, PUT, POST, or DELETE) and which of the various patterns its Request-URI matches. If the operation is PUT or POST, Snowball Edge extracts call arguments from the Request-URI path segment, query parameters, and the JSON object in the request body.

Although the operation name, such as `CreateJob`, doesn't appear on the wire, these operation names are meaningful in AWS Identity and Access Management (IAM) policies. The operation name is also used to name commands in command-line tools and elements of the AWS SDK APIs. For example, the AWS Command Line Interface (AWS CLI) command `create-job` maps to the `CreateJob` operation. The operation name also appears in CloudTrail logs for Snowball Edge API calls.

For information on installing and setting up the AWS CLI, including specifying what regions you want to make AWS CLI calls against, see the [AWS Command Line Interface User Guide](#).

Note

The job management API provides a programmatic interface to the same functionality available in the [AWS Snowball Management Console](#), that is to create and manage jobs for Snowball Edge. To transfer data locally with a Snowball appliance, use the Snowball Edge Client or the S3 SDK Adapter for Snowball Edge. For more information, see [Transferring Data with a Snowball](#) in the *AWS Snowball User Guide*.

If you use a Snowball Edge, use the Snowball Edge Client to unlock the appliance. For more information, see [Using the Snowball Client](#) in the *AWS Snowball Developer Guide*.

API Endpoint

The API endpoint is the Domain Name Service (DNS) name used as a host in the HTTP URI for the API calls. These API endpoints are region-specific and take the following form.

```
snowball.aws-region.amazonaws.com
```

For example, the Snowball Edge API endpoint for the US West (Oregon) Region is the following.

```
snowball.us-west-2.amazonaws.com
```

For a list of AWS Regions that Snowball Edge supports (where you can create and manage jobs), see [AWS Import/Export](#) in the *AWS General Reference*.

The region-specific API endpoint defines the scope of the Snowball Edge resources that are accessible when you make an API call. For example, when you call the `ListJobs` operation using the preceding endpoint, you get a list of jobs in the US West (Oregon) Region that have been created in your account.

API Version

The version of the API being used for a call is identified by the first path segment of the request URI, and its form is an ISO 8601 date. The documentation describes API version 2016-06-30.

API Permission Policy Reference

The following policies are needed for creating jobs with the job management API for Snowball Edge.

Role Trust Policy for Creating Jobs

Using the job management API to create jobs requires the following trust policy.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "",
      "Effect": "Allow",
      "Principal": {
        "Service": "importexport.amazonaws.com"
      },
      "Action": "sts:AssumeRole",
      "Condition": {
        "StringEquals": {
          "sts:ExternalId": "AWSIE"
        }
      }
    }
  ]
}
```

Note

To learn more about trust policies, see [Modifying a Role](#) in the IAM User Guide.

Role Policy for Creating Import Jobs

Creating an import job requires the following role policy.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:ListBucketMultipartUploads"
      ],
      "Resource": "arn:aws:s3:::*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketPolicy",
        "s3:PutObject",
        "s3:AbortMultipartUpload",
        "s3:ListMultipartUploadParts",
        "s3:PutObjectAcl"
      ],
      "Resource": "arn:aws:s3:::*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "snowball:*"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

Role Policy for Creating Export Jobs

Creating an export job requires the following role policy.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": "arn:aws:s3:::*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "snowball:*"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

Amazon S3 Bucket Policy Principal for Creating Jobs

In some cases, the Amazon S3 buckets that you use with Snowball Edge have bucket policies in place that require listing the role session name of the assumed role. In these cases, you need to specify a principal in those policies that identifies `AWSImportExport-Validation`. The following Amazon S3 bucket policy example demonstrates how to do so.

Example

JSON

```
{
  "Version": "2012-10-17",
```

```
"Statement": {
  "Sid": "AllowAWSSnowballToCreateJobs",
  "Effect": "Allow",
  "Principal": {
    "AWS": [
      "arn:aws:iam::111122223333:role/rolename",
      "arn:aws:sts::111122223333:assumed-role/rolename/AWSImportExport-Validation",
      "arn:aws:iam::111122223333:root"
    ]
  },
  "Action": "S3:*",
  "Resource": ["arn:aws:s3:::examplebucket/*"]
}
```

In this policy example, we deny access to all principals except the one named in the `NotPrincipal` element. For more information on how to use `NotPrincipal`, see [NotPrincipal](#) in the *IAM User Guide*.

Note

For jobs in AWS GovCloud (US), Snowball Edge uses `AWSIEJob` as the role session name of the assumed role.

Creating an IAM Role for Snowball Edge and Snowball Edge

An IAM role policy must be created with read and write permissions for your Amazon S3 buckets. The IAM role must also have a trust relationship with Snowball Edge. Having a trust relationship means that AWS can write the data in the Snowball and in your Amazon S3 buckets, depending on whether you're importing or exporting data.

When you create a job in the AWS Snow Family Management Console, creating the necessary IAM role occurs in step 4 in the **Permission** section. This process is automatic. The IAM role that you allow Snowball Edge to assume is only used to write your data to your bucket when the Snowball with your transferred data arrives at AWS. The following procedure outlines that process.

To create the IAM role for your import job

1. Sign in to the AWS Management Console and open the AWS Snowball Edge console at <https://console.aws.amazon.com/importexport/>.
2. Choose **Create job**.
3. In the first step, fill out the details for your import job into Amazon S3, and then choose **Next**.
4. In the second step, under **Permission**, choose **Create/Select IAM Role**.

The IAM Management Console opens, showing the IAM role that AWS uses to copy objects into your specified Amazon S3 buckets.

5. Review the details on this page, and then choose **Allow**.

You return to the AWS Snow Family Management Console, where **Selected IAM role ARN** contains the Amazon Resource Name (ARN) for the IAM role that you just created.

6. Choose **Next** to finish creating your IAM role.

The preceding procedure creates an IAM role that has write permissions for the Amazon S3 buckets that you plan to import your data into. The IAM role that is created has one of the following structures, depending on whether it's for an import job or export job.

IAM Role for an Import Job

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:ListBucketMultipartUploads"
      ],
      "Resource": "arn:aws:s3:::*"
    },
    {
      "Effect": "Allow",
      "Action": [
```

```

        "s3:GetBucketPolicy",
        "s3:PutObject",
        "s3:AbortMultipartUpload",
        "s3:ListMultipartUploadParts",
        "s3:PutObjectAcl"
    ],
    "Resource": "arn:aws:s3:::*"
}
]
}

```

If you use server-side encryption with AWS KMS–managed keys (SSE-KMS) to encrypt the Amazon S3 buckets associated with your import job, you also need to add the following statement to your IAM role.

```

{
  "Effect": "Allow",
  "Action": [
    "kms:GenerateDataKey"
  ],
  "Resource": "arn:aws:s3:::SSEKMSEncryptedBucketName"
}

```

IAM Role for an Export Job

JSON

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:GetBucketPolicy",
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": "arn:aws:s3:::*"
    }
  ]
}

```

```
]
}
```

If you use server-side encryption with AWS KMS–managed keys to encrypt the Amazon S3 buckets associated with your export job, you also need to add the following statement to your IAM role.

```
{
  "Effect": "Allow",
  "Action": [
    "kms:Decrypt"
  ],
  "Resource": "arn:aws:s3:::SSEKMSEncryptedBucketName"
}
```

Actions

The following actions are supported by AWS Snowball Edge:

- [CancelCluster](#)
- [CancelJob](#)
- [CreateAddress](#)
- [CreateCluster](#)
- [CreateJob](#)
- [CreateLongTermPricing](#)
- [CreateReturnShippingLabel](#)
- [DescribeAddress](#)
- [DescribeAddresses](#)
- [DescribeCluster](#)
- [DescribeJob](#)
- [DescribeReturnShippingLabel](#)
- [GetJobManifest](#)
- [GetJobUnlockCode](#)
- [GetSnowballUsage](#)
- [GetSoftwareUpdates](#)
- [ListClusterJobs](#)
- [ListClusters](#)
- [ListCompatibleImages](#)
- [ListJobs](#)
- [ListLongTermPricing](#)
- [ListPickupLocations](#)
- [ListServiceVersions](#)
- [UpdateCluster](#)
- [UpdateJob](#)
- [UpdateJobShipmentState](#)
- [UpdateLongTermPricing](#)

The following actions are supported by AWS Snowball Edge Device Management:

- [CancelTask](#)
- [CreateTask](#)
- [DescribeDevice](#)
- [DescribeDeviceEc2Instances](#)
- [DescribeExecution](#)
- [DescribeTask](#)
- [ListDeviceResources](#)
- [ListDevices](#)
- [ListExecutions](#)
- [ListTagsForResource](#)
- [ListTasks](#)
- [TagResource](#)
- [UntagResource](#)

AWS Snowball Edge

The following actions are supported by AWS Snowball Edge:

- [CancelCluster](#)
- [CancelJob](#)
- [CreateAddress](#)
- [CreateCluster](#)
- [CreateJob](#)
- [CreateLongTermPricing](#)
- [CreateReturnShippingLabel](#)
- [DescribeAddress](#)
- [DescribeAddresses](#)
- [DescribeCluster](#)
- [DescribeJob](#)
- [DescribeReturnShippingLabel](#)

- [GetJobManifest](#)
- [GetJobUnlockCode](#)
- [GetSnowballUsage](#)
- [GetSoftwareUpdates](#)
- [ListClusterJobs](#)
- [ListClusters](#)
- [ListCompatibleImages](#)
- [ListJobs](#)
- [ListLongTermPricing](#)
- [ListPickupLocations](#)
- [ListServiceVersions](#)
- [UpdateCluster](#)
- [UpdateJob](#)
- [UpdateJobShipmentState](#)
- [UpdateLongTermPricing](#)

CancelCluster

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Cancels a cluster job. You can only cancel a cluster job while it's in the `AwaitingQuorum` status. You'll have at least an hour after creating a cluster job to cancel it.

Request Syntax

```
{
  "ClusterId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClusterId

The 39-character ID for the cluster that you want to cancel, for example `CID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelJob

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Cancels the specified job. You can only cancel a job before its JobState value changes to PreparingAppliance. Requesting the ListJobs or DescribeJob action returns a job's JobState as part of the response element data returned.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The 39-character job ID for the job that you want to cancel, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAddress

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Creates an address for a Snow device to be shipped to. Addresses are validated at the time of creation. The address you provide must be located within the serviceable area of your region. If the address is invalid or unsupported, then an exception is thrown. If providing an address as a JSON file through the `cli-input-json` option, include the full file path. For example, `--cli-input-json file://create-address.json`.

Request Syntax

```
{
  "Address": {
    "AddressId": "string",
    "City": "string",
    "Company": "string",
    "Country": "string",
    "IsRestricted": boolean,
    "Landmark": "string",
    "Name": "string",
    "PhoneNumber": "string",
    "PostalCode": "string",
    "PrefectureOrDistrict": "string",
    "StateOrProvince": "string",
    "Street1": "string",
    "Street2": "string",
    "Street3": "string",
    "Type": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Address

The address that you want the Snow device shipped to.

Type: [Address](#) object

Required: Yes

Response Syntax

```
{  
  "AddressId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddressId

The automatically generated ID for a specific address. You'll use this ID when you create a job to specify which address you want the Snow device for that job shipped to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidAddressException

The address provided was invalid. Check the address with your region's carrier, and try again.

HTTP Status Code: 400

UnsupportedAddressException

The address is either outside the serviceable area for your region, or an error occurred. Check the address with your region's carrier and try again. If the issue persists, contact Support.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCluster

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Creates an empty cluster. Each cluster supports five nodes. You use the [CreateJob](#) action separately to create the jobs for each of these nodes. The cluster does not ship until these five node jobs have been created.

Request Syntax

```
{
  "AddressId": "string",
  "Description": "string",
  "ForceCreateJobs": boolean,
  "ForwardingAddressId": "string",
  "InitialClusterSize": number,
  "JobType": "string",
  "KmsKeyARN": "string",
  "LongTermPricingIds": [ "string" ],
  "Notification": {
    "DevicePickupSnsTopicARN": "string",
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "OnDeviceServiceConfiguration": {
    "EKSONDeviceService": {
      "EKSAnywhereVersion": "string",
      "KubernetesVersion": "string"
    },
    "NFSOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "S3OnDeviceService": {
```

```

    "FaultTolerance": number,
    "ServiceSize": number,
    "StorageLimit": number,
    "StorageUnit": "string"
  },
  "TGWOnDeviceService": {
    "StorageLimit": number,
    "StorageUnit": "string"
  }
},
"RemoteManagement": "string",
"Resources": {
  "Ec2AmiResources": [
    {
      "AmiId": "string",
      "SnowballAmiId": "string"
    }
  ],
  "LambdaResources": [
    {
      "EventTriggers": [
        {
          "EventResourceARN": "string"
        }
      ],
      "LambdaArn": "string"
    }
  ],
  "S3Resources": [
    {
      "BucketArn": "string",
      "KeyRange": {
        "BeginMarker": "string",
        "EndMarker": "string"
      },
      "TargetOnDeviceServices": [
        {
          "ServiceName": "string",
          "TransferOption": "string"
        }
      ]
    }
  ]
}
},

```

```

"RoleARN": "string",
"ShippingOption": "string",
"SnowballCapacityPreference": "string",
"SnowballType": "string",
"TaxDocuments": {
  "IND": {
    "GSTIN": "string"
  }
}
}

```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressId

The ID for the address that you want the cluster shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Description

An optional description of this specific cluster, for example Environmental Data Cluster-01.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

ForceCreateJobs

Force to create cluster when user attempts to overprovision or underprovision a cluster. A cluster is overprovisioned or underprovisioned if the initial size of the cluster is more

(overprovisioned) or less (underprovisioned) than what needed to meet capacity requirement specified with `OnDeviceServiceConfiguration`.

Type: Boolean

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

InitialClusterSize

If provided, each job will be automatically created and associated with the new cluster. If not provided, will be treated as 0.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 16.

Required: No

JobType

The type of job for this cluster. Currently, the only job type supported for clusters is LOCAL_USE.

For information about Snowball Edge device types, [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: Yes

KmsKeyARN

The KmsKeyARN value that you want to associate with this cluster. KmsKeyARN values are created by using the [CreateKey](#) API action in AWS Key Management Service (AWS KMS).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:kms:.*:[0-9]{12}:key/.*`

Required: No

LongTermPricingIds

Lists long-term pricing id that will be used to associate with jobs automatically created for the new cluster.

Type: Array of strings

Length Constraints: Fixed length of 41.

Pattern: `LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings for this cluster.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Specifies the service or services on the Snowball Edge device that your transferred data will be exported from or imported into. AWS Snowball Edge device clusters support Amazon S3 and NFS (Network File System).

Type: [OnDeviceServiceConfiguration](#) object

Required: No

RemoteManagement

Allows you to securely operate and manage Snow devices in a cluster remotely from outside of your internal network. When set to `INSTALLED_AUTOSTART`, remote management will automatically be available when the device arrives at your location. Otherwise, you need to use the Snowball Client to manage the device.

Type: String

Valid Values: `INSTALLED_ONLY` | `INSTALLED_AUTOSTART` | `NOT_INSTALLED`

Required: No

Resources

The resources associated with the cluster job. These resources include Amazon S3 buckets and optional AWS Lambda functions written in the Python language.

Type: [JobResource](#) object

Required: No

RoleARN

The RoleARN that you want to associate with this cluster. RoleArn values are created by using the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam:[0-9]{12}:role/.*`

Required: No

ShippingOption

The shipping speed for each node in this cluster. This speed doesn't dictate how soon you'll get each Snowball Edge device, rather it represents how quickly each device moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the United States of America (US), you have access to one-day shipping and two-day shipping.

- In Australia, you have access to express shipping. Typically, devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: SECOND_DAY | NEXT_DAY | EXPRESS | STANDARD

Required: Yes

SnowballCapacityPreference

If your job is being created in one of the US regions, you have the option of specifying what size Snow device you'd like for this job. In all other regions, Snowballs come with 80 TB in storage capacity.

For information about Snowball Edge device types, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: T50 | T80 | T100 | T42 | T98 | T8 | T14 | T32 | NoPreference | T240 | T13

Required: No

SnowballType

The type of Snow Family devices to use for this cluster.

Note

For cluster jobs, AWS Snowball Edge currently supports only the EDGE device type.

For information about Snowball Edge device types, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: Yes

TaxDocuments

The tax documents required in your AWS Region.

Type: [TaxDocuments](#) object

Required: No

Response Syntax

```
{
  "ClusterId": "string",
  "JobListEntries": [
    {
      "CreationDate": number,
      "Description": "string",
      "IsMaster": boolean,
      "JobId": "string",
      "JobState": "string",
      "JobType": "string",
      "SnowballType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterId

The automatically generated ID for a cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

JobListEntries

List of jobs created for this cluster. For syntax, see [ListJobsResult\\$JobListEntries](#) in this guide.

Type: Array of [JobListEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

Ec2RequestFailedException

Your user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) value supports your [CreateJob:JobType](#), and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateJob

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Creates a job to import or export data between Amazon S3 and your on-premises data center. Your AWS account must have the right trust policies and permissions in place to create a job for a Snow device. If you're creating a job for a node in a cluster, you only need to provide the `clusterId` value; the other job attributes are inherited from the cluster.

Note

Only the Snowball Edge device type is supported when ordering clustered jobs. The device capacity is optional. Availability of device types differ by AWS Region. For more information about Region availability, see [AWS Regional Services](#).

Snow Family devices and their capacities.

- Device type: **V3_5C**
 - Capacity: T32
 - Description: Snowball Edge Compute Optimized
- Device type: **V3_5S**
 - Capacity: T240
 - Description: Snowball Edge Storage Optimized 210TB

Request Syntax

```
{
```

```
"AddressId": "string",
"ClusterId": "string",
"Description": "string",
"DeviceConfiguration": {
  "SnowconeDeviceConfiguration": {
    "WirelessConnection": {
      "IsWifiEnabled": boolean
    }
  }
},
"ForwardingAddressId": "string",
"ImpactLevel": "string",
"JobType": "string",
"KmsKeyARN": "string",
"LongTermPricingId": "string",
"Notification": {
  "DevicePickupSnsTopicARN": "string",
  "JobStatesToNotify": [ "string" ],
  "NotifyAll": boolean,
  "SnsTopicARN": "string"
},
"OnDeviceServiceConfiguration": {
  "EKSONDeviceService": {
    "EKSAnywhereVersion": "string",
    "KubernetesVersion": "string"
  },
  "NFSOnDeviceService": {
    "StorageLimit": number,
    "StorageUnit": "string"
  },
  "S3OnDeviceService": {
    "FaultTolerance": number,
    "ServiceSize": number,
    "StorageLimit": number,
    "StorageUnit": "string"
  },
  "TGWOnDeviceService": {
    "StorageLimit": number,
    "StorageUnit": "string"
  }
},
"PickupDetails": {
  "DevicePickupId": "string",
  "Email": "string",
```

```

    "IdentificationExpirationDate": number,
    "IdentificationIssuingOrg": "string",
    "IdentificationNumber": "string",
    "Name": "string",
    "PhoneNumber": "string"
  },
  "RemoteManagement": "string",
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        },
        "TargetOnDeviceServices": [
          {
            "ServiceName": "string",
            "TransferOption": "string"
          }
        ]
      }
    ]
  }
},
"RoleARN": "string",
"ShippingOption": "string",
"SnowballCapacityPreference": "string",
"SnowballType": "string",

```

```
"TaxDocuments": {
  "IND": {
    "GSTIN": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressId

The ID for the address that you want the Snow device shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId

The ID of a cluster. If you're creating a job for a node in a cluster, you need to provide only this `clusterId` value. The other job attributes are inherited from the cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Description

Defines an optional description of this specific job, for example `Important Photos 2016-08-11`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9\s\-_\.\:]+$`

Required: No

DeviceConfiguration

Defines the device configuration for an AWS Snowball Edge job.

For information about Snowball Edge device types, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: [DeviceConfiguration](#) object

Required: No

ForwardingAddressId

This field is not supported in your Region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: `ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

ImpactLevel

The highest impact level of data that will be stored or processed on the device, provided at job creation.

Type: String

Valid Values: IL2 | IL4 | IL5 | IL6 | IL99

Required: No

JobType

Defines the type of job that you're creating.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

KmsKeyARN

The KmsKeyARN that you want to associate with this job. KmsKeyARNs are created using the [CreateKey](#) AWS Key Management Service (KMS) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:kms:.*:[0-9]{12}:key/.*

Required: No

LongTermPricingId

The ID of the long-term pricing type for the device.

Type: String

Length Constraints: Fixed length of 41.

Pattern: LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Notification

Defines the Amazon Simple Notification Service (Amazon SNS) notification settings for this job.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Specifies the service or services on the Snow Family device that your transferred data will be exported from or imported into. AWS Snow Family supports Amazon S3 and NFS (Network File System).

Type: [OnDeviceServiceConfiguration](#) object

Required: No

PickupDetails

Information identifying the person picking up the device.

Type: [PickupDetails](#) object

Required: No

RemoteManagement

Allows you to securely operate and manage Snowcone devices remotely from outside of your internal network. When set to `INSTALLED_AUTOSTART`, remote management will automatically be available when the device arrives at your location. Otherwise, you need to use the Snowball Edge client to manage the device. When set to `NOT_INSTALLED`, remote management will not be available on the device.

Type: String

Valid Values: `INSTALLED_ONLY` | `INSTALLED_AUTOSTART` | `NOT_INSTALLED`

Required: No

Resources

Defines the Amazon S3 buckets associated with this job.

With `IMPORT` jobs, you specify the bucket or buckets that your transferred data will be imported into.

With `EXPORT` jobs, you specify the bucket or buckets that your transferred data will be exported from. Optionally, you can also specify a `KeyRange` value. If you choose to export a range, you define the length of the range by providing either an inclusive `BeginMarker` value, an inclusive `EndMarker` value, or both. Ranges are UTF-8 binary sorted.

Type: [JobResource](#) object

Required: No

RoleARN

The `RoleARN` that you want to associate with this job. `RoleArns` are created using the [CreateRole](#) AWS Identity and Access Management (IAM) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingOption

The shipping speed for this job. This speed doesn't dictate how soon you'll get the Snow device, rather it represents how quickly the Snow device moves to its destination while in transit.

Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

SnowballCapacityPreference

If your job is being created in one of the US regions, you have the option of specifying what size Snow device you'd like for this job. In all other regions, Snowballs come with 80 TB in storage capacity.

For information about Snowball Edge device types, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: `T50` | `T80` | `T100` | `T42` | `T98` | `T8` | `T14` | `T32` | `NoPreference` | `T240` | `T13`

Required: No

SnowballType

The type of Snow Family devices to use for this job.

Note

For cluster jobs, AWS Snowball Edge currently supports only the EDGE device type.

The type of AWS Snow device to use for this job. Currently, the only supported device type for cluster jobs is EDGE.

For more information, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: No

TaxDocuments

The tax documents required in your AWS Region.

Type: [TaxDocuments](#) object

Required: No

Response Syntax

```
{
  "JobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ClusterLimitExceededException

Job creation failed. Currently, clusters support five nodes. If you have fewer than five nodes for your cluster and you have more nodes to create for this cluster, try again and create jobs until your cluster has exactly five nodes.

HTTP Status Code: 400

Ec2RequestFailedException

Your user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) value supports your [CreateJob:JobType](#), and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateLongTermPricing

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Creates a job with the long-term usage option for a device. The long-term usage is a 1-year or 3-year long-term pricing type for the device. You are billed upfront, and AWS provides discounts for long-term pricing.

Request Syntax

```
{
  "IsLongTermPricingAutoRenew": boolean,
  "LongTermPricingType": "string",
  "SnowballType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[IsLongTermPricingAutoRenew](#)

Specifies whether the current long-term pricing type for the device should be renewed.

Type: Boolean

Required: No

[LongTermPricingType](#)

The type of long-term pricing option you want for the device, either 1-year or 3-year long-term pricing.

Type: String

Valid Values: OneYear | ThreeYear | OneMonth

Required: Yes

SnowballType

The type of Snow Family devices to use for the long-term pricing job.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: Yes

Response Syntax

```
{
  "LongTermPricingId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LongTermPricingId

The ID of the long-term pricing type for the device.

Type: String

Length Constraints: Fixed length of 41.

Pattern: LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateReturnShippingLabel

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Creates a shipping label that will be used to return the Snow device to AWS.

Request Syntax

```
{
  "JobId": "string",
  "ShippingOption": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The ID for a job that you want to create the return shipping label for; for example, JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

ShippingOption

The shipping speed for a particular job. This speed doesn't dictate how soon the device is returned to AWS. This speed represents how quickly it moves to its destination while in transit. Regional shipping speeds are as follows:

Type: String

Valid Values: SECOND_DAY | NEXT_DAY | EXPRESS | STANDARD

Required: No

Response Syntax

```
{  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Status

The status information of the task on a Snow device that is being returned to AWS.

Type: String

Valid Values: InProgress | TimedOut | Succeeded | Failed

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

You get this exception when you call `CreateReturnShippingLabel` more than once when other requests are not completed.

ConflictResource

You get this resource when you call `CreateReturnShippingLabel` more than once when other requests are not completed. .

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) value supports your [CreateJob:JobType](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

ReturnShippingLabelAlreadyExistsException

You get this exception if you call `CreateReturnShippingLabel` and a valid return shipping label already exists. In this case, use `DescribeReturnShippingLabel` to get the URL.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAddress

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Takes an AddressId and returns specific details about that address in the form of an Address object.

Request Syntax

```
{
  "AddressId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressId

The automatically generated ID for a specific address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
```

```
"Address": {
  "AddressId": "string",
  "City": "string",
  "Company": "string",
  "Country": "string",
  "IsRestricted": boolean,
  "Landmark": "string",
  "Name": "string",
  "PhoneNumber": "string",
  "PostalCode": "string",
  "PrefectureOrDistrict": "string",
  "StateOrProvince": "string",
  "Street1": "string",
  "Street2": "string",
  "Street3": "string",
  "Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

The address that you want the Snow device(s) associated with a specific job to be shipped to.

Type: [Address](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAddresses

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns a specified number of ADDRESS objects. Calling this API in one of the US regions will return addresses from the list of all addresses associated with this account in all US regions.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The number of ADDRESS objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of ADDRESS objects, you have the option of specifying a value for NextToken as the starting point for your list of returned addresses.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "Addresses": [
    {
      "AddressId": "string",
      "City": "string",
      "Company": "string",
      "Country": "string",
      "IsRestricted": boolean,
      "Landmark": "string",
      "Name": "string",
      "PhoneNumber": "string",
      "PostalCode": "string",
      "PrefectureOrDistrict": "string",
      "StateOrProvince": "string",
      "Street1": "string",
      "Street2": "string",
      "Street3": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Addresses

The Snow device shipping addresses that were created for this account.

Type: Array of [Address](#) objects

NextToken

HTTP requests are stateless. If you use the automatically generated NextToken value in your next DescribeAddresses call, your list of returned addresses will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCluster

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns information about a specific cluster including shipping information, cluster status, and other important metadata.

Request Syntax

```
{
  "ClusterId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClusterId

The automatically generated ID for a cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
  "ClusterMetadata": {
```

```

"AddressId": "string",
"ClusterId": "string",
"ClusterState": "string",
"CreationDate": number,
"Description": "string",
"ForwardingAddressId": "string",
"JobType": "string",
"KmsKeyARN": "string",
"Notification": {
  "DevicePickupSnsTopicARN": "string",
  "JobStatesToNotify": [ "string" ],
  "NotifyAll": boolean,
  "SnsTopicARN": "string"
},
"OnDeviceServiceConfiguration": {
  "EKSONDeviceService": {
    "EKSAnywhereVersion": "string",
    "KubernetesVersion": "string"
  },
  "NFSOnDeviceService": {
    "StorageLimit": number,
    "StorageUnit": "string"
  },
  "S3OnDeviceService": {
    "FaultTolerance": number,
    "ServiceSize": number,
    "StorageLimit": number,
    "StorageUnit": "string"
  },
  "TGWOnDeviceService": {
    "StorageLimit": number,
    "StorageUnit": "string"
  }
},
"Resources": {
  "Ec2AmiResources": [
    {
      "AmiId": "string",
      "SnowballAmiId": "string"
    }
  ],
  "LambdaResources": [
    {
      "EventTriggers": [

```

```

        {
            "EventResourceARN": "string"
        }
    ],
    "LambdaArn": "string"
}
],
"S3Resources": [
    {
        "BucketArn": "string",
        "KeyRange": {
            "BeginMarker": "string",
            "EndMarker": "string"
        },
        "TargetOnDeviceServices": [
            {
                "ServiceName": "string",
                "TransferOption": "string"
            }
        ]
    }
]
},
"RoleARN": "string",
"ShippingOption": "string",
"SnowballType": "string",
"TaxDocuments": {
    "IND": {
        "GSTIN": "string"
    }
}
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterMetadata

Information about a specific cluster, including shipping information, cluster status, and other important metadata.

Type: [ClusterMetadata](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeJob

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns information about a specific job including shipping information, job status, and other important metadata.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
  "JobMetadata": {
    "AddressId": "string",
    "ClusterId": "string",
    "CreationDate": number,
    "DataTransferProgress": {
      "BytesTransferred": number,
      "ObjectsTransferred": number,
      "TotalBytes": number,
      "TotalObjects": number
    },
    "Description": "string",
    "DeviceConfiguration": {
      "SnowconeDeviceConfiguration": {
        "WirelessConnection": {
          "IsWifiEnabled": boolean
        }
      }
    },
    "ForwardingAddressId": "string",
    "ImpactLevel": "string",
    "JobId": "string",
    "JobLogInfo": {
      "JobCompletionReportURI": "string",
      "JobFailureLogURI": "string",
      "JobSuccessLogURI": "string"
    },
    "JobState": "string",
    "JobType": "string",
    "KmsKeyARN": "string",
    "LongTermPricingId": "string",
    "Notification": {
      "DevicePickupSnsTopicARN": "string",
      "JobStatesToNotify": [ "string" ],
      "NotifyAll": boolean,
      "SnsTopicARN": "string"
    },
    "OnDeviceServiceConfiguration": {
      "EKSONDeviceService": {
        "EKSAnywhereVersion": "string",
        "KubernetesVersion": "string"
      }
    }
  }
}
```

```

    },
    "NFSOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "S3OnDeviceService": {
      "FaultTolerance": number,
      "ServiceSize": number,
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "TGWOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  },
  "PickupDetails": {
    "DevicePickupId": "string",
    "Email": "string",
    "IdentificationExpirationDate": number,
    "IdentificationIssuingOrg": "string",
    "IdentificationNumber": "string",
    "Name": "string",
    "PhoneNumber": "string"
  },
  "RemoteManagement": "string",
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [

```

```

    {
      "BucketArn": "string",
      "KeyRange": {
        "BeginMarker": "string",
        "EndMarker": "string"
      },
      "TargetOnDeviceServices": [
        {
          "ServiceName": "string",
          "TransferOption": "string"
        }
      ]
    }
  ],
  "RoleARN": "string",
  "ShippingDetails": {
    "InboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "OutboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "ShippingOption": "string"
  },
  "SnowballCapacityPreference": "string",
  "SnowballId": "string",
  "SnowballType": "string",
  "TaxDocuments": {
    "IND": {
      "GSTIN": "string"
    }
  }
},
"SubJobMetadata": [
  {
    "AddressId": "string",
    "ClusterId": "string",
    "CreationDate": number,
    "DataTransferProgress": {
      "BytesTransferred": number,
      "ObjectsTransferred": number,

```

```

    "TotalBytes": number,
    "TotalObjects": number
  },
  "Description": "string",
  "DeviceConfiguration": {
    "SnowconeDeviceConfiguration": {
      "WirelessConnection": {
        "IsWifiEnabled": boolean
      }
    }
  },
  "ForwardingAddressId": "string",
  "ImpactLevel": "string",
  "JobId": "string",
  "JobLogInfo": {
    "JobCompletionReportURI": "string",
    "JobFailureLogURI": "string",
    "JobSuccessLogURI": "string"
  },
  "JobState": "string",
  "JobType": "string",
  "KmsKeyARN": "string",
  "LongTermPricingId": "string",
  "Notification": {
    "DevicePickupSnsTopicARN": "string",
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "OnDeviceServiceConfiguration": {
    "EKSONDeviceService": {
      "EKSAnywhereVersion": "string",
      "KubernetesVersion": "string"
    },
    "NFSOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "S3OnDeviceService": {
      "FaultTolerance": number,
      "ServiceSize": number,
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  },
},

```

```
    "TGWOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  },
  "PickupDetails": {
    "DevicePickupId": "string",
    "Email": "string",
    "IdentificationExpirationDate": number,
    "IdentificationIssuingOrg": "string",
    "IdentificationNumber": "string",
    "Name": "string",
    "PhoneNumber": "string"
  },
  "RemoteManagement": "string",
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        },
        "TargetOnDeviceServices": [
          {
            "ServiceName": "string",
            "TransferOption": "string"
          }
        ]
      }
    ]
  }
}
```

```

    ]
  }
]
},
"RoleARN": "string",
"ShippingDetails": {
  "InboundShipment": {
    "Status": "string",
    "TrackingNumber": "string"
  },
  "OutboundShipment": {
    "Status": "string",
    "TrackingNumber": "string"
  },
  "ShippingOption": "string"
},
"SnowballCapacityPreference": "string",
"SnowballId": "string",
"SnowballType": "string",
"TaxDocuments": {
  "IND": {
    "GSTIN": "string"
  }
}
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobMetadata

Information about a specific job, including shipping information, job status, and other important metadata.

Type: [JobMetadata](#) object

SubJobMetadata

Information about a specific job part (in the case of an export job), including shipping information, job status, and other important metadata.

Type: Array of [JobMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeReturnShippingLabel

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Information on the shipping label of a Snow device that is being returned to AWS.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
```

```
"ExpirationDate": number,  
"ReturnShippingLabelURI": "string",  
"Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExpirationDate

The expiration date of the current return shipping label.

Type: Timestamp

ReturnShippingLabelURI

The pre-signed Amazon S3 URI used to download the return shipping label.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Status

The status information of the task on a Snow device that is being returned to AWS.

Type: String

Valid Values: InProgress | TimedOut | Succeeded | Failed

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

You get this exception when you call `CreateReturnShippingLabel` more than once when other requests are not completed.

ConflictResource

You get this resource when you call `CreateReturnShippingLabel` more than once when other requests are not completed. .

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJobManifest

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns a link to an Amazon S3 presigned URL for the manifest file associated with the specified `JobId` value. You can access the manifest file for up to 60 minutes after this request has been made. To access the manifest file after 60 minutes have passed, you'll have to make another call to the `GetJobManifest` action.

The manifest is an encrypted file that you can download after your job enters the `WithCustomer` status. This is the only valid status for calling this API as the manifest and `UnlockCode` code value are used for securing your device and should only be used when you have the device. The manifest is decrypted by using the `UnlockCode` code value, when you pass both values to the Snow device through the Snowball client when the client is started for the first time.

As a best practice, we recommend that you don't save a copy of an `UnlockCode` value in the same location as the manifest file for that job. Saving these separately helps prevent unauthorized parties from gaining access to the Snow device associated with that job.

The credentials of a given job, including its manifest file and unlock code, expire 360 days after the job is created.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The ID for a job that you want to get the manifest file for, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "ManifestURI": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManifestURI

The Amazon S3 presigned URL for the manifest file associated with the specified JobId value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJobUnlockCode

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns the `UnlockCode` code value for the specified job. A particular `UnlockCode` value can be accessed for up to 360 days after the associated job has been created.

The `UnlockCode` value is a 29-character code with 25 alphanumeric characters and 4 hyphens. This code is used to decrypt the manifest file when it is passed along with the manifest to the Snow device through the Snowball client when the client is started for the first time. The only valid status for calling this API is `WithCustomer` as the manifest and `Unlock` code values are used for securing your device and should only be used when you have the device.

As a best practice, we recommend that you don't save a copy of the `UnlockCode` in the same location as the manifest file for that job. Saving these separately helps prevent unauthorized parties from gaining access to the Snow device associated with that job.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The ID for the job that you want to get the `UnlockCode` value for, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
  "UnlockCode": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnlockCode

The `UnlockCode` value for the specified job. The `UnlockCode` value can be accessed for up to 360 days after the job has been created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSnowballUsage

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns information about the Snowball Edge service limit for your account, and also the number of Snow devices your account has in use.

The default service limit for the number of Snow devices that you can have at one time is 1. If you want to increase your service limit, contact AWS Support.

Response Syntax

```
{
  "SnowballLimit": number,
  "SnowballsInUse": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SnowballLimit

The service limit for number of Snow devices this account can have at once. The default service limit is 1 (one).

Type: Integer

SnowballsInUse

The number of Snow devices that this account is currently using.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSoftwareUpdates

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns an Amazon S3 presigned URL for an update file associated with a specified JobId.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The ID for a job that you want to get the software update file for, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
```

```
"UpdatesURI": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UpdatesURI

The Amazon S3 presigned URL for the update file associated with the specified JobId value. The software update will be available for 2 days after this request is made. To access an update after the 2 days have passed, you'll have to make another call to GetSoftwareUpdates.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListClusterJobs

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns an array of JobListEntry objects of the specified length. Each JobListEntry object is for a job in the specified cluster and contains a job's state, a job's ID, and other information.

Request Syntax

```
{
  "ClusterId": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClusterId

The 39-character ID for the cluster that you want to list, for example CID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

MaxResults

The number of `JobListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of `JobListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

Response Syntax

```
{
  "JobListEntries": [
    {
      "CreationDate": number,
      "Description": "string",
      "IsMaster": boolean,
      "JobId": "string",
      "JobState": "string",
      "JobType": "string",
      "SnowballType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobListEntries

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs.

Type: Array of [JobListEntry](#) objects

NextToken

HTTP requests are stateless. If you use the automatically generated `NextToken` value in your next `ListClusterJobsResult` call, your list of returned jobs will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListClusters

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns an array of `ClusterListEntry` objects of the specified length. Each `ClusterListEntry` object contains a cluster's state, a cluster's ID, and other important status information.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The number of `ClusterListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of `ClusterListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "ClusterListEntries": [
    {
      "ClusterId": "string",
      "ClusterState": "string",
      "CreationDate": number,
      "Description": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterListEntries

Each `ClusterListEntry` object contains a cluster's state, a cluster's ID, and other important status information.

Type: Array of [ClusterListEntry](#) objects

NextToken

HTTP requests are stateless. If you use the automatically generated `NextToken` value in your next `ClusterListEntry` call, your list of returned clusters will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCompatibleImages

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

This action returns a list of the different Amazon EC2-compatible Amazon Machine Images (AMIs) that are owned by your AWS account that would be supported for use on a Snow device. Currently, supported AMIs are based on the Amazon Linux-2, Ubuntu 20.04 LTS - Focal, or Ubuntu 22.04 LTS - Jammy images, available on the AWS Marketplace. Ubuntu 16.04 LTS - Xenial (HVM) images are no longer supported in the Market, but still supported for use on devices through Amazon EC2 VM Import/Export and running locally in AMIs.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results for the list of compatible images. Currently, a Snowball Edge device can store 10 AMIs.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of compatible images, you can specify a value for NextToken as the starting point for your list of returned images.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "CompatibleImages": [
    {
      "AmiId": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CompatibleImages

A JSON-formatted object that describes a compatible AMI, including the ID and name for a Snow device AMI.

Type: Array of [CompatibleImage](#) objects

NextToken

Because HTTP requests are stateless, this is the starting point for your next list of returned images.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

Ec2RequestFailedException

Your user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListJobs

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Returns an array of `JobListEntry` objects of the specified length. Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs. Calling this API action in one of the US regions will return jobs from the list of all jobs associated with this account in all US regions.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The number of `JobListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of `JobListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "JobListEntries": [
    {
      "CreationDate": number,
      "Description": "string",
      "IsMaster": boolean,
      "JobId": "string",
      "JobState": "string",
      "JobType": "string",
      "SnowballType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobListEntries

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs.

Type: Array of [JobListEntry](#) objects

NextToken

HTTP requests are stateless. If you use this automatically generated NextToken value in your next ListJobs call, your returned JobListEntry objects will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListLongTermPricing

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Lists all long-term pricing types.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of ListLongTermPricing objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

Because HTTP requests are stateless, this is the starting point for your next list of ListLongTermPricing to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "LongTermPricingEntries": [
    {
      "CurrentActiveJob": "string",
      "IsLongTermPricingAutoRenew": boolean,
      "JobIds": [ "string" ],
      "LongTermPricingEndDate": number,
      "LongTermPricingId": "string",
      "LongTermPricingStartDate": number,
      "LongTermPricingStatus": "string",
      "LongTermPricingType": "string",
      "ReplacementJob": "string",
      "SnowballType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LongTermPricingEntries

Each LongTermPricingEntry object contains a status, ID, and other information about the LongTermPricing type.

Type: Array of [LongTermPricingListEntry](#) objects

NextToken

Because HTTP requests are stateless, this is the starting point for your next list of returned ListLongTermPricing list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPickupLocations

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

A list of locations from which the customer can choose to pickup a device.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of locations to list per page.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

[NextToken](#)

HTTP requests are stateless. To identify what object comes "next" in the list of ListPickupLocationsRequest objects, you have the option of specifying NextToken as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "Addresses": [
    {
      "AddressId": "string",
      "City": "string",
      "Company": "string",
      "Country": "string",
      "IsRestricted": boolean,
      "Landmark": "string",
      "Name": "string",
      "PhoneNumber": "string",
      "PostalCode": "string",
      "PrefectureOrDistrict": "string",
      "StateOrProvince": "string",
      "Street1": "string",
      "Street2": "string",
      "Street3": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Addresses

Information about the address of pickup locations.

Type: Array of [Address](#) objects

NextToken

HTTP requests are stateless. To identify what object comes "next" in the list of `ListPickupLocationsResult` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ListPickupLocations`.

```
{
  "id": "to-get-a-list-of-locations-from-which-the-customer-can-choose-to-pickup-a-device-1482542167627",
  "title": "To get a list of locations from which the customer can choose to pickup a device.",
  "description": "Returns a specified number of Address objects. Each Address is a pickup location address for Snowball Edge devices.",
  "input": {},
}
```

```
"output": {
  "Addresses": [
    {
      "City": "Seattle",
      "Name": "My Name",
      "AddressId": "ADID1234ab12-3eec-4eb3-9be6-9374c10eb51b",
      "Street1": "123 Main Street",
      "Company": "My Company",
      "PhoneNumber": "425-555-5555",
      "Country": "US",
      "PostalCode": "98101",
      "StateOrProvince": "WA"
    }
  ]
},
"comments": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceVersions

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Lists all supported versions for Snow on-device services. Returns an array of `ServiceVersion` object containing the supported versions for a particular service.

Request Syntax

```
{
  "DependentServices": [
    {
      "ServiceName": "string",
      "ServiceVersion": {
        "Version": "string"
      }
    }
  ],
  "MaxResults": number,
  "NextToken": "string",
  "ServiceName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DependentServices

A list of names and versions of dependant services of the requested service.

Type: Array of [DependentService](#) objects

Required: No

MaxResults

The maximum number of `ListServiceVersions` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken

Because HTTP requests are stateless, this is the starting point for the next list of returned `ListServiceVersionsRequest` versions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

ServiceName

The name of the service for which you're requesting supported versions.

Type: String

Valid Values: `KUBERNETES` | `EKS_ANYWHERE`

Required: Yes

Response Syntax

```
{
  "DependentServices": [
    {
      "ServiceName": "string",
      "ServiceVersion": {
        "Version": "string"
      }
    }
  ]
}
```

```
  ],
  "NextToken": "string",
  "ServiceName": "string",
  "ServiceVersions": [
    {
      "Version": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DependentServices

A list of names and versions of dependant services of the service for which the system provided supported versions.

Type: Array of [DependentService](#) objects

NextToken

Because HTTP requests are stateless, this is the starting point of the next list of returned `ListServiceVersionsResult` results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

ServiceName

The name of the service for which the system provided supported versions.

Type: String

Valid Values: KUBERNETES | EKS_ANYWHERE

ServiceVersions

A list of supported versions.

Type: Array of [ServiceVersion](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidNextTokenException

The NextToken string was altered unexpectedly, and the operation has stopped. Run the operation without changing the NextToken string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCluster

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

While a cluster's `ClusterState` value is in the `AwaitingQuorum` state, you can update some of the information associated with a cluster. Once the cluster changes to a different job state, usually 60 minutes after the cluster being created, this action is no longer available.

Request Syntax

```
{
  "AddressId": "string",
  "ClusterId": "string",
  "Description": "string",
  "ForwardingAddressId": "string",
  "Notification": {
    "DevicePickupSnsTopicARN": "string",
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "OnDeviceServiceConfiguration": {
    "EKSONDeviceService": {
      "EKSEverywhereVersion": "string",
      "KubernetesVersion": "string"
    },
    "NFSOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "S3OnDeviceService": {
      "FaultTolerance": number,
      "ServiceSize": number,
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  }
}
```

```

    },
    "TGWOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        },
        "TargetOnDeviceServices": [
          {
            "ServiceName": "string",
            "TransferOption": "string"
          }
        ]
      }
    ]
  },
  "RoleARN": "string",
  "ShippingOption": "string"
}

```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressId

The ID of the updated [Address](#) object.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId

The cluster ID of the cluster that you want to update, for example CID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Description

The updated description of this cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Notification

The new or updated [Notification](#) object.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Specifies the service or services on the Snowball Edge device that your transferred data will be exported from or imported into. AWS Snowball Edge device clusters support Amazon S3 and NFS (Network File System).

Type: [OnDeviceServiceConfiguration](#) object

Required: No

Resources

The updated arrays of [JobResource](#) objects that can include updated [S3Resource](#) objects or [LambdaResource](#) objects.

Type: [JobResource](#) object

Required: No

RoleARN

The new role Amazon Resource Name (ARN) that you want to associate with this cluster. To create a role ARN, use the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:iam:[0-9]{12}:role/.*

Required: No

ShippingOption

The updated shipping option value of this cluster's [ShippingDetails](#) object.

Type: String

Valid Values: SECOND_DAY | NEXT_DAY | EXPRESS | STANDARD

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

Ec2RequestFailedException

Your user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) value supports your [CreateJob:JobType](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateJob

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

While a job's JobState value is New, you can update some of the information associated with a job. Once the job changes to a different job state, usually within 60 minutes of the job being created, this action is no longer available.

Request Syntax

```
{
  "AddressId": "string",
  "Description": "string",
  "ForwardingAddressId": "string",
  "JobId": "string",
  "Notification": {
    "DevicePickupSnsTopicARN": "string",
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "OnDeviceServiceConfiguration": {
    "EKSONDeviceService": {
      "EKSAnywhereVersion": "string",
      "KubernetesVersion": "string"
    },
    "NFSOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    },
    "S3OnDeviceService": {
      "FaultTolerance": number,
      "ServiceSize": number,
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  }
}
```

```
    },
    "TGWOnDeviceService": {
      "StorageLimit": number,
      "StorageUnit": "string"
    }
  },
  "PickupDetails": {
    "DevicePickupId": "string",
    "Email": "string",
    "IdentificationExpirationDate": number,
    "IdentificationIssuingOrg": "string",
    "IdentificationNumber": "string",
    "Name": "string",
    "PhoneNumber": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        },
        "TargetOnDeviceServices": [
          {
            "ServiceName": "string",
            "TransferOption": "string"
          }
        ]
      }
    ]
  }
}
```

```
    ]
  }
]
},
"RoleARN": "string",
"ShippingOption": "string",
"SnowballCapacityPreference": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressId

The ID of the updated [Address](#) object.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Description

The updated description of this job's [JobMetadata](#) object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobId

The job ID of the job that you want to update, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Notification

The new or updated [Notification](#) object.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Specifies the service or services on the Snow Family device that your transferred data will be exported from or imported into. AWS Snowball Edge supports Amazon S3 and NFS (Network File System).

Type: [OnDeviceServiceConfiguration](#) object

Required: No

PickupDetails

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure

physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Information identifying the person picking up the device.

Type: [PickupDetails](#) object

Required: No

[Resources](#)

The updated JobResource object, or the updated [JobResource](#) object.

Type: [JobResource](#) object

Required: No

[RoleARN](#)

The new role Amazon Resource Name (ARN) that you want to associate with this job. To create a role ARN, use the [CreateRole](#) AWS Identity and Access Management (IAM) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam:[0-9]{12}:role/.*`

Required: No

[ShippingOption](#)

The updated shipping option value of this job's [ShippingDetails](#) object.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

[SnowballCapacityPreference](#)

The updated SnowballCapacityPreference of this job's [JobMetadata](#) object.

For information about Snowball Edge device types, see [Device hardware information](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: T50 | T80 | T100 | T42 | T98 | T8 | T14 | T32 | NoPreference | T240 | T13

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ClusterLimitExceededException

Job creation failed. Currently, clusters support five nodes. If you have fewer than five nodes for your cluster and you have more nodes to create for this cluster, try again and create jobs until your cluster has exactly five nodes.

HTTP Status Code: 400

Ec2RequestFailedException

Your user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) value supports your [CreateJob:JobType](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) or [UpdateJob](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateJobShipmentState

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Updates the state when a shipment state changes to a different state.

Request Syntax

```
{
  "JobId": "string",
  "ShipmentState": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The job ID of the job whose shipment date you want to update, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

ShipmentState

The state of a device when it is being shipped.

Set to RECEIVED when the device arrives at your location.

Set to RETURNED when you have returned the device to AWS.

Type: String

Valid Values: RECEIVED | RETURNED

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateLongTermPricing

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Updates the long-term pricing type.

Request Syntax

```
{
  "IsLongTermPricingAutoRenew": boolean,
  "LongTermPricingId": "string",
  "ReplacementJob": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[IsLongTermPricingAutoRenew](#)

If set to `true`, specifies that the current long-term pricing type for the device should be automatically renewed before the long-term pricing contract expires.

Type: Boolean

Required: No

[LongTermPricingId](#)

The ID of the long-term pricing type for the device.

Type: String

Length Constraints: Fixed length of 41.

Pattern: LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

ReplacementJob

Specifies that a device that is ordered with long-term pricing should be replaced with a new device.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

ResourceType

The provided resource value is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AWS Snowball Edge Device Management

The following actions are supported by AWS Snowball Edge Device Management:

- [CancelTask](#)
- [CreateTask](#)
- [DescribeDevice](#)
- [DescribeDeviceEc2Instances](#)
- [DescribeExecution](#)
- [DescribeTask](#)
- [ListDeviceResources](#)
- [ListDevices](#)
- [ListExecutions](#)
- [ListTagsForResource](#)
- [ListTasks](#)
- [TagResource](#)
- [UntagResource](#)

CancelTask

Service: AWS Snowball Edge Device Management

Sends a cancel request for a specified task. You can cancel a task only if it's still in a QUEUED state. Tasks that are already running can't be cancelled.

Note

A task might still run if it's processed from the queue before the `CancelTask` operation changes the task's state.

Request Syntax

```
POST /task/taskId/cancel HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

taskId

The ID of the task that you are attempting to cancel. You can retrieve a task ID by using the `ListTasks` operation.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "taskId": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

taskId

The ID of the task that you are attempting to cancel.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTask

Service: AWS Snowball Edge Device Management

Instructs one or more devices to start a task, such as unlocking or rebooting.

Request Syntax

```
POST /task HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "command": { ... },
  "description": "string",
  "tags": {
    "string" : "string"
  },
  "targets": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A token ensuring that the action is called only once with the specified details.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [!-~]+

Required: No

command

The task to be performed. Only one task is executed on a device at a time.

Type: [Command](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[description](#)

A description of the task and its targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9 _.,!#]*

Required: No

[tags](#)

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

Required: No

[targets](#)

A list of managed device IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "taskArn": "string",
  "taskId": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

taskArn

The Amazon Resource Name (ARN) of the task that you created.

Type: String

taskId

The ID of the task that you created.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDevice

Service: AWS Snowball Edge Device Management

Checks device-specific information, such as the device type, software version, IP addresses, and lock status.

Request Syntax

```
POST /managed-device/managedDeviceId/describe HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

managedDeviceId

The ID of the device that you are checking the information of.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "associatedWithJob": "string",
  "deviceCapacities": [
    {
      "available": number,
      "name": "string",
      "total": number,
      "unit": "string",
      "used": number
    }
  ]
}
```

```

    }
  ],
  "deviceState": "string",
  "deviceType": "string",
  "lastReachedOutAt": number,
  "lastUpdatedAt": number,
  "managedDeviceArn": "string",
  "managedDeviceId": "string",
  "physicalNetworkInterfaces": [
    {
      "defaultGateway": "string",
      "ipAddress": "string",
      "ipAddressAssignment": "string",
      "macAddress": "string",
      "netmask": "string",
      "physicalConnectorType": "string",
      "physicalNetworkInterfaceId": "string"
    }
  ],
  "software": {
    "installedVersion": "string",
    "installingVersion": "string",
    "installState": "string"
  },
  "tags": {
    "string" : "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

associatedWithJob

The ID of the job used when ordering the device.

Type: String

deviceCapacities

The hardware specifications of the device.

Type: Array of [Capacity](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

[deviceState](#)

The current state of the device.

Type: String

Valid Values: UNLOCKED | LOCKED | UNLOCKING

[deviceType](#)

The type of AWS Snow Family device.

Type: String

[lastReachedOutAt](#)

When the device last contacted the AWS Cloud. Indicates that the device is online.

Type: Timestamp

[lastUpdatedAt](#)

When the device last pushed an update to the AWS Cloud. Indicates when the device cache was refreshed.

Type: Timestamp

[managedDeviceArn](#)

The Amazon Resource Name (ARN) of the device.

Type: String

[managedDeviceId](#)

The ID of the device that you checked the information for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[physicalNetworkInterfaces](#)

The network interfaces available on the device.

Type: Array of [PhysicalNetworkInterface](#) objects

[software](#)

The software installed on the device.

Type: [SoftwareInformation](#) object

[tags](#)

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDeviceEc2Instances

Service: AWS Snowball Edge Device Management

Checks the current state of the Amazon EC2-compatible instances. The output is similar to `describeDevice`, but the results are sourced from the device cache in the AWS Cloud and include a subset of the available fields.

Request Syntax

```
POST /managed-device/managedDeviceId/resources/ec2/describe HTTP/1.1
Content-type: application/json

{
  "instanceIds": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

managedDeviceId

The ID of the managed device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request accepts the following data in JSON format.

instanceIds

A list of instance IDs associated with the managed device.

Type: Array of strings

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "instances": [
    {
      "instance": {
        "amiLaunchIndex": number,
        "blockDeviceMappings": [
          {
            "deviceName": "string",
            "ebs": {
              "attachTime": number,
              "deleteOnTermination": boolean,
              "status": "string",
              "volumeId": "string"
            }
          }
        ],
        "cpuOptions": {
          "coreCount": number,
          "threadsPerCore": number
        },
        "createdAt": number,
        "imageId": "string",
        "instanceId": "string",
        "instanceType": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",
        "rootDeviceName": "string",
        "securityGroups": [
          {
            "groupId": "string",
            "groupName": "string"
          }
        ],
        "state": {
          "code": number,
          "name": "string"
        },
        "updatedAt": number
      }
    }
  ]
}
```

```
    },  
    "lastUpdatedAt": number  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instances

A list of structures containing information about each instance.

Type: Array of [InstanceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeExecution

Service: AWS Snowball Edge Device Management

Checks the status of a remote task running on one or more target devices.

Request Syntax

```
POST /task/taskId/execution/managedDeviceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

managedDeviceId

The ID of the managed device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

taskId

The ID of the task that the action is describing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "executionId": string,
  "lastUpdatedAt": number,
```

```
"managedDeviceId": "string",  
"startedAt": number,  
"state": "string",  
"taskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

executionId

The ID of the execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

lastUpdatedAt

When the status of the execution was last updated.

Type: Timestamp

managedDeviceId

The ID of the managed device that the task is being executed on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

startedAt

When the execution began.

Type: Timestamp

state

The current state of the execution.

Type: String

Valid Values: QUEUED | IN_PROGRESS | CANCELED | FAILED | SUCCEEDED | REJECTED | TIMED_OUT

taskId

The ID of the task being executed on the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTask

Service: AWS Snowball Edge Device Management

Checks the metadata for a given task on a device.

Request Syntax

```
POST /task/taskId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

taskId

The ID of the task to be described.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "completedAt": number,  
  "createdAt": number,  
  "description": "string",  
  "lastUpdatedAt": number,  
  "state": "string",  
  "tags": {  
    "string" : "string"  
  },  
  "targets": [ "string" ],  
  "taskArn": "string",
```

```
"taskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

completedAt

When the task was completed.

Type: Timestamp

createdAt

When the CreateTask operation was called.

Type: Timestamp

description

The description provided of the task and managed devices.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9 _., !#]*

lastUpdatedAt

When the state of the task was last updated.

Type: Timestamp

state

The current state of the task.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED

tags

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

targets

The managed devices that the task was sent to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

taskArn

The Amazon Resource Name (ARN) of the task.

Type: String

taskId

The ID of the task.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDeviceResources

Service: AWS Snowball Edge Device Management

Returns a list of the AWS resources available for a device. Currently, Amazon EC2 instances are the only supported resource type.

Request Syntax

```
GET /managed-device/managedDeviceId/resources?  
maxResults=maxResults&nextToken=nextToken&type=type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

managedDeviceId

The ID of the managed device that you are listing the resources of.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

maxResults

The maximum number of resources per page.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token to continue to the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [a-zA-Z0-9+/=]*

type

A structure used to filter the results by type of resource.

Length Constraints: Minimum length of 1. Maximum length of 50.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resources": [
    {
      "arn": "string",
      "id": "string",
      "resourceType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A pagination token to continue to the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [a-zA-Z0-9+/=]*

resources

A structure defining the resource's type, Amazon Resource Name (ARN), and ID.

Type: Array of [ResourceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevices

Service: AWS Snowball Edge Device Management

Returns a list of all devices on your AWS account that have AWS Snow Device Management enabled in the AWS Region where the command is run.

Request Syntax

```
GET /managed-devices?jobId=jobId&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

jobId

The ID of the job used to order the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

maxResults

The maximum number of devices to list per page.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token to continue to the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9+/=]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "devices": [
    {
      "associatedWithJob": "string",
      "managedDeviceArn": "string",
      "managedDeviceId": "string",
      "tags": {
        "string" : "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devices

A list of device structures that contain information about the device.

Type: Array of [DeviceSummary](#) objects

nextToken

A pagination token to continue to the next page of devices.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [a-zA-Z0-9+/=]*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListExecutions

Service: AWS Snowball Edge Device Management

Returns the status of tasks for one or more target devices.

Request Syntax

```
GET /executions?maxResults=maxResults&nextToken=nextToken&state=state&taskId=taskId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of tasks to list per page.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token to continue to the next page of tasks.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [a-zA-Z0-9+/=]*

state

A structure used to filter the tasks by their current state.

Valid Values: QUEUED | IN_PROGRESS | CANCELED | FAILED | SUCCEEDED | REJECTED | TIMED_OUT

taskId

The ID of the task.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "executions": [
    {
      "executionId": "string",
      "managedDeviceId": "string",
      "state": "string",
      "taskId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

executions

A list of executions. Each execution contains the task ID, the device that the task is executing on, the execution ID, and the status of the execution.

Type: Array of [ExecutionSummary](#) objects

nextToken

A pagination token to continue to the next page of executions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9+/=]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Service: AWS Snowball Edge Device Management

Returns a list of tags for a managed device or task.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the device or task.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The list of tags for the device or task.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTasks

Service: AWS Snowball Edge Device Management

Returns a list of tasks that can be filtered by state.

Request Syntax

```
GET /tasks?maxResults=maxResults&nextToken=nextToken&state=state HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of tasks per page.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token to continue to the next page of tasks.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9+/=]*`

state

A structure used to filter the list of tasks.

Valid Values: `IN_PROGRESS` | `CANCELED` | `COMPLETED`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "nextToken": "string",
  "tasks": [
    {
      "state": "string",
      "tags": {
        "string" : "string"
      },
      "taskArn": "string",
      "taskId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A pagination token to continue to the next page of tasks.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [a-zA-Z0-9+/=]*

tasks

A list of task structures containing details about each task.

Type: Array of [TaskSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Service: AWS Snowball Edge Device Management

Adds or replaces tags on a device or task.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the device or task.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Service: AWS Snowball Edge Device Management

Removes a tag from a device or task.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the device or task.

Required: Yes

tagKeys

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The following data types are supported by AWS Snowball Edge:

- [Address](#)
- [ClusterListEntry](#)
- [ClusterMetadata](#)
- [CompatibleImage](#)
- [DataTransfer](#)
- [DependentService](#)
- [DeviceConfiguration](#)
- [Ec2AmiResource](#)
- [EKSONDeviceServiceConfiguration](#)
- [EventTriggerDefinition](#)
- [INDTaxDocuments](#)
- [JobListEntry](#)
- [JobLogs](#)
- [JobMetadata](#)
- [JobResource](#)
- [KeyRange](#)
- [LambdaResource](#)
- [LongTermPricingListEntry](#)
- [NFSOnDeviceServiceConfiguration](#)
- [Notification](#)
- [OnDeviceServiceConfiguration](#)
- [PickupDetails](#)
- [S3OnDeviceServiceConfiguration](#)
- [S3Resource](#)
- [ServiceVersion](#)
- [Shipment](#)
- [ShippingDetails](#)

- [SnowconeDeviceConfiguration](#)
- [TargetOnDeviceService](#)
- [TaxDocuments](#)
- [TGWOnDeviceServiceConfiguration](#)
- [WirelessConnection](#)

The following data types are supported by AWS Snowball Edge Device Management:

- [Capacity](#)
- [Command](#)
- [CpuOptions](#)
- [DeviceSummary](#)
- [EbsInstanceBlockDevice](#)
- [ExecutionSummary](#)
- [Instance](#)
- [InstanceBlockDeviceMapping](#)
- [InstanceState](#)
- [InstanceSummary](#)
- [PhysicalNetworkInterface](#)
- [Reboot](#)
- [ResourceSummary](#)
- [SecurityGroupIdentifier](#)
- [SoftwareInformation](#)
- [TaskSummary](#)
- [Unlock](#)

AWS Snowball Edge

The following data types are supported by AWS Snowball Edge:

- [Address](#)
- [ClusterListEntry](#)

- [ClusterMetadata](#)
- [CompatibleImage](#)
- [DataTransfer](#)
- [DependentService](#)
- [DeviceConfiguration](#)
- [Ec2AmiResource](#)
- [EKSONDeviceServiceConfiguration](#)
- [EventTriggerDefinition](#)
- [INDTaxDocuments](#)
- [JobListEntry](#)
- [JobLogs](#)
- [JobMetadata](#)
- [JobResource](#)
- [KeyRange](#)
- [LambdaResource](#)
- [LongTermPricingListEntry](#)
- [NFSOnDeviceServiceConfiguration](#)
- [Notification](#)
- [OnDeviceServiceConfiguration](#)
- [PickupDetails](#)
- [S3OnDeviceServiceConfiguration](#)
- [S3Resource](#)
- [ServiceVersion](#)
- [Shipment](#)
- [ShippingDetails](#)
- [SnowconeDeviceConfiguration](#)
- [TargetOnDeviceService](#)
- [TaxDocuments](#)
- [TGWOnDeviceServiceConfiguration](#)
- [WirelessConnection](#)

Address

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The address that you want the Snow device(s) associated with a specific job to be shipped to. Addresses are validated at the time of creation. The address you provide must be located within the serviceable area of your region. Although no individual elements of the Address are required, if the address is invalid or unsupported, then an exception is thrown.

Contents

AddressId

The unique ID for an address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

City

The city in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Company

The name of the company to receive a Snow device at an address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Country

The country in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

IsRestricted

This field is not supported in your region.

Type: Boolean

Required: No

Landmark

This field is no longer used and the value is ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Name

The name of a person to receive a Snow device at an address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

PhoneNumber

The phone number associated with an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

PostalCode

The postal code in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

PrefectureOrDistrict

This field is no longer used and the value is ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

StateOrProvince

The state or province in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Street1

The first line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Street2

The second line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Street3

The third line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Type

Differentiates between delivery address and pickup address in the customer account. Provided at job creation.

Type: String

Valid Values: CUST_PICKUP | AWS_SHIP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusterListEntry

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains a cluster's state, a cluster's ID, and other important information.

Contents

ClusterId

The 39-character ID for the cluster that you want to list, for example CID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Required: No

ClusterState

The current state of this cluster. For information about the state of a specific node, see [JobListEntry:JobState](#).

Type: String

Valid Values: AwaitingQuorum | Pending | InUse | Complete | Cancelled

Required: No

CreationDate

The creation date for this cluster.

Type: Timestamp

Required: No

Description

Defines an optional description of the cluster, for example `Environmental Data Cluster-01`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusterMetadata

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains metadata about a specific cluster.

Contents

AddressId

The automatically generated ID for a specific address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId

The automatically generated ID for a cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

ClusterState

The current status of the cluster.

Type: String

Valid Values: AwaitingQuorum | Pending | InUse | Complete | Cancelled

Required: No

CreationDate

The creation date for this cluster.

Type: Timestamp

Required: No

Description

The optional description of the cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobType

The type of job for this cluster. Currently, the only job type supported for clusters is LOCAL_USE.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

KmsKeyARN

The KmsKeyARN Amazon Resource Name (ARN) associated with this cluster. This ARN was created using the [CreateKey](#) API action in AWS Key Management Service (AWS KMS).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:kms:.*:[0-9]{12}:key/.*`

Required: No

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings for this cluster.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Represents metadata and configuration settings for services on an AWS Snowball Edge device.

Type: [OnDeviceServiceConfiguration](#) object

Required: No

Resources

The arrays of [JobResource](#) objects that can include updated [S3Resource](#) objects or [LambdaResource](#) objects.

Type: [JobResource](#) object

Required: No

RoleARN

The role ARN associated with this cluster. This ARN was created using the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingOption

The shipping speed for each node in this cluster. This speed doesn't dictate how soon you'll get each device, rather it represents how quickly each device moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

SnowballType

The type of Snowball Edge device to use for this cluster.

Note

For cluster jobs, AWS Snowball Edge currently supports only the `EDGE` device type.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD` | `SNC1_SSD` | `V3_5C` | `V3_5S` | `RACK_5U_C`

Required: No

TaxDocuments

The tax documents required in your AWS Region.

Type: [TaxDocuments](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CompatibleImage

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

A JSON-formatted object that describes a compatible Amazon Machine Image (AMI), including the ID and name for a Snow device AMI. This AMI is compatible with the device's physical hardware requirements, and it should be able to be run in an SBE1 instance on the device.

Contents

Amild

The unique identifier for an individual Snow device AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Name

The optional name of a compatible image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataTransfer

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Defines the real-time status of a Snow device's data transfer while the device is at AWS. This data is only available while a job has a JobState value of InProgress, for both import and export jobs.

Contents

BytesTransferred

The number of bytes transferred between a Snow device and Amazon S3.

Type: Long

Required: No

ObjectsTransferred

The number of objects transferred between a Snow device and Amazon S3.

Type: Long

Required: No

TotalBytes

The total bytes of data for a transfer between a Snow device and Amazon S3. This value is set to 0 (zero) until all the keys that will be transferred have been listed.

Type: Long

Required: No

TotalObjects

The total number of objects for a transfer between a Snow device and Amazon S3. This value is set to 0 (zero) until all the keys that will be transferred have been listed.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DependentService

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The name and version of the service dependant on the requested service.

Contents

ServiceName

The name of the dependent service.

Type: String

Valid Values: KUBERNETES | EKS_ANYWHERE

Required: No

ServiceVersion

The version of the dependent service.

Type: [ServiceVersion](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceConfiguration

Service: AWS Snowball Edge

The container for SnowconeDeviceConfiguration.

Contents

SnowconeDeviceConfiguration

Returns information about the device configuration for an AWS Snowball Edge job.

Type: [SnowconeDeviceConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Ec2AmiResource

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

A JSON-formatted object that contains the IDs for an Amazon Machine Image (AMI), including the Amazon EC2-compatible AMI ID and the Snow device AMI ID. Each AMI has these two IDs to simplify identifying the AMI in both the AWS Cloud and on the device.

Contents

Amild

The ID of the AMI in Amazon EC2.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 21.

Pattern: `(ami-[0-9a-f]{8})|(ami-[0-9a-f]{17})`

Required: Yes

SnowballAmild

The ID of the AMI on the Snow device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EKSONDeviceServiceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

An object representing the metadata and configuration settings of EKS Anywhere on the Snowball Edge device.

Contents

EKSAnywhereVersion

The optional version of EKS Anywhere on the Snowball Edge device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Required: No

KubernetesVersion

The Kubernetes version for EKS Anywhere on the Snowball Edge device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventTriggerDefinition

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The container for the [EventTriggerDefinition:EventResourceARN](#).

Contents

EventResourceARN

The Amazon Resource Name (ARN) for any local Amazon S3 resource that is an AWS Lambda function's event trigger associated with this job.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

INDTaxDocuments

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The tax documents required in AWS Region in India.

Contents

GSTIN

The Goods and Services Tax (GST) documents required in AWS Region in India.

Type: String

Length Constraints: Fixed length of 15.

Pattern: `\d{2}[A-Z]{5}\d{4}[A-Z]{1}[A-Z\d]{1}[Z]{1}[A-Z\d]{1}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobListEntry

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of an export job.

Contents

CreationDate

The creation date for this job.

Type: Timestamp

Required: No

Description

The optional description of this specific job, for example `Important Photos 2016-08-11`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

IsMaster

A value that indicates that this job is a main job. A main job represents a successful request to create an export job. Main jobs aren't associated with any Snowballs. Instead, each main job will have at least one job part, and each job part is associated with a Snowball. It might take some time before the job parts associated with a particular main job are listed, because they are created after the main job is created.

Type: Boolean

Required: No

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

JobState

The current state of this job.

Type: String

Valid Values: New | PreparingAppliance | PreparingShipment | InTransitToCustomer | WithCustomer | InTransitToAWS | WithAWSSortingFacility | WithAWS | InProgress | Complete | Cancelled | Listing | Pending

Required: No

JobType

The type of job.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

SnowballType

The type of device used with this job.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobLogs

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains job logs. Whenever a Snow device is used to import data into or export data out of Amazon S3, you'll have the option of downloading a PDF job report. Job logs are returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type. The job logs can be accessed for up to 60 minutes after this request has been made. To access any of the job logs after 60 minutes have passed, you'll have to make another call to the `DescribeJob` action.

For import jobs, the PDF job report becomes available at the end of the import process. For export jobs, your job report typically becomes available while the Snow device for your job part is being delivered to you.

The job report provides you insight into the state of your Amazon S3 data transfer. The report includes details about your job or job part for your records.

For deeper visibility into the status of your transferred objects, you can look at the two associated logs: a success log and a failure log. The logs are saved in comma-separated value (CSV) format, and the name of each log includes the ID of the job or job part that the log describes.

Contents

JobCompletionReportURI

A link to an Amazon S3 presigned URL where the job completion report is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

JobFailureLogURI

A link to an Amazon S3 presigned URL where the job failure log is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

JobSuccessLogURI

A link to an Amazon S3 presigned URL where the job success log is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobMetadata

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains information about a specific job including shipping information, job status, and other important metadata. This information is returned as a part of the response syntax of the DescribeJob action.

Contents

AddressId

The ID for the address that you want the Snow device shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId

The 39-character ID for the cluster, for example CID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

CreationDate

The creation date for this job.

Type: Timestamp

Required: No

DataTransferProgress

A value that defines the real-time status of a Snow device's data transfer while the device is at AWS. This data is only available while a job has a JobState value of InProgress, for both import and export jobs.

Type: [DataTransfer](#) object

Required: No

Description

The description of the job, provided at job creation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

DeviceConfiguration

The container for SnowconeDeviceConfiguration.

Type: [DeviceConfiguration](#) object

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ImpactLevel

The highest impact level of data that will be stored or processed on the device, provided at job creation.

Type: String

Valid Values: IL2 | IL4 | IL5 | IL6 | IL99

Required: No

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

JobLogInfo

Links to Amazon S3 presigned URLs for the job report and logs. For import jobs, the PDF job report becomes available at the end of the import process. For export jobs, your job report typically becomes available while the Snow device for your job part is being delivered to you.

Type: [JobLogs](#) object

Required: No

JobState

The current status of the jobs.

Type: String

Valid Values: New | PreparingAppliance | PreparingShipment | InTransitToCustomer | WithCustomer | InTransitToAWS | WithAWSSortingFacility | WithAWS | InProgress | Complete | Cancelled | Listing | Pending

Required: No

JobType

The type of job.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

KmsKeyARN

The Amazon Resource Name (ARN) for the AWS Key Management Service (AWS KMS) key associated with this job. This ARN was created using the [CreateKey](#) API action in AWS KMS.

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:kms:.*:[0-9]{12}:key/.*

Required: No

LongTermPricingId

The ID of the long-term pricing type for the device.

Type: String

Length Constraints: Fixed length of 41.

Pattern: LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings associated with a specific job. The `Notification` object is returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type.

Type: [Notification](#) object

Required: No

OnDeviceServiceConfiguration

Represents metadata and configuration settings for services on an AWS Snowball Edge device.

Type: [OnDeviceServiceConfiguration](#) object

Required: No

PickupDetails

Information identifying the person picking up the device.

Type: [PickupDetails](#) object

Required: No

RemoteManagement

Allows you to securely operate and manage Snowcone devices remotely from outside of your internal network. When set to `INSTALLED_AUTOSTART`, remote management will automatically be available when the device arrives at your location. Otherwise, you need to use the Snowball Client to manage the device.

Type: String

Valid Values: `INSTALLED_ONLY` | `INSTALLED_AUTOSTART` | `NOT_INSTALLED`

Required: No

Resources

An array of `S3Resource` objects. Each `S3Resource` object represents an Amazon S3 bucket that your transferred data will be exported from or imported into.

Type: [JobResource](#) object

Required: No

RoleARN

The role ARN associated with this job. This ARN was created using the [CreateRole](#) API action in AWS Identity and Access Management.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingDetails

A job's shipping information, including inbound and outbound tracking numbers and shipping speed options.

Type: [ShippingDetails](#) object

Required: No

SnowballCapacityPreference

The Snow device capacity preference for this job, specified at job creation. In US regions, you can choose between 50 TB and 80 TB Snowballs. All other regions use 80 TB capacity Snowballs.

For information about Snowball Edge device types, see [Device hardware differences](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: T50 | T80 | T100 | T42 | T98 | T8 | T14 | T32 | NoPreference | T240 | T13

Required: No

SnowballId

Unique ID associated with a device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

SnowballType

The type of device used with this job.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: No

TaxDocuments

The metadata associated with the tax documents required in your AWS Region.

Type: [TaxDocuments](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobResource

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains an array of AWS resource objects. Each object represents an Amazon S3 bucket, an AWS Lambda function, or an Amazon Machine Image (AMI) based on Amazon EC2 that is associated with a particular job.

Contents

Ec2AmiResources

The Amazon Machine Images (AMIs) associated with this job.

Type: Array of [Ec2AmiResource](#) objects

Required: No

LambdaResources

The Python-language Lambda functions for this job.

Type: Array of [LambdaResource](#) objects

Required: No

S3Resources

An array of S3Resource objects.

Type: Array of [S3Resource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KeyRange

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Contains a key range. For export jobs, a `S3Resource` object can have an optional `KeyRange` value. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Contents

BeginMarker

The key that starts an optional key range for an export job. Ranges are inclusive and UTF-8 binary sorted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

EndMarker

The key that ends an optional key range for an export job. Ranges are inclusive and UTF-8 binary sorted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LambdaResource

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Identifies

Contents

EventTriggers

The array of ARNs for [S3Resource](#) objects to trigger the [LambdaResource](#) objects associated with this job.

Type: Array of [EventTriggerDefinition](#) objects

Required: No

LambdaArn

An Amazon Resource Name (ARN) that represents an AWS Lambda function to be triggered by PUT object actions on the associated local Amazon S3 resource.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LongTermPricingListEntry

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Each LongTermPricingListEntry object contains information about a long-term pricing type.

Contents

CurrentActiveJob

The current active jobs on the device the long-term pricing type.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

IsLongTermPricingAutoRenew

If set to `true`, specifies that the current long-term pricing type for the device should be automatically renewed before the long-term pricing contract expires.

Type: Boolean

Required: No

JobIds

The IDs of the jobs that are associated with a long-term pricing type.

Type: Array of strings

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

LongTermPricingEndDate

The end date the long-term pricing contract.

Type: Timestamp

Required: No

LongTermPricingId

The ID of the long-term pricing type for the device.

Type: String

Length Constraints: Fixed length of 41.

Pattern: LTPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

LongTermPricingStartDate

The start date of the long-term pricing contract.

Type: Timestamp

Required: No

LongTermPricingStatus

The status of the long-term pricing type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

LongTermPricingType

The type of long-term pricing that was selected for the device.

Type: String

Valid Values: OneYear | ThreeYear | OneMonth

Required: No

ReplacementJob

A new device that replaces a device that is ordered with long-term pricing.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

SnowballType

The type of Snow Family devices associated with this long-term pricing job.

Type: String

Valid Values: STANDARD | EDGE | EDGE_C | EDGE_CG | EDGE_S | SNC1_HDD | SNC1_SSD | V3_5C | V3_5S | RACK_5U_C

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NFSOnDeviceServiceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

An object that represents the metadata and configuration settings for the NFS (Network File System) service on an AWS Snowball Edge device.

Contents

StorageLimit

The maximum NFS storage for one Snowball Edge device.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

StorageUnit

The scale unit of the NFS storage on the device.

Valid values: TB.

Type: String

Valid Values: TB

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Notification

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The Amazon Simple Notification Service (Amazon SNS) notification settings associated with a specific job. The `Notification` object is returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type.

When the notification settings are defined during job creation, you can choose to notify based on a specific set of job states using the `JobStatesToNotify` array of strings, or you can specify that you want to have Amazon SNS notifications sent out for all job states with `NotifyAll` set to true.

Contents

`DevicePickupSnsTopicARN`

Used to send SNS notifications for the person picking up the device (identified during job creation).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:sns:.*:[0-9]{12}:.*`

Required: No

`JobStatesToNotify`

The list of job states that will trigger a notification for this job.

Type: Array of strings

Valid Values: `New` | `PreparingAppliance` | `PreparingShipment` | `InTransitToCustomer` | `WithCustomer` | `InTransitToAWS` |

WithAWSSortingFacility | WithAWS | InProgress | Complete | Cancelled | Listing | Pending

Required: No

NotifyAll

Any change in job state will trigger a notification for this job.

Type: Boolean

Required: No

SnsTopicARN

The new SNS TopicArn that you want to associate with this job. You can create Amazon Resource Names (ARNs) for topics by using the [CreateTopic](#) Amazon SNS API action.

You can subscribe email addresses to an Amazon SNS topic through the AWS Management Console, or by using the [Subscribe](#) Amazon Simple Notification Service (Amazon SNS) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:sns:.*:[0-9]{12}:.*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OnDeviceServiceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

An object that represents the metadata and configuration settings for services on an AWS Snowball Edge device.

Contents

EKSONDeviceService

The configuration of EKS Anywhere on the Snowball Edge device.

Type: [EKSONDeviceServiceConfiguration](#) object

Required: No

NFSOnDeviceService

Represents the NFS (Network File System) service on a Snowball Edge device.

Type: [NFSOnDeviceServiceConfiguration](#) object

Required: No

S3OnDeviceService

Configuration for Amazon S3 compatible storage on Snowball Edge devices.

Type: [S3OnDeviceServiceConfiguration](#) object

Required: No

TGWOnDeviceService

Represents the Storage Gateway service Tape Gateway type on a Snow Family device.

Note

The Tape Gateway service is no longer available on Snowball Edge devices.

Type: [TGWOnDeviceServiceConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PickupDetails

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Information identifying the person picking up the device.

Contents

DevicePickupId

The unique ID for a device that will be picked up.

Type: String

Length Constraints: Fixed length of 40.

Pattern: DPID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Email

The email address of the person picking up the device.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

Pattern: ^(?=.{3,100}\$).+@.+[.] .+\$

Required: No

IdentificationExpirationDate

Expiration date of the credential identifying the person picking up the device.

Type: Timestamp

Required: No

IdentificationIssuingOrg

Organization that issued the credential identifying the person picking up the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

IdentificationNumber

The number on the credential identifying the person picking up the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Name

The name of the person picking up the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

PhoneNumber

The phone number of the person picking up the device.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 30.

Pattern: `^\s*(?:\+?(\d{1,3}))?[-. (]*(\d{3})[-.]*(\d{4})(?:*x(\d+))?\s*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3OnDeviceServiceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Amazon S3 compatible storage on Snowball Edge devices configuration items.

Contents

FaultTolerance

>Fault tolerance level of the cluster. This indicates the number of nodes that can go down without degrading the performance of the cluster. This additional input helps when the specified `StorageLimit` matches more than one Amazon S3 compatible storage on Snowball Edge devices service configuration.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 4.

Required: No

ServiceSize

Applicable when creating a cluster. Specifies how many nodes are needed for Amazon S3 compatible storage on Snowball Edge devices. If specified, the other input can be omitted.

Type: Integer

Valid Range: Minimum value of 3. Maximum value of 16.

Required: No

StorageLimit

If the specified storage limit value matches storage limit of one of the defined configurations, that configuration will be used. If the specified storage limit value does not match any defined

configuration, the request will fail. If more than one configuration has the same storage limit as specified, the other input need to be provided.

Type: Double

Valid Range: Minimum value of 0.0.

Required: No

StorageUnit

Storage unit. Currently the only supported unit is TB.

Type: String

Valid Values: TB

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Resource

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Each `S3Resource` object represents an Amazon S3 bucket that your transferred data will be exported from or imported into. For export jobs, this object can have an optional `KeyRange` value. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Contents

BucketArn

The Amazon Resource Name (ARN) of an Amazon S3 bucket.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:*`

Required: No

KeyRange

For export jobs, you can provide an optional `KeyRange` within a specific Amazon S3 bucket. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Type: [KeyRange](#) object

Required: No

TargetOnDeviceServices

Specifies the service or services on the Snowball Edge device that your transferred data will be exported from or imported into. AWS Snowball Edge supports Amazon S3 and NFS (Network File System).

Type: Array of [TargetOnDeviceService](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceVersion

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The version of the requested service.

Contents

Version

The version number of the requested service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Shipment

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The `Status` and `TrackingNumber` information for an inbound or outbound shipment.

Contents

Status

Status information for a shipment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

TrackingNumber

The tracking number for this job. Using this tracking number with your region's carrier's website, you can track a Snow device as the carrier transports it.

For India, the carrier is Amazon Logistics. For all other regions, UPS is the carrier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ShippingDetails

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

A job's shipping information, including inbound and outbound tracking numbers and shipping speed options.

Contents

InboundShipment

The `Status` and `TrackingNumber` values for a Snow device being returned to AWS for a particular job.

Type: [Shipment](#) object

Required: No

OutboundShipment

The `Status` and `TrackingNumber` values for a Snow device being delivered to the address that you specified for a particular job.

Type: [Shipment](#) object

Required: No

ShippingOption

The shipping speed for a particular job. This speed doesn't dictate how soon you'll get the Snow device from the job's creation date. This speed represents how quickly it moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.

- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the United States of America (US), you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: SECOND_DAY | NEXT_DAY | EXPRESS | STANDARD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SnowconeDeviceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Specifies the device configuration for an AWS Snowball Edge job.

Contents

WirelessConnection

Configures the wireless connection for the Snowball Edge device.

Type: [WirelessConnection](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetOnDeviceService

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

An object that represents the service or services on the Snowball Edge device that your transferred data will be exported from or imported into. AWS Snowball Edge supports Amazon S3 and NFS (Network File System).

Contents

ServiceName

Specifies the name of the service on the Snowball Edge device that your transferred data will be exported from or imported into.

Type: String

Valid Values: NFS_ON_DEVICE_SERVICE | S3_ON_DEVICE_SERVICE

Required: No

TransferOption

Specifies whether the data is being imported or exported. You can import or export the data, or use it locally on the device.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TaxDocuments

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The tax documents required in your AWS Region.

Contents

IND

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

The tax documents required in AWS Region in India.

Type: [INDTaxDocuments](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TGWOnDeviceServiceConfiguration

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

An object that represents the metadata and configuration settings for the Storage Gateway service Tape Gateway type on an AWS Snowball Edge device.

Note

The Tape Gateway service is no longer available on Snow Family devices.

Contents

StorageLimit

The maximum number of virtual tapes to store on one Snowball Edge device. Due to physical resource limitations, this value must be set to 80 for Snowball Edge.

Note

The Tape Gateway service is no longer available on Snow Family devices.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

StorageUnit

The scale unit of the virtual tapes on the device.

Note

The Tape Gateway service is no longer available on Snow Family devices.

Type: String

Valid Values: TB

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WirelessConnection

Service: AWS Snowball Edge

Note

AWS Snowball Edge is no longer available to new customers. New customers should explore [AWS DataSync](#) for online transfers, [AWS Data Transfer Terminal](#) for secure physical transfers, or AWS Partner solutions. For edge computing, explore [AWS Outposts](#).

Configures the wireless connection on an AWS Snowball Edge device.

Contents

IsWifiEnabled

Enables the Wi-Fi adapter on an AWS Snowball Edge device.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AWS Snowball Edge Device Management

The following data types are supported by AWS Snowball Edge Device Management:

- [Capacity](#)
- [Command](#)
- [CpuOptions](#)

- [DeviceSummary](#)
- [EbsInstanceBlockDevice](#)
- [ExecutionSummary](#)
- [Instance](#)
- [InstanceBlockDeviceMapping](#)
- [InstanceState](#)
- [InstanceSummary](#)
- [PhysicalNetworkInterface](#)
- [Reboot](#)
- [ResourceSummary](#)
- [SecurityGroupIdentifier](#)
- [SoftwareInformation](#)
- [TaskSummary](#)
- [Unlock](#)

Capacity

Service: AWS Snowball Edge Device Management

The physical capacity of the AWS Snow Family device.

Contents

available

The amount of capacity available for use on the device.

Type: Long

Required: No

name

The name of the type of capacity, such as memory.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

total

The total capacity on the device.

Type: Long

Required: No

unit

The unit of measure for the type of capacity.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20.

Required: No

used

The amount of capacity used on the device.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Command

Service: AWS Snowball Edge Device Management

The command given to the device to execute.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

reboot

Reboots the device.

Type: [Reboot](#) object

Required: No

unlock

Unlocks the device.

Type: [Unlock](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CpuOptions

Service: AWS Snowball Edge Device Management

The options for how a device's CPU is configured.

Contents

coreCount

The number of cores that the CPU can use.

Type: Integer

Required: No

threadsPerCore

The number of threads per core in the CPU.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceSummary

Service: AWS Snowball Edge Device Management

Identifying information about the device.

Contents

associatedWithJob

The ID of the job used to order the device.

Type: String

Required: No

managedDeviceArn

The Amazon Resource Name (ARN) of the device.

Type: String

Required: No

managedDeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

tags

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EbsInstanceBlockDevice

Service: AWS Snowball Edge Device Management

Describes a parameter used to set up an Amazon Elastic Block Store (Amazon EBS) volume in a block device mapping.

Contents

attachTime

When the attachment was initiated.

Type: Timestamp

Required: No

deleteOnTermination

A value that indicates whether the volume is deleted on instance termination.

Type: Boolean

Required: No

status

The attachment state.

Type: String

Valid Values: ATTACHING | ATTACHED | DETACHING | DETACHED

Required: No

volumeld

The ID of the Amazon EBS volume.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExecutionSummary

Service: AWS Snowball Edge Device Management

The summary of a task execution on a specified device.

Contents

executionId

The ID of the execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

managedDeviceId

The ID of the managed device that the task is being executed on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

state

The state of the execution.

Type: String

Valid Values: QUEUED | IN_PROGRESS | CANCELED | FAILED | SUCCEEDED | REJECTED | TIMED_OUT

Required: No

taskId

The ID of the task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Instance

Service: AWS Snowball Edge Device Management

The description of an instance. Currently, Amazon EC2 instances are the only supported instance type.

Contents

amiLaunchIndex

The Amazon Machine Image (AMI) launch index, which you can use to find this instance in the launch group.

Type: Integer

Required: No

blockDeviceMappings

Any block device mapping entries for the instance.

Type: Array of [InstanceBlockDeviceMapping](#) objects

Required: No

cpuOptions

The CPU options for the instance.

Type: [CpuOptions](#) object

Required: No

createdAt

When the instance was created.

Type: Timestamp

Required: No

imageId

The ID of the AMI used to launch the instance.

Type: String

Required: No

instanceId

The ID of the instance.

Type: String

Required: No

instanceType

The instance type.

Type: String

Required: No

privateIpAddress

The private IPv4 address assigned to the instance.

Type: String

Required: No

publicIpAddress

The public IPv4 address assigned to the instance.

Type: String

Required: No

rootDeviceName

The device name of the root device volume (for example, /dev/sda1).

Type: String

Required: No

securityGroups

The security groups for the instance.

Type: Array of [SecurityGroupIdentifier](#) objects

Required: No

state

The description of the current state of an instance.

Type: [InstanceState](#) object

Required: No

updatedAt

When the instance was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceBlockDeviceMapping

Service: AWS Snowball Edge Device Management

The description of a block device mapping.

Contents

deviceName

The block device name.

Type: String

Required: No

ebs

The parameters used to automatically set up Amazon Elastic Block Store (Amazon EBS) volumes when the instance is launched.

Type: [EbsInstanceBlockDevice](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceState

Service: AWS Snowball Edge Device Management

The description of the current state of an instance.

Contents

code

The state of the instance as a 16-bit unsigned integer.

The high byte is all of the bits between 2^8 and $(2^{16})-1$, which equals decimal values between 256 and 65,535. These numerical values are used for internal purposes and should be ignored.

The low byte is all of the bits between 2^0 and $(2^8)-1$, which equals decimal values between 0 and 255.

The valid values for the instance state code are all in the range of the low byte. These values are:

- 0: pending
- 16: running
- 32: shutting-down
- 48: terminated
- 64: stopping
- 80: stopped

You can ignore the high byte value by zeroing out all of the bits above 2^8 or 256 in decimal.

Type: Integer

Required: No

name

The current state of the instance.

Type: String

Valid Values: PENDING | RUNNING | SHUTTING_DOWN | TERMINATED | STOPPING | STOPPED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceSummary

Service: AWS Snowball Edge Device Management

The details about the instance.

Contents

instance

A structure containing details about the instance.

Type: [Instance](#) object

Required: No

lastUpdatedAt

When the instance summary was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PhysicalNetworkInterface

Service: AWS Snowball Edge Device Management

The details about the physical network interface for the device.

Contents

defaultGateway

The default gateway of the device.

Type: String

Required: No

ipAddress

The IP address of the device.

Type: String

Required: No

ipAddressAssignment

A value that describes whether the IP address is dynamic or persistent.

Type: String

Valid Values: DHCP | STATIC

Required: No

macAddress

The MAC address of the device.

Type: String

Required: No

netmask

The netmask used to divide the IP address into subnets.

Type: String

Required: No

physicalConnectorType

The physical connector type.

Type: String

Valid Values: RJ45 | SFP_PLUS | QSFP | RJ45_2 | WIFI

Required: No

physicalNetworkInterfaceId

The physical network interface ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Reboot

Service: AWS Snowball Edge Device Management

A structure used to reboot the device.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceSummary

Service: AWS Snowball Edge Device Management

A summary of a resource available on the device.

Contents

resourceType

The resource type.

Type: String

Required: Yes

arn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

id

The ID of the resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityGroupIdentifier

Service: AWS Snowball Edge Device Management

Information about the device's security group.

Contents

groupId

The security group ID.

Type: String

Required: No

groupName

The security group name.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SoftwareInformation

Service: AWS Snowball Edge Device Management

Information about the software on the device.

Contents

installedVersion

The version of the software currently installed on the device.

Type: String

Required: No

installingVersion

The version of the software being installed on the device.

Type: String

Required: No

installState

The state of the software that is installed or that is being installed on the device.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TaskSummary

Service: AWS Snowball Edge Device Management

Information about the task assigned to one or many devices.

Contents

taskId

The task ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

state

The state of the task assigned to one or many devices.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED

Required: No

tags

Optional metadata that you assign to a resource. You can use tags to categorize a resource in different ways, such as by purpose, owner, or environment.

Type: String to string map

Required: No

taskArn

The Amazon Resource Name (ARN) of the task.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Unlock

Service: AWS Snowball Edge Device Management

A structure used to unlock a device.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400