API Reference

AWS Systems Manager



API Version 2014-11-06

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Systems Manager: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome **1**
Actions **2**
AddTagsToResource 7
Request Syntax 7
Request Parameters 8
Response Elements 9
Errors 9
Examples 10
See Also 11
AssociateOpsItemRelatedItem 13
Request Syntax 13
Request Parameters 13
Response Syntax 14
Response Elements 14
Errors 14
Examples 15
See Also 16
CancelCommand 17
Request Syntax 17
Request Parameters 17
Response Elements 18
Errors 18
Examples 18
See Also 19
CancelMaintenanceWindowExecution 21
Request Syntax 21
Request Parameters 21
Response Syntax 21
Response Elements 21
Errors 22
Examples 22
See Also 23
CreateActivation 24
Request Syntax 24

Request Parameters ... 25
Response Syntax ... 27
Response Elements ... 27
Errors ... 28
Examples ... 28
See Also ... 29
CreateAssociation ... 31
Request Syntax ... 31
Request Parameters ... 33
Response Syntax ... 40
Response Elements ... 43
Errors ... 43
Examples ... 45
See Also ... 46
CreateAssociationBatch ... 48
Request Syntax ... 48
Request Parameters ... 50
Response Syntax ... 50
Response Elements ... 54
Errors ... 55
Examples ... 56
See Also ... 59
CreateDocument ... 60
Request Syntax ... 60
Request Parameters ... 61
Response Syntax ... 65
Response Elements ... 66
Errors ... 66
Examples ... 67
See Also ... 69
CreateMaintenanceWindow ... 70
Request Syntax ... 70
Request Parameters ... 70
Response Syntax ... 74
Response Elements ... 74
Errors ... 75

Examples ... 75
See Also ... 76
CreateOpsItem ... 78
Request Syntax ... 78
Request Parameters ... 79
Response Syntax ... 84
Response Elements ... 84
Errors ... 85
Examples ... 85
See Also ... 86
CreateOpsMetadata ... 88
Request Syntax ... 88
Request Parameters ... 88
Response Syntax ... 89
Response Elements ... 89
Errors ... 90
See Also ... 91
CreatePatchBaseline ... 92
Request Syntax ... 92
Request Parameters ... 93
Response Syntax ... 98
Response Elements ... 98
Errors ... 98
Examples ... 99
See Also ... 101
CreateResourceDataSync ... 102
Request Syntax ... 102
Request Parameters ... 103
Response Elements ... 104
Errors ... 104
Examples ... 105
See Also ... 106
DeleteActivation ... 107
Request Syntax ... 107
Request Parameters ... 107
Response Elements ... 107

Errors ... 107
Examples ... 108
See Also ... 109
DeleteAssociation ... 110
Request Syntax ... 110
Request Parameters ... 110
Response Elements ... 111
Errors ... 111
Examples ... 112
See Also ... 113
DeleteDocument ... 114
Request Syntax ... 114
Request Parameters ... 114
Response Elements ... 115
Errors ... 115
Examples ... 116
See Also ... 117
DeleteInventory ... 118
Request Syntax ... 118
Request Parameters ... 118
Response Syntax ... 119
Response Elements ... 120
Errors ... 120
Examples ... 121
See Also ... 122
DeleteMaintenanceWindow ... 124
Request Syntax ... 124
Request Parameters ... 124
Response Syntax ... 124
Response Elements ... 124
Errors ... 125
Examples ... 125
See Also ... 126
DeleteOpsItem ... 127
Request Syntax ... 127
Request Parameters ... 127

Response Elements ... 128
Errors ... 128
Examples ... 128
See Also ... 129
DeleteOpsMetadata ... 130
Request Syntax ... 130
Request Parameters ... 130
Response Elements ... 130
Errors ... 130
See Also ... 131
DeleteParameter ... 132
Request Syntax ... 132
Request Parameters ... 132
Response Elements ... 132
Errors ... 132
Examples ... 133
See Also ... 134
DeleteParameters ... 135
Request Syntax ... 135
Request Parameters ... 135
Response Syntax ... 135
Response Elements ... 136
Errors ... 136
Examples ... 136
See Also ... 137
DeletePatchBaseline ... 139
Request Syntax ... 139
Request Parameters ... 139
Response Syntax ... 139
Response Elements ... 139
Errors ... 140
Examples ... 140
See Also ... 141
DeleteResourceDataSync ... 142
Request Syntax ... 142
Request Parameters ... 142

Response Elements ... 142
Errors ... 143
Examples ... 143
See Also ... 144
DeleteResourcePolicy ... 145
Request Syntax ... 145
Request Parameters ... 145
Response Elements ... 146
Errors ... 146
See Also ... 147
DeregisterManagedInstance ... 148
Request Syntax ... 148
Request Parameters ... 148
Response Elements ... 148
Errors ... 149
Examples ... 149
See Also ... 150
DeregisterPatchBaselineForPatchGroup ... 151
Request Syntax ... 151
Request Parameters ... 151
Response Syntax ... 152
Response Elements ... 152
Errors ... 152
Examples ... 153
See Also ... 154
DeregisterTargetFromMaintenanceWindow ... 155
Request Syntax ... 155
Request Parameters ... 155
Response Syntax ... 156
Response Elements ... 156
Errors ... 157
Examples ... 157
See Also ... 158
DeregisterTaskFromMaintenanceWindow ... 159
Request Syntax ... 159
Request Parameters ... 159

Response Syntax ... 160
Response Elements ... 160
Errors ... 160
Examples ... 161
See Also ... 162
DescribeActivations ... 163
Request Syntax ... 163
Request Parameters ... 163
Response Syntax ... 164
Response Elements ... 164
Errors ... 165
Examples ... 165
See Also ... 166
DescribeAssociation ... 168
Request Syntax ... 168
Request Parameters ... 168
Response Syntax ... 169
Response Elements ... 171
Errors ... 172
Examples ... 173
See Also ... 174
DescribeAssociationExecutions ... 176
Request Syntax ... 176
Request Parameters ... 176
Response Syntax ... 177
Response Elements ... 178
Errors ... 178
Examples ... 179
See Also ... 180
DescribeAssociationExecutionTargets ... 181
Request Syntax ... 181
Request Parameters ... 181
Response Syntax ... 182
Response Elements ... 183
Errors ... 183
Examples ... 184

See Also ... 186
DescribeAutomationExecutions ... 187
Request Syntax ... 187
Request Parameters ... 187
Response Syntax ... 188
Response Elements ... 190
Errors ... 191
Examples ... 192
See Also ... 193
DescribeAutomationStepExecutions ... 194
Request Syntax ... 194
Request Parameters ... 194
Response Syntax ... 195
Response Elements ... 197
Errors ... 198
Examples ... 198
See Also ... 200
DescribeAvailablePatches ... 201
Request Syntax ... 201
Request Parameters ... 201
Response Syntax ... 204
Response Elements ... 205
Errors ... 205
Examples ... 205
See Also ... 208
DescribeDocument ... 210
Request Syntax ... 210
Request Parameters ... 210
Response Syntax ... 211
Response Elements ... 212
Errors ... 213
Examples ... 213
See Also ... 215
DescribeDocumentPermission ... 216
Request Syntax ... 216
Request Parameters ... 216

Response Syntax ... 217
Response Elements ... 217
Errors ... 218
Examples ... 219
See Also ... 220
DescribeEffectiveInstanceAssociations ... 221
Request Syntax ... 221
Request Parameters ... 221
Response Syntax ... 222
Response Elements ... 222
Errors ... 222
Examples ... 223
See Also ... 224
DescribeEffectivePatchesForPatchBaseline ... 225
Request Syntax ... 225
Request Parameters ... 225
Response Syntax ... 226
Response Elements ... 227
Errors ... 227
Examples ... 228
See Also ... 231
DescribeInstanceAssociationsStatus ... 232
Request Syntax ... 232
Request Parameters ... 232
Response Syntax ... 233
Response Elements ... 233
Errors ... 234
Examples ... 234
See Also ... 235
DescribeInstanceInformation ... 237
Request Syntax ... 237
Request Parameters ... 237
Response Syntax ... 239
Response Elements ... 240
Errors ... 240
Examples ... 241

See Also ... 242
DescribeInstancePatches ... 244
Request Syntax ... 244
Request Parameters ... 244
Response Syntax ... 245
Response Elements ... 246
Errors ... 246
Examples ... 247
See Also ... 249
DescribeInstancePatchStates ... 250
Request Syntax ... 250
Request Parameters ... 250
Response Syntax ... 251
Response Elements ... 251
Errors ... 252
Examples ... 252
See Also ... 254
DescribeInstancePatchStatesForPatchGroup ... 255
Request Syntax ... 255
Request Parameters ... 255
Response Syntax ... 256
Response Elements ... 257
Errors ... 257
Examples ... 258
See Also ... 260
DescribeInstanceProperties ... 261
Request Syntax ... 261
Request Parameters ... 261
Response Syntax ... 262
Response Elements ... 263
Errors ... 263
See Also ... 265
DescribeInventoryDeletions ... 266
Request Syntax ... 266
Request Parameters ... 266
Response Syntax ... 267

Response Elements ... 267
Errors ... 268
Examples ... 268
See Also ... 269
DescribeMaintenanceWindowExecutions ... 271
Request Syntax ... 271
Request Parameters ... 271
Response Syntax ... 272
Response Elements ... 273
Errors ... 273
Examples ... 273
See Also ... 275
DescribeMaintenanceWindowExecutionTaskInvocations ... 276
Request Syntax ... 276
Request Parameters ... 276
Response Syntax ... 277
Response Elements ... 278
Errors ... 278
Examples ... 279
See Also ... 280
DescribeMaintenanceWindowExecutionTasks ... 281
Request Syntax ... 281
Request Parameters ... 281
Response Syntax ... 282
Response Elements ... 283
Errors ... 283
Examples ... 284
See Also ... 285
DescribeMaintenanceWindows ... 286
Request Syntax ... 286
Request Parameters ... 286
Response Syntax ... 287
Response Elements ... 287
Errors ... 288
Examples ... 288
See Also ... 290

DescribeMaintenanceWindowSchedule ... 291
Request Syntax ... 291
Request Parameters ... 291
Response Syntax ... 293
Response Elements ... 293
Errors ... 293
Examples ... 294
See Also ... 295
DescribeMaintenanceWindowsForTarget ... 296
Request Syntax ... 296
Request Parameters ... 296
Response Syntax ... 297
Response Elements ... 297
Errors ... 298
Examples ... 298
See Also ... 299
DescribeMaintenanceWindowTargets ... 301
Request Syntax ... 301
Request Parameters ... 301
Response Syntax ... 302
Response Elements ... 303
Errors ... 303
Examples ... 304
See Also ... 305
DescribeMaintenanceWindowTasks ... 306
Request Syntax ... 306
Request Parameters ... 306
Response Syntax ... 307
Response Elements ... 308
Errors ... 309
Examples ... 309
See Also ... 311
DescribeOpsItems ... 312
Request Syntax ... 312
Request Parameters ... 312
Response Syntax ... 314

Response Elements ... 315
Errors ... 315
Examples ... 316
See Also ... 317
DescribeParameters ... 319
Request Syntax ... 319
Request Parameters ... 320
Response Syntax ... 321
Response Elements ... 322
Errors ... 322
Examples ... 323
See Also ... 325
DescribePatchBaselines ... 327
Request Syntax ... 327
Request Parameters ... 327
Response Syntax ... 328
Response Elements ... 328
Errors ... 329
Examples ... 329
See Also ... 331
DescribePatchGroups ... 332
Request Syntax ... 332
Request Parameters ... 332
Response Syntax ... 333
Response Elements ... 333
Errors ... 334
Examples ... 334
See Also ... 336
DescribePatchGroupState ... 337
Request Syntax ... 337
Request Parameters ... 337
Response Syntax ... 337
Response Elements ... 338
Errors ... 340
Examples ... 340
See Also ... 341

DescribePatchProperties ... 343
Request Syntax ... 344
Request Parameters ... 344
Response Syntax ... 345
Response Elements ... 345
Errors ... 346
Examples ... 346
See Also ... 347
DescribeSessions ... 349
Request Syntax ... 349
Request Parameters ... 349
Response Syntax ... 350
Response Elements ... 351
Errors ... 351
Examples ... 352
See Also ... 353
DisassociateOpsItemRelatedItem ... 354
Request Syntax ... 354
Request Parameters ... 354
Response Elements ... 354
Errors ... 355
Examples ... 355
See Also ... 356
GetAccessToken ... 357
Request Syntax ... 357
Request Parameters ... 357
Response Syntax ... 357
Response Elements ... 357
Errors ... 358
See Also ... 359
GetAutomationExecution ... 360
Request Syntax ... 360
Request Parameters ... 360
Response Syntax ... 360
Response Elements ... 366
Errors ... 366

Examples ... 366
See Also ... 368
GetCalendarState ... 370
Request Syntax ... 370
Request Parameters ... 370
Response Syntax ... 371
Response Elements ... 371
Errors ... 372
Examples ... 372
See Also ... 373
GetCommandInvocation ... 375
Request Syntax ... 375
Request Parameters ... 375
Response Syntax ... 376
Response Elements ... 377
Errors ... 381
Examples ... 382
See Also ... 384
GetConnectionStatus ... 385
Request Syntax ... 385
Request Parameters ... 385
Response Syntax ... 385
Response Elements ... 385
Errors ... 386
Examples ... 386
See Also ... 387
GetDefaultPatchBaseline ... 388
Request Syntax ... 388
Request Parameters ... 388
Response Syntax ... 388
Response Elements ... 388
Errors ... 389
Examples ... 389
See Also ... 390
GetDeployablePatchSnapshotForInstance ... 392
Request Syntax ... 392

Request Parameters ... 393
Response Syntax ... 394
Response Elements ... 394
Errors ... 395
Examples ... 396
See Also ... 397
GetDocument ... 398
Request Syntax ... 398
Request Parameters ... 398
Response Syntax ... 399
Response Elements ... 400
Errors ... 402
Examples ... 403
See Also ... 404
GetExecutionPreview ... 405
Request Syntax ... 405
Request Parameters ... 405
Response Syntax ... 405
Response Elements ... 406
Errors ... 407
Examples ... 407
See Also ... 408
GetInventory ... 409
Request Syntax ... 409
Request Parameters ... 410
Response Syntax ... 411
Response Elements ... 411
Errors ... 412
Examples ... 413
See Also ... 414
GetInventorySchema ... 415
Request Syntax ... 415
Request Parameters ... 415
Response Syntax ... 416
Response Elements ... 417
Errors ... 417

Examples ... 418
See Also ... 420
GetMaintenanceWindow ... 421
Request Syntax ... 421
Request Parameters ... 421
Response Syntax ... 421
Response Elements ... 422
Errors ... 424
Examples ... 425
See Also ... 426
GetMaintenanceWindowExecution ... 427
Request Syntax ... 427
Request Parameters ... 427
Response Syntax ... 427
Response Elements ... 428
Errors ... 429
Examples ... 429
See Also ... 430
GetMaintenanceWindowExecutionTask ... 432
Request Syntax ... 432
Request Parameters ... 432
Response Syntax ... 433
Response Elements ... 433
Errors ... 436
Examples ... 437
See Also ... 439
GetMaintenanceWindowExecutionTaskInvocation ... 440
Request Syntax ... 440
Request Parameters ... 440
Response Syntax ... 441
Response Elements ... 441
Errors ... 444
Examples ... 444
See Also ... 445
GetMaintenanceWindowTask ... 446
Request Syntax ... 446

Request Parameters ... 446
Response Syntax ... 447
Response Elements ... 449
Errors ... 453
Examples ... 453
See Also ... 455
GetOpsItem ... 456
Request Syntax ... 456
Request Parameters ... 456
Response Syntax ... 457
Response Elements ... 458
Errors ... 458
Examples ... 459
See Also ... 460
GetOpsMetadata ... 462
Request Syntax ... 462
Request Parameters ... 462
Response Syntax ... 463
Response Elements ... 463
Errors ... 464
See Also ... 464
GetOpsSummary ... 466
Request Syntax ... 466
Request Parameters ... 467
Response Syntax ... 468
Response Elements ... 469
Errors ... 469
Examples ... 470
See Also ... 471
GetParameter ... 473
Request Syntax ... 473
Request Parameters ... 473
Response Syntax ... 474
Response Elements ... 474
Errors ... 474
Examples ... 475

See Also ... 476
GetParameterHistory ... 478
Request Syntax ... 478
Request Parameters ... 478
Response Syntax ... 479
Response Elements ... 480
Errors ... 480
Examples ... 481
See Also ... 482
GetParameters ... 484
Request Syntax ... 484
Request Parameters ... 484
Response Syntax ... 485
Response Elements ... 485
Errors ... 486
Examples ... 486
See Also ... 488
GetParametersByPath ... 489
Request Syntax ... 489
Request Parameters ... 489
Response Syntax ... 491
Response Elements ... 492
Errors ... 492
Examples ... 493
See Also ... 494
GetPatchBaseline ... 496
Request Syntax ... 496
Request Parameters ... 496
Response Syntax ... 496
Response Elements ... 498
Errors ... 501
Examples ... 501
See Also ... 503
GetPatchBaselineForPatchGroup ... 505
Request Syntax ... 505
Request Parameters ... 505

Response Syntax ... 506
Response Elements ... 506
Errors ... 507
Examples ... 507
See Also ... 508
GetResourcePolicies ... 509
Request Syntax ... 509
Request Parameters ... 509
Response Syntax ... 510
Response Elements ... 510
Errors ... 510
See Also ... 511
GetServiceSetting ... 512
Request Syntax ... 512
Request Parameters ... 512
Response Syntax ... 513
Response Elements ... 513
Errors ... 513
Examples ... 514
See Also ... 515
LabelParameterVersion ... 516
Request Syntax ... 516
Request Parameters ... 517
Response Syntax ... 518
Response Elements ... 518
Errors ... 518
Examples ... 519
See Also ... 520
ListAssociations ... 521
Request Syntax ... 521
Request Parameters ... 521
Response Syntax ... 522
Response Elements ... 523
Errors ... 523
Examples ... 524
See Also ... 525

ListAssociationVersions ... 526
Request Syntax ... 526
Request Parameters ... 526
Response Syntax ... 527
Response Elements ... 528
Errors ... 529
Examples ... 529
See Also ... 531
ListCommandInvocations ... 532
Request Syntax ... 532
Request Parameters ... 532
Response Syntax ... 534
Response Elements ... 535
Errors ... 535
Examples ... 536
See Also ... 538
ListCommands ... 540
Request Syntax ... 540
Request Parameters ... 540
Response Syntax ... 541
Response Elements ... 543
Errors ... 543
Examples ... 544
See Also ... 546
ListComplianceItems ... 547
Request Syntax ... 547
Request Parameters ... 547
Response Syntax ... 548
Response Elements ... 549
Errors ... 549
Examples ... 550
See Also ... 552
ListComplianceSummaries ... 553
Request Syntax ... 553
Request Parameters ... 553
Response Syntax ... 554

Response Elements ... 555
Errors ... 555
Examples ... 556
See Also ... 558
ListDocumentMetadataHistory ... 559
Request Syntax ... 559
Request Parameters ... 559
Response Syntax ... 560
Response Elements ... 561
Errors ... 562
Examples ... 563
See Also ... 564
ListDocuments ... 565
Request Syntax ... 565
Request Parameters ... 565
Response Syntax ... 566
Response Elements ... 567
Errors ... 568
Examples ... 568
See Also ... 570
ListDocumentVersions ... 571
Request Syntax ... 571
Request Parameters ... 571
Response Syntax ... 572
Response Elements ... 572
Errors ... 573
Examples ... 573
See Also ... 574
ListInventoryEntries ... 576
Request Syntax ... 576
Request Parameters ... 576
Response Syntax ... 577
Response Elements ... 578
Errors ... 579
Examples ... 580
See Also ... 582

ListNodes ... 583
Request Syntax ... 583
Request Parameters ... 583
Response Syntax ... 584
Response Elements ... 585
Errors ... 585
Examples ... 586
See Also ... 587
ListNodesSummary ... 589
Request Syntax ... 589
Request Parameters ... 589
Response Syntax ... 591
Response Elements ... 591
Errors ... 592
Examples ... 592
See Also ... 594
ListOpsItemEvents ... 595
Request Syntax ... 595
Request Parameters ... 595
Response Syntax ... 596
Response Elements ... 596
Errors ... 597
See Also ... 597
ListOpsItemRelatedItems ... 599
Request Syntax ... 599
Request Parameters ... 599
Response Syntax ... 600
Response Elements ... 601
Errors ... 601
Examples ... 601
See Also ... 603
ListOpsMetadata ... 604
Request Syntax ... 604
Request Parameters ... 604
Response Syntax ... 605
Response Elements ... 605

Errors ... 606
See Also ... 606
ListResourceComplianceSummaries ... 607
Request Syntax ... 607
Request Parameters ... 607
Response Syntax ... 608
Response Elements ... 609
Errors ... 609
Examples ... 610
See Also ... 612
ListResourceDataSync ... 613
Request Syntax ... 613
Request Parameters ... 613
Response Syntax ... 614
Response Elements ... 615
Errors ... 615
Examples ... 616
See Also ... 617
ListTagsForResource ... 618
Request Syntax ... 618
Request Parameters ... 618
Response Syntax ... 618
Response Elements ... 619
Errors ... 619
Examples ... 620
See Also ... 621
ModifyDocumentPermission ... 622
Request Syntax ... 622
Request Parameters ... 622
Response Elements ... 624
Errors ... 624
Examples ... 625
See Also ... 625
PutComplianceItems ... 627
Request Syntax ... 628
Request Parameters ... 628

Response Elements ... 630
Errors ... 631
Examples ... 632
See Also ... 633
PutInventory ... 634
Request Syntax ... 634
Request Parameters ... 634
Response Syntax ... 635
Response Elements ... 635
Errors ... 635
Examples ... 637
See Also ... 638
PutParameter ... 639
Request Syntax ... 639
Request Parameters ... 639
Response Syntax ... 646
Response Elements ... 646
Errors ... 647
Examples ... 650
See Also ... 651
PutResourcePolicy ... 652
Request Syntax ... 652
Request Parameters ... 653
Response Syntax ... 654
Response Elements ... 654
Errors ... 654
See Also ... 655
RegisterDefaultPatchBaseline ... 657
Request Syntax ... 657
Request Parameters ... 657
Response Syntax ... 657
Response Elements ... 658
Errors ... 658
Examples ... 659
See Also ... 659
RegisterPatchBaselineForPatchGroup ... 661

Request Syntax ... 661
Request Parameters ... 661
Response Syntax ... 662
Response Elements ... 662
Errors ... 662
Examples ... 663
See Also ... 664
RegisterTargetWithMaintenanceWindow ... 665
Request Syntax ... 665
Request Parameters ... 665
Response Syntax ... 668
Response Elements ... 668
Errors ... 668
Examples ... 669
See Also ... 670
RegisterTaskWithMaintenanceWindow ... 672
Request Syntax ... 672
Request Parameters ... 673
Response Syntax ... 679
Response Elements ... 679
Errors ... 680
Examples ... 681
See Also ... 682
RemoveTagsFromResource ... 683
Request Syntax ... 683
Request Parameters ... 683
Response Elements ... 685
Errors ... 685
Examples ... 685
See Also ... 686
ResetServiceSetting ... 687
Request Syntax ... 687
Request Parameters ... 687
Response Syntax ... 688
Response Elements ... 688
Errors ... 688

Examples ... 689
See Also ... 690
ResumeSession ... 691
Request Syntax ... 691
Request Parameters ... 691
Response Syntax ... 691
Response Elements ... 692
Errors ... 692
Examples ... 693
See Also ... 694
SendAutomationSignal ... 695
Request Syntax ... 695
Request Parameters ... 695
Response Elements ... 696
Errors ... 696
Examples ... 697
See Also ... 698
SendCommand ... 699
Request Syntax ... 699
Request Parameters ... 700
Response Syntax ... 705
Response Elements ... 707
Errors ... 707
Examples ... 709
See Also ... 711
StartAccessRequest ... 713
Request Syntax ... 713
Request Parameters ... 713
Response Syntax ... 714
Response Elements ... 714
Errors ... 714
See Also ... 716
StartAssociationsOnce ... 717
Request Syntax ... 717
Request Parameters ... 717
Response Elements ... 717

Errors ... 717
Examples ... 718
See Also ... 718
StartAutomationExecution ... 720
Request Syntax ... 720
Request Parameters ... 721
Response Syntax ... 726
Response Elements ... 726
Errors ... 727
Examples ... 728
See Also ... 729
StartChangeRequestExecution ... 730
Request Syntax ... 730
Request Parameters ... 732
Response Syntax ... 735
Response Elements ... 735
Errors ... 736
Examples ... 737
See Also ... 739
StartExecutionPreview ... 740
Request Syntax ... 740
Request Parameters ... 740
Response Syntax ... 741
Response Elements ... 741
Errors ... 741
Examples ... 742
See Also ... 743
StartSession ... 744
Request Syntax ... 744
Request Parameters ... 744
Response Syntax ... 746
Response Elements ... 746
Errors ... 747
Examples ... 747
See Also ... 748
StopAutomationExecution ... 750

Request Syntax ... 750
Request Parameters ... 750
Response Elements ... 750
Errors ... 751
Examples ... 751
See Also ... 752
TerminateSession ... 753
Request Syntax ... 753
Request Parameters ... 753
Response Syntax ... 753
Response Elements ... 753
Errors ... 754
Examples ... 754
See Also ... 755
UnlabelParameterVersion ... 756
Request Syntax ... 756
Request Parameters ... 756
Response Syntax ... 757
Response Elements ... 757
Errors ... 758
Examples ... 759
See Also ... 759
UpdateAssociation ... 761
Request Syntax ... 761
Request Parameters ... 763
Response Syntax ... 771
Response Elements ... 773
Errors ... 773
Examples ... 775
See Also ... 776
UpdateAssociationStatus ... 778
Request Syntax ... 778
Request Parameters ... 778
Response Syntax ... 779
Response Elements ... 781
Errors ... 781

See Also ... 783
UpdateDocument ... 784
Request Syntax ... 784
Request Parameters ... 784
Response Syntax ... 786
Response Elements ... 788
Errors ... 788
Examples ... 790
See Also ... 791
UpdateDocumentDefaultVersion ... 793
Request Syntax ... 793
Request Parameters ... 793
Response Syntax ... 794
Response Elements ... 794
Errors ... 794
Examples ... 795
See Also ... 796
UpdateDocumentMetadata ... 797
Request Syntax ... 797
Request Parameters ... 797
Response Elements ... 798
Errors ... 798
Examples ... 799
See Also ... 800
UpdateMaintenanceWindow ... 801
Request Syntax ... 801
Request Parameters ... 801
Response Syntax ... 805
Response Elements ... 805
Errors ... 807
Examples ... 808
See Also ... 809
UpdateMaintenanceWindowTarget ... 810
Request Syntax ... 810
Request Parameters ... 810
Response Syntax ... 812

Response Elements ... 813
Errors ... 814
Examples ... 815
See Also ... 816
UpdateMaintenanceWindowTask ... 817
Request Syntax ... 818
Request Parameters ... 820
Response Syntax ... 826
Response Elements ... 828
Errors ... 831
Examples ... 832
See Also ... 833
UpdateManagedInstanceRole ... 835
Request Syntax ... 835
Request Parameters ... 835
Response Elements ... 836
Errors ... 836
Examples ... 836
See Also ... 837
UpdateOpsItem ... 839
Request Syntax ... 839
Request Parameters ... 840
Response Elements ... 844
Errors ... 844
Examples ... 845
See Also ... 846
UpdateOpsMetadata ... 847
Request Syntax ... 847
Request Parameters ... 847
Response Syntax ... 848
Response Elements ... 848
Errors ... 849
See Also ... 849
UpdatePatchBaseline ... 851
Request Syntax ... 851
Request Parameters ... 852

Response Syntax ... 856
Response Elements ... 857
Errors ... 860
Examples ... 861
See Also ... 863
UpdateResourceDataSync ... 864
Request Syntax ... 864
Request Parameters ... 864
Response Elements ... 865
Errors ... 865
Examples ... 866
See Also ... 867
UpdateServiceSetting ... 868
Request Syntax ... 868
Request Parameters ... 868
Response Elements ... 870
Errors ... 870
Examples ... 870
See Also ... 871
Data Types ... 873
AccountSharingInfo ... 879
Contents ... 879
See Also ... 879
Activation ... 880
Contents ... 880
See Also ... 882
Alarm ... 883
Contents ... 883
See Also ... 883
AlarmConfiguration ... 884
Contents ... 884
See Also ... 884
AlarmStateInformation ... 885
Contents ... 885
See Also ... 885
Association ... 886

Contents ... 886
See Also ... 889
AssociationDescription ... 890
Contents ... 890
See Also ... 897
AssociationExecution ... 898
Contents ... 898
See Also ... 900
AssociationExecutionFilter ... 901
Contents ... 901
See Also ... 901
AssociationExecutionTarget ... 903
Contents ... 903
See Also ... 905
AssociationExecutionTargetsFilter ... 906
Contents ... 906
See Also ... 906
AssociationFilter ... 907
Contents ... 907
See Also ... 907
AssociationOverview ... 909
Contents ... 909
See Also ... 909
AssociationStatus ... 910
Contents ... 910
See Also ... 911
AssociationVersionInfo ... 912
Contents ... 912
See Also ... 917
AttachmentContent ... 918
Contents ... 918
See Also ... 919
AttachmentInformation ... 920
Contents ... 920
See Also ... 920
AttachmentsSource ... 921

Contents ... 921
See Also ... 922
AutomationExecution ... 923
Contents ... 923
See Also ... 931
AutomationExecutionFilter ... 932
Contents ... 932
See Also ... 932
AutomationExecutionInputs ... 934
Contents ... 934
See Also ... 935
AutomationExecutionMetadata ... 937
Contents ... 937
See Also ... 944
AutomationExecutionPreview ... 945
Contents ... 945
See Also ... 946
BaselineOverride ... 947
Contents ... 947
See Also ... 949
CloudWatchOutputConfig ... 950
Contents ... 950
See Also ... 950
Command ... 951
Contents ... 951
See Also ... 957
CommandFilter ... 958
Contents ... 958
See Also ... 960
CommandInvocation ... 961
Contents ... 961
See Also ... 965
CommandPlugin ... 966
Contents ... 966
See Also ... 970
ComplianceExecutionSummary ... 971

Contents ... 971
See Also ... 972
ComplianceItem ... 973
Contents ... 973
See Also ... 975
ComplianceItemEntry ... 976
Contents ... 976
See Also ... 977
ComplianceStringFilter ... 978
Contents ... 978
See Also ... 978
ComplianceSummaryItem ... 980
Contents ... 980
See Also ... 980
CompliantSummary ... 982
Contents ... 982
See Also ... 982
CreateAssociationBatchRequestEntry ... 983
Contents ... 983
See Also ... 989
Credentials ... 990
Contents ... 990
See Also ... 990
DescribeActivationsFilter ... 992
Contents ... 992
See Also ... 992
DocumentDefaultVersionDescription ... 993
Contents ... 993
See Also ... 993
DocumentDescription ... 995
Contents ... 995
See Also ... 1001
DocumentFilter ... 1003
Contents ... 1003
See Also ... 1003
DocumentIdentifier ... 1004

Contents 1004
See Also 1007
DocumentKeyValuesFilter 1008
Contents 1009
See Also 1009
DocumentMetadataResponseInfo 1011
Contents 1011
See Also 1011
DocumentParameter 1012
Contents 1012
See Also 1013
DocumentRequires 1014
Contents 1014
See Also 1015
DocumentReviewCommentSource 1016
Contents 1016
See Also 1016
DocumentReviewerResponseSource 1017
Contents 1017
See Also 1018
DocumentReviews 1019
Contents 1019
See Also 1019
DocumentVersionInfo 1020
Contents 1020
See Also 1022
EffectivePatch 1023
Contents 1023
See Also 1023
ExecutionInputs 1024
Contents 1024
See Also 1024
ExecutionPreview 1025
Contents 1025
See Also 1025
FailedCreateAssociation 1026

Contents ... 1026
See Also ... 1026
FailureDetails ... 1027
Contents ... 1027
See Also ... 1027
GetResourcePoliciesResponseEntry ... 1029
Contents ... 1029
See Also ... 1029
InstanceAggregatedAssociationOverview ... 1031
Contents ... 1031
See Also ... 1031
InstanceAssociation ... 1032
Contents ... 1032
See Also ... 1033
InstanceAssociationOutputLocation ... 1034
Contents ... 1034
See Also ... 1034
InstanceAssociationOutputUrl ... 1035
Contents ... 1035
See Also ... 1035
InstanceAssociationStatusInfo ... 1036
Contents ... 1036
See Also ... 1038
InstanceInfo ... 1039
Contents ... 1039
See Also ... 1041
InstanceInformation ... 1042
Contents ... 1042
See Also ... 1046
InstanceInformationFilter ... 1048
Contents ... 1048
See Also ... 1048
InstanceInformationStringFilter ... 1050
Contents ... 1050
See Also ... 1051
InstancePatchState ... 1052

Contents 1052
See Also 1057
InstancePatchStateFilter 1059
Contents 1059
See Also 1060
InstanceProperty 1061
Contents 1061
See Also 1066
InstancePropertyFilter 1067
Contents 1067
See Also 1067
InstancePropertyStringFilter 1069
Contents 1069
See Also 1070
InventoryAggregator 1071
Contents 1071
See Also 1071
InventoryDeletionStatusItem 1073
Contents 1073
See Also 1074
InventoryDeletionSummary 1075
Contents 1075
See Also 1075
InventoryDeletionSummaryItem 1076
Contents 1076
See Also 1076
InventoryFilter 1077
Contents 1077
See Also 1078
InventoryGroup 1079
Contents 1079
See Also 1079
InventoryItem 1080
Contents 1080
See Also 1081
InventoryItemAttribute 1083

Contents ... 1083
See Also ... 1083
InventoryItemSchema ... 1084
Contents ... 1084
See Also ... 1085
InventoryResultEntity ... 1086
Contents ... 1086
See Also ... 1086
InventoryResultItem ... 1087
Contents ... 1087
See Also ... 1088
LoggingInfo ... 1089
Contents ... 1089
See Also ... 1090
MaintenanceWindowAutomationParameters ... 1091
Contents ... 1091
See Also ... 1092
MaintenanceWindowExecution ... 1093
Contents ... 1093
See Also ... 1094
MaintenanceWindowExecutionTaskIdentity ... 1095
Contents ... 1095
See Also ... 1097
MaintenanceWindowExecutionTaskInvocationIdentity ... 1098
Contents ... 1098
See Also ... 1100
MaintenanceWindowFilter ... 1102
Contents ... 1102
See Also ... 1102
MaintenanceWindowIdentity ... 1104
Contents ... 1104
See Also ... 1106
MaintenanceWindowIdentityForTarget ... 1107
Contents ... 1107
See Also ... 1107
MaintenanceWindowLambdaParameters ... 1108

Contents 1108
See Also 1109
MaintenanceWindowRunCommandParameters 1110
Contents 1110
See Also 1113
MaintenanceWindowStepFunctionsParameters 1114
Contents 1114
See Also 1115
MaintenanceWindowTarget 1116
Contents 1116
See Also 1118
MaintenanceWindowTask 1119
Contents 1119
See Also 1124
MaintenanceWindowTaskInvocationParameters 1125
Contents 1125
See Also 1125
MaintenanceWindowTaskParameterValueExpression 1127
Contents 1127
See Also 1127
MetadataValue 1128
Contents 1128
See Also 1128
Node 1129
Contents 1129
See Also 1130
NodeAggregator 1131
Contents 1131
See Also 1132
NodeFilter 1133
Contents 1133
See Also 1134
NodeOwnerInfo 1135
Contents 1135
See Also 1136
NodeType 1137

Contents ... 1137
See Also ... 1137
NonCompliantSummary ... 1138
Contents ... 1138
See Also ... 1138
NotificationConfig ... 1139
Contents ... 1139
See Also ... 1140
OpsAggregator ... 1141
Contents ... 1141
See Also ... 1142
OpsEntity ... 1143
Contents ... 1143
See Also ... 1143
OpsEntityItem ... 1144
Contents ... 1144
See Also ... 1144
OpsFilter ... 1146
Contents ... 1146
See Also ... 1146
OpsItem ... 1148
Contents ... 1148
See Also ... 1154
OpsItemDataValue ... 1155
Contents ... 1155
See Also ... 1155
OpsItemEventFilter ... 1156
Contents ... 1156
See Also ... 1156
OpsItemEventSummary ... 1158
Contents ... 1158
See Also ... 1159
OpsItemFilter ... 1160
Contents ... 1160
See Also ... 1161
OpsItemIdentity ... 1162

Contents 1162
See Also 1162
OpsItemNotification 1163
Contents 1163
See Also 1163
OpsItemRelatedItemsFilter 1164
Contents 1164
See Also 1164
OpsItemRelatedItemSummary 1166
Contents 1166
See Also 1167
OpsItemSummary 1168
Contents 1168
See Also 1172
OpsMetadata 1173
Contents 1173
See Also 1174
OpsMetadataFilter 1175
Contents 1175
See Also 1175
OpsResultAttribute 1176
Contents 1176
See Also 1176
OutputSource 1177
Contents 1177
See Also 1177
Parameter 1178
Contents 1178
See Also 1180
ParameterHistory 1181
Contents 1181
See Also 1183
ParameterInlinePolicy 1185
Contents 1185
See Also 1185
ParameterMetadata 1187

Contents ... 1187
See Also ... 1189
ParametersFilter ... 1190
Contents ... 1190
See Also ... 1190
ParameterStringFilter ... 1191
Contents ... 1191
See Also ... 1192
ParentStepDetails ... 1193
Contents ... 1193
See Also ... 1194
Patch ... 1195
Contents ... 1195
See Also ... 1199
PatchBaselineIdentity ... 1200
Contents ... 1200
See Also ... 1201
PatchComplianceData ... 1202
Contents ... 1202
See Also ... 1203
PatchFilter ... 1204
Contents ... 1204
See Also ... 1205
PatchFilterGroup ... 1206
Contents ... 1206
See Also ... 1206
PatchGroupPatchBaselineMapping ... 1207
Contents ... 1207
See Also ... 1207
PatchOrchestratorFilter ... 1208
Contents ... 1208
See Also ... 1208
PatchRule ... 1210
Contents ... 1210
See Also ... 1212
PatchRuleGroup ... 1213

Contents ... 1213
See Also ... 1213
PatchSource ... 1214
Contents ... 1214
See Also ... 1215
PatchStatus ... 1216
Contents ... 1216
See Also ... 1216
ProgressCounters ... 1218
Contents ... 1218
See Also ... 1219
RegistrationMetadataItem ... 1220
Contents ... 1220
See Also ... 1220
RelatedOpsItem ... 1221
Contents ... 1221
See Also ... 1221
ResolvedTargets ... 1222
Contents ... 1222
See Also ... 1222
ResourceComplianceSummaryItem ... 1223
Contents ... 1223
See Also ... 1224
ResourceDataSyncAwsOrganizationsSource ... 1226
Contents ... 1226
See Also ... 1226
ResourceDataSyncDestinationDataSharing ... 1227
Contents ... 1227
See Also ... 1227
ResourceDataSyncItem ... 1228
Contents ... 1228
See Also ... 1230
ResourceDataSyncOrganizationalUnit ... 1231
Contents ... 1231
See Also ... 1231
ResourceDataSyncS3Destination ... 1232

Contents 1232
See Also 1233
ResourceDataSyncSource 1234
Contents 1234
See Also 1235
ResourceDataSyncSourceWithState 1236
Contents 1236
See Also 1238
ResultAttribute 1239
Contents 1239
See Also 1239
ReviewInformation 1240
Contents 1240
See Also 1240
Runbook 1242
Contents 1242
See Also 1244
S3OutputLocation 1246
Contents 1246
See Also 1246
S3OutputUrl 1248
Contents 1248
See Also 1248
ScheduledWindowExecution 1249
Contents 1249
See Also 1249
ServiceSetting 1251
Contents 1251
See Also 1252
Session 1253
Contents 1253
See Also 1255
SessionFilter 1256
Contents 1256
See Also 1257
SessionManagerOutputUrl 1258

Contents 1258
See Also 1258
SeveritySummary 1259
Contents 1259
See Also 1260
StepExecution 1261
Contents 1261
See Also 1266
StepExecutionFilter 1267
Contents 1267
See Also 1267
Tag 1268
Contents 1268
See Also 1268
Target 1270
Contents 1271
See Also 1272
TargetLocation 1273
Contents 1273
See Also 1276
TargetPreview 1277
Contents 1277
See Also 1277
Common Parameters 1278
Common Error Types 1281

Welcome

AWS Systems Manager is the operations hub for your AWS applications and resources and a secure end-to-end management solution for hybrid cloud environments that enables safe and secure operations at scale.

This reference is intended to be used with the AWS Systems Manager User Guide. To get started, see Setting up AWS Systems Manager.

Related resources

- For information about each of the tools that comprise Systems Manager, see Using Systems Manager tools in the *AWS Systems Manager User Guide*.
- For details about predefined runbooks for Automation, a tool in AWS Systems Manager, see the *Systems Manager Automation Runbook Reference* .
- For information about AWS AppConfig, a tool in Systems Manager, see the *AWS AppConfig User Guide* and the *AWS AppConfig API Reference* .
- For information about Incident Manager, a tool in Systems Manager, see the *AWS Systems Manager Incident Manager User Guide* and the *AWS Systems Manager Incident Manager API Reference* .

This document was last published on April 5, 2026.

Actions

The following actions are supported:

- AddTagsToResource
- AssociateOpsItemRelatedItem
- CancelCommand
- CancelMaintenanceWindowExecution
- CreateActivation
- CreateAssociation
- CreateAssociationBatch
- CreateDocument
- CreateMaintenanceWindow
- CreateOpsItem
- CreateOpsMetadata
- CreatePatchBaseline
- CreateResourceDataSync
- DeleteActivation
- DeleteAssociation
- DeleteDocument
- DeleteInventory
- DeleteMaintenanceWindow
- DeleteOpsItem
- DeleteOpsMetadata
- DeleteParameter
- DeleteParameters
- DeletePatchBaseline
- DeleteResourceDataSync
- DeleteResourcePolicy
- DeregisterManagedInstance
- DeregisterPatchBaselineForPatchGroup

- DeregisterTargetFromMaintenanceWindow
- DeregisterTaskFromMaintenanceWindow
- DescribeActivations
- DescribeAssociation
- DescribeAssociationExecutions
- DescribeAssociationExecutionTargets
- DescribeAutomationExecutions
- DescribeAutomationStepExecutions
- DescribeAvailablePatches
- DescribeDocument
- DescribeDocumentPermission
- DescribeEffectiveInstanceAssociations
- DescribeEffectivePatchesForPatchBaseline
- DescribeInstanceAssociationsStatus
- DescribeInstanceInformation
- DescribeInstancePatches
- DescribeInstancePatchStates
- DescribeInstancePatchStatesForPatchGroup
- DescribeInstanceProperties
- DescribeInventoryDeletions
- DescribeMaintenanceWindowExecutions
- DescribeMaintenanceWindowExecutionTaskInvocations
- DescribeMaintenanceWindowExecutionTasks
- DescribeMaintenanceWindows
- DescribeMaintenanceWindowSchedule
- DescribeMaintenanceWindowsForTarget
- DescribeMaintenanceWindowTargets
- DescribeMaintenanceWindowTasks
- DescribeOpsItems
- DescribeParameters

- DescribePatchBaselines
- DescribePatchGroups
- DescribePatchGroupState
- DescribePatchProperties
- DescribeSessions
- DisassociateOpsItemRelatedItem
- GetAccessToken
- GetAutomationExecution
- GetCalendarState
- GetCommandInvocation
- GetConnectionStatus
- GetDefaultPatchBaseline
- GetDeployablePatchSnapshotForInstance
- GetDocument
- GetExecutionPreview
- GetInventory
- GetInventorySchema
- GetMaintenanceWindow
- GetMaintenanceWindowExecution
- GetMaintenanceWindowExecutionTask
- GetMaintenanceWindowExecutionTaskInvocation
- GetMaintenanceWindowTask
- GetOpsItem
- GetOpsMetadata
- GetOpsSummary
- GetParameter
- GetParameterHistory
- GetParameters
- GetParametersByPath
- GetPatchBaseline

- GetPatchBaselineForPatchGroup
- GetResourcePolicies
- GetServiceSetting
- LabelParameterVersion
- ListAssociations
- ListAssociationVersions
- ListCommandInvocations
- ListCommands
- ListComplianceItems
- ListComplianceSummaries
- ListDocumentMetadataHistory
- ListDocuments
- ListDocumentVersions
- ListInventoryEntries
- ListNodes
- ListNodesSummary
- ListOpsItemEvents
- ListOpsItemRelatedItems
- ListOpsMetadata
- ListResourceComplianceSummaries
- ListResourceDataSync
- ListTagsForResource
- ModifyDocumentPermission
- PutComplianceItems
- PutInventory
- PutParameter
- PutResourcePolicy
- RegisterDefaultPatchBaseline
- RegisterPatchBaselineForPatchGroup
- RegisterTargetWithMaintenanceWindow

- RegisterTaskWithMaintenanceWindow
- RemoveTagsFromResource
- ResetServiceSetting
- ResumeSession
- SendAutomationSignal
- SendCommand
- StartAccessRequest
- StartAssociationsOnce
- StartAutomationExecution
- StartChangeRequestExecution
- StartExecutionPreview
- StartSession
- StopAutomationExecution
- TerminateSession
- UnlabelParameterVersion
- UpdateAssociation
- UpdateAssociationStatus
- UpdateDocument
- UpdateDocumentDefaultVersion
- UpdateDocumentMetadata
- UpdateMaintenanceWindow
- UpdateMaintenanceWindowTarget
- UpdateMaintenanceWindowTask
- UpdateManagedInstanceRole
- UpdateOpsItem
- UpdateOpsMetadata
- UpdatePatchBaseline
- UpdateResourceDataSync
- UpdateServiceSetting

AddTagsToResource

Adds or overwrites one or more tags for the specified resource. *Tags* are metadata that you can assign to your automations, documents, managed nodes, maintenance windows, Parameter Store parameters, and patch baselines. Tags enable you to categorize your resources in different ways, for example, by purpose, owner, or environment. Each tag consists of a key and an optional value, both of which you define. For example, you could define a set of tags for your account's managed nodes that helps you track each node's owner and stack level. For example:

- `Key=Owner,Value=DbAdmin`
- `Key=Owner,Value=SysAdmin`
- `Key=Owner,Value=Dev`
- `Key=Stack,Value=Production`
- `Key=Stack,Value=Pre-Production`
- `Key=Stack,Value=Test`

Most resources can have a maximum of 50 tags. Automations can have a maximum of 5 tags.

We recommend that you devise a set of tag keys that meets your needs for each resource type. Using a consistent set of tag keys makes it easier for you to manage your resources. You can search and filter the resources based on the tags you add. Tags don't have any semantic meaning to and are interpreted strictly as a string of characters.

For more information about using tags with Amazon Elastic Compute Cloud (Amazon EC2) instances, see Tag your Amazon EC2 resources in the *Amazon EC2 User Guide*.

Request Syntax

```
{
   "ResourceId": "string",
   "ResourceType": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceId

The resource ID you want to tag.

Use the ID of the resource. Here are some examples:

`MaintenanceWindow`: `mw-012345abcde`

`PatchBaseline`: `pb-012345abcde`

`Automation`: `example-c160-4567-8519-012345abcde`

`OpsMetadata` object: `ResourceID` for tagging is created from the Amazon Resource Name (ARN) for the object. Specifically, `ResourceID` is created from the strings that come after the word `opsmetadata` in the ARN. For example, an OpsMetadata object with an ARN of `arn:aws:ssm:us-east-2:1234567890:opsmetadata/aws/ssm/MyGroup/appmanager` has a `ResourceID` of either `aws/ssm/MyGroup/appmanager` or `/aws/ssm/MyGroup/appmanager`.

For the `Document` and `Parameter` values, use the name of the resource. If you're tagging a shared document, you must use the full ARN of the document.

`ManagedInstance`: `mi-012345abcde`

> **Note**
>
> The `ManagedInstance` type for this API operation is only for on-premises managed nodes. You must specify the name of the managed node in the following format: `mi-`*`ID_number`* . For example, `mi-1a2b3c4d5e6f`.

Type: String

Required: Yes

ResourceType

Specifies the type of resource you are tagging.

> **Note**
>
> The `ManagedInstance` type for this API operation is for on-premises managed nodes. You must specify the name of the managed node in the following format: `mi-ID_number` . For example, `mi-1a2b3c4d5e6f`.

Type: String

Valid Values: `Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation | Association`

Required: Yes

Tags

One or more tags. The value parameter is required.

> **Important**
>
> Don't enter personally identifiable information in this field.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

TooManyTagsError

The `Targets` parameter includes too many tags. Remove one or more tags and try the command again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of AddTagsToResource.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.AddTagsToResource
```

```
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240220T232503Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 122

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE",
    "Tags": [
        {
            "Key": "Stack",
            "Value": "Production"
        }
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

AssociateOpsItemRelatedItem

Associates a related item to a Systems Manager OpsCenter OpsItem. For example, you can associate an Incident Manager incident or analysis with an OpsItem. Incident Manager and OpsCenter are tools in AWS Systems Manager.

Request Syntax

```
{
   "AssociationType": "string",
   "OpsItemId": "string",
   "ResourceType": "string",
   "ResourceUri": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationType

The type of association that you want to create between an OpsItem and a resource. OpsCenter supports `IsParentOf` and `RelatesTo` association types.

Type: String

Required: Yes

OpsItemId

The ID of the OpsItem to which you want to associate a resource as a related item.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

ResourceType

The type of resource that you want to associate with an OpsItem. OpsCenter supports the following types:

`AWS::SSMIncidents::IncidentRecord`: an Incident Manager incident.

`AWS::SSM::Document`: a Systems Manager (SSM) document.

Type: String

Required: Yes

ResourceUri

The Amazon Resource Name (ARN) of the AWS resource that you want to associate with the OpsItem.

Type: String

Required: Yes

Response Syntax

```
{
   "AssociationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationId

The association ID.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemConflictException

The specified OpsItem is in the process of being deleted.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

OpsItemRelatedItemAlreadyExistsException

The Amazon Resource Name (ARN) is already associated with the OpsItem.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of AssociateOpsItemRelatedItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.AssociateOpsItemRelatedItem
Content-Type: application/x-amz-json-1.1
```

```
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/
x86_64.amzn.2 prompt/off command/ssm.associate-ops-item-related-item
X-Amz-Date: 20240804T181929Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240804/us-east-1/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 229

{
  "OpsItemId": "oi-649fExample",
  "AssociationType": "RelatesTo",
  "ResourceType": "AWS::SSMIncidents::IncidentRecord",
  "ResourceUri": "arn:aws:ssm-incidents::111122223333:incident-record/Test/c6bd8931-
efae-a4ff-7f98-4490Example"
}
```

Sample Response

```
{
        "AssociationId": "61d7178d-a30d-4bc5-9b4e-a9e74EXAMPLE"
    }
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CancelCommand

Attempts to cancel the command specified by the Command ID. There is no guarantee that the command will be terminated and the underlying process stopped.

Request Syntax

```
{
   "CommandId": "string",
   "InstanceIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

CommandId

The ID of the command you want to cancel.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

InstanceIds

(Optional) A list of managed node IDs on which you want to cancel the command. If not provided, the command is canceled on every node on which it was requested.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CancelCommand.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CancelCommand
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240220T233525Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53

{
    "CommandId": "25173b39-c88d-4459-ba3d-8704aEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CancelMaintenanceWindowExecution

Stops a maintenance window execution that is already in progress and cancels any tasks in the window that haven't already starting running. Tasks already in progress will continue to completion.

Request Syntax

```
{
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowExecutionId

The ID of the maintenance window execution to stop.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "WindowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowExecutionId

The ID of the maintenance window execution that has been stopped.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of CancelMaintenanceWindowExecution.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CancelMaintenanceWindowExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T010054Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 61

{
    "WindowExecutionId": "02f05632-d0bc-470d-b1e5-c59a8EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "02f05632-d0bc-470d-b1e5-c59a8EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateActivation

Generates an activation code and activation ID you can use to register your on-premises servers, edge devices, or virtual machine (VM) with AWS Systems Manager. Registering these machines with Systems Manager makes it possible to manage them using Systems Manager tools. You use the activation code and ID when installing SSM Agent on machines in your hybrid environment. For more information about requirements for managing on-premises machines using Systems Manager, see Using AWS Systems Manager in hybrid and multicloud environments in the *AWS Systems Manager User Guide*.

> **Note**
>
> Amazon Elastic Compute Cloud (Amazon EC2) instances, edge devices, and on-premises servers and VMs that are configured for Systems Manager are all called *managed nodes*.

Request Syntax

```
{
   "DefaultInstanceName": "string",
   "Description": "string",
   "ExpirationDate": number,
   "IamRole": "string",
   "RegistrationLimit": number,
   "RegistrationMetadata": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DefaultInstanceName

The name of the registered, managed node as it will appear in the AWS Systems Manager console or when you use the AWS command line tools to list Systems Manager resources.

> **Important**
> Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: No

Description

A user-defined description of the resource that you want to register with Systems Manager.

> **Important**
> Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ExpirationDate

The date by which this activation request should expire, in timestamp format, such as "2024-07-07T00:00:00". You can specify a date up to 30 days in advance. If you don't provide an expiration date, the activation code expires in 24 hours.

Type: Timestamp

Required: No

IamRole

The name of the AWS Identity and Access Management (IAM) role that you want to assign to the managed node. This IAM role must provide AssumeRole permissions for the AWS Systems Manager service principal `ssm.amazonaws.com`. For more information, see Create the IAM service role required for Systems Manager in a hybrid and multicloud environments in the *AWS Systems Manager User Guide*.

> **Note**
>
> You can't specify an IAM service-linked role for this parameter. You must create a unique role.

Type: String

Length Constraints: Maximum length of 64.

Required: Yes

RegistrationLimit

Specify the maximum number of managed nodes you want to register. The default value is 1.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RegistrationMetadata

Reserved for internal use.

Type: Array of RegistrationMetadataItem objects

Required: No

Tags

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want

to tag an activation to identify which servers or virtual machines (VMs) in your on-premises environment you intend to activate. In this case, you could specify the following key-value pairs:

- `Key=OS,Value=Windows`
- `Key=Environment,Value=Production`

> **Important**
>
> When you install SSM Agent on your on-premises servers and VMs, you specify an activation ID and code. When you specify the activation ID and code, tags assigned to the activation are automatically applied to the on-premises servers or VMs.

You can't add tags to or delete tags from an existing activation. You can tag your on-premises servers, edge devices, and VMs after they connect to Systems Manager for the first time and are assigned a managed node ID. This means they are listed in the AWS Systems Manager console with an ID that is prefixed with "mi-". For information about how to add tags to your managed nodes, see AddTagsToResource. For information about how to remove tags from your managed nodes, see RemoveTagsFromResource.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
   "ActivationCode": "string",
   "ActivationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActivationCode

The code the system generates when it processes the activation. The activation code functions like a password to validate the activation ID.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 250.

ActivationId

The ID number generated by the system when it processed the activation. The activation ID functions like a user name.

Type: String

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateActivation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateActivation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T135329Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 70

{
    "IamRole": "service-role/role_name"
}
```

Sample Response

```
{
    "ActivationCode": "Fjz3/sZfSvv78EXAMPLE",
    "ActivationId": "e488f2f6-e686-4afb-8a04-ef6dfEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

CreateAssociation

A State Manager association defines the state that you want to maintain on your managed nodes. For example, an association can specify that anti-virus software must be installed and running on your managed nodes, or that certain ports must be closed. For static targets, the association specifies a schedule for when the configuration is reapplied. For dynamic targets, such as an AWS resource group or an AWS autoscaling group, State Manager, a tool in AWS Systems Manager applies the configuration when new managed nodes are added to the group. The association also specifies actions to take when applying the configuration. For example, an association for anti-virus software might run once a day. If the software isn't installed, then State Manager installs it. If the software is installed, but the service isn't running, then the association might instruct State Manager to start the service.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "ApplyOnlyAtCronInterval": boolean,
   "AssociationName": "string",
   "AutomationTargetParameterName": "string",
   "CalendarNames": [ "string" ],
   "ComplianceSeverity": "string",
   "DocumentVersion": "string",
   "Duration": number,
   "InstanceId": "string",
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "OutputLocation": {
      "S3Location": {
         "OutputS3BucketName": "string",
         "OutputS3KeyPrefix": "string",
         "OutputS3Region": "string"
      }
```

```
    },
    "Parameters": {
       "string" : [ "string" ]
    },
    "ScheduleExpression": "string",
    "ScheduleOffset": number,
    "SyncCompliance": "string",
    "Tags": [
       {
          "Key": "string",
          "Value": "string"
       }
    ],
    "TargetLocations": [
       {
          "Accounts": [ "string" ],
          "ExcludeAccounts": [ "string" ],
          "ExecutionRoleName": "string",
          "IncludeChildOrganizationUnits": boolean,
          "Regions": [ "string" ],
          "TargetLocationAlarmConfiguration": {
             "Alarms": [
                {
                   "Name": "string"
                }
             ],
             "IgnorePollAlarmFailure": boolean
          },
          "TargetLocationMaxConcurrency": "string",
          "TargetLocationMaxErrors": "string",
          "Targets": [
             {
                "Key": "string",
                "Values": [ "string" ]
             }
          ],
          "TargetsMaxConcurrency": "string",
          "TargetsMaxErrors": "string"
       }
    ],
    "TargetMaps": [
       {
          "string" : [ "string" ]
       }
```

```
    ],
    "Targets": [
       {
          "Key": "string",
          "Values": [ "string" ]
       }
    ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

ApplyOnlyAtCronInterval

By default, when you create a new association, the system runs it immediately after it is created and then according to the schedule you specified and when target changes are detected. Specify `true` for `ApplyOnlyAtCronInterval`if you want the association to run only according to the schedule you specified.

For more information, see Understanding when associations are applied to resources and >About target updates with Automation runbooks in the *AWS Systems Manager User Guide*.

This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationName

Specify a descriptive name for the association.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AutomationTargetParameterName

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a tool in AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names of Amazon Resource Names (ARNs) of the Change Calendar type documents you want to gate your associations under. The associations only run when that change calendar is open. For more information, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Type: Array of strings

Required: No

ComplianceSeverity

The severity level to assign to the association.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED`

Required: No

DocumentVersion

The document version you want to associate with the targets. Can be a specific version or the default version.

> **Important**
>
> State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs

the `default` version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared form another account, you must set the document version to `default`.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours the association can run before it is canceled. Duration applies to associations that are currently running, and any pending and in progress commands on all targets. If a target was taken offline for the association to run, it is made available again immediately, without a reboot.

The `Duration` parameter applies only when both these conditions are true:

- The association for which you specify a duration is cancelable according to the parameters of the SSM command document or Automation runbook associated with this execution.
- The command specifies the `ApplyOnlyAtCronInterval` parameter, which means that the association doesn't run immediately after it is created, but only according to the specified schedule.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

InstanceId

The managed node ID.

> **Note**
>
> `InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceID` with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the

parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there

won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The name of the SSM Command document or Automation runbook that contains the configuration information for the managed node.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another AWS account.

For Systems Manager documents (SSM documents) that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:`*`partition`*`:ssm:`*`region`*`:`*`account-id`*`:document/`*`document-name`*

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

OutputLocation

An Amazon Simple Storage Service (Amazon S3) bucket where you want to store the output details of the request.

Type: InstanceAssociationOutputLocation object

Required: No

Parameters

The parameters for the runtime configuration of the document.

Type: String to array of strings map

Required: No

ScheduleExpression

A cron expression when the association will be applied to the targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association. For example, if you specified a cron schedule of `cron(0 0 ? * THU#2 *)`, you could specify an offset of 3 to run the association each Sunday after the second Thursday of the month. For more information about cron schedules for associations, see Reference: Cron and rate expressions for Systems Manager in the *AWS Systems Manager User Guide*.

> **Note**
>
> To use offsets, you must specify the `ApplyOnlyAtCronInterval` parameter. This option tells the system not to run an association immediately after you create it.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the PutComplianceItems API operation. In this case, compliance data isn't managed by State Manager. It is managed by your direct call to the PutComplianceItems API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

Tags

Adds or overwrites one or more tags for a State Manager association. *Tags* are metadata that you can assign to your AWS resources. Tags enable you to categorize your resources in different ways, for example, by purpose, owner, or environment. Each tag consists of a key and an optional value, both of which you define.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

TargetLocations

A location is a combination of AWS Regions and AWS accounts where you want to run the association. Use this action to create an association in multiple Regions and multiple accounts.

> **Note**
>
> `IncludeChildOrganizationUnits`, `ExcludeAccounts`, `TargetsMaxErrors`, `TargetsMaxConcurrency`, `Targets`, `TargetLocationAlarmConfiguration` parameters are not supported by State Manager.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets for the association. You can target managed nodes by using tags, AWS resource groups, all managed nodes in an AWS account, or individual managed node IDs. You can target all managed nodes in an AWS account by specifying the `InstanceIds` key with a value of `*`. For more information about choosing targets for an association, see Understanding targets and rate controls in State Manager associations in the *AWS Systems Manager User Guide*.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{
   "AssociationDescription": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
```

```
      },
      "ApplyOnlyAtCronInterval": boolean,
      "AssociationId": "string",
      "AssociationName": "string",
      "AssociationVersion": "string",
      "AutomationTargetParameterName": "string",
      "CalendarNames": [ "string" ],
      "ComplianceSeverity": "string",
      "Date": number,
      "DocumentVersion": "string",
      "Duration": number,
      "InstanceId": "string",
      "LastExecutionDate": number,
      "LastSuccessfulExecutionDate": number,
      "LastUpdateAssociationDate": number,
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "Name": "string",
      "OutputLocation": {
         "S3Location": {
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
         }
      },
      "Overview": {
         "AssociationStatusAggregatedCount": {
            "string" : number
         },
         "DetailedStatus": "string",
         "Status": "string"
      },
      "Parameters": {
         "string" : [ "string" ]
      },
      "ScheduleExpression": "string",
      "ScheduleOffset": number,
      "Status": {
         "AdditionalInfo": "string",
         "Date": number,
         "Message": "string",
         "Name": "string"
      },
      "SyncCompliance": "string",
```

```
   "TargetLocations": [
      {
         "Accounts": [ "string" ],
         "ExcludeAccounts": [ "string" ],
         "ExecutionRoleName": "string",
         "IncludeChildOrganizationUnits": boolean,
         "Regions": [ "string" ],
         "TargetLocationAlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "TargetLocationMaxConcurrency": "string",
         "TargetLocationMaxErrors": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TargetsMaxConcurrency": "string",
         "TargetsMaxErrors": "string"
      }
   ],
   "TargetMaps": [
      {
         "string" : [ "string" ]
      }
   ],
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TriggeredAlarms": [
      {
         "Name": "string",
         "State": "string"
      }
   ]
```

```
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription

Information about the association.

Type: AssociationDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationAlreadyExists

The specified association already exists.

HTTP Status Code: 400

AssociationLimitExceeded

You can have at most 2,000 active associations.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTag

The specified tag key or value isn't valid.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node IDs. For example, you sent an document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T140427Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "Name": "AWS-UpdateSSMAgent",
```

```
    "InstanceId": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "f7d193fe-7722-4f2b-ac53-d8736EXAMPLE",
        "AssociationVersion": "1",
        "Date": 1585058668.255,
        "DocumentVersion": "$DEFAULT",
        "InstanceId": "i-02573cafcfEXAMPLE",
        "LastUpdateAssociationDate": 1585058668.255,
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "DetailedStatus": "Creating",
            "Status": "Pending"
        },
        "Status": {
            "Date": 1585058668.255,
            "Message": "Associated with AWS-UpdateSSMAgent",
            "Name": "Associated"
        },
        "Targets": [
            {
                "Key": "InstanceIds",
                "Values": [
                    "i-02573cafcfEXAMPLE"
                ]
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateAssociationBatch

Associates the specified AWS Systems Manager document (SSM document) with the specified managed nodes or targets.

When you associate a document with one or more managed nodes using IDs or tags, AWS Systems Manager Agent (SSM Agent) running on the managed node processes the document and configures the node as specified.

If you associate a document with a managed node that already has an associated document, the system returns the AssociationAlreadyExists exception.

Request Syntax

```
{
   "Entries": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "ApplyOnlyAtCronInterval": boolean,
         "AssociationName": "string",
         "AutomationTargetParameterName": "string",
         "CalendarNames": [ "string" ],
         "ComplianceSeverity": "string",
         "DocumentVersion": "string",
         "Duration": number,
         "InstanceId": "string",
         "MaxConcurrency": "string",
         "MaxErrors": "string",
         "Name": "string",
         "OutputLocation": {
            "S3Location": {
               "OutputS3BucketName": "string",
               "OutputS3KeyPrefix": "string",
               "OutputS3Region": "string"
            }
```

```
        },
        "Parameters": {
           "string" : [ "string" ]
        },
        "ScheduleExpression": "string",
        "ScheduleOffset": number,
        "SyncCompliance": "string",
        "TargetLocations": [
           {
              "Accounts": [ "string" ],
              "ExcludeAccounts": [ "string" ],
              "ExecutionRoleName": "string",
              "IncludeChildOrganizationUnits": boolean,
              "Regions": [ "string" ],
              "TargetLocationAlarmConfiguration": {
                 "Alarms": [
                    {
                       "Name": "string"
                    }
                 ],
                 "IgnorePollAlarmFailure": boolean
              },
              "TargetLocationMaxConcurrency": "string",
              "TargetLocationMaxErrors": "string",
              "Targets": [
                 {
                    "Key": "string",
                    "Values": [ "string" ]
                 }
              ],
              "TargetsMaxConcurrency": "string",
              "TargetsMaxErrors": "string"
           }
        ],
        "TargetMaps": [
           {
              "string" : [ "string" ]
           }
        ],
        "Targets": [
           {
              "Key": "string",
              "Values": [ "string" ]
           }
```

```
         ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Entries

One or more associations.

Type: Array of CreateAssociationBatchRequestEntry objects

Array Members: Minimum number of 1 item.

Required: Yes

Response Syntax

```
{
   "Failed": [
      {
         "Entry": {
            "AlarmConfiguration": {
               "Alarms": [
                  {
                     "Name": "string"
                  }
               ],
               "IgnorePollAlarmFailure": boolean
            },
            "ApplyOnlyAtCronInterval": boolean,
            "AssociationName": "string",
            "AutomationTargetParameterName": "string",
            "CalendarNames": [ "string" ],
            "ComplianceSeverity": "string",
            "DocumentVersion": "string",
            "Duration": number,
            "InstanceId": "string",
```

```
            "MaxConcurrency": "string",
            "MaxErrors": "string",
            "Name": "string",
            "OutputLocation": {
               "S3Location": {
                  "OutputS3BucketName": "string",
                  "OutputS3KeyPrefix": "string",
                  "OutputS3Region": "string"
               }
            },
            "Parameters": {
               "string" : [ "string" ]
            },
            "ScheduleExpression": "string",
            "ScheduleOffset": number,
            "SyncCompliance": "string",
            "TargetLocations": [
               {
                  "Accounts": [ "string" ],
                  "ExcludeAccounts": [ "string" ],
                  "ExecutionRoleName": "string",
                  "IncludeChildOrganizationUnits": boolean,
                  "Regions": [ "string" ],
                  "TargetLocationAlarmConfiguration": {
                     "Alarms": [
                        {
                           "Name": "string"
                        }
                     ],
                     "IgnorePollAlarmFailure": boolean
                  },
                  "TargetLocationMaxConcurrency": "string",
                  "TargetLocationMaxErrors": "string",
                  "Targets": [
                     {
                        "Key": "string",
                        "Values": [ "string" ]
                     }
                  ],
                  "TargetsMaxConcurrency": "string",
                  "TargetsMaxErrors": "string"
               }
            ],
            "TargetMaps": [
```

```
                {
                   "string" : [ "string" ]
                }
             ],
             "Targets": [
                {
                   "Key": "string",
                   "Values": [ "string" ]
                }
             ]
          },
          "Fault": "string",
          "Message": "string"
       }
    ],
    "Successful": [
       {
          "AlarmConfiguration": {
             "Alarms": [
                {
                   "Name": "string"
                }
             ],
             "IgnorePollAlarmFailure": boolean
          },
          "ApplyOnlyAtCronInterval": boolean,
          "AssociationId": "string",
          "AssociationName": "string",
          "AssociationVersion": "string",
          "AutomationTargetParameterName": "string",
          "CalendarNames": [ "string" ],
          "ComplianceSeverity": "string",
          "Date": number,
          "DocumentVersion": "string",
          "Duration": number,
          "InstanceId": "string",
          "LastExecutionDate": number,
          "LastSuccessfulExecutionDate": number,
          "LastUpdateAssociationDate": number,
          "MaxConcurrency": "string",
          "MaxErrors": "string",
          "Name": "string",
          "OutputLocation": {
             "S3Location": {
```

```
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
         }
      },
      "Overview": {
         "AssociationStatusAggregatedCount": {
            "string" : number
         },
         "DetailedStatus": "string",
         "Status": "string"
      },
      "Parameters": {
         "string" : [ "string" ]
      },
      "ScheduleExpression": "string",
      "ScheduleOffset": number,
      "Status": {
         "AdditionalInfo": "string",
         "Date": number,
         "Message": "string",
         "Name": "string"
      },
      "SyncCompliance": "string",
      "TargetLocations": [
         {
            "Accounts": [ "string" ],
            "ExcludeAccounts": [ "string" ],
            "ExecutionRoleName": "string",
            "IncludeChildOrganizationUnits": boolean,
            "Regions": [ "string" ],
            "TargetLocationAlarmConfiguration": {
               "Alarms": [
                  {
                     "Name": "string"
                  }
               ],
               "IgnorePollAlarmFailure": boolean
            },
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string",
            "Targets": [
               {
                  "Key": "string",
```

```
                    "Values": [ "string" ]
                 }
              ],
              "TargetsMaxConcurrency": "string",
              "TargetsMaxErrors": "string"
           }
        ],
        "TargetMaps": [
           {
              "string" : [ "string" ]
           }
        ],
        "Targets": [
           {
              "Key": "string",
              "Values": [ "string" ]
           }
        ],
        "TriggeredAlarms": [
           {
              "Name": "string",
              "State": "string"
           }
        ]
     }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Failed

Information about the associations that failed.

Type: Array of FailedCreateAssociation objects

Successful

Information about the associations that succeeded.

Type: Array of AssociationDescription objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationLimitExceeded

You can have at most 2,000 active associations.

HTTP Status Code: 400

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node IDs. For example, you sent an document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssociationBatch.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateAssociationBatch
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T142446Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 151

{
    "Entries": [
        {
            "InstanceId": "i-0471e04240EXAMPLE",
            "Name": "AWS-UpdateSSMAgent"
        },
        {
            "InstanceId": "i-07782c72faEXAMPLE",
            "Name": "AWS-UpdateSSMAgent"
        }
    ]
}
```

Sample Response

```
{
    "Failed": [],
    "Successful": [
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "33858bec-0c55-4547-a054-eb5fcEXAMPLE",
            "AssociationVersion": "1",
            "Date": 1585059887.692,
            "DocumentVersion": "$DEFAULT",
            "InstanceId": "i-0471e04240EXAMPLE",
            "LastUpdateAssociationDate": 1585059887.692,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "DetailedStatus": "Creating",
```

```
                "Status": "Pending"
            },
            "Status": {
                "Date": 1585059887.692,
                "Message": "Associated with AWS-UpdateSSMAgent",
                "Name": "Associated"
            },
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-0471e04240EXAMPLE"
                    ]
                }
            ]
        },
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "e0e0a062-3dcb-4b3e-bb2b-d01b4EXAMPLE",
            "AssociationVersion": "1",
            "Date": 1585059887.726,
            "DocumentVersion": "$DEFAULT",
            "InstanceId": "i-07782c72faEXAMPLE",
            "LastUpdateAssociationDate": 1585059887.726,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "DetailedStatus": "Creating",
                "Status": "Pending"
            },
            "Status": {
                "Date": 1585059887.726,
                "Message": "Associated with AWS-UpdateSSMAgent",
                "Name": "Associated"
            },
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-07782c72faEXAMPLE"
                    ]
                }
            ]
        }
    ]
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateDocument

Creates a AWS Systems Manager (SSM document). An SSM document defines the actions that Systems Manager performs on your managed nodes. For more information about SSM documents, including information about supported schemas, features, and syntax, see AWS Systems Manager Documents in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "Attachments": [
      {
         "Key": "string",
         "Name": "string",
         "Values": [ "string" ]
      }
   ],
   "Content": "string",
   "DisplayName": "string",
   "DocumentFormat": "string",
   "DocumentType": "string",
   "Name": "string",
   "Requires": [
      {
         "Name": "string",
         "RequireType": "string",
         "Version": "string",
         "VersionName": "string"
      }
   ],
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "TargetType": "string",
   "VersionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Attachments

A list of key-value pairs that describe attachments to a version of a document.

Type: Array of AttachmentsSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Content

The content for the new SSM document in JSON or YAML format. The content of the document must not exceed 64KB. This quota also includes the content specified for input parameters at runtime. We recommend storing the contents for your new document in an external JSON or YAML file and referencing the file in a command.

For examples, see the following topics in the *AWS Systems Manager User Guide*.

- Create an SSM document (console)
- Create an SSM document (command line)
- Create an SSM document (API)

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

DisplayName

An optional field where you can specify a friendly name for the SSM document. This value can differ for each version of the document. You can update this value at a later time using the UpdateDocument operation.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

Required: No

DocumentFormat

Specify the document format for the request. The document format can be JSON, YAML, or TEXT. JSON is the default format.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentType

The type of document to create.

> **Note**
>
> The `DeploymentStrategy` document type is an internal-use-only document type reserved for AWS AppConfig.

Type: String

Valid Values: `Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate | CloudFormation | ConformancePackTemplate | QuickSetup | ManualApprovalPolicy | AutoApprovalPolicy`

Required: No

Name

A name for the SSM document.

> **Important**
>
> You can't use the following strings as document name prefixes. These are reserved by AWS for use as document name prefixes:
>
> - `aws`
> - `amazon`
> - `amzn`
> - `AWSEC2`
> - `AWSConfigRemediation`
> - `AWSSupport`

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

Requires

A list of SSM documents required by a document. This parameter is used exclusively by AWS AppConfig. When a user creates an AWS AppConfig configuration in an SSM document, the user must also specify a required document for validation purposes. In this case, an `ApplicationConfiguration` document requires an `ApplicationConfigurationSchema` document for validation purposes. For more information, see What is AWS AppConfig? in the *AWS AppConfig User Guide*.

Type: Array of DocumentRequires objects

Array Members: Minimum number of 1 item.

Required: No

Tags

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an SSM document to identify the types of targets or the environment where it will run. In this case, you could specify the following key-value pairs:

- `Key=OS,Value=Windows`
- `Key=Environment,Value=Production`

> **Note**
>
> To add tags to an existing SSM document, use the AddTagsToResource operation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

TargetType

Specify a target type to define the kinds of resources the document can run on. For example, to run a document on EC2 instances, specify the following value: `/AWS::EC2::Instance`. If you specify a value of '/' the document can run on all types of resources. If you don't specify a value, the document can't run on any resources. For a list of valid resource types, see AWS resource and property types reference in the *AWS CloudFormation User Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^\/[\w\.\-\:\/]*$`

Required: No

VersionName

An optional field specifying the version of the artifact you are creating with the document. For example, `Release12.1`. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Syntax

```
{
   "DocumentDescription": {
      "ApprovedVersion": "string",
      "AttachmentsInformation": [
         {
            "Name": "string"
         }
      ],
      "Author": "string",
      "Category": [ "string" ],
      "CategoryEnum": [ "string" ],
      "CreatedDate": number,
      "DefaultVersion": "string",
      "Description": "string",
      "DisplayName": "string",
      "DocumentFormat": "string",
      "DocumentType": "string",
      "DocumentVersion": "string",
      "Hash": "string",
      "HashType": "string",
      "LatestVersion": "string",
      "Name": "string",
      "Owner": "string",
      "Parameters": [
         {
            "DefaultValue": "string",
            "Description": "string",
            "Name": "string",
            "Type": "string"
         }
      ],
      "PendingReviewVersion": "string",
      "PlatformTypes": [ "string" ],
      "Requires": [
         {
            "Name": "string",
            "RequireType": "string",
            "Version": "string",
            "VersionName": "string"
         }
      ],
```

```
      "ReviewInformation": [
         {
            "ReviewedTime": number,
            "Reviewer": "string",
            "Status": "string"
         }
      ],
      "ReviewStatus": "string",
      "SchemaVersion": "string",
      "Sha1": "string",
      "Status": "string",
      "StatusInformation": "string",
      "Tags": [
         {
            "Key": "string",
            "Value": "string"
         }
      ],
      "TargetType": "string",
      "VersionName": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentDescription

Information about the SSM document.

Type: DocumentDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

DocumentAlreadyExists

The specified document already exists.

HTTP Status Code: 400

DocumentLimitExceeded

You can have at most 500 active SSM documents.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocumentContent

The content for the document isn't valid.

Message

A description of the validation error.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T145550Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 963

{
    "Content": "---\ndescription: \"Example\"\nschemaVersion: '0.3'\nassumeRole:
 \"{{ AutomationAssumeRole }}\"--truncated--",
    "Name": "Example",
    "DocumentType": "Automation",
    "DocumentFormat": "YAML"
}
```

Sample Response

```
{
    "DocumentDescription": {
        "CreatedDate": 1585061751.738,
        "DefaultVersion": "1",
        "Description": "Custom Automation Example",
        "DocumentFormat": "YAML",
        "DocumentType": "Automation",
        "DocumentVersion": "1",
        "Hash": "0d3d879b3ca072e03c12638d0255ebd004d2c65bd318f8354fcde820dEXAMPLE",
        "HashType": "Sha256",
        "LatestVersion": "1",
        "Name": "Example",
        "Owner": "111122223333",
        "Parameters": [
            {
                "DefaultValue": "",
                "Description": "(Optional) The ARN of the role that allows Automation
 to perform the actions on your behalf. If no role is specified, Systems Manager
 Automation uses your IAM permissions to execute this document.",
```

```
                "Name": "AutomationAssumeRole",
                "Type": "String"
            },
            {
                "DefaultValue": "",
                "Description": "(Required) The Instance Id to create an image of.",
                "Name": "InstanceId",
                "Type": "String"
            }
        ],
        "PlatformTypes": [
            "Windows",
            "Linux"
        ],
        "SchemaVersion": "0.3",
        "Status": "Creating",
        "Tags": []
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateMaintenanceWindow

Creates a new maintenance window.

> **Note**
>
> The value you specify for `Duration` determines the specific end time for the maintenance window based on the time it begins. No maintenance window tasks are permitted to start after the resulting endtime minus the number of hours you specify for `Cutoff`. For example, if the maintenance window starts at 3 PM, the duration is three hours, and the value you specify for `Cutoff` is one hour, no maintenance window tasks can start after 5 PM.

Request Syntax

```
{
   "AllowUnassociatedTargets": boolean,
   "ClientToken": "string",
   "Cutoff": number,
   "Description": "string",
   "Duration": number,
   "EndDate": "string",
   "Name": "string",
   "Schedule": "string",
   "ScheduleOffset": number,
   "ScheduleTimezone": "string",
   "StartDate": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AllowUnassociatedTargets

Enables a maintenance window task to run on managed nodes, even if you haven't registered those nodes as targets. If enabled, then you must specify the unregistered managed nodes (by node ID) when you register a task with the maintenance window.

If you don't enable this option, then you must specify previously-registered targets when you register a task with the maintenance window.

Type: Boolean

Required: Yes

ClientToken

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

Description

An optional description for the maintenance window. We recommend specifying a description to help you organize your maintenance windows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: Yes

EndDate

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become inactive. `EndDate` allows you to set a date and time in the future when the maintenance window will no longer run.

Type: String

Required: No

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

ScheduleOffset

The number of days to wait after the date and time specified by a cron expression before running the maintenance window.

For example, the following cron expression schedules a maintenance window to run on the third Tuesday of every month at 11:30 PM.

```
cron(30 23 ? * TUE#3 *)
```

If the schedule offset is 2, the maintenance window won't run until two days later.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the Time Zone Database on the IANA website.

Type: String

Required: No

StartDate

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become active. `StartDate` allows you to delay activation of the maintenance window until the specified future date.

> **Note**
>
> When using a rate schedule, if you provide a start date that occurs in the past, the current date and time are used as the start date.

Type: String

Required: No

Tags

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to

tag a maintenance window to identify the type of tasks it will run, the types of targets, and the environment it will run in. In this case, you could specify the following key-value pairs:

- `Key=TaskType,Value=AgentUpdate`
- `Key=OS,Value=Windows`
- `Key=Environment,Value=Production`

> **Note**
>
> To add tags to an existing maintenance window, use the AddTagsToResource operation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
   "WindowId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 186
X-Amz-Target: AmazonSSM.CreateMaintenanceWindow
X-Amz-Date: 20240312T201809Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "My-Development-Maintenance-Window",
    "Cutoff": 2,
    "Schedule": "cron(0 12 ? * WED *)",
    "AllowUnassociatedTargets": true,
    "Duration": 6,
    "Tags": [
        {
            "Key": "Environment",
            "Value": "Development"
        }
    ],
    "ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

CreateOpsItem

Creates a new OpsItem. You must have permission in AWS Identity and Access Management (IAM) to create a new OpsItem. For more information, see Set up OpsCenter in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see AWS Systems Manager OpsCenter in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "AccountId": "string",
   "ActualEndTime": number,
   "ActualStartTime": number,
   "Category": "string",
   "Description": "string",
   "Notifications": [
      {
         "Arn": "string"
      }
   ],
   "OperationalData": {
      "string" : {
         "Type": "string",
         "Value": "string"
      }
   },
   "OpsItemType": "string",
   "PlannedEndTime": number,
   "PlannedStartTime": number,
   "Priority": number,
   "RelatedOpsItems": [
      {
         "OpsItemId": "string"
      }
   ],
   "Severity": "string",
   "Source": "string",
   "Tags": [
```

```
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "Title": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AccountId

The target AWS account where you want to create an OpsItem. To make this call, your account must be configured to work with OpsItems across accounts. For more information, see Set up OpsCenter in the *AWS Systems Manager User Guide*.

Type: String

Pattern: `^[0-9]{12}$`

Required: No

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Category

Specify a category to assign to an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Description

User-defined text that contains information about the OpsItem, in Markdown format.

> **Note**
>
> Provide enough information so that users viewing this OpsItem for the first time understand the issue.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\s\S]*\S[\s\S]*`

Required: Yes

Notifications

The Amazon Resource Name (ARN) of an SNS topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of OpsItemNotification objects

Required: No

OperationalData

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

> **Important**
>
> Operational data keys *can't* begin with the following: `amazon`, `aws`, `amzn`, `ssm`, `/amazon`, `/aws`, `/amzn`, `/ssm`.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the DescribeOpsItems API operation) can view and search on the specified data. Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the GetOpsItem API operation).

Use the `/aws/resources` key in OperationalData to specify a related resource in the request. Use the `/aws/automations` key in OperationalData to associate an Automation runbook with the OpsItem. To view AWS CLI example commands that use these keys, see Create OpsItems manually in the *AWS Systems Manager User Guide*.

Type: String to OpsItemDataValue object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\s*$).+`

Required: No

OpsItemType

The type of OpsItem to create. Systems Manager supports the following types of OpsItems:

- `/aws/issue`

  This type of OpsItem is used for default OpsItems created by OpsCenter.

- `/aws/insight`

  This type of OpsItem is used by OpsCenter for aggregating and reporting on duplicate OpsItems.

- `/aws/changerequest`

  This type of OpsItem is used by Change Manager for reviewing and approving or rejecting change requests.

> **Important**
>
> AWS Systems Manager Change Manager is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see AWS Systems Manager Change Manager availability change.

Type: String

Required: No

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

RelatedOpsItems

One or more OpsItems that share something in common with the current OpsItems. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of RelatedOpsItem objects

Required: No

Severity

Specify a severity to assign to an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Source

The origin of the OpsItem, such as Amazon EC2 or Systems Manager.

> **Note**
>
> The source name can't contain the following strings: `aws`, `amazon`, and `amzn`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\s*$).+`

Required: Yes

Tags

Optional metadata that you assign to a resource.

Tags use a key-value pair. For example:

`Key=Department,Value=Finance`

> **Important**
>
> To add tags to a new OpsItem, a user must have IAM permissions for both the `ssm:CreateOpsItems` operation and the `ssm:AddTagsToResource` operation. To add tags to an existing OpsItem, use the AddTagsToResource operation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: Yes

Response Syntax

```
{
   "OpsItemArn": "string",
   "OpsItemId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsItemArn

The OpsItem Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[0-9]{12}:opsitem.*`

OpsItemId

The ID of the OpsItem.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemAccessDeniedException

You don't have permission to view OpsItems in the specified account. Verify that your account is configured either as a Systems Manager delegated administrator or that you are logged into the AWS Organizations management account.

HTTP Status Code: 400

OpsItemAlreadyExistsException

The OpsItem already exists.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateOpsItem.

Sample Request

```
POST / HTTP/1.1
 Host: ssm.us-east-2.amazonaws.com
 Accept-Encoding: identity
 X-Amz-Target: AmazonSSM.CreateOpsItem
 Content-Type: application/x-amz-json-1.1
 User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
 X-Amz-Date: 20240401T161257Z
 Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/
ssm/aws4_request,
 SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE
 Content-Length: 80

 {
     "Description": "Example Ops Item",
     "Source": "SSM",
     "Title": "DocumentDeleted"
 }
```

Sample Response

```
{{
     "OpsItemId": "oi-1f050EXAMPLE"
 }
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateOpsMetadata

If you create a new application in Application Manager, AWS Systems Manager calls this API operation to specify information about the new application, including the application type.

Request Syntax

```
{
   "Metadata": {
      "string" : {
         "Value": "string"
      }
   },
   "ResourceId": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Metadata

Metadata for a new Application Manager application.

Type: String to MetadataValue object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `^(?!\s*$).+`

Required: No

ResourceId

A resource ID for a new Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: Yes

Tags

Optional metadata that you assign to a resource. You can specify a maximum of five tags for an OpsMetadata object. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an OpsMetadata object to identify an environment or target AWS Region. In this case, you could specify the following key-value pairs:

- `Key=Environment,Value=Production`
- `Key=Region,Value=us-east-2`

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
   "OpsMetadataArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsMetadataArn

The Amazon Resource Name (ARN) of the OpsMetadata Object or blob created by the call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataAlreadyExistsException

An OpsMetadata object already exists for the selected resource.

HTTP Status Code: 400

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataLimitExceededException

Your account reached the maximum number of OpsMetadata objects allowed by Application Manager. The maximum is 200 OpsMetadata objects. Delete one or more OpsMetadata object and try again.

HTTP Status Code: 400

OpsMetadataTooManyUpdatesException

The system is processing too many concurrent updates. Wait a few moments and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreatePatchBaseline

Creates a patch baseline.

> **Note**
>
> For information about valid key-value pairs in `PatchFilters` for each supported operating system type, see PatchFilter.

Request Syntax

```
{
   "ApprovalRules": {
      "PatchRules": [
         {
            "ApproveAfterDays": number,
            "ApproveUntilDate": "string",
            "ComplianceLevel": "string",
            "EnableNonSecurity": boolean,
            "PatchFilterGroup": {
               "PatchFilters": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ]
            }
         }
      ]
   },
   "ApprovedPatches": [ "string" ],
   "ApprovedPatchesComplianceLevel": "string",
   "ApprovedPatchesEnableNonSecurity": boolean,
   "AvailableSecurityUpdatesComplianceStatus": "string",
   "ClientToken": "string",
   "Description": "string",
   "GlobalFilters": {
      "PatchFilters": [
         {
            "Key": "string",
            "Values": [ "string" ]
```

```
            }
         ]
      },
      "Name": "string",
      "OperatingSystem": "string",
      "RejectedPatches": [ "string" ],
      "RejectedPatchesAction": "string",
      "Sources": [
         {
            "Configuration": "string",
            "Name": "string",
            "Products": [ "string" ]
         }
      ],
      "Tags": [
         {
            "Key": "string",
            "Value": "string"
         }
      ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ApprovalRules

A set of rules used to include patches in the baseline.

Type: PatchRuleGroup object

Required: No

ApprovedPatches

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ApprovedPatchesComplianceLevel

Defines the compliance level for approved patches. When an approved patch is reported as missing, this value describes the severity of the compliance violation. The default value is `UNSPECIFIED`.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

AvailableSecurityUpdatesComplianceStatus

Indicates the status you want to assign to security patches that are available but not approved because they don't meet the installation criteria specified in the patch baseline.

Example scenario: Security patches that you might want installed can be skipped if you have specified a long period to wait after a patch is released before installation. If an update to the patch is released during your specified waiting period, the waiting period for installing the patch starts over. If the waiting period is too long, multiple versions of the patch could be released but never installed.

Supported for Windows Server managed nodes only.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: No

ClientToken

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Description

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

GlobalFilters

A set of global filters used to include patches in the baseline.

> **Important**
>
> The `GlobalFilters` parameter can be configured only by using the AWS CLI or an AWS SDK. It can't be configured from the Patch Manager console, and its value isn't displayed in the console.

Type: PatchFilterGroup object

Required: No

Name

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

OperatingSystem

Defines the operating system the patch baseline applies to. The default value is `WINDOWS`.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: No

RejectedPatches

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RejectedPatchesAction

The action for Patch Manager to take on patches included in the `RejectedPackages` list.

ALLOW_AS_DEPENDENCY

> **Linux and macOS**: A package in the rejected patches list is installed only if it is a dependency of another package. It is considered compliant with the patch baseline, and its status is reported as `INSTALLED_OTHER`. This is the default action if no option is specified.

Windows Server: Windows Server doesn't support the concept of package dependencies. If a package in the rejected patches list and already installed on the node, its status is reported as `INSTALLED_OTHER`. Any package not already installed on the node is skipped. This is the default action if no option is specified.

BLOCK

All OSs: Packages in the rejected patches list, and packages that include them as dependencies, aren't installed by Patch Manager under any circumstances.

State value assignment for patch compliance:

- If a package was installed before it was added to the rejected patches list, or is installed outside of Patch Manager afterward, it's considered noncompliant with the patch baseline and its status is reported as `INSTALLED_REJECTED`.
- If an update attempts to install a dependency package that is now rejected by the baseline, when previous versions of the package were not rejected, the package being updated is reported as `MISSING` for `SCAN` operations and as `FAILED` for `INSTALL` operations.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY | BLOCK`

Required: No

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of PatchSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Tags

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a patch baseline to identify the severity level of patches it specifies and the operating system family it applies to. In this case, you could specify the following key-value pairs:

- `Key=PatchSeverity,Value=Critical`
- `Key=OS,Value=Windows`

> **Note**
>
> To add tags to an existing patch baseline, use the AddTagsToResource operation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
   "BaselineId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the created patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreatePatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 461
X-Amz-Target: AmazonSSM.CreatePatchBaseline
X-Amz-Date: 20240309T022356Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
```

```
{
    "Description": "Baseline containing all updates approved for production systems",
    "ApprovalRules": {
        "PatchRules": [
            {
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Values": [
                                "Critical",
                                "Important",
                                "Moderate"
                            ],
                            "Key": "MSRC_SEVERITY"
                        },
                        {
                            "Values": [
                                "SecurityUpdates",
                                "Updates",
                                "UpdateRollups",
                                "CriticalUpdates"
                            ],
                            "Key": "CLASSIFICATION"
                        }
                    ]
                },
                "ApproveAfterDays": 7,
                "ApproveUntilDate": "",
                "EnableNonSecurity": true,
                "ComplianceLevel": "MEDIUM"
            }
        ]
    },
    "Name": "my-Windows-Server-patch-baseline",
    "OperatingSystem": "WINDOWS",
    "ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateResourceDataSync

A resource data sync helps you view data from multiple sources in a single location. AWS Systems Manager offers two types of resource data sync: `SyncToDestination` and `SyncFromSource`.

You can configure Systems Manager Inventory to use the `SyncToDestination` type to synchronize Inventory data from multiple AWS Regions to a single Amazon Simple Storage Service (Amazon S3) bucket. For more information, see Creating a resource data sync for Inventory in the *AWS Systems Manager User Guide*.

You can configure Systems Manager Explorer to use the `SyncFromSource` type to synchronize operational work items (OpsItems) and operational data (OpsData) from multiple AWS Regions to a single Amazon S3 bucket. This type can synchronize OpsItems and OpsData from multiple AWS accounts and AWS Regions or `EntireOrganization` by using AWS Organizations. For more information, see Setting up Systems Manager Explorer to display data from multiple accounts and Regions in the *AWS Systems Manager User Guide*.

A resource data sync is an asynchronous operation that returns immediately. After a successful initial sync is completed, the system continuously syncs data. To check the status of a sync, use the ListResourceDataSync.

> **Note**
>
> By default, data isn't encrypted in Amazon S3. We strongly recommend that you enable encryption in Amazon S3 to ensure secure data storage. We also recommend that you secure access to the Amazon S3 bucket by creating a restrictive bucket policy.

Request Syntax

```
{
   "S3Destination": {
      "AWSKMSKeyARN": "string",
      "BucketName": "string",
      "DestinationDataSharing": {
         "DestinationDataSharingType": "string"
      },
      "Prefix": "string",
      "Region": "string",
```

```
      "SyncFormat": "string"
   },
   "SyncName": "string",
   "SyncSource": {
      "AwsOrganizationsSource": {
         "OrganizationalUnits": [
            {
               "OrganizationalUnitId": "string"
            }
         ],
         "OrganizationSourceType": "string"
      },
      "EnableAllOpsDataSources": boolean,
      "IncludeFutureRegions": boolean,
      "SourceRegions": [ "string" ],
      "SourceType": "string"
   },
   "SyncType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

S3Destination

Amazon S3 configuration details for the sync. This parameter is required if the SyncType value is SyncToDestination.

Type: ResourceDataSyncS3Destination object

Required: No

SyncName

A name for the configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncSource

Specify information about the data sources to synchronize. This parameter is required if the SyncType value is SyncFromSource.

Type: ResourceDataSyncSource object

Required: No

SyncType

Specify SyncToDestination to create a resource data sync that synchronizes data to an S3 bucket for Inventory. If you specify SyncToDestination, you must provide a value for S3Destination. Specify SyncFromSource to synchronize data from a single account and multiple Regions, or multiple AWS accounts and AWS Regions, as listed in AWS Organizations for Explorer. If you specify SyncFromSource, you must provide a value for SyncSource. The default value is SyncToDestination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncAlreadyExistsException

A sync configuration with the same name already exists.

HTTP Status Code: 400

ResourceDataSyncCountExceededException

You have exceeded the allowed maximum sync configurations.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240327T173437Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240327/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 186

{
    "SyncName": "Example",
    "S3Destination": {
        "BucketName": "amzn-s3-demo-bucket",
        "Prefix": "amzn-s3-demo-bucket-prefix",
        "SyncFormat": "JsonSerDe",
        "Region": "us-east-2"
    },
    "SyncType": "SyncToDestination"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteActivation

Deletes an activation. You aren't required to delete an activation. If you delete an activation, you can no longer use it to register additional managed nodes. Deleting an activation doesn't de-register managed nodes. You must manually de-register managed nodes.

Request Syntax

```
{
   "ActivationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ActivationId

The ID of the activation that you want to delete.

Type: String

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidActivation

The activation isn't valid. The activation might have been deleted, or the ActivationId and the ActivationCode don't match.

HTTP Status Code: 400

InvalidActivationId

The activation ID isn't valid. Verify that you entered the correct ActivationId or ActivationCode and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteActivation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteActivation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T151218Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 56

{
    "ActivationId": "e488f2f6-e686-4afb-8a04-ef6dfEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteAssociation

Disassociates the specified AWS Systems Manager document (SSM document) from the specified managed node. If you created the association by using the `Targets` parameter, then you must delete the association by using the association ID.

When you disassociate a document from a managed node, it doesn't change the configuration of the node. To change the configuration state of a managed node after you disassociate a document, you must create a new document with the desired configuration and associate it with the node.

Request Syntax

```
{
   "AssociationId": "string",
   "InstanceId": "string",
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The association ID that you want to delete.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

InstanceId

The managed node ID.

> **Note**
>
> `InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceID`

with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
```

```
X-Amz-Date: 20240324T150348Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "33858bec-0c55-4547-a054-eb5fcEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteDocument

Deletes the AWS Systems Manager document (SSM document) and all managed node associations to the document.

Before you delete the document, we recommend that you use DeleteAssociation to disassociate all managed nodes that are associated with the document.

Request Syntax

```
{
   "DocumentVersion": "string",
   "Force": boolean,
   "Name": "string",
   "VersionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentVersion

The version of the document that you want to delete. If not provided, all versions of the document are deleted.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Force

Some SSM document types require that you specify a `Force` flag before you can delete the document. For example, you must specify a `Force` flag to delete a document of type `ApplicationConfigurationSchema`. You can restrict access to the `Force` flag in an AWS Identity and Access Management (IAM) policy.

Type: Boolean

Required: No

Name

The name of the document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

VersionName

The version name of the document that you want to delete. If not provided, all versions of the document are deleted.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociatedInstances

You must disassociate a document from all managed nodes before you can delete it.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T151532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 19

{
    "Name": "Example"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteInventory

Delete a custom inventory type or the data associated with a custom Inventory type. Deleting a custom inventory type is also referred to as deleting a custom inventory schema.

Request Syntax

```
{
   "ClientToken": "string",
   "DryRun": boolean,
   "SchemaDeleteOption": "string",
   "TypeName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ClientToken

User-provided idempotency token.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

DryRun

Use this option to view a summary of the deletion request without deleting any data or the data type. This option is useful when you only want to understand what will be deleted. Once you validate that the data to be deleted is what you intend to delete, you can run the same command without specifying the `DryRun` option.

Type: Boolean

Required: No

SchemaDeleteOption

Use the `SchemaDeleteOption` to delete a custom inventory type (schema). If you don't choose this option, the system only deletes existing inventory data associated with the custom inventory type. Choose one of the following options:

DisableSchema: If you choose this option, the system ignores all inventory data for the specified version, and any earlier versions. To enable this schema again, you must call the `PutInventory` operation for a version greater than the disabled version.

DeleteSchema: This option deletes the specified custom type from the Inventory service. You can recreate the schema later, if you want.

Type: String

Valid Values: `DisableSchema | DeleteSchema`

Required: No

TypeName

The name of the custom inventory type for which you want to delete either all previously collected data or the inventory type itself.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

Response Syntax

```
{
   "DeletionId": "string",
   "DeletionSummary": {
      "RemainingCount": number,
      "SummaryItems": [
         {
            "Count": number,
            "RemainingCount": number,
            "Version": "string"
```

```
            }
        ],
        "TotalCount": number
    },
    "TypeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeletionId

Every `DeleteInventory` operation is assigned a unique ID. This option returns a unique ID. You can use this ID to query the status of a delete operation. This option is useful for ensuring that a delete operation has completed before you begin other operations.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

DeletionSummary

A summary of the delete operation. For more information about this summary, see Deleting custom inventory in the *AWS Systems Manager User Guide*.

Type: InventoryDeletionSummary object

TypeName

The name of the inventory data type specified in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDeleteInventoryParametersException

One or more of the parameters specified for the delete operation isn't valid. Verify all parameters and try again.

HTTP Status Code: 400

InvalidInventoryRequestException

The request isn't valid.

HTTP Status Code: 400

InvalidOptionException

The delete inventory option specified isn't valid. Verify the option and try again.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteInventory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteInventory
Content-Type: application/x-amz-json-1.1
```

```
User-Agent: aws-cli/2.2.25 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.delete-inventory
X-Amz-Date: 20240809T230226Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240809/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature39c3b3042cd2aEXAMPLE
Content-Length: 124

{
  "TypeName": "Custom:RackInfo",
  "SchemaDeleteOption": "DeleteSchema",
  "ClientToken": "a7d4972c-ab3e-4b9a-b5c0-d5aExample"
}
```

Sample Response

```
{
  "DeletionId": "5bc2ba3b-ee6a-40fa-8d09-5e5Example",
  "DeletionSummary": {
    "RemainingCount": 1,
    "SummaryItems": [
      {
        "Count": 1,
        "RemainingCount": 1,
        "Version": "1.0"
      }
    ],
    "TotalCount": 1
  },
  "TypeName": "Custom:RackInfo"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteMaintenanceWindow

Deletes a maintenance window.

Request Syntax

```
{
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowId

The ID of the maintenance window to delete.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "WindowId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId

The ID of the deleted maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DeleteMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.DeleteMaintenanceWindow
X-Amz-Date: 20240312T210257Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
```

```
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteOpsItem

Delete an OpsItem. You must have permission in AWS Identity and Access Management (IAM) to delete an OpsItem.

Important

Note the following important information about this operation.

- Deleting an OpsItem is irreversible. You can't restore a deleted OpsItem.
- This operation uses an *eventual consistency model*, which means the system can take a few minutes to complete this operation. If you delete an OpsItem and immediately call, for example, GetOpsItem, the deleted OpsItem might still appear in the response.
- This operation is idempotent. The system doesn't throw an exception if you repeatedly call this operation for the same OpsItem. If the first call is successful, all additional calls return the same successful response as the first call.
- This operation doesn't support cross-account calls. A delegated administrator or management account can't delete OpsItems in other accounts, even if OpsCenter has been set up for cross-account administration. For more information about cross-account administration, see Setting up OpsCenter to centrally manage OpsItems across accounts in the *Systems Manager User Guide*.

Request Syntax

```
{
   "OpsItemId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

OpsItemId

The ID of the OpsItem that you want to delete.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteOpsItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T151532Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 19

{
    "OpsItemId": "oi-abcdef12345"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteOpsMetadata

Delete OpsMetadata related to an application.

Request Syntax

```
{
   "OpsMetadataArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

OpsMetadataArn

The Amazon Resource Name (ARN) of an OpsMetadata Object to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteParameter

Delete a parameter from the system. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

Request Syntax

```
{
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name of the parameter to delete.

> **Note**
>
> You can't enter the Amazon Resource Name (ARN) for a parameter, only the parameter name itself.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

> **Note**
>
> For the `DeleteParameter` and `GetParameter` actions, if the specified parameter doesn't exist, the `ParameterNotFound` exception is *not* recorded in AWS CloudTrail event logs.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonSSM.DeleteParameter
X-Amz-Date: 20240316T010702Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "EC2DevServerType"
```

```
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteParameters

Delete a list of parameters. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

Request Syntax

```
{
   "Names": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Names

The names of the parameters to delete. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

> **Note**
>
> You can't enter the Amazon Resource Name (ARN) for a parameter, only the parameter name itself.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Response Syntax

```
{
   "DeletedParameters": [ "string" ],
   "InvalidParameters": [ "string" ]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeletedParameters

The names of the deleted parameters.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

InvalidParameters

The names of parameters that weren't deleted because the parameters aren't valid.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DeleteParameters.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 53
X-Amz-Target: AmazonSSM.DeleteParameters
X-Amz-Date: 20240316T010844Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Names": [
        "EC2TestServerType",
        "EC2ProdServerType"
    ]
}
```

Sample Response

```
{
    "DeletedParameters": [
        "EC2ProdServerType",
        "EC2TestServerType"
    ],
    "InvalidParameters": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeletePatchBaseline

Deletes a patch baseline.

Request Syntax

```
{
   "BaselineId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline to delete.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

Response Syntax

```
{
   "BaselineId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the deleted patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceInUseException

Error returned if an attempt is made to delete a patch baseline that is registered for a patch group.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeletePatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.DeletePatchBaseline
X-Amz-Date: 20240309T062407Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteResourceDataSync

Deletes a resource data sync configuration. After the configuration is deleted, changes to data on managed nodes are no longer synced to or from the target. Deleting a sync configuration doesn't delete data.

Request Syntax

```
{
   "SyncName": "string",
   "SyncType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SyncName

The name of the configuration to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncType

Specify the type of resource data sync to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T144518Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 28

{
```

```
    "SyncName": "exampleSync"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteResourcePolicy

Deletes a Systems Manager resource policy. A resource policy helps you to define the IAM entity (for example, an AWS account) that can manage your Systems Manager resources. The following resources support Systems Manager resource policies.

- `OpsItemGroup` - The resource policy for `OpsItemGroup` enables AWS accounts to view and interact with OpsCenter operational work items (OpsItems).
- `Parameter` - The resource policy is used to share a parameter with other accounts using AWS Resource Access Manager (AWS RAM). For more information about cross-account sharing of parameters, see Working with shared parameters in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "PolicyHash": "string",
   "PolicyId": "string",
   "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

PolicyHash

ID of the current policy version. The hash helps to prevent multiple calls from attempting to overwrite a policy.

Type: String

Required: Yes

PolicyId

The policy ID.

Type: String

Required: Yes

ResourceArn

Amazon Resource Name (ARN) of the resource to which the policies are attached.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

MalformedResourcePolicyDocumentException

The specified policy document is malformed or invalid, or excessive `PutResourcePolicy` or `DeleteResourcePolicy` calls have been made.

HTTP Status Code: 400

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

ResourcePolicyConflictException

The hash provided in the call doesn't match the stored hash. This exception is thrown when trying to update an obsolete policy version or when multiple requests to update a policy are sent.

HTTP Status Code: 400

ResourcePolicyInvalidParameterException

One or more parameters specified for the call aren't valid. Verify the parameters and their values and try again.

HTTP Status Code: 400

ResourcePolicyNotFoundException

No policies with the specified policy ID and hash could be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeregisterManagedInstance

Removes the server or virtual machine from the list of registered servers.

If you want to reregister an on-premises server, edge device, or VM, you must use a different Activation Code and Activation ID than used to register the machine previously. The Activation Code and Activation ID must not have already been used on the maximum number of activations specified when they were created. For more information, see Deregistering managed nodes in a hybrid and multicloud environment in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "InstanceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InstanceId

The ID assigned to the managed node when you registered it using the activation process.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 124.

Pattern: `(^mi-[0-9a-f]{17}$)|(^eks_c:[0-9A-Za-z][A-Za-z0-9\-_]{0,99}_\w{17}$)`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeregisterManagedInstance.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterManagedInstance
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240220T234004Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37
```

```
{
    "InstanceId": "mi-017431b35cEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeregisterPatchBaselineForPatchGroup

Removes a patch group from a patch baseline.

Request Syntax

```
{
   "BaselineId": "string",
   "PatchGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline to deregister the patch group from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

PatchGroup

The name of the patch group that should be deregistered from the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
   "BaselineId": "string",
   "PatchGroup": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the patch baseline the patch group was deregistered from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

PatchGroup

The name of the patch group deregistered from the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeregisterPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
  Host: ssm.us-east-2.amazonaws.com
  Accept-Encoding: identity
  Content-Length: 74
  X-Amz-Target: AmazonSSM.DeregisterPatchBaselineForPatchGroup
  X-Amz-Date: 20240309T062043Z
  User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
  Content-Type: application/x-amz-json-1.1
  Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/
ssm/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeregisterTargetFromMaintenanceWindow

Removes a target from a maintenance window.

Request Syntax

```
{
   "Safe": boolean,
   "WindowId": "string",
   "WindowTargetId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Safe

The system checks if the target is being referenced by a task. If the target is being referenced, the system returns an error and doesn't deregister the target from the maintenance window.

Type: Boolean

Required: No

WindowId

The ID of the maintenance window the target should be removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

WindowTargetId

The ID of the target definition to remove.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "WindowId": "string",
   "WindowTargetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId

The ID of the maintenance window the target was removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

WindowTargetId

The ID of the removed target definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

TargetInUseException

You specified the `Safe` option for the DeregisterTargetFromMaintenanceWindow operation, but the target is still referenced in a task.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeregisterTargetFromMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterTargetFromMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T182719Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 94

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeregisterTaskFromMaintenanceWindow

Removes a task from a maintenance window.

Request Syntax

```
{
   "WindowId": "string",
   "WindowTaskId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowId

The ID of the maintenance window the task should be removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

WindowTaskId

The ID of the task to remove from the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "WindowId": "string",
   "WindowTaskId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId

The ID of the maintenance window the task was removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

WindowTaskId

The ID of the task removed from the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DeregisterTaskFromMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterTaskFromMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T180133Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 92

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeActivations

Describes details about the activation, such as the date and time the activation was created, its expiration date, the AWS Identity and Access Management (IAM) role assigned to the managed nodes in the activation, and the number of nodes registered by using this activation.

Request Syntax

```
{
   "Filters": [
      {
         "FilterKey": "string",
         "FilterValues": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

A filter to view information about your activations.

Type: Array of DescribeActivationsFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "ActivationList": [
      {
         "ActivationId": "string",
         "CreatedDate": number,
         "DefaultInstanceName": "string",
         "Description": "string",
         "ExpirationDate": number,
         "Expired": boolean,
         "IamRole": "string",
         "RegistrationLimit": number,
         "RegistrationsCount": number,
         "Tags": [
            {
               "Key": "string",
               "Value": "string"
            }
         ]
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActivationList

A list of activations for your AWS account.

Type: Array of Activation objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeActivations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeActivations
```

```
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T152059Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ActivationList": [
        {
            "ActivationId": "e9136c70-ba7b-4d7d-8e31-174a7EXAMPLE",
            "CreatedDate": 1581954699.792,
            "Description": "Example",
            "ExpirationDate": 1584316800,
            "Expired": true,
            "IamRole": "service-role/RoleForManagedInstances",
            "RegistrationLimit": 5,
            "RegistrationsCount": 1
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

DescribeAssociation

Describes the association for the specified target or managed node. If you created the association by using the `Targets` parameter, then you must retrieve the association by using the association ID.

Request Syntax

```
{
   "AssociationId": "string",
   "AssociationVersion": "string",
   "InstanceId": "string",
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The association ID for which you want information.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationVersion

Specify the association version to retrieve. To view the latest version, either specify `$LATEST` for this parameter, or omit this parameter. To view a list of all associations for a managed node, use ListAssociations. To get a list of versions for a specific association, use ListAssociationVersions.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Response Syntax

```
{
   "AssociationDescription": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
      },
      "ApplyOnlyAtCronInterval": boolean,
      "AssociationId": "string",
      "AssociationName": "string",
      "AssociationVersion": "string",
      "AutomationTargetParameterName": "string",
      "CalendarNames": [ "string" ],
      "ComplianceSeverity": "string",
      "Date": number,
      "DocumentVersion": "string",
      "Duration": number,
      "InstanceId": "string",
```

```
      "LastExecutionDate": number,
      "LastSuccessfulExecutionDate": number,
      "LastUpdateAssociationDate": number,
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "Name": "string",
      "OutputLocation": {
         "S3Location": {
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
         }
      },
      "Overview": {
         "AssociationStatusAggregatedCount": {
            "string" : number
         },
         "DetailedStatus": "string",
         "Status": "string"
      },
      "Parameters": {
         "string" : [ "string" ]
      },
      "ScheduleExpression": "string",
      "ScheduleOffset": number,
      "Status": {
         "AdditionalInfo": "string",
         "Date": number,
         "Message": "string",
         "Name": "string"
      },
      "SyncCompliance": "string",
      "TargetLocations": [
         {
            "Accounts": [ "string" ],
            "ExcludeAccounts": [ "string" ],
            "ExecutionRoleName": "string",
            "IncludeChildOrganizationUnits": boolean,
            "Regions": [ "string" ],
            "TargetLocationAlarmConfiguration": {
               "Alarms": [
                  {
                     "Name": "string"
                  }
```

```
                ],
                "IgnorePollAlarmFailure": boolean
             },
             "TargetLocationMaxConcurrency": "string",
             "TargetLocationMaxErrors": "string",
             "Targets": [
                {
                   "Key": "string",
                   "Values": [ "string" ]
                }
             ],
             "TargetsMaxConcurrency": "string",
             "TargetsMaxErrors": "string"
          }
       ],
       "TargetMaps": [
          {
             "string" : [ "string" ]
          }
       ],
       "Targets": [
          {
             "Key": "string",
             "Values": [ "string" ]
          }
       ],
       "TriggeredAlarms": [
          {
             "Name": "string",
             "State": "string"
          }
       ]
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription

Information about the association.

Type: AssociationDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAssociationVersion

The version you specified isn't valid. Use ListAssociationVersions to view all versions of an association according to the association ID. Or, use the $LATEST parameter to view the latest version of the association.

HTTP Status Code: 400

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.

- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T153423Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
        "AssociationVersion": "1",
        "ComplianceSeverity": "UNSPECIFIED",
        "Date": 1561053271.583,
        "DocumentVersion": "$DEFAULT",
        "LastExecutionDate": 1582037438.692,
        "LastSuccessfulExecutionDate": 1582037438.692,
        "LastUpdateAssociationDate": 1561053271.583,
```

```
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "AssociationStatusAggregatedCount": {
                "Success": 3
            },
            "DetailedStatus": "Success",
            "Status": "Success"
        },
        "Parameters": {
            "allowDowngrade": [
                "false"
            ],
            "version": [
                ""
            ]
        },
        "Targets": [
            {
                "Key": "tag:ssm",
                "Values": [
                    "true"
                ]
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeAssociationExecutions

Views all executions for a specific association ID.

Request Syntax

```
{
   "AssociationId": "string",
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Value": "string"
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The association ID for which you want to view execution history details.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

Filters

Filters for the request. You can specify the following filters and values.

ExecutionId (EQUAL)

Status (EQUAL)

CreatedTime (EQUAL, GREATER_THAN, LESS_THAN)

Type: Array of AssociationExecutionFilter objects

Array Members: Minimum number of 1 item.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "AssociationExecutions": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "AssociationId": "string",
         "AssociationVersion": "string",
         "CreatedTime": number,
```

```
         "DetailedStatus": "string",
         "ExecutionId": "string",
         "LastExecutionDate": number,
         "ResourceCountByStatus": "string",
         "Status": "string",
         "TriggeredAlarms": [
            {
               "Name": "string",
               "State": "string"
            }
         ]
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationExecutions

A list of the executions for the specified association ID.

Type: Array of AssociationExecution objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssociationExecutions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociationExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T154610Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationExecutions": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
```

```
            "AssociationVersion": "1",
            "CreatedTime": 1561053271.718,
            "DetailedStatus": "Success",
            "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
            "ResourceCountByStatus": "{Success=3}",
            "Status": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeAssociationExecutionTargets

Views information about a specific execution of a specific association.

Request Syntax

```
{
   "AssociationId": "string",
   "ExecutionId": "string",
   "Filters": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The association ID that includes the execution for which you want to view details.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

ExecutionId

The execution ID for which you want to view details.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

Filters

Filters for the request. You can specify the following filters and values.

Status (EQUAL)

ResourceId (EQUAL)

ResourceType (EQUAL)

Type: Array of AssociationExecutionTargetsFilter objects

Array Members: Minimum number of 1 item.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "AssociationExecutionTargets": [
```

```
      {
         "AssociationId": "string",
         "AssociationVersion": "string",
         "DetailedStatus": "string",
         "ExecutionId": "string",
         "LastExecutionDate": number,
         "OutputSource": {
            "OutputSourceId": "string",
            "OutputSourceType": "string"
         },
         "ResourceId": "string",
         "ResourceType": "string",
         "Status": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationExecutionTargets

Information about the execution.

Type: Array of AssociationExecutionTarget objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

AssociationExecutionDoesNotExist

The specified execution ID doesn't exist. Verify the ID number and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssociationExecutionTargets.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociationExecutionTargets
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T165104Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 112

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE"
}
```

Sample Response


```
{
    "AssociationExecutionTargets": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "DetailedStatus": "Success",
            "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
            "LastExecutionDate": 1582037438.692,
            "OutputSource": {
                "OutputSourceId": "1cdbb1e6-2e69-40b1-ac1d-121dcEXAMPLE",
                "OutputSourceType": "RunCommand"
            },
            "ResourceId": "i-02573cafcfEXAMPLE",
            "ResourceType": "ManagedInstance",
            "Status": "Success"
        },
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "DetailedStatus": "Success",
            "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
            "LastExecutionDate": 1581948052.198,
            "OutputSource": {
                "OutputSourceId": "b170ae99-4959-479b-ab4d-f6ae0EXAMPLE",
                "OutputSourceType": "RunCommand"
            },
            "ResourceId": "i-0471e04240EXAMPLE",
            "ResourceType": "ManagedInstance",
            "Status": "Success"
        },
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "DetailedStatus": "Success",
            "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
            "LastExecutionDate": 1561053316.711,
            "OutputSource": {
                "OutputSourceId": "89cd739c-d1a5-4dc9-af4f-8b624EXAMPLE",
                "OutputSourceType": "RunCommand"
            },
            "ResourceId": "i-07782c72faEXAMPLE",
            "ResourceType": "ManagedInstance",
```

```
            "Status": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeAutomationExecutions

Provides details about all active and terminated Automation executions.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Filters used to limit the scope of executions that are requested.

Type: Array of AutomationExecutionFilter objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "AutomationExecutionMetadataList": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "AssociationId": "string",
         "AutomationExecutionId": "string",
         "AutomationExecutionStatus": "string",
         "AutomationSubtype": "string",
         "AutomationType": "string",
         "ChangeRequestName": "string",
         "CurrentAction": "string",
         "CurrentStepName": "string",
         "DocumentName": "string",
         "DocumentVersion": "string",
         "ExecutedBy": "string",
         "ExecutionEndTime": number,
         "ExecutionStartTime": number,
         "FailureMessage": "string",
         "LogFile": "string",
         "MaxConcurrency": "string",
         "MaxErrors": "string",
         "Mode": "string",
         "OpsItemId": "string",
         "Outputs": {
            "string" : [ "string" ]
         },
```

```
      "ParentAutomationExecutionId": "string",
      "ResolvedTargets": {
         "ParameterValues": [ "string" ],
         "Truncated": boolean
      },
      "Runbooks": [
         {
            "DocumentName": "string",
            "DocumentVersion": "string",
            "MaxConcurrency": "string",
            "MaxErrors": "string",
            "Parameters": {
               "string" : [ "string" ]
            },
            "TargetLocations": [
               {
                  "Accounts": [ "string" ],
                  "ExcludeAccounts": [ "string" ],
                  "ExecutionRoleName": "string",
                  "IncludeChildOrganizationUnits": boolean,
                  "Regions": [ "string" ],
                  "TargetLocationAlarmConfiguration": {
                     "Alarms": [
                        {
                           "Name": "string"
                        }
                     ],
                     "IgnorePollAlarmFailure": boolean
                  },
                  "TargetLocationMaxConcurrency": "string",
                  "TargetLocationMaxErrors": "string",
                  "Targets": [
                     {
                        "Key": "string",
                        "Values": [ "string" ]
                     }
                  ],
                  "TargetsMaxConcurrency": "string",
                  "TargetsMaxErrors": "string"
               }
            ],
            "TargetMaps": [
               {
                  "string" : [ "string" ]
```

```
                }
             ],
             "TargetParameterName": "string",
             "Targets": [
                {
                   "Key": "string",
                   "Values": [ "string" ]
                }
             ]
          }
       ],
       "ScheduledTime": number,
       "Target": "string",
       "TargetLocationsURL": "string",
       "TargetMaps": [
          {
             "string" : [ "string" ]
          }
       ],
       "TargetParameterName": "string",
       "Targets": [
          {
             "Key": "string",
             "Values": [ "string" ]
          }
       ],
       "TriggeredAlarms": [
          {
             "Name": "string",
             "State": "string"
          }
       ]
    }
 ],
 "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecutionMetadataList

The list of details about each automation execution which has occurred which matches the filter specification, if any.

Type: Array of AutomationExecutionMetadata objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAutomationExecutions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAutomationExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T173011Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "AutomationExecutionMetadataList": [
        {
            "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE",
            "AutomationExecutionStatus": "Success",
            "AutomationType": "Local",
            "DocumentName": "Example",
            "DocumentVersion": "1",
            "ExecutedBy": "arn:aws:sts::111122223333:assumed-role/Example",
            "ExecutionEndTime": 1585062669.053,
            "ExecutionStartTime": 1585061570.827,
            "LogFile": "",
            "Mode": "Auto",
            "Outputs": {},
            "ResolvedTargets": {
                "ParameterValues": [],
                "Truncated": false
            },
            "Targets": []
        }
    ]
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeAutomationStepExecutions

Information about all active and terminated step executions in an Automation workflow.

Request Syntax

```
{
   "AutomationExecutionId": "string",
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ReverseOrder": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AutomationExecutionId

The Automation execution ID for which you want step execution descriptions.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Filters

One or more filters to limit the number of step executions returned by the request.

Type: Array of StepExecutionFilter objects

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ReverseOrder

Indicates whether to list step executions in reverse order by start time. The default value is 'false'.

Type: Boolean

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "StepExecutions": [
      {
         "Action": "string",
         "ExecutionEndTime": number,
         "ExecutionStartTime": number,
         "FailureDetails": {
            "Details": {
               "string" : [ "string" ]
            },
            "FailureStage": "string",
            "FailureType": "string"
         },
         "FailureMessage": "string",
```

```
      "Inputs": {
         "string" : "string"
      },
      "IsCritical": boolean,
      "IsEnd": boolean,
      "MaxAttempts": number,
      "NextStep": "string",
      "OnFailure": "string",
      "Outputs": {
         "string" : [ "string" ]
      },
      "OverriddenParameters": {
         "string" : [ "string" ]
      },
      "ParentStepDetails": {
         "Action": "string",
         "Iteration": number,
         "IteratorValue": "string",
         "StepExecutionId": "string",
         "StepName": "string"
      },
      "Response": "string",
      "ResponseCode": "string",
      "StepExecutionId": "string",
      "StepName": "string",
      "StepStatus": "string",
      "TargetLocation": {
         "Accounts": [ "string" ],
         "ExcludeAccounts": [ "string" ],
         "ExecutionRoleName": "string",
         "IncludeChildOrganizationUnits": boolean,
         "Regions": [ "string" ],
         "TargetLocationAlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "TargetLocationMaxConcurrency": "string",
         "TargetLocationMaxErrors": "string",
         "Targets": [
            {
```

```
                  "Key": "string",
                  "Values": [ "string" ]
               }
            ],
            "TargetsMaxConcurrency": "string",
            "TargetsMaxErrors": "string"
         },
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TimeoutSeconds": number,
         "TriggeredAlarms": [
            {
               "Name": "string",
               "State": "string"
            }
         ],
         "ValidNextSteps": [ "string" ]
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

StepExecutions

A list of details about the current state of all steps that make up an execution.

Type: Array of StepExecution objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAutomationStepExecutions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAutomationStepExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T180909Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
    "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE"
}
```

Sample Response

```
{
    "StepExecutions": [
        {
            "Action": "aws:createImage",
            "ExecutionEndTime": 1585062668.968,
            "ExecutionStartTime": 1585061571.144,
            "Inputs": {
                "ImageDescription": "\"AMI for i-02573cafcfEXAMPLE created on
 2020-03-24_14.52.51\"",
                "ImageName": "\"i-02573cafcfEXAMPLE-2020-03-24_14.52.51\"",
                "InstanceId": "\"i-02573cafcfEXAMPLE\"",
                "NoReboot": "false"
            },
            "OnFailure": "Abort",
            "Outputs": {
                "ImageId": [
                    "ami-0f4706cb37EXAMPLE"
                ],
                "ImageState": [
                    "available"
                ],
                "OutputPayload": [
                    "{\"ImageId\":\"ami-0f4706cb37EXAMPLE\",\"ImageState\":\"available
\"}"
                ]
            },
            "OverriddenParameters": {},
```

```
            "StepExecutionId": "eff80946-356d-4128-97b2-6a0f5EXAMPLE",
            "StepName": "createImage",
            "StepStatus": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeAvailablePatches

Lists all patches eligible to be included in a patch baseline.

> **Note**
>
> Currently, `DescribeAvailablePatches` supports only the Amazon Linux 1, Amazon Linux 2, and Windows Server operating systems.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each element in the array is a structure containing a key-value pair.

Windows Server

Supported keys for Windows Server managed node patches include the following:

- **PATCH_SET**

  Sample values: `OS` | `APPLICATION`

- **PRODUCT**

  Sample values: `WindowsServer2012` | `Office 2010` | `MicrosoftDefenderAntivirus`

- **PRODUCT_FAMILY**

  Sample values: `Windows` | `Office`

- **MSRC_SEVERITY**

  Sample values: `ServicePacks` | `Important` | `Moderate`

- **CLASSIFICATION**

  Sample values: `ServicePacks` | `SecurityUpdates` | `DefinitionUpdates`

- **PATCH_ID**

  Sample values: `KB123456` | `KB4516046`

Linux

> **Important**
>
> When specifying filters for Linux patches, you must specify a key-pair for PRODUCT. For example, using the AWS Command Line Interface (AWS CLI), the following command fails:
> `aws ssm describe-available-patches --filters Key=CVE_ID,Values=CVE-2018-3615`
> However, the following command succeeds:
> `aws ssm describe-available-patches --filters Key=PRODUCT,Values=AmazonLinux2018.03 Key=CVE_ID,Values=CVE-2018-3615`

Supported keys for Linux managed node patches include the following:

- **PRODUCT**

  Sample values: `AmazonLinux2018.03` | `AmazonLinux2.0`

- **NAME**

  Sample values: `kernel-headers` | `samba-python` | `php`

- **SEVERITY**

  Sample values: `Critical` | `Important` | `Medium` | `Low`

- **EPOCH**

  Sample values: `0` | `1`

- **VERSION**

  Sample values: `78.6.1` | `4.10.16`

- **RELEASE**

  Sample values: `9.56.amzn1` | `1.amzn2`

- **ARCH**

  Sample values: `i686` | `x86_64`

- **REPOSITORY**

  Sample values: `Core` | `Updates`

- **ADVISORY_ID**

  Sample values: `ALAS-2018-1058` | `ALAS2-2021-1594`

- **CVE_ID**

  Sample values: `CVE-2018-3615` | `CVE-2020-1472`

- **BUGZILLA_ID**

  Sample values: `1463241`

Type: Array of PatchOrchestratorFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Patches": [
      {
         "AdvisoryIds": [ "string" ],
         "Arch": "string",
         "BugzillaIds": [ "string" ],
         "Classification": "string",
         "ContentUrl": "string",
         "CVEIds": [ "string" ],
         "Description": "string",
         "Epoch": number,
         "Id": "string",
         "KbNumber": "string",
         "Language": "string",
         "MsrcNumber": "string",
         "MsrcSeverity": "string",
         "Name": "string",
         "Product": "string",
         "ProductFamily": "string",
         "Release": "string",
         "ReleaseDate": number,
         "Repository": "string",
         "Severity": "string",
         "Title": "string",
         "Vendor": "string",
         "Version": "string"
      }
   ]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Patches

An array of patches. Each entry in the array is a patch structure.

Type: Array of Patch objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeAvailablePatches.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 17
X-Amz-Target: AmazonSSM.DescribeAvailablePatches
X-Amz-Date: 20240308T193543Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Filters": [
        {
            "Key": "PRODUCT",
            "Values": [
                "WindowsServer2016"
            ]
        },
        {
            "Key": "CLASSIFICATION",
            "Values": [
                "SecurityUpdates"
            ]
        },
        {
            "Key": "MSRC_SEVERITY",
            "Values": [
                "Critical"
            ]
        }
    ]
}
```

Sample Response

```
{
    "Patches": [
        {
            "Classification": "SecurityUpdates",
            "ContentUrl": "https://support.microsoft.com/en-us/kb/4074588",
            "Description": "A security issue has been identified in a Microsoft
 software
            product that could affect your system. You can help protect your system by
```

```
            installing this update from Microsoft. For a complete listing of the
 issues
            that are included in this update, see the associated Microsoft Knowledge
 Base
            article. After you install this update, you may have to restart your
 system.",
            "Id": "11adea10-0701-430e-954f-9471595ae246",
            "KbNumber": "KB4074588",
            "Language": "All",
            "MsrcNumber": "",
            "MsrcSeverity": "Critical",
            "Product": "WindowsServer2016",
            "ProductFamily": "Windows",
            "ReleaseDate": 1518548400,
            "Title": "2018-02 Cumulative Update for Windows Server 2016 (1709) for x64-
based
            Systems (KB4074588)",
            "Vendor": "Microsoft"
        },
        {
            "Classification": "SecurityUpdates",
            "ContentUrl": "https://support.microsoft.com/en-us/kb/4074590",
            "Description": "A security issue has been identified in a Microsoft
 software
            product that could affect your system. You can help protect your system by
            installing this update from Microsoft. For a complete listing of the issues
 that are included in this update, see the associated Microsoft Knowledge Base article.
 After you install this update, you may have to restart your system.",
            "Id": "f5f58231-ac5d-4640-ab1b-9dc8d857c265",
            "KbNumber": "KB4074590",
            "Language": "All",
            "MsrcNumber": "",
            "MsrcSeverity": "Critical",
            "Product": "WindowsServer2016",
            "ProductFamily": "Windows",
            "ReleaseDate": 1518544805,
            "Title": "2018-02 Cumulative Update for Windows Server 2016 for x64-based
            Systems (KB4074590)",
            "Vendor": "Microsoft"
        },
        {
            "Classification": "SecurityUpdates",
            "ContentUrl": "https://support.microsoft.com/en-us/kb/4074595",
```

```
            "Description": "A security issue has been identified in a Microsoft
 software
            product that could affect your system. You can help protect your system by
            installing this update from Microsoft. For a complete listing of the
 issues
            that are included in this update, see the associated Microsoft Knowledge
 Base
            article. After you install this update, you may have to restart your
 system.",
            "Id": "754b5889-2e01-40cc-8833-edf86b35541f",
            "KbNumber": "KB4074595",
            "Language": "All",
            "MsrcNumber": "",
            "MsrcSeverity": "Critical",
            "Product": "WindowsServer2016",
            "ProductFamily": "Windows",
            "ReleaseDate": 1517965209,
            "Title": "2018-02 Security Update for Adobe Flash Player for Windows Server
 2016
            for x64-based Systems (KB4074595)",
            "Vendor": "Microsoft"
        }
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

DescribeDocument

Describes the specified AWS Systems Manager document (SSM document).

Request Syntax

```
{
   "DocumentVersion": "string",
   "Name": "string",
   "VersionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentVersion

The document version for which you want information. Can be a specific version or the default version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the SSM document.

> **Note**
>
> If you're calling a shared SSM document from a different AWS account, `Name` is the full Amazon Resource Name (ARN) of the document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

VersionName

An optional field specifying the version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Syntax

```
{
   "Document": {
      "ApprovedVersion": "string",
      "AttachmentsInformation": [
         {
            "Name": "string"
         }
      ],
      "Author": "string",
      "Category": [ "string" ],
      "CategoryEnum": [ "string" ],
      "CreatedDate": number,
      "DefaultVersion": "string",
      "Description": "string",
      "DisplayName": "string",
      "DocumentFormat": "string",
      "DocumentType": "string",
      "DocumentVersion": "string",
      "Hash": "string",
      "HashType": "string",
      "LatestVersion": "string",
      "Name": "string",
      "Owner": "string",
      "Parameters": [
         {
            "DefaultValue": "string",
```

```
            "Description": "string",
            "Name": "string",
            "Type": "string"
         }
      ],
      "PendingReviewVersion": "string",
      "PlatformTypes": [ "string" ],
      "Requires": [
         {
            "Name": "string",
            "RequireType": "string",
            "Version": "string",
            "VersionName": "string"
         }
      ],
      "ReviewInformation": [
         {
            "ReviewedTime": number,
            "Reviewer": "string",
            "Status": "string"
         }
      ],
      "ReviewStatus": "string",
      "SchemaVersion": "string",
      "Sha1": "string",
      "Status": "string",
      "StatusInformation": "string",
      "Tags": [
         {
            "Key": "string",
            "Value": "string"
         }
      ],
      "TargetType": "string",
      "VersionName": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Document

Information about the SSM document.

Type: DocumentDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T182134Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 23

{
    "Name": "Example"
}
```

Sample Response

```
{
    "Document": {
        "CreatedDate": 1585061514.204,
        "DefaultVersion": "1",
        "Description": "Example",
        "DocumentFormat": "YAML",
        "DocumentType": "Automation",
        "DocumentVersion": "1",
        "DisplayName": "ExampleDoc",
        "Hash": "68b196e538f5a895f87a0cc15eb74614021f44b47329aa95ccc0f4f71EXAMPLE",
        "HashType": "Sha256",
        "LatestVersion": "1",
        "Name": "Example",
        "Owner": "111122223333",
        "Parameters": [
            {
                "DefaultValue": "",
                "Description": "(Required) The ARN of the role that allows Automation
 to perform the actions on your behalf. If no role is specified, Systems Manager
 Automation uses your IAM permissions to execute this document.",
                "Name": "AutomationAssumeRole",
                "Type": "String"
            },
            {
                "DefaultValue": "",
                "Description": "(Required) The Instance Id to create an image of.",
                "Name": "InstanceId",
```

```
                "Type": "String"
            }
        ],
        "PlatformTypes": [
            "Windows",
            "Linux"
        ],
        "SchemaVersion": "0.3",
        "Status": "Active",
        "Tags": []
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeDocumentPermission

Describes the permissions for a AWS Systems Manager document (SSM document). If you created the document, you are the owner. If a document is shared, it can either be shared privately (by specifying a user's AWS account ID) or publicly (*All*).

Request Syntax

```
{
   "MaxResults": number,
   "Name": "string",
   "NextToken": "string",
   "PermissionType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 200.

Required: No

Name

The name of the document for which you are the owner.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

PermissionType

The permission type for the document. The permission type can be *Share*.

Type: String

Valid Values: `Share`

Required: Yes

Response Syntax

```
{
   "AccountIds": [ "string" ],
   "AccountSharingInfoList": [
      {
         "AccountId": "string",
         "SharedDocumentVersion": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountIds

The account IDs that have permission to use this document. The ID can be either an AWS account number or `all`.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: `(?i)all|[0-9]{12}`

AccountSharingInfoList

A list of AWS accounts where the current document is shared and the version shared with each account.

Type: Array of AccountSharingInfo objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidPermissionType

The permission type isn't supported. *Share* is the only supported permission type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeDocumentPermission.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeDocumentPermission
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T182653Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "Name": "Example",
    "PermissionType": "Share"
}
```

Sample Response

```
{
    "AccountIds": [],
    "AccountSharingInfoList": []
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeEffectiveInstanceAssociations

All associations for the managed nodes.

Request Syntax

```
{
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InstanceId

The managed node ID for which you want to view all associations.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "Associations": [
      {
         "AssociationId": "string",
         "AssociationVersion": "string",
         "Content": "string",
         "InstanceId": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

The associations for the requested managed node.

Type: Array of InstanceAssociation objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeEffectiveInstanceAssociations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeEffectiveInstanceAssociations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240326T144721Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240326/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37
```

```
{
    "InstanceId": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "Associations": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "InstanceId": "i-02573cafcfEXAMPLE",
            "Content": "{\n    \"schemaVersion\": \"1.2\",\n    \"description\":
 \"Update the Amazon SSM Agent to the latest version or specified version.\",\n--
truncated--",
            "AssociationVersion": "1"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeEffectivePatchesForPatchBaseline

Retrieves the current effective patches (the patch and the approval state) for the specified patch baseline. Applies to patch baselines for Windows only.

Request Syntax

```
{
   "BaselineId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline to retrieve the effective patches for.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

MaxResults

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "EffectivePatches": [
      {
         "Patch": {
            "AdvisoryIds": [ "string" ],
            "Arch": "string",
            "BugzillaIds": [ "string" ],
            "Classification": "string",
            "ContentUrl": "string",
            "CVEIds": [ "string" ],
            "Description": "string",
            "Epoch": number,
            "Id": "string",
            "KbNumber": "string",
            "Language": "string",
            "MsrcNumber": "string",
            "MsrcSeverity": "string",
            "Name": "string",
            "Product": "string",
            "ProductFamily": "string",
            "Release": "string",
            "ReleaseDate": number,
            "Repository": "string",
            "Severity": "string",
            "Title": "string",
            "Vendor": "string",
            "Version": "string"
         },
         "PatchStatus": {
            "ApprovalDate": number,
            "ComplianceLevel": "string",
            "DeploymentStatus": "string"
         }
```

```
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EffectivePatches

An array of patches and patch status.

Type: Array of EffectivePatch objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

UnsupportedOperatingSystem

The operating systems you specified isn't supported, or the operation isn't supported for the operating system.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeEffectivePatchesForPatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.DescribeEffectivePatchesForPatchBaseline
X-Amz-Date: 20240309T061447Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "EffectivePatches": [
        {
            "Patch": {
```

```
                "Classification": "SecurityUpdates",
                "ContentUrl": "https://support.microsoft.com/en-us/kb/2032276",
                "Description": "A security issue has been identified that could allow
an
                unauthenticated remote attacker to compromise your system and gain
control
                over it. You can help protect your system by installing this update
from
                Microsoft. After you install this update, you may have to restart your
system.",
                "Id": "8692029b-a3a2-4a87-a73b-8ea881b4b4d6",
                "KbNumber": "KB2032276",
                "Language": "All",
                "MsrcNumber": "MS10-043",
                "MsrcSeverity": "Important",
                "Product": "WindowsServer2008R2",
                "ProductFamily": "Windows",
                "ReleaseDate": 1279040400,
                "Title": "Security Update for Windows Server 2008 R2 x64 Edition
(KB2032276)",
                "Vendor": "Microsoft"
            },
            "PatchStatus": {
                "ApprovalDate": 1279299600,
                "ComplianceLevel": "UNSPECIFIED",
                "DeploymentStatus": "APPROVED"
            }
        },
        {
            "Patch": {
                "Classification": "SecurityUpdates",
                "ContentUrl": "https://support.microsoft.com/en-us/kb/2124261",
                "Description": "A security issue has been identified that could allow
an
                unauthenticated remote attacker to compromise your system and gain
control
                over it. You can help protect your system by installing this update
from
                Microsoft. After you install this update, you may have to restart your
system.",
                "Id": "12ef1bed-0dd2-4633-b3ac-60888aa8ba33",
                "KbNumber": "KB2124261",
                "Language": "All",
                "MsrcNumber": "MS10-065",
```

```
                "MsrcSeverity": "Important",
                "Product": "Windows7",
                "ProductFamily": "Windows",
                "ReleaseDate": 1284483600,
                "Title": "Security Update for Windows 7 (KB2124261)",
                "Vendor": "Microsoft"
            },
            "PatchStatus": {
                "ApprovalDate": 1284742800,
                "ComplianceLevel": "UNSPECIFIED",
                "DeploymentStatus": "APPROVED"
            }
        },
        {
            "Patch": {
                "Classification": "SecurityUpdates",
                "ContentUrl": "https://support.microsoft.com/en-us/kb/2124261",
                "Description": "A security issue has been identified that could allow
an
                unauthenticated remote attacker to compromise your system and gain
control
                over it. You can help protect your system by installing this update
from
                Microsoft. After you install this update, you may have to restart your
system.",
                "Id": "1b571637-30ed-48d6-b2f3-24d374fdebb8",
                "KbNumber": "KB2124261",
                "Language": "All",
                "MsrcNumber": "MS10-065",
                "MsrcSeverity": "Important",
                "Product": "WindowsServer2008R2",
                "ProductFamily": "Windows",
                "ReleaseDate": 1284483600,
                "Title": "Security Update for Windows Server 2008 R2 x64 Edition
(KB2124261)",
                "Vendor": "Microsoft"
            },
            "PatchStatus": {
                "ApprovalDate": 1284742800,
                "ComplianceLevel": "UNSPECIFIED",
                "DeploymentStatus": "APPROVED"
            }
        }
        // There may be more content here
```

```
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstanceAssociationsStatus

The status of the associations for the managed nodes.

Request Syntax

```
{
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InstanceId

The managed node IDs for which you want association status information.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "InstanceAssociationStatusInfos": [
      {
         "AssociationId": "string",
         "AssociationName": "string",
         "AssociationVersion": "string",
         "DetailedStatus": "string",
         "DocumentVersion": "string",
         "ErrorCode": "string",
         "ExecutionDate": number,
         "ExecutionSummary": "string",
         "InstanceId": "string",
         "Name": "string",
         "OutputUrl": {
            "S3OutputUrl": {
               "OutputUrl": "string"
            }
         },
         "Status": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceAssociationStatusInfos

Status information about the association.

Type: Array of InstanceAssociationStatusInfo objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInstanceAssociationsStatus.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInstanceAssociationsStatus
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T185152Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37

{
    "InstanceId": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "InstanceAssociationStatusInfos": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "DetailedStatus": "Success",
            "DocumentVersion": "1",
            "ExecutionDate": 1581948052.198,
            "InstanceId": "i-02573cafcfEXAMPLE",
            "Name": "AWS-UpdateSSMAgent",
            "Status": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstanceInformation

Provides information about one or more of your managed nodes, including the operating system platform, SSM Agent version, association status, and IP address. This operation does not return information for nodes that are either Stopped or Terminated.

If you specify one or more node IDs, the operation returns information for those managed nodes. If you don't specify node IDs, it returns information for all your managed nodes. If you specify a node ID that isn't valid or a node that you don't own, you receive an error.

> **Note**
>
> The `IamRole` field returned for this API operation is the role assigned to an Amazon EC2 instance configured with a Systems Manager Quick Setup host management configuration or the role assigned to an on-premises managed node.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "InstanceInformationFilterList": [
      {
         "key": "string",
         "valueSet": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters. Use a filter to return a more specific list of managed nodes. You can filter based on tags applied to your managed nodes. Tag filters can't be combined with other filter types. Use this `Filters` data type instead of `InstanceInformationFilterList`, which is deprecated.

Type: Array of InstanceInformationStringFilter objects

Array Members: Minimum number of 0 items.

Required: No

InstanceInformationFilterList

This is a legacy method. We recommend that you don't use this method. Instead, use the `Filters` data type. `Filters` enables you to return node information by filtering based on tags applied to managed nodes.

> **Note**
>
> Attempting to use `InstanceInformationFilterList` and `Filters` leads to an exception error.

Type: Array of InstanceInformationFilter objects

Array Members: Minimum number of 0 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results. The default value is 10 items.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "InstanceInformationList": [
      {
         "ActivationId": "string",
         "AgentVersion": "string",
         "AssociationOverview": {
            "DetailedStatus": "string",
            "InstanceAssociationStatusAggregatedCount": {
               "string" : number
            }
         },
         "AssociationStatus": "string",
         "ComputerName": "string",
         "IamRole": "string",
         "InstanceId": "string",
         "IPAddress": "string",
         "IsLatestVersion": boolean,
         "LastAssociationExecutionDate": number,
         "LastPingDateTime": number,
         "LastSuccessfulAssociationExecutionDate": number,
         "Name": "string",
         "PingStatus": "string",
         "PlatformName": "string",
         "PlatformType": "string",
         "PlatformVersion": "string",
         "RegistrationDate": number,
         "ResourceType": "string",
         "SourceId": "string",
         "SourceType": "string"
      }
   ],
```

```
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceInformationList

The managed node information list.

Type: Array of InstanceInformation objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.

- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidInstanceInformationFilterValue

The specified filter value isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInstanceInformation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInstanceInformation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240220T234247Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 72

{
    "Filters": [
        {
            "Key": "InstanceIds",
            "Values": [
```

```
                "i-02573cafcfEXAMPLE"
            ]
        }
    ]
}
```

Sample Response

```
{
    "InstanceInformationList": [
        {
            "AgentVersion": "2.3.871.0",
            "AssociationOverview": {
                "DetailedStatus": "Failed",
                "InstanceAssociationStatusAggregatedCount": {
                    "Failed": 1,
                    "Success": 1
                }
            },
            "AssociationStatus": "Failed",
            "ComputerName": "WIN-11RMS222RPK.WORKGROUP",
            "IPAddress": "203.0.113.0",
            "InstanceId": "i-02573cafcfEXAMPLE",
            "IsLatestVersion": false,
            "LastAssociationExecutionDate": 1582242019,
            "LastPingDateTime": 1582242018.094,
            "PingStatus": "Online",
            "PlatformName": "Microsoft Windows Server 2008 R2 Datacenter",
            "PlatformType": "Windows",
            "PlatformVersion": "6.1.7601",
            "ResourceType": "EC2Instance"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstancePatches

Retrieves information about the patches on the specified managed node and their state relative to the patch baseline being used for the node.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribeInstancePatches`include the following:

- **`Classification`**

  Sample values: `Security` | `SecurityUpdates`

- **`KBId`**

  Sample values: `KB4480056` | `java-1.7.0-openjdk.x86_64`

- **`Severity`**

  Sample values: `Important` | `Medium` | `Low`

- **`State`**

Sample values: `Installed` | `InstalledOther` | `InstalledPendingReboot`

For lists of all `State` values, see Patch compliance state values in the *AWS Systems Manager User Guide*.

Type: Array of PatchOrchestratorFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

InstanceId

The ID of the managed node whose patch state information should be retrieved.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

MaxResults

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Patches": [
      {
```

```
            "Classification": "string",
            "CVEIds": "string",
            "InstalledTime": number,
            "KBId": "string",
            "Severity": "string",
            "State": "string",
            "Title": "string"
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Patches

Each entry in the array is a structure containing:

- Title (string)
- KBId (string)
- Classification (string)
- Severity (string)
- State (string, such as "INSTALLED" or "FAILED")
- InstalledTime (DateTime)
- InstalledBy (string)

Type: Array of PatchComplianceData objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInstancePatches.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 37
```

```
X-Amz-Target: AmazonSSM.DescribeInstancePatches
X-Amz-Date: 20240308T205131Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "InstanceId": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "Patches": [
        {
            "Title": "NetworkManager.x86_64:1:1.30.0-7.el8",
            "KBId": "NetworkManager.x86_64",
            "Classification": "Security",
            "Severity": "Moderate",
            "State": "Installed",
            "InstalledTime": "2024-05-19T10:03:07-07:00"
        },
        {
            "Title": "bash.x86_64:0:4.4.19-14.el8",
            "KBId": "bash.x86_64",
            "Classification": "Security",
            "Severity": "Low",
            "State": "Installed",
            "InstalledTime": "2024-05-19T10:03:25-07:00"
        },
        {
            "Title": "kernel-modules.x86_64:0:4.18.0-305.10.2.el8_4",
            "KBId": "kernel-modules.x86_64",
            "Classification": "Security",
            "Severity": "Important",
            "State": "Installed",
            "InstalledTime": "2024-08-04T10:45:42-07:00"
        }
        // There may be more content here
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstancePatchStates

Retrieves the high-level patch state of one or more managed nodes.

Request Syntax

```
{
   "InstanceIds": [ "string" ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InstanceIds

The ID of the managed node for which patch state information should be retrieved.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

MaxResults

The maximum number of managed nodes to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "InstancePatchStates": [
      {
         "AvailableSecurityUpdateCount": number,
         "BaselineId": "string",
         "CriticalNonCompliantCount": number,
         "FailedCount": number,
         "InstalledCount": number,
         "InstalledOtherCount": number,
         "InstalledPendingRebootCount": number,
         "InstalledRejectedCount": number,
         "InstallOverrideList": "string",
         "InstanceId": "string",
         "LastNoRebootInstallOperationTime": number,
         "MissingCount": number,
         "NotApplicableCount": number,
         "Operation": "string",
         "OperationEndTime": number,
         "OperationStartTime": number,
         "OtherNonCompliantCount": number,
         "OwnerInformation": "string",
         "PatchGroup": "string",
         "RebootOption": "string",
         "SecurityNonCompliantCount": number,
         "SnapshotId": "string",
         "UnreportedNotApplicableCount": number
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstancePatchStates

The high-level patch state for the requested managed nodes.

Type: Array of InstancePatchState objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInstancePatchStates.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 40
X-Amz-Target: AmazonSSM.DescribeInstancePatchStates
X-Amz-Date: 20240308T202310Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "InstanceIds": [
        "i-02573cafcfEXAMPLE"
    ]
}
```

Sample Response

```
{
    "InstancePatchStates": [
        {
            "InstanceId": "i-02573cafcfEXAMPLE",
            "PatchGroup": "mypatchgroup",
            "BaselineId": "pb-0c10e65780EXAMPLE",
            "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
            "CriticalNonCompliantCount": 2,
            "SecurityNonCompliantCount": 2,
            "OtherNonCompliantCount": 1,
            "InstalledCount": 123,
            "InstalledOtherCount": 334,
            "InstalledPendingRebootCount": 0,
            "InstalledRejectedCount": 0,
            "MissingCount": 1,
            "FailedCount": 2,
            "UnreportedNotApplicableCount": 11,
            "NotApplicableCount": 2063,
            "OperationStartTime": "2024-05-03T11:00:56-07:00",
            "OperationEndTime": "2024-05-03T11:01:09-07:00",
            "Operation": "Scan",
            "LastNoRebootInstallOperationTime": "2024-04-14T12:17:41-07:00",
            "RebootOption": "RebootIfNeeded"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstancePatchStatesForPatchGroup

Retrieves the high-level patch state for the managed nodes in the specified patch group.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "PatchGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each entry in the array is a structure containing:

- Key (string between 1 and 200 characters)
- Values (array containing a single string)
- Type (string "Equal", "NotEqual", "LessThan", "GreaterThan")

Type: Array of InstancePatchStateFilter objects

Array Members: Minimum number of 0 items. Maximum number of 4 items.

Required: No

MaxResults

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

PatchGroup

The name of the patch group for which the patch state information should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
   "InstancePatchStates": [
      {
         "AvailableSecurityUpdateCount": number,
         "BaselineId": "string",
         "CriticalNonCompliantCount": number,
         "FailedCount": number,
         "InstalledCount": number,
         "InstalledOtherCount": number,
         "InstalledPendingRebootCount": number,
         "InstalledRejectedCount": number,
         "InstallOverrideList": "string",
         "InstanceId": "string",
         "LastNoRebootInstallOperationTime": number,
```

```
            "MissingCount": number,
            "NotApplicableCount": number,
            "Operation": "string",
            "OperationEndTime": number,
            "OperationStartTime": number,
            "OtherNonCompliantCount": number,
            "OwnerInformation": "string",
            "PatchGroup": "string",
            "RebootOption": "string",
            "SecurityNonCompliantCount": number,
            "SnapshotId": "string",
            "UnreportedNotApplicableCount": number
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstancePatchStates

The high-level patch state for the requested managed nodes.

Type: Array of InstancePatchState objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInstancePatchStatesForPatchGroup.

Sample Request

```
POST / HTTP/1.1
  Host: ssm.us-east-2.amazonaws.com
  Accept-Encoding: identity
  Content-Length: 33
  X-Amz-Target: AmazonSSM.DescribeInstancePatchStatesForPatchGroup
  X-Amz-Date: 20240308T204541Z
  User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
  Content-Type: application/x-amz-json-1.1
  Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/
ssm/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE

  {
    "PatchGroup": "mypatchgroup"
}
```

Sample Response


```
{
    "InstancePatchStates": [
        {
            "InstanceId": "i-02573cafcfEXAMPLE",
            "PatchGroup": "mypatchgroup",
            "BaselineId": "pb-0c10e65780EXAMPLE",
            "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
            "OwnerInformation": "",
            "InstalledCount": 32,
            "InstalledOtherCount": 1,
            "InstalledPendingRebootCount": 0,
            "InstalledRejectedCount": 0,
            "MissingCount": 2,
            "FailedCount": 0,
            "UnreportedNotApplicableCount": 2671,
            "NotApplicableCount": 400,
            "OperationStartTime": "2024-08-04T11:03:50.590000-07:00",
            "OperationEndTime": "2024-08-04T11:04:21.555000-07:00",
            "Operation": "Scan",
            "RebootOption": "NoReboot",
            "CriticalNonCompliantCount": 0,
            "SecurityNonCompliantCount": 1,
            "OtherNonCompliantCount": 0
        },
        {

            "InstanceId": "i-0471e04240EXAMPLE",
            "PatchGroup": "mypatchgroup",
            "BaselineId": "pb-09ca3fb51fEXAMPLE",
            "SnapshotId": "05d8ffb0-1bbe-4812-ba2d-d9b7bEXAMPLE",
            "OwnerInformation": "",
            "InstalledCount": 45,
            "InstalledOtherCount": 3,
            "InstalledPendingRebootCount": 1,
            "InstalledRejectedCount": 0,
            "MissingCount": 2,
            "FailedCount": 1,
            "UnreportedNotApplicableCount": 3154,
            "NotApplicableCount": 321,
            "OperationStartTime": "2024-08-04T11:04:30.290000-07:00",
            "OperationEndTime": "2024-08-04T11:04:49.255000-07:00",
            "Operation": "Scan",
```

```
            "RebootOption": "NoReboot",
            "CriticalNonCompliantCount": 0,
            "SecurityNonCompliantCount": 2,
            "OtherNonCompliantCount": 1
        }
        // There may be more content here
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInstanceProperties

An API operation used by the Systems Manager console to display information about Systems Manager managed nodes.

Request Syntax

```
{
   "FiltersWithOperator": [
      {
         "Key": "string",
         "Operator": "string",
         "Values": [ "string" ]
      }
   ],
   "InstancePropertyFilterList": [
      {
         "key": "string",
         "valueSet": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

FiltersWithOperator

The request filters to use with the operator.

Type: Array of InstancePropertyStringFilter objects

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Required: No

InstancePropertyFilterList

An array of instance property filters.

Type: Array of InstancePropertyFilter objects

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Required: No

MaxResults

The maximum number of items to return for the call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 1000.

Required: No

NextToken

The token provided by a previous request to use to return the next set of properties.

Type: String

Required: No

Response Syntax

```
{
   "InstanceProperties": [
      {
         "ActivationId": "string",
         "AgentVersion": "string",
         "Architecture": "string",
         "AssociationOverview": {
            "DetailedStatus": "string",
            "InstanceAssociationStatusAggregatedCount": {
               "string" : number
            }
         },
         "AssociationStatus": "string",
         "ComputerName": "string",
         "IamRole": "string",
         "InstanceId": "string",
         "InstanceRole": "string",
```

```
            "InstanceState": "string",
            "InstanceType": "string",
            "IPAddress": "string",
            "KeyName": "string",
            "LastAssociationExecutionDate": number,
            "LastPingDateTime": number,
            "LastSuccessfulAssociationExecutionDate": number,
            "LaunchTime": number,
            "Name": "string",
            "PingStatus": "string",
            "PlatformName": "string",
            "PlatformType": "string",
            "PlatformVersion": "string",
            "RegistrationDate": number,
            "ResourceType": "string",
            "SourceId": "string",
            "SourceType": "string"
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceProperties

Properties for the managed instances.

Type: Array of InstanceProperty objects

NextToken

The token for the next set of properties to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidActivationId

The activation ID isn't valid. Verify that you entered the correct ActivationId or ActivationCode and try again.

HTTP Status Code: 400

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidInstancePropertyFilterValue

The specified filter value isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeInventoryDeletions

Describes a specific delete inventory operation.

Request Syntax

```
{
   "DeletionId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DeletionId

Specify the delete inventory ID for which you want information. This ID was returned by the `DeleteInventory` operation.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "InventoryDeletions": [
      {
         "DeletionId": "string",
         "DeletionStartTime": number,
         "DeletionSummary": {
            "RemainingCount": number,
            "SummaryItems": [
               {
                  "Count": number,
                  "RemainingCount": number,
                  "Version": "string"
               }
            ],
            "TotalCount": number
         },
         "LastStatus": "string",
         "LastStatusMessage": "string",
         "LastStatusUpdateTime": number,
         "TypeName": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InventoryDeletions

A list of status items for deleted inventory.

Type: Array of InventoryDeletionStatusItem objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDeletionIdException

The ID specified for the delete operation doesn't exist or isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeInventoryDeletions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInventoryDeletions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.25 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.describe-inventory-deletions
```

```
X-Amz-Date: 20240810T211220Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240810/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2

{}
```

Sample Response

```
{
  "InventoryDeletions": [
    {
      "DeletionId": "5bc2ba3b-ee6a-40fa-8d09-5eExample",
      "DeletionStartTime": 1628550146,
      "DeletionSummary": {
        "RemainingCount": 0,
        "SummaryItems": [
          {
            "Count": 1,
            "RemainingCount": 0,
            "Version": "1.0"
          }
        ],
        "TotalCount": 1
      },
      "LastStatus": "Complete",
      "LastStatusMessage": "Deletion is successful",
      "LastStatusUpdateTime": 1628550238,
      "TypeName": "Custom:RackInfo"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowExecutions

Lists the executions of a maintenance window. This includes information about when the maintenance window was scheduled to be active, and information about tasks registered and run with the maintenance window.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each entry in the array is a structure containing:

- Key. A string between 1 and 128 characters. Supported keys include `ExecutedBefore` and `ExecutedAfter`.
- Values. An array of strings, each between 1 and 256 characters. Supported values are date/time strings in a valid ISO 8601 date/time format, such as `2024-11-04T05:00:00Z`.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowId

The ID of the maintenance window whose executions should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "WindowExecutions": [
      {
         "EndTime": number,
         "StartTime": number,
         "Status": "string",
         "StatusDetails": "string",
         "WindowExecutionId": "string",
         "WindowId": "string"
      }
```

```
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

WindowExecutions

Information about the maintenance window executions.

Type: Array of MaintenanceWindowExecution objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowExecutions.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutions
X-Amz-Date: 20240312T204551Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "NextToken": "AAEABbrXFUcgJpmXZxxu+AD17F+5bzlsAyqrig1EXAMPLE...pYY",
    "WindowExecutions": [
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "6027b513-64fe-4cf0-be7d-1191aEXAMPLE",
            "Status": "IN_PROGRESS",
            "StartTime": "2024-08-04T11:00:00.000000-07:00"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "ff75b750-4834-4377-8f61-b3cadEXAMPLE",
            "Status": "SUCCESS",
            "StartTime": "2024-08-03T11:00:00.000000-07:00",
            "EndTime": "2024-08-03T11:37:21.450000-07:00"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE",
            "Status": "FAILED",
            "StatusDetails": "One or more tasks in the orchestration failed.",
            "StartTime": "2024-08-02T11:00:00.000000-07:00",
            "EndTime": "2024-08-02T11:22:36.190000-07:00"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowExecutionTaskInvocations

Retrieves the individual task executions (one per target) for a particular task run as part of a maintenance window execution.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "TaskId": "string",
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Optional filters used to scope down the returned task invocations. The supported filter key is STATUS with the corresponding values PENDING, IN_PROGRESS, SUCCESS, FAILED, TIMED_OUT, CANCELLING, and CANCELLED.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

TaskId

The ID of the specific task in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

WindowExecutionId

The ID of the maintenance window execution the task is part of.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "WindowExecutionTaskInvocationIdentities": [
      {
```

```
            "EndTime": number,
            "ExecutionId": "string",
            "InvocationId": "string",
            "OwnerInformation": "string",
            "Parameters": "string",
            "StartTime": number,
            "Status": "string",
            "StatusDetails": "string",
            "TaskExecutionId": "string",
            "TaskType": "string",
            "WindowExecutionId": "string",
            "WindowTargetId": "string"
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

WindowExecutionTaskInvocationIdentities

Information about the task invocation results per invocation.

Type: Array of MaintenanceWindowExecutionTaskInvocationIdentity objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowExecutionTaskInvocations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutionTaskInvocations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240224T233800Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 111

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
    "TaskId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionTaskInvocationIdentities": [
        {
            "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
```

```
            "TaskExecutionId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE",
            "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE",
            "ExecutionId": "1203cf98-5a79-4ec3-97e9-12e0bEXAMPLE",
            "TaskType": "RUN_COMMAND",
            "Parameters": "{\"comment\":\"\",\"documentName\":\"AWS-ApplyPatchBaseline
\",\"instanceIds\":[\"i-00ec29b21eEXAMPLE\",\"i-09911ddd90EXAMPLE\"],\"maxConcurrency
\":\"1\",\"maxErrors\":\"1\",\"parameters\":{\"SnapshotId\":[\"\"],\"Operation\":
[\"Install\"]},\"timeoutSeconds\":600}",
            "Status": "SUCCESS",
            "StatusDetails": "Success",
            "StartTime": "2024-08-04T11:35:35.170000-07:00",
            "EndTime": "2024-08-04T11:42:11.330000-07:00"
        }
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowExecutionTasks

For a given maintenance window execution, lists the tasks that were run.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Optional filters used to scope down the returned tasks. The supported filter key is STATUS with the corresponding values PENDING, IN_PROGRESS, SUCCESS, FAILED, TIMED_OUT, CANCELLING, and CANCELLED.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowExecutionId

The ID of the maintenance window execution whose task executions should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "WindowExecutionTaskIdentities": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "EndTime": number,
         "StartTime": number,
         "Status": "string",
         "StatusDetails": "string",
         "TaskArn": "string",
```

```
            "TaskExecutionId": "string",
            "TaskType": "string",
            "TriggeredAlarms": [
               {
                  "Name": "string",
                  "State": "string"
               }
            ],
            "WindowExecutionId": "string"
         }
      ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

WindowExecutionTaskIdentities

Information about the task executions.

Type: Array of MaintenanceWindowExecutionTaskIdentity objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowExecutionTasks.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutionTasks
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240224T234903Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 61

{
    "WindowExecutionId": "a06e9f91-3b9c-4c3e-8bd4-246ccEXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionTaskIdentities": [
        {
            "WindowExecutionId": "a06e9f91-3b9c-4c3e-8bd4-246ccEXAMPLE",
            "TaskExecutionId": "f407ba63-998f-4b89-8467-279fcEXAMPLE",
            "Status": "SUCCESS",
            "StartTime": "2024-08-04T11:35:35.145000-07:00",
            "EndTime": "2024-08-04T11:38:09.062000-07:00",
```

```
            "TaskArn": "AWS-RunPatchBaseline",
            "TaskType": "RUN_COMMAND"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindows

Retrieves the maintenance windows in an AWS account.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Optional filters used to narrow down the scope of the returned maintenance windows. Supported filter keys are `Name` and `Enabled`. For example, `Name=MyMaintenanceWindow` and `Enabled=True`.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "WindowIdentities": [
      {
         "Cutoff": number,
         "Description": "string",
         "Duration": number,
         "Enabled": boolean,
         "EndDate": "string",
         "Name": "string",
         "NextExecutionTime": "string",
         "Schedule": "string",
         "ScheduleOffset": number,
         "ScheduleTimezone": "string",
         "StartDate": "string",
         "WindowId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

WindowIdentities

Information about the maintenance windows.

Type: Array of MaintenanceWindowIdentity objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindows.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindows
X-Amz-Date: 20240312T202609Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Filters": [
        {
            "Values": [
```

```
                "true"
            ],
            "Key": "Enabled"
        }
    ]
}
```

Sample Response

```
{
    "WindowIdentities": [
        {
            "WindowId": "mw-0c5ed765acEXAMPLE",
            "Name": "Windows-Testing-Maintenance-Window",
            "Description": "Standard maintenance windows for Test Servers",
            "Enabled": true,
            "Duration": 6,
            "Cutoff": 2,
            "Schedule": "rate(2 weeks)",
            "NextExecutionTime": "2024-02-24T23:52:15.099Z"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "Name": "Windows-Staging-Maintenance-Window",
            "Description": "Standard maintenance windows for Staging Servers",
            "Enabled": true,
            "Duration": 10,
            "Cutoff": 4,
            "Schedule": "cron(0 0 6 ? * MON *)",
            "NextExecutionTime": "2024-03-02T06:00:00.099Z"
        },
        {
            "WindowId": "mw-07f80c1841EXAMPLE",
            "Cutoff": 4,
            "Name": "Windows-Production-Maintenance-Window",
            "Description": "Standard maintenance windows for Production Servers",
            "Enabled": true,
            "Duration": 10,
            "Schedule": "cron(0 0 6 ? * WED *)",
            "NextExecutionTime": "2024-03-05T06:00:00.099Z"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowSchedule

Retrieves information about upcoming executions of a maintenance window.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ResourceType": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Filters used to limit the range of results. For example, you can limit maintenance window executions to only those scheduled before or after a certain date and time.

Type: Array of PatchOrchestratorFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ResourceType

The type of resource you want to retrieve information about. For example, `INSTANCE`.

Type: String

Valid Values: `INSTANCE | RESOURCE_GROUP`

Required: No

Targets

The managed node ID or key-value pair to retrieve information about.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

WindowId

The ID of the maintenance window to retrieve information about.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "ScheduledWindowExecutions": [
      {
         "ExecutionTime": "string",
         "Name": "string",
         "WindowId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. (You use this token in the next call.)

Type: String

ScheduledWindowExecutions

Information about maintenance window executions scheduled for the specified time range.

Type: Array of ScheduledWindowExecution objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowSchedule.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowSchedule
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240224T235938Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "NextToken": "EXAMPLE/39c3b3042cd2aEXAMPLEAKIAIOSFODNN7EXAMPLE==",
    "ScheduledWindowExecutions": [
        {
            "ExecutionTime": "2024-02-25T00:00:15.099Z",
```

```
            "Name": "MyMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        },
        {
            "ExecutionTime": "2024-02-26T00:00:15.099Z",
            "Name": "MyMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        },
        {
            "ExecutionTime": "2024-02-27T00:00:15.099Z",
            "Name": "MyMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowsForTarget

Retrieves information about the maintenance window targets or tasks that a managed node is associated with.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "ResourceType": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ResourceType

The type of resource you want to retrieve information about. For example, `INSTANCE`.

Type: String

Valid Values: `INSTANCE | RESOURCE_GROUP`

Required: Yes

Targets

The managed node ID or key-value pair to retrieve information about.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "WindowIdentities": [
      {
         "Name": "string",
         "WindowId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. (You use this token in the next call.)

Type: String

WindowIdentities

Information about the maintenance window targets and tasks a managed node is associated with.

Type: Array of MaintenanceWindowIdentityForTarget objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowsForTarget.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowsForTarget
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T003520Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 100

{
    "Targets": [
        {
            "Key": "InstanceIds",
```

```
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "ResourceType": "INSTANCE"
}
```

Sample Response

```
{
    "WindowIdentities": [
        {
            "Name": "MyFirstMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        },
        {
            "Name": "MySecondMaintenanceWindow",
            "WindowId": "mw-05aaf9f490EXAMPLE"
        },
        {
            "Name": "MyThirdMaintenanceWindow",
            "WindowId": "mw-0ecb1226ddEXAMPLE"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowTargets

Lists the targets registered with the maintenance window.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Optional filters that can be used to narrow down the scope of the returned window targets. The supported filter keys are `Type`, `WindowTargetId`, and `OwnerInformation`.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowId

The ID of the maintenance window whose targets should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "Targets": [
      {
         "Description": "string",
         "Name": "string",
         "OwnerInformation": "string",
         "ResourceType": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "WindowId": "string",
         "WindowTargetId": "string"
      }
```

```
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Targets

Information about the targets in the maintenance window.

Type: Array of MaintenanceWindowTarget objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowTargets.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowTargets
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T003928Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "Targets": [
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "Name": "MyTargets",
            "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE",
            "ResourceType": "INSTANCE",
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-02573cafcfEXAMPLE",
                        "i-0471e04240EXAMPLE"
                    ]
                }
            ]
        },
```

```
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowTargetId": "7f4813bb-df25-4e59-b34f-c9e83EXAMPLE",
            "ResourceType": "INSTANCE",
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-07782c72faEXAMPLE"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeMaintenanceWindowTasks

Lists the tasks in a maintenance window.

> **Note**
>
> For maintenance window tasks without a specified target, you can't supply values for `--max-errors` and `--max-concurrency`. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. These values don't affect the running of your task and can be ignored.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Optional filters used to narrow down the scope of the returned tasks. The supported filter keys are `WindowTaskId`, `TaskArn`, `Priority`, and `TaskType`.

Type: Array of MaintenanceWindowFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowId

The ID of the maintenance window whose tasks should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "Tasks": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
```

```
            "IgnorePollAlarmFailure": boolean
         },
         "CutoffBehavior": "string",
         "Description": "string",
         "LoggingInfo": {
            "S3BucketName": "string",
            "S3KeyPrefix": "string",
            "S3Region": "string"
         },
         "MaxConcurrency": "string",
         "MaxErrors": "string",
         "Name": "string",
         "Priority": number,
         "ServiceRoleArn": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TaskArn": "string",
         "TaskParameters": {
            "string" : {
               "Values": [ "string" ]
            }
         },
         "Type": "string",
         "WindowId": "string",
         "WindowTaskId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Tasks

Information about the tasks in the maintenance window.

Type: Array of MaintenanceWindowTask objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeMaintenanceWindowTasks.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowTasks
Content-Type: application/x-amz-json-1.1
```

```
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T004311Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0ecb1226dd7bEXAMPLE"
}
```

Sample Response

```
{
    "Tasks": [
        {
            "WindowId": "mw-0ecb1226ddEXAMPLE",
            "WindowTaskId": "018b31c3-2d77-4b9e-bd48-c91edEXAMPLE",
            "TaskArn": "AWS-RestartEC2Instance",
            "TaskParameters": {},
            "Type": "AUTOMATION",
            "Description": "Restarting EC2 Instance for maintenance",
            "MaxConcurrency": "1",
            "MaxErrors": "1",
            "Name": "My-Automation-Example-Task",
            "Priority": 0,
            "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/AWSServiceRoleForAmazonSSM",
            "Targets": [
                {
                    "Key": "WindowTargetIds",
                    "Values": [
                        "da89dcc3-7f9c-481d-ba2b-edcb7EXAMPLE"
                    ]
                }
            ]
        },
        {
            "WindowId": "mw-0ecb1226ddEXAMPLE",
            "WindowTaskId": "1943dee0-0a17-4978-9bf4-3cc2fEXAMPLE",
            "TaskArn": "AWS-DisableS3BucketPublicReadWrite",
            "TaskParameters": {},
            "Type": "AUTOMATION",
```

```
            "Description": "Automation task to disable read/write access on public S3
 buckets",
            "MaxConcurrency": "10",
            "MaxErrors": "5",
            "Name": "My-Disable-S3-Public-Read-Write-Access-Automation-Task",
            "Priority": 0,
            "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/AWSServiceRoleForAmazonSSM",
            "Targets": [
                {
                    "Key": "WindowTargetIds",
                    "Values": [
                        "da89dcc3-7f9c-481d-ba2b-edcb7EXAMPLE"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeOpsItems

Query a set of OpsItems. You must have permission in AWS Identity and Access Management (IAM) to query a list of OpsItems. For more information, see Set up OpsCenter in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see AWS Systems Manager OpsCenter in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "OpsItemFilters": [
      {
         "Key": "string",
         "Operator": "string",
         "Values": [ "string" ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

OpsItemFilters

One or more filters to limit the response.

- Key: CreatedTime

  Operations: GreaterThan, LessThan
- Key: LastModifiedBy

  Operations: Contains, Equals
- Key: LastModifiedTime

  Operations: GreaterThan, LessThan
- Key: Priority

  Operations: Equals
- Key: Source

  Operations: Contains, Equals
- Key: Status

  Operations: Equals
- Key: Title*

  Operations: Equals,Contains
- Key: OperationalData**

  Operations: Equals
- Key: OperationalDataKey

  Operations: Equals
- Key: OperationalDataValue

Operations: Equals, Contains

- Key: OpsItemId

  Operations: Equals

- Key: ResourceId

  Operations: Contains

- Key: AutomationId

  Operations: Equals

- Key: AccountId

  Operations: Equals

*The Equals operator for Title matches the first 100 characters. If you specify more than 100 characters, they system returns an error that the filter value exceeds the length limit.

**If you filter the response by using the OperationalData operator, specify a key-value pair by using the following JSON format: {"key":"key_name","value":"a_value"}

Type: Array of OpsItemFilter objects

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "OpsItemSummaries": [
      {
         "ActualEndTime": number,
         "ActualStartTime": number,
         "Category": "string",
         "CreatedBy": "string",
         "CreatedTime": number,
         "LastModifiedBy": "string",
         "LastModifiedTime": number,
         "OperationalData": {
            "string" : {
               "Type": "string",
```

```
                "Value": "string"
            }
        },
        "OpsItemId": "string",
        "OpsItemType": "string",
        "PlannedEndTime": number,
        "PlannedStartTime": number,
        "Priority": number,
        "Severity": "string",
        "Source": "string",
        "Status": "string",
        "Title": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

OpsItemSummaries

A list of OpsItems.

Type: Array of OpsItemSummary objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeOpsItems.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeOpsItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T163154Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 80

{
    "OpsItemFilters": [
        {
            "Key": "Status",
            "Values": [
                "Open"
            ],
            "Operator": "Equal"
        }
    ]
}
```

Sample Response

```
{
    "OpsItemSummaries": [
        {
            "CreatedBy": "arn:aws:iam::111122223333:user/example",
            "CreatedTime": 1585757579.218,
            "LastModifiedBy": "arn:aws:iam::111122223333:user/example",
            "LastModifiedTime": 1585757579.218,
            "OpsItemId": "oi-1f050EXAMPLE",
```

```
            "Source": "SSM",
            "Status": "Open",
            "Title": "DocumentDeleted"
        },
        {
            "Category": "Availability",
            "CreatedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
            "CreatedTime": 1582701517.193,
            "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
            "LastModifiedTime": 1582701517.193,
            "OperationalData": {
                "/aws/dedup": {
                    "Type": "SearchableString",
                    "Value": "{\"dedupString\":\"SSMOpsItems-SSM-maintenance-window-
execution-failed\"}"
                },
                "/aws/resources": {
                    "Type": "SearchableString",
                    "Value": "[{\"arn\":\"arn:aws:ssm:us-
east-2:111122223333:maintenancewindow/mw-0e357ebdc6EXAMPLE\"}]"
                }
            },
            "OpsItemId": "oi-f99f2EXAMPLE",
            "Severity": "3",
            "Source": "SSM",
            "Status": "Open",
            "Title": "SSM Maintenance Window execution failed"
        }
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeParameters

Lists the parameters in your AWS account or the parameters shared with you when you enable the Shared option.

Request results are returned on a best-effort basis. If you specify `MaxResults` in the request, the response includes information up to the limit specified. The number of items returned, however, can be between zero and the value of `MaxResults`. If the service reaches an internal limit while processing the results, it stops the operation and returns the matching values up to that point and a `NextToken`. You can specify the `NextToken` in a subsequent call to get the next set of results.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

> **Important**
>
> If you change the AWS KMS key alias for the KMS key used to encrypt a parameter, then you must also update the key alias the parameter uses to reference KMS. Otherwise, `DescribeParameters` retrieves whatever the original key alias was referencing.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ParameterFilters": [
      {
         "Key": "string",
         "Option": "string",
         "Values": [ "string" ]
      }
   ],
```

```
    "Shared": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

This data type is deprecated. Instead, use `ParameterFilters`.

Type: Array of ParametersFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ParameterFilters

Filters to limit the request results.

Type: Array of ParameterStringFilter objects

Required: No

Shared

Lists parameters that are shared with you.

> **Note**
>
> By default when using this option, the command returns parameters that have been shared using a standard AWS Resource Access Manager Resource Share. In order for a parameter that was shared using the PutResourcePolicy command to be returned, the associated `AWS RAM Resource Share Created From Policy` must have been promoted to a standard Resource Share using the AWS RAM PromoteResourceShareCreatedFromPolicy API operation.
> For more information about sharing parameters, see Working with shared parameters in the *AWS Systems Manager User Guide*.

Type: Boolean

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Parameters": [
      {
         "AllowedPattern": "string",
         "ARN": "string",
         "DataType": "string",
         "Description": "string",
         "KeyId": "string",
         "LastModifiedDate": number,
         "LastModifiedUser": "string",
         "Name": "string",
         "Policies": [
            {
               "PolicyStatus": "string",
               "PolicyText": "string",
               "PolicyType": "string"
            }
         ],
         "Tier": "string",
         "Type": "string",
         "Version": number
```

```
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items.

Type: String

Parameters

Parameters returned by the request.

Type: Array of ParameterMetadata objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterOption

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

message

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeParameters.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 95
X-Amz-Target: AmazonSSM.DescribeParameters
X-Amz-Date: 20240316T010204Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "ParameterFilters": [
        {
            "Values": [
```

```
                "String"
            ],
            "Key": "Type"
        },
        {
            "Values": [
                "/Branch312"
            ],
            "Key": "Name"
        }
    ]
}
```

Sample Response

```
{
    "Parameters": [
        {
            "LastModifiedDate": 1521160696.821,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer1",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160709.358,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer2",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160717.945,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer3",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
```

```
        },
        {
            "LastModifiedDate": 1521160747.499,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mary.Major",
            "Name": "/Branch312/Dev/Intern",
            "Policies": [
                {
                    "PolicyStatus": "Pending",
                    "PolicyText": "{\"Type\":\"Expiration\",\"Version\":\"1.0\",
\"Attributes\":{\"Timestamp\":\"2024-03-31T17:00:00Z\"}}",
                    "PolicyType": "Expiration"
                },
                {
                    "PolicyStatus": "Pending",
                    "PolicyText": "{\"Type\":\"ExpirationNotification\",\"Version\":
\"1.0\",\"Attributes\":{\"Before\":\"14\",\"Unit\":\"Days\"}}",
                    "PolicyType": "ExpirationNotification"
                }
            ],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160588.291,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/John.Stiles",
            "Name": "/Branch312/Dev/TeamLead",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribePatchBaselines

Lists the patch baselines in your AWS account.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribePatchBaselines` include the following:

- **`NAME_PREFIX`**

  Sample values: `AWS-` | `My-`

- **`OWNER`**

  Sample values: `AWS` | `Self`

- **`OPERATING_SYSTEM`**

  Sample values: `AMAZON_LINUX` | `SUSE` | `WINDOWS`

Type: Array of PatchOrchestratorFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of patch baselines to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "BaselineIdentities": [
      {
         "BaselineDescription": "string",
         "BaselineId": "string",
         "BaselineName": "string",
         "DefaultBaseline": boolean,
         "OperatingSystem": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineIdentities

An array of `PatchBaselineIdentity` elements.

Type: Array of PatchBaselineIdentity objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribePatchBaselines.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribePatchBaselines
X-Amz-Date: 20240309T024139Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{}
```

Sample Response


```
{
    "BaselineIdentities": [
        {
            "BaselineDescription": "Default Patch Baseline for Suse Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-07d8884178EXAMPLE",
            "BaselineName": "AWS-SuseDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "SUSE"
        },
        {
            "BaselineDescription": "Default Patch Baseline Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-09ca3fb51fEXAMPLE",
            "BaselineName": "AWS-DefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "WINDOWS"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Amazon Linux Provided by
 AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0c10e65780EXAMPLE",
            "BaselineName": "AWS-AmazonLinuxDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "AMAZON_LINUX"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Ubuntu Provided by
 AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0c7e89f711EXAMPLE",
            "BaselineName": "AWS-UbuntuDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "UBUNTU"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Redhat Enterprise Linux
 Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0cbb3a633dEXAMPLE",
            "BaselineName": "AWS-RedHatDefaultPatchBaseline",
```

```
            "DefaultBaseline": true,
            "OperatingSystem": "REDHAT_ENTERPRISE_LINUX"
        }
        // There may be more content here
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribePatchGroups

Lists all patch groups that have been registered with patch baselines.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribePatchGroups` include the following:

- **`NAME_PREFIX`**

  Sample values: `AWS-` | `My-`.

- **`OPERATING_SYSTEM`**

  Sample values: `AMAZON_LINUX` | `SUSE` | `WINDOWS`

Type: Array of PatchOrchestratorFilter objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of patch groups to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "Mappings": [
      {
         "BaselineIdentity": {
            "BaselineDescription": "string",
            "BaselineId": "string",
            "BaselineName": "string",
            "DefaultBaseline": boolean,
            "OperatingSystem": "string"
         },
         "PatchGroup": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Mappings

Each entry in the array contains:

- `PatchGroup`: string (between 1 and 256 characters. Regex: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`)
- `PatchBaselineIdentity`: A `PatchBaselineIdentity` element.

Type: Array of PatchGroupPatchBaselineMapping objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribePatchGroups.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribePatchGroups
X-Amz-Date: 20240308T211212Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{}
```

Sample Response

```
{
    "Mappings": [
        {
            "PatchGroup": "Database Servers",
            "BaselineIdentity": {
                "BaselineName": "Windows-Server-2012R2",
                "DefaultBaseline": false,
                "BaselineDescription": "Windows Server 2012 R2, Important and Critical
 security updates",
                "BaselineId": "pb-0c4e592064EXAMPLE",
                "OperatingSystem": "WINDOWS"
            }
        },
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "Windows-Server-2012R2",
                "DefaultBaseline": false,
                "BaselineDescription": "Windows Server 2012 R2, Important and Critical
 security updates",
                "BaselineId": "pb-0c4e592064EXAMPLE",
                "OperatingSystem": "WINDOWS"
            }
        },
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "Amazon-Linux-Production",
                "DefaultBaseline": false,
                "BaselineDescription": "Patch baseline used for production instances",
                "BaselineId": "pb-022cbaf99cEXAMPLE",
                "OperatingSystem": "AMAZON_LINUX"
            }
        },
```

```
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "RHEL-ZeroDay-Critical",
                "DefaultBaseline": false,
                "BaselineId": "pb-0ea5bc85f4EXAMPLE",
                "OperatingSystem": "REDHAT_ENTERPRISE_LINUX"
            }
        },
        {
            "PatchGroup": "Production-Demo",
            "BaselineIdentity": {
                "BaselineName": "Only-Security-Patches",
                "DefaultBaseline": false,
                "BaselineDescription": "Security updates for all versions of Windows",
                "BaselineId": "pb-08521bdf9eEXAMPLE",
                "OperatingSystem": "WINDOWS"
            }
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribePatchGroupState

Returns high-level aggregated patch compliance state information for a patch group.

Request Syntax

```
{
   "PatchGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

PatchGroup

The name of the patch group whose patch snapshot should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
   "Instances": number,
   "InstancesWithAvailableSecurityUpdates": number,
   "InstancesWithCriticalNonCompliantPatches": number,
   "InstancesWithFailedPatches": number,
   "InstancesWithInstalledOtherPatches": number,
   "InstancesWithInstalledPatches": number,
   "InstancesWithInstalledPendingRebootPatches": number,
   "InstancesWithInstalledRejectedPatches": number,
   "InstancesWithMissingPatches": number,
   "InstancesWithNotApplicablePatches": number,
```

```
    "InstancesWithOtherNonCompliantPatches": number,
    "InstancesWithSecurityNonCompliantPatches": number,
    "InstancesWithUnreportedNotApplicablePatches": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Instances

The number of managed nodes in the patch group.

Type: Integer

InstancesWithAvailableSecurityUpdates

The number of managed nodes for which security-related patches are available but not approved because because they didn't meet the patch baseline requirements. For example, an updated version of a patch might have been released before the specified auto-approval period was over.

Applies to Windows Server managed nodes only.

Type: Integer

InstancesWithCriticalNonCompliantPatches

The number of managed nodes where patches that are specified as `Critical` for compliance reporting in the patch baseline aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

InstancesWithFailedPatches

The number of managed nodes with patches from the patch baseline that failed to install.

Type: Integer

InstancesWithInstalledOtherPatches

The number of managed nodes with patches installed that aren't defined in the patch baseline.

Type: Integer

InstancesWithInstalledPatches

The number of managed nodes with installed patches.

Type: Integer

InstancesWithInstalledPendingRebootPatches

The number of managed nodes with patches installed by Patch Manager that haven't been rebooted after the patch installation. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

InstancesWithInstalledRejectedPatches

The number of managed nodes with patches installed that are specified in a `RejectedPatches` list. Patches with a status of `INSTALLED_REJECTED` were typically installed before they were added to a `RejectedPatches` list.

> **Note**
>
> If `ALLOW_AS_DEPENDENCY` is the specified option for `RejectedPatchesAction`, the value of `InstancesWithInstalledRejectedPatches` will always be `0` (zero).

Type: Integer

InstancesWithMissingPatches

The number of managed nodes with missing patches from the patch baseline.

Type: Integer

InstancesWithNotApplicablePatches

The number of managed nodes with patches that aren't applicable.

Type: Integer

InstancesWithOtherNonCompliantPatches

The number of managed nodes with patches installed that are specified as other than `Critical` or `Security` but aren't compliant with the patch baseline. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

InstancesWithSecurityNonCompliantPatches

The number of managed nodes where patches that are specified as `Security` in a patch advisory aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

InstancesWithUnreportedNotApplicablePatches

The number of managed nodes with `NotApplicable` patches beyond the supported limit, which aren't reported by name to Inventory. Inventory is a tool in AWS Systems Manager.

Type: Integer

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribePatchGroupState.

Sample Request

```
POST / HTTP/1.1
```

```
  Host: ssm.us-east-2.amazonaws.com
  Accept-Encoding: identity
  Content-Length: 33
  X-Amz-Target: AmazonSSM.DescribePatchGroupState
  X-Amz-Date: 20240308T205757Z
  User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
  Content-Type: application/x-amz-json-1.1
  Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240308/us-east-2/
ssm/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE

  {
    "PatchGroup": "mypatchgroup"
}
```

Sample Response

```
{
    "Instances": 12,
    "InstancesWithCriticalNonCompliantPatches": 1,
    "InstancesWithFailedPatches": 2,
    "InstancesWithInstalledOtherPatches": 3,
    "InstancesWithInstalledPatches": 12,
    "InstancesWithInstalledPendingRebootPatches": 2,
    "InstancesWithInstalledRejectedPatches": 1,
    "InstancesWithMissingPatches": 3,
    "InstancesWithNotApplicablePatches": 0,
    "InstancesWithOtherNonCompliantPatches": 0,
    "InstancesWithSecurityNonCompliantPatches": 1,
    "InstancesWithUnreportedNotApplicablePatches": 0
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribePatchProperties

Lists the properties of available patches organized by product, product family, classification, severity, and other properties of available patches. You can use the reported properties in the filters you specify in requests for operations such as CreatePatchBaseline, UpdatePatchBaseline, DescribeAvailablePatches, and DescribePatchBaselines.

The following section lists the properties that can be used in filters for each major operating system type:

AMAZON_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

AMAZON_LINUX_2

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

AMAZON_LINUX_2023

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

CENTOS

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

DEBIAN

Valid properties: PRODUCT | PRIORITY

MACOS

Valid properties: PRODUCT | CLASSIFICATION

ORACLE_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

REDHAT_ENTERPRISE_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

SUSE

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

UBUNTU

Valid properties: PRODUCT | PRIORITY

WINDOWS

Valid properties: PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | MSRC_SEVERITY

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "OperatingSystem": "string",
   "PatchSet": "string",
   "Property": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

OperatingSystem

The operating system type for which to list patches.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: Yes

PatchSet

Indicates whether to list patches for the Windows operating system or for applications released by Microsoft. Not applicable for the Linux or macOS operating systems.

Type: String

Valid Values: `OS | APPLICATION`

Required: No

Property

The patch property for which you want to view patch details.

Type: String

Valid Values: `PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | MSRC_SEVERITY | PRIORITY | SEVERITY`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "Properties": [
      {
         "string" : "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. (You use this token in the next call.)

Type: String

Properties

A list of the properties for patches matching the filter request parameters.

Type: Array of string to string maps

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribePatchProperties.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 95
X-Amz-Target: AmazonSSM.DescribePatchProperties
X-Amz-Date: 20240312T010204Z
```

```
User-Agent: aws-cli/1.16.96 Python/2.7.15 Windows/10 botocore/1.12.86
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "OperatingSystem": "Windows",
    "Property": "PRODUCT",
    "PatchSet": "OS"
}
```

Sample Response

```
{
    "Properties": [
        {
            "Name": "WindowsServer2012",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2012R2",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2016",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2019",
            "ProductFamily": "Windows"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeSessions

Retrieves a list of all active sessions (both connected and disconnected) or terminated sessions from the past 30 days.

Request Syntax

```
{
   "Filters": [
      {
         "key": "string",
         "value": "string"
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "State": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters to limit the type of sessions returned by the request.

Type: Array of SessionFilter objects

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 200.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

State

The session status to retrieve a list of sessions for. For example, "Active".

Type: String

Valid Values: `Active | History`

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "Sessions": [
      {
         "AccessType": "string",
         "Details": "string",
         "DocumentName": "string",
         "EndDate": number,
         "MaxSessionDuration": "string",
         "OutputUrl": {
            "CloudWatchOutputUrl": "string",
            "S3OutputUrl": "string"
         },
         "Owner": "string",
         "Reason": "string",
         "SessionId": "string",
         "StartDate": number,
         "Status": "string",
         "Target": "string"
```

```
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Sessions

A list of sessions meeting the request parameters.

Type: Array of Session objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeSessions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeSessions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T175636Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 20

{
    "State": "History"
}
```

Sample Response

```
{
    "Sessions": [
        {
            "EndDate": 1582069847.807,
            "OutputUrl": {
                "S3OutputUrl": "https://us-east-2.console.aws.amazon.com/s3/object/
amzn-s3-demo-bucket/session-data/Mary-Major-0ab177d470EXAMPLE.log"
            },
            "Owner": "arn:aws:iam::111122223333:user/Mary-Major",
            "SessionId": "Mary-Major-0ab177d470EXAMPLE",
            "StartDate": 1582068633.188,
            "Status": "Terminated",
            "Target": "i-07782c72faEXAMPLE"
        }
        // There may be more content here
    ]
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DisassociateOpsItemRelatedItem

Deletes the association between an OpsItem and a related item. For example, this API operation can delete an Incident Manager incident from an OpsItem. Incident Manager is a tool in AWS Systems Manager.

Request Syntax

```
{
   "AssociationId": "string",
   "OpsItemId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The ID of the association for which you want to delete an association between the OpsItem and a related item.

Type: String

Required: Yes

OpsItemId

The ID of the OpsItem for which you want to delete an association between the OpsItem and a related item.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemConflictException

The specified OpsItem is in the process of being deleted.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

OpsItemRelatedItemAssociationNotFoundException

The association wasn't found using the parameters you specified in the call. Verify the information and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DisassociateOpsItemRelatedItem.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DisassociateOpsItemRelatedItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/
x86_64.amzn.2 prompt/off command/ssm.disassociate-ops-item-related-item
X-Amz-Date: 20240910T182919Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240910/us-
east-1/ssm/aws4_request, SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE
Content-Length: 89

{
 "OpsItemId": "oi-f99f2EXAMPLE",
 "AssociationId": "e2036148-cccb-490e-ac2a-390e5EXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetAccessToken

Returns a credentials set to be used with just-in-time node access.

Request Syntax

```
{
   "AccessRequestId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AccessRequestId

The ID of a just-in-time node access request.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

Response Syntax

```
{
   "AccessRequestStatus": "string",
   "Credentials": {
      "AccessKeyId": "string",
      "ExpirationTime": number,
      "SecretAccessKey": "string",
      "SessionToken": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccessRequestStatus

The status of the access request.

Type: String

Valid Values: `Approved | Rejected | Revoked | Expired | Pending`

Credentials

The temporary security credentials which can be used to start just-in-time node access sessions.

Type: Credentials object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AccessDeniedException

The requester doesn't have permissions to perform the requested operation.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

ThrottlingException

The request or operation couldn't be performed because the service is throttling requests.

QuotaCode

The quota code recognized by the AWS Service Quotas service.

ServiceCode

The code for the AWS service that owns the quota.

HTTP Status Code: 400

ValidationException

The request isn't valid. Verify that you entered valid contents for the command and try again.

ReasonCode

The reason code for the invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetAutomationExecution

Get detailed information about a particular Automation execution.

Request Syntax

```
{
   "AutomationExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AutomationExecutionId

The unique identifier for an existing automation execution to examine. The execution ID is returned by StartAutomationExecution when the execution of an Automation runbook is initiated.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Response Syntax

```
{
   "AutomationExecution": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
      },
      "AssociationId": "string",
```

```
      "AutomationExecutionId": "string",
      "AutomationExecutionStatus": "string",
      "AutomationSubtype": "string",
      "ChangeRequestName": "string",
      "CurrentAction": "string",
      "CurrentStepName": "string",
      "DocumentName": "string",
      "DocumentVersion": "string",
      "ExecutedBy": "string",
      "ExecutionEndTime": number,
      "ExecutionStartTime": number,
      "FailureMessage": "string",
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "Mode": "string",
      "OpsItemId": "string",
      "Outputs": {
         "string" : [ "string" ]
      },
      "Parameters": {
         "string" : [ "string" ]
      },
      "ParentAutomationExecutionId": "string",
      "ProgressCounters": {
         "CancelledSteps": number,
         "FailedSteps": number,
         "SuccessSteps": number,
         "TimedOutSteps": number,
         "TotalSteps": number
      },
      "ResolvedTargets": {
         "ParameterValues": [ "string" ],
         "Truncated": boolean
      },
      "Runbooks": [
         {
            "DocumentName": "string",
            "DocumentVersion": "string",
            "MaxConcurrency": "string",
            "MaxErrors": "string",
            "Parameters": {
               "string" : [ "string" ]
            },
            "TargetLocations": [
```

```
            {
               "Accounts": [ "string" ],
               "ExcludeAccounts": [ "string" ],
               "ExecutionRoleName": "string",
               "IncludeChildOrganizationUnits": boolean,
               "Regions": [ "string" ],
               "TargetLocationAlarmConfiguration": {
                  "Alarms": [
                     {
                        "Name": "string"
                     }
                  ],
                  "IgnorePollAlarmFailure": boolean
               },
               "TargetLocationMaxConcurrency": "string",
               "TargetLocationMaxErrors": "string",
               "Targets": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ],
               "TargetsMaxConcurrency": "string",
               "TargetsMaxErrors": "string"
            }
         ],
         "TargetMaps": [
            {
               "string" : [ "string" ]
            }
         ],
         "TargetParameterName": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ]
      }
   ],
   "ScheduledTime": number,
   "StepExecutions": [
      {
         "Action": "string",
```

```
            "ExecutionEndTime": number,
            "ExecutionStartTime": number,
            "FailureDetails": {
               "Details": {
                  "string" : [ "string" ]
               },
               "FailureStage": "string",
               "FailureType": "string"
            },
            "FailureMessage": "string",
            "Inputs": {
               "string" : "string"
            },
            "IsCritical": boolean,
            "IsEnd": boolean,
            "MaxAttempts": number,
            "NextStep": "string",
            "OnFailure": "string",
            "Outputs": {
               "string" : [ "string" ]
            },
            "OverriddenParameters": {
               "string" : [ "string" ]
            },
            "ParentStepDetails": {
               "Action": "string",
               "Iteration": number,
               "IteratorValue": "string",
               "StepExecutionId": "string",
               "StepName": "string"
            },
            "Response": "string",
            "ResponseCode": "string",
            "StepExecutionId": "string",
            "StepName": "string",
            "StepStatus": "string",
            "TargetLocation": {
               "Accounts": [ "string" ],
               "ExcludeAccounts": [ "string" ],
               "ExecutionRoleName": "string",
               "IncludeChildOrganizationUnits": boolean,
               "Regions": [ "string" ],
               "TargetLocationAlarmConfiguration": {
                  "Alarms": [
```

```
                  {
                     "Name": "string"
                  }
               ],
               "IgnorePollAlarmFailure": boolean
            },
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string",
            "Targets": [
               {
                  "Key": "string",
                  "Values": [ "string" ]
               }
            ],
            "TargetsMaxConcurrency": "string",
            "TargetsMaxErrors": "string"
         },
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TimeoutSeconds": number,
         "TriggeredAlarms": [
            {
               "Name": "string",
               "State": "string"
            }
         ],
         "ValidNextSteps": [ "string" ]
      }
   ],
   "StepExecutionsTruncated": boolean,
   "Target": "string",
   "TargetLocations": [
      {
         "Accounts": [ "string" ],
         "ExcludeAccounts": [ "string" ],
         "ExecutionRoleName": "string",
         "IncludeChildOrganizationUnits": boolean,
         "Regions": [ "string" ],
         "TargetLocationAlarmConfiguration": {
            "Alarms": [
```

```
                    {
                        "Name": "string"
                    }
                ],
                "IgnorePollAlarmFailure": boolean
            },
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string",
            "Targets": [
                {
                    "Key": "string",
                    "Values": [ "string" ]
                }
            ],
            "TargetsMaxConcurrency": "string",
            "TargetsMaxErrors": "string"
        }
    ],
    "TargetLocationsURL": "string",
    "TargetMaps": [
        {
            "string" : [ "string" ]
        }
    ],
    "TargetParameterName": "string",
    "Targets": [
        {
            "Key": "string",
            "Values": [ "string" ]
        }
    ],
    "TriggeredAlarms": [
        {
            "Name": "string",
            "State": "string"
        }
    ],
    "Variables": {
        "string" : [ "string" ]
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecution

Detailed information about the current state of an automation execution.

Type: AutomationExecution object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetAutomationExecution
Content-Type: application/x-amz-json-1.1
```

```
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T185532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
    "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE"
}
```

Sample Response

```
{
    "AutomationExecution": {
        "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE",
        "AutomationExecutionStatus": "Success",
        "DocumentName": "CreateImage",
        "DocumentVersion": "1",
        "ExecutedBy": "arn:aws:sts::111122223333:assumed-role/Example",
        "ExecutionEndTime": 1585062669.053,
        "ExecutionStartTime": 1585061570.827,
        "Mode": "Auto",
        "Outputs": {},
        "Parameters": {
            "InstanceId": [
                "i-02573cafcfEXAMPLE"
            ]
        },
        "ResolvedTargets": {
            "ParameterValues": [],
            "Truncated": false
        },
        "StepExecutions": [
            {
                "Action": "aws:createImage",
                "ExecutionEndTime": 1585062668.968,
                "ExecutionStartTime": 1585061571.144,
                "Inputs": {
                    "ImageDescription": "\"AMI for i-02573cafcfEXAMPLE created on
 2020-03-24_14.52.51\"",
                    "ImageName": "\"i-02573cafcfEXAMPLE-2020-03-24_14.52.51\"",
                    "InstanceId": "\"i-02573cafcfEXAMPLE\"",
```

```
                    "NoReboot": "false"
                },
                "OnFailure": "Abort",
                "Outputs": {
                    "ImageId": [
                        "ami-0f4706cb37EXAMPLE"
                    ],
                    "ImageState": [
                        "available"
                    ],
                    "OutputPayload": [
                        "{\"ImageId\":\"ami-0f4706cb37EXAMPLE\",\"ImageState\":
\"available\"}"
                    ]
                },
                "OverriddenParameters": {},
                "StepExecutionId": "eff80946-356d-4128-97b2-6a0f5EXAMPLE",
                "StepName": "createImage",
                "StepStatus": "Success"
            }
        ],
        "StepExecutionsTruncated": false,
        "Targets": []
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

GetCalendarState

Gets the state of a AWS Systems Manager change calendar at the current time or a specified time. If you specify a time, `GetCalendarState` returns the state of the calendar at that specific time, and returns the next time that the change calendar state will transition. If you don't specify a time, `GetCalendarState` uses the current time. Change Calendar entries have two possible states: `OPEN` or `CLOSED`.

If you specify more than one calendar in a request, the command returns the status of `OPEN` only if all calendars in the request are open. If one or more calendars in the request are closed, the status returned is `CLOSED`.

For more information about Change Calendar, a tool in AWS Systems Manager, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "AtTime": "string",
   "CalendarNames": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AtTime

(Optional) The specific time for which you want to get calendar state information, in ISO 8601 format. If you don't specify a value or `AtTime`, the current time is used.

Type: String

Required: No

CalendarNames

The names of Amazon Resource Names (ARNs) of the Systems Manager documents (SSM documents) that represent the calendar entries for which you want to get the state.

Type: Array of strings

Required: Yes

Response Syntax

```
{
   "AtTime": "string",
   "NextTransitionTime": "string",
   "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AtTime

The time, as an ISO 8601 string, that you specified in your command. If you don't specify a time, `GetCalendarState` uses the current time.

Type: String

NextTransitionTime

The time, as an ISO 8601 string, that the calendar state will change. If the current calendar state is `OPEN`, `NextTransitionTime` indicates when the calendar state changes to `CLOSED`, and vice-versa.

Type: String

State

The state of the calendar. An `OPEN` calendar indicates that actions are allowed to proceed, and a `CLOSED` calendar indicates that actions aren't allowed to proceed.

Type: String

Valid Values: `OPEN` | `CLOSED`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentType

The SSM document type isn't valid. Valid document types are described in the `DocumentType` property.

HTTP Status Code: 400

UnsupportedCalendarException

The calendar entry contained in the specified SSM document isn't supported.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetCalendarState.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetCalendarState
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240224T191829Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "CalendarNames": [
        "MyCalendar"
    ],
    "AtTime": "2024-02-25T19:05:47Z"
}
```

Sample Response

```
{
    "AtTime": "2024-02-25T19:05:47Z",
    "State": "OPEN"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

GetCommandInvocation

Returns detailed information about command execution for an invocation or plugin. The Run Command API follows an eventual consistency model, due to the distributed nature of the system supporting the API. This means that the result of an API command you run that affects your resources might not be immediately visible to all subsequent commands you run. You should keep this in mind when you carry out an API command that immediately follows a previous API command.

`GetCommandInvocation` only gives the execution status of a plugin in a document. To get the command execution status on a specific managed node, use ListCommandInvocations. To get the command execution status across managed nodes, use ListCommands.

Request Syntax

```
{
   "CommandId": "string",
   "InstanceId": "string",
   "PluginName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

CommandId

(Required) The parent command ID of the invocation plugin.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

InstanceId

(Required) The ID of the managed node targeted by the command. A *managed node* can be an Amazon Elastic Compute Cloud (Amazon EC2) instance, edge device, and on-premises server or VM in your hybrid environment that is configured for AWS Systems Manager.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

PluginName

The name of the step for which you want detailed results. If the document contains only one step, you can omit the name and details for that step. If the document contains more than one step, you must specify the name of the step for which you want to view details. Be sure to specify the name of the step, not the name of a plugin like `aws:RunShellScript`.

To find the `PluginName`, check the document content and find the name of the step you want details for. Alternatively, use ListCommandInvocations with the `CommandId` and `Details` parameters. The `PluginName` is the `Name` attribute of the `CommandPlugin` object in the `CommandPlugins` list.

Type: String

Length Constraints: Minimum length of 4.

Required: No

Response Syntax

```
{
   "CloudWatchOutputConfig": {
      "CloudWatchLogGroupName": "string",
      "CloudWatchOutputEnabled": boolean
   },
   "CommandId": "string",
   "Comment": "string",
   "DocumentName": "string",
   "DocumentVersion": "string",
   "ExecutionElapsedTime": "string",
   "ExecutionEndDateTime": "string",
   "ExecutionStartDateTime": "string",
   "InstanceId": "string",
   "PluginName": "string",
   "ResponseCode": number,
   "StandardErrorContent": "string",
```

```
    "StandardErrorUrl": "string",
    "StandardOutputContent": "string",
    "StandardOutputUrl": "string",
    "Status": "string",
    "StatusDetails": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CloudWatchOutputConfig

Amazon CloudWatch Logs information where Systems Manager sent the command output.

Type: CloudWatchOutputConfig object

CommandId

The parent command ID of the invocation plugin.

Type: String

Length Constraints: Fixed length of 36.

Comment

The comment text for the command.

Type: String

Length Constraints: Maximum length of 100.

DocumentName

The name of the document that was run. For example, `AWS-RunShellScript`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

DocumentVersion

The Systems Manager document (SSM document) version used in the request.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

ExecutionElapsedTime

Duration since `ExecutionStartDateTime`.

Type: String

Pattern: `^([\-]?\d{4}(?!\d{2}\b))((-?)((0[1-9]|1[0-2])(\3([12]\d|0[1-9]|3[01]))?|W([0-4]\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\d|[12]\d{2}|3([0-5]\d|6[1-6])))([T\s](([01]\d|2[0-3])((:?)[0-5]\d)?|24\:?00)([\.,]\d(?!:))?)?(\17[0-5]\d([\.,]\d)?)?([zZ]|([\-])([01]\d|2[0-3]):?([0-5]\d)?)?)?)?$`

ExecutionEndDateTime

The date and time the plugin finished running. Date and time are written in ISO 8601 format. For example, June 7, 2017 is represented as 2017-06-7. The following sample AWS CLI command uses the `InvokedAfter` filter.

```
aws ssm list-commands --filters
key=InvokedAfter,value=2017-06-07T00:00:00Z
```

If the plugin hasn't started to run, the string is empty.

Type: String

Pattern: `^([\-]?\d{4}(?!\d{2}\b))((-?)((0[1-9]|1[0-2])(\3([12]\d|0[1-9]|3[01]))?|W([0-4]\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\d|[12]\d{2}|3([0-5]\d|6[1-6])))([T\s](([01]\d|2[0-3])((:?)[0-5]\d)?|24\:?00)([\.,]\d(?!:))?)?(\17[0-5]\d([\.,]\d)?)?([zZ]|([\-])([01]\d|2[0-3]):?([0-5]\d)?)?)?)?$`

ExecutionStartDateTime

The date and time the plugin started running. Date and time are written in ISO 8601 format. For example, June 7, 2017 is represented as 2017-06-7. The following sample AWS CLI command uses the `InvokedBefore` filter.

```
aws ssm list-commands --filters
key=InvokedBefore,value=2017-06-07T00:00:00Z
```

If the plugin hasn't started to run, the string is empty.

Type: String

Pattern: `^([\-]?\d{4}(?!\d{2}\b))((-?)((0[1-9]|1[0-2])(\3([12]\d|0[1-9]|3[01]))?|W([0-4]\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\d|[12]\d{2}|3([0-5]\d|6[1-6])))([T\s](([01]\d|2[0-3])((:?)[0-5]\d)?|24\:?00)([\.,]\d(?!:))?)?(\17[0-5]\d([\.,]\d)?)?([zZ]|([\-])([01]\d|2[0-3]):?([0-5]\d)?)?)?)?$`

InstanceId

The ID of the managed node targeted by the command. A *managed node* can be an Amazon Elastic Compute Cloud (Amazon EC2) instance, edge device, or on-premises server or VM in your hybrid environment that is configured for AWS Systems Manager.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

PluginName

The name of the plugin, or *step name*, for which details are reported. For example, `aws:RunShellScript` is a plugin.

Type: String

Length Constraints: Minimum length of 4.

ResponseCode

The error level response code for the plugin script. If the response code is `-1`, then the command hasn't started running on the managed node, or it wasn't received by the node.

Type: Integer

StandardErrorContent

The first 8,000 characters written by the plugin to `stderr`. If the command hasn't finished running, then this string is empty.

Type: String

Length Constraints: Maximum length of 8000.

StandardErrorUrl

The URL for the complete text written by the plugin to `stderr`. If the command hasn't finished running, then this string is empty.

Type: String

StandardOutputContent

The first 24,000 characters written by the plugin to `stdout`. If the command hasn't finished running, if `ExecutionStatus` is neither Succeeded nor Failed, then this string is empty.

Type: String

Length Constraints: Maximum length of 24000.

StandardOutputUrl

The URL for the complete text written by the plugin to `stdout` in Amazon Simple Storage Service (Amazon S3). If an S3 bucket wasn't specified, then this string is empty.

Type: String

Status

The status of this invocation plugin. This status can be different than `StatusDetails`.

Type: String

Valid Values: `Pending | InProgress | Delayed | Success | Cancelled | TimedOut | Failed | Cancelling`

StatusDetails

A detailed status of the command execution for an invocation. `StatusDetails` includes more information than `Status` because it includes states resulting from error and concurrency control parameters. `StatusDetails` can show different results than `Status`. For more information about these statuses, see Understanding command statuses in the *AWS Systems Manager User Guide*. `StatusDetails` can be one of the following values:

- Pending: The command hasn't been sent to the managed node.
- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.

- Delayed: The system attempted to send the command to the target, but the target wasn't available. The managed node might not be available because of network issues, because the node was stopped, or for similar reasons. The system will try to send the command again.
- Success: The command or plugin ran successfully. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's `MaxErrors` limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: The command started to run on the managed node, but the execution wasn't complete before the timeout expired. Execution timeouts count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Failed: The command wasn't run successfully on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The node might not exist or might not be responding. Undeliverable invocations don't count against the parent command's `MaxErrors` limit and don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Terminated: The parent command exceeded its `MaxErrors` limit and subsequent command invocations were canceled by the system. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidPluginName

The plugin name isn't valid.

HTTP Status Code: 400

InvocationDoesNotExist

The command ID and managed node ID you specified didn't match any invocations. Verify the command ID and the managed node ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetCommandInvocation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetCommandInvocation
```

```
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240220T235111Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 90

{
    "CommandId": "32d70fe0-ddbc-4a4e-943f-ffcbcEXAMPLE",
    "InstanceId": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "",
        "CloudWatchOutputEnabled": false
    },
    "CommandId": "32d70fe0-ddbc-4a4e-943f-ffcbcEXAMPLE",
    "Comment": "b48291dd-ba76-43e0-b9df-13e11ddaac26:6960febb-2907-4b59-8e1a-
d6ce8EXAMPLE",
    "DocumentName": "AWS-UpdateSSMAgent",
    "DocumentVersion": "",
    "ExecutionElapsedTime": "PT44.002S",
    "ExecutionEndDateTime": "2024-02-20T23:35:26.758Z",
    "ExecutionStartDateTime": "2024-02-20T23:34:42.758Z",
    "InstanceId": "i-02573cafcfEXAMPLE",
    "PluginName": "aws:updateSsmAgent",
    "ResponseCode": 0,
    "StandardErrorContent": "",
    "StandardErrorUrl": "",
    "StandardOutputContent": "Updating amazon-ssm-agent from 2.3.842.0 to latest
        \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-
east-2/ssm-agent-manifest.json
        \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-
east-2/amazon-ssm-agent-updater/2.3.871.0/amazon-ssm-agent-updater-windows-amd64.zip
        \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-
east-2/amazon-ssm-agent/2.3.842.0/amazon-ssm-agent-windows-amd64.zip
        \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-
east-2/amazon-ssm-agent/2.3.871.0/amazon-ssm-agent-windows-amd64.zip
        \nInitiating amazon-ssm-agent update to 2.3.871.0
```

```
        \namazon-ssm-agent updated successfully to 2.3.871.0",
    "StandardOutputUrl": "",
    "Status": "Success",
    "StatusDetails": "Success"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConnectionStatus

Retrieves the Session Manager connection status for a managed node to determine whether it is running and ready to receive Session Manager connections.

Request Syntax

```
{
   "Target": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Target

The managed node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

Response Syntax

```
{
   "Status": "string",
   "Target": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Status

The status of the connection to the managed node.

Type: String

Valid Values: `connected | notconnected`

Target

The ID of the managed node to check connection status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetConnectionStatus.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetConnectionStatus
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T180655Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 33

{
    "Target": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "Status": "connected",
    "Target": "i-02573cafcfEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetDefaultPatchBaseline

Retrieves the default patch baseline. AWS Systems Manager supports creating multiple default patch baselines. For example, you can create a default patch baseline for each operating system.

If you don't specify an operating system value, the default patch baseline for Windows is returned.

Request Syntax

```
{
   "OperatingSystem": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

OperatingSystem

Returns the default patch baseline for the specified operating system.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: No

Response Syntax

```
{
   "BaselineId": "string",
   "OperatingSystem": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

OperatingSystem

The operating system for the returned patch baseline.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetDefaultPatchBaseline.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 35
X-Amz-Target: AmazonSSM.GetDefaultPatchBaseline
X-Amz-Date: 20240309T025228Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "OperatingSystem": "AMAZON_LINUX"
}
```

Sample Response

```
{
    "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0c10e65780EXAMPLE",
    "OperatingSystem": "AMAZON_LINUX"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetDeployablePatchSnapshotForInstance

Retrieves the current snapshot for the patch baseline the managed node uses. This API is primarily used by the `AWS-RunPatchBaseline` Systems Manager document (SSM document).

> **Note**
>
> If you run the command locally, such as with the AWS Command Line Interface (AWS CLI), the system attempts to use your local AWS credentials and the operation fails. To avoid this, you can run the command in the AWS Systems Manager console. Use Run Command, a tool in AWS Systems Manager, with an SSM document that enables you to target a managed node with a script or command. For example, run the command using the `AWS-RunShellScript` document or the `AWS-RunPowerShellScript` document.

Request Syntax

```
{
   "BaselineOverride": {
      "ApprovalRules": {
         "PatchRules": [
            {
               "ApproveAfterDays": number,
               "ApproveUntilDate": "string",
               "ComplianceLevel": "string",
               "EnableNonSecurity": boolean,
               "PatchFilterGroup": {
                  "PatchFilters": [
                     {
                        "Key": "string",
                        "Values": [ "string" ]
                     }
                  ]
               }
            }
         ]
      },
      "ApprovedPatches": [ "string" ],
      "ApprovedPatchesComplianceLevel": "string",
      "ApprovedPatchesEnableNonSecurity": boolean,
      "AvailableSecurityUpdatesComplianceStatus": "string",
```

```
      "GlobalFilters": {
         "PatchFilters": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ]
      },
      "OperatingSystem": "string",
      "RejectedPatches": [ "string" ],
      "RejectedPatchesAction": "string",
      "Sources": [
         {
            "Configuration": "string",
            "Name": "string",
            "Products": [ "string" ]
         }
      ]
   },
   "InstanceId": "string",
   "SnapshotId": "string",
   "UseS3DualStackEndpoint": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineOverride

Defines the basic information about a patch baseline override.

Type: BaselineOverride object

Required: No

InstanceId

The ID of the managed node for which the appropriate patch snapshot should be retrieved.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

SnapshotId

The snapshot ID provided by the user when running `AWS-RunPatchBaseline`.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

UseS3DualStackEndpoint

Specifies whether to use S3 dualstack endpoints for the patch snapshot download URL. Set to `true` to receive a presigned URL that supports both IPv4 and IPv6 connectivity. Set to `false` to use standard IPv4-only endpoints. Default is `false`. This parameter is required for managed nodes in IPv6-only environments.

Type: Boolean

Required: No

Response Syntax

```
{
   "InstanceId": "string",
   "Product": "string",
   "SnapshotDownloadUrl": "string",
   "SnapshotId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Product

Returns the specific operating system (for example Windows Server 2012 or Amazon Linux 2015.09) on the managed node for the specified patch snapshot.

Type: String

SnapshotDownloadUrl

A pre-signed Amazon Simple Storage Service (Amazon S3) URL that can be used to download the patch snapshot.

Type: String

SnapshotId

The user-defined snapshot ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

UnsupportedFeatureRequiredException

Patching for applications released by Microsoft is only available on EC2 instances and advanced instances. To patch applications released by Microsoft on on-premises servers and VMs, you must enable advanced instances. For more information, see Turning on the advanced-instances tier in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

UnsupportedOperatingSystem

The operating systems you specified isn't supported, or the operation isn't supported for the operating system.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetDeployablePatchSnapshotForInstance.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 91
X-Amz-Target: AmazonSSM.GetDeployablePatchSnapshotForInstance
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.12 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.get-deployable-patch-snapshot-for-instance
X-Amz-Date: 20240618T204500Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240618/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "InstanceId": "i-02573cafcfEXAMPLE",
    "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE"
}
```

Sample Response

```
{
    "InstanceId": "i-02573cafcfEXAMPLE",
    "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
    "Product": "AmazonLinux2018.03",
    "SnapshotDownloadUrl": "https://amzn-s3-demo-bucket.s3.us-east-2.amazonaws.com/
b7d801675252464bEXAMPLE--truncated--"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetDocument

Gets the contents of the specified AWS Systems Manager document (SSM document).

Request Syntax

```
{
   "DocumentFormat": "string",
   "DocumentVersion": "string",
   "Name": "string",
   "VersionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentFormat

Returns the document in the specified format. The document format can be either JSON or YAML. JSON is the default format.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentVersion

The document version for which you want information.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

VersionName

An optional field specifying the version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Syntax

```
{
   "AttachmentsContent": [
      {
         "Hash": "string",
         "HashType": "string",
         "Name": "string",
         "Size": number,
         "Url": "string"
      }
   ],
   "Content": "string",
   "CreatedDate": number,
   "DisplayName": "string",
   "DocumentFormat": "string",
   "DocumentType": "string",
   "DocumentVersion": "string",
   "Name": "string",
   "Requires": [
      {
         "Name": "string",
         "RequireType": "string",
         "Version": "string",
         "VersionName": "string"
      }
```

```
    ],
    "ReviewStatus": "string",
    "Status": "string",
    "StatusInformation": "string",
    "VersionName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachmentsContent

A description of the document attachments, including names, locations, sizes, and so on.

Type: Array of AttachmentContent objects

Content

The contents of the SSM document.

Type: String

Length Constraints: Minimum length of 1.

CreatedDate

The date the SSM document was created.

Type: Timestamp

DisplayName

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see UpdateDocument.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: `YAML | JSON | TEXT`

DocumentType

The document type.

Type: String

Valid Values: `Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate | CloudFormation | ConformancePackTemplate | QuickSetup | ManualApprovalPolicy | AutoApprovalPolicy`

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Requires

A list of SSM documents required by a document. For example, an `ApplicationConfiguration` document requires an `ApplicationConfigurationSchema` document.

Type: Array of DocumentRequires objects

Array Members: Minimum number of 1 item.

ReviewStatus

The current review status of a new custom Systems Manager document (SSM document) created by a member of your organization, or of the latest version of an existing SSM document.

Only one version of an SSM document can be in the APPROVED state at a time. When a new version is approved, the status of the previous version changes to REJECTED.

Only one version of an SSM document can be in review, or PENDING, at a time.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Status

The status of the SSM document, such as `Creating`, `Active`, `Updating`, `Failed`, and `Deleting`.

Type: String

Valid Values: `Creating | Active | Updating | Deleting | Failed`

StatusInformation

A message returned by AWS Systems Manager that explains the `Status` value. For example, a `Failed` status might be explained by the `StatusInformation` message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

VersionName

The version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T190721Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 30

{
```

```
    "Name": "AWS-UpdateSSMAgent"
}
```

Sample Response

```
{
   "Content":"{\n    \"schemaVersion\": \"1.2\",\n  \"description\": \"Update the
 Amazon SSM Agent to the latest version or specified version.\",--truncated--n",
   "DocumentFormat":"JSON",
   "DocumentType":"Command",
   "DocumentVersion":"1",
   "Name":"AWS-UpdateSSMAgent",
   "Status":"Active"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetExecutionPreview

Initiates the process of retrieving an existing preview that shows the effects that running a specified Automation runbook would have on the targeted resources.

Request Syntax

```
{
   "ExecutionPreviewId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ExecutionPreviewId

The ID of the existing execution preview.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Required: Yes

Response Syntax

```
{
   "EndedAt": number,
   "ExecutionPreview": { ... },
   "ExecutionPreviewId": "string",
   "Status": "string",
   "StatusMessage": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EndedAt

A UTC timestamp indicating when the execution preview operation ended.

Type: Timestamp

ExecutionPreview

Information about the changes that would be made if an execution were run.

Type: ExecutionPreview object

Note: This object is a Union. Only one member of this object can be specified or returned.

ExecutionPreviewId

The generated ID for the existing execution preview.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Status

The current status of the execution preview operation.

Type: String

Valid Values: `Pending | InProgress | Success | Failed`

StatusMessage

Supplemental information about the current status of the execution preview.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetExecutionPreview.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetExecutionPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20241125T162110Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 86

{
    "ExecutionPreviewId": "2f27d6e5-9676-4708-b8bd-aef0aEXAMPLE"
}
```

Example

This example illustrates one usage of GetExecutionPreview.

Sample Response

```
{
    "ExecutionPreviewId": "2f27d6e5-9676-4708-b8bd-aef0EXAMPLE",
    "EndedAt": "2024-11-25T01:50:39.424000+00:00",
    "Status": "Success",
    "ExecutionPreview": {
        "Automation": {
            "StepPreviews": {
                "Undetermined": 1
            },
            "Regions": [
                "us-east-2"
            ],
            "TotalAccounts": 7
        }
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetInventory

Query inventory information. This includes managed node status, such as `Stopped` or `Terminated`.

Request Syntax

```
{
   "Aggregators": [
      {
         "Aggregators": [
            "InventoryAggregator"
         ],
         "Expression": "string",
         "Groups": [
            {
               "Filters": [
                  {
                     "Key": "string",
                     "Type": "string",
                     "Values": [ "string" ]
                  }
               ],
               "Name": "string"
            }
         ]
      }
   ],
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ResultAttributes": [
      {
         "TypeName": "string"
      }
   ]
```

```
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Aggregators

Returns counts of inventory types based on one or more expressions. For example, if you aggregate by using an expression that uses the `AWS:InstanceInformation.PlatformType` type, you can see a count of how many Windows and Linux managed nodes exist in your inventoried fleet.

Type: Array of InventoryAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

Filters

One or more filters. Use a filter to return a more specific list of results.

Type: Array of InventoryFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ResultAttributes

The list of inventory item types to return.

Type: Array of ResultAttribute objects

Array Members: Fixed number of 1 item.

Required: No

Response Syntax

```
{
   "Entities": [
      {
         "Data": {
            "string" : {
               "CaptureTime": "string",
               "Content": [
                  {
                     "string" : "string"
                  }
               ],
               "ContentHash": "string",
               "SchemaVersion": "string",
               "TypeName": "string"
            }
         },
         "Id": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entities

Collection of inventory entities such as a collection of managed node inventory.

Type: Array of InventoryResultEntity objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAggregatorException

The specified aggregator isn't valid for the group type. Verify that the aggregator you provided is supported.

HTTP Status Code: 400

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidInventoryGroupException

The specified inventory group isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidResultAttributeException

The specified inventory item result attribute isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetInventory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetInventory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T145054Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Entities": [
        {
            "Data": {
                "Id": "i-04bf6ad63bEXAMPLE",
                "AWS:InstanceInformation": {
                    "TypeName": "AWS:InstanceInformation",
```

```
                    "SchemaVersion": "1.0",
                    "CaptureTime": "2024-03-30T14:00:57Z",
                    "Content": [
                        {
                            "AgentType": "amazon-ssm-agent",
                            "AgentVersion": "2.3.930.0",
                            "ComputerName": "EC2AMAZ-EXAMPLE.WORKGROUP",
                            "InstanceId": "i-04bf6ad63bEXAMPLE",
                            "InstanceStatus": "Stopped",
                            "IpAddress": "172.16.0.4",
                            "PlatformName": "Microsoft Windows Server 2016 Datacenter",
                            "PlatformType": "Windows",
                            "PlatformVersion": "10.0.14393",
                            "ResourceType": "EC2Instance"
                        }
                    ]
                }
            }
        }
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetInventorySchema

Return a list of inventory type names for the account, or return a list of attribute names for a specific Inventory item type.

Request Syntax

```
{
   "Aggregator": boolean,
   "MaxResults": number,
   "NextToken": "string",
   "SubType": boolean,
   "TypeName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Aggregator

Returns inventory schemas that support aggregation. For example, this call returns the `AWS:InstanceInformation` type, because it supports aggregation based on the `PlatformName`, `PlatformType`, and `PlatformVersion` attributes.

Type: Boolean

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 200.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

SubType

Returns the sub-type schema for a specified inventory type.

Type: Boolean

Required: No

TypeName

The type of inventory item to return.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Schemas": [
      {
         "Attributes": [
            {
               "DataType": "string",
               "Name": "string"
            }
         ],
         "DisplayName": "string",
         "TypeName": "string",
         "Version": "string"
      }
   ]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Schemas

Inventory schemas returned by the request.

Type: Array of InventoryItemSchema objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetInventorySchema.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetInventorySchema
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T150040Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
   "Schemas":[
      {
         "Attributes":[
            {
               "DataType":"STRING",
               "Name":"Name"
            },
            {
               "DataType":"STRING",
               "Name":"ApplicationType"
            },
            {
               "DataType":"STRING",
               "Name":"Publisher"
            },
            {
               "DataType":"STRING",
               "Name":"Version"
            },
            {
```

```
            "DataType":"STRING",
            "Name":"InstalledTime"
         },
         {
            "DataType":"STRING",
            "Name":"Architecture"
         },
         {
            "DataType":"STRING",
            "Name":"URL"
         }
      ],
      "TypeName":"AWS:AWSComponent",
      "Version":"1.0"
   },--truncated--
   {
      "Attributes":[
         {
            "DataType":"STRING",
            "Name":"Name"
         },
         {
            "DataType":"STRING",
            "Name":"DisplayName"
         },
         {
            "DataType":"STRING",
            "Name":"ServiceType"
         },
         {
            "DataType":"STRING",
            "Name":"Status"
         },
         {
            "DataType":"STRING",
            "Name":"DependentServices"
         },
         {
            "DataType":"STRING",
            "Name":"ServicesDependedOn"
         },
         {
            "DataType":"STRING",
            "Name":"StartType"
```

```
            }
         ],
         "TypeName":"AWS:Service",
         "Version":"1.0"
      }--truncated--
   ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMaintenanceWindow

Retrieves a maintenance window.

Request Syntax

```
{
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowId

The ID of the maintenance window for which you want to retrieve information.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "AllowUnassociatedTargets": boolean,
   "CreatedDate": number,
   "Cutoff": number,
   "Description": "string",
   "Duration": number,
   "Enabled": boolean,
   "EndDate": "string",
   "ModifiedDate": number,
   "Name": "string",
   "NextExecutionTime": "string",
```

```
    "Schedule": "string",
    "ScheduleOffset": number,
    "ScheduleTimezone": "string",
    "StartDate": "string",
    "WindowId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AllowUnassociatedTargets

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

CreatedDate

The date the maintenance window was created.

Type: Timestamp

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Description

The description of the maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Enabled

Indicates whether the maintenance window is enabled.

Type: Boolean

EndDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive. The maintenance window won't run after this specified time.

Type: String

ModifiedDate

The date the maintenance window was last modified.

Type: Timestamp

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

NextExecutionTime

The next time the maintenance window will actually run, taking into account any specified times for the maintenance window to become active or inactive.

Type: String

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ScheduleOffset

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the Time Zone Database on the IANA website.

Type: String

StartDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active. The maintenance window won't run before this specified time.

Type: String

WindowId

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.GetMaintenanceWindow
X-Amz-Date: 20240312T203140Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "AllowUnassociatedTargets": true,
    "CreatedDate": 1515006912.957,
    "Cutoff": 1,
    "Duration": 6,
```

```
    "Enabled": true,
    "ModifiedDate": "2024-01-01T10:04:04.099Z",
    "Name": "My-Maintenance-Window",
    "Schedule": "rate(3 days)",
    "WindowId": "mw-0c50858d01EXAMPLE",
    "NextExecutionTime": "2024-02-25T00:08:15.099Z"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMaintenanceWindowExecution

Retrieves details about a specific a maintenance window execution.

Request Syntax

```
{
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowExecutionId

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "EndTime": number,
   "StartTime": number,
   "Status": "string",
   "StatusDetails": "string",
   "TaskIds": [ "string" ],
   "WindowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EndTime

The time the maintenance window finished running.

Type: Timestamp

StartTime

The time the maintenance window started running.

Type: Timestamp

Status

The status of the maintenance window execution.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

StatusDetails

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

TaskIds

The ID of the task executions from the maintenance window execution.

Type: Array of strings

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

WindowExecutionId

The ID of the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 61
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecution
X-Amz-Date: 20240312T205830Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE",
    "TaskIds": [
        "4b9f371e-a820-422d-b432-8dec9EXAMPLE"
    ],
    "Status": "SUCCESS",
    "StartTime": "2024-08-04T11:45:34.994000-07:00",
    "EndTime": "2024-08-04T11:48:09.123000-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

GetMaintenanceWindowExecutionTask

Retrieves the details about a specific task run as part of a maintenance window execution.

Request Syntax

```
{
   "TaskId": "string",
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

TaskId

The ID of the specific task execution in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

WindowExecutionId

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "EndTime": number,
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Priority": number,
   "ServiceRole": "string",
   "StartTime": number,
   "Status": "string",
   "StatusDetails": "string",
   "TaskArn": "string",
   "TaskExecutionId": "string",
   "TaskParameters": [
      {
         "string" : {
            "Values": [ "string" ]
         }
      }
   ],
   "TriggeredAlarms": [
      {
         "Name": "string",
         "State": "string"
      }
   ],
   "Type": "string",
   "WindowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AlarmConfiguration

The details for the CloudWatch alarm you applied to your maintenance window task.

Type: AlarmConfiguration object

EndTime

The time the task execution completed.

Type: Timestamp

MaxConcurrency

The defined maximum number of task executions that could be run in parallel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

MaxErrors

The defined maximum number of task execution errors allowed before scheduling of the task execution would have been stopped.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Priority

The priority of the task.

Type: Integer

Valid Range: Minimum value of 0.

ServiceRole

The role that was assumed when running the task.

Type: String

StartTime

The time the task execution started.

Type: Timestamp

Status

The status of the task.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

StatusDetails

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

TaskArn

The Amazon Resource Name (ARN) of the task that ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

TaskExecutionId

The ID of the specific task execution in the maintenance window task that was retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

TaskParameters

The parameters passed to the task when it was run.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the

`TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

The map has the following format:

- `Key`: string, between 1 and 255 characters
- `Value`: an array of strings, each between 1 and 255 characters

Type: Array of string to MaintenanceWindowTaskParameterValueExpression object maps

Key Length Constraints: Minimum length of 1. Maximum length of 255.

TriggeredAlarms

The CloudWatch alarms that were invoked by the maintenance window task.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Type

The type of task that was run.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

WindowExecutionId

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecutionTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecutionTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T001515Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 111

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef436EXAMPLE",
    "TaskId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE"
}
```

Sample Response


```
{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef436EXAMPLE",
    "TaskExecutionId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE",
    "TaskArn": "AWS-RunPatchBaseline",
    "ServiceRole": "arn:aws:iam::111122223333:role/aws-service-role/ssm.amazonaws.com/
AWSServiceRoleForAmazonSSM",
    "Type": "RUN_COMMAND",
    "TaskParameters": [
        {
            "BaselineOverride": {
                "Values": [
                    ""
                ]
            },
            "InstallOverrideList": {
                "Values": [
                    ""
                ]
            },
            "Operation": {
                "Values": [
                    "Scan"
                ]
            },
            "RebootOption": {
                "Values": [
                    "RebootIfNeeded"
                ]
            },
            "SnapshotId": {
                "Values": [
                    "{{ aws:ORCHESTRATION_ID }}"
                ]
            },
            "aws:InstanceId": {
                "Values": [
                    "i-02573cafcfEXAMPLE",
                    "i-0471e04240EXAMPLE",
                    "i-07782c72faEXAMPLE"
                ]
            }
        }
```

```
    ],
    "Priority": 1,
    "MaxConcurrency": "1",
    "MaxErrors": "3",
    "Status": "SUCCESS",
    "StartTime": "2024-08-04T11:45:35.088000-07:00",
    "EndTime": "2024-08-04T11:48:09.079000-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMaintenanceWindowExecutionTaskInvocation

Retrieves information about a specific task running on a specific target.

Request Syntax

```
{
   "InvocationId": "string",
   "TaskId": "string",
   "WindowExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InvocationId

The invocation ID to retrieve.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

TaskId

The ID of the specific task in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

WindowExecutionId

The ID of the maintenance window execution for which the task is a part.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "EndTime": number,
   "ExecutionId": "string",
   "InvocationId": "string",
   "OwnerInformation": "string",
   "Parameters": "string",
   "StartTime": number,
   "Status": "string",
   "StatusDetails": "string",
   "TaskExecutionId": "string",
   "TaskType": "string",
   "WindowExecutionId": "string",
   "WindowTargetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EndTime

The time that the task finished running on the target.

Type: Timestamp

ExecutionId

The execution ID.

Type: String

InvocationId

The invocation ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

OwnerInformation

User-provided value to be included in any Amazon CloudWatch Events or Amazon EventBridge events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Parameters

The parameters used at the time that the task ran.

Type: String

StartTime

The time that the task started running on the target.

Type: Timestamp

Status

The task status for an invocation.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

StatusDetails

The details explaining the status. Details are only available for certain status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

TaskExecutionId

The task execution ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

TaskType

Retrieves the task type for a maintenance window.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

WindowExecutionId

The maintenance window execution ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

WindowTargetId

The maintenance window target ID.

Type: String

Length Constraints: Maximum length of 36.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecutionTaskInvocation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecutionTaskInvocation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T001923Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 167

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
```

```
    "TaskId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE",
    "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
    "TaskExecutionId": "0c9ac961-dafd-4a94-b6c7-1bef3EXAMPLE",
    "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE",
    "ExecutionId": "1203cf98-5a79-4ec3-97e9-12e0bEXAMPLE",
    "TaskType": "RUN_COMMAND",
    "Parameters": "{\"comment\":\"\",\"documentName\":\"AWS-ApplyPatchBaseline\",
\"instanceIds\":[\"i-02573cafcfEXAMPLE\",\"i-0471e04240EXAMPLE\"],\"maxConcurrency
\":\"1\",\"maxErrors\":\"1\",\"parameters\":{\"SnapshotId\":[\"\"],\"Operation\":
[\"Install\"]},\"timeoutSeconds\":600}",
    "Status": "SUCCESS",
    "StatusDetails": "Success",
    "StartTime": "2024-08-04T11:45:35.141000-07:00",
    "EndTime": "2024-08-04T11:48:08.960000-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMaintenanceWindowTask

Retrieves the details of a maintenance window task.

> **Note**
>
> For maintenance window tasks without a specified target, you can't supply values for `--max-errors` and `--max-concurrency`. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. These values don't affect the running of your task and can be ignored.

To retrieve a list of tasks in a maintenance window, instead use the DescribeMaintenanceWindowTasks command.

Request Syntax

```
{
   "WindowId": "string",
   "WindowTaskId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

WindowId

The maintenance window ID that includes the task to retrieve.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

WindowTaskId

The maintenance window task ID to retrieve.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "CutoffBehavior": "string",
   "Description": "string",
   "LoggingInfo": {
      "S3BucketName": "string",
      "S3KeyPrefix": "string",
      "S3Region": "string"
   },
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "Priority": number,
   "ServiceRoleArn": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TaskArn": "string",
```

```
   "TaskInvocationParameters": {
      "Automation": {
         "DocumentVersion": "string",
         "Parameters": {
            "string" : [ "string" ]
         }
      },
      "Lambda": {
         "ClientContext": "string",
         "Payload": blob,
         "Qualifier": "string"
      },
      "RunCommand": {
         "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
         },
         "Comment": "string",
         "DocumentHash": "string",
         "DocumentHashType": "string",
         "DocumentVersion": "string",
         "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
         },
         "OutputS3BucketName": "string",
         "OutputS3KeyPrefix": "string",
         "Parameters": {
            "string" : [ "string" ]
         },
         "ServiceRoleArn": "string",
         "TimeoutSeconds": number
      },
      "StepFunctions": {
         "Input": "string",
         "Name": "string"
      }
   },
   "TaskParameters": {
      "string" : {
         "Values": [ "string" ]
      }
   },
```

```
    "TaskType": "string",
    "WindowId": "string",
    "WindowTaskId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AlarmConfiguration

The details for the CloudWatch alarm you applied to your maintenance window task.

Type: AlarmConfiguration object

CutoffBehavior

The action to take on tasks when the maintenance window cutoff time is reached. `CONTINUE_TASK` means that tasks continue to run. For Automation, AWS Lambda, AWS Step Functions tasks, `CANCEL_TASK` means that currently running task invocations continue, but no new task invocations are started. For Run Command tasks, `CANCEL_TASK` means the system attempts to stop the task by sending a `CancelCommand` operation.

Type: String

Valid Values: `CONTINUE_TASK | CANCEL_TASK`

Description

The retrieved task description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

LoggingInfo

The location in Amazon Simple Storage Service (Amazon S3) where the task results are logged.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and

`OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: LoggingInfo object

MaxConcurrency

The maximum number of targets allowed to run this task in parallel.

> **Note**
>
> For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. This value doesn't affect the running of your task and can be ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

MaxErrors

The maximum number of errors allowed before the task stops being scheduled.

> **Note**
>
> For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. This value doesn't affect the running of your task and can be ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Name

The retrieved task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Priority

The priority of the task when it runs. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Targets

The targets where the task should run.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

TaskArn

The resource that the task used during execution. For `RUN_COMMAND` and `AUTOMATION` task types, the value of `TaskArn` is the SSM document name/ARN. For `LAMBDA` tasks, the value is the function name/ARN. For `STEP_FUNCTIONS` tasks, the value is the state machine ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

TaskInvocationParameters

The parameters to pass to the task when it runs.

Type: MaintenanceWindowTaskInvocationParameters object

TaskParameters

The parameters to pass to the task when it runs.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: String to MaintenanceWindowTaskParameterValueExpression object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

TaskType

The type of task to run.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

WindowId

The retrieved maintenance window ID.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

WindowTaskId

The retrieved maintenance window task ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T002532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 92

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE",
    "Name": "MyRunCommandTask",
    "Targets": [
        {
            "Key": "WindowTargetIds",
            "Values": [
                "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-ApplyPatchBaseline",
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/AWSServiceRoleForAmazonSSM",
    "TaskType": "RUN_COMMAND",
    "TaskParameters": {},
    "Priority": 1,
    "TaskInvocationParameters": {
        "RunCommand": {
            "Comment": "",
            "Parameters": {
```

```
                "Operation": [
                    "Install"
                ],
                "SnapshotId": [
                    ""
                ]
            },
            "TimeoutSeconds": 600
        }
    },
    "MaxConcurrency": "1",
    "MaxErrors": "1"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetOpsItem

Get information about an OpsItem by using the ID. You must have permission in AWS Identity and Access Management (IAM) to view information about an OpsItem. For more information, see Set up OpsCenter in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see AWS Systems Manager OpsCenter in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "OpsItemArn": "string",
   "OpsItemId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

OpsItemArn

The OpsItem Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[0-9]{12}:opsitem.*`

Required: No

OpsItemId

The ID of the OpsItem that you want to get.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

Response Syntax

```
{
   "OpsItem": {
      "ActualEndTime": number,
      "ActualStartTime": number,
      "Category": "string",
      "CreatedBy": "string",
      "CreatedTime": number,
      "Description": "string",
      "LastModifiedBy": "string",
      "LastModifiedTime": number,
      "Notifications": [
         {
            "Arn": "string"
         }
      ],
      "OperationalData": {
         "string" : {
            "Type": "string",
            "Value": "string"
         }
      },
      "OpsItemArn": "string",
      "OpsItemId": "string",
      "OpsItemType": "string",
      "PlannedEndTime": number,
      "PlannedStartTime": number,
      "Priority": number,
      "RelatedOpsItems": [
         {
            "OpsItemId": "string"
         }
      ],
      "Severity": "string",
      "Source": "string",
      "Status": "string",
      "Title": "string",
      "Version": "string"
```

```
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsItem

The OpsItem.

Type: OpsItem object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemAccessDeniedException

You don't have permission to view OpsItems in the specified account. Verify that your account is configured either as a Systems Manager delegated administrator or that you are logged into the AWS Organizations management account.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetOpsItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T153712Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 32

{
    "OpsItemId": "oi-f99f2EXAMPLE"
}
```

Sample Response

```
{
    "OpsItem": {
        "Category": "Availability",
        "CreatedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
        "CreatedTime": 1582701517.193,
        "Description": "CloudWatch Event Rule SSMOpsItems-SSM-maintenance-window-
execution-failed was triggered. Your SSM Maintenance Window execution has failed. See
 below for more details.",
        "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
        "LastModifiedTime": 1582701517.193,
        "Notifications": [],
        "OperationalData": {
            "/aws/dedup": {
                "Type": "SearchableString",
```

```
                "Value": "{\"dedupString\":\"SSMOpsItems-SSM-maintenance-window-
execution-failed\"}"
            },
            "/aws/resources": {
                "Type": "SearchableString",
                "Value": "[{\"arn\":\"arn:aws:ssm:us-
east-2:111122223333:maintenancewindow/mw-0e357ebdc6EXAMPLE\"}]"
            },
            "window-execution-id": {
                "Type": "String",
                "Value": "e79e904b-0e42-43b8-a83d-b2aedEXAMPLE"
            },
            "window-id": {
                "Type": "String",
                "Value": "mw-0e357ebdc6EXAMPLE"
            }
        },
        "OpsItemId": "oi-f99f2EXAMPLE",
        "RelatedOpsItems": [],
        "Severity": "3",
        "Source": "SSM",
        "Status": "Open",
        "Title": "SSM Maintenance Window execution failed"
    }
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

GetOpsMetadata

View operational metadata related to an application in Application Manager.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "OpsMetadataArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

OpsMetadataArn

The Amazon Resource Name (ARN) of an OpsMetadata Object to view.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Required: Yes

Response Syntax

```
{
   "Metadata": {
      "string" : {
         "Value": "string"
      }
   },
   "NextToken": "string",
   "ResourceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Metadata

OpsMetadata for an Application Manager application.

Type: String to MetadataValue object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `^(?!\s*$).+`

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

ResourceId

The resource ID of the Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetOpsSummary

View a summary of operations metadata (OpsData) based on specified filters and aggregators. OpsData can include information about AWS Systems Manager OpsCenter operational workitems (OpsItems) as well as information about any AWS resource or service configured to report OpsData to AWS Systems Manager Explorer.

Request Syntax

```
{
   "Aggregators": [
      {
         "Aggregators": [
            "OpsAggregator"
         ],
         "AggregatorType": "string",
         "AttributeName": "string",
         "Filters": [
            {
               "Key": "string",
               "Type": "string",
               "Values": [ "string" ]
            }
         ],
         "TypeName": "string",
         "Values": {
            "string" : "string"
         }
      }
   ],
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ResultAttributes": [
      {
         "TypeName": "string"
```

```
      }
   ],
   "SyncName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Aggregators

Optional aggregators that return counts of OpsData based on one or more expressions.

Type: Array of OpsAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 12 items.

Required: No

Filters

Optional filters used to scope down the returned OpsData.

Type: Array of OpsFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ResultAttributes

The OpsData data type to return.

Type: Array of OpsResultAttribute objects

Array Members: Minimum number of 1 item.

Required: No

SyncName

Specify the name of a resource data sync to get.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{
   "Entities": [
      {
         "Data": {
            "string" : {
               "CaptureTime": "string",
               "Content": [
                  {
                     "string" : "string"
                  }
               ]
            }
         },
         "Id": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entities

The list of aggregated details and filtered OpsData.

Type: Array of OpsEntity objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAggregatorException

The specified aggregator isn't valid for the group type. Verify that the aggregator you provided is supported.

HTTP Status Code: 400

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetOpsSummary.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetOpsSummary
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T152044Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Entities": [
        {
            "Data": {
                "AWS:OpsItem": {
                    "CaptureTime": "2024-02-26T05:59:57.430Z",
                    "Content": [
```

```
                        {
                            "AccountId": "111122223333",
                            "Category": "Availability",
                            "CreatedBy": "arn:aws:sts::111122223333:assumed-role/
OpsCenterRole/af3935bb93783f02aeea51784EXAMPLE",
                            "CreatedTime": "2024-02-26T07:18:37.193Z",
                            "Description": "CloudWatch Event Rule SSMOpsItems-SSM-
maintenance-window-execution-failed was triggered. Your SSM Maintenance Window
 execution has failed. See below for more details.",
                            "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/
OpsCenterRole/af3935bb93783f02aeea51784EXAMPLE",
                            "LastModifiedTime": "2024-02-26T07:18:37.193Z",
                            "Notifications": "",
                            "OperationalData": "{\"/aws/resources\":{\"type
\":\"SearchableString\",\"value\":\"[{\\\"arn\\\":\\\"arn:aws:ssm:us-
east-2:111122223333:maintenancewindow/mw-0e357ebdc6EXAMPLE\\\"}]\"},\"/aws/dedup\":
{\"type\":\"SearchableString\",\"value\":\"{\\\"dedupString\\\":\\\"SSMOpsItems-SSM-
maintenance-window-execution-failed\\\"}\"}}",
                            "OpsItemId": "oi-f99f2EXAMPLE",
                            "RelatedItems": "",
                            "Severity": "3",
                            "Source": "SSM",
                            "Status": "Open",
                            "Title": "SSM Maintenance Window execution failed"
                        }
                    ]
                }
            },
            "Id": "oi-f99f2EXAMPLE"
        },---truncated---
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetParameter

Get information about a single parameter by specifying the parameter name.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

> **Note**
>
> To get information about more than one parameter at a time, use the GetParameters operation.

Request Syntax

```
{
   "Name": "string",
   "WithDecryption": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name or Amazon Resource Name (ARN) of the parameter that you want to query. For parameters shared with you from another account, you must use the full ARN.

To query by parameter label, use `"Name": "name:label"`. To query by parameter version, use `"Name": "name:version"`.

For more information about shared parameters, see Working with shared parameters in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

WithDecryption

Return decrypted values for secure string parameters. This flag is ignored for `String` and `StringList` parameter types.

Type: Boolean

Required: No

Response Syntax

```
{
   "Parameter": {
      "ARN": "string",
      "DataType": "string",
      "LastModifiedDate": number,
      "Name": "string",
      "Selector": "string",
      "SourceResult": "string",
      "Type": "string",
      "Value": "string",
      "Version": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Parameter

Information about a parameter.

Type: Parameter object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

> **Note**
>
> For the `DeleteParameter` and `GetParameter` actions, if the specified parameter doesn't exist, the `ParameterNotFound` exception is *not* recorded in AWS CloudTrail event logs.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 29
X-Amz-Target: AmazonSSM.GetParameter
X-Amz-Date: 20240316T005724Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "MyGitHubPassword"
}
```

Sample Response

```
{
    "Parameter": {
        "ARN": "arn:aws:ssm:us-east-2:111122223333:parameter/MyGitHubPassword",
        "DataType": "text",
        "LastModifiedDate": 1582657288.8,
        "Name": "MyGitHubPassword",
        "Type": "SecureString",
        "Value": "AYA39c3b3042cd2aEXAMPLE/AKIAIOSFODNN7EXAMPLE/fh983hg9awEXAMPLE==",
        "Version": 3
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetParameterHistory

Retrieves the history of all changes to a parameter.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

> **Important**
>
> If you change the AWS KMS key alias for the KMS key used to encrypt a parameter, then you must also update the key alias the parameter uses to reference KMS. Otherwise, `GetParameterHistory` retrieves whatever the original key alias was referencing.

Request Syntax

```
{
   "MaxResults": number,
   "Name": "string",
   "NextToken": "string",
   "WithDecryption": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Name

The name or Amazon Resource Name (ARN) of the parameter for which you want to review history. For parameters shared with you from another account, you must use the full ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WithDecryption

Return decrypted values for secure string parameters. This flag is ignored for `String` and `StringList` parameter types.

Type: Boolean

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Parameters": [
      {
         "AllowedPattern": "string",
         "DataType": "string",
         "Description": "string",
         "KeyId": "string",
         "Labels": [ "string" ],
         "LastModifiedDate": number,
         "LastModifiedUser": "string",
         "Name": "string",
         "Policies": [
            {
               "PolicyStatus": "string",
```

```
                "PolicyText": "string",
                "PolicyType": "string"
            }
         ],
         "Tier": "string",
         "Type": "string",
         "Value": "string",
         "Version": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Parameters

A list of parameters returned by the request.

Type: Array of ParameterHistory objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

> **Note**
>
> For the `DeleteParameter` and `GetParameter` actions, if the specified parameter doesn't exist, the `ParameterNotFound` exception is *not* recorded in AWS CloudTrail event logs.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameterHistory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 29
X-Amz-Target: AmazonSSM.GetParameterHistory
X-Amz-Date: 20240316T005206Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "EC2TestServerType"
```

```
}
```

Sample Response

```
{
    "Parameters": [
        {
            "Description": "Instance type for Test servers",
            "LastModifiedDate": 1521158745.607,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "EC2TestServerType",
            "Policies": [],
            "Type": "String",
            "Value": "t2.nano",
            "Version": 1
        },
        {
            "Description": "Instance type for Test servers",
            "LastModifiedDate": 1521158834.467,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "EC2TestServerType",
            "Policies": [],
            "Type": "String",
            "Value": "t2.micro",
            "Version": 2
        },
        {
            "Description": "Instance type for Test servers",
            "LastModifiedDate": 1521158912.828,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Jane.Roe",
            "Name": "EC2TestServerType",
            "Policies": [],
            "Type": "String",
            "Value": "t2.large",
            "Version": 3
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetParameters

Get information about one or more parameters by specifying multiple parameter names.

> **Note**
>
> To get information about a single parameter, you can use the GetParameter operation instead.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

Request Syntax

```
{
   "Names": [ "string" ],
   "WithDecryption": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Names

The names or Amazon Resource Names (ARNs) of the parameters that you want to query. For parameters shared with you from another account, you must use the full ARNs.

To query by parameter label, use `"Name": "name:label"`. To query by parameter version, use `"Name": "name:version"`.

> **Note**
>
> The results for `GetParameters` requests are listed in alphabetical order in query responses.

For information about shared parameters, see Working with shared parameters in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

WithDecryption

Return decrypted secure string value. Return decrypted values for secure string parameters. This flag is ignored for `String` and `StringList` parameter types.

Type: Boolean

Required: No

Response Syntax

```
{
   "InvalidParameters": [ "string" ],
   "Parameters": [
      {
         "ARN": "string",
         "DataType": "string",
         "LastModifiedDate": number,
         "Name": "string",
         "Selector": "string",
         "SourceResult": "string",
         "Type": "string",
         "Value": "string",
         "Version": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidParameters

A list of parameters that aren't formatted correctly or don't run during an execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Parameters

A list of details for a parameter.

Type: Array of Parameter objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameters.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 73
X-Amz-Target: AmazonSSM.GetParameters
X-Amz-Date: 20240316T001029Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Names": [
        "EC2DevServerTypo",
        "EC2DevServerType",
        "EC2TestServerType",
        "EC2ProdServerType"
    ]
}
```

Sample Response

```
{
    "InvalidParameters": [
        "EC2DevServerTypo"
    ],
    "Parameters": [
        {
            "Name": "EC2DevServerType",
            "Type": "String",
            "Value": "t2.micro",
            "Version": 2
        },
        {
            "Name": "EC2ProdServerType",
            "Type": "String",
            "Value": "m4.large",
            "Version": 1
        },
        {
            "Name": "EC2TestServerType",
            "Type": "String",
            "Value": "t2.large",
```

```
            "Version": 3
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetParametersByPath

Retrieve information about one or more parameters under a specified level in a hierarchy.

Request results are returned on a best-effort basis. If you specify `MaxResults` in the request, the response includes information up to the limit specified. The number of items returned, however, can be between zero and the value of `MaxResults`. If the service reaches an internal limit while processing the results, it stops the operation and returns the matching values up to that point and a `NextToken`. You can specify the `NextToken` in a subsequent call to get the next set of results.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "ParameterFilters": [
      {
         "Key": "string",
         "Option": "string",
         "Values": [ "string" ]
      }
   ],
   "Path": "string",
   "Recursive": boolean,
   "WithDecryption": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ParameterFilters

Filters to limit the request results.

> **Note**
>
> The following `Key` values are supported for `GetParametersByPath`: `Type`, `KeyId`, and `Label`.
> The following `Key` values aren't supported for `GetParametersByPath`: `tag`, `DataType`, `Name`, `Path`, and `Tier`.

Type: Array of ParameterStringFilter objects

Required: No

Path

The hierarchy for the parameter. Hierarchies start with a forward slash (/). The hierarchy is the parameter name except the last part of the parameter. For the API call to succeed, the last part of the parameter name can't be in the path. A parameter name hierarchy can have a maximum of 15 levels. Here is an example of a hierarchy: `/Finance/Prod/IAD/WinServ2016/license33`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Recursive

Retrieve all parameters within a hierarchy.

> **Important**
>
> If a user has access to a path, then the user can access all levels of that path. For example, if a user has permission to access path /a, then the user can also access /a/b. Even if a user has explicitly been denied access in IAM for parameter /a/b, they can still call the GetParametersByPath API operation recursively for /a and view /a/b.

Type: Boolean

Required: No

WithDecryption

Retrieve all parameters in a hierarchy with their value decrypted.

Type: Boolean

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Parameters": [
      {
         "ARN": "string",
         "DataType": "string",
         "LastModifiedDate": number,
         "Name": "string",
         "Selector": "string",
         "SourceResult": "string",
         "Type": "string",
         "Value": "string",
         "Version": number
      }
   ]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Parameters

A list of parameters found in the specified hierarchy.

Type: Array of Parameter objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterOption

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

message

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParametersByPath.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 46
X-Amz-Target: AmazonSSM.GetParametersByPath
X-Amz-Date: 20240316T004724Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Path": "/Branch312/Dev/",
    "Recursive": true
}
```

Sample Response

```
{
    "Parameters": [
        {
            "Name": "/Branch312/Dev/Engineer1",
            "Type": "String",
            "Value": "Saanvi Sarkar",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Engineer2",
            "Type": "String",
            "Value": "Zhang Wei",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Engineer3",
            "Type": "String",
            "Value": "Alejandro Rosalez",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Intern",
            "Type": "String",
            "Value": "Nikhil Jayashankar",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/TeamLead",
            "Type": "String",
            "Value": "Jane Roe",
            "Version": 1
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetPatchBaseline

Retrieves information about a patch baseline.

Request Syntax

```
{
   "BaselineId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline to retrieve.

> **Note**
>
> To retrieve information about an AWS managed patch baseline, specify the full Amazon Resource Name (ARN) of the baseline. For example, for the baseline `AWS-AmazonLinuxDefaultPatchBaseline`, specify `arn:aws:ssm:us-east-2:733109147000:patchbaseline/pb-0e392de35e7c563b7` instead of `pb-0e392de35e7c563b7`.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

Response Syntax

```
{
```

```
   "ApprovalRules": {
      "PatchRules": [
         {
            "ApproveAfterDays": number,
            "ApproveUntilDate": "string",
            "ComplianceLevel": "string",
            "EnableNonSecurity": boolean,
            "PatchFilterGroup": {
               "PatchFilters": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ]
            }
         }
      ]
   },
   "ApprovedPatches": [ "string" ],
   "ApprovedPatchesComplianceLevel": "string",
   "ApprovedPatchesEnableNonSecurity": boolean,
   "AvailableSecurityUpdatesComplianceStatus": "string",
   "BaselineId": "string",
   "CreatedDate": number,
   "Description": "string",
   "GlobalFilters": {
      "PatchFilters": [
         {
            "Key": "string",
            "Values": [ "string" ]
         }
      ]
   },
   "ModifiedDate": number,
   "Name": "string",
   "OperatingSystem": "string",
   "PatchGroups": [ "string" ],
   "RejectedPatches": [ "string" ],
   "RejectedPatchesAction": "string",
   "Sources": [
      {
         "Configuration": "string",
         "Name": "string",
         "Products": [ "string" ]
```

```
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApprovalRules

A set of rules used to include patches in the baseline.

Type: PatchRuleGroup object

ApprovedPatches

A list of explicitly approved patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

ApprovedPatchesComplianceLevel

Returns the specified compliance severity level for approved patches in the patch baseline.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

AvailableSecurityUpdatesComplianceStatus

Indicates the compliance status of managed nodes for which security-related patches are available but were not approved. This preference is specified when the `CreatePatchBaseline` or `UpdatePatchBaseline` commands are run.

Applies to Windows Server managed nodes only.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

BaselineId

The ID of the retrieved patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

CreatedDate

The date the patch baseline was created.

Type: Timestamp

Description

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

GlobalFilters

A set of global filters used to exclude patches from the baseline.

Type: PatchFilterGroup object

ModifiedDate

The date the patch baseline was last modified.

Type: Timestamp

Name

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

OperatingSystem

Returns the operating system specified for the patch baseline.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

PatchGroups

Patch groups included in the patch baseline.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

RejectedPatches

A list of explicitly rejected patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

RejectedPatchesAction

The action specified to take on patches included in the `RejectedPatches` list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY | BLOCK`

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of PatchSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetPatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.GetPatchBaseline
X-Amz-Date: 20240309T020232Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "ApprovalRules": {
        "PatchRules": [
            {
                "ApproveAfterDays": 1,
                "ComplianceLevel": "UNSPECIFIED",
                "EnableNonSecurity": false,
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Key": "PRODUCT",
                            "Values": [
                                "WindowsServer2012R2"
                            ]
                        },
                        {
                            "Key": "CLASSIFICATION",
                            "Values": [
                                "SecurityUpdates"
                            ]
                        },
                        {
                            "Key": "MSRC_SEVERITY",
```

```
                            "Values": [
                                "Important",
                                "Critical",
                                "Moderate"
                            ]
                        }
                    ]
                }
            }
        ]
    },
    "ApprovedPatches": [],
    "ApprovedPatchesComplianceLevel": "HIGH",
    "ApprovedPatchesEnableNonSecurity": false,
    "BaselineId": "pb-0c10e65780EXAMPLE",
    "Description": "My Moderate, Important, and Critical security updates for Windows
 Server 2012 R2",
    "GlobalFilters": {
        "PatchFilters": []
    },
    "CreatedDate": 1520561435.87,
    "ModifiedDate": 1520561435.869,
    "Name": "my-Windows-Server-2012R2",
    "OperatingSystem": "WINDOWS",
    "PatchGroups": [
        "mypatchgroup"
    ],
    "RejectedPatches": [
        "KB3452678"
    ],
    "RejecteddPatchesAction": "ALLOW_AS_DEPENDENCY",
    "Sources": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetPatchBaselineForPatchGroup

Retrieves the patch baseline that should be used for the specified patch group.

Request Syntax

```
{
   "OperatingSystem": "string",
   "PatchGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

OperatingSystem

Returns the operating system rule specified for patch groups using the patch baseline.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: No

PatchGroup

The name of the patch group whose patch baseline should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
   "BaselineId": "string",
   "OperatingSystem": "string",
   "PatchGroup": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the patch baseline that should be used for the patch group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

OperatingSystem

The operating system rule specified for patch groups using the patch baseline.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

PatchGroup

The name of the patch group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 66
X-Amz-Target: AmazonSSM.GetPatchBaselineForPatchGroup
X-Amz-Date: 20240309T060906Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup",
    "OperatingSystem": "WINDOWS"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE",
    "OperatingSystem": "WINDOWS",
    "PatchGroup": "mypatchgroup"
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetResourcePolicies

Returns an array of the `Policy` object.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource to which the policies are attached.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Response Syntax

```
{
   "NextToken": "string",
   "Policies": [
      {
         "Policy": "string",
         "PolicyHash": "string",
         "PolicyId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Policies

An array of the `Policy` object.

Type: Array of GetResourcePoliciesResponseEntry objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

ResourcePolicyInvalidParameterException

One or more parameters specified for the call aren't valid. Verify the parameters and their values and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetServiceSetting

`ServiceSetting` is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of `false`. This means the user can't use this feature unless they change the setting to `true` and intentionally opt in for a paid feature.

Services map a `SettingId` object to a setting value. AWS services teams define the default value for a `SettingId`. You can't create a new `SettingId`, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the UpdateServiceSetting API operation to change the default setting. Or use the ResetServiceSetting to change the value back to the original value defined by the AWS service team.

Query the current service setting for the AWS account.

Request Syntax

```
{
   "SettingId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SettingId

The ID of the service setting to get. The setting ID can be one of the following.

- `/ssm/appmanager/appmanager-enabled`
- `/ssm/automation/customer-script-log-destination`
- `/ssm/automation/customer-script-log-group-name`
- /ssm/automation/enable-adaptive-concurrency
- `/ssm/documents/console/public-sharing-permission`
- `/ssm/managed-instance/activation-tier`

- `/ssm/managed-instance/default-ec2-instance-management-role`
- `/ssm/opsinsights/opscenter`
- `/ssm/parameter-store/default-parameter-tier`
- `/ssm/parameter-store/high-throughput-enabled`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Response Syntax

```
{
   "ServiceSetting": {
      "ARN": "string",
      "LastModifiedDate": number,
      "LastModifiedUser": "string",
      "SettingId": "string",
      "SettingValue": "string",
      "Status": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ServiceSetting

The query result of the current service setting.

Type: ServiceSetting object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240324T203339Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 54

{
    "SettingId": "/ssm/managed-instance/activation-tier"
}
```

Sample Response

```
{
    "ServiceSetting": {
        "ARN": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/managed-instance/
activation-tier",
```

```
        "LastModifiedDate": 1579136114.275,
        "LastModifiedUser": "System",
        "SettingId": "/ssm/managed-instance/activation-tier",
        "SettingValue": "standard",
        "Status": "Default"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

LabelParameterVersion

A parameter label is a user-defined alias to help you manage different versions of a parameter. When you modify a parameter, AWS Systems Manager automatically saves a new version and increments the version number by one. A label can help you remember the purpose of a parameter when there are multiple versions.

Parameter labels have the following requirements and restrictions.

- A version of a parameter can have a maximum of 10 labels.
- You can't attach the same label to different versions of the same parameter. For example, if version 1 has the label Production, then you can't attach Production to version 2.
- You can move a label from one version of a parameter to another.
- You can't create a label when you create a new parameter. You must attach a label to a specific version of a parameter.
- If you no longer want to use a parameter label, then you can either delete it or move it to a different version of a parameter.
- A label can have a maximum of 100 characters.
- Labels can contain letters (case sensitive), numbers, periods (.), hyphens (-), or underscores (_).
- Labels can't begin with a number, "`aws`" or "`ssm`" (not case sensitive). If a label fails to meet these requirements, then the label isn't associated with a parameter and the system displays it in the list of InvalidLabels.
- Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

Request Syntax

```
{
   "Labels": [ "string" ],
   "Name": "string",
   "ParameterVersion": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Labels

One or more labels to attach to the specified parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Name

The parameter name on which you want to attach one or more labels.

> **Note**
>
> You can't enter the Amazon Resource Name (ARN) for a parameter, only the parameter name itself.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

ParameterVersion

The specific version of the parameter on which you want to attach one or more labels. If no version is specified, the system attaches the label to the latest version.

Type: Long

Required: No

Response Syntax

```
{
   "InvalidLabels": [ "string" ],
   "ParameterVersion": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidLabels

The label doesn't meet the requirements. For information about parameter label requirements, see Working with parameter labels in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

ParameterVersion

The version of the parameter that has been labeled.

Type: Long

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

> **Note**
>
> For the `DeleteParameter` and `GetParameter` actions, if the specified parameter doesn't exist, the `ParameterNotFound` exception is *not* recorded in AWS CloudTrail event logs.

HTTP Status Code: 400

ParameterVersionLabelLimitExceeded

A parameter version can have a maximum of ten labels.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of LabelParameterVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.LabelParameterVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T191052Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240229/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 76

{
    "Name": "MyGitHubPassword",
    "ParameterVersion": 3,
    "Labels": [
        "March-2020"
    ]
}
```

Sample Response

```
{
    "InvalidLabels": [],
    "ParameterVersion": 3
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListAssociations

Returns all State Manager associations in the current AWS account and AWS Region. You can limit the results to a specific State Manager association document or managed node by specifying a filter. State Manager is a tool in AWS Systems Manager.

Request Syntax

```
{
   "AssociationFilterList": [
      {
         "key": "string",
         "value": "string"
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationFilterList

One or more filters. Use a filter to return a more specific list of results.

> **Note**
>
> Filtering associations using the `InstanceID` attribute only returns legacy associations created using the `InstanceID` attribute. Associations targeting the managed node that are part of the Target Attributes `ResourceGroup` or `Tags` aren't returned.

Type: Array of AssociationFilter objects

Array Members: Minimum number of 1 item.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "Associations": [
      {
         "AssociationId": "string",
         "AssociationName": "string",
         "AssociationVersion": "string",
         "DocumentVersion": "string",
         "Duration": number,
         "InstanceId": "string",
         "LastExecutionDate": number,
         "Name": "string",
         "Overview": {
            "AssociationStatusAggregatedCount": {
               "string" : number
            },
            "DetailedStatus": "string",
            "Status": "string"
         },
         "ScheduleExpression": "string",
         "ScheduleOffset": number,
         "TargetMaps": [
            {
```

```
                "string" : [ "string" ]
            }
         ],
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ]
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

The associations.

Type: Array of Association objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssociations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListAssociations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T143814Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Associations": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "LastExecutionDate": 1582037438.692,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "AssociationStatusAggregatedCount": {
                    "Success": 3
                },
                "DetailedStatus": "Success",
                "Status": "Success"
            },
```

```
            "Targets": [
                {
                    "Key": "tag:ssm",
                    "Values": [
                        "true"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListAssociationVersions

Retrieves all versions of an association for a specific association ID.

Request Syntax

```
{
   "AssociationId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationId

The association ID for which you want to view all versions.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "AssociationVersions": [
      {
         "ApplyOnlyAtCronInterval": boolean,
         "AssociationId": "string",
         "AssociationName": "string",
         "AssociationVersion": "string",
         "CalendarNames": [ "string" ],
         "ComplianceSeverity": "string",
         "CreatedDate": number,
         "DocumentVersion": "string",
         "Duration": number,
         "MaxConcurrency": "string",
         "MaxErrors": "string",
         "Name": "string",
         "OutputLocation": {
            "S3Location": {
               "OutputS3BucketName": "string",
               "OutputS3KeyPrefix": "string",
               "OutputS3Region": "string"
            }
         },
         "Parameters": {
            "string" : [ "string" ]
         },
         "ScheduleExpression": "string",
         "ScheduleOffset": number,
         "SyncCompliance": "string",
         "TargetLocations": [
            {
               "Accounts": [ "string" ],
               "ExcludeAccounts": [ "string" ],
               "ExecutionRoleName": "string",
               "IncludeChildOrganizationUnits": boolean,
               "Regions": [ "string" ],
               "TargetLocationAlarmConfiguration": {
                  "Alarms": [
```

```
                        {
                           "Name": "string"
                        }
                     ],
                     "IgnorePollAlarmFailure": boolean
                  },
                  "TargetLocationMaxConcurrency": "string",
                  "TargetLocationMaxErrors": "string",
                  "Targets": [
                     {
                        "Key": "string",
                        "Values": [ "string" ]
                     }
                  ],
                  "TargetsMaxConcurrency": "string",
                  "TargetsMaxErrors": "string"
               }
            ],
            "TargetMaps": [
               {
                  "string" : [ "string" ]
               }
            ],
            "Targets": [
               {
                  "Key": "string",
                  "Values": [ "string" ]
               }
            ]
         }
      ],
      "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationVersions

Information about all versions of the association for the specified association ID.

Type: Array of AssociationVersionInfo objects

Array Members: Minimum number of 1 item.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssociationVersions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListAssociationVersions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T144807Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationVersions": [
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "CreatedDate": 1561053271.583,
            "Name": "AWS-UpdateSSMAgent",
            "Parameters": {
                "allowDowngrade": [
                    "false"
                ],
                "version": [
                    ""
                ]
            },
            "Targets": [
                {
                    "Key": "tag:ssm",
                    "Values": [
                        "true"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCommandInvocations

An invocation is copy of a command sent to a specific managed node. A command can apply to one or more managed nodes. A command invocation applies to one managed node. For example, if a user runs SendCommand against three managed nodes, then a command invocation is created for each requested managed node ID. ListCommandInvocations provide status about command execution.

Request Syntax

```
{
   "CommandId": "string",
   "Details": boolean,
   "Filters": [
      {
         "key": "string",
         "value": "string"
      }
   ],
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

CommandId

(Optional) The invocations for a specific command ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

Details

(Optional) If set this returns the response of the command executions and any command output. The default value is `false`.

Type: Boolean

Required: No

Filters

(Optional) One or more filters. Use a filter to return a more specific list of results.

Type: Array of CommandFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

InstanceId

(Optional) The command execution details for a specific managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxResults

(Optional) The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "CommandInvocations": [
      {
         "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
         },
         "CommandId": "string",
         "CommandPlugins": [
            {
               "Name": "string",
               "Output": "string",
               "OutputS3BucketName": "string",
               "OutputS3KeyPrefix": "string",
               "OutputS3Region": "string",
               "ResponseCode": number,
               "ResponseFinishDateTime": number,
               "ResponseStartDateTime": number,
               "StandardErrorUrl": "string",
               "StandardOutputUrl": "string",
               "Status": "string",
               "StatusDetails": "string"
            }
         ],
         "Comment": "string",
         "DocumentName": "string",
         "DocumentVersion": "string",
         "InstanceId": "string",
         "InstanceName": "string",
         "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
         },
         "RequestedDateTime": number,
         "ServiceRole": "string",
         "StandardErrorUrl": "string",
```

```
            "StandardOutputUrl": "string",
            "Status": "string",
            "StatusDetails": "string",
            "TraceOutput": "string"
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CommandInvocations

(Optional) A list of all invocations.

Type: Array of CommandInvocation objects

NextToken

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListCommandInvocations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListCommandInvocations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T000322Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53
```

```
{
    "CommandId": "4171bb3b-fe26-48ea-94fe-d1727b4d58e5"
}
```

Sample Response

```
{
    "CommandInvocations": [
        {
            "CloudWatchOutputConfig": {
                "CloudWatchLogGroupName": "",
                "CloudWatchOutputEnabled": false
            },
            "CommandId": "4171bb3b-fe26-48ea-94fe-d1727EXAMPLE",
            "CommandPlugins": [],
            "Comment": "",
            "DocumentName": "AWS-FindWindowsUpdates",
            "DocumentVersion": "1",
            "InstanceId": "i-02573cafcfEXAMPLE",
            "InstanceName": "EXAMPLE-4J5FVEG.WORKGROUP",
            "NotificationConfig": {
                "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
                "NotificationEvents": [
                    "All"
                ],
                "NotificationType": "Invocation"
            },
            "RequestedDateTime": 1579893879.775,
            "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
            "StandardErrorUrl": "https://s3.us-east-2.amazonaws.com/amzn-s3-
demo-bucket/my-output/1231bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-02573cafcfEXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stderr",
            "StandardOutputUrl": "https://s3.us-east-2.amazonaws.com/amzn-s3-
demo-bucket/my-output/1231bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-02573cafcfEXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stdout",
            "Status": "Success",
            "StatusDetails": "Success"
        },
        {
            "CloudWatchOutputConfig": {
                "CloudWatchLogGroupName": "",
```

```
                "CloudWatchOutputEnabled": false
            },
            "CommandId": "4171bb3b-fe26-48ea-94fe-d1727EXAMPLE",
            "CommandPlugins": [],
            "Comment": "",
            "DocumentName": "AWS-FindWindowsUpdates",
            "DocumentVersion": "1",
            "InstanceId": "i-0471e04240EXAMPLE",
            "InstanceName": "EXAMPLE-A1PDOM8.WORKGROUP",
            "NotificationConfig": {
                "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
                "NotificationEvents": [
                    "All"
                ],
                "NotificationType": "Invocation"
            },
            "RequestedDateTime": 1579893879.6,
            "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
            "StandardErrorUrl": "https://s3.us-east-2.amazonaws.com/amzn-s3-
demo-bucket/my-output/4171bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-0471e04240EXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stderr",
            "StandardOutputUrl": "https://s3.us-east-2.amazonaws.com/amzn-s3-
demo-bucket/my-output/4171bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-0471e04240EXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stdout",
            "Status": "Success",
            "StatusDetails": "Success"
        }
    ]
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCommands

Lists the commands requested by users of the AWS account.

Request Syntax

```
{
   "CommandId": "string",
   "Filters": [
      {
         "key": "string",
         "value": "string"
      }
   ],
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

CommandId

(Optional) If provided, lists only the specified command.

Type: String

Length Constraints: Fixed length of 36.

Required: No

Filters

(Optional) One or more filters. Use a filter to return a more specific list of results.

Type: Array of CommandFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

InstanceId

(Optional) Lists commands issued against this managed node ID.

> **Note**
>
> You can't specify a managed node ID in the same command that you specify `Status = Pending`. This is because the command hasn't reached the managed node yet.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxResults

(Optional) The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "Commands": [
      {
         "AlarmConfiguration": {
            "Alarms": [
               {
```

```
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "CloudWatchOutputConfig": {
      "CloudWatchLogGroupName": "string",
      "CloudWatchOutputEnabled": boolean
   },
   "CommandId": "string",
   "Comment": "string",
   "CompletedCount": number,
   "DeliveryTimedOutCount": number,
   "DocumentName": "string",
   "DocumentVersion": "string",
   "ErrorCount": number,
   "ExpiresAfter": number,
   "InstanceIds": [ "string" ],
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "NotificationConfig": {
      "NotificationArn": "string",
      "NotificationEvents": [ "string" ],
      "NotificationType": "string"
   },
   "OutputS3BucketName": "string",
   "OutputS3KeyPrefix": "string",
   "OutputS3Region": "string",
   "Parameters": {
      "string" : [ "string" ]
   },
   "RequestedDateTime": number,
   "ServiceRole": "string",
   "Status": "string",
   "StatusDetails": "string",
   "TargetCount": number,
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TimeoutSeconds": number,
   "TriggeredAlarms": [
```

```
            {
               "Name": "string",
               "State": "string"
            }
         ]
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Commands

(Optional) The list of commands requested by the user.

Type: Array of Command objects

NextToken

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListCommands.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListCommands
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T002657Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53
```

```
{
    "CommandId": "088e4813-f292-48b3-8180-d8be9EXAMPLE"
}
```

Sample Response

```
{
    "Commands": [
        {
            "CloudWatchOutputConfig": {
                "CloudWatchLogGroupName": "my-log-group",
                "CloudWatchOutputEnabled": true
            },
            "CommandId": "088e4813-f292-48b3-8180-d8be9EXAMPLE",
            "Comment": "",
            "CompletedCount": 0,
            "DeliveryTimedOutCount": 0,
            "DocumentName": "AWS-InstallMissingWindowsUpdates",
            "DocumentVersion": "1",
            "ErrorCount": 0,
            "ExpiresAfter": 1582248743.188,
            "InstanceIds": [],
            "Interactive": false,
            "MaxConcurrency": "2",
            "MaxErrors": "3",
            "NotificationConfig": {
                "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
                "NotificationEvents": [
                    "All"
                ],
                "NotificationType": "Command"
            },
            "OutputS3BucketName": "amzn-s3-demo-bucket",
            "OutputS3KeyPrefix": "my-prefix",
            "Parameters": {
                "ExcludeKbArticleIds": [
                    ""
                ],
                "UpdateLevel": [
                    "All"
                ]
```

```
            },
            "RequestedDateTime": 1582244543.188,
            "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
            "Status": "InProgress",
            "StatusDetails": "InProgress",
            "TargetCount": 5,
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-09c350ed76EXAMPLE",
                        "i-07be1baa4aEXAMPLE",
                        "i-00ec29b21eEXAMPLE",
                        "i-09911ddd90EXAMPLE",
                        "i-017431b35cEXAMPLE"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListComplianceItems

For a specified resource ID, this API operation returns a list of compliance statuses for different resource types. Currently, you can only specify one resource ID per call. List results depend on the criteria specified in the filter.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "ResourceIds": [ "string" ],
   "ResourceTypes": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more compliance filters. Use a filter to return a more specific list of results.

Type: Array of ComplianceStringFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ResourceIds

The ID for the resources from which to get compliance information. Currently, you can only specify one resource ID.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceTypes

The type of resource from which to get compliance information. Currently, the only supported resource type is `ManagedInstance`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Response Syntax

```
{
   "ComplianceItems": [
      {
         "ComplianceType": "string",
         "Details": {
```

```
            "string" : "string"
         },
         "ExecutionSummary": {
            "ExecutionId": "string",
            "ExecutionTime": number,
            "ExecutionType": "string"
         },
         "Id": "string",
         "ResourceId": "string",
         "ResourceType": "string",
         "Severity": "string",
         "Status": "string",
         "Title": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ComplianceItems

A list of compliance information for the specified resource ID.

Type: Array of ComplianceItem objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListComplianceItems.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListComplianceItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T173645Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
```

```
Content-Length: 40

{
    "ResourceIds": [
        "i-0cb99161f6EXAMPLE"
    ]
}
```

Sample Response

```
{
    "ComplianceItems": [
        {
            "ComplianceType": "Association",
            "ResourceType": "ManagedInstance",
            "ResourceId": "i-0cb99161f6EXAMPLE",
            "Id": "bdf308d4-b431-440d-a2ee-dcca7EXAMPLE",
            "Title": "",
            "Status": "COMPLIANT",
            "Severity": "UNSPECIFIED",
            "ExecutionSummary": {
                "ExecutionTime": 1585761335
            },
            "Details": {
                "DocumentName": "AWS-GatherSoftwareInventory",
                "DocumentVersion": "1"
            }
        },
        {
            "ComplianceType": "Association",
            "ResourceType": "ManagedInstance",
            "ResourceId": "i-0cb99161f6EXAMPLE",
            "Id": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "Title": "",
            "Status": "COMPLIANT",
            "Severity": "HIGH",
            "ExecutionSummary": {
                "ExecutionTime": 1585761335
            },
            "Details": {
                "DocumentName": "AWS-UpdateSSMAgent",
                "DocumentVersion": "1"
            }
```

```
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListComplianceSummaries

Returns a summary count of compliant and non-compliant resources for a compliance type. For example, this call can return State Manager associations, patches, or custom compliance types according to the filter criteria that you specify.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more compliance or inventory filters. Use a filter to return a more specific list of results.

Type: Array of ComplianceStringFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. Currently, you can specify null or 50. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "ComplianceSummaryItems": [
      {
         "ComplianceType": "string",
         "CompliantSummary": {
            "CompliantCount": number,
            "SeveritySummary": {
               "CriticalCount": number,
               "HighCount": number,
               "InformationalCount": number,
               "LowCount": number,
               "MediumCount": number,
               "UnspecifiedCount": number
            }
         },
         "NonCompliantSummary": {
            "NonCompliantCount": number,
            "SeveritySummary": {
               "CriticalCount": number,
               "HighCount": number,
               "InformationalCount": number,
               "LowCount": number,
               "MediumCount": number,
               "UnspecifiedCount": number
            }
         }
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ComplianceSummaryItems

A list of compliant and non-compliant summary counts based on compliance types. For example, this call returns State Manager associations, patches, or custom compliance types according to the filter criteria that you specified.

Type: Array of ComplianceSummaryItem objects

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListComplianceSummaries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListComplianceSummaries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T174348Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ComplianceSummaryItems": [
        {
            "ComplianceType": "FleetTotal",
            "CompliantSummary": {
                "CompliantCount": 1,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 1,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 0
                }
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 2,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
```

```
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 2
                }
            }
        },
        {
            "ComplianceType": "Association",
            "CompliantSummary": {
                "CompliantCount": 3,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 2,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 1
                }
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 0,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 0
                }
            }
        },
        {
            "ComplianceType": "Patch",
            "CompliantSummary": {
                "CompliantCount": 1,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 1
                }
            },
```

```
            "NonCompliantSummary": {
                "NonCompliantCount": 2,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 2
                }
            }
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListDocumentMetadataHistory

> **Important**
>
> AWS Systems Manager Change Manager is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see AWS Systems Manager Change Manager availability change.

Information about approval reviews for a version of a change template in Change Manager.

Request Syntax

```
{
   "DocumentVersion": "string",
   "MaxResults": number,
   "Metadata": "string",
   "Name": "string",
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentVersion

The version of the change template.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Metadata

The type of data for which details are being requested. Currently, the only supported value is `DocumentReviews`.

Type: String

Valid Values: `DocumentReviews`

Required: Yes

Name

The name of the change template.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "Author": "string",
   "DocumentVersion": "string",
   "Metadata": {
      "ReviewerResponse": [
         {
            "Comment": [
```

```
                {
                   "Content": "string",
                   "Type": "string"
                }
             ],
             "CreateTime": number,
             "Reviewer": "string",
             "ReviewStatus": "string",
             "UpdatedTime": number
          }
       ]
    },
    "Name": "string",
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Author

The user ID of the person in the organization who requested the review of the change template.

Type: String

DocumentVersion

The version of the change template.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Metadata

Information about the response to the change template approval request.

Type: DocumentMetadataResponseInfo object

Name

The name of the change template.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

NextToken

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocumentMetadataHistory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocumentMetadataHistory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240730T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240730/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68

{
    "Name": "MyChangeManagerTemplate",
    "Metadata": "DocumentReviews"
}
```

Sample Response

```
{
    "Name": "MyChangeManagerTemplate",
    "DocumentVersion": "1",
    "Author": "arn:aws:iam::111122223333:user/JohnDoe",
    "Metadata": {
        "ReviewerResponse": [
            {
                "CreateTime": "2024-07-30T11:58:28.025000-07:00",
                "UpdatedTime": "2024-07-30T12:01:19.274000-07:00",
                "ReviewStatus": "APPROVED",
                "Comment": [
                    {
                        "Type": "COMMENT",
                        "Content": "I approve this template version"
                    }
                ],
```

```
                "Reviewer": "arn:aws:iam::111122223333:user/ShirleyRodriguez"
            },
            {
                "CreateTime": "2024-07-30T11:58:28.025000-07:00",
                "UpdatedTime": "2024-07-30T11:58:28.025000-07:00",
                "ReviewStatus": "PENDING"
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListDocuments

Returns all Systems Manager (SSM) documents in the current AWS account and AWS Region. You can limit the results of this request by using a filter.

Request Syntax

```
{
   "DocumentFilterList": [
      {
         "key": "string",
         "value": "string"
      }
   ],
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentFilterList

This data type is deprecated. Instead, use `Filters`.

Type: Array of DocumentFilter objects

Array Members: Minimum number of 1 item.

Required: No

Filters

One or more `DocumentKeyValuesFilter` objects. Use a filter to return a more specific list of results. For keys, you can specify one or more key-value pair tags that have been applied to a document. Other valid keys include `Owner`, `Name`, `PlatformTypes`, `DocumentType`, and `TargetType`. For example, to return documents you own use `Key=Owner,Values=Self`. To specify a custom key-value pair, use the format `Key=tag:tagName,Values=valueName`.

> **Note**
>
> This API operation only supports filtering documents by using a single tag key and one or more tag values. For example: `Key=tag:tagName,Values=valueName1,valueName2`

Type: Array of DocumentKeyValuesFilter objects

Array Members: Minimum number of 0 items. Maximum number of 6 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
```

```
   "DocumentIdentifiers": [
      {
         "Author": "string",
         "CreatedDate": number,
         "DisplayName": "string",
         "DocumentFormat": "string",
         "DocumentType": "string",
         "DocumentVersion": "string",
         "Name": "string",
         "Owner": "string",
         "PlatformTypes": [ "string" ],
         "Requires": [
            {
               "Name": "string",
               "RequireType": "string",
               "Version": "string",
               "VersionName": "string"
            }
         ],
         "ReviewStatus": "string",
         "SchemaVersion": "string",
         "Tags": [
            {
               "Key": "string",
               "Value": "string"
            }
         ],
         "TargetType": "string",
         "VersionName": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentIdentifiers

The names of the SSM documents.

Type: Array of DocumentIdentifier objects

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocuments.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocuments
```

```
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T150301Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 97

{
    "Filters": [
        {
            "Key": "Owner",
            "Values": [
                "Self"
            ]
        },
        {
            "Key": "tag:DocUse",
            "Values": [
                "Testing"
            ]
        }
    ]
}
```

Sample Response

```
{
    "DocumentIdentifiers": [
        {
            "CreatedDate": 1486594364.541,
            "DocumentFormat": "YAML",
            "DocumentType": "Automation",
            "DocumentVersion": "1",
            "DisplayName": "ExampleDoc",
            "Name": "Example",
            "Owner": "111122223333",
            "PlatformTypes": [
                "Windows",
                "Linux"
            ],
            "SchemaVersion": "0.3",
            "Tags": [
```

```
                {
                    "Key": "DocUse",
                    "Value": "Testing"
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListDocumentVersions

List all versions for a document.

Request Syntax

```
{
   "MaxResults": number,
   "Name": "string",
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Name

The name of the document. You can specify an Amazon Resource Name (ARN).

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
   "DocumentVersions": [
      {
         "CreatedDate": number,
         "DisplayName": "string",
         "DocumentFormat": "string",
         "DocumentVersion": "string",
         "IsDefaultVersion": boolean,
         "Name": "string",
         "ReviewStatus": "string",
         "Status": "string",
         "StatusInformation": "string",
         "VersionName": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentVersions

The document versions.

Type: Array of DocumentVersionInfo objects

Array Members: Minimum number of 1 item.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocumentVersions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocumentVersions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
```

```
X-Amz-Date: 20240325T151751Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 30

{
    "Name": "AWS-UpdateSSMAgent"
}
```

Sample Response

```
{
    "DocumentVersions": [
        {
            "CreatedDate": 1486594364.541,
            "DisplayName": "ExampleDoc",
            "DocumentFormat": "JSON",
            "DocumentVersion": "1",
            "IsDefaultVersion": true,
            "Name": "AWS-UpdateSSMAgent",
            "Status": "Active"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

ListInventoryEntries

A list of inventory items returned by the request.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "InstanceId": "string",
   "MaxResults": number,
   "NextToken": "string",
   "TypeName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters. Use a filter to return a more specific list of results.

Type: Array of InventoryFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

InstanceId

The managed node ID for which you want inventory information.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

TypeName

The type of inventory item for which you want information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

Response Syntax

```
{
   "CaptureTime": "string",
   "Entries": [
      {
         "string" : "string"
      }
```

```
    ],
    "InstanceId": "string",
    "NextToken": "string",
    "SchemaVersion": "string",
    "TypeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CaptureTime

The time that inventory information was collected for the managed nodes.

Type: String

Pattern: `^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|[0-1][0-9])(:[0-5][0-9])(:[0-5][0-9])(Z)$`

Entries

A list of inventory items on the managed nodes.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

InstanceId

The managed node ID targeted by the request to query inventory information.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

SchemaVersion

The inventory schema version used by the managed nodes.

Type: String

Pattern: `^([0-9]{1,6})(\.[0-9]{1,6})$`

TypeName

The type of inventory item returned by the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.

- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListInventoryEntries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListInventoryEntries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68

{
    "InstanceId": "i-04bf6ad63bEXAMPLE",
    "TypeName": "AWS:Application"
}
```

Sample Response


```
{
    "CaptureTime": "2020-03-30T15:45:32Z",
    "Entries": [
        {
            "Architecture": "i386",
            "InstalledTime": "2020-01-15T00:00:00Z",
            "Name": "AWS Tools for Windows",
            "PackageId": "{2088D019-97CC-4349-BA45-9777568EAE94}",
            "Publisher": "Amazon Web Services Developer Relations",
            "Version": "3.15.925"
        },
        {
            "Architecture": "i386",
            "Name": "Amazon SSM Agent",
            "PackageId": "{2a4673c2-68c6-4a4c-9be6-c3b1be96fdff}",
            "Publisher": "Amazon Web Services",
            "Version": "2.3.930.0"
        },
        {
            "Architecture": "x86_64",
            "InstalledTime": "2018-10-14T00:00:00Z",
            "Name": "aws-cfn-bootstrap",
            "PackageId": "{34CD0CCF-195B-4BC5-B409-D44EB9A129C8}",
            "Publisher": "Amazon Web Services",
            "Version": "1.4.31"
        },
        {
            "Architecture": "x86_64",
            "InstalledTime": "2020-03-10T00:00:00Z",
            "Name": "PowerShell 7-x64",
            "PackageId": "{B324E508-9AAE-446A-BC4C-BB446E8C2A18}",
            "Publisher": "Microsoft Corporation",
            "Version": "7.0.0.0"
        },
        {
            "Architecture": "x86_64",
            "InstalledTime": "2019-09-06T00:00:00Z",
            "Name": "AWS PV Drivers",
            "PackageId": "{C1F68A8D-F235-4886-87B0-150107C07EDA}",
            "Publisher": "Amazon Web Services",
            "Version": "8.3.2"
        }
```

```
    ],
    "InstanceId": "i-04bf6ad63bEXAMPLE",
    "SchemaVersion": "1.1",
    "TypeName": "AWS:Application"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListNodes

Takes in filters and returns a list of managed nodes matching the filter criteria.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "SyncName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters. Use a filter to return a more specific list of managed nodes.

Type: Array of NodeFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

SyncName

The name of the AWS managed resource data sync to retrieve information about.

For cross-account/cross-Region configurations, this parameter is required, and the name of the supported resource data sync is `AWS-QuickSetup-ManagedNode`.

For single account/single-Region configurations, the parameter is not required.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Nodes": [
      {
         "CaptureTime": number,
         "Id": "string",
         "NodeType": { ... },
         "Owner": {
            "AccountId": "string",
            "OrganizationalUnitId": "string",
            "OrganizationalUnitPath": "string"
         },
         "Region": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Nodes

A list of managed nodes that match the specified filter criteria.

Type: Array of Node objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

UnsupportedOperationException

This operation is not supported for the current account. You must first enable the Systems Manager integrated experience in your account.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListNodes.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListNodes
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20241119/25T150301Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 97

{
  "SyncName": "AWS-QuickSetup-ManagedNode",
  "Filters": [
    {
      "Key": "Region",
      "Values": [
        "us-east-2"
      ],
      "Type": "Equal"
    }
  ],
  "MaxResults": 1
}
```

Sample Response

```
{
  "NextToken": "A9lT8CAxj9aDFRi+MNA---truncated---oFq08IEXAMPLE",
  "Nodes": [
    {
      "CaptureTime": 2024-11-19T22:01:18,
      "Id": "i-0471e04240EXAMPLE",
      "NodeType": {
        "Instance": {
          "AgentType": "amazon-ssm-agent",
          "AgentVersion": "3.3.859.0",
          "ComputerName": "ip-192.0.2.0.ec2.internal",
          "InstanceStatus": "Active",
          "IpAddress": "192.0.2.0",
          "ManagedStatus": "Managed",
          "PlatformName": "Amazon Linux",
          "PlatformType": "Linux",
          "PlatformVersion": "2023",
          "ResourceType": "EC2Instance"
        }
      },
      "Owner": {
        "AccountId": "444455556666",
        "OrganizationalUnitId": "ou-b8dn-sEXAMPLE",
        "OrganizationalUnitPath": "r-b8dn/ou-b8dn-sEXAMPLE"
      },
      "Region": "us-east-2"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListNodesSummary

Generates a summary of managed instance/node metadata based on the filters and aggregators you specify. Results are grouped by the input aggregator you specify.

Request Syntax

```
{
   "Aggregators": [
      {
         "Aggregators": [
            "NodeAggregator"
         ],
         "AggregatorType": "string",
         "AttributeName": "string",
         "TypeName": "string"
      }
   ],
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "SyncName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Aggregators

Specify one or more aggregators to return a count of managed nodes that match that expression. For example, a count of managed nodes by operating system.

Type: Array of NodeAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: Yes

Filters

One or more filters. Use a filter to generate a summary that matches your specified filter criteria.

Type: Array of NodeFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.) The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: String

Required: No

SyncName

The name of the AWS managed resource data sync to retrieve information about.

For cross-account/cross-Region configurations, this parameter is required, and the name of the supported resource data sync is `AWS-QuickSetup-ManagedNode`.

For single account/single-Region configurations, the parameter is not required.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Summary": [
      {
         "string" : "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Summary

A collection of objects reporting information about your managed nodes, such as the count of nodes by operating system.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Map Entries: Minimum number of 0 items. Maximum number of 3 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAggregatorException

The specified aggregator isn't valid for the group type. Verify that the aggregator you provided is supported.

HTTP Status Code: 400

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

UnsupportedOperationException

This operation is not supported for the current account. You must first enable the Systems Manager integrated experience in your account.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListNodesSummary.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListNodesSummary
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20241119/25T150301Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 197

{
 "SyncName": "AWS-QuickSetup-ManagedNode",
 "Aggregators":
  [
    {"AggregatorType": "Count",
     "TypeName": "Instance",
     "AttributeName": "Region"}
  ],
  "Filters":
  [
    {"Key": "InstanceStatus",
     "Values":
      ["Active"],
     "Type": "Equal"}
  ],
  "MaxResults" : 2,
  "NextToken": "A9lT8CAxj9aDFRi+MNA---truncated---oFq08IEXAMPLE"
 }
```

Example

This example illustrates one usage of ListNodesSummary.

Sample Response

```
{
    "Summary": [
        {
            "Count": "26",
```

```
            "Region": "us-east-1"
        },
        {
            "Count": "7",
            "Region": "us-east-2"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListOpsItemEvents

Returns a list of all OpsItem events in the current AWS Region and AWS account. You can limit the results to events associated with specific OpsItems by specifying a filter.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Operator": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more OpsItem filters. Use a filter to return a more specific list of results.

Type: Array of OpsItemEventFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Summaries": [
      {
         "CreatedBy": {
            "Arn": "string"
         },
         "CreatedTime": number,
         "Detail": "string",
         "DetailType": "string",
         "EventId": "string",
         "OpsItemId": "string",
         "Source": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Summaries

A list of event information for the specified OpsItems.

Type: Array of OpsItemEventSummary objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListOpsItemRelatedItems

Lists all related-item resources associated with a Systems Manager OpsCenter OpsItem. OpsCenter is a tool in AWS Systems Manager.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Operator": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string",
   "OpsItemId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more OpsItem filters. Use a filter to return a more specific list of results.

Type: Array of OpsItemRelatedItemsFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

OpsItemId

The ID of the OpsItem for which you want to list all related-item resources.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "Summaries": [
      {
         "AssociationId": "string",
         "AssociationType": "string",
         "CreatedBy": {
            "Arn": "string"
         },
         "CreatedTime": number,
         "LastModifiedBy": {
            "Arn": "string"
         },
         "LastModifiedTime": number,
         "OpsItemId": "string",
         "ResourceType": "string",
         "ResourceUri": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Summaries

A list of related-item resources for the specified OpsItem.

Type: Array of OpsItemRelatedItemSummary objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListOpsItemRelatedItems.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListOpsItemRelatedItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/
x86_64.amzn.2 prompt/off command/ssm.list-ops-item-related-items
X-Amz-Date: 20240910T180314Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240910/us-
east-1/ssm/aws4_request, SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE
Content-Length: 32

{
 "OpsItemId": "oi-f99f2EXAMPLE"
}
```

Sample Response

```
{
    "Summaries": [
        {
            "OpsItemId": "oi-f99f2EXAMPLE",
            "AssociationId": "e2036148-cccb-490e-ac2a-390e5EXAMPLE",
            "ResourceType": "AWS::SSMIncidents::IncidentRecord",
            "AssociationType": "IsParentOf",
            "ResourceUri": "arn:aws:ssm-incidents::111122223333:incident-record/
example-response/64bd9b45-1d0e-2622-840d-03a87a1451fa",
            "CreatedBy": {
                "Arn": "arn:aws:sts::111122223333:assumed-role/
AWSServiceRoleForIncidentManager/IncidentResponse"
            },
            "CreatedTime": "2024-08-11T18:47:14.994000+00:00",
            "LastModifiedBy": {
                "Arn": "arn:aws:sts::111122223333:assumed-role/
AWSServiceRoleForIncidentManager/IncidentResponse"
            },
            "LastModifiedTime": "2024-08-11T18:47:14.994000+00:00"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListOpsMetadata

AWS Systems Manager calls this API operation when displaying all Application Manager OpsMetadata objects or blobs.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters to limit the number of OpsMetadata objects returned by the call.

Type: Array of OpsMetadataFilter objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "OpsMetadataList": [
      {
         "CreationDate": number,
         "LastModifiedDate": number,
         "LastModifiedUser": "string",
         "OpsMetadataArn": "string",
         "ResourceId": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

OpsMetadataList

Returns a list of OpsMetadata objects.

Type: Array of OpsMetadata objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListResourceComplianceSummaries

Returns a resource-level summary count. The summary includes information about compliant and non-compliant statuses and detailed compliance-item severity counts, according to the filter criteria you specify.

Request Syntax

```
{
   "Filters": [
      {
         "Key": "string",
         "Type": "string",
         "Values": [ "string" ]
      }
   ],
   "MaxResults": number,
   "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Filters

One or more filters. Use a filter to return a more specific list of results.

Type: Array of ComplianceStringFilter objects

Required: No

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "ResourceComplianceSummaryItems": [
      {
         "ComplianceType": "string",
         "CompliantSummary": {
            "CompliantCount": number,
            "SeveritySummary": {
               "CriticalCount": number,
               "HighCount": number,
               "InformationalCount": number,
               "LowCount": number,
               "MediumCount": number,
               "UnspecifiedCount": number
            }
         },
         "ExecutionSummary": {
            "ExecutionId": "string",
            "ExecutionTime": number,
            "ExecutionType": "string"
         },
         "NonCompliantSummary": {
            "NonCompliantCount": number,
            "SeveritySummary": {
               "CriticalCount": number,
               "HighCount": number,
               "InformationalCount": number,
               "LowCount": number,
               "MediumCount": number,
               "UnspecifiedCount": number
            }
```

```
            },
            "OverallSeverity": "string",
            "ResourceId": "string",
            "ResourceType": "string",
            "Status": "string"
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

ResourceComplianceSummaryItems

A summary count for specified or targeted managed nodes. Summary count includes information about compliant and non-compliant State Manager associations, patch status, or custom items according to the filter criteria that you specify.

Type: Array of ResourceComplianceSummaryItem objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify that you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListResourceComplianceSummaries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListResourceComplianceSummaries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T185225Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ResourceComplianceSummaryItems": [
        {
            "ComplianceType": "Association",
            "CompliantSummary": {
                "CompliantCount": 3,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 1,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 2
                }
            },
```

```
            "ExecutionSummary": {
                "ExecutionTime": 1585766022
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 0,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 0
                }
            },
            "OverallSeverity": "HIGH",
            "ResourceId": "i-04bf6ad63bEXAMPLE",
            "ResourceType": "ManagedInstance",
            "Status": "COMPLIANT"
        },
        {
            "ComplianceType": "Patch",
            "CompliantSummary": {
                "CompliantCount": 27,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 27
                }
            },
            "ExecutionSummary": {
                "ExecutionId": "b95523e7-28e5-488e-a753-fd1d3EXAMPLE",
                "ExecutionTime": 1585244656,
                "ExecutionType": "Command"
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 1,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
```

```
                    "MediumCount": 0,
                    "UnspecifiedCount": 1
                }
            },
            "OverallSeverity": "UNSPECIFIED",
            "ResourceId": "i-04bf6ad63bEXAMPLE",
            "ResourceType": "ManagedInstance",
            "Status": "NON_COMPLIANT"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListResourceDataSync

Lists your resource data sync configurations. Includes information about the last time a sync attempted to start, the last sync status, and the last time a sync successfully completed.

The number of sync configurations might be too large to return using a single call to `ListResourceDataSync`. You can limit the number of sync configurations returned by using the `MaxResults` parameter. To determine whether there are more sync configurations to list, check the value of `NextToken` in the output. If there are more sync configurations to list, you can request them by specifying the `NextToken` returned in the call to the parameter of a subsequent call.

Request Syntax

```
{
   "MaxResults": number,
   "NextToken": "string",
   "SyncType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

SyncType

View a list of resource data syncs according to the sync type. Specify `SyncToDestination` to view resource data syncs that synchronize data to an Amazon S3 bucket. Specify `SyncFromSource` to view resource data syncs from AWS Organizations or from multiple AWS Regions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "ResourceDataSyncItems": [
      {
         "LastStatus": "string",
         "LastSuccessfulSyncTime": number,
         "LastSyncStatusMessage": "string",
         "LastSyncTime": number,
         "S3Destination": {
            "AWSKMSKeyARN": "string",
            "BucketName": "string",
            "DestinationDataSharing": {
               "DestinationDataSharingType": "string"
            },
            "Prefix": "string",
            "Region": "string",
            "SyncFormat": "string"
         },
         "SyncCreatedTime": number,
         "SyncLastModifiedTime": number,
         "SyncName": "string",
         "SyncSource": {
            "AwsOrganizationsSource": {
               "OrganizationalUnits": [
                  {
                     "OrganizationalUnitId": "string"
```

```
                }
            ],
            "OrganizationSourceType": "string"
        },
        "EnableAllOpsDataSources": boolean,
        "IncludeFutureRegions": boolean,
        "SourceRegions": [ "string" ],
        "SourceType": "string",
        "State": "string"
    },
    "SyncType": "string"
  }
 ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

ResourceDataSyncItems

A list of your current resource data sync configurations and their statuses.

Type: Array of ResourceDataSyncItem objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240330T143820Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ResourceDataSyncItems": [
        {
            "LastStatus": "Successful",
            "LastSuccessfulSyncTime": 1585578819.829,
            "LastSyncStatusMessage": "The sync was successfully completed",
            "LastSyncTime": 1585578819.829,
            "S3Destination": {
```

```
                "BucketName": "amzn-s3-demo-bucket",
                "Prefix": "amzn-s3-demo-bucket-prefix",
                "Region": "us-east-2",
                "SyncFormat": "JsonSerDe"
            },
            "SyncCreatedTime": 1585330479.404,
            "SyncLastModifiedTime": 1585330479.404,
            "SyncName": "exampleSync"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListTagsForResource

Returns a list of the tags assigned to the specified resource.

For information about the ID format for each supported resource type, see AddTagsToResource.

Request Syntax

```
{
   "ResourceId": "string",
   "ResourceType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceId

The resource ID for which you want to see a list of tags.

Type: String

Required: Yes

ResourceType

Returns a list of tags for a specific resource type.

Type: String

Valid Values: `Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation | Association`

Required: Yes

Response Syntax

```
{
```

```
   "TagList": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TagList

A list of tags.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListTagsForResource.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListTagsForResource
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T003710Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 71

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "TagList": [
        {
            "Key": "Platform",
            "Value": "Windows Server"
        },
        {
            "Key": "Environment",
            "Value": "Production"
        },
        {
            "Key": "Region",
            "Value": "EMEA"
```

```
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ModifyDocumentPermission

Shares a AWS Systems Manager document (SSM document)publicly or privately. If you share a document privately, you must specify the Amazon Web Services user IDs for those people who can use the document. If you share a document publicly, you must specify *All* as the account ID.

Request Syntax

```
{
   "AccountIdsToAdd": [ "string" ],
   "AccountIdsToRemove": [ "string" ],
   "Name": "string",
   "PermissionType": "string",
   "SharedDocumentVersion": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AccountIdsToAdd

The Amazon Web Services users that should have access to the document. The account IDs can either be a group of account IDs or *All*. You must specify a value for this parameter or the `AccountIdsToRemove` parameter.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: `(?i)all|[0-9]{12}`

Required: No

AccountIdsToRemove

The Amazon Web Services users that should no longer have access to the document. The Amazon Web Services user can either be a group of account IDs or *All*. This action has a higher priority than `AccountIdsToAdd`. If you specify an ID to add and the same ID to remove, the

system removes access to the document. You must specify a value for this parameter or the `AccountIdsToAdd` parameter.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: `(?i)all|[0-9]{12}`

Required: No

Name

The name of the document that you want to share.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

PermissionType

The permission type for the document. The permission type can be *Share*.

Type: String

Valid Values: `Share`

Required: Yes

SharedDocumentVersion

(Optional) The version of the document to share. If it isn't specified, the system choose the `Default` version to share.

Type: String

Length Constraints: Maximum length of 8.

Pattern: `([$]LATEST|[$]DEFAULT|[$]ALL)`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DocumentLimitExceeded

You can have at most 500 active SSM documents.

HTTP Status Code: 400

DocumentPermissionLimit

The document can't be shared with more AWS accounts. You can specify a maximum of 20 accounts per API operation to share a private document.

By default, you can share a private document with a maximum of 1,000 accounts and publicly share up to five documents.

If you need to increase the quota for privately or publicly shared Systems Manager documents, contact AWS Support.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidPermissionType

The permission type isn't supported. *Share* is the only supported permission type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ModifyDocumentPermission.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ModifyDocumentPermission
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T152441Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 78

{
    "Name": "Example",
    "PermissionType": "Share",
    "AccountIdsToAdd": [
        "444455556666"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PutComplianceItems

Registers a compliance type and other compliance details on a designated resource. This operation lets you register custom compliance details with a resource. This call overwrites existing compliance information on the resource, so you must provide a full list of compliance items each time that you send the request.

ComplianceType can be one of the following:

- ExecutionId: The execution ID when the patch, association, or custom compliance item was applied.
- ExecutionType: Specify patch, association, or Custom:`string`.
- ExecutionTime. The time the patch, association, or custom compliance item was applied to the managed node.

> **Important**
>
> For State Manager associations, this represents the time when compliance status was captured by the Systems Manager service during its internal compliance aggregation workflow, not necessarily when the association was executed on the managed node. State Manager updates compliance information for all associations on an instance whenever any association executes, which may result in multiple associations showing the same execution time.

- Id: The patch, association, or custom compliance ID.
- Title: A title.
- Status: The status of the compliance item. For example, `approved` for patches, or `Failed` for associations.
- Severity: A patch severity. For example, `Critical`.
- DocumentName: An SSM document name. For example, `AWS-RunPatchBaseline`.
- DocumentVersion: An SSM document version number. For example, 4.
- Classification: A patch classification. For example, `security updates`.
- PatchBaselineId: A patch baseline ID.
- PatchSeverity: A patch severity. For example, `Critical`.
- PatchState: A patch state. For example, `InstancesWithFailedPatches`.

- PatchGroup: The name of a patch group.
- InstalledTime: The time the association, patch, or custom compliance item was applied to the resource. Specify the time by using the following format: `yyyy-MM-dd'T'HH:mm:ss'Z'`

Request Syntax

```
{
   "ComplianceType": "string",
   "ExecutionSummary": {
      "ExecutionId": "string",
      "ExecutionTime": number,
      "ExecutionType": "string"
   },
   "ItemContentHash": "string",
   "Items": [
      {
         "Details": {
            "string" : "string"
         },
         "Id": "string",
         "Severity": "string",
         "Status": "string",
         "Title": "string"
      }
   ],
   "ResourceId": "string",
   "ResourceType": "string",
   "UploadType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ComplianceType

Specify the compliance type. For example, specify Association (for a State Manager association), Patch, or Custom:`string`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[A-Za-z0-9_\-]\w+|Custom:[a-zA-Z0-9_\-]\w+`

Required: Yes

ExecutionSummary

A summary of the call execution that includes an execution ID, the type of execution (for example, `Command`), and the date/time of the execution using a datetime object that is saved in the following format: `yyyy-MM-dd'T'HH:mm:ss'Z'`

Type: ComplianceExecutionSummary object

Required: Yes

ItemContentHash

MD5 or SHA-256 content hash. The content hash is used to determine if existing information should be overwritten or ignored. If the content hashes match, the request to put compliance information is ignored.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Items

Information about the compliance as defined by the resource type. For example, for a patch compliance type, `Items` includes information about the PatchSeverity, Classification, and so on.

Type: Array of ComplianceItemEntry objects

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Required: Yes

ResourceId

Specify an ID for this resource. For a managed node, this is the node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

ResourceType

Specify the type of resource. `ManagedInstance` is currently the only supported resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

UploadType

The mode for uploading compliance items. You can specify `COMPLETE` or `PARTIAL`. In `COMPLETE` mode, the system overwrites all existing compliance information for the resource. You must provide a full list of compliance items each time you send the request.

In `PARTIAL` mode, the system overwrites compliance information for a specific association. The association must be configured with `SyncCompliance` set to `MANUAL`. By default, all requests use `COMPLETE` mode.

> **Note**
>
> This attribute is only valid for association compliance.

Type: String

Valid Values: `COMPLETE | PARTIAL`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

ComplianceTypeCountLimitExceededException

You specified too many custom compliance types. You can specify a maximum of 10 different types.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidItemContentException

One or more content items isn't valid.

HTTP Status Code: 400

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

ItemSizeLimitExceededException

The inventory item size has exceeded the size limit.

HTTP Status Code: 400

TotalSizeLimitExceededException

The size of inventory data has exceeded the total size limit for the resource.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PutComplianceItems.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.PutComplianceItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.27 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.put-compliance-items
X-Amz-Date: 20240811T170036Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240811/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 260

{
  "ResourceId": "i-02573cafcfEXAMPLE",
  "ResourceType": "ManagedInstance",
  "ComplianceType": "Custom:AVCheck",
  "ExecutionSummary": {
    "ExecutionTime": 1628697600
  },
  "Items": [
    {
      "Id": "Version2.0",
      "Title": "ScanHost",
      "Severity": "CRITICAL",
      "Status": "COMPLIANT"
    }
  ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PutInventory

Bulk update custom inventory items on one or more managed nodes. The request adds an inventory item, if it doesn't already exist, or updates an inventory item, if it does exist.

Request Syntax

```
{
   "InstanceId": "string",
   "Items": [
      {
         "CaptureTime": "string",
         "Content": [
            {
               "string" : "string"
            }
         ],
         "ContentHash": "string",
         "Context": {
            "string" : "string"
         },
         "SchemaVersion": "string",
         "TypeName": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

InstanceId

An managed node ID where you want to add or update inventory items.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

Items

The inventory items that you want to add or update on managed nodes.

Type: Array of InventoryItem objects

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Required: Yes

Response Syntax

```
{
   "Message": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Message

Information about the request.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

CustomSchemaCountLimitExceededException

You have exceeded the limit for custom schemas. Delete one or more custom schemas and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidInventoryItemContextException

You specified invalid keys or values in the `Context` attribute for `InventoryItem`. Verify the keys and values, and try again.

HTTP Status Code: 400

InvalidItemContentException

One or more content items isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

ItemContentMismatchException

The inventory item has invalid content.

HTTP Status Code: 400

ItemSizeLimitExceededException

The inventory item size has exceeded the size limit.

HTTP Status Code: 400

SubTypeCountLimitExceededException

The sub-type count exceeded the limit for the inventory type.

HTTP Status Code: 400

TotalSizeLimitExceededException

The size of inventory data has exceeded the total size limit for the resource.

HTTP Status Code: 400

UnsupportedInventoryItemContextException

The `Context` attribute that you specified for the `InventoryItem` isn't allowed for this inventory type. You can only use the `Context` attribute with inventory types like `AWS:ComplianceItem`.

HTTP Status Code: 400

UnsupportedInventorySchemaVersionException

Inventory item type schema version has to match supported versions in the service. Check output of GetInventorySchema to see the available schema version for each type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PutInventory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.PutInventory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T181858Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 180

{
```

```
    "InstanceId": "i-0cb99161f6EXAMPLE",
    "Items": [
        {
            "TypeName": "Custom:StageInfo",
            "SchemaVersion": "1.0",
            "CaptureTime": "2020-03-31T08:00:00Z",
            "Content": [
                {
                    "Stage": "PreProd"
                }
            ]
        }
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PutParameter

Create or update a parameter in Parameter Store.

Request Syntax

```
{
   "AllowedPattern": "string",
   "DataType": "string",
   "Description": "string",
   "KeyId": "string",
   "Name": "string",
   "Overwrite": boolean,
   "Policies": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "Tier": "string",
   "Type": "string",
   "Value": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AllowedPattern

A regular expression used to validate the parameter value. For example, for String types with values restricted to numbers, you can specify the following: AllowedPattern=^\d+$

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

DataType

The data type for a `String` parameter. Supported data types include plain text and Amazon Machine Image (AMI) IDs.

The following data type values are supported.

- `text`
- `aws:ec2:image`
- `aws:ssm:integration`

When you create a `String` parameter and specify `aws:ec2:image`, AWS Systems Manager validates the parameter value is in the required format, such as `ami-12345abcdeEXAMPLE`, and that the specified AMI is available in your AWS account.

> **Note**
>
> If the action is successful, the service sends back an HTTP 200 response which indicates a successful `PutParameter` call for all cases except for data type `aws:ec2:image`. If you call `PutParameter` with `aws:ec2:image` data type, a successful HTTP 200 response does not guarantee that your parameter was successfully created or updated. The `aws:ec2:image` value is validated asynchronously, and the `PutParameter` call returns before the validation is complete. If you submit an invalid AMI value, the PutParameter operation will return success, but the asynchronous validation will fail and the parameter will not be created or updated. To monitor whether your `aws:ec2:image` parameters are created successfully, see Setting up notifications or trigger actions based on Parameter Store events. For more information about AMI format validation , see Native parameter support for Amazon Machine Image IDs.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description

Information about the parameter that you want to add to the system. Optional but recommended.

> **Important**
>
> Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId

The AWS Key Management Service (AWS KMS) ID that you want to use to encrypt a parameter. Use a custom key for better security. Required for parameters that use the `SecureString` data type.

If you don't specify a key ID, the system uses the default key associated with your AWS account, which is not as secure as using a custom key.

- To use a custom AWS KMS key, choose the `SecureString` data type with the `Key ID` parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([a-zA-Z0-9:/_-]+)$`

Required: No

Name

The fully qualified name of the parameter that you want to create or update.

> **Note**
>
> You can't enter the Amazon Resource Name (ARN) for a parameter, only the parameter name itself.

The fully qualified name includes the complete hierarchy of the parameter path and name. For parameters in a hierarchy, you must include a leading forward slash character (/) when you create or reference a parameter. For example: `/Dev/DBServer/MySQL/db-string13`

Naming Constraints:

- Parameter names are case sensitive.
- A parameter name must be unique within an AWS Region
- A parameter name can't be prefixed with "`aws`" or "`ssm`" (case-insensitive).
- Parameter names can include only the following symbols and letters: `a-zA-Z0-9_.-`

  In addition, the slash character (/) is used to delineate hierarchies in parameter names. For example: `/Dev/Production/East/Project-ABC/MyParameter`
- Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.
- Parameter hierarchies are limited to a maximum depth of fifteen levels.

For additional information about valid values for parameter names, see Creating Systems Manager parameters in the *AWS Systems Manager User Guide*.

> **Note**
>
> The reported maximum length of 2048 characters for a parameter name includes 1037 characters that are reserved for internal use by Systems Manager. The maximum length for a parameter name that you specify is 1011 characters.
> This count of 1011 characters includes the characters in the ARN that precede the name you specify. This ARN length will vary depending on your partition and Region. For example, the following 45 characters count toward the 1011 character maximum for a parameter created in the US East (Ohio) Region: `arn:aws:ssm:us-east-2:111122223333:parameter/`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Overwrite

Overwrite an existing parameter. The default value is `false`.

Type: Boolean

Required: No

Policies

One or more policies to apply to a parameter. This operation takes a JSON array. Parameter Store, a tool in AWS Systems Manager supports the following policy types:

Expiration: This policy deletes the parameter after it expires. When you create the policy, you specify the expiration date. You can update the expiration date and time by updating the policy. Updating the *parameter* doesn't affect the expiration date and time. When the expiration time is reached, Parameter Store deletes the parameter.

ExpirationNotification: This policy initiates an event in Amazon CloudWatch Events that notifies you about the expiration. By using this policy, you can receive notification before or after the expiration time is reached, in units of days or hours.

NoChangeNotification: This policy initiates a CloudWatch Events event if a parameter hasn't been modified for a specified period of time. This policy type is useful when, for example, a secret needs to be changed within a period of time, but it hasn't been changed.

All existing policies are preserved until you send new policies or an empty policy. For more information about parameter policies, see Assigning parameter policies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Tags

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a Systems Manager parameter to identify the type of resource to which it applies, the environment, or the type of configuration data referenced by the parameter. In this case, you could specify the following key-value pairs:

- `Key=Resource,Value=S3bucket`
- `Key=OS,Value=Windows`
- `Key=ParameterType,Value=LicenseKey`

> **Note**
>
> To add tags to an existing Systems Manager parameter, use the AddTagsToResource operation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Tier

The parameter tier to assign to a parameter.

Parameter Store offers a standard tier and an advanced tier for parameters. Standard parameters have a content size limit of 4 KB and can't be configured to use parameter policies. You can create a maximum of 10,000 standard parameters for each Region in an AWS account. Standard parameters are offered at no additional cost.

Advanced parameters have a content size limit of 8 KB and can be configured to use parameter policies. You can create a maximum of 100,000 advanced parameters for each Region in an AWS account. Advanced parameters incur a charge. For more information, see Managing parameter tiers in the *AWS Systems Manager User Guide*.

You can change a standard parameter to an advanced parameter any time. But you can't revert an advanced parameter to a standard parameter. Reverting an advanced parameter to a standard parameter would result in data loss because the system would truncate the size of the parameter from 8 KB to 4 KB. Reverting would also remove any policies attached to the parameter. Lastly, advanced parameters use a different form of encryption than standard parameters.

If you no longer need an advanced parameter, or if you no longer want to incur charges for an advanced parameter, you must delete it and recreate it as a new standard parameter.

Using the Default Tier Configuration

In `PutParameter` requests, you can specify the tier to create the parameter in. Whenever you specify a tier in the request, Parameter Store creates or updates the parameter according to that request. However, if you don't specify a tier in a request, Parameter Store assigns the tier based on the current Parameter Store default tier configuration.

The default tier when you begin using Parameter Store is the standard-parameter tier. If you use the advanced-parameter tier, you can specify one of the following as the default:

- **Advanced**: With this option, Parameter Store evaluates all requests as advanced parameters.
- **Intelligent-Tiering**: With this option, Parameter Store evaluates each request to determine if the parameter is standard or advanced.

  If the request doesn't include any options that require an advanced parameter, the parameter is created in the standard-parameter tier. If one or more options requiring an advanced parameter are included in the request, Parameter Store create a parameter in the advanced-parameter tier.

  This approach helps control your parameter-related costs by always creating standard parameters unless an advanced parameter is necessary.

Options that require an advanced parameter include the following:

- The content size of the parameter is more than 4 KB.
- The parameter uses a parameter policy.
- More than 10,000 parameters already exist in your AWS account in the current AWS Region.

For more information about configuring the default tier option, see Specifying a default parameter tier in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `Standard | Advanced | Intelligent-Tiering`

Required: No

Type

The type of parameter that you want to create.

> **Note**
>
> `SecureString` isn't currently supported for AWS CloudFormation templates.

Items in a `StringList` must be separated by a comma (,). You can't use other punctuation or special character to escape items in the list. If you have a parameter value that requires a comma, then use the `String` data type.

> **Important**
>
> Specifying a parameter type isn't required when updating a parameter. You must specify a parameter type when creating a parameter.

Type: String

Valid Values: `String | StringList | SecureString`

Required: No

Value

The parameter value that you want to add to the system. Standard parameters have a value limit of 4 KB. Advanced parameters have a value limit of 8 KB.

> **Note**
>
> Parameters can't be referenced or nested in the values of other parameters. You can't include values wrapped in double brackets `{{}}` or `{{ssm:parameter-name}}` in a parameter value.

Type: String

Required: Yes

Response Syntax

```
{
   "Tier": "string",
   "Version": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tier

The tier assigned to the parameter.

Type: String

Valid Values: `Standard | Advanced | Intelligent-Tiering`

Version

The new version number of a parameter. If you edit a parameter value, Parameter Store automatically creates a new version and assigns this new version a unique ID. You can reference a parameter version ID in API operations or in Systems Manager documents (SSM documents). By default, if you don't specify a specific version, the system returns the latest parameter value when a parameter is called.

Type: Long

Errors

For information about the errors that are common to all actions, see Common Error Types.

HierarchyLevelLimitExceededException

A hierarchy can have a maximum of 15 levels. For more information, see Requirements and constraints for parameter names in the *AWS Systems Manager User Guide*.

message

A hierarchy can have a maximum of 15 levels. For more information, see About requirements and constraints for parameter names in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

HierarchyTypeMismatchException

Parameter Store doesn't support changing a parameter type in a hierarchy. For example, you can't change a parameter from a `String` type to a `SecureString` type. You must create a new, unique parameter.

message

Parameter Store doesn't support changing a parameter type in a hierarchy. For example, you can't change a parameter from a `String` type to a `SecureString` type. You must create a new, unique parameter.

HTTP Status Code: 400

IncompatiblePolicyException

There is a conflict in the policies specified for this parameter. You can't, for example, specify two Expiration policies for a parameter. Review your policies, and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAllowedPatternException

The request doesn't meet the regular expression requirement.

message

The request doesn't meet the regular expression requirement.

HTTP Status Code: 400

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidPolicyAttributeException

A policy attribute or its value is invalid.

HTTP Status Code: 400

InvalidPolicyTypeException

The policy type isn't supported. Parameter Store supports the following policy types: Expiration, ExpirationNotification, and NoChangeNotification.

HTTP Status Code: 400

ParameterAlreadyExists

The parameter already exists. You can't create duplicate parameters.

HTTP Status Code: 400

ParameterLimitExceeded

You have exceeded the number of parameters for this AWS account. Delete one or more parameters and try again.

HTTP Status Code: 400

ParameterMaxVersionLimitExceeded

Parameter Store retains the 100 most recently created versions of a parameter. After this number of versions has been created, Parameter Store deletes the oldest version when a new one is created. However, if the oldest version has a *label* attached to it, Parameter Store won't delete the version and instead presents this error message:

`An error occurred (ParameterMaxVersionLimitExceeded) when calling the PutParameter operation: You attempted to create a new version of` *`parameter-name`* `by calling the PutParameter API with the overwrite flag. Version` *`version-number`*`, the oldest version, can't be deleted because it has a label associated with it. Move the label to another version of the parameter, and try again.`

This safeguard is to prevent parameter versions with mission critical labels assigned to them from being deleted. To continue creating new parameters, first move the label from the oldest version of the parameter to a newer one for use in your operations. For information about moving parameter labels, see Move a parameter label (console) or Move a parameter label (CLI) in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

ParameterPatternMismatchException

The parameter name isn't valid.

message

The parameter name isn't valid.

HTTP Status Code: 400

PoliciesLimitExceededException

You specified more than the maximum number of allowed policies for the parameter. The maximum is 10.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

UnsupportedParameterType

The parameter type isn't supported.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PutParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 136
X-Amz-Target: AmazonSSM.PutParameter
X-Amz-Date: 20240316T000626Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Overwrite": true,
    "Type": "String",
```

```
    "Name": "EC2TestServerType",
    "Value": "t2.large",
    "Description": "Instance type for Test servers"
}
```

Sample Response

```
{
    "Version": 2
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PutResourcePolicy

Creates or updates a Systems Manager resource policy. A resource policy helps you to define the IAM entity (for example, an AWS account) that can manage your Systems Manager resources. The following resources support Systems Manager resource policies.

- `OpsItemGroup` - The resource policy for `OpsItemGroup` enables AWS accounts to view and interact with OpsCenter operational work items (OpsItems).
- `Parameter` - The resource policy is used to share a parameter with other accounts using AWS Resource Access Manager (AWS RAM).

  To share a parameter, it must be in the advanced parameter tier. For information about parameter tiers, see Managing parameter tiers. For information about changing an existing standard parameter to an advanced parameter, see Changing a standard parameter to an advanced parameter.

  To share a `SecureString` parameter, it must be encrypted with a customer managed key, and you must share the key separately through AWS Key Management Service. AWS managed keys cannot be shared. Parameters encrypted with the default AWS managed key can be updated to use a customer managed key instead. For AWS KMS key definitions, see AWS KMS concepts in the *AWS Key Management Service Developer Guide*.

  > **Important**
  >
  > While you can share a parameter using the Systems Manager `PutResourcePolicy` operation, we recommend using AWS Resource Access Manager (AWS RAM) instead. This is because using `PutResourcePolicy` requires the extra step of promoting the parameter to a standard AWS RAM Resource Share using the AWS RAM PromoteResourceShareCreatedFromPolicy API operation. Otherwise, the parameter won't be returned by the Systems Manager DescribeParameters API operation using the `--shared` option.
  > For more information, see Sharing a parameter in the *AWS Systems Manager User Guide*

Request Syntax

```
{
   "Policy": "string",
```

```
    "PolicyHash": "string",
    "PolicyId": "string",
    "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Policy

A policy you want to associate with a resource.

Type: String

Pattern: `^(?!\s*$).+`

Required: Yes

PolicyHash

ID of the current policy version. The hash helps to prevent a situation where multiple users attempt to overwrite a policy. You must provide this hash when updating or deleting a policy.

Type: String

Required: No

PolicyId

The policy ID.

Type: String

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource to which you want to attach a policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Response Syntax

```
{
   "PolicyHash": "string",
   "PolicyId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PolicyHash

ID of the current policy version.

Type: String

PolicyId

The policy ID. To update a policy, you must specify `PolicyId` and `PolicyHash`.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

MalformedResourcePolicyDocumentException

The specified policy document is malformed or invalid, or excessive `PutResourcePolicy` or `DeleteResourcePolicy` calls have been made.

HTTP Status Code: 400

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

ResourcePolicyConflictException

The hash provided in the call doesn't match the stored hash. This exception is thrown when trying to update an obsolete policy version or when multiple requests to update a policy are sent.

HTTP Status Code: 400

ResourcePolicyInvalidParameterException

One or more parameters specified for the call aren't valid. Verify the parameters and their values and try again.

HTTP Status Code: 400

ResourcePolicyLimitExceededException

The PutResourcePolicy API action enforces two limits. A policy can't be greater than 1024 bytes in size. And only one policy can be attached to `OpsItemGroup`. Verify these limits and try again.

HTTP Status Code: 400

ResourcePolicyNotFoundException

No policies with the specified policy ID and hash could be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

RegisterDefaultPatchBaseline

Defines the default patch baseline for the relevant operating system.

To reset the AWS-predefined patch baseline as the default, specify the full patch baseline Amazon Resource Name (ARN) as the baseline ID value. For example, for CentOS, specify `arn:aws:ssm:us-east-2:733109147000:patchbaseline/pb-0574b43a65ea646ed` instead of `pb-0574b43a65ea646ed`.

Request Syntax

```
{
   "BaselineId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline that should be the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

Response Syntax

```
{
   "BaselineId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterDefaultPatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.RegisterDefaultPatchBaseline
X-Amz-Date: 20240309T025821Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

RegisterPatchBaselineForPatchGroup

Registers a patch baseline for a patch group.

Request Syntax

```
{
   "BaselineId": "string",
   "PatchGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

BaselineId

The ID of the patch baseline to register with the patch group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

PatchGroup

The name of the patch group to be registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
   "BaselineId": "string",
   "PatchGroup": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId

The ID of the patch baseline the patch group was registered with.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

PatchGroup

The name of the patch group registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

AlreadyExistsException

Error returned if an attempt is made to register a patch group with a patch baseline that is already registered with a different patch baseline.

HTTP Status Code: 400

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 74
X-Amz-Target: AmazonSSM.RegisterPatchBaselineForPatchGroup
X-Amz-Date: 20240309T060234Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

RegisterTargetWithMaintenanceWindow

Registers a target with a maintenance window.

Request Syntax

```
{
   "ClientToken": "string",
   "Description": "string",
   "Name": "string",
   "OwnerInformation": "string",
   "ResourceType": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ClientToken

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Description

An optional description for the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

An optional name for the target.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

OwnerInformation

User-provided value that will be included in any Amazon CloudWatch Events events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

ResourceType

The type of target being registered with the maintenance window.

Type: String

Valid Values: `INSTANCE | RESOURCE_GROUP`

Required: Yes

Targets

The targets to register with the maintenance window. In other words, the managed nodes to run commands on when the maintenance window runs.

> **Note**
>
> If a single maintenance window task is registered with multiple targets, its task invocations occur sequentially and not in parallel. If your task must run on multiple

targets at the same time, register a task for each target individually and assign each task the same priority level.

You can specify targets using managed node IDs, resource group names, or tags that have been applied to managed nodes.

Example 1: Specify managed node IDs

```
Key=InstanceIds,Values=<instance-id-1>,<instance-id-2>,<instance-id-3>
```

Example 2: Use tag key-pairs applied to managed nodes

```
Key=tag:<my-tag-key>,Values=<my-tag-value-1>,<my-tag-value-2>
```

Example 3: Use tag-keys applied to managed nodes

```
Key=tag-key,Values=<my-tag-key-1>,<my-tag-key-2>
```

Example 4: Use resource group names

```
Key=resource-groups:Name,Values=<resource-group-name>
```

Example 5: Use filters for resource group types

```
Key=resource-groups:ResourceTypeFilters,Values=<resource-
type-1>,<resource-type-2>
```

Note

For `Key=resource-groups:ResourceTypeFilters`, specify resource types in the following format `Key=resource-groups:ResourceTypeFilters,Values=AWS::EC2::INSTANCE,AWS::EC2::VPC`

For more information about these examples formats, including the best use case for each one, see Examples: Register targets with a maintenance window in the *AWS Systems Manager User Guide*.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: Yes

WindowId

The ID of the maintenance window the target should be registered with.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "WindowTargetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowTargetId

The ID of the target definition in this maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterTargetWithMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
```

```
X-Amz-Target: AmazonSSM.RegisterTargetWithMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T003144Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target,Signature=39c3b3042cd2aEXAMPLE
Content-Length: 191

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "ResourceType": "INSTANCE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "WindowTargetId": "7f4813bb-df25-4e59-b34f-c9e83EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

RegisterTaskWithMaintenanceWindow

Adds a new task to a maintenance window.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "ClientToken": "string",
   "CutoffBehavior": "string",
   "Description": "string",
   "LoggingInfo": {
      "S3BucketName": "string",
      "S3KeyPrefix": "string",
      "S3Region": "string"
   },
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "Priority": number,
   "ServiceRoleArn": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TaskArn": "string",
   "TaskInvocationParameters": {
      "Automation": {
         "DocumentVersion": "string",
         "Parameters": {
            "string" : [ "string" ]
         }
      },
      "Lambda": {
```

```
            "ClientContext": "string",
            "Payload": blob,
            "Qualifier": "string"
         },
         "RunCommand": {
            "CloudWatchOutputConfig": {
               "CloudWatchLogGroupName": "string",
               "CloudWatchOutputEnabled": boolean
            },
            "Comment": "string",
            "DocumentHash": "string",
            "DocumentHashType": "string",
            "DocumentVersion": "string",
            "NotificationConfig": {
               "NotificationArn": "string",
               "NotificationEvents": [ "string" ],
               "NotificationType": "string"
            },
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "Parameters": {
               "string" : [ "string" ]
            },
            "ServiceRoleArn": "string",
            "TimeoutSeconds": number
         },
         "StepFunctions": {
            "Input": "string",
            "Name": "string"
         }
      },
      "TaskParameters": {
         "string" : {
            "Values": [ "string" ]
         }
      },
      "TaskType": "string",
      "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The CloudWatch alarm you want to apply to your maintenance window task.

Type: AlarmConfiguration object

Required: No

ClientToken

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

CutoffBehavior

Indicates whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

- `CONTINUE_TASK`: When the cutoff time is reached, any tasks that are running continue. The default value.
- `CANCEL_TASK`:
  - For Automation, AWS Lambda, AWS Step Functions tasks: When the cutoff time is reached, any task invocations that are already running continue, but no new task invocations are started.
  - For Run Command tasks: When the cutoff time is reached, the system sends a CancelCommand operation that attempts to cancel the command associated with the task. However, there is no guarantee that the command will be terminated and the underlying process stopped.

  The status for tasks that are not completed is `TIMED_OUT`.

Type: String

Valid Values: `CONTINUE_TASK | CANCEL_TASK`

Required: No

Description

An optional description for the task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

LoggingInfo

A structure containing information about an Amazon Simple Storage Service (Amazon S3) bucket to write managed node-level logs to.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: LoggingInfo object

Required: No

MaxConcurrency

The maximum number of targets this task can be run for, in parallel.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The maximum number of errors allowed before this task stops being scheduled.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

An optional name for the task.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Priority

The priority of the task in the maintenance window, the lower the number the higher the priority. Tasks in a maintenance window are scheduled in priority order with tasks that have the same priority scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Required: No

Targets

The targets (either managed nodes or maintenance window targets).

> **Note**
>
> One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see Registering maintenance window tasks without targets in the *AWS Systems Manager User Guide*.

Specify managed nodes using the following format:

`Key=InstanceIds,Values=<instance-id-1>,<instance-id-2>`

Specify maintenance window targets using the following format:

`Key=WindowTargetIds,Values=<window-target-id-1>,<window-target-id-2>`

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TaskArn

The ARN of the task to run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

TaskInvocationParameters

The parameters that the task should use during execution. Populate only the fields that match the task type. All other fields should be empty.

Type: MaintenanceWindowTaskInvocationParameters object

Required: No

TaskParameters

The parameters that should be passed to the task when it is run.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: String to MaintenanceWindowTaskParameterValueExpression object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

TaskType

The type of task being registered.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

Required: Yes

WindowId

The ID of the maintenance window the task should be added to.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "WindowTaskId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowTaskId

The ID of the task in the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

FeatureNotAvailableException

You attempted to register a `LAMBDA` or `STEP_FUNCTIONS` task in a region where the corresponding service isn't available.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterTaskWithMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.RegisterTaskWithMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T181553Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 362

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-02573cafcfEXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-RunShellScript",
    "TaskType": "RUN_COMMAND",
    "TaskInvocationParameters": {
        "RunCommand": {
            "Parameters": {
                "commands": [
                    "df"
```

```
                ]
            }
        }
    },
    "Priority": 10,
    "MaxConcurrency": "1",
    "MaxErrors": "1",
    "ClientToken": "8a3f60db-1d39-4938-a566-c2ec2EXAMPLE"
}
```

Sample Response

```
{
    "WindowTaskId": "216ae877-0be9-4746-a19d-ed654EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

RemoveTagsFromResource

Removes tag keys from the specified resource.

Request Syntax

```
{
   "ResourceId": "string",
   "ResourceType": "string",
   "TagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceId

The ID of the resource from which you want to remove tags. For example:

ManagedInstance: mi-012345abcde

MaintenanceWindow: mw-012345abcde

Automation: `example-c160-4567-8519-012345abcde`

PatchBaseline: pb-012345abcde

OpsMetadata object: `ResourceID` for tagging is created from the Amazon Resource Name (ARN) for the object. Specifically, `ResourceID` is created from the strings that come after the word `opsmetadata` in the ARN. For example, an OpsMetadata object with an ARN of `arn:aws:ssm:us-east-2:1234567890:opsmetadata/aws/ssm/MyGroup/appmanager` has a `ResourceID` of either `aws/ssm/MyGroup/appmanager` or `/aws/ssm/MyGroup/appmanager`.

For the Document and Parameter values, use the name of the resource.

> **Note**
>
> The `ManagedInstance` type for this API operation is only for on-premises managed nodes. Specify the name of the managed node in the following format: mi-ID_number. For example, mi-1a2b3c4d5e6f.

Type: String

Required: Yes

ResourceType

The type of resource from which you want to remove a tag.

> **Note**
>
> The `ManagedInstance` type for this API operation is only for on-premises managed nodes. Specify the name of the managed node in the following format: `mi-`*`ID_number`* . For example, `mi-1a2b3c4d5e6f`.

Type: String

Valid Values: `Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation | Association`

Required: Yes

TagKeys

Tag keys that you want to remove from the specified resource.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RemoveTagsFromResource.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.RemoveTagsFromResource
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T004031Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 99

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE",
    "TagKeys": [
        "Environment"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ResetServiceSetting

`ServiceSetting` is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a `SettingId` object to a setting value. AWS services teams define the default value for a `SettingId`. You can't create a new `SettingId`, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the GetServiceSetting API operation to view the current value. Use the UpdateServiceSetting API operation to change the default setting.

Reset the service setting for the account to the default value as provisioned by the AWS service team.

Request Syntax

```
{
   "SettingId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SettingId

The Amazon Resource Name (ARN) of the service setting to reset. The setting ID can be one of the following.

- `/ssm/appmanager/appmanager-enabled`
- `/ssm/automation/customer-script-log-destination`
- `/ssm/automation/customer-script-log-group-name`
- /ssm/automation/enable-adaptive-concurrency
- `/ssm/documents/console/public-sharing-permission`

- `/ssm/managed-instance/activation-tier`
- `/ssm/managed-instance/default-ec2-instance-management-role`
- `/ssm/opsinsights/opscenter`
- `/ssm/parameter-store/default-parameter-tier`
- `/ssm/parameter-store/high-throughput-enabled`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Response Syntax

```
{
   "ServiceSetting": {
      "ARN": "string",
      "LastModifiedDate": number,
      "LastModifiedUser": "string",
      "SettingId": "string",
      "SettingValue": "string",
      "Status": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ServiceSetting

The current, effective service setting after calling the ResetServiceSetting API operation.

Type: ServiceSetting object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ResetServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ResetServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T153659Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 110

{
    "SettingId": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/parameter-
store/high-throughput-enabled"
}
```

Sample Response

```
{
    "ServiceSetting": {
        "ARN": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/parameter-store/
high-throughput-enabled",
        "LastModifiedDate": 1555532571.138,
        "LastModifiedUser": "System",
        "SettingId": "/ssm/parameter-store/high-throughput-enabled",
        "SettingValue": "false",
        "Status": "Default"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ResumeSession

Reconnects a session to a managed node after it has been disconnected. Connections can be resumed for disconnected sessions, but not terminated sessions.

> **Note**
>
> This command is primarily for use by client machines to automatically reconnect during intermittent network issues. It isn't intended for any other use.

Request Syntax

```
{
   "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SessionId

The ID of the disconnected session to resume.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: Yes

Response Syntax

```
{
   "SessionId": "string",
   "StreamUrl": "string",
   "TokenValue": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SessionId

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

StreamUrl

A URL back to SSM Agent on the managed node that the Session Manager client uses to send commands and receive output from the managed node. Format: `wss://ssmmessages.`**`region`**`.amazonaws.com/v1/data-channel/`**`session-id`**`?stream=(input|output)`.

region represents the Region identifier for an AWS Region supported by AWS Systems Manager, such as `us-east-2` for the US East (Ohio) Region. For a list of supported **region** values, see the **Region** column in Systems Manager service endpoints in the *Amazon Web Services General Reference*.

session-id represents the ID of a Session Manager session, such as `1a2b3c4dEXAMPLE`.

Type: String

TokenValue

An encrypted token value containing session and caller information. Used to authenticate the connection to the managed node.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of ResumeSession.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ResumeSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T181144Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

Sample Response

```
{{
```

```
    "SessionId": "John-Doe-0402960697EXAMPLE",
    "StreamUrl": "wss://ssmmessages.us-east-2.amazonaws.com/v1/data-channel/John-
Doe-0402960697EXAMPLE?role=publish_subscribe",
    "TokenValue": "EXAMPLENPKTm3/39c3b3042cd2aEXAMPLE/a3f5ff34-9bc4-4d2c-
a665-4d1c1EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

SendAutomationSignal

Sends a signal to an Automation execution to change the current behavior or status of the execution.

Request Syntax

```
{
   "AutomationExecutionId": "string",
   "Payload": {
      "string" : [ "string" ]
   },
   "SignalType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AutomationExecutionId

The unique identifier for an existing Automation execution that you want to send the signal to.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Payload

The data sent with the signal. The data schema depends on the type of signal used in the request.

For `Approve` and `Reject` signal types, the payload is an optional comment that you can send with the signal type. For example:

`Comment="Looks good"`

For `StartStep` and `Resume` signal types, you must send the name of the Automation step to start or resume as the payload. For example:

`StepName="step1"`

For the `StopStep` signal type, you must send the step execution ID as the payload. For example:

`StepExecutionId="97fff367-fc5a-4299-aed8-0123456789ab"`

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

SignalType

The type of signal to send to an Automation execution.

Type: String

Valid Values: `Approve | Reject | StartStep | StopStep | Resume | Revoke`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

AutomationStepNotFoundException

The specified step name and execution ID don't exist. Verify the information and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationSignalException

The signal isn't valid for the current Automation execution.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of SendAutomationSignal.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.SendAutomationSignal
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T162449Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 165

{
    "AutomationExecutionId": "b2bc0e75-4d48-4b7b-be9b-0cb5cEXAMPLE",
    "SignalType": "StopStep",
    "Payload": {
        "StepExecutionId": [
            "33d93afd-9535-4dd5-a06b-c91bdEXAMPLE"
```

```
        ]
    }
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

SendCommand

Runs commands on one or more managed nodes.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "CloudWatchOutputConfig": {
      "CloudWatchLogGroupName": "string",
      "CloudWatchOutputEnabled": boolean
   },
   "Comment": "string",
   "DocumentHash": "string",
   "DocumentHashType": "string",
   "DocumentName": "string",
   "DocumentVersion": "string",
   "InstanceIds": [ "string" ],
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "NotificationConfig": {
      "NotificationArn": "string",
      "NotificationEvents": [ "string" ],
      "NotificationType": "string"
   },
   "OutputS3BucketName": "string",
   "OutputS3KeyPrefix": "string",
   "OutputS3Region": "string",
   "Parameters": {
      "string" : [ "string" ]
   },
   "ServiceRoleArn": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
```

```
      }
   ],
   "TimeoutSeconds": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The CloudWatch alarm you want to apply to your command.

Type: AlarmConfiguration object

Required: No

CloudWatchOutputConfig

Enables AWS Systems Manager to send Run Command output to Amazon CloudWatch Logs. Run Command is a tool in AWS Systems Manager.

Type: CloudWatchOutputConfig object

Required: No

Comment

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DocumentHash

The Sha256 or Sha1 hash created by the system when the document was created.

> **Note**
>
> Sha1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DocumentHashType

Sha256 or Sha1.

> **Note**
>
> Sha1 hashes have been deprecated.

Type: String

Valid Values: `Sha256 | Sha1`

Required: No

DocumentName

The name of the AWS Systems Manager document (SSM document) to run. This can be a public document or a custom document. To run a shared document belonging to another account, specify the document Amazon Resource Name (ARN). For more information about how to use shared documents, see Sharing SSM documents in the *AWS Systems Manager User Guide*.

> **Note**
>
> If you specify a document name or ARN that hasn't been shared with your account, you receive an `InvalidDocument` error.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

DocumentVersion

The SSM document version to use in the request. You can specify $DEFAULT, $LATEST, or a specific version number. If you run commands by using the AWS Command Line Interface (AWS CLI), then you must escape the first two options by using a backslash. If you specify a version number, then you don't need to use the backslash. For example:

--document-version "\$DEFAULT"

--document-version "\$LATEST"

--document-version "3"

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

InstanceIds

The IDs of the managed nodes where the command should run. Specifying managed node IDs is most useful when you are targeting a limited number of managed nodes, though you can specify up to 50 IDs.

To target a larger number of managed nodes, or if you prefer not to list individual node IDs, we recommend using the `Targets` option instead. Using `Targets`, which accepts tag key-value pairs to identify the managed nodes to send commands to, you can a send command to tens, hundreds, or thousands of nodes at once.

For more information about how to use targets, see Run commands at scale in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxConcurrency

(Optional) The maximum number of managed nodes that are allowed to run the command at the same time. You can specify a number such as 10 or a percentage such as 10%. The default value is 50. For more information about how to use MaxConcurrency, see Using concurrency controls in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$

Required: No

MaxErrors

The maximum number of errors allowed without the command failing. When the command fails one more time beyond the value of MaxErrors, the systems stops sending the command to additional targets. You can specify a number like 10 or a percentage like 10%. The default value is 0. For more information about how to use MaxErrors, see Using error controls in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$

Required: No

NotificationConfig

Configurations for sending notifications.

Type: NotificationConfig object

Required: No

OutputS3BucketName

The name of the S3 bucket where command execution responses should be stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The directory structure within the S3 bucket where the responses should be stored.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, Systems Manager automatically determines the AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

Parameters

The required and optional parameters specified in the document being run.

Type: String to array of strings map

Required: No

ServiceRoleArn

The ARN of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for Run Command commands.

This role must provide the `sns:Publish` permission for your notification topic. For information about creating and using this service role, see Monitoring Systems Manager status changes using Amazon SNS notifications in the *AWS Systems Manager User Guide*.

Type: String

Required: No

Targets

An array of search criteria that targets managed nodes using a `Key,Value` combination that you specify. Specifying targets is most useful when you want to send a command to a large

number of managed nodes at once. Using `Targets`, which accepts tag key-value pairs to identify managed nodes, you can send a command to tens, hundreds, or thousands of nodes at once.

To send a command to a smaller number of managed nodes, you can use the `InstanceIds` option instead.

For more information about how to use targets, see Run commands at scale in the *AWS Systems Manager User Guide*.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TimeoutSeconds

If this time is reached and the command hasn't already started running, it won't run.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

Response Syntax

```
{
   "Command": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
      },
      "CloudWatchOutputConfig": {
         "CloudWatchLogGroupName": "string",
         "CloudWatchOutputEnabled": boolean
      },
      "CommandId": "string",
      "Comment": "string",
```

```
      "CompletedCount": number,
      "DeliveryTimedOutCount": number,
      "DocumentName": "string",
      "DocumentVersion": "string",
      "ErrorCount": number,
      "ExpiresAfter": number,
      "InstanceIds": [ "string" ],
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "NotificationConfig": {
         "NotificationArn": "string",
         "NotificationEvents": [ "string" ],
         "NotificationType": "string"
      },
      "OutputS3BucketName": "string",
      "OutputS3KeyPrefix": "string",
      "OutputS3Region": "string",
      "Parameters": {
         "string" : [ "string" ]
      },
      "RequestedDateTime": number,
      "ServiceRole": "string",
      "Status": "string",
      "StatusDetails": "string",
      "TargetCount": number,
      "Targets": [
         {
            "Key": "string",
            "Values": [ "string" ]
         }
      ],
      "TimeoutSeconds": number,
      "TriggeredAlarms": [
         {
            "Name": "string",
            "State": "string"
         }
      ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Command

The request as it was received by Systems Manager. Also provides the command ID which can be used future references to this request.

Type: Command object

Errors

For information about the errors that are common to all actions, see Common Error Types.

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

InvalidNotificationConfig

One or more configuration items isn't valid. Verify that a valid Amazon Resource Name (ARN) was provided for an Amazon Simple Notification Service topic.

HTTP Status Code: 400

InvalidOutputFolder

The S3 bucket doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidRole

The role name can't contain invalid characters. Also verify that you specified an IAM role for notifications that includes the required trust policy. For information about configuring the IAM role for Run Command notifications, see Monitoring Systems Manager status changes using Amazon SNS notifications in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node IDs. For example, you sent an document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of SendCommand.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.SendCommand
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T000322Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 153

{
    "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "my-log-group",
        "CloudWatchOutputEnabled": true
    },
    "DocumentName": "AWS-ConfigureCloudWatch",
    "DocumentVersion": "1",
    "InstanceIds": [
        "i-07be1baa4aEXAMPLE",
        "i-017431b35cEXAMPLE",
        "i-09c350ed76EXAMPLE"
    ],
    "MaxConcurrency": "2",
    "MaxErrors": "1",
    "NotificationConfig": {
```

```
        "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
        "NotificationEvents": [
            "Failed",
            "Success"
        ],
        "NotificationType": "Command"
    },
    "OutputS3BucketName": "amzn-s3-demo-bucket",
    "OutputS3KeyPrefix": "my-prefix",
    "OutputS3Region": "us-east-2",
    "Parameters": {
        "string": []
    },
    "TimeoutSeconds": 30
}
```

Sample Response

```
{
    "Command": {
        "CommandId": "b94bf1dc-fe7d-4e88-851d-e85e5EXAMPLE",
        "DocumentName": "AWS-ConfigureCloudWatch",
        "DocumentVersion": "1",
        "Comment": "",
        "ExpiresAfter": 1582250177.7,
        "Parameters": {
            "properties": [
                ""
            ],
            "status": [
                "Enabled"
            ]
        },
        "InstanceIds": [],
        "Targets": [
            {
                "Key": "InstanceIds",
                "Values": [
                    "i-07be1baa4aEXAMPLE",
                    "i-017431b35cEXAMPLE",
                    "i-09c350ed76EXAMPLE"
                ]
```

```
            }
        ],
        "RequestedDateTime": 1582245977.7,
        "Status": "Pending",
        "StatusDetails": "Pending",
        "OutputS3BucketName": "amzn-s3-demo-bucket",
        "OutputS3KeyPrefix": "my-prefix",
        "MaxConcurrency": "2",
        "MaxErrors": "1",
        "TargetCount": 0,
        "CompletedCount": 0,
        "ErrorCount": 0,
        "DeliveryTimedOutCount": 0,
        "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
        "NotificationConfig": {
            "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
            "NotificationEvents": [
                "Failed",
                "Success"
            ],
            "NotificationType": "Command"
        },
        "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "my-log-group",
            "CloudWatchOutputEnabled": true
        }
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartAccessRequest

Starts the workflow for just-in-time node access sessions.

Request Syntax

```
{
   "Reason": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Reason

A brief description explaining why you are requesting access to the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Tags

Key-value pairs of metadata you want to assign to the access request.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Targets

The node you are requesting access to.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: Yes

Response Syntax

```
{
   "AccessRequestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccessRequestId

The ID of the access request.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

AccessDeniedException

The requester doesn't have permissions to perform the requested operation.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceNotFoundException

The specified parameter to be shared could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The request exceeds the service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account.

QuotaCode

The quota code recognized by the AWS Service Quotas service.

ResourceId

The unique ID of the resource referenced in the failed request.

ResourceType

The resource type of the resource referenced in the failed request.

ServiceCode

The code for the AWS service that owns the quota.

HTTP Status Code: 400

ThrottlingException

The request or operation couldn't be performed because the service is throttling requests.

QuotaCode

The quota code recognized by the AWS Service Quotas service.

ServiceCode

The code for the AWS service that owns the quota.

HTTP Status Code: 400

ValidationException

The request isn't valid. Verify that you entered valid contents for the command and try again.

ReasonCode

The reason code for the invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartAssociationsOnce

Runs an association immediately and only one time. This operation can be helpful when troubleshooting associations.

Request Syntax

```
{
   "AssociationIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationIds

The association IDs that you want to run immediately and only one time.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InvalidAssociation

The association isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartAssociationsOnce.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartAssociationsOnce
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T163434Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 60

{
    "AssociationIds": [
        "4332cf28-050d-4fa1-a4df-11b39EXAMPLE"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartAutomationExecution

Initiates execution of an Automation runbook.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "ClientToken": "string",
   "DocumentName": "string",
   "DocumentVersion": "string",
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Mode": "string",
   "Parameters": {
      "string" : [ "string" ]
   },
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "TargetLocations": [
      {
         "Accounts": [ "string" ],
         "ExcludeAccounts": [ "string" ],
         "ExecutionRoleName": "string",
         "IncludeChildOrganizationUnits": boolean,
         "Regions": [ "string" ],
         "TargetLocationAlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
```

```
            "IgnorePollAlarmFailure": boolean
         },
         "TargetLocationMaxConcurrency": "string",
         "TargetLocationMaxErrors": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TargetsMaxConcurrency": "string",
         "TargetsMaxErrors": "string"
      }
   ],
   "TargetLocationsURL": "string",
   "TargetMaps": [
      {
         "string" : [ "string" ]
      }
   ],
   "TargetParameterName": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The CloudWatch alarm you want to apply to your automation.

Type: AlarmConfiguration object

Required: No

ClientToken

User-provided idempotency token. The token must be unique, is case insensitive, enforces the UUID format, and can't be reused.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Required: No

DocumentName

The name of the SSM document to run. This can be a public document or a custom document. To run a shared document belonging to another account, specify the document ARN. For more information about how to use shared documents, see Sharing SSM documents in the *AWS Systems Manager User Guide*.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

DocumentVersion

The version of the Automation runbook to use for this execution.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

MaxConcurrency

The maximum number of targets allowed to run this task in parallel. You can specify a number, such as 10, or a percentage, such as 10%. The default value is `10`.

If both this parameter and the `TargetLocation:TargetsMaxConcurrency` are supplied, `TargetLocation:TargetsMaxConcurrency` takes precedence.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops running the automation on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops running the automation when the fourth error is received. If you specify 0, then the system stops running the automation on additional targets after the first error result is returned. If you run an automation on 50 resources and set max-errors to 10%, then the system stops running the automation on additional targets when the sixth error is received.

Executions that are already running an automation when max-errors is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set max-concurrency to 1 so the executions proceed one at a time.

If this parameter and the `TargetLocation:TargetsMaxErrors` parameter are both supplied, `TargetLocation:TargetsMaxErrors` takes precedence.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Mode

The execution mode of the automation. Valid modes include the following: Auto and Interactive. The default mode is Auto.

Type: String

Valid Values: `Auto | Interactive`

Required: No

Parameters

A key-value map of execution parameters, which match the declared parameters in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Tags

Optional metadata that you assign to a resource. You can specify a maximum of five tags for an automation. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an automation to identify an environment or operating system. In this case, you could specify the following key-value pairs:

- `Key=environment,Value=test`
- `Key=OS,Value=Windows`

> **Note**
>
> The `Array Members` maximum value is reported as 1000. This number includes capacity reserved for internal operations. When calling the `StartAutomationExecution` action, you can specify a maximum of 5 tags. You can, however, use the AddTagsToResource action to add up to a total of 50 tags to an existing automation configuration.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

TargetLocations

A location is a combination of AWS Regions and/or AWS accounts where you want to run the automation. Use this operation to start an automation in multiple AWS Regions and multiple AWS accounts. For more information, see Running automations in multiple AWS Regions and accounts in the *AWS Systems Manager User Guide*.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetLocationsURL

Specify a publicly accessible URL for a file that contains the `TargetLocations` body. Currently, only files in presigned Amazon S3 buckets are supported.

Type: String

Pattern: `^https:\/\/[-a-zA-Z0-9@:%._\+~#=]{1,253}\.s3(\.[a-z\d-]{9,16})?\.amazonaws\.com\/.{1,2000}`

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The name of the parameter used as the target resource for the rate-controlled execution. Required if you specify targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

A key-value mapping to target resources. Required if you specify TargetParameterName.

If both this parameter and the `TargetLocation:Targets` parameter are supplied, `TargetLocation:Targets` takes precedence.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{
   "AutomationExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecutionId

The unique ID of a newly scheduled automation execution.

Type: String

Length Constraints: Fixed length of 36.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationDefinitionNotFoundException

An Automation runbook with the specified name couldn't be found.

HTTP Status Code: 400

AutomationDefinitionVersionNotFoundException

An Automation runbook with the specified name and version couldn't be found.

HTTP Status Code: 400

AutomationExecutionLimitExceededException

The number of simultaneously running Automation executions exceeded the allowable limit.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationExecutionParametersException

The supplied parameters for invoking the specified Automation runbook are incorrect. For example, they may not match the set of parameters permitted for the specified Automation document.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartAutomationExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T162110Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 86

{
    "DocumentName": "Example",
    "Parameters": {
        "InstanceId": [
            "i-02573cafcfEXAMPLE"
        ]
    }
}
```

Sample Response

```
{
    "AutomationExecutionId": "832a6fba-f4f0-4b2a-ab85-587adEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartChangeRequestExecution

> **Important**
>
> AWS Systems Manager Change Manager is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see AWS Systems Manager Change Manager availability change.

Creates a change request for Change Manager. The Automation runbooks specified in the change request run only after all required approvals for the change request have been received.

Request Syntax

```
{
   "AutoApprove": boolean,
   "ChangeDetails": "string",
   "ChangeRequestName": "string",
   "ClientToken": "string",
   "DocumentName": "string",
   "DocumentVersion": "string",
   "Parameters": {
      "string" : [ "string" ]
   },
   "Runbooks": [
      {
         "DocumentName": "string",
         "DocumentVersion": "string",
         "MaxConcurrency": "string",
         "MaxErrors": "string",
         "Parameters": {
            "string" : [ "string" ]
         },
         "TargetLocations": [
            {
               "Accounts": [ "string" ],
               "ExcludeAccounts": [ "string" ],
               "ExecutionRoleName": "string",
               "IncludeChildOrganizationUnits": boolean,
               "Regions": [ "string" ],
               "TargetLocationAlarmConfiguration": {
```

```
                  "Alarms": [
                     {
                        "Name": "string"
                     }
                  ],
                  "IgnorePollAlarmFailure": boolean
               },
               "TargetLocationMaxConcurrency": "string",
               "TargetLocationMaxErrors": "string",
               "Targets": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ],
               "TargetsMaxConcurrency": "string",
               "TargetsMaxErrors": "string"
            }
         ],
         "TargetMaps": [
            {
               "string" : [ "string" ]
            }
         ],
         "TargetParameterName": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ]
      }
   ],
   "ScheduledEndTime": number,
   "ScheduledTime": number,
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AutoApprove

Indicates whether the change request can be approved automatically without the need for manual approvals.

If `AutoApprovable` is enabled in a change template, then setting `AutoApprove` to `true` in `StartChangeRequestExecution` creates a change request that bypasses approver review.

> **Note**
>
> Change Calendar restrictions are not bypassed in this scenario. If the state of an associated calendar is `CLOSED`, change freeze approvers must still grant permission for this change request to run. If they don't, the change won't be processed until the calendar state is again `OPEN`.

Type: Boolean

Required: No

ChangeDetails

User-provided details about the change. If no details are provided, content specified in the **Template information** section of the associated change template is added.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

ChangeRequestName

The name of the change request associated with the runbook workflow to be run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

ClientToken

The user-provided idempotency token. The token must be unique, is case insensitive, enforces the UUID format, and can't be reused.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Required: No

DocumentName

The name of the change template document to run during the runbook workflow.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

DocumentVersion

The version of the change template document to run during the runbook workflow.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Parameters

A key-value map of parameters that match the declared parameters in the change template document.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Runbooks

Information about the Automation runbooks that are run during the runbook workflow.

> **Note**
>
> The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of Runbook objects

Array Members: Fixed number of 1 item.

Required: Yes

ScheduledEndTime

The time that the requester expects the runbook workflow related to the change request to complete. The time is an estimate only that the requester provides for reviewers.

Type: Timestamp

Required: No

ScheduledTime

The date and time specified in the change request to run the Automation runbooks.

> **Note**
>
> The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Timestamp

Required: No

Tags

Optional metadata that you assign to a resource. You can specify a maximum of five tags for a change request. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a change request to identify an environment or target AWS Region. In this case, you could specify the following key-value pairs:

- `Key=Environment,Value=Production`
- `Key=Region,Value=us-east-2`

> **Note**
>
> The `Array Members` maximum value is reported as 1000. This number includes capacity reserved for internal operations. When calling the `StartChangeRequestExecution` action, you can specify a maximum of 5 tags. You can, however, use the AddTagsToResource action to add up to a total of 50 tags to an existing change request configuration.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
   "AutomationExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecutionId

The unique ID of a runbook workflow operation. (A runbook workflow is a type of Automation operation.)

Type: String

Length Constraints: Fixed length of 36.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationDefinitionNotApprovedException

Indicates that the Change Manager change template used in the change request was rejected or is still in a pending state.

HTTP Status Code: 400

AutomationDefinitionNotFoundException

An Automation runbook with the specified name couldn't be found.

HTTP Status Code: 400

AutomationDefinitionVersionNotFoundException

An Automation runbook with the specified name and version couldn't be found.

HTTP Status Code: 400

AutomationExecutionLimitExceededException

The number of simultaneously running Automation executions exceeded the allowable limit.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationExecutionParametersException

The supplied parameters for invoking the specified Automation runbook are incorrect. For example, they may not match the set of parameters permitted for the specified Automation document.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartChangeRequestExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartChangeRequestExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.12 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.start-change-request-execution
X-Amz-Date: 20240820T192759Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240820/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 1247

{
    "ChangeRequestName": "MyChangeRequest",
    "DocumentName": "AWS-HelloWorldChangeTemplate",
    "DocumentVersion": "$DEFAULT",
    "ScheduledTime": 1640833200,
    "ScheduledEndTime": 1640833500,
    "Tags": [
        {
```

```
            "Key": "Purpose",
            "Value": "Testing"
        }
    ],
    "Parameters": {
        "Approver": [
            "JohnDoe"
        ],
        "ApproverType": [
            "IamUser"
        ],
        "ApproverSnsTopicArn": [
            "arn:aws:sns:us-east-2:111122223333:MyNotificationTopic"
        ]
    },
    "Runbooks": [
        {
            "DocumentName": "AWS-HelloWorld",
            "DocumentVersion": "1",
            "MaxConcurrency": "1",
            "MaxErrors": "1",
            "Parameters": {
                "AutomationAssumeRole": [
                    "arn:aws:iam::111122223333:role/MyChangeManagerAssumeRole"
                ]
            }
        }
    ],
    "ChangeDetails": "### Document Name: HelloWorldChangeTemplate\n\n## What does
 this document do?\nThis change template demonstrates the feature set available
 for creating change templates for Change Manager. This template starts a Runbook
 workflow for the Automation document called AWS-HelloWorld.\n\n## Input Parameters
\n* ApproverSnsTopicArn: (Required) Amazon Simple Notification Service ARN for
 approvers.\n* Approver: (Required) The name of the approver to send this request
 to.\n* ApproverType: (Required) The type of reviewer.\n  * Allowed Values: IamUser,
 IamGroup, IamRole, SSOGroup, SSOUser\n\n## Output Parameters\nThis document has no
 outputs \n"
}
```

Sample Response

```
{
    "AutomationExecutionId": "dddd1c6c-849d-4ee0-acc1-0be9dEXAMPLE"
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartExecutionPreview

Initiates the process of creating a preview showing the effects that running a specified Automation runbook would have on the targeted resources.

Request Syntax

```
{
   "DocumentName": "string",
   "DocumentVersion": "string",
   "ExecutionInputs": { ... }
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentName

The name of the Automation runbook to run. The result of the execution preview indicates what the impact would be of running this runbook.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

DocumentVersion

The version of the Automation runbook to run. The default value is `$DEFAULT`.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

ExecutionInputs

Information about the inputs that can be specified for the preview operation.

Type: ExecutionInputs object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
{
   "ExecutionPreviewId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExecutionPreviewId

The ID of the execution preview generated by the system.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ValidationException

The request isn't valid. Verify that you entered valid contents for the command and try again.

ReasonCode

The reason code for the invalid request.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartExecutionPreview.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartExecutionPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20241125T162110Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 86

{
    "DocumentName": "MyExampleDocument"
}
```

Example

This example illustrates one usage of StartExecutionPreview.

Sample Response

```
{
    "ExecutionPreviewId": "2f27d6e5-9676-4708-b8bd-aef0aEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartSession

Initiates a connection to a target (for example, a managed node) for a Session Manager session. Returns a URL and token that can be used to open a WebSocket connection for sending input and receiving outputs.

> **Note**
>
> AWS CLI usage: `start-session` is an interactive command that requires the Session Manager plugin to be installed on the client machine making the call. For information, see Install the Session Manager plugin for the AWS CLI in the *AWS Systems Manager User Guide*.
> AWS Tools for PowerShell usage: Start-SSMSession isn't currently supported by AWS Tools for PowerShell on Windows local machines.

Request Syntax

```
{
   "DocumentName": "string",
   "Parameters": {
      "string" : [ "string" ]
   },
   "Reason": "string",
   "Target": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentName

The name of the SSM document you want to use to define the type of session, input parameters, or preferences for the session. For example, `SSM-SessionManagerRunShell`. You can call the GetDocument API to verify the document exists before attempting to start a

session. If no document name is provided, a shell to the managed node is launched by default. For more information, see Start a session in the *AWS Systems Manager User Guide*.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Parameters

The values you want to specify for the parameters defined in the Session document. For more information about these parameters, see Create a Session Manager preferences document in the *AWS Systems Manager User Guide*.

Type: String to array of strings map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Reason

The reason for connecting to the instance. This value is included in the details for the Amazon CloudWatch Events event created when you start the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^.{1,256}$`

Required: No

Target

The managed node to connect to for the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

Response Syntax

```
{
   "SessionId": "string",
   "StreamUrl": "string",
   "TokenValue": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SessionId

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

StreamUrl

A URL back to SSM Agent on the managed node that the Session Manager client uses to send commands and receive output from the node. Format: `wss://ssmmessages.`**`region`**`.amazonaws.com/v1/data-channel/`**`session-id`**`?stream=(input|output)`

region represents the Region identifier for an AWS Region supported by AWS Systems Manager, such as `us-east-2` for the US East (Ohio) Region. For a list of supported **region** values, see the **Region** column in Systems Manager service endpoints in the *Amazon Web Services General Reference*.

session-id represents the ID of a Session Manager session, such as `1a2b3c4dEXAMPLE`.

Type: String

TokenValue

An encrypted token value containing session and caller information. This token is used to authenticate the connection to the managed node, and is valid only long enough to ensure the connection is successful. Never share your session's token.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

TargetNotConnected

The specified target managed node for the session isn't fully configured for use with Session Manager. For more information, see Setting up Session Manager in the *AWS Systems Manager User Guide*. This error is also returned if you attempt to start a session on a managed node that is located in a different account or Region

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartSession.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T181823Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 33

{
    "Target": "i-02573cafcfEXAMPLE"
}
```

Sample Response

```
{
    "SessionId": "John-Doe-0dc5b7af96EXAMPLE",
    "StreamUrl": "wss://ssmmessages.us-east-2.amazonaws.com/v1/data-channel/John-
Doe-0dc5b7af96EXAMPLE?role=publish_subscribe",
    "TokenValue": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE/39c3b3042cd2aEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

StopAutomationExecution

Stop an Automation that is currently running.

Request Syntax

```
{
   "AutomationExecutionId": "string",
   "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AutomationExecutionId

The execution ID of the Automation to stop.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Type

The stop request type. Valid types include the following: Cancel and Complete. The default type is Cancel.

Type: String

Valid Values: `Complete | Cancel`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationStatusUpdateException

The specified update status operation isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StopAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StopAutomationExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T171100Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
```

```
    "AutomationExecutionId": "f7d1f82d-6cde-4f7a-aa53-d485bEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

TerminateSession

Permanently ends a session and closes the data connection between the Session Manager client and SSM Agent on the managed node. A terminated session can't be resumed.

Request Syntax

```
{
   "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SessionId

The ID of the session to terminate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: Yes

Response Syntax

```
{
   "SessionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SessionId

The ID of the session that has been terminated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of TerminateSession.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.TerminateSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240221T182708Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

Sample Response

```
{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UnlabelParameterVersion

Remove a label or labels from a parameter.

Parameter names can't contain spaces. The service removes any spaces specified for the beginning or end of a parameter name. If the specified name for a parameter contains spaces between characters, the request fails with a `ValidationException` error.

Request Syntax

```
{
   "Labels": [ "string" ],
   "Name": "string",
   "ParameterVersion": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Labels

One or more labels to delete from the specified parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Name

The name of the parameter from which you want to delete one or more labels.

> **Note**
>
> You can't enter the Amazon Resource Name (ARN) for a parameter, only the parameter name itself.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

ParameterVersion

The specific version of the parameter which you want to delete one or more labels from. If it isn't present, the call will fail.

Type: Long

Required: Yes

Response Syntax

```
{
   "InvalidLabels": [ "string" ],
   "RemovedLabels": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidLabels

The labels that aren't attached to the given parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

RemovedLabels

A list of all labels deleted from the parameter.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

> **Note**
>
> For the `DeleteParameter` and `GetParameter` actions, if the specified parameter doesn't exist, the `ParameterNotFound` exception is *not* recorded in AWS CloudTrail event logs.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UnlabelParameterVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UnlabelParameterVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240712T183221Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "Name": "MyParameter",
    "ParameterVersion": 2,
    "Labels": [
        "label"
    ]
}
```

Sample Response

```
{
    "InvalidLabels": [],
    "RemovedLabels": [
        "label"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateAssociation

Updates an association. You can update the association name and version, the document version, schedule, parameters, and Amazon Simple Storage Service (Amazon S3) output. When you call `UpdateAssociation`, the system removes all optional parameters from the request and overwrites the association with null values for those parameters. This is by design. You must specify all optional parameters in the call, even if you are not changing the parameters. This includes the `Name` parameter. Before calling this API action, we recommend that you call the DescribeAssociation API operation and make a note of all optional parameters required for your `UpdateAssociation` call.

In order to call this API operation, a user, group, or role must be granted permission to call the DescribeAssociation API operation. If you don't have permission to call `DescribeAssociation`, then you receive the following error: `An error occurred (AccessDeniedException) when calling the UpdateAssociation operation: User: <user_arn> isn't authorized to perform: ssm:DescribeAssociation on resource: <resource_arn>`

> **Important**
>
> When you update an association, the association immediately runs against the specified targets. You can add the `ApplyOnlyAtCronInterval` parameter to run the association during the next schedule run.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "ApplyOnlyAtCronInterval": boolean,
   "AssociationId": "string",
   "AssociationName": "string",
   "AssociationVersion": "string",
   "AutomationTargetParameterName": "string",
```

```
   "CalendarNames": [ "string" ],
   "ComplianceSeverity": "string",
   "DocumentVersion": "string",
   "Duration": number,
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "OutputLocation": {
      "S3Location": {
         "OutputS3BucketName": "string",
         "OutputS3KeyPrefix": "string",
         "OutputS3Region": "string"
      }
   },
   "Parameters": {
      "string" : [ "string" ]
   },
   "ScheduleExpression": "string",
   "ScheduleOffset": number,
   "SyncCompliance": "string",
   "TargetLocations": [
      {
         "Accounts": [ "string" ],
         "ExcludeAccounts": [ "string" ],
         "ExecutionRoleName": "string",
         "IncludeChildOrganizationUnits": boolean,
         "Regions": [ "string" ],
         "TargetLocationAlarmConfiguration": {
            "Alarms": [
               {
                  "Name": "string"
               }
            ],
            "IgnorePollAlarmFailure": boolean
         },
         "TargetLocationMaxConcurrency": "string",
         "TargetLocationMaxErrors": "string",
         "Targets": [
            {
               "Key": "string",
               "Values": [ "string" ]
            }
         ],
         "TargetsMaxConcurrency": "string",
```

```
         "TargetsMaxErrors": "string"
      }
   ],
   "TargetMaps": [
      {
         "string" : [ "string" ]
      }
   ],
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

ApplyOnlyAtCronInterval

By default, when you update an association, the system runs it immediately after it is updated and then according to the schedule you specified. Specify `true` for `ApplyOnlyAtCronInterval` if you want the association to run only according to the schedule you specified.

If you chose this option when you created an association and later you edit that association or you make changes to the Automation runbook or SSM document on which that association is based, State Manager applies the association at the next specified cron interval. For example, if you chose the `Latest` version of an SSM document when you created an association and you edit the association by choosing a different document version on the Documents page,

State Manager applies the association at the next specified cron interval if you previously set `ApplyOnlyAtCronInterval` to `true`. If this option wasn't selected, State Manager immediately runs the association.

For more information, see Understanding when associations are applied to resources and About target updates with Automation runbooks in the *AWS Systems Manager User Guide*.

This parameter isn't supported for rate expressions.

You can reset this parameter. To do so, specify the `no-apply-only-at-cron-interval` parameter when you update the association from the command line. This parameter forces the association to run immediately after updating it and according to the interval specified.

Type: Boolean

Required: No

AssociationId

The ID of the association you want to update.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

AssociationName

The name of the association that you want to update.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AssociationVersion

This parameter is provided for concurrency control purposes. You must specify the latest association version in the service. If you want to ensure that this request succeeds, either specify `$LATEST`, or omit this parameter.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

AutomationTargetParameterName

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a tool in AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents you want to gate your associations under. The associations only run when that change calendar is open. For more information, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Type: Array of strings

Required: No

ComplianceSeverity

The severity level to assign to the association.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED`

Required: No

DocumentVersion

The document version you want update for the association.

> **Important**
>
> State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs

the `default` version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared form another account, you must set the document version to `default`.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours the association can run before it is canceled. Duration applies to associations that are currently running, and any pending and in progress commands on all targets. If a target was taken offline for the association to run, it is made available again immediately, without a reboot.

The `Duration` parameter applies only when both these conditions are true:

- The association for which you specify a duration is cancelable according to the parameters of the SSM command document or Automation runbook associated with this execution.
- The command specifies the `ApplyOnlyAtCronInterval` parameter, which means that the association doesn't run immediately after it is updated, but only according to the specified schedule.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next

association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The name of the SSM Command document or Automation runbook that contains the configuration information for the managed node.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another account.

For Systems Manager document (SSM document) that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:aws:ssm:region:account-id:document/document-name`

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

OutputLocation

An S3 bucket where you want to store the results of this request.

Type: InstanceAssociationOutputLocation object

Required: No

Parameters

The parameters you want to update for the association. If you create a parameter using Parameter Store, a tool in AWS Systems Manager, you can reference the parameter using `{{ssm:parameter-name}}`.

Type: String to array of strings map

Required: No

ScheduleExpression

The cron expression used to schedule the association that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association. For example, if you specified a cron schedule of `cron(0 0 ? * THU#2 *)`, you could specify an offset of 3 to run the association each Sunday after the second Thursday of the month. For more information about cron schedules for associations, see Reference: Cron and rate expressions for Systems Manager in the *AWS Systems Manager User Guide*.

> **Note**
>
> To use offsets, you must specify the `ApplyOnlyAtCronInterval` parameter. This option tells the system not to run an association immediately after you create it.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the PutComplianceItems API operation. In this case, compliance data isn't managed by State Manager, a tool in AWS Systems Manager. It is managed by your direct call to the PutComplianceItems API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

TargetLocations

A location is a combination of AWS Regions and AWS accounts where you want to run the association. Use this action to update an association in multiple Regions and multiple accounts.

> **Note**
>
> `IncludeChildOrganizationUnits`, `ExcludeAccounts`, `TargetsMaxErrors`, `TargetsMaxConcurrency`, `Targets`, `TargetLocationAlarmConfiguration` parameters are not supported by State Manager.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets of the association.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{
   "AssociationDescription": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
      },
      "ApplyOnlyAtCronInterval": boolean,
      "AssociationId": "string",
      "AssociationName": "string",
      "AssociationVersion": "string",
      "AutomationTargetParameterName": "string",
      "CalendarNames": [ "string" ],
      "ComplianceSeverity": "string",
      "Date": number,
      "DocumentVersion": "string",
      "Duration": number,
      "InstanceId": "string",
      "LastExecutionDate": number,
      "LastSuccessfulExecutionDate": number,
      "LastUpdateAssociationDate": number,
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "Name": "string",
      "OutputLocation": {
         "S3Location": {
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
         }
      },
      "Overview": {
         "AssociationStatusAggregatedCount": {
            "string" : number
         },
         "DetailedStatus": "string",
         "Status": "string"
      },
```

```
      "Parameters": {
         "string" : [ "string" ]
      },
      "ScheduleExpression": "string",
      "ScheduleOffset": number,
      "Status": {
         "AdditionalInfo": "string",
         "Date": number,
         "Message": "string",
         "Name": "string"
      },
      "SyncCompliance": "string",
      "TargetLocations": [
         {
            "Accounts": [ "string" ],
            "ExcludeAccounts": [ "string" ],
            "ExecutionRoleName": "string",
            "IncludeChildOrganizationUnits": boolean,
            "Regions": [ "string" ],
            "TargetLocationAlarmConfiguration": {
               "Alarms": [
                  {
                     "Name": "string"
                  }
               ],
               "IgnorePollAlarmFailure": boolean
            },
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string",
            "Targets": [
               {
                  "Key": "string",
                  "Values": [ "string" ]
               }
            ],
            "TargetsMaxConcurrency": "string",
            "TargetsMaxErrors": "string"
         }
      ],
      "TargetMaps": [
         {
            "string" : [ "string" ]
         }
      ],
```

```
      "Targets": [
         {
            "Key": "string",
            "Values": [ "string" ]
         }
      ],
      "TriggeredAlarms": [
         {
            "Name": "string",
            "State": "string"
         }
      ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription

The description of the association that was updated.

Type: AssociationDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

AssociationVersionLimitExceeded

You have reached the maximum number versions allowed for an association. Each association has a limit of 1,000 versions.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAssociationVersion

The version you specified isn't valid. Use ListAssociationVersions to view all versions of an association according to the association ID. Or, use the $LATEST parameter to view the latest version of the association.

HTTP Status Code: 400

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

InvalidUpdate

The update isn't valid.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T171857Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 87
```

```
{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "ComplianceSeverity": "HIGH"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
        "AssociationVersion": "2",
        "ComplianceSeverity": "HIGH",
        "Date": 1561053271.583,
        "DocumentVersion": "$DEFAULT",
        "LastExecutionDate": 1582037438.692,
        "LastSuccessfulExecutionDate": 1582037438.692,
        "LastUpdateAssociationDate": 1585156739.103,
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "DetailedStatus": "Creating",
            "Status": "Pending"
        },
        "Targets": [
            {
                "Key": "tag:ssm",
                "Values": [
                    "true"
                ]
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateAssociationStatus

Updates the status of the AWS Systems Manager document (SSM document) associated with the specified managed node.

`UpdateAssociationStatus` is primarily used by the AWS Systems Manager Agent (SSM Agent) to report status updates about your associations and is only used for associations created with the `InstanceId` legacy parameter.

Request Syntax

```
{
   "AssociationStatus": {
      "AdditionalInfo": "string",
      "Date": number,
      "Message": "string",
      "Name": "string"
   },
   "InstanceId": "string",
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AssociationStatus

The association status.

Type: AssociationStatus object

Required: Yes

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

Response Syntax

```
{
   "AssociationDescription": {
      "AlarmConfiguration": {
         "Alarms": [
            {
               "Name": "string"
            }
         ],
         "IgnorePollAlarmFailure": boolean
      },
      "ApplyOnlyAtCronInterval": boolean,
      "AssociationId": "string",
      "AssociationName": "string",
      "AssociationVersion": "string",
      "AutomationTargetParameterName": "string",
      "CalendarNames": [ "string" ],
      "ComplianceSeverity": "string",
      "Date": number,
      "DocumentVersion": "string",
      "Duration": number,
      "InstanceId": "string",
      "LastExecutionDate": number,
      "LastSuccessfulExecutionDate": number,
      "LastUpdateAssociationDate": number,
      "MaxConcurrency": "string",
      "MaxErrors": "string",
      "Name": "string",
      "OutputLocation": {
         "S3Location": {
            "OutputS3BucketName": "string",
```

```
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
         }
      },
      "Overview": {
         "AssociationStatusAggregatedCount": {
            "string" : number
         },
         "DetailedStatus": "string",
         "Status": "string"
      },
      "Parameters": {
         "string" : [ "string" ]
      },
      "ScheduleExpression": "string",
      "ScheduleOffset": number,
      "Status": {
         "AdditionalInfo": "string",
         "Date": number,
         "Message": "string",
         "Name": "string"
      },
      "SyncCompliance": "string",
      "TargetLocations": [
         {
            "Accounts": [ "string" ],
            "ExcludeAccounts": [ "string" ],
            "ExecutionRoleName": "string",
            "IncludeChildOrganizationUnits": boolean,
            "Regions": [ "string" ],
            "TargetLocationAlarmConfiguration": {
               "Alarms": [
                  {
                     "Name": "string"
                  }
               ],
               "IgnorePollAlarmFailure": boolean
            },
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string",
            "Targets": [
               {
                  "Key": "string",
                  "Values": [ "string" ]
```

```
                }
            ],
            "TargetsMaxConcurrency": "string",
            "TargetsMaxErrors": "string"
         }
      ],
      "TargetMaps": [
         {
            "string" : [ "string" ]
         }
      ],
      "Targets": [
         {
            "Key": "string",
            "Values": [ "string" ]
         }
      ],
      "TriggeredAlarms": [
         {
            "Name": "string",
            "State": "string"
         }
      ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription

Information about the association.

Type: AssociationDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

StatusUnchanged

The updated status is the same as the current status.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateDocument

Updates one or more values for an SSM document.

Request Syntax

```
{
   "Attachments": [
      {
         "Key": "string",
         "Name": "string",
         "Values": [ "string" ]
      }
   ],
   "Content": "string",
   "DisplayName": "string",
   "DocumentFormat": "string",
   "DocumentVersion": "string",
   "Name": "string",
   "TargetType": "string",
   "VersionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Attachments

A list of key-value pairs that describe attachments to a version of a document.

Type: Array of AttachmentsSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Content

A valid JSON or YAML string.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

DisplayName

The friendly name of the SSM document that you want to update. This value can differ for each version of the document. If you don't specify a value for this parameter in your request, the existing value is applied to the new document version.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

Required: No

DocumentFormat

Specify the document format for the new document version. Systems Manager supports JSON and YAML documents. JSON is the default format.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentVersion

The version of the document that you want to update. Currently, Systems Manager supports updating only the latest version of the document. You can specify the version number of the latest version or use the `$LATEST` variable.

> **Note**
>
> If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specifed the `apply-only-at-cron-interval` parameter.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the SSM document that you want to update.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

TargetType

Specify a new target type for the document.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^\/[\w\.\-\:\/]*$`

Required: No

VersionName

An optional field specifying the version of the artifact you are updating with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Syntax

```
{
   "DocumentDescription": {
      "ApprovedVersion": "string",
      "AttachmentsInformation": [
         {
            "Name": "string"
         }
      ],
      "Author": "string",
```

```
   "Category": [ "string" ],
   "CategoryEnum": [ "string" ],
   "CreatedDate": number,
   "DefaultVersion": "string",
   "Description": "string",
   "DisplayName": "string",
   "DocumentFormat": "string",
   "DocumentType": "string",
   "DocumentVersion": "string",
   "Hash": "string",
   "HashType": "string",
   "LatestVersion": "string",
   "Name": "string",
   "Owner": "string",
   "Parameters": [
      {
         "DefaultValue": "string",
         "Description": "string",
         "Name": "string",
         "Type": "string"
      }
   ],
   "PendingReviewVersion": "string",
   "PlatformTypes": [ "string" ],
   "Requires": [
      {
         "Name": "string",
         "RequireType": "string",
         "Version": "string",
         "VersionName": "string"
      }
   ],
   "ReviewInformation": [
      {
         "ReviewedTime": number,
         "Reviewer": "string",
         "Status": "string"
      }
   ],
   "ReviewStatus": "string",
   "SchemaVersion": "string",
   "Sha1": "string",
   "Status": "string",
   "StatusInformation": "string",
```

```
      "Tags": [
         {
            "Key": "string",
            "Value": "string"
         }
      ],
      "TargetType": "string",
      "VersionName": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentDescription

A description of the document that was updated.

Type: DocumentDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

DocumentVersionLimitExceeded

The document has too many versions. Delete one or more document versions and try again.

HTTP Status Code: 400

DuplicateDocumentContent

The content of the association document matches another document. Change the content of the document and try again.

HTTP Status Code: 400

DuplicateDocumentVersionName

The version name has already been used in this document. Specify a different version name, and then try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentContent

The content for the document isn't valid.

Message

A description of the validation error.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T180432Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 953

{
    "Content": "---\ndescription: \"CreateImage\"\nschemaVersion: '0.3'\nassumeRole:
 \"{{ AutomationAssumeRole }}\"--truncated--",
    "Name": "CreateImage",
    "DocumentVersion": "$LATEST",
    "DocumentFormat": "YAML"
}
```

Sample Response

```
{
    "DocumentDescription": {
        "CreatedDate": 1585159474.781,
        "DefaultVersion": "1",
        "Description": "Example",
```

```
        "DisplayName": "ExampleDoc",
        "DocumentFormat": "YAML",
        "DocumentType": "Automation",
        "DocumentVersion": "2",
        "Hash": "ff7430df11be00b0593ac116b2570d488bd37a2a2fa7ddf49da67976eEXAMPLE",
        "HashType": "Sha256",
        "LatestVersion": "2",
        "Name": "CreateImage",
        "Owner": "111122223333",
        "Parameters": [
            {
                "DefaultValue": "",
                "Description": "(Optional) The ARN of the role that allows Automation
 to perform the actions on your behalf. If no role is specified, Systems Manager
 Automation uses your IAM permissions to execute this document.",
                "Name": "AutomationAssumeRole",
                "Type": "String"
            },
            {
                "DefaultValue": "",
                "Description": "(Required) The Instance Id whose root EBS volume you
 want to restore the latest Snapshot.",
                "Name": "InstanceId",
                "Type": "String"
            }
        ],
        "PlatformTypes": [
            "Windows",
            "Linux"
        ],
        "SchemaVersion": "0.3",
        "Status": "Updating",
        "Tags": []
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateDocumentDefaultVersion

Set the default version of a document.

> **Note**
>
> If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specifed the `apply-only-at-cron-interval` parameter.

Request Syntax

```
{
   "DocumentVersion": "string",
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentVersion

The version of a custom document that you want to set as the default version.

Type: String

Pattern: `(^[1-9][0-9]*$)`

Required: Yes

Name

The name of a custom document that you want to set as the default version.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

Response Syntax

```
{
   "Description": {
      "DefaultVersion": "string",
      "DefaultVersionName": "string",
      "Name": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The description of a custom document that you want to set as the default version.

Type: DocumentDefaultVersionDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateDocumentDefaultVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocumentDefaultVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T183926Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 47

{
    "Name": "Example",
    "DocumentVersion": "2"
}
```

Sample Response

```
{
    "Description": {
```

```
        "DefaultVersion": "2",
        "Name": "Example"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateDocumentMetadata

> **Important**
>
> AWS Systems Manager Change Manager is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see AWS Systems Manager Change Manager availability change.

Updates information related to approval reviews for a specific version of a change template in Change Manager.

Request Syntax

```
{
   "DocumentReviews": {
      "Action": "string",
      "Comment": [
         {
            "Content": "string",
            "Type": "string"
         }
      ]
   },
   "DocumentVersion": "string",
   "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DocumentReviews

The change template review details to update.

Type: DocumentReviews object

Required: Yes

DocumentVersion

The version of a change template in which to update approval metadata.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the change template for which a version's metadata is to be updated.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

Message

The SSM document doesn't exist or the document isn't available to the user. This exception can be issued by various API operations.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateDocumentMetadata.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocumentMetadata
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240730T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240730/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68

{
    "DocumentReviews": [
        {
            "Action": "Approve",
```

```
            "Comment": [
                {
                    "Type": "Comment",
                    "Content": "Approved!"
                }
            ]
        }
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateMaintenanceWindow

Updates an existing maintenance window. Only specified parameters are modified.

> **Note**
>
> The value you specify for `Duration` determines the specific end time for the maintenance window based on the time it begins. No maintenance window tasks are permitted to start after the resulting endtime minus the number of hours you specify for `Cutoff`. For example, if the maintenance window starts at 3 PM, the duration is three hours, and the value you specify for `Cutoff` is one hour, no maintenance window tasks can start after 5 PM.

Request Syntax

```
{
   "AllowUnassociatedTargets": boolean,
   "Cutoff": number,
   "Description": "string",
   "Duration": number,
   "Enabled": boolean,
   "EndDate": "string",
   "Name": "string",
   "Replace": boolean,
   "Schedule": "string",
   "ScheduleOffset": number,
   "ScheduleTimezone": "string",
   "StartDate": "string",
   "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AllowUnassociatedTargets

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

Required: No

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: No

Description

An optional description for the update request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

Enabled

Whether the maintenance window is enabled.

Type: Boolean

Required: No

EndDate

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become inactive. `EndDate` allows you to set a date and time in the future when the maintenance window will no longer run.

Type: String

Required: No

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Replace

If `True`, then all fields that are required by the CreateMaintenanceWindow operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

The number of days to wait after the date and time specified by a cron expression before running the maintenance window.

For example, the following cron expression schedules a maintenance window to run the third Tuesday of every month at 11:30 PM.

```
cron(30 23 ? * TUE#3 *)
```

If the schedule offset is 2, the maintenance window won't run until two days later.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the Time Zone Database on the IANA website.

Type: String

Required: No

StartDate

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become active. `StartDate` allows you to delay activation of the maintenance window until the specified future date.

> **Note**
>
> When using a rate schedule, if you provide a start date that occurs in the past, the current date and time are used as the start date.

Type: String

Required: No

WindowId

The ID of the maintenance window to update.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{
   "AllowUnassociatedTargets": boolean,
   "Cutoff": number,
   "Description": "string",
   "Duration": number,
   "Enabled": boolean,
   "EndDate": "string",
   "Name": "string",
   "Schedule": "string",
   "ScheduleOffset": number,
   "ScheduleTimezone": "string",
   "StartDate": "string",
   "WindowId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AllowUnassociatedTargets

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Description

An optional description of the update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Enabled

Whether the maintenance window is enabled.

Type: Boolean

EndDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive. The maintenance window won't run after this specified time.

Type: String

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ScheduleOffset

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the Time Zone Database on the IANA website.

Type: String

StartDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active. The maintenance window won't run before this specified time.

Type: String

WindowId

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdateMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 160
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindow
X-Amz-Date: 20240312T203703Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Duration": 10,
    "WindowId": "mw-0c50858d01EXAMPLE",
    "Name": "Default-Maintenance-Window",
    "Description": "Standard maintenance windows for production servers"
}
```

Sample Response

```
{
    "AllowUnassociatedTargets": true,
```

```
    "Cutoff": 4,
    "Description": "Standard maintenance windows for production servers",
    "Duration": 10,
    "Enabled": true,
    "Name": "Default-Maintenance-Window",
    "Schedule": "rate(3 minutes)",
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateMaintenanceWindowTarget

Modifies the target of an existing maintenance window. You can change the following:

- Name
- Description
- Owner
- IDs for an ID target
- Tags for a Tag target
- From any supported tag type to another. The three supported tag types are ID target, Tag target, and resource group. For more information, see Target.

> **Note**
>
> If a parameter is null, then the corresponding field isn't modified.

Request Syntax

```
{
   "Description": "string",
   "Name": "string",
   "OwnerInformation": "string",
   "Replace": boolean,
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "WindowId": "string",
   "WindowTargetId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Description

An optional description for the update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

A name for the update.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

OwnerInformation

User-provided value that will be included in any Amazon CloudWatch Events events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Replace

If `True`, then all fields that are required by the RegisterTargetWithMaintenanceWindow operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

Targets

The targets to add or replace.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

WindowId

The maintenance window ID with which to modify the target.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

WindowTargetId

The target ID to modify.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "Description": "string",
   "Name": "string",
   "OwnerInformation": "string",
   "Targets": [
```

```
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "WindowId": "string",
   "WindowTargetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The updated description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Name

The updated name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

OwnerInformation

The updated owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Targets

The updated targets.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

WindowId

The maintenance window ID specified in the update request.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

WindowTargetId

The target ID specified in the update request.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdateMaintenanceWindowTarget.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindowTarget
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T005329Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 233

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "Name": "MyNewTaskName",
    "Description": "My new task description"
}
```

Sample Response

```
{
    "Description": "My new task description",
    "Name": "MyNewTaskName",
    "Targets": [
        {
            "Key": "InstanceIds",
```

```
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateMaintenanceWindowTask

Modifies a task assigned to a maintenance window. You can't change the task type, but you can change the following values:

- `TaskARN`. For example, you can change a `RUN_COMMAND` task from `AWS-RunPowerShellScript` to `AWS-RunShellScript`.
- `ServiceRoleArn`
- `TaskInvocationParameters`
- `Priority`
- `MaxConcurrency`
- `MaxErrors`

Note

One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see Registering maintenance window tasks without targets in the *AWS Systems Manager User Guide*.

If the value for a parameter in `UpdateMaintenanceWindowTask` is null, then the corresponding field isn't modified. If you set `Replace` to true, then all fields required by the RegisterTaskWithMaintenanceWindow operation are required for this request. Optional fields that aren't specified are set to null.

Important

When you update a maintenance window task that has options specified in `TaskInvocationParameters`, you must provide again all the `TaskInvocationParameters` values that you want to retain. The values you don't specify again are removed. For example, suppose that when you registered a Run Command task, you specified `TaskInvocationParameters` values for `Comment`, `NotificationConfig`, and `OutputS3BucketName`. If you update the maintenance

window task and specify only a different `OutputS3BucketName` value, the values for `Comment` and `NotificationConfig` are removed.

Request Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "CutoffBehavior": "string",
   "Description": "string",
   "LoggingInfo": {
      "S3BucketName": "string",
      "S3KeyPrefix": "string",
      "S3Region": "string"
   },
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "Priority": number,
   "Replace": boolean,
   "ServiceRoleArn": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TaskArn": "string",
   "TaskInvocationParameters": {
      "Automation": {
         "DocumentVersion": "string",
         "Parameters": {
            "string" : [ "string" ]
         }
      },
```

```
      "Lambda": {
         "ClientContext": "string",
         "Payload": blob,
         "Qualifier": "string"
      },
      "RunCommand": {
         "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
         },
         "Comment": "string",
         "DocumentHash": "string",
         "DocumentHashType": "string",
         "DocumentVersion": "string",
         "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
         },
         "OutputS3BucketName": "string",
         "OutputS3KeyPrefix": "string",
         "Parameters": {
            "string" : [ "string" ]
         },
         "ServiceRoleArn": "string",
         "TimeoutSeconds": number
      },
      "StepFunctions": {
         "Input": "string",
         "Name": "string"
      }
   },
   "TaskParameters": {
      "string" : {
         "Values": [ "string" ]
      }
   },
   "WindowId": "string",
   "WindowTaskId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

AlarmConfiguration

The CloudWatch alarm you want to apply to your maintenance window task.

Type: AlarmConfiguration object

Required: No

CutoffBehavior

Indicates whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

- `CONTINUE_TASK`: When the cutoff time is reached, any tasks that are running continue. The default value.
- `CANCEL_TASK`:
  - For Automation, AWS Lambda, AWS Step Functions tasks: When the cutoff time is reached, any task invocations that are already running continue, but no new task invocations are started.
  - For Run Command tasks: When the cutoff time is reached, the system sends a CancelCommand operation that attempts to cancel the command associated with the task. However, there is no guarantee that the command will be terminated and the underlying process stopped.

  The status for tasks that are not completed is `TIMED_OUT`.

Type: String

Valid Values: `CONTINUE_TASK | CANCEL_TASK`

Required: No

Description

The new task description to specify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

LoggingInfo

The new logging location in Amazon S3 to specify.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: LoggingInfo object

Required: No

MaxConcurrency

The new `MaxConcurrency` value you want to specify. `MaxConcurrency` is the number of targets that are allowed to run this task, in parallel.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The new `MaxErrors` value to specify. `MaxErrors` is the maximum number of errors that are allowed before the task stops being scheduled.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The new task name to specify.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Priority

The new task priority to specify. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

Replace

If True, then all fields that are required by the RegisterTaskWithMaintenanceWindow operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Required: No

Targets

The targets (either managed nodes or tags) to modify. Managed nodes are specified using the format `Key=instanceids,Values=instanceID_1,instanceID_2`. Tags are specified using the format `Key=tag_name,Values=tag_value`.

> **Note**
>
> One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task

types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see Registering maintenance window tasks without targets in the *AWS Systems Manager User Guide*.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TaskArn

The task ARN to modify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

TaskInvocationParameters

The parameters that the task should use during execution. Populate only the fields that match the task type. All other fields should be empty.

Important

When you update a maintenance window task that has options specified in `TaskInvocationParameters`, you must provide again all the `TaskInvocationParameters` values that you want to retain. The values you don't specify again are removed. For example, suppose that when you registered a Run Command task, you specified `TaskInvocationParameters` values for `Comment`, `NotificationConfig`, and `OutputS3BucketName`. If you update the maintenance window task and specify only a different `OutputS3BucketName` value, the values for `Comment` and `NotificationConfig` are removed.

Type: MaintenanceWindowTaskInvocationParameters object

Required: No

TaskParameters

The parameters to modify.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

The map has the following format:

Key: string, between 1 and 255 characters

Value: an array of strings, each string is between 1 and 255 characters

Type: String to MaintenanceWindowTaskParameterValueExpression object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

WindowId

The maintenance window ID that contains the task to modify.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

WindowTaskId

The task ID to modify.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
{
   "AlarmConfiguration": {
      "Alarms": [
         {
            "Name": "string"
         }
      ],
      "IgnorePollAlarmFailure": boolean
   },
   "CutoffBehavior": "string",
   "Description": "string",
   "LoggingInfo": {
      "S3BucketName": "string",
      "S3KeyPrefix": "string",
      "S3Region": "string"
   },
   "MaxConcurrency": "string",
   "MaxErrors": "string",
   "Name": "string",
   "Priority": number,
   "ServiceRoleArn": "string",
   "Targets": [
      {
         "Key": "string",
         "Values": [ "string" ]
      }
   ],
   "TaskArn": "string",
   "TaskInvocationParameters": {
      "Automation": {
         "DocumentVersion": "string",
         "Parameters": {
            "string" : [ "string" ]
```

```
            }
         },
         "Lambda": {
            "ClientContext": "string",
            "Payload": blob,
            "Qualifier": "string"
         },
         "RunCommand": {
            "CloudWatchOutputConfig": {
               "CloudWatchLogGroupName": "string",
               "CloudWatchOutputEnabled": boolean
            },
            "Comment": "string",
            "DocumentHash": "string",
            "DocumentHashType": "string",
            "DocumentVersion": "string",
            "NotificationConfig": {
               "NotificationArn": "string",
               "NotificationEvents": [ "string" ],
               "NotificationType": "string"
            },
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "Parameters": {
               "string" : [ "string" ]
            },
            "ServiceRoleArn": "string",
            "TimeoutSeconds": number
         },
         "StepFunctions": {
            "Input": "string",
            "Name": "string"
         }
      },
      "TaskParameters": {
         "string" : {
            "Values": [ "string" ]
         }
      },
      "WindowId": "string",
      "WindowTaskId": "string"
   }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AlarmConfiguration

The details for the CloudWatch alarm you applied to your maintenance window task.

Type: AlarmConfiguration object

CutoffBehavior

The specification for whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

Type: String

Valid Values: `CONTINUE_TASK | CANCEL_TASK`

Description

The updated task description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

LoggingInfo

The updated logging information in Amazon S3.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: LoggingInfo object

MaxConcurrency

The updated `MaxConcurrency` value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

MaxErrors

The updated `MaxErrors` value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Name

The updated task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Priority

The updated priority value.

Type: Integer

Valid Range: Minimum value of 0.

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Targets

The updated target values.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

TaskArn

The updated task ARN value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

TaskInvocationParameters

The updated parameter values.

Type: MaintenanceWindowTaskInvocationParameters object

TaskParameters

The updated parameter values.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: String to MaintenanceWindowTaskParameterValueExpression object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

WindowId

The ID of the maintenance window that was updated.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

WindowTaskId

The task ID of the maintenance window that was updated.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdateMaintenanceWindowTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindowTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20240225T010531Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 244

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE",
    "Priority": 2,
    "MaxConcurrency": "10",
    "MaxErrors": "3",
    "Name": "MyRevisedMaintenanceWindowTask",
    "Description": "My updated maintenance window task",
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/MyCustomMaintenanceWindowTaskRole"
}
```

Sample Response

```
{
    "Description": "My updated maintenance window task",
    "MaxConcurrency": "10",
    "MaxErrors": "3",
    "Name": "MyRevisedMaintenanceWindowTask",
    "Priority": 2,
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/MyCustomMaintenanceWindowTaskRole",
    "Targets": [
```

```
        {
            "Key": "WindowTargetIds",
            "Values": [
                "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-ApplyPatchBaseline",
    "TaskInvocationParameters": {
        "RunCommand": {
            "Comment": "",
            "Parameters": {
                "Operation": [
                    "Install"
                ],
                "SnapshotId": [
                    ""
                ]
            },
            "TimeoutSeconds": 600
        }
    },
    "TaskParameters": {},
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateManagedInstanceRole

Changes the AWS Identity and Access Management (IAM) role that is assigned to the on-premises server, edge device, or virtual machines (VM). IAM roles are first assigned to these hybrid nodes during the activation process. For more information, see CreateActivation.

Request Syntax

```
{
   "IamRole": "string",
   "InstanceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

IamRole

The name of the AWS Identity and Access Management (IAM) role that you want to assign to the managed node. This IAM role must provide AssumeRole permissions for the AWS Systems Manager service principal `ssm.amazonaws.com`. For more information, see Create the IAM service role required for Systems Manager in hybrid and multicloud environments in the *AWS Systems Manager User Guide*.

> **Note**
>
> You can't specify an IAM service-linked role for this parameter. You must create a unique role.

Type: String

Length Constraints: Maximum length of 64.

Required: Yes

InstanceId

The ID of the managed node where you want to update the role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 124.

Pattern: `(^mi-[0-9a-f]{17}$)|(^eks_c:[0-9A-Za-z][A-Za-z0-9\-_]{0,99}_\w{17}$)`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent (SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in a valid state. Valid states are: `Running`, `Pending`, `Stopped`, and `Stopping`. Invalid states are: `Shutting-down` and `Terminated`.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateManagedInstanceRole.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateManagedInstanceRole
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T191724Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 56

{
    "InstanceId": "mi-0ce084dd39EXAMPLE",
    "IamRole": "SSM"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateOpsItem

Edit or change an OpsItem. You must have permission in AWS Identity and Access Management (IAM) to update an OpsItem. For more information, see Set up OpsCenter in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see AWS Systems Manager OpsCenter in the *AWS Systems Manager User Guide*.

Request Syntax

```
{
   "ActualEndTime": number,
   "ActualStartTime": number,
   "Category": "string",
   "Description": "string",
   "Notifications": [
      {
         "Arn": "string"
      }
   ],
   "OperationalData": {
      "string" : {
         "Type": "string",
         "Value": "string"
      }
   },
   "OperationalDataToDelete": [ "string" ],
   "OpsItemArn": "string",
   "OpsItemId": "string",
   "PlannedEndTime": number,
   "PlannedStartTime": number,
   "Priority": number,
   "RelatedOpsItems": [
      {
         "OpsItemId": "string"
      }
   ],
   "Severity": "string",
   "Status": "string",
```

```
    "Title": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Category

Specify a new category for an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Description

User-defined text that contains information about the OpsItem, in Markdown format.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\s\S]*\S[\s\S]*`

Required: No

Notifications

The Amazon Resource Name (ARN) of an SNS topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of OpsItemNotification objects

Required: No

OperationalData

Add new keys or edit existing key-value pairs of the OperationalData map in the OpsItem object.

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

> **Important**
>
> Operational data keys *can't* begin with the following: `amazon`, `aws`, `amzn`, `ssm`, `/amazon`, `/aws`, `/amzn`, `/ssm`.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the DescribeOpsItems API operation) can view and search on the specified data. Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the GetOpsItem API operation).

Use the `/aws/resources` key in OperationalData to specify a related resource in the request. Use the `/aws/automations` key in OperationalData to associate an Automation runbook with the OpsItem. To view AWS CLI example commands that use these keys, see Creating OpsItems manually in the *AWS Systems Manager User Guide*.

Type: String to OpsItemDataValue object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\s*$).+`

Required: No

OperationalDataToDelete

Keys that you want to remove from the OperationalData map.

Type: Array of strings

Required: No

OpsItemArn

The OpsItem Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[0-9]{12}:opsitem.*`

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

RelatedOpsItems

One or more OpsItems that share something in common with the current OpsItems. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of RelatedOpsItem objects

Required: No

Severity

Specify a new severity for an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Status

The OpsItem status. For more information, see Editing OpsItem details in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Revoked | Rejected | Closed`

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemAccessDeniedException

You don't have permission to view OpsItems in the specified account. Verify that your account is configured either as a Systems Manager delegated administrator or that you are logged into the AWS Organizations management account.

HTTP Status Code: 400

OpsItemAlreadyExistsException

The OpsItem already exists.

HTTP Status Code: 400

OpsItemConflictException

The specified OpsItem is in the process of being deleted.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateOpsItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240401T184738Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 54

{
    "Status": "Resolved",
    "OpsItemId": "oi-1f050EXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateOpsMetadata

AWS Systems Manager calls this API operation when you edit OpsMetadata in Application Manager.

Request Syntax

```
{
   "KeysToDelete": [ "string" ],
   "MetadataToUpdate": {
      "string" : {
         "Value": "string"
      }
   },
   "OpsMetadataArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

KeysToDelete

The metadata keys to delete from the OpsMetadata object.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(?!\s*$).+`

Required: No

MetadataToUpdate

Metadata to add to an OpsMetadata object.

Type: String to MetadataValue object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `^(?!\s*$).+`

Required: No

OpsMetadataArn

The Amazon Resource Name (ARN) of the OpsMetadata Object to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Required: Yes

Response Syntax

```
{
   "OpsMetadataArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsMetadataArn

The Amazon Resource Name (ARN) of the OpsMetadata Object that was updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataKeyLimitExceededException

The OpsMetadata object exceeds the maximum number of OpsMetadata keys that you can assign to an application in Application Manager.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

OpsMetadataTooManyUpdatesException

The system is processing too many concurrent updates. Wait a few moments and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdatePatchBaseline

Modifies an existing patch baseline. Fields not specified in the request are left unchanged.

> **Note**
>
> For information about valid key-value pairs in `PatchFilters` for each supported operating system type, see PatchFilter.

Request Syntax

```
{
   "ApprovalRules": {
      "PatchRules": [
         {
            "ApproveAfterDays": number,
            "ApproveUntilDate": "string",
            "ComplianceLevel": "string",
            "EnableNonSecurity": boolean,
            "PatchFilterGroup": {
               "PatchFilters": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ]
            }
         }
      ]
   },
   "ApprovedPatches": [ "string" ],
   "ApprovedPatchesComplianceLevel": "string",
   "ApprovedPatchesEnableNonSecurity": boolean,
   "AvailableSecurityUpdatesComplianceStatus": "string",
   "BaselineId": "string",
   "Description": "string",
   "GlobalFilters": {
      "PatchFilters": [
         {
            "Key": "string",
            "Values": [ "string" ]
```

```
            }
         ]
      },
      "Name": "string",
      "RejectedPatches": [ "string" ],
      "RejectedPatchesAction": "string",
      "Replace": boolean,
      "Sources": [
         {
            "Configuration": "string",
            "Name": "string",
            "Products": [ "string" ]
         }
      ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ApprovalRules

A set of rules used to include patches in the baseline.

Type: PatchRuleGroup object

Required: No

ApprovedPatches

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ApprovedPatchesComplianceLevel

Assigns a new compliance severity level to an existing patch baseline.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

AvailableSecurityUpdatesComplianceStatus

Indicates the status to be assigned to security patches that are available but not approved because they don't meet the installation criteria specified in the patch baseline.

Example scenario: Security patches that you might want installed can be skipped if you have specified a long period to wait after a patch is released before installation. If an update to the patch is released during your specified waiting period, the waiting period for installing the patch starts over. If the waiting period is too long, multiple versions of the patch could be released but never installed.

Supported for Windows Server managed nodes only.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: No

BaselineId

The ID of the patch baseline to update.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

Description

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

GlobalFilters

A set of global filters used to include patches in the baseline.

> **Important**
>
> The `GlobalFilters` parameter can be configured only by using the AWS CLI or an AWS SDK. It can't be configured from the Patch Manager console, and its value isn't displayed in the console.

Type: PatchFilterGroup object

Required: No

Name

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

RejectedPatches

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RejectedPatchesAction

The action for Patch Manager to take on patches included in the `RejectedPackages` list.

ALLOW_AS_DEPENDENCY

Linux and macOS: A package in the rejected patches list is installed only if it is a dependency of another package. It is considered compliant with the patch baseline, and its status is reported as `INSTALLED_OTHER`. This is the default action if no option is specified.

Windows Server: Windows Server doesn't support the concept of package dependencies. If a package in the rejected patches list and already installed on the node, its status is reported as `INSTALLED_OTHER`. Any package not already installed on the node is skipped. This is the default action if no option is specified.

BLOCK

All OSs: Packages in the rejected patches list, and packages that include them as dependencies, aren't installed by Patch Manager under any circumstances.

State value assignment for patch compliance:

- If a package was installed before it was added to the rejected patches list, or is installed outside of Patch Manager afterward, it's considered noncompliant with the patch baseline and its status is reported as `INSTALLED_REJECTED`.
- If an update attempts to install a dependency package that is now rejected by the baseline, when previous versions of the package were not rejected, the package being updated is reported as `MISSING` for `SCAN` operations and as `FAILED` for `INSTALL` operations.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY | BLOCK`

Required: No

Replace

If True, then all fields that are required by the CreatePatchBaseline operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of PatchSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Response Syntax

```
{
   "ApprovalRules": {
      "PatchRules": [
         {
            "ApproveAfterDays": number,
            "ApproveUntilDate": "string",
            "ComplianceLevel": "string",
            "EnableNonSecurity": boolean,
            "PatchFilterGroup": {
               "PatchFilters": [
                  {
                     "Key": "string",
                     "Values": [ "string" ]
                  }
               ]
            }
```

```
         }
      ]
   },
   "ApprovedPatches": [ "string" ],
   "ApprovedPatchesComplianceLevel": "string",
   "ApprovedPatchesEnableNonSecurity": boolean,
   "AvailableSecurityUpdatesComplianceStatus": "string",
   "BaselineId": "string",
   "CreatedDate": number,
   "Description": "string",
   "GlobalFilters": {
      "PatchFilters": [
         {
            "Key": "string",
            "Values": [ "string" ]
         }
      ]
   },
   "ModifiedDate": number,
   "Name": "string",
   "OperatingSystem": "string",
   "RejectedPatches": [ "string" ],
   "RejectedPatchesAction": "string",
   "Sources": [
      {
         "Configuration": "string",
         "Name": "string",
         "Products": [ "string" ]
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApprovalRules

A set of rules used to include patches in the baseline.

Type: PatchRuleGroup object

ApprovedPatches

A list of explicitly approved patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

ApprovedPatchesComplianceLevel

The compliance severity level assigned to the patch baseline after the update completed.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

AvailableSecurityUpdatesComplianceStatus

Indicates the compliance status of managed nodes for which security-related patches are available but were not approved. This preference is specified when the `CreatePatchBaseline` or `UpdatePatchBaseline` commands are run.

Applies to Windows Server managed nodes only.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

BaselineId

The ID of the deleted patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

CreatedDate

The date when the patch baseline was created.

Type: Timestamp

Description

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

GlobalFilters

A set of global filters used to exclude patches from the baseline.

Type: PatchFilterGroup object

ModifiedDate

The date when the patch baseline was last modified.

Type: Timestamp

Name

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

OperatingSystem

The operating system rule used by the updated patch baseline.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

RejectedPatches

A list of explicitly rejected patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

RejectedPatchesAction

The action specified to take on patches included in the `RejectedPatches` list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY | BLOCK`

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of PatchSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see Common Error Types.

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see Systems Manager service quotas in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdatePatchBaseline.

Sample Request

```
POST / HTTP/1.1
   Host: ssm.us-east-2.amazonaws.com
   Accept-Encoding: identity
   Content-Length: 306
   X-Amz-Target: AmazonSSM.UpdatePatchBaseline
   X-Amz-Date: 20240309T023346Z
   User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
   Content-Type: application/x-amz-json-1.1
   Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240309/us-east-2/
ssm/aws4_request,
   SignedHeaders=content-type;host;x-amz-date;x-amz-target,
 Signature=39c3b3042cd2aEXAMPLE

  {
    "ApprovalRules": {
        "PatchRules": [
            {
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Values": [
                                "Critical",
                                "Important"
                            ],
                            "Key": "MSRC_SEVERITY"
                        },
                        {
                            "Values": [
                                "SecurityUpdates",
                                "Updates",
                                "UpdateRollups",
                                "CriticalUpdates"
                            ],
                            "Key": "CLASSIFICATION"
                        }
```

```
                    ]
                },
                "ApproveAfterDays": 3
            }
        ]
    },
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "ApprovalRules": {
        "PatchRules": [
            {
                "ApproveAfterDays": 3,
                "ComplianceLevel": "UNSPECIFIED",
                "EnableNonSecurity": false,
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Key": "MSRC_SEVERITY",
                            "Values": [
                                "Critical",
                                "Important"
                            ]
                        },
                        {
                            "Key": "CLASSIFICATION",
                            "Values": [
                                "SecurityUpdates",
                                "Updates",
                                "UpdateRollups",
                                "CriticalUpdates"
                            ]
                        }
                    ]
                }
            }
        ]
    },
    "ApprovedPatches": [],
    "ApprovedPatchesComplianceLevel": "UNSPECIFIED",
```

```
    "ApprovedPatchesEnableNonSecurity": false,
    "BaselineId": "pb-0c10e65780EXAMPLE",
    "Description": "Baseline containing all updates approved for production systems",
    "GlobalFilters": {
        "PatchFilters": []
    },
    "CreatedDate": 1520562237.968,
    "ModifiedDate": 1520562239.765,
    "Name": "my-Windows-Server-patch-baseline",
    "OperatingSystem": "WINDOWS",
    "RejectedPatches": [],
    "RejectedPatchesAction": "ALLOW_AS_DEPENDENCY",
    "Sources": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateResourceDataSync

Update a resource data sync. After you create a resource data sync for a Region, you can't change the account options for that sync. For example, if you create a sync in the us-east-2 (Ohio) Region and you choose the `Include only the current account` option, you can't edit that sync later and choose the `Include all accounts from my AWS Organizations configuration` option. Instead, you must delete the first resource data sync, and create a new one.

> **Note**
>
> This API operation only supports a resource data sync that was created with a SyncFromSource SyncType.

Request Syntax

```
{
   "SyncName": "string",
   "SyncSource": {
      "AwsOrganizationsSource": {
         "OrganizationalUnits": [
            {
               "OrganizationalUnitId": "string"
            }
         ],
         "OrganizationSourceType": "string"
      },
      "EnableAllOpsDataSources": boolean,
      "IncludeFutureRegions": boolean,
      "SourceRegions": [ "string" ],
      "SourceType": "string"
   },
   "SyncType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SyncName

The name of the resource data sync you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncSource

Specify information about the data sources to synchronize.

Type: ResourceDataSyncSource object

Required: Yes

SyncType

The type of resource data sync. The supported SyncType is SyncFromSource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncConflictException

Another UpdateResourceDataSync request is being processed. Wait a few minutes and try again.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240327T160454Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240327/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 161

{
    "SyncName": "exampleSync",
    "SyncType": "SyncFromSource",
    "SyncSource": {
        "SourceType": "SingleAccountMultiRegions",
        "SourceRegions": [
            "us-east-2",
            "us-west-2"
        ]
    }
```

```
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateServiceSetting

`ServiceSetting` is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a `SettingId` object to a setting value. AWS services teams define the default value for a `SettingId`. You can't create a new `SettingId`, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the GetServiceSetting API operation to view the current value. Or, use the ResetServiceSetting to change the value back to the original value defined by the AWS service team.

Update the service setting for the account.

Request Syntax

```
{
   "SettingId": "string",
   "SettingValue": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

SettingId

The Amazon Resource Name (ARN) of the service setting to update. For example, `arn:aws:ssm:us-east-1:111122223333:servicesetting/ssm/parameter-store/high-throughput-enabled`. The setting ID can be one of the following.

- `/ssm/appmanager/appmanager-enabled`
- `/ssm/automation/customer-script-log-destination`
- `/ssm/automation/customer-script-log-group-name`
- /ssm/automation/enable-adaptive-concurrency

- /ssm/documents/console/public-sharing-permission
- /ssm/managed-instance/activation-tier
- /ssm/managed-instance/default-ec2-instance-management-role
- /ssm/opsinsights/opscenter
- /ssm/parameter-store/default-parameter-tier
- /ssm/parameter-store/high-throughput-enabled

> **Note**
>
> Permissions to update the /ssm/managed-instance/default-ec2-instance-management-role setting should only be provided to administrators. Implement least privilege access when allowing individuals to configure or modify the Default Host Management Configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

SettingValue

The new value to specify for the service setting. The following list specifies the available values for each setting.

- For /ssm/appmanager/appmanager-enabled, enter True or False.
- For /ssm/automation/customer-script-log-destination, enter CloudWatch.
- For /ssm/automation/customer-script-log-group-name, enter the name of an Amazon CloudWatch Logs log group.
- For /ssm/documents/console/public-sharing-permission, enter Enable or Disable.
- For /ssm/managed-instance/activation-tier, enter standard or advanced.
- For /ssm/managed-instance/default-ec2-instance-management-role, enter the name of an IAM role.
- For /ssm/opsinsights/opscenter, enter Enabled or Disabled.

- For `/ssm/parameter-store/default-parameter-tier`, enter `Standard`, `Advanced`, or `Intelligent-Tiering`
- For `/ssm/parameter-store/high-throughput-enabled`, enter `true` or `false`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20240325T154927Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20240325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 134

{
    "SettingId": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/parameter-
store/high-throughput-enabled",
    "SettingValue": "true"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

- AWS SDK for Ruby V3

Data Types

The AWS Systems Manager API contains several data types that various actions use. This section describes each data type in detail.

> **Note**
>
> The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- AccountSharingInfo
- Activation
- Alarm
- AlarmConfiguration
- AlarmStateInformation
- Association
- AssociationDescription
- AssociationExecution
- AssociationExecutionFilter
- AssociationExecutionTarget
- AssociationExecutionTargetsFilter
- AssociationFilter
- AssociationOverview
- AssociationStatus
- AssociationVersionInfo
- AttachmentContent
- AttachmentInformation
- AttachmentsSource
- AutomationExecution
- AutomationExecutionFilter

- AutomationExecutionInputs
- AutomationExecutionMetadata
- AutomationExecutionPreview
- BaselineOverride
- CloudWatchOutputConfig
- Command
- CommandFilter
- CommandInvocation
- CommandPlugin
- ComplianceExecutionSummary
- ComplianceItem
- ComplianceItemEntry
- ComplianceStringFilter
- ComplianceSummaryItem
- CompliantSummary
- CreateAssociationBatchRequestEntry
- Credentials
- DescribeActivationsFilter
- DocumentDefaultVersionDescription
- DocumentDescription
- DocumentFilter
- DocumentIdentifier
- DocumentKeyValuesFilter
- DocumentMetadataResponseInfo
- DocumentParameter
- DocumentRequires
- DocumentReviewCommentSource
- DocumentReviewerResponseSource
- DocumentReviews
- DocumentVersionInfo

- EffectivePatch
- ExecutionInputs
- ExecutionPreview
- FailedCreateAssociation
- FailureDetails
- GetResourcePoliciesResponseEntry
- InstanceAggregatedAssociationOverview
- InstanceAssociation
- InstanceAssociationOutputLocation
- InstanceAssociationOutputUrl
- InstanceAssociationStatusInfo
- InstanceInfo
- InstanceInformation
- InstanceInformationFilter
- InstanceInformationStringFilter
- InstancePatchState
- InstancePatchStateFilter
- InstanceProperty
- InstancePropertyFilter
- InstancePropertyStringFilter
- InventoryAggregator
- InventoryDeletionStatusItem
- InventoryDeletionSummary
- InventoryDeletionSummaryItem
- InventoryFilter
- InventoryGroup
- InventoryItem
- InventoryItemAttribute
- InventoryItemSchema
- InventoryResultEntity

- InventoryResultItem
- LoggingInfo
- MaintenanceWindowAutomationParameters
- MaintenanceWindowExecution
- MaintenanceWindowExecutionTaskIdentity
- MaintenanceWindowExecutionTaskInvocationIdentity
- MaintenanceWindowFilter
- MaintenanceWindowIdentity
- MaintenanceWindowIdentityForTarget
- MaintenanceWindowLambdaParameters
- MaintenanceWindowRunCommandParameters
- MaintenanceWindowStepFunctionsParameters
- MaintenanceWindowTarget
- MaintenanceWindowTask
- MaintenanceWindowTaskInvocationParameters
- MaintenanceWindowTaskParameterValueExpression
- MetadataValue
- Node
- NodeAggregator
- NodeFilter
- NodeOwnerInfo
- NodeType
- NonCompliantSummary
- NotificationConfig
- OpsAggregator
- OpsEntity
- OpsEntityItem
- OpsFilter
- OpsItem
- OpsItemDataValue

- OpsItemEventFilter
- OpsItemEventSummary
- OpsItemFilter
- OpsItemIdentity
- OpsItemNotification
- OpsItemRelatedItemsFilter
- OpsItemRelatedItemSummary
- OpsItemSummary
- OpsMetadata
- OpsMetadataFilter
- OpsResultAttribute
- OutputSource
- Parameter
- ParameterHistory
- ParameterInlinePolicy
- ParameterMetadata
- ParametersFilter
- ParameterStringFilter
- ParentStepDetails
- Patch
- PatchBaselineIdentity
- PatchComplianceData
- PatchFilter
- PatchFilterGroup
- PatchGroupPatchBaselineMapping
- PatchOrchestratorFilter
- PatchRule
- PatchRuleGroup
- PatchSource
- PatchStatus

- ProgressCounters
- RegistrationMetadataItem
- RelatedOpsItem
- ResolvedTargets
- ResourceComplianceSummaryItem
- ResourceDataSyncAwsOrganizationsSource
- ResourceDataSyncDestinationDataSharing
- ResourceDataSyncItem
- ResourceDataSyncOrganizationalUnit
- ResourceDataSyncS3Destination
- ResourceDataSyncSource
- ResourceDataSyncSourceWithState
- ResultAttribute
- ReviewInformation
- Runbook
- S3OutputLocation
- S3OutputUrl
- ScheduledWindowExecution
- ServiceSetting
- Session
- SessionFilter
- SessionManagerOutputUrl
- SeveritySummary
- StepExecution
- StepExecutionFilter
- Tag
- Target
- TargetLocation
- TargetPreview

AccountSharingInfo

Information includes the AWS account ID where the current document is shared and the version shared with that account.

Contents

AccountId

The AWS account ID where the current document is shared.

Type: String

Pattern: `(?i)all|[0-9]{12}`

Required: No

SharedDocumentVersion

The version of the current document shared with the account.

Type: String

Length Constraints: Maximum length of 8.

Pattern: `([$]LATEST|[$]DEFAULT|[$]ALL)`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Activation

An activation registers one or more on-premises servers or virtual machines (VMs) with AWS so that you can configure those servers or VMs using Run Command. A server or VM that has been registered with AWS Systems Manager is called a managed node.

Contents

ActivationId

The ID created by Systems Manager when you submitted the activation.

Type: String

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

CreatedDate

The date the activation was created.

Type: Timestamp

Required: No

DefaultInstanceName

A name for the managed node when it is created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: No

Description

A user defined description of the activation.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ExpirationDate

The date when this activation can no longer be used to register managed nodes.

Type: Timestamp

Required: No

Expired

Whether or not the activation is expired.

Type: Boolean

Required: No

IamRole

The AWS Identity and Access Management (IAM) role to assign to the managed node.

Type: String

Length Constraints: Maximum length of 64.

Required: No

RegistrationLimit

The maximum number of managed nodes that can be registered using this activation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RegistrationsCount

The number of managed nodes already registered with this activation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

Tags

Tags assigned to the activation.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Alarm

A CloudWatch alarm you apply to an automation or command.

Contents

Name

The name of your CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(?!\s*$).+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Contents

Alarms

The name of the CloudWatch alarm specified in the configuration.

Type: Array of Alarm objects

Array Members: Fixed number of 1 item.

Required: Yes

IgnorePollAlarmFailure

When this value is *true*, your automation or command continues to run in cases where we can't retrieve alarm status information from CloudWatch. In cases where we successfully retrieve an alarm status of OK or INSUFFICIENT_DATA, the automation or command continues to run, regardless of this value. Default is *false*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AlarmStateInformation

The details about the state of your CloudWatch alarm.

Contents

Name

The name of your CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(?!\s*$).+`

Required: Yes

State

The state of your CloudWatch alarm.

Type: String

Valid Values: `UNKNOWN | ALARM`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Association

Describes an association of a AWS Systems Manager document (SSM document) and a managed node.

Contents

AssociationId

The ID created by the system when you create an association. An association is a binding between a document and a set of targets with a schedule.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationName

The association name.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AssociationVersion

The association version.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

DocumentVersion

The version of the document used in the association. If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specifed the `apply-only-at-cron-interval` parameter.

> **Important**
>
> State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs the `default` version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared form another account, you must set the document version to `default`.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours that an association can run on specified targets. After the resulting cutoff time passes, associations that are currently running are cancelled, and no pending executions are started on remaining targets.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

LastExecutionDate

The date on which the association was last run.

Type: Timestamp

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Overview

Information about the association.

Type: AssociationOverview object

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs. The schedule runs in Coordinated Universal Time (UTC).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request to create an association. You can target all managed nodes in an AWS account by specifying the `InstanceIds` key with a value of `*`.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationDescription

Describes the parameters for a document.

Contents

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

ApplyOnlyAtCronInterval

By default, when you create a new associations, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationId

The association ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationName

The association name.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AssociationVersion

The association version.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

AutomationTargetParameterName

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a tool in AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations only run when that change calendar is open. For more information, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Type: Array of strings

Required: No

ComplianceSeverity

The severity level that is assigned to the association.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED`

Required: No

Date

The date when the association was made.

Type: Timestamp

Required: No

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours that an association can run on specified targets. After the resulting cutoff time passes, associations that are currently running are cancelled, and no pending executions are started on remaining targets.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

LastExecutionDate

The date on which the association was last run.

Type: Timestamp

Required: No

LastSuccessfulExecutionDate

The last date on which the association was successfully run.

Type: Timestamp

Required: No

LastUpdateAssociationDate

The date when the association was last updated.

Type: Timestamp

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

OutputLocation

An S3 bucket where you want to store the output details of the request.

Type: InstanceAssociationOutputLocation object

Required: No

Overview

Information about the association.

Type: AssociationOverview object

Required: No

Parameters

A description of the parameters for a document.

Type: String to array of strings map

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

Status

The association status.

Type: AssociationStatus object

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the PutComplianceItems API operation. In this case, compliance data isn't managed by State Manager, a tool in AWS Systems Manager. It is managed by your direct call to the PutComplianceItems API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

TargetLocations

The combination of AWS Regions and AWS accounts where you want to run the association.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TriggeredAlarms

The CloudWatch alarm that was invoked during the association.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationExecution

Includes information about the specified association.

Contents

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

AssociationId

The association ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationVersion

The association version.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

CreatedTime

The time the execution started.

Type: Timestamp

Required: No

DetailedStatus

Detailed status information about the execution.

Type: String

Required: No

ExecutionId

The execution ID for the association.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

LastExecutionDate

The date of the last execution.

Type: Timestamp

Required: No

ResourceCountByStatus

An aggregate status of the resources in the execution based on the status type.

Type: String

Required: No

Status

The status of the association execution.

Type: String

Required: No

TriggeredAlarms

The CloudWatch alarms that were invoked by the association.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationExecutionFilter

Filters used in the request.

Contents

Key

The key value used in the request.

Type: String

Valid Values: `ExecutionId | Status | CreatedTime`

Required: Yes

Type

The filter type specified in the request.

Type: String

Valid Values: `EQUAL | LESS_THAN | GREATER_THAN`

Required: Yes

Value

The value specified for the key.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

AssociationExecutionTarget

Includes information about the specified association execution.

Contents

AssociationId

The association ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationVersion

The association version.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

DetailedStatus

Detailed information about the execution status.

Type: String

Required: No

ExecutionId

The execution ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

LastExecutionDate

The date of the last execution.

Type: Timestamp

Required: No

OutputSource

The location where the association details are saved.

Type: OutputSource object

Required: No

ResourceId

The resource ID, for example, the managed node ID where the association ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The resource type, for example, EC2.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Status

The association execution status.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationExecutionTargetsFilter

Filters for the association execution.

Contents

Key

The key value used in the request.

Type: String

Valid Values: `Status | ResourceId | ResourceType`

Required: Yes

Value

The value specified for the key.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationFilter

Describes a filter.

Contents

key

The name of the filter.

> **Note**
>
> `InstanceId` has been deprecated.

Type: String

Valid Values: `InstanceId | Name | AssociationId | AssociationStatusName | LastExecutedBefore | LastExecutedAfter | AssociationName | ResourceGroupName`

Required: Yes

value

The filter value.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

AssociationOverview

Information about the association.

Contents

AssociationStatusAggregatedCount

Returns the number of targets for the association status. For example, if you created an association with two managed nodes, and one of them was successful, this would return the count of managed nodes by status.

Type: String to integer map

Required: No

DetailedStatus

A detailed status of the association.

Type: String

Required: No

Status

The status of the association. Status can be: Pending, Success, or Failed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationStatus

Describes an association status.

Contents

Date

The date when the status changed.

Type: Timestamp

Required: Yes

Message

The reason for the status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

Name

The status.

Type: String

Valid Values: `Pending | Success | Failed`

Required: Yes

AdditionalInfo

A user-defined string.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AssociationVersionInfo

Information about the association version.

Contents

ApplyOnlyAtCronInterval

By default, when you create new associations, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationId

The ID created by the system when the association was created.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationName

The name specified for the association version when the association version was created.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AssociationVersion

The association version.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations for this version only run when that Change Calendar is open. For more information, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Type: Array of strings

Required: No

ComplianceSeverity

The severity level that is assigned to the association.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED`

Required: No

CreatedDate

The date the association version was created.

Type: Timestamp

Required: No

DocumentVersion

The version of an AWS Systems Manager document (SSM document) used when the association version was created.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours that an association can run on specified targets. After the resulting cutoff time passes, associations that are currently running are cancelled, and no pending executions are started on remaining targets.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The name specified when the association was created.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

OutputLocation

The location in Amazon S3 specified for the association when the association version was created.

Type: InstanceAssociationOutputLocation object

Required: No

Parameters

Parameters specified when the association version was created.

Type: String to array of strings map

Required: No

ScheduleExpression

The cron or rate schedule specified for the association when the association version was created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the PutComplianceItems API operation. In this case, compliance data isn't managed by State Manager, a tool in AWS Systems Manager. It is managed by your direct call to the PutComplianceItems API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

TargetLocations

The combination of AWS Regions and AWS accounts where you wanted to run the association when this association version was created.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets specified for the association when the association version was created.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AttachmentContent

A structure that includes attributes that describe a document attachment.

Contents

Hash

The cryptographic hash value of the document content.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HashType

The hash algorithm used to calculate the hash value.

Type: String

Valid Values: `Sha256`

Required: No

Name

The name of an attachment.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Size

The size of an attachment in bytes.

Type: Long

Required: No

Url

The URL location of the attachment content.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AttachmentInformation

An attribute of an attachment, such as the attachment name.

Contents

Name

The name of the attachment.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AttachmentsSource

Identifying information about a document attachment, including the file name and a key-value pair that identifies the location of an attachment to a document.

Contents

Key

The key of a key-value pair that identifies the location of an attachment to a document.

Type: String

Valid Values: `SourceUrl | S3FileUrl | AttachmentReference`

Required: No

Name

The name of the document attachment file.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Values

The value of a key-value pair that identifies the location of an attachment to a document. The format for **Value** depends on the type of key you specify.

- For the key *SourceUrl*, the value is an S3 bucket location. For example:

  ```
  "Values": [ "s3://amzn-s3-demo-bucket/my-prefix" ]
  ```

- For the key *S3FileUrl*, the value is a file in an S3 bucket. For example:

  ```
  "Values": [ "s3://amzn-s3-demo-bucket/my-prefix/my-file.py" ]
  ```

- For the key *AttachmentReference*, the value is constructed from the name of another SSM document in your account, a version number of that document, and a file attached to that document version that you want to reuse. For example:

  ```
  "Values": [ "MyOtherDocument/3/my-other-file.py" ]
  ```

However, if the SSM document is shared with you from another account, the full SSM document ARN must be specified instead of the document name only. For example:

```
"Values": [ "arn:aws:ssm:us-east-2:111122223333:document/
OtherAccountDocument/3/their-file.py" ]
```

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AutomationExecution

Detailed information about the current state of an individual Automation execution.

Contents

AlarmConfiguration

The details for the CloudWatch alarm applied to your automation.

Type: AlarmConfiguration object

Required: No

AssociationId

The ID of a State Manager association used in the Automation operation.

Type: String

Required: No

AutomationExecutionId

The execution ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

AutomationExecutionStatus

The execution status of the Automation.

Type: String

Valid Values: `Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure | Exited`

Required: No

AutomationSubtype

The subtype of the Automation operation. Currently, the only supported value is `ChangeRequest`.

Type: String

Valid Values: `ChangeRequest | AccessRequest`

Required: No

ChangeRequestName

The name of the Change Manager change request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

CurrentAction

The action of the step that is currently running.

Type: String

Required: No

CurrentStepName

The name of the step that is currently running.

Type: String

Required: No

DocumentName

The name of the Automation runbook used during the execution.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

DocumentVersion

The version of the document to use during execution.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

ExecutedBy

The Amazon Resource Name (ARN) of the user who ran the automation.

Type: String

Required: No

ExecutionEndTime

The time the execution finished.

Type: Timestamp

Required: No

ExecutionStartTime

The time the execution started.

Type: Timestamp

Required: No

FailureMessage

A message describing why an execution has failed, if the status is set to Failed.

Type: String

Required: No

MaxConcurrency

The `MaxConcurrency` value specified by the user when the execution started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The MaxErrors value specified by the user when the execution started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Mode

The automation execution mode.

Type: String

Valid Values: `Auto | Interactive`

Required: No

OpsItemId

The ID of an OpsItem that is created to represent a Change Manager change request.

Type: String

Required: No

Outputs

The list of execution outputs as defined in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Parameters

The key-value map of execution parameters, which were supplied when calling StartAutomationExecution.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

ParentAutomationExecutionId

The AutomationExecutionId of the parent automation.

Type: String

Length Constraints: Fixed length of 36.

Required: No

ProgressCounters

An aggregate of step execution statuses displayed in the AWS Systems Manager console for a multi-Region and multi-account Automation execution.

Type: ProgressCounters object

Required: No

ResolvedTargets

A list of resolved targets in the rate control execution.

Type: ResolvedTargets object

Required: No

Runbooks

Information about the Automation runbooks that are run as part of a runbook workflow.

> **Note**
>
> The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of Runbook objects

Array Members: Fixed number of 1 item.

Required: No

ScheduledTime

The date and time the Automation operation is scheduled to start.

Type: Timestamp

Required: No

StepExecutions

A list of details about the current state of all steps that comprise an execution. An Automation runbook contains a list of steps that are run in order.

Type: Array of StepExecution objects

Required: No

StepExecutionsTruncated

A boolean value that indicates if the response contains the full list of the Automation step executions. If true, use the DescribeAutomationStepExecutions API operation to get the full list of step executions.

Type: Boolean

Required: No

Target

The target of the execution.

Type: String

Required: No

TargetLocations

The combination of AWS Regions and/or AWS accounts where you want to run the Automation.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetLocationsURL

A publicly accessible URL for a file that contains the `TargetLocations` body. Currently, only files in presigned Amazon S3 buckets are supported

Type: String

Pattern: `^https:\/\/[-a-zA-Z0-9@:%._\+~#=]{1,253}\.s3(\.[a-z\d-]{9,16})?\.amazonaws\.com\/.{1,2000}`

Required: No

TargetMaps

The specified key-value mapping of document parameters to target resources.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The parameter name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The specified targets.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TriggeredAlarms

The CloudWatch alarm that was invoked by the automation.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

Variables

Variables defined for the automation.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AutomationExecutionFilter

A filter used to match specific automation executions. This is used to limit the scope of Automation execution information returned.

Contents

Key

One or more keys to limit the results.

Type: String

Valid Values: `DocumentNamePrefix | ExecutionStatus | ExecutionId | ParentExecutionId | CurrentAction | StartTimeBefore | StartTimeAfter | AutomationType | TagKey | TargetResourceGroup | AutomationSubtype | OpsItemId`

Required: Yes

Values

The values used to limit the execution information associated with the filter's key.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AutomationExecutionInputs

Information about the optional inputs that can be specified for an automation execution preview.

Contents

Parameters

Information about parameters that can be specified for the preview operation.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

TargetLocations

Information about the AWS Regions and AWS accounts targeted by the Automation execution preview operation.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetLocationsURL

A publicly accessible URL for a file that contains the `TargetLocations` body. Currently, only files in presigned Amazon S3 buckets are supported.

Type: String

Pattern: `^https:\/\/[-a-zA-Z0-9@:%._\+~#=]{1,253}\.s3(\.[a-z\d-]{9,16})?\.amazonaws\.com\/.{1,2000}`

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The name of the parameter used as the target resource for the rate-controlled execution. Required if you specify targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

Information about the resources that would be included in the actual runbook execution, if it were to be run. Both Targets and TargetMaps can't be specified together.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AutomationExecutionMetadata

Details about a specific Automation execution.

Contents

AlarmConfiguration

The details for the CloudWatch alarm applied to your automation.

Type: AlarmConfiguration object

Required: No

AssociationId

The ID of a State Manager association used in the Automation operation.

Type: String

Required: No

AutomationExecutionId

The execution ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

AutomationExecutionStatus

The status of the execution.

Type: String

Valid Values: `Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure | Exited`

Required: No

AutomationSubtype

The subtype of the Automation operation. Currently, the only supported value is `ChangeRequest`.

Type: String

Valid Values: `ChangeRequest | AccessRequest`

Required: No

AutomationType

Use this filter with DescribeAutomationExecutions. Specify either Local or CrossAccount. CrossAccount is an Automation that runs in multiple AWS Regions and AWS accounts. For more information, see Running automations in multiple AWS Regions and accounts in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `CrossAccount | Local`

Required: No

ChangeRequestName

The name of the Change Manager change request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

CurrentAction

The action of the step that is currently running.

Type: String

Required: No

CurrentStepName

The name of the step that is currently running.

Type: String

Required: No

DocumentName

The name of the Automation runbook used during execution.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

DocumentVersion

The document version used during the execution.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

ExecutedBy

The IAM role ARN of the user who ran the automation.

Type: String

Required: No

ExecutionEndTime

The time the execution finished. This isn't populated if the execution is still in progress.

Type: Timestamp

Required: No

ExecutionStartTime

The time the execution started.

Type: Timestamp

Required: No

FailureMessage

The list of execution outputs as defined in the Automation runbook.

Type: String

Required: No

LogFile

An S3 bucket where execution information is stored.

Type: String

Required: No

MaxConcurrency

The `MaxConcurrency` value specified by the user when starting the automation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The `MaxErrors` value specified by the user when starting the automation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Mode

The Automation execution mode.

Type: String

Valid Values: `Auto | Interactive`

Required: No

OpsItemId

The ID of an OpsItem that is created to represent a Change Manager change request.

Type: String

Required: No

Outputs

The list of execution outputs as defined in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

ParentAutomationExecutionId

The execution ID of the parent automation.

Type: String

Length Constraints: Fixed length of 36.

Required: No

ResolvedTargets

A list of targets that resolved during the execution.

Type: ResolvedTargets object

Required: No

Runbooks

Information about the Automation runbooks that are run during a runbook workflow in Change Manager.

> **Note**
>
> The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of Runbook objects

Array Members: Fixed number of 1 item.

Required: No

ScheduledTime

The date and time the Automation operation is scheduled to start.

Type: Timestamp

Required: No

Target

The list of execution outputs as defined in the Automation runbook.

Type: String

Required: No

TargetLocationsURL

A publicly accessible URL for a file that contains the `TargetLocations` body. Currently, only files in presigned Amazon S3 buckets are supported

Type: String

Pattern: `^https:\/\/[-a-zA-Z0-9@:%._\+~#=]{1,253}\.s3(\.[a-z\d-]{9,16})?\.amazonaws\.com\/.{1,2000}`

Required: No

TargetMaps

The specified key-value mapping of document parameters to target resources.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The list of execution outputs as defined in the Automation runbook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets defined by the user when starting the automation.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TriggeredAlarms

The CloudWatch alarm that was invoked by the automation.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AutomationExecutionPreview

Information about the results of the execution preview.

Contents

Regions

Information about the AWS Regions targeted by the execution preview.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

StepPreviews

Information about the type of impact a runbook step would have on a resource.

- `Mutating`: The runbook step would make changes to the targets through actions that create, modify, or delete resources.
- `Non_Mutating`: The runbook step would retrieve data about resources but not make changes to them. This category generally includes `Describe*`, `List*`, `Get*`, and similar read-only API actions.
- `Undetermined`: An undetermined step invokes executions performed by another orchestration service like AWS Lambda, AWS Step Functions, or AWS Systems Manager Run Command. An undetermined step might also call a third-party API. Systems Manager Automation doesn't know the outcome of the orchestration processes or third-party API executions, so the results of the steps are undetermined.

Type: String to integer map

Valid Keys: `Mutating | NonMutating | Undetermined`

Required: No

TargetPreviews

Information that provides a preview of what the impact of running the specified Automation runbook would be.

Type: Array of TargetPreview objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

TotalAccounts

Information about the AWS accounts that were included in the execution preview.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

BaselineOverride

Defines the basic information about a patch baseline override.

Contents

ApprovalRules

A set of rules defining the approval rules for a patch baseline.

Type: PatchRuleGroup object

Required: No

ApprovedPatches

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ApprovedPatchesComplianceLevel

Defines the compliance level for approved patches. When an approved patch is reported as missing, this value describes the severity of the compliance violation.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

AvailableSecurityUpdatesComplianceStatus

Indicates whether managed nodes for which there are available security-related patches that have not been approved by the baseline are being defined as `COMPLIANT` or `NON_COMPLIANT`. This option is specified when the `CreatePatchBaseline` or `UpdatePatchBaseline` commands are run.

Applies to Windows Server managed nodes only.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: No

GlobalFilters

A set of patch filters, typically used for approval rules.

Type: PatchFilterGroup object

Required: No

OperatingSystem

The operating system rule used by the patch baseline override.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: No

RejectedPatches

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see Package name formats for approved and rejected patch lists in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RejectedPatchesAction

The action for Patch Manager to take on patches included in the `RejectedPackages` list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY | BLOCK`

Required: No

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of PatchSource objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CloudWatchOutputConfig

Configuration options for sending command output to Amazon CloudWatch Logs.

Contents

CloudWatchLogGroupName

The name of the CloudWatch Logs log group where you want to send command output. If you don't specify a group name, AWS Systems Manager automatically creates a log group for you. The log group uses the following naming format:

`aws/ssm/SystemsManagerDocumentName`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

CloudWatchOutputEnabled

Enables Systems Manager to send command output to CloudWatch Logs.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Command

Describes a command request.

Contents

AlarmConfiguration

The details for the CloudWatch alarm applied to your command.

Type: AlarmConfiguration object

Required: No

CloudWatchOutputConfig

Amazon CloudWatch Logs information where you want AWS Systems Manager to send the command output.

Type: CloudWatchOutputConfig object

Required: No

CommandId

A unique identifier for this command.

Type: String

Length Constraints: Fixed length of 36.

Required: No

Comment

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

CompletedCount

The number of targets for which the command invocation reached a terminal state. Terminal states include the following: Success, Failed, Execution Timed Out, Delivery Timed Out, Cancelled, Terminated, or Undeliverable.

Type: Integer

Required: No

DeliveryTimedOutCount

The number of targets for which the status is Delivery Timed Out.

Type: Integer

Required: No

DocumentName

The name of the document requested for execution.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

DocumentVersion

The Systems Manager document (SSM document) version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

ErrorCount

The number of targets for which the status is Failed or Execution Timed Out.

Type: Integer

Required: No

ExpiresAfter

If a command expires, it changes status to `DeliveryTimedOut` for all invocations that have the status `InProgress`, `Pending`, or `Delayed`. `ExpiresAfter` is calculated based on the total timeout for the overall command. For more information, see Understanding command timeout values in the *AWS Systems Manager User Guide*.

Type: Timestamp

Required: No

InstanceIds

The managed node IDs against which this command was requested.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxConcurrency

The maximum number of managed nodes that are allowed to run the command at the same time. You can specify a number of managed nodes, such as 10, or a percentage of nodes, such as 10%. The default value is 50. For more information about how to use `MaxConcurrency`, see AWS Systems Manager Run Command in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The maximum number of errors allowed before the system stops sending the command to additional targets. You can specify a number of errors, such as 10, or a percentage or errors, such as 10%. The default value is `0`. For more information about how to use `MaxErrors`, see AWS Systems Manager Run Command in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

NotificationConfig

Configurations for sending notifications about command status changes.

Type: NotificationConfig object

Required: No

OutputS3BucketName

The S3 bucket where the responses to the command executions should be stored. This was requested when issuing the command.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 directory path inside the bucket where the responses to the command executions should be stored. This was requested when issuing the command.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, Systems Manager automatically determines the AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

Parameters

The parameter values to be inserted in the document when running the command.

Type: String to array of strings map

Required: No

RequestedDateTime

The date and time the command was requested.

Type: Timestamp

Required: No

ServiceRole

The AWS Identity and Access Management (IAM) service role that Run Command, a tool in AWS Systems Manager, uses to act on your behalf when sending notifications about command status changes.

Type: String

Required: No

Status

The status of the command.

Type: String

Valid Values: `Pending | InProgress | Success | Cancelled | Failed | TimedOut | Cancelling`

Required: No

StatusDetails

A detailed status of the command execution. `StatusDetails` includes more information than `Status` because it includes states resulting from error and concurrency control parameters. `StatusDetails` can show different results than Status. For more information about these statuses, see Understanding command statuses in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to any managed nodes.
- In Progress: The command has been sent to at least one managed node but hasn't reached a final state on all managed nodes.
- Success: The command successfully ran on all invocations. This is a terminal state.
- Delivery Timed Out: The value of MaxErrors or more command invocations shows a status of Delivery Timed Out. This is a terminal state.
- Execution Timed Out: The value of MaxErrors or more command invocations shows a status of Execution Timed Out. This is a terminal state.
- Failed: The value of MaxErrors or more command invocations shows a status of Failed. This is a terminal state.
- Incomplete: The command was attempted on all managed nodes and one or more invocations doesn't have a value of Success but not enough invocations failed for the status to be Failed. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Rate Exceeded: The number of managed nodes targeted by the command exceeded the account limit for pending invocations. The system has canceled the command before running it on any managed node. This is a terminal state.
- Delayed: The system attempted to send the command to the managed node but wasn't successful. The system retries again.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

TargetCount

The number of targets for the command.

Type: Integer

Required: No

Targets

An array of search criteria that targets managed nodes using a Key,Value combination that you specify. Targets is required if you don't provide one or more managed node IDs in the call.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TimeoutSeconds

The `TimeoutSeconds` value specified for a command.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

TriggeredAlarms

The CloudWatch alarm that was invoked by the command.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CommandFilter

Describes a command filter.

> **Note**
>
> A managed node ID can't be specified when a command status is `Pending` because the command hasn't run on the node yet.

Contents

key

The name of the filter.

> **Note**
>
> The `ExecutionStage` filter can't be used with the `ListCommandInvocations` operation, only with `ListCommands`.

Type: String

Valid Values: `InvokedAfter | InvokedBefore | Status | ExecutionStage | DocumentName`

Required: Yes

value

The filter value. Valid values for each filter key are as follows:

- **InvokedAfter**: Specify a timestamp to limit your results. For example, specify `2024-07-07T00:00:00Z` to see a list of command executions occurring July 7, 2021, and later.
- **InvokedBefore**: Specify a timestamp to limit your results. For example, specify `2024-07-07T00:00:00Z` to see a list of command executions from before July 7, 2021.
- **Status**: Specify a valid command status to see a list of all command executions with that status. The status choices depend on the API you call.

The status values you can specify for `ListCommands` are:

- `Pending`
- `InProgress`
- `Success`
- `Cancelled`
- `Failed`
- `TimedOut` (this includes both Delivery and Execution time outs)
- `AccessDenied`
- `DeliveryTimedOut`
- `ExecutionTimedOut`
- `Incomplete`
- `NoInstancesInTag`
- `LimitExceeded`

The status values you can specify for `ListCommandInvocations` are:

- `Pending`
- `InProgress`
- `Delayed`
- `Success`
- `Cancelled`
- `Failed`
- `TimedOut` (this includes both Delivery and Execution time outs)
- `AccessDenied`
- `DeliveryTimedOut`
- `ExecutionTimedOut`
- `Undeliverable`
- `InvalidPlatform`
- `Terminated`

- **DocumentName**: Specify name of the AWS Systems Manager document (SSM document) for which you want to see command execution results. For example, specify `AWS-`

`RunPatchBaseline` to see command executions that used this SSM document to perform security patching operations on managed nodes.

- **ExecutionStage**: Specify one of the following values (`ListCommands` operations only):
  - `Executing`: Returns a list of command executions that are currently still running.
  - `Complete`: Returns a list of command executions that have already completed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CommandInvocation

An invocation is a copy of a command sent to a specific managed node. A command can apply to one or more managed nodes. A command invocation applies to one managed node. For example, if a user runs SendCommand against three managed nodes, then a command invocation is created for each requested managed node ID. A command invocation returns status and detail information about a command you ran.

Contents

CloudWatchOutputConfig

Amazon CloudWatch Logs information where you want AWS Systems Manager to send the command output.

Type: CloudWatchOutputConfig object

Required: No

CommandId

The command against which this invocation was requested.

Type: String

Length Constraints: Fixed length of 36.

Required: No

CommandPlugins

Plugins processed by the command.

Type: Array of CommandPlugin objects

Required: No

Comment

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DocumentName

The document name that was requested for execution.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

DocumentVersion

The Systems Manager document (SSM document) version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

InstanceId

The managed node ID in which this invocation was requested.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

InstanceName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Maximum length of 255.

Required: No

NotificationConfig

Configurations for sending notifications about command status changes on a per managed node basis.

Type: NotificationConfig object

Required: No

RequestedDateTime

The time and date the request was sent to this managed node.

Type: Timestamp

Required: No

ServiceRole

The AWS Identity and Access Management (IAM) service role that Run Command, a tool in AWS Systems Manager, uses to act on your behalf when sending notifications about command status changes on a per managed node basis.

Type: String

Required: No

StandardErrorUrl

The URL to the plugin's StdErr file in Amazon Simple Storage Service (Amazon S3), if the S3 bucket was defined for the parent command. For an invocation, `StandardErrorUrl` is populated if there is just one plugin defined for the command, and the S3 bucket was defined for the command.

Type: String

Required: No

StandardOutputUrl

The URL to the plugin's StdOut file in Amazon Simple Storage Service (Amazon S3), if the S3 bucket was defined for the parent command. For an invocation, `StandardOutputUrl` is populated if there is just one plugin defined for the command, and the S3 bucket was defined for the command.

Type: String

Required: No

Status

Whether or not the invocation succeeded, failed, or is pending.

Type: String

Valid Values: `Pending | InProgress | Delayed | Success | Cancelled | TimedOut | Failed | Cancelling`

Required: No

StatusDetails

A detailed status of the command execution for each invocation (each managed node targeted by the command). StatusDetails includes more information than Status because it includes states resulting from error and concurrency control parameters. StatusDetails can show different results than Status. For more information about these statuses, see Understanding command statuses in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to the managed node.
- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.
- Success: The execution of the command or plugin was successfully completed. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's `MaxErrors` limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: Command execution started on the managed node, but the execution wasn't complete before the execution timeout expired. Execution timeouts count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Failed: The command wasn't successful on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The managed node might not exist or might not be responding. Undeliverable invocations don't count against

the parent command's MaxErrors limit and don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.

- Terminated: The parent command exceeded its MaxErrors limit and subsequent command invocations were canceled by the system. This is a terminal state.
- Delayed: The system attempted to send the command to the managed node but wasn't successful. The system retries again.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

TraceOutput

Gets the trace output sent by the agent.

Type: String

Length Constraints: Maximum length of 2500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CommandPlugin

Describes plugin details.

Contents

Name

The name of the plugin. Must be one of the following: `aws:updateAgent`, `aws:domainjoin`, `aws:applications`, `aws:runPowerShellScript`, `aws:psmodule`, `aws:cloudWatch`, `aws:runShellScript`, or `aws:updateSSMAgent`.

Type: String

Length Constraints: Minimum length of 4.

Required: No

Output

Output of the plugin execution.

Type: String

Length Constraints: Maximum length of 2500.

Required: No

OutputS3BucketName

The S3 bucket where the responses to the command executions should be stored. This was requested when issuing the command. For example, in the following response:

`amzn-s3-demo-bucket/my-prefix/i-02573cafcfEXAMPLE/awsrunShellScript`

`amzn-s3-demo-bucket` is the name of the S3 bucket;

`my-prefix` is the name of the S3 prefix;

`i-02573cafcfEXAMPLE` is the managed node ID;

`awsrunShellScript` is the name of the plugin.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 directory path inside the bucket where the responses to the command executions should be stored. This was requested when issuing the command. For example, in the following response:

`amzn-s3-demo-bucket/my-prefix/i-02573cafcfEXAMPLE/awsrunShellScript`

`amzn-s3-demo-bucket` is the name of the S3 bucket;

`my-prefix` is the name of the S3 prefix;

`i-02573cafcfEXAMPLE` is the managed node ID;

`awsrunShellScript` is the name of the plugin.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, AWS Systems Manager automatically determines the S3 bucket region.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

ResponseCode

A numeric response code generated after running the plugin.

Type: Integer

Required: No

ResponseFinishDateTime

The time the plugin stopped running. Could stop prematurely if, for example, a cancel command was sent.

Type: Timestamp

Required: No

ResponseStartDateTime

The time the plugin started running.

Type: Timestamp

Required: No

StandardErrorUrl

The URL for the complete text written by the plugin to stderr. If execution isn't yet complete, then this string is empty.

Type: String

Required: No

StandardOutputUrl

The URL for the complete text written by the plugin to stdout in Amazon S3. If the S3 bucket for the command wasn't specified, then this string is empty.

Type: String

Required: No

Status

The status of this plugin. You can run a document with multiple plugins.

Type: String

Valid Values: `Pending | InProgress | Success | TimedOut | Cancelled | Failed`

Required: No

StatusDetails

A detailed status of the plugin execution. `StatusDetails` includes more information than Status because it includes states resulting from error and concurrency control parameters. StatusDetails can show different results than Status. For more information about these statuses, see Understanding command statuses in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to the managed node.
- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.
- Success: The execution of the command or plugin was successfully completed. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's `MaxErrors` limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: Command execution started on the managed node, but the execution wasn't complete before the execution timeout expired. Execution timeouts count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Failed: The command wasn't successful on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the MaxErrors limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The managed node might not exist, or it might not be responding. Undeliverable invocations don't count against the parent command's MaxErrors limit, and they don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Terminated: The parent command exceeded its MaxErrors limit and subsequent command invocations were canceled by the system. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComplianceExecutionSummary

A summary of the call execution that includes an execution ID, the type of execution (for example, Command), and the date/time of the execution using a datetime object that is saved in the following format: `yyyy-MM-dd'T'HH:mm:ss'Z'`

Contents

ExecutionTime

The time the execution ran as a datetime object that is saved in the following format: `yyyy-MM-dd'T'HH:mm:ss'Z'`

> **Important**
>
> For State Manager associations, this timestamp represents when the compliance status was captured and reported by the Systems Manager service, not when the underlying association was actually executed on the managed node. To track actual association execution times, use the DescribeAssociationExecutionTargets command or check the association execution history in the Systems Manager console.

Type: Timestamp

Required: Yes

ExecutionId

An ID created by the system when `PutComplianceItems` was called. For example, `CommandID` is a valid execution ID. You can use this ID in subsequent calls.

Type: String

Length Constraints: Maximum length of 100.

Required: No

ExecutionType

The type of execution. For example, `Command` is a valid execution type.

Type: String

Length Constraints: Maximum length of 50.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComplianceItem

Information about the compliance as defined by the resource type. For example, for a patch resource type, `Items` includes information about the PatchSeverity, Classification, and so on.

Contents

ComplianceType

The compliance type. For example, Association (for a State Manager association), Patch, or Custom:`string` are all valid compliance types.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[A-Za-z0-9_\-]\w+|Custom:[a-zA-Z0-9_\-]\w+`

Required: No

Details

A "Key": "Value" tag combination for the compliance item.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

ExecutionSummary

A summary for the compliance item. The summary includes an execution ID, the execution type (for example, command), and the execution time.

> **Important**
>
> For State Manager associations, the `ExecutionTime` value represents when the compliance status was captured and aggregated by the Systems Manager service, not necessarily when the underlying association was executed on the managed node. State Manager updates compliance status for all associations on an instance whenever any

association executes, which means multiple associations may show the same execution time even if they were executed at different times.

Type: ComplianceExecutionSummary object

Required: No

Id

An ID for the compliance item. For example, if the compliance item is a Windows patch, the ID could be the number of the KB article; for example: KB4010320.

Type: String

Required: No

ResourceId

An ID for the resource. For a managed node, this is the node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The type of resource. `ManagedInstance` is currently the only supported resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Severity

The severity of the compliance status. Severity can be one of the following: Critical, High, Medium, Low, Informational, Unspecified.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

Status

The status of the compliance item. An item is either COMPLIANT, NON_COMPLIANT, or an empty string (for Windows patches that aren't applicable).

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: No

Title

A title for the compliance item. For example, if the compliance item is a Windows patch, the title could be the title of the KB article for the patch; for example: Security Update for Active Directory Federation Services.

Type: String

Length Constraints: Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComplianceItemEntry

Information about a compliance item.

Contents

Severity

The severity of the compliance status. Severity can be one of the following: Critical, High, Medium, Low, Informational, Unspecified.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: Yes

Status

The status of the compliance item. An item is either COMPLIANT or NON_COMPLIANT.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: Yes

Details

A "Key": "Value" tag combination for the compliance item.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

Id

The compliance item ID. For example, if the compliance item is a Windows patch, the ID could be the number of the KB article.

Type: String

Required: No

Title

The title of the compliance item. For example, if the compliance item is a Windows patch, the title could be the title of the KB article for the patch; for example: Security Update for Active Directory Federation Services.

Type: String

Length Constraints: Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComplianceStringFilter

One or more filters. Use a filter to return a more specific list of results.

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

Type

The type of comparison that should be performed for the value: Equal, NotEqual, BeginWith, LessThan, or GreaterThan.

Type: String

Valid Values: `EQUAL | NOT_EQUAL | BEGIN_WITH | LESS_THAN | GREATER_THAN`

Required: No

Values

The value for which to search.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComplianceSummaryItem

A summary of compliance information by compliance type.

Contents

ComplianceType

The type of compliance item. For example, the compliance type can be Association, Patch, or Custom:string.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[A-Za-z0-9_\-]\w+|Custom:[a-zA-Z0-9_\-]\w+`

Required: No

CompliantSummary

A list of COMPLIANT items for the specified compliance type.

Type: CompliantSummary object

Required: No

NonCompliantSummary

A list of NON_COMPLIANT items for the specified compliance type.

Type: NonCompliantSummary object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

CompliantSummary

A summary of resources that are compliant. The summary is organized according to the resource count for each compliance type.

Contents

CompliantCount

The total number of resources that are compliant.

Type: Integer

Required: No

SeveritySummary

A summary of the compliance severity by compliance type.

Type: SeveritySummary object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CreateAssociationBatchRequestEntry

Describes the association of a AWS Systems Manager document (SSM document) and a managed node.

Contents

Name

The name of the SSM document that contains the configuration information for the managed node. You can specify Command or Automation runbooks.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another account.

For SSM documents that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:aws:ssm:`*`region`*`:`*`account-id`*`:document/`*`document-name`*

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

AlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

ApplyOnlyAtCronInterval

By default, when you create a new association, the system runs it immediately after it is created and then according to the schedule you specified and when target changes are detected. Specify `true` for `ApplyOnlyAtCronInterval` if you want the association to run only according to the schedule you specified.

For more information, see Understanding when associations are applied to resources and >About target updates with Automation runbooks in the *AWS Systems Manager User Guide*.

This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationName

Specify a descriptive name for the association.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AutomationTargetParameterName

Specify the target for the association. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a tool in AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations only run when that Change Calendar is open. For more information, see AWS Systems Manager Change Calendar in the *AWS Systems Manager User Guide*.

Type: Array of strings

Required: No

ComplianceSeverity

The severity level to assign to the association.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED`

Required: No

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Duration

The number of hours the association can run before it is canceled. Duration applies to associations that are currently running, and any pending and in progress commands on all targets. If a target was taken offline for the association to run, it is made available again immediately, without a reboot.

The `Duration` parameter applies only when both these conditions are true:

- The association for which you specify a duration is cancelable according to the parameters of the SSM command document or Automation runbook associated with this execution.
- The command specifies the `ApplyOnlyAtCronInterval` parameter, which means that the association doesn't run immediately after it is created, but only according to the specified schedule.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

InstanceId

The managed node ID.

> **Note**
>
> `InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceID` with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the

system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

OutputLocation

An S3 bucket where you want to store the results of this request.

Type: InstanceAssociationOutputLocation object

Required: No

Parameters

A description of the parameters for a document.

Type: String to array of strings map

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the PutComplianceItems API operation. In this case, compliance data isn't managed by State Manager, a tool in AWS Systems Manager. It is managed by your direct call to the PutComplianceItems API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

TargetLocations

Use this action to create an association in multiple Regions and multiple accounts.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Credentials

The temporary security credentials, which include an access key ID, a secret access key, and a security (or session) token.

Contents

AccessKeyId

The access key ID that identifies the temporary security credentials.

Type: String

Pattern: `\w{16,128}`

Required: Yes

ExpirationTime

The datetime on which the current credentials expire.

Type: Timestamp

Required: Yes

SecretAccessKey

The secret access key that can be used to sign requests.

Type: String

Required: Yes

SessionToken

The token that users must pass to the service API to use the temporary credentials.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DescribeActivationsFilter

Filter for the DescribeActivation API.

Contents

FilterKey

The name of the filter.

Type: String

Valid Values: `ActivationIds | DefaultInstanceName | IamRole`

Required: No

FilterValues

The filter values.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentDefaultVersionDescription

A default version of a document.

Contents

DefaultVersion

The default version of the document.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

DefaultVersionName

The default version of the artifact associated with the document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Name

The name of the document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

DocumentDescription

Describes an AWS Systems Manager document (SSM document).

Contents

ApprovedVersion

The version of the document currently approved for use in the organization.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

AttachmentsInformation

Details about the document attachments, including names, locations, sizes, and so on.

Type: Array of AttachmentInformation objects

Required: No

Author

The user in your organization who created the document.

Type: String

Required: No

Category

The classification of a document to help you identify and categorize its use.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Length Constraints: Maximum length of 128.

Required: No

CategoryEnum

The value that identifies a document's category.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Length Constraints: Maximum length of 128.

Required: No

CreatedDate

The date when the document was created.

Type: Timestamp

Required: No

DefaultVersion

The default version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Description

A description of the document.

Type: String

Required: No

DisplayName

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see UpdateDocument.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentType

The type of document.

Type: String

Valid Values: `Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate | CloudFormation | ConformancePackTemplate | QuickSetup | ManualApprovalPolicy | AutoApprovalPolicy`

Required: No

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Hash

The Sha256 or Sha1 hash created by the system when the document was created.

> **Note**
>
> Sha1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HashType

The hash type of the document. Valid values include Sha256 or Sha1.

> **Note**
>
> Sha1 hashes have been deprecated.

Type: String

Valid Values: `Sha256 | Sha1`

Required: No

LatestVersion

The latest version of the document.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Owner

The Amazon Web Services user that created the document.

Type: String

Required: No

Parameters

A description of the parameters for a document.

Type: Array of DocumentParameter objects

Required: No

PendingReviewVersion

The version of the document that is currently under review.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

PlatformTypes

The list of operating system (OS) platforms compatible with this SSM document.

Type: Array of strings

Valid Values: `Windows | Linux | MacOS`

Required: No

Requires

A list of SSM documents required by a document. For example, an `ApplicationConfiguration` document requires an `ApplicationConfigurationSchema` document.

Type: Array of DocumentRequires objects

Array Members: Minimum number of 1 item.

Required: No

ReviewInformation

Details about the review of a document.

Type: Array of ReviewInformation objects

Array Members: Minimum number of 1 item.

Required: No

ReviewStatus

The current status of the review.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Required: No

SchemaVersion

The schema version.

Type: String

Pattern: `([0-9]+)\.([0-9]+)`

Required: No

Sha1

The SHA1 hash of the document, which you can use for verification.

Type: String

Required: No

Status

The status of the SSM document.

Type: String

Valid Values: `Creating | Active | Updating | Deleting | Failed`

Required: No

StatusInformation

A message returned by AWS Systems Manager that explains the `Status` value. For example, a `Failed` status might be explained by the `StatusInformation` message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

Required: No

Tags

The tags, or metadata, that have been applied to the document.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

TargetType

The target type which defines the kinds of resources the document can run on. For example, `/AWS::EC2::Instance`. For a list of valid resource types, see AWS resource and property types reference in the *AWS CloudFormation User Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^\/[\w\.\-\:\/]*$`

Required: No

VersionName

The version of the artifact associated with the document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentFilter

This data type is deprecated. Instead, use DocumentKeyValuesFilter.

Contents

key

The name of the filter.

Type: String

Valid Values: `Name | Owner | PlatformTypes | DocumentType`

Required: Yes

value

The value of the filter.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentIdentifier

Describes the name of a SSM document.

Contents

Author

The user in your organization who created the document.

Type: String

Required: No

CreatedDate

The date the SSM document was created.

Type: Timestamp

Required: No

DisplayName

An optional field where you can specify a friendly name for the SSM document. This value can differ for each version of the document. If you want to update this value, see UpdateDocument.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentType

The document type.

Type: String

Valid Values: `Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate | CloudFormation | ConformancePackTemplate | QuickSetup | ManualApprovalPolicy | AutoApprovalPolicy`

Required: No

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Name

The name of the SSM document.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

Owner

The Amazon Web Services user that created the document.

Type: String

Required: No

PlatformTypes

The operating system platform.

Type: Array of strings

Valid Values: `Windows | Linux | MacOS`

Required: No

Requires

A list of SSM documents required by a document. For example, an `ApplicationConfiguration` document requires an `ApplicationConfigurationSchema` document.

Type: Array of DocumentRequires objects

Array Members: Minimum number of 1 item.

Required: No

ReviewStatus

The current status of a document review.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Required: No

SchemaVersion

The schema version.

Type: String

Pattern: `([0-9]+)\.([0-9]+)`

Required: No

Tags

The tags, or metadata, that have been applied to the document.

Type: Array of Tag objects

Array Members: Maximum number of 1000 items.

Required: No

TargetType

The target type which defines the kinds of resources the document can run on. For example, `/AWS::EC2::Instance`. For a list of valid resource types, see AWS resource and property types reference in the *AWS CloudFormation User Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^\/[\w\.\-\:\/]*$`

Required: No

VersionName

An optional field specifying the version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentKeyValuesFilter

One or more filters. Use a filter to return a more specific list of documents.

For keys, you can specify one or more tags that have been applied to a document.

You can also use AWS-provided keys, some of which have specific allowed values. These keys and their associated values are as follows:

DocumentType

- `ApplicationConfiguration`
- `ApplicationConfigurationSchema`
- `Automation`
- `ChangeCalendar`
- `Command`
- `Package`
- `Policy`
- `Session`

Owner

Note that only one `Owner` can be specified in a request. For example: `Key=Owner,Values=Self`.

- `Amazon`
- `Private`
- `Public`
- `Self`
- `ThirdParty`

PlatformTypes

- `Linux`
- `Windows`

`Name` is another AWS-provided key. If you use `Name` as a key, you can use a name prefix to return a list of documents. For example, in the AWS CLI, to return a list of all documents that begin with `Te`, run the following command:

```
aws ssm list-documents --filters Key=Name,Values=Te
```

You can also use the `TargetType` AWS-provided key. For a list of valid resource type values that can be used with this key, see AWS resource and property types reference in the *AWS CloudFormation User Guide*.

If you specify more than two keys, only documents that are identified by all the tags are returned in the results. If you specify more than two values for a key, documents that are identified by any of the values are returned in the results.

To specify a custom key-value pair, use the format `Key=tag:tagName,Values=valueName`.

For example, if you created a key called region and are using the AWS CLI to call the `list-documents` command:

```
aws ssm list-documents --filters Key=tag:region,Values=east,west
Key=Owner,Values=Self
```

Contents

Key

The name of the filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The value for the filter key.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentMetadataResponseInfo

Details about the response to a document review request.

Contents

ReviewerResponse

Details about a reviewer's response to a document review request.

Type: Array of DocumentReviewerResponseSource objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentParameter

Parameters specified in a Systems Manager document that run on the server when the command is run.

Contents

DefaultValue

If specified, the default values for the parameters. Parameters without a default value are required. Parameters with a default value are optional.

Type: String

Required: No

Description

A description of what the parameter does, how to use it, the default value, and whether or not the parameter is optional.

Type: String

Required: No

Name

The name of the parameter.

Type: String

Required: No

Type

The type of parameter. The type can be either String or StringList.

Type: String

Valid Values: `String | StringList`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentRequires

An SSM document required by the current document.

Contents

Name

The name of the required SSM document. The name can be an Amazon Resource Name (ARN).

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

RequireType

The document type of the required SSM document.

Type: String

Length Constraints: Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Version

The document version required by the current document.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

VersionName

An optional field specifying the version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentReviewCommentSource

Information about comments added to a document review request.

Contents

Content

The content of a comment entered by a user who requests a review of a new document version, or who reviews the new version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: No

Type

The type of information added to a review request. Currently, only the value `Comment` is supported.

Type: String

Valid Values: `Comment`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentReviewerResponseSource

Information about a reviewer's response to a document review request.

Contents

Comment

The comment entered by a reviewer as part of their document review response.

Type: Array of DocumentReviewCommentSource objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

CreateTime

The date and time that a reviewer entered a response to a document review request.

Type: Timestamp

Required: No

Reviewer

The user in your organization assigned to review a document request.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

ReviewStatus

The current review status of a new custom SSM document created by a member of your organization, or of the latest version of an existing SSM document.

Only one version of a document can be in the APPROVED state at a time. When a new version is approved, the status of the previous version changes to REJECTED.

Only one version of a document can be in review, or PENDING, at a time.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Required: No

UpdatedTime

The date and time that a reviewer last updated a response to a document review request.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentReviews

Information about a document approval review.

Contents

Action

The action to take on a document approval review request.

Type: String

Valid Values: `SendForReview | UpdateReview | Approve | Reject`

Required: Yes

Comment

A comment entered by a user in your organization about the document review request.

Type: Array of DocumentReviewCommentSource objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DocumentVersionInfo

Version information about the document.

Contents

CreatedDate

The date the document was created.

Type: Timestamp

Required: No

DisplayName

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see UpdateDocument.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^[\w\.\-\:\/ ]*$`

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: `YAML | JSON | TEXT`

Required: No

DocumentVersion

The document version.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

IsDefaultVersion

An identifier for the default version of the document.

Type: Boolean

Required: No

Name

The document name.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

ReviewStatus

The current status of the approval review for the latest version of the document.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Required: No

Status

The status of the SSM document, such as `Creating`, `Active`, `Failed`, and `Deleting`.

Type: String

Valid Values: `Creating | Active | Updating | Deleting | Failed`

Required: No

StatusInformation

A message returned by AWS Systems Manager that explains the `Status` value. For example, a `Failed` status might be explained by the `StatusInformation` message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

Required: No

VersionName

The version of the artifact associated with the document. For example, 12.6. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EffectivePatch

The `EffectivePatch` structure defines metadata about a patch along with the approval state of the patch in a particular patch baseline. The approval state includes information about whether the patch is currently approved, due to be approved by a rule, explicitly approved, or explicitly rejected and the date the patch was or will be approved.

Contents

Patch

Provides metadata for a patch, including information such as the KB ID, severity, classification and a URL for where more information can be obtained about the patch.

Type: Patch object

Required: No

PatchStatus

The status of the patch in a patch baseline. This includes information about whether the patch is currently approved, due to be approved by a rule, explicitly approved, or explicitly rejected and the date the patch was or will be approved.

Type: PatchStatus object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ExecutionInputs

Information about the inputs for an execution preview.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

Automation

Information about the optional inputs that can be specified for an automation execution preview.

Type: AutomationExecutionInputs object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ExecutionPreview

Information about the changes that would be made if an execution were run.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

Automation

Information about the changes that would be made if an Automation workflow were run.

Type: AutomationExecutionPreview object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FailedCreateAssociation

Describes a failed association.

Contents

Entry

The association.

Type: CreateAssociationBatchRequestEntry object

Required: No

Fault

The source of the failure.

Type: String

Valid Values: `Client | Server | Unknown`

Required: No

Message

A description of the failure.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FailureDetails

Information about an Automation failure.

Contents

Details

Detailed information about the Automation step failure.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

FailureStage

The stage of the Automation execution when the failure occurred. The stages include the following: InputValidation, PreVerification, Invocation, PostVerification.

Type: String

Required: No

FailureType

The type of Automation failure. Failure types include the following: Action, Permission, Throttling, Verification, Internal.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

GetResourcePoliciesResponseEntry

A resource policy helps you to define the IAM entity (for example, an AWS account) that can manage your Systems Manager resources. Currently, `OpsItemGroup` is the only resource that supports Systems Manager resource policies. The resource policy for `OpsItemGroup` enables AWS accounts to view and interact with OpsCenter operational work items (OpsItems).

Contents

Policy

A resource policy helps you to define the IAM entity (for example, an AWS account) that can manage your Systems Manager resources. Currently, `OpsItemGroup` is the only resource that supports Systems Manager resource policies. The resource policy for `OpsItemGroup` enables AWS accounts to view and interact with OpsCenter operational work items (OpsItems).

Type: String

Pattern: `^(?!\s*$).+`

Required: No

PolicyHash

ID of the current policy version. The hash helps to prevent a situation where multiple users attempt to overwrite a policy. You must provide this hash when updating or deleting a policy.

Type: String

Required: No

PolicyId

A policy ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceAggregatedAssociationOverview

Status information about the aggregated associations.

Contents

DetailedStatus

Detailed status information about the aggregated associations.

Type: String

Required: No

InstanceAssociationStatusAggregatedCount

The number of associations for the managed nodes.

Type: String to integer map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceAssociation

One or more association documents on the managed node.

Contents

AssociationId

The association ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationVersion

Version information for the association on the managed node.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

Content

The content of the association document for the managed nodes.

Type: String

Length Constraints: Minimum length of 1.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceAssociationOutputLocation

An S3 bucket where you want to store the results of this request.

For the minimal permissions required to enable Amazon S3 output for an association, see Create an association (console) in the *Systems Manager User Guide*.

Contents

S3Location

An S3 bucket where you want to store the results of this request.

Type: S3OutputLocation object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceAssociationOutputUrl

The URL of S3 bucket where you want to store the results of this request.

Contents

S3OutputUrl

The URL of S3 bucket where you want to store the results of this request.

Type: S3OutputUrl object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceAssociationStatusInfo

Status information about the association.

Contents

AssociationId

The association ID.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: No

AssociationName

The name of the association applied to the managed node.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

AssociationVersion

The version of the association applied to the managed node.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

DetailedStatus

Detailed status information about the association.

Type: String

Required: No

DocumentVersion

The association document versions.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

ErrorCode

An error code returned by the request to create the association.

Type: String

Length Constraints: Maximum length of 10.

Required: No

ExecutionDate

The date the association ran.

Type: Timestamp

Required: No

ExecutionSummary

Summary information about association execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

InstanceId

The managed node ID where the association was created.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

Name

The name of the association.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: No

OutputUrl

A URL for an S3 bucket where you want to store the results of this request.

Type: InstanceAssociationOutputUrl object

Required: No

Status

Status information about the association.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceInfo

Details about a specific managed node.

Contents

AgentType

The type of agent installed on the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

AgentVersion

The version number of the agent installed on the node.

Type: String

Pattern: `^[0-9]{1,6}(\.[0-9]{1,6}){2,3}$`

Required: No

ComputerName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

InstanceStatus

The current status of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

IpAddress

The IP address of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 46.

Required: No

ManagedStatus

Indicates whether the node is managed by Systems Manager.

Type: String

Valid Values: `All | Managed | Unmanaged`

Required: No

PlatformName

The name of the operating system platform running on your managed node.

Type: String

Length Constraints: Maximum length of 120.

Required: No

PlatformType

The operating system platform type of the managed node.

Type: String

Valid Values: `Windows | Linux | MacOS`

Required: No

PlatformVersion

The version of the OS platform running on your managed node.

Type: String

Length Constraints: Maximum length of 120.

Required: No

ResourceType

The type of instance, either an EC2 instance or another supported machine type in a hybrid fleet.

Type: String

Valid Values: `ManagedInstance | EC2Instance`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceInformation

Describes a filter for a specific list of managed nodes.

Contents

ActivationId

The activation ID created by AWS Systems Manager when the server or virtual machine (VM) was registered.

Type: String

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

AgentVersion

The version of SSM Agent running on your Linux managed node.

Type: String

Pattern: `^[0-9]{1,6}(\.[0-9]{1,6}){2,3}$`

Required: No

AssociationOverview

Information about the association.

Type: InstanceAggregatedAssociationOverview object

Required: No

AssociationStatus

The status of the association.

Type: String

Required: No

ComputerName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

IamRole

The role assigned to an Amazon EC2 instance configured with a Systems Manager Quick Setup host management configuration or the role assigned to an on-premises managed node.

This call doesn't return the IAM role for *unmanaged* Amazon EC2 instances (instances not configured for Systems Manager). To retrieve the role for an unmanaged instance, use the Amazon EC2 `DescribeInstances` operation. For information, see DescribeInstances in the *Amazon EC2 API Reference* or describe-instances in the *AWS CLI Command Reference*.

Type: String

Length Constraints: Maximum length of 64.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

IPAddress

The IP address of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 46.

Required: No

IsLatestVersion

Indicates whether the latest version of SSM Agent is running on your Linux managed node. This field doesn't indicate whether or not the latest version is installed on Windows managed nodes,

because some older versions of Windows Server use the EC2Config service to process Systems Manager requests.

Type: Boolean

Required: No

LastAssociationExecutionDate

The date the association was last run.

Type: Timestamp

Required: No

LastPingDateTime

The date and time when the agent last pinged the Systems Manager service.

Type: Timestamp

Required: No

LastSuccessfulAssociationExecutionDate

The last date the association was successfully run.

Type: Timestamp

Required: No

Name

The name assigned to an on-premises server, edge device, or virtual machine (VM) when it is activated as a Systems Manager managed node. The name is specified as the `DefaultInstanceName` property using the CreateActivation command. It is applied to the managed node by specifying the Activation Code and Activation ID when you install SSM Agent on the node, as explained in How to install SSM Agent on hybrid Linux nodes and How to install SSM Agent on hybrid Windows Server nodes. To retrieve the `Name` tag of an EC2 instance, use the Amazon EC2 `DescribeInstances` operation. For information, see DescribeInstances in the *Amazon EC2 API Reference* or describe-instances in the *AWS CLI Command Reference*.

Type: String

Required: No

PingStatus

Connection status of SSM Agent.

> **Note**
>
> The status `Inactive` has been deprecated and is no longer in use.

Type: String

Valid Values: `Online | ConnectionLost | Inactive`

Required: No

PlatformName

The name of the operating system platform running on your managed node.

Type: String

Required: No

PlatformType

The operating system platform type.

Type: String

Valid Values: `Windows | Linux | MacOS`

Required: No

PlatformVersion

The version of the OS platform running on your managed node.

Type: String

Required: No

RegistrationDate

The date the server or VM was registered with AWS as a managed node.

Type: Timestamp

Required: No

ResourceType

The type of instance. Instances are either EC2 instances or managed instances.

Type: String

Valid Values: `ManagedInstance | EC2Instance`

Required: No

SourceId

The ID of the source resource. For AWS IoT Greengrass devices, `SourceId` is the Thing name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^[a-zA-Z0-9:_-]*$`

Required: No

SourceType

The type of the source resource. For AWS IoT Greengrass devices, `SourceType` is `AWS::IoT::Thing`.

Type: String

Valid Values: `AWS::EC2::Instance | AWS::IoT::Thing | AWS::SSM::ManagedInstance`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

InstanceInformationFilter

Describes a filter for a specific list of managed nodes. You can filter node information by using tags. You specify tags by using a key-value mapping.

Use this operation instead of the DescribeInstanceInformation:InstanceInformationFilterList method. The `InstanceInformationFilterList` method is a legacy method and doesn't support tags.

Contents

key

The name of the filter.

Type: String

Valid Values: `InstanceIds | AgentVersion | PingStatus | PlatformTypes | ActivationIds | IamRole | ResourceType | AssociationStatus`

Required: Yes

valueSet

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

InstanceInformationStringFilter

The filters to describe or get information about your managed nodes.

Contents

Key

The filter key name to describe your managed nodes.

Valid filter key values: ActivationIds | AgentVersion | AssociationStatus | IamRole | InstanceIds | PingStatus | PlatformType | ResourceType | SourceIds | SourceTypes | "tag-key" | "tag:{keyname}

- Valid values for the `AssociationStatus` filter key: Success | Pending | Failed
- Valid values for the `PingStatus` filter key: Online | ConnectionLost | Inactive (deprecated)
- Valid values for the `PlatformType` filter key: Windows | Linux | MacOS
- Valid values for the `ResourceType` filter key: EC2Instance | ManagedInstance
- Valid values for the `SourceType` filter key: AWS::EC2::Instance | AWS::SSM::ManagedInstance | AWS::IoT::Thing
- Valid tag examples: `Key=tag-key,Values=Purpose` | `Key=tag:Purpose,Values=Test`.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Values

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstancePatchState

Defines the high-level patch compliance state for a managed node, providing information about the number of installed, missing, not applicable, and failed patches along with metadata about the operation when this information was gathered for the managed node.

Contents

BaselineId

The ID of the patch baseline used to patch the managed node.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: Yes

InstanceId

The ID of the managed node the high-level patch compliance information was collected for.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: Yes

Operation

The type of patching operation that was performed: or

- `SCAN` assesses the patch compliance state.
- `INSTALL` installs missing patches.

Type: String

Valid Values: `Scan | Install`

Required: Yes

OperationEndTime

The time the most recent patching operation completed on the managed node.

Type: Timestamp

Required: Yes

OperationStartTime

The time the most recent patching operation was started on the managed node.

Type: Timestamp

Required: Yes

PatchGroup

The name of the patch group the managed node belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

AvailableSecurityUpdateCount

The number of security-related patches that are available but not approved because they didn't meet the patch baseline requirements. For example, an updated version of a patch might have been released before the specified auto-approval period was over.

Applies to Windows Server managed nodes only.

Type: Integer

Required: No

CriticalNonCompliantCount

The number of patches per node that are specified as `Critical` for compliance reporting in the patch baseline aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

Required: No

FailedCount

The number of patches from the patch baseline that were attempted to be installed during the last patching operation, but failed to install.

Type: Integer

Required: No

InstalledCount

The number of patches from the patch baseline that are installed on the managed node.

Type: Integer

Required: No

InstalledOtherCount

The number of patches not specified in the patch baseline that are installed on the managed node.

Type: Integer

Required: No

InstalledPendingRebootCount

The number of patches installed by Patch Manager since the last time the managed node was rebooted.

Type: Integer

Required: No

InstalledRejectedCount

The number of patches installed on a managed node that are specified in a `RejectedPatches` list. Patches with a status of `InstalledRejected` were typically installed before they were added to a `RejectedPatches` list.

> **Note**
>
> If `ALLOW_AS_DEPENDENCY` is the specified option for `RejectedPatchesAction`, the value of `InstalledRejectedCount` will always be `0` (zero).

Type: Integer

Required: No

InstallOverrideList

An https URL or an Amazon Simple Storage Service (Amazon S3) path-style URL to a list of patches to be installed. This patch installation list, which you maintain in an S3 bucket in YAML format and specify in the SSM document `AWS-RunPatchBaseline`, overrides the patches specified by the default patch baseline.

For more information about the `InstallOverrideList` parameter, see SSM Command document for patching: `AWS-RunPatchBaseline` in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^https://.+$|^s3://([^/]+)/(.*?([^/]+))$`

Required: No

LastNoRebootInstallOperationTime

The time of the last attempt to patch the managed node with `NoReboot` specified as the reboot option.

Type: Timestamp

Required: No

MissingCount

The number of patches from the patch baseline that are applicable for the managed node but aren't currently installed.

Type: Integer

Required: No

NotApplicableCount

The number of patches from the patch baseline that aren't applicable for the managed node and therefore aren't installed on the node. This number may be truncated if the list

of patch names is very large. The number of patches beyond this limit are reported in `UnreportedNotApplicableCount`.

Type: Integer

Required: No

OtherNonCompliantCount

The number of patches per node that are specified as other than `Critical` or `Security` but aren't compliant with the patch baseline. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

Required: No

OwnerInformation

Placeholder information. This field will always be empty in the current release of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

RebootOption

Indicates the reboot option specified in the patch baseline.

> **Note**
>
> Reboot options apply to `Install` operations only. Reboots aren't attempted for Patch Manager `Scan` operations.

- `RebootIfNeeded`: Patch Manager tries to reboot the managed node if it installed any patches, or if any patches are detected with a status of `InstalledPendingReboot`.
- `NoReboot`: Patch Manager attempts to install missing packages without trying to reboot the system. Patches installed with this option are assigned a status of `InstalledPendingReboot`. These patches might not be in effect until a reboot is performed.

Type: String

Valid Values: `RebootIfNeeded | NoReboot`

Required: No

SecurityNonCompliantCount

The number of patches per node that are specified as `Security` in a patch advisory aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

Required: No

SnapshotId

The ID of the patch baseline snapshot used during the patching operation when this compliance data was collected.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

UnreportedNotApplicableCount

The number of patches beyond the supported limit of `NotApplicableCount` that aren't reported by name to Inventory. Inventory is a tool in AWS Systems Manager.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstancePatchStateFilter

Defines a filter used in DescribeInstancePatchStatesForPatchGroup to scope down the information returned by the API.

Example: To filter for all managed nodes in a patch group having more than three patches with a `FailedCount` status, use the following for the filter:

- Value for `Key`: `FailedCount`
- Value for `Type`: `GreaterThan`
- Value for `Values`: `3`

Contents

Key

The key for the filter. Supported values include the following:

- `InstalledCount`
- `InstalledOtherCount`
- `InstalledPendingRebootCount`
- `InstalledRejectedCount`
- `MissingCount`
- `FailedCount`
- `UnreportedNotApplicableCount`
- `NotApplicableCount`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Type

The type of comparison that should be performed for the value.

Type: String

Valid Values: `Equal | NotEqual | LessThan | GreaterThan`

Required: Yes

Values

The value for the filter. Must be an integer greater than or equal to 0.

Type: Array of strings

Array Members: Fixed number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstanceProperty

An object containing various properties of a managed node.

Contents

ActivationId

The activation ID created by Systems Manager when the server or virtual machine (VM) was registered

Type: String

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

AgentVersion

The version of SSM Agent running on your managed node.

Type: String

Pattern: `^[0-9]{1,6}(\.[0-9]{1,6}){2,3}$`

Required: No

Architecture

The CPU architecture of the node. For example, `x86_64`.

Type: String

Length Constraints: Maximum length of 120.

Required: No

AssociationOverview

Status information about the aggregated associations.

Type: InstanceAggregatedAssociationOverview object

Required: No

AssociationStatus

The status of the State Manager association applied to the managed node.

Type: String

Required: No

ComputerName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

IamRole

The IAM role used in the hybrid activation to register the node with Systems Manager.

Type: String

Length Constraints: Maximum length of 64.

Required: No

InstanceId

The ID of the managed node.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

InstanceRole

The instance profile attached to the node. If an instance profile isn't attached to the node, this value is blank.

Type: String

Length Constraints: Maximum length of 120.

Required: No

InstanceState

The current state of the node.

Type: String

Length Constraints: Maximum length of 120.

Required: No

InstanceType

The instance type of the managed node. For example, t3.large.

Type: String

Length Constraints: Maximum length of 120.

Required: No

IPAddress

The public IPv4 address assigned to the node. If a public IPv4 address isn't assigned to the node, this value is blank.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 46.

Required: No

KeyName

The name of the key pair associated with the node. If a key pair isnt't associated with the node, this value is blank.

Type: String

Length Constraints: Maximum length of 255.

Required: No

LastAssociationExecutionDate

The date the association was last run.

Type: Timestamp

Required: No

LastPingDateTime

The date and time when the SSM Agent last pinged the Systems Manager service.

Type: Timestamp

Required: No

LastSuccessfulAssociationExecutionDate

The last date the association was successfully run.

Type: Timestamp

Required: No

LaunchTime

The timestamp for when the node was launched.

Type: Timestamp

Required: No

Name

The value of the EC2 `Name` tag associated with the node. If a `Name` tag hasn't been applied to the node, this value is blank.

Type: String

Length Constraints: Maximum length of 255.

Required: No

PingStatus

Connection status of the SSM Agent on the managed node.

Type: String

Valid Values: `Online | ConnectionLost | Inactive`

Required: No

PlatformName

The name of the operating system platform running on your managed node.

Type: String

Length Constraints: Maximum length of 120.

Required: No

PlatformType

The operating system platform type of the managed node. For example, Windows Server or Amazon Linux 2.

Type: String

Valid Values: `Windows | Linux | MacOS`

Required: No

PlatformVersion

The version of the OS platform running on your managed node.

Type: String

Length Constraints: Maximum length of 120.

Required: No

RegistrationDate

The date the node was registered with Systems Manager.

Type: Timestamp

Required: No

ResourceType

The type of managed node.

Type: String

Required: No

SourceId

The ID of the source resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^[a-zA-Z0-9:_-]*$`

Required: No

SourceType

The type of the source resource.

Type: String

Valid Values: `AWS::EC2::Instance | AWS::IoT::Thing | AWS::SSM::ManagedInstance`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstancePropertyFilter

Describes a filter for a specific list of managed nodes. You can filter node information by using tags. You specify tags by using a key-value mapping.

Contents

key

The name of the filter.

Type: String

Valid Values: `InstanceIds | AgentVersion | PingStatus | PlatformTypes | DocumentName | ActivationIds | IamRole | ResourceType | AssociationStatus`

Required: Yes

valueSet

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Length Constraints: Minimum length of 1. Maximum length of 100000.

Pattern: `^.{1,100000}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InstancePropertyStringFilter

The filters to describe or get information about your managed nodes.

Contents

Key

The filter key name to describe your managed nodes.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100000.

Pattern: `^.{1,100000}$`

Required: Yes

Values

The filter key name to describe your managed nodes.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Length Constraints: Minimum length of 1. Maximum length of 100000.

Pattern: `^.{1,100000}$`

Required: Yes

Operator

The operator used by the filter call.

Type: String

Valid Values: `Equal | NotEqual | BeginWith | LessThan | GreaterThan`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryAggregator

Specifies the inventory type and attribute for the aggregation execution.

Contents

Aggregators

Nested aggregators to further refine aggregation for an inventory type.

Type: Array of InventoryAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

Expression

The inventory type and attribute name for aggregation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

Groups

A user-defined set of one or more filters on which to aggregate inventory data. Groups return a count of resources that match and don't match the specified criteria.

Type: Array of InventoryGroup objects

Array Members: Minimum number of 1 item. Maximum number of 15 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryDeletionStatusItem

Status information returned by the `DeleteInventory` operation.

Contents

DeletionId

The deletion ID returned by the `DeleteInventory` operation.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

DeletionStartTime

The UTC timestamp when the delete operation started.

Type: Timestamp

Required: No

DeletionSummary

Information about the delete operation. For more information about this summary, see Understanding the delete inventory summary in the *AWS Systems Manager User Guide*.

Type: InventoryDeletionSummary object

Required: No

LastStatus

The status of the operation. Possible values are InProgress and Complete.

Type: String

Valid Values: `InProgress | Complete`

Required: No

LastStatusMessage

Information about the status.

Type: String

Required: No

LastStatusUpdateTime

The UTC timestamp of when the last status report.

Type: Timestamp

Required: No

TypeName

The name of the inventory data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryDeletionSummary

Information about the delete operation.

Contents

RemainingCount

Remaining number of items to delete.

Type: Integer

Required: No

SummaryItems

A list of counts and versions for deleted items.

Type: Array of InventoryDeletionSummaryItem objects

Required: No

TotalCount

The total number of items to delete. This count doesn't change during the delete operation.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryDeletionSummaryItem

Either a count, remaining count, or a version number in a delete inventory summary.

Contents

Count

A count of the number of deleted items.

Type: Integer

Required: No

RemainingCount

The remaining number of items to delete.

Type: Integer

Required: No

Version

The inventory type version.

Type: String

Pattern: `^([0-9]{1,6})(\.[0-9]{1,6})$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryFilter

One or more filters. Use a filter to return a more specific list of results.

Example formats for the `aws ssm get-inventory` command:

```
--filters Key=AWS:InstanceInformation.AgentType,Values=amazon-ssm-
agent,Type=Equal
```

```
--filters
Key=AWS:InstanceInformation.AgentVersion,Values=3.3.2299.0,Type=Equal
```

```
--filters Key=AWS:InstanceInformation.ComputerName,Values=ip-192.0.2.0.us-
east-2.compute.internal,Type=Equal
```

```
--filters
Key=AWS:InstanceInformation.InstanceId,Values=i-0a4cd6ceffEXAMPLE,i-1a2b3c4d5e6E
```

```
--filters
Key=AWS:InstanceInformation.InstanceStatus,Values=Active,Type=Equal
```

```
--filters
Key=AWS:InstanceInformation.IpAddress,Values=198.51.100.0,Type=Equal
```

```
--filters Key=AWS:InstanceInformation.PlatformName,Values="Amazon
Linux",Type=Equal
```

```
--filters Key=AWS:InstanceInformation.PlatformType,Values=Linux,Type=Equal
```

```
--filters
Key=AWS:InstanceInformation.PlatformVersion,Values=2023,Type=BeginWith
```

```
--filters
Key=AWS:InstanceInformation.ResourceType,Values=EC2Instance,Type=Equal
```

Contents

Key

The name of the filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Values

Inventory filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Required: Yes

Type

The type of filter.

> **Note**
>
> The `Exists` filter must be used with aggregators. For more information, see Aggregating inventory data in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `Equal | NotEqual | BeginWith | LessThan | GreaterThan | Exists`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryGroup

A user-defined set of one or more filters on which to aggregate inventory data. Groups return a count of resources that match and don't match the specified criteria.

Contents

Filters

Filters define the criteria for the group. The `matchingCount` field displays the number of resources that match the criteria. The `notMatchingCount` field displays the number of resources that don't match the criteria.

Type: Array of InventoryFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Name

The name of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryItem

Information collected from managed nodes based on your inventory policy document

Contents

CaptureTime

The time the inventory information was collected.

Type: String

Pattern: `^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|[0-1][0-9])(:[0-5][0-9])(:[0-5][0-9])(Z)$`

Required: Yes

SchemaVersion

The schema version for the inventory item.

Type: String

Pattern: `^([0-9]{1,6})(\.[0-9]{1,6})$`

Required: Yes

TypeName

The name of the inventory type. Default inventory item type names start with `AWS`. Custom inventory type names will start with Custom. Default inventory item types include the following: `AWS:AWSComponent`, `AWS:Application`, `AWS:InstanceInformation`, `AWS:Network`, and `AWS:WindowsUpdate`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

Content

The inventory data of the inventory type.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

ContentHash

MD5 hash of the inventory item type contents. The content hash is used to determine whether to update inventory information. The PutInventory API doesn't update the inventory item type contents if the MD5 hash hasn't changed since last update.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Context

A map of associated properties for a specified inventory type. For example, with this attribute, you can specify the `ExecutionId`, `ExecutionType`, `ComplianceType` properties of the `AWS:ComplianceItem` type.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryItemAttribute

Attributes are the entries within the inventory item content. It contains name and value.

Contents

DataType

The data type of the inventory item attribute.

Type: String

Valid Values: `string | number`

Required: Yes

Name

Name of the inventory item attribute.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryItemSchema

The inventory item schema definition. Users can use this to compose inventory query filters.

Contents

Attributes

The schema attributes for inventory. This contains data type and attribute name.

Type: Array of InventoryItemAttribute objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

TypeName

The name of the inventory type. Default inventory item type names start with AWS. Custom inventory type names will start with Custom. Default inventory item types include the following: `AWS:AWSComponent`, `AWS:Application`, `AWS:InstanceInformation`, `AWS:Network`, and `AWS:WindowsUpdate`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

DisplayName

The alias name of the inventory type. The alias name is used for display purposes.

Type: String

Required: No

Version

The schema version for the inventory item.

Type: String

Pattern: `^([0-9]{1,6})(\.[0-9]{1,6})$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryResultEntity

Inventory query results.

Contents

Data

The data section in the inventory result entity JSON.

Type: String to InventoryResultItem object map

Required: No

Id

ID of the inventory result entity. For example, for managed node inventory the result will be the managed node ID. For EC2 instance inventory, the result will be the instance ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InventoryResultItem

The inventory result item.

Contents

Content

Contains all the inventory data of the item type. Results include attribute names and values.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: Yes

SchemaVersion

The schema version for the inventory result item/

Type: String

Pattern: `^([0-9]{1,6})(\.[0-9]{1,6})$`

Required: Yes

TypeName

The name of the inventory result item type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

CaptureTime

The time inventory item data was captured.

Type: String

Pattern: `^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|[0-1][0-9])(:[0-5][0-9])(:[0-5][0-9])(Z)$`

Required: No

ContentHash

MD5 hash of the inventory item type contents. The content hash is used to determine whether to update inventory information. The PutInventory API doesn't update the inventory item type contents if the MD5 hash hasn't changed since last update.

Type: String

Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

LoggingInfo

Information about an Amazon Simple Storage Service (Amazon S3) bucket to write managed node-level logs to.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Contents

S3BucketName

The name of an S3 bucket where execution logs are stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: Yes

S3Region

The AWS Region where the S3 bucket is located.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: Yes

S3KeyPrefix

(Optional) The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowAutomationParameters

The parameters for an `AUTOMATION` task type.

Contents

DocumentVersion

The version of an Automation runbook to use during task execution.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

Parameters

The parameters for the `AUTOMATION` task.

For information about specifying and updating task parameters, see RegisterTaskWithMaintenanceWindow and UpdateMaintenanceWindowTask.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> For `AUTOMATION` task types, AWS Systems Manager ignores any values specified for these parameters.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowExecution

Describes the information about an execution of a maintenance window.

Contents

EndTime

The time the execution finished.

Type: Timestamp

Required: No

StartTime

The time the execution started.

Type: Timestamp

Required: No

Status

The status of the execution.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

Required: No

StatusDetails

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

WindowExecutionId

The ID of the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowExecutionTaskIdentity

Information about a task execution performed as part of a maintenance window execution.

Contents

AlarmConfiguration

The details for the CloudWatch alarm applied to your maintenance window task.

Type: AlarmConfiguration object

Required: No

EndTime

The time the task execution finished.

Type: Timestamp

Required: No

StartTime

The time the task execution started.

Type: Timestamp

Required: No

Status

The status of the task execution.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

Required: No

StatusDetails

The details explaining the status of the task execution. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

TaskArn

The Amazon Resource Name (ARN) of the task that ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

TaskExecutionId

The ID of the specific task execution in the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

TaskType

The type of task that ran.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

Required: No

TriggeredAlarms

The CloudWatch alarm that was invoked by the maintenance window task.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

WindowExecutionId

The ID of the maintenance window execution that ran the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowExecutionTaskInvocationIdentity

Describes the information about a task invocation for a particular target as part of a task execution performed as part of a maintenance window execution.

Contents

EndTime

The time the invocation finished.

Type: Timestamp

Required: No

ExecutionId

The ID of the action performed in the service that actually handled the task invocation. If the task type is `RUN_COMMAND`, this value is the command ID.

Type: String

Required: No

InvocationId

The ID of the task invocation.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

OwnerInformation

User-provided value that was specified when the target was registered with the maintenance window. This was also included in any Amazon CloudWatch Events events raised during the task invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Parameters

The parameters that were provided for the invocation when it was run.

Type: String

Required: No

StartTime

The time the invocation started.

Type: Timestamp

Required: No

Status

The status of the task invocation.

Type: String

Valid Values: `PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING`

Required: No

StatusDetails

The details explaining the status of the task invocation. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

TaskExecutionId

The ID of the specific task execution in the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

TaskType

The task type.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

Required: No

WindowExecutionId

The ID of the maintenance window execution that ran the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

WindowTargetId

The ID of the target definition in this maintenance window the invocation was performed for.

Type: String

Length Constraints: Maximum length of 36.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowFilter

Filter used in the request. Supported filter keys depend on the API operation that includes the filter. API operations that use `MaintenanceWindowFilter>` include the following:

- DescribeMaintenanceWindowExecutions
- DescribeMaintenanceWindowExecutionTaskInvocations
- DescribeMaintenanceWindowExecutionTasks
- DescribeMaintenanceWindows
- DescribeMaintenanceWindowTargets
- DescribeMaintenanceWindowTasks

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The filter values.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowIdentity

Information about the maintenance window.

Contents

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: No

Description

A description of the maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

Enabled

Indicates whether the maintenance window is enabled.

Type: Boolean

Required: No

EndDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive.

Type: String

Required: No

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

NextExecutionTime

The next time the maintenance window will actually run, taking into account any specified times for the maintenance window to become active or inactive.

Type: String

Required: No

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format.

Type: String

Required: No

StartDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active.

Type: String

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowIdentityForTarget

The maintenance window to which the specified target belongs.

Contents

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowLambdaParameters

The parameters for a LAMBDA task type.

For information about specifying and updating task parameters, see RegisterTaskWithMaintenanceWindow and UpdateMaintenanceWindowTask.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters. `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters. For Lambda tasks, Systems Manager ignores any values specified for TaskParameters and LoggingInfo.

Contents

ClientContext

Pass client-specific information to the AWS Lambda function that you are invoking. You can then process the client information in your Lambda function as you choose through the context variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Required: No

Payload

JSON to provide to your Lambda function as input.

Type: Base64-encoded binary data object

Length Constraints: Maximum length of 4096.

Required: No

Qualifier

(Optional) Specify an Lambda function version or alias name. If you specify a function version, the operation uses the qualified function Amazon Resource Name (ARN) to invoke a specific Lambda function. If you specify an alias name, the operation uses the alias ARN to invoke the Lambda function version to which the alias points.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowRunCommandParameters

The parameters for a `RUN_COMMAND` task type.

For information about specifying and updating task parameters, see RegisterTaskWithMaintenanceWindow and UpdateMaintenanceWindowTask.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> For `RUN_COMMAND` tasks, Systems Manager uses specified values for `TaskParameters` and `LoggingInfo` only if no values are specified for `TaskInvocationParameters`.

Contents

CloudWatchOutputConfig

Configuration options for sending command output to Amazon CloudWatch Logs.

Type: CloudWatchOutputConfig object

Required: No

Comment

Information about the commands to run.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DocumentHash

The SHA-256 or SHA-1 hash created by the system when the document was created. SHA-1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DocumentHashType

SHA-256 or SHA-1. SHA-1 hashes have been deprecated.

Type: String

Valid Values: `Sha256 | Sha1`

Required: No

DocumentVersion

The AWS Systems Manager document (SSM document) version to use in the request. You can specify `$DEFAULT`, `$LATEST`, or a specific version number. If you run commands by using the AWS CLI, then you must escape the first two options by using a backslash. If you specify a version number, then you don't need to use the backslash. For example:

```
--document-version "\$DEFAULT"
```

```
--document-version "\$LATEST"
```

```
--document-version "3"
```

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

NotificationConfig

Configurations for sending notifications about command status changes on a per-managed node basis.

Type: NotificationConfig object

Required: No

OutputS3BucketName

The name of the Amazon Simple Storage Service (Amazon S3) bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

Parameters

The parameters for the `RUN_COMMAND` task execution.

Type: String to array of strings map

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Required: No

TimeoutSeconds

If this time is reached and the command hasn't already started running, it doesn't run.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowStepFunctionsParameters

The parameters for a STEP_FUNCTIONS task.

For information about specifying and updating task parameters, see RegisterTaskWithMaintenanceWindow and UpdateMaintenanceWindowTask.

> **Note**
>
> LoggingInfo has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the OutputS3BucketName and OutputS3KeyPrefix options in the TaskInvocationParameters structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> TaskParameters has been deprecated. To specify parameters to pass to a task when it runs, instead use the Parameters option in the TaskInvocationParameters structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.
> For Step Functions tasks, Systems Manager ignores any values specified for TaskParameters and LoggingInfo.

Contents

Input

The inputs for the STEP_FUNCTIONS task.

Type: String

Length Constraints: Maximum length of 4096.

Required: No

Name

The name of the STEP_FUNCTIONS task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowTarget

The target registered with the maintenance window.

Contents

Description

A description for the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

The name for the maintenance window target.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

OwnerInformation

A user-provided value that will be included in any Amazon CloudWatch Events events that are raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

ResourceType

The type of target that is being registered with the maintenance window.

Type: String

Valid Values: `INSTANCE | RESOURCE_GROUP`

Required: No

Targets

The targets, either managed nodes or tags.

Specify managed nodes using the following format:

`Key=instanceids,Values=<instanceid1>,<instanceid2>`

Tags are specified using the following format:

`Key=<tag name>,Values=<tag value>`.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

WindowId

The ID of the maintenance window to register the target with.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

WindowTargetId

The ID of the target.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowTask

Information about a task defined for a maintenance window.

Contents

AlarmConfiguration

The details for the CloudWatch alarm applied to your maintenance window task.

Type: AlarmConfiguration object

Required: No

CutoffBehavior

The specification for whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

Type: String

Valid Values: `CONTINUE_TASK | CANCEL_TASK`

Required: No

Description

A description of the task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

LoggingInfo

Information about an S3 bucket to write task-level logs to.

> **Note**
>
> `LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For

information about how AWS Systems Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: LoggingInfo object

Required: No

MaxConcurrency

The maximum number of targets this task can be run for, in parallel.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The maximum number of errors allowed before this task stops being scheduled.

> **Note**
>
> Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a targetless task You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Name

The task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

Priority

The priority of the task in the maintenance window. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses a service-linked role in your account. If no appropriate service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

However, for an improved security posture, we strongly recommend creating a custom policy and custom service role for running your maintenance window tasks. The policy can be crafted to provide only the permissions needed for your particular maintenance window tasks. For more information, see Setting up Maintenance Windows in the in the *AWS Systems Manager User Guide*.

Type: String

Required: No

Targets

The targets (either managed nodes or tags). Managed nodes are specified using `Key=instanceids,Values=<instanceid1>,<instanceid2>`. Tags are specified using `Key=<tag name>,Values=<tag value>`.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TaskArn

The resource that the task uses during execution. For `RUN_COMMAND` and `AUTOMATION` task types, `TaskArn` is the AWS Systems Manager (SSM document) name or ARN. For `LAMBDA` tasks, it's the function name or ARN. For `STEP_FUNCTIONS` tasks, it's the state machine ARN.

> **Note**
>
> Maintenance Window does not validate the TaskArn when you register a task. A successful registration does not guarantee that the TaskArn is valid.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

TaskParameters

The parameters that should be passed to the task when it is run.

> **Note**
>
> `TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems

Manager handles these options for the supported maintenance window task types, see MaintenanceWindowTaskInvocationParameters.

Type: String to MaintenanceWindowTaskParameterValueExpression object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Type

The type of task.

Type: String

Valid Values: `RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA`

Required: No

WindowId

The ID of the maintenance window where the task is registered.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

WindowTaskId

The task ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowTaskInvocationParameters

The parameters for task execution.

Contents

Automation

The parameters for an `AUTOMATION` task type.

Type: MaintenanceWindowAutomationParameters object

Required: No

Lambda

The parameters for a `LAMBDA` task type.

Type: MaintenanceWindowLambdaParameters object

Required: No

RunCommand

The parameters for a `RUN_COMMAND` task type.

Type: MaintenanceWindowRunCommandParameters object

Required: No

StepFunctions

The parameters for a `STEP_FUNCTIONS` task type.

Type: MaintenanceWindowStepFunctionsParameters object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

MaintenanceWindowTaskParameterValueExpression

Defines the values for a task parameter.

Contents

Values

This field contains an array of 0 or more strings, each 1 to 255 characters in length.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MetadataValue

Metadata to assign to an Application Manager application.

Contents

Value

Metadata value to assign to an Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Node

Details about an individual managed node.

Contents

CaptureTime

The UTC timestamp for when the managed node data was last captured.

Type: Timestamp

Required: No

Id

The ID of the managed node.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

NodeType

Information about the type of node.

Type: NodeType object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Owner

Information about the ownership of the managed node.

Type: NodeOwnerInfo object

Required: No

Region

The AWS Region that a managed node was created in or assigned to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NodeAggregator

One or more aggregators for viewing counts of nodes using different dimensions.

Contents

AggregatorType

The aggregator type for limiting a node summary. Currently, only `Count` is supported.

Type: String

Valid Values: `Count`

Required: Yes

AttributeName

The name of a node attribute on which to limit the count of nodes.

Type: String

Valid Values: `AgentVersion | PlatformName | PlatformType | PlatformVersion | Region | ResourceType`

Required: Yes

TypeName

The data type name to use for viewing counts of nodes. Currently, only `Instance` is supported.

Type: String

Valid Values: `Instance`

Required: Yes

Aggregators

Information about aggregators used to refine a node summary.

Type: Array of NodeAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NodeFilter

The filters for the operation.

Contents

Key

The name of the filter.

Type: String

Valid Values: `AgentType | AgentVersion | ComputerName | InstanceId | InstanceStatus | IpAddress | ManagedStatus | PlatformName | PlatformType | PlatformVersion | ResourceType | OrganizationalUnitId | OrganizationalUnitPath | Region | AccountId`

Required: Yes

Values

A filter value supported by the specified key. For example, for the key `PlatformType`, supported values include `Linux` and `Windows`.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Type

The type of filter operator.

Type: String

Valid Values: `Equal | NotEqual | BeginWith`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NodeOwnerInfo

Information about ownership of a managed node.

Contents

AccountId

The ID of the AWS account that owns the managed node.

Type: String

Pattern: `[0-9]{12}`

Required: No

OrganizationalUnitId

The ID of the organization unit (OU) that the account is part of.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 68.

Pattern: `^ou-[0-9a-z]{4,32}-[a-z0-9]{8,32}$`

Required: No

OrganizationalUnitPath

The path for the organizational unit (OU) that owns the managed node. The path for the OU is built using the IDs of the organization, root, and all OUs in the path down to and including the OU. For example:

`o-a1b2c3d4e5/r-f6g7h8i9j0example/ou-ghi0-awscccc/ou-jkl0-awsdddd/`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NodeType

Information about a managed node's type.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

Instance

Information about a specific managed node.

Type: InstanceInfo object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NonCompliantSummary

A summary of resources that aren't compliant. The summary is organized according to resource type.

Contents

NonCompliantCount

The total number of compliance items that aren't compliant.

Type: Integer

Required: No

SeveritySummary

A summary of the non-compliance severity by compliance type

Type: SeveritySummary object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

NotificationConfig

Configurations for sending notifications.

Contents

NotificationArn

An Amazon Resource Name (ARN) for an Amazon Simple Notification Service (Amazon SNS) topic. Run Command pushes notifications about command status changes to this topic.

Type: String

Required: No

NotificationEvents

The different events for which you can receive notifications. To learn more about these events, see Monitoring Systems Manager status changes using Amazon SNS notifications in the *AWS Systems Manager User Guide*.

Type: Array of strings

Valid Values: `All | InProgress | Success | TimedOut | Cancelled | Failed`

Required: No

NotificationType

The type of notification.

- `Command`: Receive notification when the status of a command changes.
- `Invocation`: For commands sent to multiple managed nodes, receive notification on a per-node basis when the status of a command changes.

Type: String

Valid Values: `Command | Invocation`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsAggregator

One or more aggregators for viewing counts of OpsData using different dimensions such as `Source`, `CreatedTime`, or `Source and CreatedTime`, to name a few.

Contents

Aggregators

A nested aggregator for viewing counts of OpsData.

Type: Array of OpsAggregator objects

Array Members: Minimum number of 1 item. Maximum number of 12 items.

Required: No

AggregatorType

Either a `Range` or `Count` aggregator for limiting an OpsData summary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^(range|count|sum)`

Required: No

AttributeName

The name of an OpsData attribute on which to limit the count of OpsData.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Filters

The aggregator filters.

Type: Array of OpsFilter objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

TypeName

The data type name to use for viewing counts of OpsData.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: No

Values

The aggregator value.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 32.

Value Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsEntity

The result of the query.

Contents

Data

The data returned by the query.

Type: String to OpsEntityItem object map

Required: No

Id

The query ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsEntityItem

The OpsData summary.

Contents

CaptureTime

The time the OpsData was captured.

Type: String

Pattern: `^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|[0-1][0-9])(:[0-5][0-9])(:[0-5][0-9])(Z)$`

Required: No

Content

The details of an OpsData summary.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsFilter

A filter for viewing OpsData summaries.

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Values

The filter value.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Type

The type of filter.

Type: String

Valid Values: `Equal | NotEqual | BeginWith | LessThan | GreaterThan | Exists`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItem

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational work items (OpsItems) impacting the performance and health of their AWS resources. OpsCenter is integrated with Amazon EventBridge and Amazon CloudWatch. This means you can configure these services to automatically create an OpsItem in OpsCenter when a CloudWatch alarm enters the ALARM state or when EventBridge processes an event from any AWS service that publishes events. Configuring Amazon CloudWatch alarms and EventBridge events to automatically create OpsItems allows you to quickly diagnose and remediate issues with AWS resources from a single console.

To help you diagnose issues, each OpsItem includes contextually relevant information such as the name and ID of the AWS resource that generated the OpsItem, alarm or event details, alarm history, and an alarm timeline graph. For the AWS resource, OpsCenter aggregates information from AWS Config, AWS CloudTrail logs, and EventBridge, so you don't have to navigate across multiple console pages during your investigation. For more information, see AWS Systems Manager OpsCenter in the *AWS Systems Manager User Guide*.

Contents

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Category

An OpsItem category. Category options include: Availability, Cost, Performance, Recovery, Security.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

CreatedBy

The ARN of the AWS account that created the OpsItem.

Type: String

Required: No

CreatedTime

The date and time the OpsItem was created.

Type: Timestamp

Required: No

Description

The OpsItem description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\s\S]*\S[\s\S]*`

Required: No

LastModifiedBy

The ARN of the AWS account that last updated the OpsItem.

Type: String

Required: No

LastModifiedTime

The date and time the OpsItem was last updated.

Type: Timestamp

Required: No

Notifications

The Amazon Resource Name (ARN) of an Amazon Simple Notification Service (Amazon SNS) topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of OpsItemNotification objects

Required: No

OperationalData

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

> **Important**
>
> Operational data keys *can't* begin with the following: `amazon`, `aws`, `amzn`, `ssm`, `/amazon`, `/aws`, `/amzn`, `/ssm`.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the DescribeOpsItems API operation) can view and search on the specified data. Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the GetOpsItem API operation).

Use the `/aws/resources` key in OperationalData to specify a related resource in the request. Use the `/aws/automations` key in OperationalData to associate an Automation runbook with the OpsItem. To view AWS CLI example commands that use these keys, see Creating OpsItems manually in the *AWS Systems Manager User Guide*.

Type: String to OpsItemDataValue object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\s*$).+`

Required: No

OpsItemArn

The OpsItem Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[0-9]{12}:opsitem.*`

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: No

OpsItemType

The type of OpsItem. Systems Manager supports the following types of OpsItems:

- `/aws/issue`

  This type of OpsItem is used for default OpsItems created by OpsCenter.

- `/aws/changerequest`

  This type of OpsItem is used by Change Manager for reviewing and approving or rejecting change requests.

- `/aws/insight`

  This type of OpsItem is used by OpsCenter for aggregating and reporting on duplicate OpsItems.

Type: String

Required: No

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

RelatedOpsItems

One or more OpsItems that share something in common with the current OpsItem. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of RelatedOpsItem objects

Required: No

Severity

The severity of the OpsItem. Severity options range from 1 to 4.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Source

The origin of the OpsItem, such as Amazon EC2 or Systems Manager. The impacted resource is a subset of source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\s*$).+`

Required: No

Status

The OpsItem status. For more information, see Editing OpsItem details in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Revoked | Rejected | Closed`

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: No

Version

The version of this OpsItem. Each time the OpsItem is edited the version number increments by one.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemDataValue

An object that defines the value of the key and its type in the OperationalData map.

Contents

Type

The type of key-value pair. Valid types include `SearchableString` and `String`.

Type: String

Valid Values: `SearchableString | String`

Required: No

Value

The value of the OperationalData key.

Type: String

Pattern: `[\s\S]*\S[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemEventFilter

Describes a filter for a specific list of OpsItem events. You can filter event information by using tags. You specify tags by using a key-value pair mapping.

Contents

Key

The name of the filter key. Currently, the only supported value is `OpsItemId`.

Type: String

Valid Values: `OpsItemId`

Required: Yes

Operator

The operator used by the filter call. Currently, the only supported value is `Equal`.

Type: String

Valid Values: `Equal`

Required: Yes

Values

The values for the filter, consisting of one or more OpsItem IDs.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 15.

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemEventSummary

Summary information about an OpsItem event or that associated an OpsItem with a related item.

Contents

CreatedBy

Information about the user or resource that created the OpsItem event.

Type: OpsItemIdentity object

Required: No

CreatedTime

The date and time the OpsItem event was created.

Type: Timestamp

Required: No

Detail

Specific information about the OpsItem event.

Type: String

Required: No

DetailType

The type of information provided as a detail.

Type: String

Required: No

EventId

The ID of the OpsItem event.

Type: String

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Required: No

Source

The source of the OpsItem event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemFilter

Describes an OpsItem filter.

Contents

Key

The name of the filter.

Type: String

Valid Values: `Status | CreatedBy | Source | Priority | Title | OpsItemId | CreatedTime | LastModifiedTime | ActualStartTime | ActualEndTime | PlannedStartTime | PlannedEndTime | OperationalData | OperationalDataKey | OperationalDataValue | ResourceId | AutomationId | Category | Severity | OpsItemType | AccessRequestByRequesterArn | AccessRequestByRequesterId | AccessRequestByApproverArn | AccessRequestByApproverId | AccessRequestBySourceAccountId | AccessRequestBySourceOpsItemId | AccessRequestBySourceRegion | AccessRequestByIsReplica | AccessRequestByTargetResourceId | ChangeRequestByRequesterArn | ChangeRequestByRequesterName | ChangeRequestByApproverArn | ChangeRequestByApproverName | ChangeRequestByTemplate | ChangeRequestByTargetsResourceGroup | InsightByType | AccountId`

Required: Yes

Operator

The operator used by the filter call.

Type: String

Valid Values: `Equal | Contains | GreaterThan | LessThan`

Required: Yes

Values

The filter value.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemIdentity

Information about the user or resource that created an OpsItem event.

Contents

Arn

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemNotification

A notification about the OpsItem.

Contents

Arn

The Amazon Resource Name (ARN) of an Amazon Simple Notification Service (Amazon SNS) topic where notifications are sent when this OpsItem is edited or changed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemRelatedItemsFilter

Describes a filter for a specific list of related-item resources.

Contents

Key

The name of the filter key. Supported values include `ResourceUri`, `ResourceType`, or `AssociationId`.

Type: String

Valid Values: `ResourceType | AssociationId | ResourceUri`

Required: Yes

Operator

The operator used by the filter call. The only supported operator is `EQUAL`.

Type: String

Valid Values: `Equal`

Required: Yes

Values

The values for the filter.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

OpsItemRelatedItemSummary

Summary information about related-item resources for an OpsItem.

Contents

AssociationId

The association ID.

Type: String

Required: No

AssociationType

The association type.

Type: String

Required: No

CreatedBy

Information about the user or resource that created an OpsItem event.

Type: OpsItemIdentity object

Required: No

CreatedTime

The time the related-item association was created.

Type: Timestamp

Required: No

LastModifiedBy

Information about the user or resource that created an OpsItem event.

Type: OpsItemIdentity object

Required: No

LastModifiedTime

The time the related-item association was last updated.

Type: Timestamp

Required: No

OpsItemId

The OpsItem ID.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: No

ResourceType

The resource type.

Type: String

Required: No

ResourceUri

The Amazon Resource Name (ARN) of the related-item resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsItemSummary

A count of OpsItems.

Contents

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Category

A list of OpsItems by category.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

CreatedBy

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem.

Type: String

Required: No

CreatedTime

The date and time the OpsItem was created.

Type: Timestamp

Required: No

LastModifiedBy

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem.

Type: String

Required: No

LastModifiedTime

The date and time the OpsItem was last updated.

Type: Timestamp

Required: No

OperationalData

Operational data is custom data that provides useful reference details about the OpsItem.

Type: String to OpsItemDataValue object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\s*$).+`

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: No

OpsItemType

The type of OpsItem. Systems Manager supports the following types of OpsItems:

- `/aws/issue`

  This type of OpsItem is used for default OpsItems created by OpsCenter.

- `/aws/changerequest`

  This type of OpsItem is used by Change Manager for reviewing and approving or rejecting change requests.

- `/aws/insight`

  This type of OpsItem is used by OpsCenter for aggregating and reporting on duplicate OpsItems.

Type: String

Required: No

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

Severity

A list of OpsItems by severity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\s*$).+`

Required: No

Source

The impacted AWS resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\s*$).+`

Required: No

Status

The OpsItem status.

Type: String

Valid Values: `Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Revoked | Rejected | Closed`

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsMetadata

Operational metadata for an application in Application Manager.

Contents

CreationDate

The date the OpsMetadata objects was created.

Type: Timestamp

Required: No

LastModifiedDate

The date the OpsMetadata object was last updated.

Type: Timestamp

Required: No

LastModifiedUser

The user name who last updated the OpsMetadata object.

Type: String

Required: No

OpsMetadataArn

The Amazon Resource Name (ARN) of the OpsMetadata Object or blob.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)`

Required: No

ResourceId

The ID of the Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\s*$).+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsMetadataFilter

A filter to limit the number of OpsMetadata objects displayed.

Contents

Key

A filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\s*$).+`

Required: Yes

Values

A filter value.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OpsResultAttribute

The OpsItem data type to return.

Contents

TypeName

Name of the data type. Valid value: `AWS:OpsItem`, `AWS:EC2InstanceInformation`, `AWS:OpsItemTrendline`, or `AWS:ComplianceSummary`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OutputSource

Information about the source where the association execution details are stored.

Contents

OutputSourceId

The ID of the output source, for example the URL of an S3 bucket.

Type: String

Length Constraints: Fixed length of 36.

Required: No

OutputSourceType

The type of source where the association execution details are stored, for example, Amazon S3.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Parameter

An AWS Systems Manager parameter in Parameter Store.

Contents

ARN

The Amazon Resource Name (ARN) of the parameter.

Type: String

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

LastModifiedDate

Date the parameter was last changed or updated and the parameter version was created.

Type: Timestamp

Required: No

Name

The name of the parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Selector

Either the version number or the label used to retrieve the parameter value. Specify selectors by using one of the following formats:

parameter_name:version

parameter_name:label

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

SourceResult

Applies to parameters that reference information in other AWS services. `SourceResult` is the raw result or response from the source.

Type: String

Required: No

Type

The type of parameter. Valid values include the following: `String`, `StringList`, and `SecureString`.

> **Note**
>
> If type is `StringList`, the system returns a comma-separated string with no spaces between commas in the `Value` field.

Type: String

Valid Values: `String | StringList | SecureString`

Required: No

Value

The parameter value.

> **Note**
>
> If type is `StringList`, the system returns a comma-separated string with no spaces between commas in the `Value` field.

Type: String

Required: No

Version

The parameter version.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParameterHistory

Information about parameter usage.

Contents

AllowedPattern

Parameter names can include the following letters and symbols.

a-zA-Z0-9_.-

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description

Information about the parameter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId

The alias of the AWS Key Management Service (AWS KMS) key used to encrypt the parameter. Applies to `SecureString` parameters only

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([a-zA-Z0-9:/_-]+)$`

Required: No

Labels

Labels assigned to the parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

LastModifiedDate

Date the parameter was last changed or updated.

Type: Timestamp

Required: No

LastModifiedUser

Amazon Resource Name (ARN) of the Amazon Web Services user who last changed the parameter.

Type: String

Required: No

Name

The name of the parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Policies

Information about the policies assigned to a parameter.

Assigning parameter policies in the *AWS Systems Manager User Guide*.

Type: Array of ParameterInlinePolicy objects

Required: No

Tier

The parameter tier.

Type: String

Valid Values: `Standard | Advanced | Intelligent-Tiering`

Required: No

Type

The type of parameter used.

Type: String

Valid Values: `String | StringList | SecureString`

Required: No

Value

The parameter value.

Type: String

Required: No

Version

The parameter version.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParameterInlinePolicy

One or more policies assigned to a parameter.

Contents

PolicyStatus

The status of the policy. Policies report the following statuses: Pending (the policy hasn't been enforced or applied yet), Finished (the policy was applied), Failed (the policy wasn't applied), or InProgress (the policy is being applied now).

Type: String

Required: No

PolicyText

The JSON text of the policy.

Type: String

Required: No

PolicyType

The type of policy. Parameter Store, a tool in AWS Systems Manager, supports the following policy types: Expiration, ExpirationNotification, and NoChangeNotification.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParameterMetadata

Metadata includes information like the Amazon Resource Name (ARN) of the last user to update the parameter and the date and time the parameter was last used.

Contents

AllowedPattern

A parameter name can include only the following letters and symbols.

a-zA-Z0-9_.-

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ARN

The Amazon Resource Name (ARN) of the parameter.

Type: String

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description

Description of the parameter actions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId

The alias of the AWS Key Management Service (AWS KMS) key used to encrypt the parameter. Applies to `SecureString` parameters only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([a-zA-Z0-9:/_-]+)$`

Required: No

LastModifiedDate

Date the parameter was last changed or updated.

Type: Timestamp

Required: No

LastModifiedUser

Amazon Resource Name (ARN) of the Amazon Web Services user who last changed the parameter.

Type: String

Required: No

Name

The parameter name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Policies

A list of policies associated with a parameter.

Type: Array of ParameterInlinePolicy objects

Required: No

Tier

The parameter tier.

Type: String

Valid Values: `Standard | Advanced | Intelligent-Tiering`

Required: No

Type

The type of parameter. Valid parameter types include the following: `String`, `StringList`, and `SecureString`.

Type: String

Valid Values: `String | StringList | SecureString`

Required: No

Version

The parameter version.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParametersFilter

This data type is deprecated. Instead, use ParameterStringFilter.

Contents

Key

The name of the filter.

Type: String

Valid Values: `Name | Type | KeyId`

Required: Yes

Values

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParameterStringFilter

One or more filters. Use a filter to return a more specific list of results.

Contents

Key

The name of the filter.

The `ParameterStringFilter` object is used by the DescribeParameters and GetParametersByPath API operations. However, not all of the pattern values listed for `Key` can be used with both operations.

For `DescribeParameters`, all of the listed patterns are valid except `Label`.

For `GetParametersByPath`, the following patterns listed for `Key` aren't valid: `tag`, `DataType`, `Name`, `Path`, and `Tier`.

For examples of AWS CLI commands demonstrating valid parameter filter constructions, see Searching for Systems Manager parameters in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 132.

Pattern: `tag:.+|Name|Type|KeyId|Path|Label|Tier|DataType`

Required: Yes

Option

For all filters used with DescribeParameters, valid options include `Equals` and `BeginsWith`. The `Name` filter additionally supports the `Contains` option. (Exception: For filters using the key `Path`, valid options include `Recursive` and `OneLevel`.)

For filters used with GetParametersByPath, valid options include `Equals` and `BeginsWith`. (Exception: For filters using `Label` as the Key name, the only valid option is `Equals`.)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Required: No

Values

The value you want to search for.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParentStepDetails

A detailed status of the parent step.

Contents

Action

The name of the automation action.

Type: String

Pattern: `^aws:[a-zA-Z]{3,25}$`

Required: No

Iteration

The current repetition of the loop represented by an integer.

Type: Integer

Required: No

IteratorValue

The current value of the specified iterator in the loop.

Type: String

Required: No

StepExecutionId

The unique ID of a step execution.

Type: String

Required: No

StepName

The name of the step.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Patch

Represents metadata about a patch.

Contents

AdvisoryIds

The Advisory ID of the patch. For example, `RHSA-2020:3779`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Arch

The architecture of the patch. For example, in `example-pkg-0.710.10-2.7.abcd.x86_64`, the architecture is indicated by `x86_64`. Applies to Linux-based managed nodes only.

Type: String

Required: No

BugzillaIds

The Bugzilla ID of the patch. For example, `1600646`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Classification

The classification of the patch. For example, `SecurityUpdates`, `Updates`, or `CriticalUpdates`.

Type: String

Required: No

ContentUrl

The URL where more information can be obtained about the patch.

Type: String

Required: No

CVEIds

The Common Vulnerabilities and Exposures (CVE) ID of the patch. For example, `CVE-2011-3192`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Description

The description of the patch.

Type: String

Required: No

Epoch

The epoch of the patch. For example in `pkg-example-EE-20180914-2.2.amzn1.noarch`, the epoch value is `20180914-2`. Applies to Linux-based managed nodes only.

Type: Integer

Required: No

Id

The ID of the patch. Applies to Windows patches only.

> **Note**
>
> This ID isn't the same as the Microsoft Knowledge Base ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

KbNumber

The Microsoft Knowledge Base ID of the patch. Applies to Windows patches only.

Type: String

Required: No

Language

The language of the patch if it's language-specific.

Type: String

Required: No

MsrcNumber

The ID of the Microsoft Security Response Center (MSRC) bulletin the patch is related to. For example, `MS14-045`. Applies to Windows patches only.

Type: String

Required: No

MsrcSeverity

The severity of the patch, such as `Critical`, `Important`, or `Moderate`. Applies to Windows patches only.

Type: String

Required: No

Name

The name of the patch. Applies to Linux-based managed nodes only.

Type: String

Required: No

Product

The specific product the patch is applicable for. For example, `WindowsServer2016` or `AmazonLinux2018.03`.

Type: String

Required: No

ProductFamily

The product family the patch is applicable for. For example, `Windows` or `Amazon Linux 2`.

Type: String

Required: No

Release

The particular release of a patch. For example, in `pkg-example-EE-20180914-2.2.amzn1.noarch`, the release is `2.amaz1`. Applies to Linux-based managed nodes only.

Type: String

Required: No

ReleaseDate

The date the patch was released.

Type: Timestamp

Required: No

Repository

The source patch repository for the operating system and version, such as `trusty-security` for Ubuntu Server 14.04 LTE and `focal-security` for Ubuntu Server 20.04 LTE. Applies to Linux-based managed nodes only.

Type: String

Required: No

Severity

The severity level of the patch. For example, `CRITICAL` or `MODERATE`.

Type: String

Required: No

Title

The title of the patch.

Type: String

Required: No

Vendor

The name of the vendor providing the patch.

Type: String

Required: No

Version

The version number of the patch. For example, in `example-pkg-1.710.10-2.7.abcd.x86_64`, the version number is indicated by `-1`. Applies to Linux-based managed nodes only.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchBaselineIdentity

Defines the basic information about a patch baseline.

Contents

BaselineDescription

The description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

BaselineId

The ID of the patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-:/]{20,128}$`

Required: No

BaselineName

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

DefaultBaseline

Indicates whether this is the default baseline. AWS Systems Manager supports creating multiple default patch baselines. For example, you can create a default patch baseline for each operating system.

Type: Boolean

Required: No

OperatingSystem

Defines the operating system the patch baseline applies to. The default value is `WINDOWS`.

Type: String

Valid Values: `WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | AMAZON_LINUX_2022 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX | ALMA_LINUX | AMAZON_LINUX_2023`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchComplianceData

Information about the state of a patch on a particular managed node as it relates to the patch baseline used to patch the node.

Contents

Classification

The classification of the patch, such as `SecurityUpdates`, `Updates`, and `CriticalUpdates`.

Type: String

Required: Yes

InstalledTime

The date/time the patch was installed on the managed node. Not all operating systems provide this level of information.

Type: Timestamp

Required: Yes

KBId

The operating system-specific ID of the patch.

Type: String

Required: Yes

Severity

The severity of the patch such as `Critical`, `Important`, and `Moderate`.

Type: String

Required: Yes

State

The state of the patch on the managed node, such as INSTALLED or FAILED.

For descriptions of each patch state, see About patch compliance in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `INSTALLED | INSTALLED_OTHER | INSTALLED_PENDING_REBOOT | INSTALLED_REJECTED | MISSING | NOT_APPLICABLE | FAILED | AVAILABLE_SECURITY_UPDATE`

Required: Yes

Title

The title of the patch.

Type: String

Required: Yes

CVEIds

The IDs of one or more Common Vulnerabilities and Exposure (CVE) issues that are resolved by the patch.

> **Note**
>
> Currently, CVE ID values are reported only for patches with a status of `Missing` or `Failed`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchFilter

Defines which patches should be included in a patch baseline.

A patch filter consists of a key and a set of values. The filter key is a patch property. For example, the available filter keys for `WINDOWS` are `PATCH_SET`, `PRODUCT`, `PRODUCT_FAMILY`, `CLASSIFICATION`, and `MSRC_SEVERITY`.

The filter values define a matching criterion for the patch property indicated by the key. For example, if the filter key is `PRODUCT` and the filter values are `["Office 2013", "Office 2016"]`, then the filter accepts all patches where product name is either "Office 2013" or "Office 2016". The filter values can be exact values for the patch property given as a key, or a wildcard (*), which matches all values.

You can view lists of valid values for the patch properties by running the `DescribePatchProperties` command. For information about which patch properties can be used with each major operating system, see DescribePatchProperties.

Contents

Key

The key for the filter.

Run the DescribePatchProperties command to view lists of valid keys for each operating system type.

Type: String

Valid Values: `ARCH | ADVISORY_ID | BUGZILLA_ID | PATCH_SET | PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | CVE_ID | EPOCH | MSRC_SEVERITY | NAME | PATCH_ID | SECTION | PRIORITY | REPOSITORY | RELEASE | SEVERITY | SECURITY | VERSION`

Required: Yes

Values

The value for the filter key.

Run the DescribePatchProperties command to view lists of valid values for each key based on operating system type.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchFilterGroup

A set of patch filters, typically used for approval rules.

Contents

PatchFilters

The set of patch filters that make up the group.

Type: Array of PatchFilter objects

Array Members: Minimum number of 0 items. Maximum number of 4 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchGroupPatchBaselineMapping

The mapping between a patch group and the patch baseline the patch group is registered with.

Contents

BaselineIdentity

The patch baseline the patch group is registered with.

Type: PatchBaselineIdentity object

Required: No

PatchGroup

The name of the patch group registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchOrchestratorFilter

Defines a filter used in Patch Manager APIs. Supported filter keys depend on the API operation that includes the filter. Patch Manager API operations that use `PatchOrchestratorFilter` include the following:

- DescribeAvailablePatches
- DescribeInstancePatches
- DescribePatchBaselines
- DescribePatchGroups

Contents

Key

The key for the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The value for the filter.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchRule

Defines an approval rule for a patch baseline.

Contents

PatchFilterGroup

The patch filter group that defines the criteria for the rule.

Type: PatchFilterGroup object

Required: Yes

ApproveAfterDays

The number of days after the release date of each patch matched by the rule that the patch is marked as approved in the patch baseline. For example, a value of 7 means that patches are approved seven days after they are released.

Patch Manager evaluates patch release dates using Coordinated Universal Time (UTC). If a patch is released at `2025-11-09T18:00:00Z` and `ApproveAfterDays` is set to 7, the patch will be approved after `2025-11-16T18:00:00Z`.

This parameter is marked as `Required: No`, but your request must include a value for either `ApproveAfterDays` or `ApproveUntilDate`.

Not supported for Debian Server or Ubuntu Server.

> **Important**
>
> Use caution when setting this value for Windows Server patch baselines. Because patch updates that are replaced by later updates are removed, setting too broad a value for this parameter can result in crucial patches not being installed. For more information, see the **Windows Server** tab in the topic How security patches are selected in the *AWS Systems Manager User Guide*.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 360.

Required: No

ApproveUntilDate

The cutoff date for auto approval of released patches. Any patches released on or before this date are installed automatically.

Enter dates in the format `YYYY-MM-DD`. For example, `2025-11-16`.

Patch Manager evaluates patch release dates using Coordinated Universal Time (UTC). If you enter the date `2025-11-16`, patches released between `2025-11-16T00:00:00Z` and `2025-11-16T23:59:59Z` will be included in the approval.

This parameter is marked as `Required: No`, but your request must include a value for either `ApproveUntilDate` or `ApproveAfterDays`.

Not supported for Debian Server or Ubuntu Server.

> **Important**
>
> Use caution when setting this value for Windows Server patch baselines. Because patch updates that are replaced by later updates are removed, setting too broad a value for this parameter can result in crucial patches not being installed. For more information, see the **Windows Server** tab in the topic How security patches are selected in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Required: No

ComplianceLevel

A compliance severity level for all approved patches in a patch baseline.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

EnableNonSecurity

For managed nodes identified by the approval rule filters, enables a patch baseline to apply non-security updates available in the specified repository. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchRuleGroup

A set of rules defining the approval rules for a patch baseline.

Contents

PatchRules

The rules that make up the rule group.

Type: Array of PatchRule objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchSource

Information about the patches to use to update the managed nodes, including target operating systems and source repository. Applies to Linux managed nodes only.

Contents

Configuration

The value of the repo configuration.

Example for yum repositories

```
[main]

name=MyCustomRepository

baseurl=https://my-custom-repository

enabled=1
```

For information about other options available for your yum repository configuration, see dnf.conf(5) on the *man7.org* website.

Examples for Ubuntu Server and Debian Server

```
deb http://security.ubuntu.com/ubuntu jammy main

deb https://site.example.com/debian distribution component1 component2 component3
```

Repo information for Ubuntu Server repositories must be specifed in a single line. For more examples and information, see jammy (5) sources.list.5.gz on the *Ubuntu Server Manuals* website and sources.list format on the *Debian Wiki*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

Name

The name specified to identify the patch source.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,50}$`

Required: Yes

Products

The specific operating system versions a patch repository applies to, such as "Ubuntu16.04", "AmazonLinux2016.09", "RedhatEnterpriseLinux7.2" or "Suse12.7". For lists of supported product values, see PatchFilter.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PatchStatus

Information about the approval status of a patch.

Contents

ApprovalDate

The date the patch was approved (or will be approved if the status is `PENDING_APPROVAL`).

Type: Timestamp

Required: No

ComplianceLevel

The compliance severity level for a patch.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

DeploymentStatus

The approval status of a patch.

Type: String

Valid Values: `APPROVED | PENDING_APPROVAL | EXPLICIT_APPROVED | EXPLICIT_REJECTED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

ProgressCounters

An aggregate of step execution statuses displayed in the AWS Systems Manager console for a multi-Region and multi-account Automation execution.

Contents

CancelledSteps

The total number of steps that the system cancelled in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

FailedSteps

The total number of steps that failed to run in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

SuccessSteps

The total number of steps that successfully completed in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

TimedOutSteps

The total number of steps that timed out in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

TotalSteps

The total number of steps run in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RegistrationMetadataItem

Reserved for internal use.

Contents

Key

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\s*$).+`

Required: Yes

Value

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?!\s*$).+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RelatedOpsItem

An OpsItems that shares something in common with the current OpsItem. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Contents

OpsItemId

The ID of an OpsItem related to the current OpsItem.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResolvedTargets

Information about targets that resolved during the Automation execution.

Contents

ParameterValues

A list of parameter values sent to targets that resolved during the Automation execution.

Type: Array of strings

Required: No

Truncated

A boolean value indicating whether the resolved target list is truncated.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceComplianceSummaryItem

Compliance summary information for a specific resource.

Contents

ComplianceType

The compliance type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[A-Za-z0-9_\-]\w+|Custom:[a-zA-Z0-9_\-]\w+`

Required: No

CompliantSummary

A list of items that are compliant for the resource.

Type: CompliantSummary object

Required: No

ExecutionSummary

Information about the execution.

Type: ComplianceExecutionSummary object

Required: No

NonCompliantSummary

A list of items that aren't compliant for the resource.

Type: NonCompliantSummary object

Required: No

OverallSeverity

The highest severity item found for the resource. The resource is compliant for this item.

Type: String

Valid Values: `CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED`

Required: No

ResourceId

The resource ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Status

The compliance status for the resource.

Type: String

Valid Values: `COMPLIANT | NON_COMPLIANT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncAwsOrganizationsSource

Information about the `AwsOrganizationsSource` resource data sync source. A sync source of this type can synchronize data from AWS Organizations or, if an AWS organization isn't present, from multiple AWS Regions.

Contents

OrganizationSourceType

If an AWS organization is present, this is either `OrganizationalUnits` or `EntireOrganization`. For `OrganizationalUnits`, the data is aggregated from a set of organization units. For `EntireOrganization`, the data is aggregated from the entire AWS organization.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

OrganizationalUnits

The AWS Organizations organization units included in the sync.

Type: Array of ResourceDataSyncOrganizationalUnit objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncDestinationDataSharing

Synchronize AWS Systems Manager Inventory data from multiple AWS accounts defined in AWS Organizations to a centralized Amazon S3 bucket. Data is synchronized to individual key prefixes in the central bucket. Each key prefix represents a different AWS account ID.

Contents

DestinationDataSharingType

The sharing data type. Only `Organization` is supported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncItem

Information about a resource data sync configuration, including its current status and last successful sync.

Contents

LastStatus

The status reported by the last sync.

Type: String

Valid Values: `Successful | Failed | InProgress`

Required: No

LastSuccessfulSyncTime

The last time the sync operations returned a status of `SUCCESSFUL` (UTC).

Type: Timestamp

Required: No

LastSyncStatusMessage

The status message details reported by the last sync.

Type: String

Required: No

LastSyncTime

The last time the configuration attempted to sync (UTC).

Type: Timestamp

Required: No

S3Destination

Configuration information for the target S3 bucket.

Type: ResourceDataSyncS3Destination object

Required: No

SyncCreatedTime

The date and time the configuration was created (UTC).

Type: Timestamp

Required: No

SyncLastModifiedTime

The date and time the resource data sync was changed.

Type: Timestamp

Required: No

SyncName

The name of the resource data sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

SyncSource

Information about the source where the data was synchronized.

Type: ResourceDataSyncSourceWithState object

Required: No

SyncType

The type of resource data sync. If `SyncType` is `SyncToDestination`, then the resource data sync synchronizes data to an S3 bucket. If the `SyncType` is `SyncFromSource` then the resource data sync synchronizes data from AWS Organizations or from multiple AWS Regions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncOrganizationalUnit

The AWS Organizations organizational unit data source for the sync.

Contents

OrganizationalUnitId

The AWS Organizations unit ID data source for the sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^ou-[0-9a-z]{4,32}-[a-z0-9]{8,32}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncS3Destination

Information about the target S3 bucket for the resource data sync.

Contents

BucketName

The name of the S3 bucket where the aggregated data is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Region

The AWS Region with the S3 bucket targeted by the resource data sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncFormat

A supported sync format. The following format is currently supported: JsonSerDe

Type: String

Valid Values: `JsonSerDe`

Required: Yes

AWSKMSKeyARN

The ARN of an encryption key for a destination in Amazon S3. Must belong to the same Region as the destination S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

DestinationDataSharing

Enables destination data sharing. By default, this field is `null`.

Type: ResourceDataSyncDestinationDataSharing object

Required: No

Prefix

An Amazon S3 prefix for the bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncSource

Information about the source of the data included in the resource data sync.

Contents

SourceRegions

The `SyncSource` AWS Regions included in the resource data sync.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SourceType

The type of data source for the resource data sync. `SourceType` is either `AwsOrganizations` (if an organization is present in AWS Organizations) or `SingleAccountMultiRegions`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

AwsOrganizationsSource

Information about the `AwsOrganizationsSource` resource data sync source. A sync source of this type can synchronize data from AWS Organizations.

Type: ResourceDataSyncAwsOrganizationsSource object

Required: No

EnableAllOpsDataSources

When you create a resource data sync, if you choose one of the AWS Organizations options, then Systems Manager automatically enables all OpsData sources in the selected AWS Regions for all AWS accounts in your organization (or in the selected organization units). For more information, see Setting up Systems Manager Explorer to display data from multiple accounts and Regions in the *AWS Systems Manager User Guide*.

Type: Boolean

Required: No

IncludeFutureRegions

Whether to automatically synchronize and aggregate data from new AWS Regions when those Regions come online.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResourceDataSyncSourceWithState

The data type name for including resource data sync state. There are four sync states:

`OrganizationNotExists` (Your organization doesn't exist)

`NoPermissions` (The system can't locate the service-linked role. This role is automatically created when a user creates a resource data sync in AWS Systems Manager Explorer.)

`InvalidOrganizationalUnit` (You specified or selected an invalid unit in the resource data sync configuration.)

`TrustedAccessDisabled` (You disabled Systems Manager access in the organization in AWS Organizations.)

Contents

AwsOrganizationsSource

The field name in `SyncSource` for the `ResourceDataSyncAwsOrganizationsSource` type.

Type: ResourceDataSyncAwsOrganizationsSource object

Required: No

EnableAllOpsDataSources

When you create a resource data sync, if you choose one of the AWS Organizations options, then Systems Manager automatically enables all OpsData sources in the selected AWS Regions for all AWS accounts in your organization (or in the selected organization units). For more information, see Setting up Systems Manager Explorer to display data from multiple accounts and Regions in the *AWS Systems Manager User Guide*.

Type: Boolean

Required: No

IncludeFutureRegions

Whether to automatically synchronize and aggregate data from new AWS Regions when those Regions come online.

Type: Boolean

Required: No

SourceRegions

The `SyncSource` AWS Regions included in the resource data sync.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

SourceType

The type of data source for the resource data sync. `SourceType` is either `AwsOrganizations` (if an organization is present in AWS Organizations) or `singleAccountMultiRegions`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

State

The data type name for including resource data sync state. There are four sync states:

`OrganizationNotExists`: Your organization doesn't exist.

`NoPermissions`: The system can't locate the service-linked role. This role is automatically created when a user creates a resource data sync in Explorer.

`InvalidOrganizationalUnit`: You specified or selected an invalid unit in the resource data sync configuration.

`TrustedAccessDisabled`: You disabled Systems Manager access in the organization in AWS Organizations.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ResultAttribute

The inventory item result attribute.

Contents

TypeName

Name of the inventory item type. Valid value: `AWS:InstanceInformation`. Default Value: `AWS:InstanceInformation`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(AWS|Custom):.*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ReviewInformation

Information about the result of a document review request.

Contents

ReviewedTime

The time that the reviewer took action on the document review request.

Type: Timestamp

Required: No

Reviewer

The reviewer assigned to take action on the document review request.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Status

The current status of the document review request.

Type: String

Valid Values: `APPROVED | NOT_REVIEWED | PENDING | REJECTED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

Runbook

Information about an Automation runbook used in a runbook workflow in Change Manager.

> **Note**
>
> The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Contents

DocumentName

The name of the Automation runbook used in a runbook workflow.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

DocumentVersion

The version of the Automation runbook used in a runbook workflow.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[1-9][0-9]*$)`

Required: No

MaxConcurrency

The `MaxConcurrency` value specified by the user when the operation started, indicating the maximum number of resources that the runbook operation can run on at the same time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

MaxErrors

The `MaxErrors` value specified by the user when the execution started, indicating the maximum number of errors that can occur during the operation before the updates are stopped or rolled back.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Parameters

The key-value map of execution parameters, which were supplied when calling `StartChangeRequestExecution`.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

TargetLocations

Information about the AWS Regions and AWS accounts targeted by the current Runbook operation.

Type: Array of TargetLocation objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of runbook parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The name of the parameter used as the target resource for the rate-controlled runbook workflow. Required if you specify `Targets`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

A key-value mapping to target resources that the runbook operation performs tasks on. Required if you specify `TargetParameterName`.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

S3OutputLocation

An S3 bucket where you want to store the results of this request.

Contents

OutputS3BucketName

The name of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

The AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

S3OutputUrl

A URL for the AWS Systems Manager (Systems Manager) bucket where you want to store the results of this request.

Contents

OutputUrl

A URL for an S3 bucket where you want to store the results of this request.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ScheduledWindowExecution

Information about a scheduled execution for a maintenance window.

Contents

ExecutionTime

The time, in ISO-8601 Extended format, that the maintenance window is scheduled to be run.

Type: String

Required: No

Name

The name of the maintenance window to be run.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

WindowId

The ID of the maintenance window to be run.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ServiceSetting

The service setting data structure.

`ServiceSetting` is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a `SettingId` object to a setting value. AWS services teams define the default value for a `SettingId`. You can't create a new `SettingId`, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the UpdateServiceSetting API operation to change the default setting. Or, use the ResetServiceSetting to change the value back to the original value defined by the AWS service team.

Contents

ARN

The ARN of the service setting.

Type: String

Required: No

LastModifiedDate

The last time the service setting was modified.

Type: Timestamp

Required: No

LastModifiedUser

The ARN of the last modified user. This field is populated only if the setting value was overwritten.

Type: String

Required: No

SettingId

The ID of the service setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

SettingValue

The value of the service setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Status

The status of the service setting. The value can be Default, Customized or PendingUpdate.

- Default: The current setting uses a default value provisioned by the AWS service team.
- Customized: The current setting use a custom value specified by the customer.
- PendingUpdate: The current setting uses a default or custom value, but a setting change request is pending approval.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Session

Information about a Session Manager connection to a managed node.

Contents

AccessType

`Standard` access type is the default for Session Manager sessions. `JustInTime` is the access type for Just-in-time node access.

Type: String

Valid Values: `Standard | JustInTime`

Required: No

Details

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

DocumentName

The name of the Session Manager SSM document used to define the parameters and plugin settings for the session. For example, `SSM-SessionManagerRunShell`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

EndDate

The date and time, in ISO-8601 Extended format, when the session was terminated.

Type: Timestamp

Required: No

MaxSessionDuration

The maximum duration of a session before it terminates.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4.

Pattern: `^([1-9]|[1-9][0-9]|[1-9][0-9][0-9]|1[0-4][0-3][0-9]|1440)$`

Required: No

OutputUrl

Reserved for future use.

Type: SessionManagerOutputUrl object

Required: No

Owner

The ID of the Amazon Web Services user that started the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

Reason

The reason for connecting to the instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^.{1,256}$`

Required: No

SessionId

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: No

StartDate

The date and time, in ISO-8601 Extended format, when the session began.

Type: Timestamp

Required: No

Status

The status of the session. For example, "Connected" or "Terminated".

Type: String

Valid Values: `Connected | Connecting | Disconnected | Terminated | Terminating | Failed`

Required: No

Target

The managed node that the Session Manager session connected to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SessionFilter

Describes a filter for Session Manager information.

Contents

key

The name of the filter.

Type: String

Valid Values: `InvokedAfter | InvokedBefore | Target | Owner | Status | SessionId | AccessType`

Required: Yes

value

The filter value. Valid values for each filter key are as follows:

- InvokedAfter: Specify a timestamp to limit your results. For example, specify 2024-08-29T00:00:00Z to see sessions that started August 29, 2024, and later.
- InvokedBefore: Specify a timestamp to limit your results. For example, specify 2024-08-29T00:00:00Z to see sessions that started before August 29, 2024.
- Target: Specify a managed node to which session connections have been made.
- Owner: Specify an Amazon Web Services user to see a list of sessions started by that user.
- Status: Specify a valid session status to see a list of all sessions with that status. Status values you can specify include:
  - Connected
  - Connecting
  - Disconnected
  - Terminated
  - Terminating
  - Failed
- SessionId: Specify a session ID to return details about the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SessionManagerOutputUrl

Reserved for future use.

Contents

CloudWatchOutputUrl

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2083.

Required: No

S3OutputUrl

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2083.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SeveritySummary

The number of managed nodes found for each patch severity level defined in the request filter.

Contents

CriticalCount

The total number of resources or compliance items that have a severity level of `Critical`. Critical severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

HighCount

The total number of resources or compliance items that have a severity level of high. High severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

InformationalCount

The total number of resources or compliance items that have a severity level of informational. Informational severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

LowCount

The total number of resources or compliance items that have a severity level of low. Low severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

MediumCount

The total number of resources or compliance items that have a severity level of medium. Medium severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

UnspecifiedCount

The total number of resources or compliance items that have a severity level of unspecified. Unspecified severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

StepExecution

Detailed information about an the execution state of an Automation step.

Contents

Action

The action this step performs. The action determines the behavior of the step.

Type: String

Pattern: `^aws:[a-zA-Z]{3,25}$`

Required: No

ExecutionEndTime

If a step has finished execution, this contains the time the execution ended. If the step hasn't yet concluded, this field isn't populated.

Type: Timestamp

Required: No

ExecutionStartTime

If a step has begun execution, this contains the time the step started. If the step is in Pending status, this field isn't populated.

Type: Timestamp

Required: No

FailureDetails

Information about the Automation failure.

Type: FailureDetails object

Required: No

FailureMessage

If a step failed, this message explains why the execution failed.

Type: String

Required: No

Inputs

Fully-resolved values passed into the step before execution.

Type: String to string map

Required: No

IsCritical

The flag which can be used to help decide whether the failure of current step leads to the Automation failure.

Type: Boolean

Required: No

IsEnd

The flag which can be used to end automation no matter whether the step succeeds or fails.

Type: Boolean

Required: No

MaxAttempts

The maximum number of tries to run the action of the step. The default value is 1.

Type: Integer

Required: No

NextStep

The next step after the step succeeds.

Type: String

Required: No

OnFailure

The action to take if the step fails. The default value is `Abort`.

Type: String

Required: No

Outputs

Returned values from the execution of the step.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

OverriddenParameters

A user-specified list of parameters to override when running a step.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

ParentStepDetails

Information about the parent step.

Type: ParentStepDetails object

Required: No

Response

A message associated with the response code for an execution.

Type: String

Required: No

ResponseCode

The response code returned by the execution of the step.

Type: String

Required: No

StepExecutionId

The unique ID of a step execution.

Type: String

Required: No

StepName

The name of this execution step.

Type: String

Required: No

StepStatus

The execution status for this step.

Type: String

Valid Values: `Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure | Exited`

Required: No

TargetLocation

The combination of AWS Regions and AWS accounts targeted by the current Automation execution.

Type: TargetLocation object

Required: No

Targets

The targets for the step execution.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TimeoutSeconds

The timeout seconds of the step.

Type: Long

Required: No

TriggeredAlarms

The CloudWatch alarms that were invoked by the automation.

Type: Array of AlarmStateInformation objects

Array Members: Fixed number of 1 item.

Required: No

ValidNextSteps

Strategies used when step fails, we support Continue and Abort. Abort will fail the automation when the step fails. Continue will ignore the failure of current step and allow automation to run the next step. With conditional branching, we add step:stepName to support the automation to go to another specific step.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

StepExecutionFilter

A filter to limit the amount of step execution information returned by the call.

Contents

Key

One or more keys to limit the results.

Type: String

Valid Values: `StartTimeBefore | StartTimeAfter | StepExecutionStatus | StepExecutionId | StepName | Action | ParentStepExecutionId | ParentStepIteration | ParentStepIteratorValue`

Required: Yes

Values

The values of the filter key.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Tag

Metadata that you assign to your AWS resources. Tags enable you to categorize your resources in different ways, for example, by purpose, owner, or environment. In AWS Systems Manager, you can apply tags to Systems Manager documents (SSM documents), managed nodes, maintenance windows, parameters, patch baselines, OpsItems, and OpsMetadata.

Contents

Key

The name of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Target

An array of search criteria that targets managed nodes using a key-value pair that you specify.

> **Note**
>
> One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see Registering maintenance window tasks without targets in the *AWS Systems Manager User Guide*.

Supported formats include the following.

For all Systems Manager tools:

- `Key=tag-key,Values=tag-value-1,tag-value-2`

For Automation and Change Manager:

- `Key=tag:tag-key,Values=tag-value`
- `Key=ResourceGroup,Values=resource-group-name`
- `Key=ParameterValues,Values=value-1,value-2,value-3`
- To target all instances in the AWS Region:
  - `Key=AWS::EC2::Instance,Values=*`
  - `Key=InstanceIds,Values=*`

For Run Command and Maintenance Windows:

- `Key=InstanceIds,Values=instance-id-1,instance-id-2,instance-id-3`
- `Key=tag:tag-key,Values=tag-value-1,tag-value-2`
- `Key=resource-groups:Name,Values=resource-group-name`
- Additionally, Maintenance Windows support targeting resource types:
  - `Key=resource-groups:ResourceTypeFilters,Values=resource-type-1,resource-type-2`

For State Manager:

- `Key=InstanceIds,Values=instance-id-1,instance-id-2,instance-id-3`
- `Key=tag:tag-key,Values=tag-value-1,tag-value-2`
- To target all instances in the AWS Region:
  - `Key=InstanceIds,Values=*`

For more information about how to send commands that target managed nodes using `Key,Value` parameters, see Targeting multiple managed nodes in the *AWS Systems Manager User Guide*.

Contents

Key

User-defined criteria for sending commands that target managed nodes that meet the criteria.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 163.

Pattern: `^[\p{L}\p{Z}\p{N}_.:/=\-@]*$|resource-groups:ResourceTypeFilters|resource-groups:Name`

Required: No

Values

User-defined criteria that maps to `Key`. For example, if you specified `tag:ServerRole`, you could specify `value:WebServer` to run a command on instances that include EC2 tags of `ServerRole,WebServer`.

Depending on the type of target, the maximum number of values for a key might be lower than the global maximum of 50.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TargetLocation

The combination of AWS Regions and AWS accounts targeted by the current Automation execution.

Contents

Accounts

The AWS accounts targeted by the current Automation execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

ExcludeAccounts

AWS accounts or organizational units to exclude as expanded targets.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5000 items.

Length Constraints: Minimum length of 6. Maximum length of 68.

Pattern: `^(ou-[a-z0-9]{4,32}-[a-z0-9]{8,32})|(\d{12})$`

Required: No

ExecutionRoleName

The Automation execution role used by the currently running Automation. If not specified, the default value is `AWS-SystemsManager-AutomationExecutionRole`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@/-]+`

Required: No

IncludeChildOrganizationUnits

Indicates whether to include child organizational units (OUs) that are children of the targeted OUs. The default is `false`.

> **Note**
>
> This parameter is not supported by State Manager.

Type: Boolean

Required: No

Regions

The AWS Regions targeted by the current Automation execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

TargetLocationAlarmConfiguration

The details for the CloudWatch alarm you want to apply to an automation or command.

Type: AlarmConfiguration object

Required: No

TargetLocationMaxConcurrency

The maximum number of AWS Regions and AWS accounts allowed to run the Automation concurrently. `TargetLocationMaxConcurrency` has a default value of 1.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

TargetLocationMaxErrors

The maximum number of errors allowed before the system stops queueing additional Automation executions for the currently running Automation. `TargetLocationMaxErrors` has a default value of 0.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

Targets

A list of key-value mappings to target resources. If you specify values for this data type, you must also specify a value for `TargetParameterName`.

This `Targets` parameter takes precedence over the `StartAutomationExecution:Targets` parameter if both are supplied.

Type: Array of Target objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TargetsMaxConcurrency

The maximum number of targets allowed to run this task in parallel. This `TargetsMaxConcurrency` takes precedence over the `StartAutomationExecution:MaxConcurrency` parameter if both are supplied.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%|100%)$`

Required: No

TargetsMaxErrors

The maximum number of errors that are allowed before the system stops running the automation on additional targets. This `TargetsMaxErrors` parameter takes precedence over the `StartAutomationExecution:MaxErrors` parameter if both are supplied.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TargetPreview

Information about the resources that would be included in the actual runbook execution, if it were to be run.

Contents

Count

The number of resources of a certain type included in an execution preview.

Type: Integer

Required: No

TargetType

A type of resource that was included in the execution preview.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see Signing AWS API requests in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key*/*YYYYMMDD*/*region*/*service*/aws4_request.

For more information, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an AWS API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see AWS services that work with IAM in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400