



API Reference

AWS Trusted Advisor



API Version 2022-09-15

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Trusted Advisor: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchUpdateRecommendationResourceExclusion	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	4
Response Elements	4
Errors	4
Examples	5
See Also	6
GetOrganizationRecommendation	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	7
Response Elements	8
Errors	8
Examples	9
See Also	10
GetRecommendation	12
Request Syntax	12
URI Request Parameters	12
Request Body	12
Response Syntax	12
Response Elements	13
Errors	14
Examples	14
See Also	15
ListChecks	17
Request Syntax	17
URI Request Parameters	17
Request Body	18
Response Syntax	18

Response Elements	18
Errors	19
Examples	20
See Also	22
ListOrganizationRecommendationAccounts	24
Request Syntax	24
URI Request Parameters	24
Request Body	25
Response Syntax	25
Response Elements	25
Errors	26
Examples	26
See Also	27
ListOrganizationRecommendationResources	28
Request Syntax	28
URI Request Parameters	28
Request Body	29
Response Syntax	29
Response Elements	30
Errors	30
Examples	31
See Also	33
ListOrganizationRecommendations	34
Request Syntax	34
URI Request Parameters	34
Request Body	35
Response Syntax	35
Response Elements	36
Errors	37
Examples	37
See Also	41
ListRecommendationResources	42
Request Syntax	42
URI Request Parameters	42
Request Body	43
Response Syntax	43

Response Elements	44
Errors	44
Examples	45
See Also	47
ListRecommendations	48
Request Syntax	48
URI Request Parameters	48
Request Body	49
Response Syntax	49
Response Elements	50
Errors	51
Examples	51
See Also	55
UpdateOrganizationRecommendationLifecycle	57
Request Syntax	57
URI Request Parameters	57
Request Body	57
Response Syntax	58
Response Elements	58
Errors	58
Examples	59
See Also	60
UpdateRecommendationLifecycle	61
Request Syntax	61
URI Request Parameters	61
Request Body	61
Response Syntax	62
Response Elements	62
Errors	62
Examples	63
See Also	64
Data Types	65
AccountRecommendationLifecycleSummary	66
Contents	66
See Also	68
Checksum	69

Contents	69
See Also	70
OrganizationRecommendation	72
Contents	72
See Also	76
OrganizationRecommendationResourceSummary	77
Contents	77
See Also	79
OrganizationRecommendationSummary	80
Contents	80
See Also	83
Recommendation	84
Contents	84
See Also	88
RecommendationCostOptimizingAggregates	89
Contents	89
See Also	89
RecommendationPillarSpecificAggregates	90
Contents	90
See Also	90
RecommendationResourceExclusion	91
Contents	91
See Also	91
RecommendationResourcesAggregates	92
Contents	92
See Also	93
RecommendationResourceSummary	94
Contents	94
See Also	96
RecommendationSummary	97
Contents	97
See Also	100
UpdateRecommendationResourceExclusionError	101
Contents	101
See Also	101
Common Parameters	103

Common Error Types 106

Welcome

TrustedAdvisor Public API

This document was last published on April 10, 2026.

Actions

The following actions are supported:

- [BatchUpdateRecommendationResourceExclusion](#)
- [GetOrganizationRecommendation](#)
- [GetRecommendation](#)
- [ListChecks](#)
- [ListOrganizationRecommendationAccounts](#)
- [ListOrganizationRecommendationResources](#)
- [ListOrganizationRecommendations](#)
- [ListRecommendationResources](#)
- [ListRecommendations](#)
- [UpdateOrganizationRecommendationLifecycle](#)
- [UpdateRecommendationLifecycle](#)

BatchUpdateRecommendationResourceExclusion

Update one or more exclusion statuses for a list of recommendation resources. This API supports up to 25 unique recommendation resource ARNs per request. This API currently doesn't support prioritized recommendation resources. This API updates global recommendations, eliminating the need to call the API in each AWS Region. After submitting an exclusion update, note that it might take a few minutes for the changes to be reflected in the system.

Request Syntax

```
PUT /v1/batch-update-recommendation-resource-exclusion HTTP/1.1
Content-type: application/json

{
  "recommendationResourceExclusions": [
    {
      "arn": "string",
      "isExcluded": boolean
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[recommendationResourceExclusions](#)

A list of recommendation resource ARNs and exclusion status to update

Type: Array of [RecommendationResourceExclusion](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "batchUpdateRecommendationResourceExclusionErrors": [
    {
      "arn": "string",
      "errorCode": "string",
      "errorMessage": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[batchUpdateRecommendationResourceExclusionErrors](#)

A list of recommendation resource ARNs whose exclusion status failed to update, if any

Type: Array of [UpdateRecommendationResourceExclusionError](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

ConflictException

Exception that the request was denied due to conflicts in state

HTTP Status Code: 409

InternalServerErrorException

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

Update one or more exclusion status for a list of recommendation resources

Batch update one or more exclusion status for a list of recommendation resources

Sample Request

```
{
    "recommendationResourceExclusions": [
        {
            "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/55fa4d2e-
bbb7-491a-833b-5773e9589578/18959a1f1973cff8e706e9d9bde28bba36cd602a6b2cb86c8b61252835236010",
            "isExcluded": true
        }
    ]
}
```

Sample Response

```
{
    "batchUpdateRecommendationResourceExclusionErrors": [
        {
```

```
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-  
resource/55fa4d2e-  
bbb7-491a-833b-5773e9589578/18959a1f1973cff8e706e9d9bde28bba36cd602a6b2cb86c8b61252835236010",  
    "errorCode": "404",  
    "errorMessage": "Exception that the requested resource has not been  
found"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOrganizationRecommendation

Get a specific recommendation within an AWS Organizations organization. This API supports only prioritized recommendations and provides global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/organization-recommendations/organizationRecommendationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

organizationRecommendationIdentifier

The Recommendation identifier

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\/[\w-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "organizationRecommendation": {
    "arn": "string",
    "awsServices": [ "string" ],
    "checkArn": "string",
    "createdAt": "string",
    "createdBy": "string",
    "description": "string",
```

```
"id": "string",
"lastUpdatedAt": "string",
"lifecycleStage": "string",
"name": "string",
"pillars": [ "string" ],
"pillarSpecificAggregates": {
  "costOptimizing": {
    "estimatedMonthlySavings": number,
    "estimatedPercentMonthlySavings": number
  }
},
"resolvedAt": "string",
"resourcesAggregates": {
  "errorCount": number,
  "excludedCount": number,
  "okCount": number,
  "warningCount": number
},
"source": "string",
"status": "string",
"type": "string",
"updatedOnBehalfOf": "string",
"updatedOnBehalfOfJobTitle": "string",
"updateReason": "string",
"updateReasonCode": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

organizationRecommendation

The Recommendation

Type: [OrganizationRecommendation](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

Get Organization Recommendation

Get an organization recommendation by identifier.

Sample Request

```
{
    "organizationRecommendationIdentifier":
    "arn:aws:trustedadvisor::organization-recommendation/9534ec9b-
    bf3a-44e8-8213-2ed68b39d9d5"
}
```

Sample Response

```
{
  "organizationRecommendation": {
    "arn": "arn:aws:trustedadvisor::organization-
recommendation/9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
    "name": "Lambda Runtime Deprecation Warning",
    "description": "One or more lambdas are using a deprecated
runtime",
    "awsServices": [
      "lambda"
    ],
    "checkArn": "arn:aws:trustedadvisor::check/L4dfs2Q4C5",
    "id": "9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
    "lifecycleStage": "resolved",
    "pillars": [
      "security"
    ],
    "resourcesAggregates": {
      "errorCount": 0,
      "okCount": 0,
      "warningCount": 0
    },
    "source": "ta_check",
    "status": "warning",
    "type": "priority"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRecommendation

Get a specific Recommendation. This API provides global recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/recommendations/recommendationIdentifier?language=language HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

language

The ISO 639-1 code for the language that you want your recommendations to appear in.

Valid Values: en | ja | zh | fr | de | ko | zh_TW | it | es | pt_BR | id

recommendationIdentifier

The Recommendation identifier

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: arn:[\w-]+:trustedadvisor::\d{12}:recommendation\[/[\w-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "recommendation": {
    "arn": "string",
    "awsServices": [ "string" ],
```

```
"checkArn": "string",
"createdAt": "string",
"createdBy": "string",
"description": "string",
"id": "string",
"lastUpdatedAt": "string",
"lifecycleStage": "string",
"name": "string",
"pillars": [ "string" ],
"pillarSpecificAggregates": {
  "costOptimizing": {
    "estimatedMonthlySavings": number,
    "estimatedPercentMonthlySavings": number
  }
},
"resolvedAt": "string",
"resourcesAggregates": {
  "errorCount": number,
  "excludedCount": number,
  "okCount": number,
  "warningCount": number
},
"source": "string",
"status": "string",
"statusReason": "string",
"type": "string",
"updatedOnBehalfOf": "string",
"updatedOnBehalfOfJobTitle": "string",
"updateReason": "string",
"updateReasonCode": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

recommendation

The Recommendation

Type: [Recommendation](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

Get A Recommendation

Get a recommendation by identifier.

Sample Request

```
{
    "recommendationIdentifier":
    "arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
    bbb7-491a-833b-5773e9589578",
```

```
}
```

Sample Response

```
{
    "recommendation": {
        "arn":
            "arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
            bbb7-491a-833b-5773e9589578",
        "name": "MFA Recommendation",
        "description": "Enable multi-factor authentication",
        "awsServices": [
            "iam"
        ],
        "checkArn": "arn:aws:trustedadvisor:::check/7DAFEmoDos",
        "id": "55fa4d2e-bbb7-491a-833b-5773e9589578",
        "lastUpdatedAt": "2023-11-01T15:57:58.673Z",
        "pillarSpecificAggregates": {
            "costOptimizing": {
                "estimatedMonthlySavings": 0.0,
                "estimatedPercentMonthlySavings": 0.0
            }
        },
        "pillars": [
            "security"
        ],
        "resourcesAggregates": {
            "errorCount": 1,
            "okCount": 0,
            "warningCount": 0
        },
        "source": "ta_check",
        "status": "error",
        "type": "standard"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChecks

List a filterable set of Checks. This API provides global recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/checks?  
awsService=awsService&language=language&maxResults=maxResults&nextToken=nextToken&pillar=pillar  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[awsService](#)

The aws service associated with the check

Length Constraints: Minimum length of 2. Maximum length of 30.

[language](#)

The ISO 639-1 code for the language that you want your checks to appear in.

Valid Values: en | ja | zh | fr | de | ko | zh_TW | it | es | pt_BR | id

[maxResults](#)

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 200.

[nextToken](#)

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

[pillar](#)

The pillar of the check

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

[source](#)

The source of the check

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "checkSummaries": [
    {
      "arn": "string",
      "awsServices": [ "string" ],
      "description": "string",
      "id": "string",
      "metadata": {
        "string" : "string"
      },
      "name": "string",
      "pillars": [ "string" ],
      "source": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

checkSummaries

The list of Checks

Type: Array of [CheckSummary](#) objects

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List Checks With A Max Result

List at most two Checks.

Sample Request

```
{
    "maxResults": 2
}
```

Sample Response

```
{
    "checkSummaries": [
        {
            "arn": "arn:aws:trustedadvisor:::check/1iG5NDGVre",
            "awsServices": [
                "EC2"
            ],
            "description": "Checks security groups for rules that allow unrestricted access to a resource. Unrestricted access increases opportunities for malicious activity (hacking, denial-of-service attacks, loss of data)",
            "id": "1iG5NDGVre",
            "metadata": {
                "0": "Region",
                "1": "Security Group Name",
                "2": "Security Group ID",
                "3": "Protocol",
                "4": "Port",
                "5": "Status",
                "6": "IP Range"
            },
            "name": "Security Groups - Unrestricted Access",
            "pillars": [
                "security"
            ],
            "source": "ta_check"
        },
        {
            "arn": "arn:aws:trustedadvisor:::check/1qazXsw23e",
            "awsServices": [
```

```

    "RDS"
  ],
  "description": "Checks your usage of RDS and provides
recommendations on purchase of Reserved Instances to help reduce costs incurred
from using RDS On-Demand. AWS generates these recommendations by analyzing your On-
Demand usage for the past 30 days. We then simulate every combination of reservations
in the generated category of usage in order to identify the best number of each
type of Reserved Instance to purchase to maximize your savings. This check covers
recommendations based on partial upfront payment option with 1-year or 3-year
commitment. This check is not available to accounts linked in Consolidated Billing.
Recommendations are only available for the Paying Account.",
  "id": "1qazXsw23e",
  "metadata": {
    "0": "Region",
    "1": "Family",
    "2": "Instance Type",
    "3": "License Model",
    "4": "Database Edition",
    "5": "Database Engine",
    "6": "Deployment Option",
    "7": "Recommended number of Reserved Instances to purchase",
    "8": "Expected Average Reserved Instance Utilization",
    "9": "Estimated Savings with Recommendation (monthly)"
    "10": "Upfront Cost of Reserved Instances",
    "11": "Estimated cost of Reserved Instances (monthly)",
    "12": "Estimated On-Demand Cost Post Recommended Reserved Instance
Purchase (monthly)",
    "13": "Estimated Break Even (months)",
    "14": "Lookback Period (days)",
    "15": "Term (years)"
  },
  "name": "Amazon Relational Database Service (RDS) Reserved Instance
Optimization",
  "pillars": [
    "cost_optimizing"
  ],
  "source": "ta_check"
},
{
  "arn": "arn:aws:trustedadvisor:::check/1qw23er45t",
  "awsServices": [
    "Redshift"
  ],

```

```
    "description": "Checks your usage of Redshift and provides
recommendations on purchase of Reserved Nodes to help reduce costs incurred from using
Redshift On-Demand. AWS generates these recommendations by analyzing your On-Demand
usage for the past 30 days. We then simulate every combination of reservations in
the generated category of usage in order to identify the best number of each type of
Reserved Nodes to purchase to maximize your savings. This check covers recommendations
based on partial upfront payment option with 1-year or 3-year commitment. This check
is not available to accounts linked in Consolidated Billing. Recommendations are only
available for the Paying Account.",
    "id": "1qw23er45t",
    "metadata": {
      "0": "Region",
      "1": "Family",
      "2": "Node Type",
      "3": "Recommended number of Reserved Nodes to purchase",
      "4": "Expected Average Reserved Node Utilization",
      "5": "Estimated Savings with Recommendation (monthly)",
      "6": "Upfront Cost of Reserved Nodes",
      "7": "Estimated cost of Reserved Nodes (monthly)",
      "8": "Estimated On-Demand Cost Post Recommended Reserved Nodes
Purchase (monthly)",
      "9": "Estimated Break Even (months)",
      "10": "Lookback Period (days)",
      "11": "Term (years)",
    },
    "name": "Amazon Redshift Reserved Node Optimization",
    "pillars": [
      "cost_optimizing"
    ],
    "source": "ta_check"
  },
  ],
  "nextToken": "REDACTED"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrganizationRecommendationAccounts

Lists the accounts that own the resources for an organization aggregate recommendation. This API only supports prioritized recommendations and provides global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/organization-recommendations/organizationRecommendationIdentifier/accounts?  
affectedAccountId=affectedAccountId&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

affectedAccountId

An account affected by this organization recommendation

Length Constraints: Fixed length of 12.

Pattern: `\d+`

maxResults

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 200.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

organizationRecommendationIdentifier

The Recommendation identifier

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\[/[\w-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accountRecommendationLifecycleSummaries": [
    {
      "accountId": "string",
      "accountRecommendationArn": "string",
      "lastUpdatedAt": "string",
      "lifecycleStage": "string",
      "updatedOnBehalfOf": "string",
      "updatedOnBehalfOfJobTitle": "string",
      "updateReason": "string",
      "updateReasonCode": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[accountRecommendationLifecycleSummaries](#)

The account recommendations lifecycles that are applicable to the Recommendation

Type: Array of [AccountRecommendationLifecycleSummary](#) objects

[nextToken](#)

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerErrorException

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List Accounts For An Organization Recommendation

List all account recommendation summaries for an organization recommendation by its identifier.

Sample Request

```
{
```

```
        "organizationRecommendationIdentifier":
          "arn:aws:trustedadvisor::organization-recommendation/9534ec9b-
          bf3a-44e8-8213-2ed68b39d9d5"
      }
```

Sample Response

```
{
    "accountRecommendationLifecycleSummaries": [{
        "accountId": "000000000000",
        "accountRecommendationArn":
          "arn:aws:trustedadvisor::000000000000:recommendation/9534ec9b-
          bf3a-44e8-8213-2ed68b39d9d5",
        "lifecycleStage": "resolved",
        "updateReason": "Resolved issue",
        "updateReasonCode": "valid_business_case",
        "lastUpdatedAt": "2023-01-17T18:25:44.552Z"
    }],
    "nextToken": "REDACTED"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrganizationRecommendationResources

List Resources of a Recommendation within an Organization. This API only supports prioritized recommendations and provides global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/organization-recommendations/organizationRecommendationIdentifier/resources?
affectedAccountId=affectedAccountId&exclusionStatus=exclusionStatus&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

affectedAccountId

An account affected by this organization recommendation

Length Constraints: Fixed length of 12.

Pattern: \d+

exclusionStatus

The exclusion status of the resource

Valid Values: `excluded` | `included`

maxResults

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 200.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

organizationRecommendationIdentifier

The AWS Organization organization's Recommendation identifier

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\[/[\w-]+`

Required: Yes

regionCode

The AWS Region code of the resource

status

The status of the resource

Valid Values: `ok` | `warning` | `error`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "organizationRecommendationResourceSummaries": [
    {
      "accountId": "string",
      "arn": "string",
      "awsResourceId": "string",
      "exclusionStatus": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "metadata": {
        "string": "string"
      },
      "recommendationArn": "string",
      "regionCode": "string",
      "status": "string"
    }
  ]
}
```

```
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

organizationRecommendationResourceSummaries

A list of Recommendation Resources

Type: Array of [OrganizationRecommendationResourceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List All Organization Recommendation Resources

List all resources for an organization recommendation by its identifier.

Sample Request

```
{
  "organizationRecommendationIdentifier":
  "arn:aws:trustedadvisor::organization-recommendation/5a694939-2e54-45a2-
  ae72-730598fa89d0"
}
```

Sample Response

```
{
  "organizationRecommendationResourceSummaries": [
    {
      "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
      resource/5a694939-2e54-45a2-ae72-730598fa89d0/
      bb38affc0ce0681d9a6cd13f30238ba03a8f63dfe7a379dc403c619119d86af",
      "awsResourceId": "database-1-instance-1",
      "id":
      "bb38affc0ce0681d9a6cd13f302383ba03a8f63dfe7a379dc403c619119d86af",
      "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
      "metadata": {
        "0": "14",
        "1": "208.79999999999998",
        "2": "database-1-instance-1",
        "3": "db.r5.large",
      }
    }
  ]
}
```

```

        "4": "false",
        "5": "us-west-2",
        "6": "arn:aws:rds:us-west-2:000000000000:db:database-1-instance-1",
        "7": "1"
    },
    "recommendationArn": "arn:aws:trustedadvisor::organization-
recommendation/5a694939-2e54-45a2-ae72-730598fa89d0",
    "regionCode": "us-west-2",
    "exclusionStatus": "included",
    "status": "warning"
},
{
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/5a694939-2e54-45a2-
ae72-730598fa89d0/51fded4d7a3278818df9cfe344ff5762cec46c095a6763d1ba1ba53bd0e1b0e6",
    "awsResourceId": "database-1",
    "id":
"51fded4d7a3278818df9cfe344ff5762cec46c095a6763d1ba1ba53bd0e1b0e6",
    "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
    "metadata": {
        "0": "14",
        "1": "31.679999999999996",
        "2": "database-1",
        "3": "db.t3.small",
        "4": "false",
        "5": "us-west-2",
        "6": "arn:aws:rds:us-west-2:000000000000:db:database-1",
        "7": "20"
    },
    "recommendationArn": "arn:aws:trustedadvisor::organization-
recommendation/5a694939-2e54-45a2-ae72-730598fa89d0",
    "regionCode": "us-west-2",
    "exclusionStatus": "included",
    "status": "warning"
},
{
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/5a694939-2e54-45a2-ae72-730598fa89d0/
f4d01bd20f4cd5372062aafc8786c489e48f0ead7cdab121463bf9f89e40a36b",
    "awsResourceId": "database-2-instance-1-us-west-2a",
    "id":
"f4d01bd20f4cd5372062aafc8786c489e48f0ead7cdab121463bf9f89e40a36b",
    "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
    "metadata": {

```

```
    "0": "14",
    "1": "187.200000000000002",
    "2": "database-2-instance-1-us-west-2a",
    "3": "db.r6g.large",
    "4": "true",
    "5": "us-west-2",
    "6": "arn:aws:rds:us-west-2:000000000000:db:database-2-instance-1-
us-west-2a",
    "7": "1"
  },
  "recommendationArn": "arn:aws:trustedadvisor:::organization-
recommendation/5a694939-2e54-45a2-ae72-730598fa89d0",
  "regionCode": "us-west-2",
  "exclusionStatus": "included",
  "status": "warning"
},
],
"nextToken": "REDACTED"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrganizationRecommendations

List a filterable set of Recommendations within an Organization. This API only supports prioritized recommendations and provides global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/organization-recommendations?  
afterLastUpdatedAt=afterLastUpdatedAt&awsService=awsService&beforeLastUpdatedAt=beforeLastUpdatedAt  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[afterLastUpdatedAt](#)

After the last update of the Recommendation

[awsService](#)

The aws service associated with the Recommendation

Length Constraints: Minimum length of 2. Maximum length of 30.

[beforeLastUpdatedAt](#)

Before the last update of the Recommendation

[checkIdentifier](#)

The check identifier of the Recommendation

Length Constraints: Minimum length of 20. Maximum length of 64.

Pattern: `arn:[\w-]+:trustedadvisor:::check\[\w-]+`

[maxResults](#)

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 200.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

pillar

The pillar of the Recommendation

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

source

The source of the Recommendation

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

status

The status of the Recommendation

Valid Values: `ok` | `warning` | `error`

type

The type of the Recommendation

Valid Values: `standard` | `priority`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "nextToken": "string",
  "organizationRecommendationSummaries": [
    {
      "arn": "string",
      "awsServices": [ "string" ],
      "checkArn": "string",
      "createdAt": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "lifecycleStage": "string",
      "name": "string",
      "pillars": [ "string" ],
      "pillarSpecificAggregates": {
        "costOptimizing": {
          "estimatedMonthlySavings": number,
          "estimatedPercentMonthlySavings": number
        }
      },
      "resourcesAggregates": {
        "errorCount": number,
        "excludedCount": number,
        "okCount": number,
        "warningCount": number
      },
      "source": "string",
      "status": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

[organizationRecommendationSummaries](#)

The list of Recommendations

Type: Array of [OrganizationRecommendationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List All Organization Recommendations

List all organization recommendations and do not include a filter.

Sample Response

```
{
  "organizationRecommendationSummaries": [
    {
      "arn": "arn:aws:trustedadvisor::organization-
recommendation/9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
      "name": "Lambda Runtime Deprecation Warning",
      "awsServices": [
        "lambda"
      ],
      "checkArn": "arn:aws:trustedadvisor::check/L4dfs2Q4C5",
      "id": "9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
      "lifecycleStage": "resolved",
      "pillars": [
        "security"
      ],
      "resourcesAggregates": {
        "errorCount": 0,
        "okCount": 0,
        "warningCount": 0
      },
      "source": "ta_check",
      "status": "warning",
      "type": "priority"
    },
    {
      "arn": "arn:aws:trustedadvisor::organization-
recommendation/4ecff4d4-1bc1-4c99-a5b8-0fff9ee500d6",
      "name": "Lambda Runtime Deprecation Warning",
      "awsServices": [
        "lambda"
      ],
      "checkArn": "arn:aws:trustedadvisor::check/L4dfs2Q4C5",
      "id": "4ecff4d4-1bc1-4c99-a5b8-0fff9ee500d6",
      "lifecycleStage": "resolved",
      "pillars": [
        "security"
      ],
      "resourcesAggregates": {
        "errorCount": 0,
        "okCount": 0,
        "warningCount": 0
      },
    }
  ]
}
```

```
"source": "ta_check",
"status": "warning",
"type": "priority"
},
],
"nextToken": "REDACTED"
}
```

List Organization Recommendations With Filter

Filter and return a max of one organization recommendation that is a part of the "security" pillar.

Sample Request

```
{
    "pillar": "security",
    "maxResults": 100
}
```

Sample Response

```
{
    "organizationRecommendationSummaries": [{
        "arn": "arn:aws:trustedadvisor::organization-recommendation/9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
        "name": "Lambda Runtime Deprecation Warning",
        "awsServices": [
            "lambda"
        ],
        "checkArn": "arn:aws:trustedadvisor::check/L4dfs2Q4C5",
        "id": "9534ec9b-bf3a-44e8-8213-2ed68b39d9d5",
        "lifecycleStage": "resolved",
        "pillars": [
            "security"
        ],
        "resourcesAggregates": {
            "errorCount": 0,
            "okCount": 0,
            "warningCount": 0
        },
        "source": "ta_check",
        "status": "warning",
        "type": "priority"
    }
]
```

```
    ]],  
    "nextToken": "REDACTED"  
  }  
}
```

Fetch The Next Page Of A Previous Request

Use the "nextToken" returned from a previous request to fetch the next page of filtered organization recommendations that are a part of the "security" pillar.

Sample Request

```
{  
  "nextToken": "REDACTED",  
  "pillar": "security",  
  "maxResults": 100  
}
```

Sample Response

```
{  
  "organizationRecommendationSummaries": [{  
    "arn": "arn:aws:trustedadvisor::organization-recommendation/4ecff4d4-1bc1-4c99-a5b8-0fff9ee500d6",  
    "name": "Lambda Runtime Deprecation Warning",  
    "awsServices": [  
      "lambda"  
    ],  
    "checkArn": "arn:aws:trustedadvisor::check/L4dfs2Q4C5",  
    "id": "4ecff4d4-1bc1-4c99-a5b8-0fff9ee500d6",  
    "lifecycleStage": "resolved",  
    "pillars": [  
      "security"  
    ],  
    "resourcesAggregates": {  
      "errorCount": 0,  
      "okCount": 0,  
      "warningCount": 0  
    },  
    "source": "ta_check",  
    "status": "warning",  
    "type": "priority"  
  }]  
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRecommendationResources

List Resources of a Recommendation. This API provides global recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/recommendations/recommendationIdentifier/resources?  
exclusionStatus=exclusionStatus&language=language&maxResults=maxResults&nextToken=nextToken&reg  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

exclusionStatus

The exclusion status of the resource

Valid Values: `excluded` | `included`

language

The ISO 639-1 code for the language that you want your recommendations to appear in.

Valid Values: `en` | `ja` | `zh` | `fr` | `de` | `ko` | `zh_TW` | `it` | `es` | `pt_BR` | `id`

maxResults

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 5000.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

recommendationIdentifier

The Recommendation identifier

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: Yes

regionCode

The AWS Region code of the resource

status

The status of the resource

Valid Values: `ok` | `warning` | `error`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "recommendationResourceSummaries": [
    {
      "arn": "string",
      "awsResourceId": "string",
      "exclusionStatus": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "metadata": {
        "string" : "string"
      },
      "recommendationArn": "string",
      "regionCode": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

recommendationResourceSummaries

A list of Recommendation Resources

Type: Array of [RecommendationResourceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List All Recommendation Resources

List all resources for a recommendation by its identifier.

Sample Request

```
{
    "recommendationIdentifier":
    "arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
bbb7-491a-833b-5773e9589578"
}
```

Sample Response

```
{
    "recommendationResourceSummaries": [
    {
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/55fa4d2e-
bbb7-491a-833b-5773e9589578/18959a1f1973cff8e706e9d9bde28bba36cd602a6b2cb86c8b61252835236010",
    "id":
    "18959a1f1973cff8e706e9d9bde28bba36cd602a6b2cb86c8b61252835236010",
    "awsResourceId": "webcms-dev-01",
    "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
    "metadata": {
    "0": "14",
    "1": "123.120000000000002",
    "2": "webcms-dev-01",
    "3": "db.m6i.large",
    "4": "false",
    "5": "us-east-1",
    "6": "arn:aws:rds:us-east-1:000000000000:db:webcms-dev-01",
    "7": "20"
    }
    }
    ]
}
```

```

    },
    "recommendationArn":
"arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
bbb7-491a-833b-5773e9589578",
    "regionCode": "us-east-1",
    "exclusionStatus": "included",
    "status": "warning"
  },
  {
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/55fa4d2e-bbb7-491a-833b-5773e9589578/
e6367ff500ac90db8e4adeb4892e39ee9c36bbf812dcbce4b9e4fefcec9eb63e",
    "id":
"e6367ff500ac90db8e4adeb4892e39ee9c36bbf812dcbce4b9e4fefcec9eb63e",
    "awsResourceId": "aws-dev-db-stack-instance-1",
    "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
    "metadata": {
      "0": "14",
      "1": "29.52",
      "2": "aws-dev-db-stack-instance-1",
      "3": "db.t2.small",
      "4": "false",
      "5": "us-east-1",
      "6": "arn:aws:rds:us-east-1:000000000000:db:aws-dev-db-stack-
instance-1",
      "7": "1"
    },
    "recommendationArn":
"arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
bbb7-491a-833b-5773e9589578",
    "regionCode": "us-east-1",
    "exclusionStatus": "included",
    "status": "warning"
  },
  {
    "arn": "arn:aws:trustedadvisor::000000000000:recommendation-
resource/55fa4d2e-
bbb7-491a-833b-5773e9589578/31aa78ba050a5015d2d38cca7f5f1ce88f70857c4e1c3ad03f8f9fd95dad7459",
    "id":
"31aa78ba050a5015d2d38cca7f5f1ce88f70857c4e1c3ad03f8f9fd95dad7459",
    "awsResourceId": "aws-awesome-apps-stack-db",
    "lastUpdatedAt": "2023-11-01T15:09:51.891Z",
    "metadata": {
      "0": "14",

```

```
    "1": "114.48000000000002",
    "2": "aws-awesome-apps-stack-db",
    "3": "db.m6g.large",
    "4": "false",
    "5": "us-east-1",
    "6": "arn:aws:rds:us-east-1:000000000000:db:aws-awesome-apps-stack-
db",
    "7": "100"
  },
  "recommendationArn":
  "arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
bbb7-491a-833b-5773e9589578",
  "regionCode": "us-east-1",
  "exclusionStatus": "included",
  "status": "warning"
}
],
"nextToken": "REDACTED"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRecommendations

List a filterable set of Recommendations. This API provides global recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
GET /v1/recommendations?  
afterLastUpdatedAt=afterLastUpdatedAt&awsService=awsService&beforeLastUpdatedAt=beforeLastUpdatedAt  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

afterLastUpdatedAt

After the last update of the Recommendation

awsService

The aws service associated with the Recommendation

Length Constraints: Minimum length of 2. Maximum length of 30.

beforeLastUpdatedAt

Before the last update of the Recommendation

checkIdentifier

The check identifier of the Recommendation

Length Constraints: Minimum length of 20. Maximum length of 64.

Pattern: `arn:[\w-]+:trustedadvisor:::check\[\w-]+`

language

The ISO 639-1 code for the language that you want your recommendations to appear in.

Valid Values: `en | ja | zh | fr | de | ko | zh_TW | it | es | pt_BR | id`

maxResults

The maximum number of results to return per page.

Valid Range: Minimum value of 1. Maximum value of 200.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Length Constraints: Minimum length of 4. Maximum length of 10000.

pillar

The pillar of the Recommendation

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

source

The source of the Recommendation

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

status

The status of the Recommendation

Valid Values: `ok` | `warning` | `error`

type

The type of the Recommendation

Valid Values: `standard` | `priority`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "nextToken": "string",
  "recommendationSummaries": [
    {
      "arn": "string",
      "awsServices": [ "string" ],
      "checkArn": "string",
      "createdAt": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "lifecycleStage": "string",
      "name": "string",
      "pillars": [ "string" ],
      "pillarSpecificAggregates": {
        "costOptimizing": {
          "estimatedMonthlySavings": number,
          "estimatedPercentMonthlySavings": number
        }
      },
      "resourcesAggregates": {
        "errorCount": number,
        "excludedCount": number,
        "okCount": number,
        "warningCount": number
      },
      "source": "string",
      "status": "string",
      "statusReason": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. Use the value returned in the previous response in the next request to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 10000.

[recommendationSummaries](#)

The list of Recommendations

Type: Array of [RecommendationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

List All Recommendations

List all recommendations and do not include a filter.

Sample Response

```
{
  "recommendationSummaries": [
    {
      "arn":
"arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
bbb7-491a-833b-5773e9589578",
      "name": "MFA Recommendation",
      "awsServices": [
        "iam"
      ],
      "checkArn": "arn:aws:trustedadvisor:::check/7DAFEmoDos",
      "id": "55fa4d2e-bbb7-491a-833b-5773e9589578",
      "lastUpdatedAt": "2023-11-01T15:57:58.673Z",
      "pillarSpecificAggregates": {
        "costOptimizing": {
          "estimatedMonthlySavings": 0.0,
          "estimatedPercentMonthlySavings": 0.0
        }
      },
      "pillars": [
        "security"
      ],
      "resourcesAggregates": {
        "errorCount": 1,
        "okCount": 0,
        "warningCount": 0
      },
      "source": "ta_check",
      "status": "error",
      "type": "standard"
    },
    {
      "arn":
"arn:aws:trustedadvisor::000000000000:recommendation/8b602b6f-452d-4cb2-8a9e-
c7650955d9cd",
      "name": "RDS clusters quota warning",
      "awsServices": [
        "rds"
      ],
      "checkArn": "arn:aws:trustedadvisor:::check/gjqMBn6pjz",
      "id": "8b602b6f-452d-4cb2-8a9e-c7650955d9cd",
      "lastUpdatedAt": "2023-11-01T15:58:17.397Z",
```

```
"pillarSpecificAggregates": {
  "costOptimizing": {
    "estimatedMonthlySavings": 0.0,
    "estimatedPercentMonthlySavings": 0.0
  }
},
"pillars": [
  "service_limits"
],
"resourcesAggregates": {
  "errorCount": 0,
  "okCount": 3,
  "warningCount": 6
},
"source": "ta_check",
"status": "warning",
"type": "standard"
}
],
"nextToken": "REDACTED"
}
```

List Recommendations With Filter

Filter and return a max of one Recommendation that regards AWS IAM.

Sample Request

```
{
  "awsService": "iam",
  "maxResults": 100
}
```

Sample Response

```
{
  "recommendationSummaries": [{
    "arn":
      "arn:aws:trustedadvisor::000000000000:recommendation/55fa4d2e-
      bbb7-491a-833b-5773e9589578",
    "name": "MFA Recommendation",
    "awsServices": [
      "iam"
    ]
  }
]
```

```
    ],
    "checkArn": "arn:aws:trustedadvisor:::check/7DAFEmoDos",
    "id": "55fa4d2e-bbb7-491a-833b-5773e9589578",
    "lastUpdatedAt": "2023-11-01T15:57:58.673Z",
    "pillarSpecificAggregates": {
      "costOptimizing": {
        "estimatedMonthlySavings": 0.0,
        "estimatedPercentMonthlySavings": 0.0
      }
    },
    "pillars": [
      "security"
    ],
    "resourcesAggregates": {
      "errorCount": 1,
      "okCount": 0,
      "warningCount": 0
    },
    "source": "ta_check",
    "status": "error",
    "type": "standard"
  }],
  "nextToken": "REDACTED"
}
```

Fetch The Next Page Of A Previous Request

Use the "nextToken" returned from a previous request to fetch the next page of filtered Recommendations.

Sample Request

```
{
  "nextToken": "REDACTED",
  "awsService": "rds",
  "maxResults": 100
}
```

Sample Response

```
{
  "recommendationSummaries": [{
```

```
    "arn":
      "arn:aws:trustedadvisor::000000000000:recommendation/8b602b6f-452d-4cb2-8a9e-
c7650955d9cd",
      "name": "RDS clusters quota warning",
      "awsServices": [
        "rds"
      ],
      "checkArn": "arn:aws:trustedadvisor:::check/gjqMBn6pjz",
      "id": "8b602b6f-452d-4cb2-8a9e-c7650955d9cd",
      "lastUpdatedAt": "2023-11-01T15:58:17.397Z",
      "pillarSpecificAggregates": {
        "costOptimizing": {
          "estimatedMonthlySavings": 0.0,
          "estimatedPercentMonthlySavings": 0.0
        }
      },
      "pillars": [
        "service_limits"
      ],
      "resourcesAggregates": {
        "errorCount": 0,
        "okCount": 3,
        "warningCount": 6
      },
      "source": "ta_check",
      "status": "warning",
      "type": "standard"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateOrganizationRecommendationLifecycle

Update the lifecycle of a Recommendation within an Organization. This API only supports prioritized recommendations and updates global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
PUT /v1/organization-recommendations/organizationRecommendationIdentifier/lifecycle
HTTP/1.1
Content-type: application/json

{
  "lifecycleStage": "string",
  "updateReason": "string",
  "updateReasonCode": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

organizationRecommendationIdentifier

The Recommendation identifier for AWS Trusted Advisor Priority recommendations

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\/[\w-]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

lifecycleStage

The new lifecycle stage

Type: String

Valid Values: `pending_response` | `in_progress` | `dismissed` | `resolved`

Required: Yes

updateReason

Reason for the lifecycle stage change

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Pattern: `[\s\S]*`

Required: No

updateReasonCode

Reason code for the lifecycle state change

Type: String

Valid Values: `non_critical_account` | `temporary_account` | `valid_business_case` | `other_methods_available` | `low_priority` | `not_applicable` | `other`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

ConflictException

Exception that the request was denied due to conflicts in state

HTTP Status Code: 409

InternalServerErrorException

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

Update the Lifecycle of an Organization Recommendation

Update the lifecycle stage of an organization recommendation that is managed by AWS Trusted Advisor Priority.

Sample Request

```
{
    "organizationRecommendationIdentifier":
    "arn:aws:trustedadvisor:::organization-
    recommendation/96b5e5ca-7930-444c-90c6-06d386128100",
```

```
"lifecycleStage": "dismissed",
"updateReasonCode": "not_applicable",
"updateReason": "Does not apply to this resource"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRecommendationLifecycle

Update the lifecycle of a Recommendation. This API only supports prioritized recommendations and updates global priority recommendations, eliminating the need to call the API in each AWS Region.

Request Syntax

```
PUT /v1/recommendations/recommendationIdentifier/lifecycle HTTP/1.1
Content-type: application/json

{
  "lifecycleStage": "string",
  "updateReason": "string",
  "updateReasonCode": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

recommendationIdentifier

The Recommendation identifier for AWS Trusted Advisor Priority recommendations

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

lifecycleStage

The new lifecycle stage

Type: String

Valid Values: `pending_response` | `in_progress` | `dismissed` | `resolved`

Required: Yes

updateReason

Reason for the lifecycle stage change

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Pattern: `[\s\S]*`

Required: No

updateReasonCode

Reason code for the lifecycle state change

Type: String

Valid Values: `non_critical_account | temporary_account | valid_business_case | other_methods_available | low_priority | not_applicable | other`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Exception that access has been denied due to insufficient access

HTTP Status Code: 403

ConflictException

Exception that the request was denied due to conflicts in state

HTTP Status Code: 409

InternalServerError

Exception to notify that an unexpected internal error occurred during processing of the request

HTTP Status Code: 500

ResourceNotFoundException

Exception that the requested resource has not been found

HTTP Status Code: 404

ThrottlingException

Exception to notify that requests are being throttled

HTTP Status Code: 429

ValidationException

Exception that the request failed to satisfy service constraints

HTTP Status Code: 400

Examples

Update the Lifecycle of a Recommendation

Update the lifecycle stage of a recommendation managed by AWS Trusted Advisor Priority.

Sample Request

```
{
    "recommendationIdentifier":
    "arn:aws:trustedadvisor::000000000000:recommendation/861c9c6e-
    f169-405a-8b59-537a8caccd7a",
    "lifecycleStage": "resolved",
    "updateReasonCode": "valid_business_case",
    "updateReason": "Resolved the recommendation"
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The TrustedAdvisor Public API API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountRecommendationLifecycleSummary](#)
- [CheckSummary](#)
- [OrganizationRecommendation](#)
- [OrganizationRecommendationResourceSummary](#)
- [OrganizationRecommendationSummary](#)
- [Recommendation](#)
- [RecommendationCostOptimizingAggregates](#)
- [RecommendationPillarSpecificAggregates](#)
- [RecommendationResourceExclusion](#)
- [RecommendationResourcesAggregates](#)
- [RecommendationResourceSummary](#)
- [RecommendationSummary](#)
- [UpdateRecommendationResourceExclusionError](#)

AccountRecommendationLifecycleSummary

Summary of an AccountRecommendationLifecycle for an Organization Recommendation

Contents

accountId

The AWS account ID

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

accountRecommendationArn

The Recommendation ARN

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: No

lastUpdatedAt

When the Recommendation was last updated

Type: Timestamp

Required: No

lifecycleStage

The lifecycle stage from AWS Trusted Advisor Priority

Type: String

Valid Values: `in_progress` | `pending_response` | `dismissed` | `resolved`

Required: No

updatedOnBehalfOf

The person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updatedOnBehalfOfJobTitle

The job title of the person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updateReason

Reason for the lifecycle stage change

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Pattern: `[\s\S]*`

Required: No

updateReasonCode

Reason code for the lifecycle state change

Type: String

Valid Values: `non_critical_account` | `temporary_account` | `valid_business_case` | `other_methods_available` | `low_priority` | `not_applicable` | `other`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CheckSummary

A summary of an AWS Trusted Advisor Check

Contents

arn

The ARN of the AWS Trusted Advisor Check

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor:::check\/[\w-]+`

Required: Yes

awsServices

The AWS Services that the Check applies to

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 30.

Required: Yes

description

A description of what the AWS Trusted Advisor Check is monitoring

Type: String

Required: Yes

id

The unique identifier of the AWS Trusted Advisor Check

Type: String

Required: Yes

metadata

The column headings for the metadata returned in the resource

Type: String to string map

Required: Yes

name

The name of the AWS Trusted Advisor Check

Type: String

Required: Yes

pillars

The Recommendation pillars that the AWS Trusted Advisor Check falls under

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

Required: Yes

source

The source of the Recommendation

Type: String

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrganizationRecommendation

A Recommendation for accounts within an Organization

Contents

arn

The ARN of the Recommendation

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\/[\w-]+`

Required: Yes

description

A description for AWS Trusted Advisor recommendations

Type: String

Required: Yes

id

The ID which identifies where the Recommendation was produced

Type: String

Required: Yes

name

The name of the AWS Trusted Advisor Recommendation

Type: String

Required: Yes

pillars

The Pillars that the Recommendation is optimizing

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

Required: Yes

resourcesAggregates

An aggregation of all resources

Type: [RecommendationResourcesAggregates](#) object

Required: Yes

source

The source of the Recommendation

Type: String

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

Required: Yes

status

The status of the Recommendation

Type: String

Valid Values: `ok` | `warning` | `error`

Required: Yes

type

Whether the Recommendation was automated or generated by AWS Trusted Advisor Priority

Type: String

Valid Values: `standard` | `priority`

Required: Yes

awsServices

The AWS Services that the Recommendation applies to

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 30.

Required: No

checkArn

The AWS Trusted Advisor Check ARN that relates to the Recommendation

Type: String

Required: No

createdAt

When the Recommendation was created, if created by AWS Trusted Advisor Priority

Type: Timestamp

Required: No

createdBy

The creator, if created by AWS Trusted Advisor Priority

Type: String

Required: No

lastUpdatedAt

When the Recommendation was last updated

Type: Timestamp

Required: No

lifecycleStage

The lifecycle stage from AWS Trusted Advisor Priority

Type: String

Valid Values: `in_progress` | `pending_response` | `dismissed` | `resolved`

Required: No

pillarSpecificAggregates

The pillar aggregations for cost savings

Type: [RecommendationPillarSpecificAggregates](#) object

Required: No

resolvedAt

When the Recommendation was resolved

Type: Timestamp

Required: No

updatedOnBehalfOf

The person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updatedOnBehalfOfJobTitle

The job title of the person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updateReason

Reason for the lifecycle stage change

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Pattern: `[\s\S]*`

Required: No

updateReasonCode

Reason code for the lifecycle state change

Type: String

Valid Values: `non_critical_account` | `temporary_account` | `valid_business_case` | `other_methods_available` | `low_priority` | `not_applicable` | `other`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

metadata

Metadata associated with the Recommendation Resource

Type: String to string map

Required: Yes

recommendationArn

The Recommendation ARN

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\/[\w-]+`

Required: Yes

regionCode

The AWS Region code that the Recommendation Resource is in

Type: String

Length Constraints: Minimum length of 9. Maximum length of 20.

Required: Yes

status

The current status of the Recommendation Resource

Type: String

Valid Values: `ok` | `warning` | `error`

Required: Yes

accountId

The AWS account ID

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

exclusionStatus

The exclusion status of the Recommendation Resource

Type: String

Valid Values: `excluded` | `included`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrganizationRecommendationSummary

Summary of recommendation for accounts within an Organization

Contents

arn

The ARN of the Recommendation

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor:::organization-recommendation\/[\w-]+`

Required: Yes

id

The ID which identifies where the Recommendation was produced

Type: String

Required: Yes

name

The name of the AWS Trusted Advisor Recommendation

Type: String

Required: Yes

pillars

The Pillars that the Recommendation is optimizing

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Valid Values: `cost_optimizing | performance | security | service_limits | fault_tolerance | operational_excellence`

Required: Yes

resourcesAggregates

An aggregation of all resources

Type: [RecommendationResourcesAggregates](#) object

Required: Yes

source

The source of the Recommendation

Type: String

Valid Values: aws_config | compute_optimizer | cost_explorer | lse | manual | pse | rds | resilience | resilience_hub | security_hub | stir | ta_check | well_architected | cost_optimization_hub

Required: Yes

status

The status of the Recommendation

Type: String

Valid Values: ok | warning | error

Required: Yes

type

Whether the Recommendation was automated or generated by AWS Trusted Advisor Priority

Type: String

Valid Values: standard | priority

Required: Yes

awsServices

The AWS Services that the Recommendation applies to

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 30.

Required: No

checkArn

The AWS Trusted Advisor Check ARN that relates to the Recommendation

Type: String

Required: No

createdAt

When the Recommendation was created, if created by AWS Trusted Advisor Priority

Type: Timestamp

Required: No

lastUpdatedAt

When the Recommendation was last updated

Type: Timestamp

Required: No

lifecycleStage

The lifecycle stage from AWS Trusted Advisor Priority

Type: String

Valid Values: `in_progress` | `pending_response` | `dismissed` | `resolved`

Required: No

pillarSpecificAggregates

The pillar aggregations for cost savings

Type: [RecommendationPillarSpecificAggregates](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Recommendation

A Recommendation for an Account

Contents

arn

The ARN of the Recommendation

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: Yes

description

A description for AWS Trusted Advisor recommendations

Type: String

Required: Yes

id

The ID which identifies where the Recommendation was produced

Type: String

Required: Yes

name

The name of the AWS Trusted Advisor Recommendation

Type: String

Required: Yes

pillars

The Pillars that the Recommendation is optimizing

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Valid Values: `cost_optimizing` | `performance` | `security` | `service_limits` | `fault_tolerance` | `operational_excellence`

Required: Yes

resourcesAggregates

An aggregation of all resources

Type: [RecommendationResourcesAggregates](#) object

Required: Yes

source

The source of the Recommendation

Type: String

Valid Values: `aws_config` | `compute_optimizer` | `cost_explorer` | `lse` | `manual` | `pse` | `rds` | `resilience` | `resilience_hub` | `security_hub` | `stir` | `ta_check` | `well_architected` | `cost_optimization_hub`

Required: Yes

status

The status of the Recommendation

Type: String

Valid Values: `ok` | `warning` | `error`

Required: Yes

type

Whether the Recommendation was automated or generated by AWS Trusted Advisor Priority

Type: String

Valid Values: `standard` | `priority`

Required: Yes

awsServices

The AWS Services that the Recommendation applies to

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 30.

Required: No

checkArn

The AWS Trusted Advisor Check ARN that relates to the Recommendation

Type: String

Required: No

createdAt

When the Recommendation was created, if created by AWS Trusted Advisor Priority

Type: Timestamp

Required: No

createdBy

The creator, if created by AWS Trusted Advisor Priority

Type: String

Required: No

lastUpdatedAt

When the Recommendation was last updated

Type: Timestamp

Required: No

lifecycleStage

The lifecycle stage from AWS Trusted Advisor Priority

Type: String

Valid Values: `in_progress` | `pending_response` | `dismissed` | `resolved`

Required: No

pillarSpecificAggregates

The pillar aggregations for cost savings

Type: [RecommendationPillarSpecificAggregates](#) object

Required: No

resolvedAt

When the Recommendation was resolved

Type: Timestamp

Required: No

statusReason

This attribute provides additional details about potential discrepancies in check status determination.

Type: String

Valid Values: `no_data_ok`

Required: No

updatedOnBehalfOf

The person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updatedOnBehalfOfJobTitle

The job title of the person on whose behalf a Technical Account Manager (TAM) updated the recommendation. This information is only available when a Technical Account Manager takes an action on a recommendation managed by AWS Trusted Advisor Priority

Type: String

Required: No

updateReason

Reason for the lifecycle stage change

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Pattern: `[\s\S]*`

Required: No

updateReasonCode

Reason code for the lifecycle state change

Type: String

Valid Values: `non_critical_account` | `temporary_account` | `valid_business_case` | `other_methods_available` | `low_priority` | `not_applicable` | `other`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationCostOptimizingAggregates

Cost optimizing aggregates for a Recommendation

Contents

estimatedMonthlySavings

The estimated monthly savings

Type: Double

Required: Yes

estimatedPercentMonthlySavings

The estimated percently monthly savings

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationPillarSpecificAggregates

Recommendation pillar aggregates

Contents

costOptimizing

Cost optimizing aggregates

Type: [RecommendationCostOptimizingAggregates](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationResourceExclusion

The request entry for Recommendation Resource exclusion. Each entry is a combination of Recommendation Resource ARN and corresponding exclusion status

Contents

arn

The ARN of the Recommendation Resource

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation-resource\/[\w-]+\/[\w-]+`

Required: Yes

isExcluded

The exclusion status

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationResourcesAggregates

Aggregation of Recommendation Resources

Contents

errorCount

The number of AWS resources that were flagged to have errors according to the Trusted Advisor check

Type: Long

Required: Yes

okCount

The number of AWS resources that were flagged to be OK according to the Trusted Advisor check

Type: Long

Required: Yes

warningCount

The number of AWS resources that were flagged to have warning according to the Trusted Advisor check

Type: Long

Required: Yes

excludedCount

The number of AWS resources belonging to this Trusted Advisor check that were excluded by the customer

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

metadata

Metadata associated with the Recommendation Resource

Type: String to string map

Required: Yes

recommendationArn

The Recommendation ARN

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: Yes

regionCode

The AWS Region code that the Recommendation Resource is in

Type: String

Length Constraints: Minimum length of 9. Maximum length of 20.

Required: Yes

status

The current status of the Recommendation Resource

Type: String

Valid Values: `ok` | `warning` | `error`

Required: Yes

exclusionStatus

The exclusion status of the Recommendation Resource

Type: String

Valid Values: `excluded` | `included`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationSummary

Summary of Recommendation for an Account

Contents

arn

The ARN of the Recommendation

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation\/[\w-]+`

Required: Yes

id

The ID which identifies where the Recommendation was produced

Type: String

Required: Yes

name

The name of the AWS Trusted Advisor Recommendation

Type: String

Required: Yes

pillars

The Pillars that the Recommendation is optimizing

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Valid Values: `cost_optimizing | performance | security | service_limits | fault_tolerance | operational_excellence`

Required: Yes

resourcesAggregates

An aggregation of all resources

Type: [RecommendationResourcesAggregates](#) object

Required: Yes

source

The source of the Recommendation

Type: String

Valid Values: aws_config | compute_optimizer | cost_explorer | lse | manual | pse | rds | resilience | resilience_hub | security_hub | stir | ta_check | well_architected | cost_optimization_hub

Required: Yes

status

The status of the Recommendation

Type: String

Valid Values: ok | warning | error

Required: Yes

type

Whether the Recommendation was automated or generated by AWS Trusted Advisor Priority

Type: String

Valid Values: standard | priority

Required: Yes

awsServices

The AWS Services that the Recommendation applies to

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 30.

Required: No

checkArn

The AWS Trusted Advisor Check ARN that relates to the Recommendation

Type: String

Required: No

createdAt

When the Recommendation was created, if created by AWS Trusted Advisor Priority

Type: Timestamp

Required: No

lastUpdatedAt

When the Recommendation was last updated

Type: Timestamp

Required: No

lifecycleStage

The lifecycle stage from AWS Trusted Advisor Priority

Type: String

Valid Values: `in_progress` | `pending_response` | `dismissed` | `resolved`

Required: No

pillarSpecificAggregates

The pillar aggregations for cost savings

Type: [RecommendationPillarSpecificAggregates](#) object

Required: No

statusReason

This attribute provides additional details about potential discrepancies in check status determination.

Type: String

Valid Values: no_data_ok

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateRecommendationResourceExclusionError

The error entry for Recommendation Resource exclusion. Each entry is a combination of Recommendation Resource ARN, error code and error message

Contents

arn

The ARN of the Recommendation Resource

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[\w-]+:trustedadvisor::\d{12}:recommendation-resource\/[\w-]+\/[\w-]+`

Required: No

errorCode

The error code

Type: String

Required: No

errorMessage

The error message

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400